
LIMITER
Vapc/Vbpf Buffer
De-Emp
CT/CD LPF
2T/5T DET
LPF Voice AF
HPF Voice AF
LPF-Sub-Audio
Wave Form Buffer
CT/CD-LPF
CT/CD-OUT
DCS WAVE FORM
TXAF
APC/BPF
MIC/TONE
HPF-T/R
DTMF
2STDET
2T/5T-DET
TONEBUFF
CTCDDET
CT/CD-DET
TO LIMITER
TO De-EMP
TO HPF
RX AF IN
2/5/DT IN
Beep Gen
Dimmer, 0~2.5V
SQL IN
SQL OUT
CDCSS Wave Form
From Limitter
E1TOOL
E1RESET-OUT
E1RESET-IN
VDC-DET
VCO-T/R
FX-H/L
CLKSHIFT
BEEP
WIDE/NARROW
RXAF-MUTE
SIDETONE-MUTE
PWR-KEYDET
PWR-KEY
PWR-OFF
TO VOL
FROM VOL
REMOTE
BUSY
LCD-CLK
LCD-RXD
LCD-TXD
LCD-CE
EN-B
EN-A
RXLED
TXLED
PTT
DIMMER
TO-VOL
MIC
BATT +
BATT -
---History---
2014年10月01日 Rev.001
リリース
2014年11月05日 Rev.002
R329 : 100k → 1k Tone Gen最適化
C328 : 1u → 1800p Tone Gen最適化
R303 : 36k → 10k Mod Limiting 最適化
R304 : 36k → 10k Mod Limiting 最適化
Title
Size A2
Number
Revision
Date: 2014/11/05
File: \\...\PT203_AF_CNTL_RevB.SchDoc
Sheet of
Drawn By: