

**Certification
Issued Under the Authority of the
Federal Communications Commission
By:**

**Bay Area Compliance Laboratory Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089**

**Date of Grant: 03/07/2018
Application Dated: 03/07/2018**

**PO FUNG ELECTRONIC(HK) INTERNATIOANL GROUP
COMPANY
3/F FULOK BLDG 131-133 WING LOK ST
SHEUNG WAN,
Hong Kong**

Attention: Peter Wang

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2AJGM-DM-5R
Name of Grantee: PO FUNG ELECTRONIC(HK)
INTERNATIOANL GROUP COMPANY
Equipment Class: Licensed Non-Broadcast Transmitter Held to Face
Notes: VHF/UHF Two Way Radio

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
EF	90	136.0 - 174.0	5.0	2.5 PM	11K0F3E
EF ES	90	136.0 - 174.0	5.0	2.5 PM	7K60F1E
EF ES	90	136.0 - 174.0	5.0	2.5 PM	7K60F1D
EF	90	136.0 - 174.0	2.0	2.5 PM	11K0F3E
EF ES	90	136.0 - 174.0	2.0	2.5 PM	7K60F1E
EF ES	90	136.0 - 174.0	2.0	2.5 PM	7K60F1D
EF	90	400.0 - 406.0	4.0	2.5 PM	11K0F3E
EF	90	406.1 - 480.0	2.0	2.5 PM	11K0F3E
EF ES	90	400.0 - 406.0	4.0	2.5 PM	7K60F1E
EF ES	90	406.1 - 480.0	2.0	2.5 PM	7K60F1E
EF ES	90	400.0 - 406.0	4.0	2.5 PM	7K60F1D
EF ES	90	406.1 - 480.0	2.0	2.5 PM	7K60F1D

Output power listed is rated conducted. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment, not exceeding a maximum transmitting duty factor of 50%. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with the Occupational/Controlled SAR limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. Body-worn operating configuration is limited to the specific belt-clip and accessory configurations as documented in this filing. End-users must be informed of the body-worn operating requirements for satisfying RF exposure compliance. The highest reported SAR values for head and body-worn accessory transmission exposure conditions are 2.31 W/kg and 3.59 W/kg, respectively when operating at 50% duty cycle.

EF: This device may contain functions that are not operational in U.S Territories except as noted in the filing. This grant has extended

frequencies as noted in the filing and Section 2.927(b) applies to this authorization.

ES: This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth.