

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Ep
224	1st R. F.	2.4	2	0	54	175
224	2nd R.F.	2.4	2	0	54	175
224	Det.	2.4	5	0	36	90
227	1st Aud.	2.4	2	0	-	55
227	2nd Aud.	2.4	13.5	0	-	143
227	2nd Aud.	2.4	13.5	0	-	143
245	PWR.	2.2	45	0	-	248
245	PWR	2.2	45	0	-	248

Line voltage 115

Fuse in 120 volt clips

Volume control in maximum position

Alignment


Through holes in the rear of the condenser shield four hexagonal nuts can be seen. By turning these nuts to the right or left, increases or decreases the capacity of the vernier condensers. The adjusting may be done with a socket wrench of the Spintite type, size No.5.


Balancing at the factory is done with an oscillator tuned to 203 meters. Since an oscillator is not at all times available, rebalancing may be accomplished with the carrier wave of a station, preferably a distant one between 200 and 250 meters. The set should be tuned to the station and without further turning the dial, the balancing nuts, starting with the one to the left, turned until the peak of the signal is reached. A tolerance of 5 meters is allowed between the dial setting and the given wave-length of the station. That is, it may be necessary to rebalance a set so that it is off scale 5 meters each way from the wave-length of the station, in order to bring the set to the best operating point. The difference in the dial reading may afterwards be corrected by adjusting the dial strip.

Adjusting Dial Strip

The dial strip is held in place by the knurled dial segment, which in turn is secured at each end to the drum with two flat head machine screws. There are also three small screws running through the dial strip into the dial segment on the inside of the drum.

The five screws (2 large and 3 small) should be loosened just enough to allow the dial strip to be slipped around the drum under the dial segment. After the dial strip is adjusted to the proper position the screws should be tightened.





ZENITH RADIO CORPORATION
 3620 IRON ST., CHICAGO, ILL. A.M.M. 7-25-29

"FADING" OR "CUTTING-OUT"

"50" AND "60" SERIES

The most common cause of complaint in the "50" or "60" series is of Fading or Cutting-out. Outside of the usual possibility of a poorly soldered connection, it may be attributed to two major conditions, as follows:

The original audio tuning condenser, (Part #22-64, on diagram) had a tendency to open internally as a result of poor connection between the leads and the tinfoil. At the time this occurs, the volume will drop about sixty (60%) percent and the reproduction becomes distorted. In this case the condenser should be replaced with one of similar capacity, namely .03 mfd.

In many cases of "fading" or "cutting-out" of the "50" and "60" series, we have found the fault traceable to a certain condition of the volume control unit.

The graphite lubricating material seems to dry between the roller and roller arm, causing a high resistance or semi-contact surface which causes the circuit to open or close at this point. A simple remedy is to disassemble the volume control and clean all movable parts thoroughly in alcohol.

The resistance strip should also be wiped with a clean dry cloth, in order to remove grease and loose carbon particles. Be careful not to use alcohol on the resistance strip, since it may dissolve and remove the carbon. When reassembling, the pressure washer must be set tightly between the inner face and the roller arm.

Complaint of noisy volume control operation may be attributed to loose carbon particles between the rollers and resistance strip. This may also be corrected in the above manner.

Where the case is very obstinate and can not be corrected with the data given, the Service man should direct his attention to the by-pass condensers. An intermittently open or shorted unit will also cause "fading" or "cutting-out"; however, the possibility of trouble at this point is very small in comparison to the audio coupling condenser or volume control.

A. C. HUM IN 50 and 60 SERIES

Abnormal hum in any 50 or 60 model may be traced to either one of two definite sources. First, the screen grid detector tube. Due to the use of three audio stages a slight hum, originating in the detector, is greatly amplified by the time it reaches the speaker. To actually determine whether this is the cause, remove this tube from the set. If the hum level decreases, a new tube will remedy it immediately.

The second cause may be due to lack of proper filtering resulting from a defective electrolytic condenser. This unit is housed in the round metal container near the dial drum. The condenser is removed by simply loosening, with two or three full turns, the screws at the base and sides of the container. Three leads will be found at the top of the condenser which should be carefully unsoldered. The terminal which bears a paint or crayon mark is the 18 mfd. section. (Be careful to note color of the wire which attaches to it in order that it can be soldered to the corresponding lug of the replacement unit.) The condenser can then be easily removed by prying from the bottom and sides and lifting from the top. Be sure to place the new condenser in the same relative position in order that the leads (cut to a specific length) can be soldered back in place properly. A new, improved condenser of the dry type, Zenith part number 22-61D, is available at \$4.00 list. Its use will afford a permanent hum cure.

If a slight residual hum is present after following instructions given above, connect a 250,000 ohm, 1 watt carbon resistor from grid to grid of the '27 first push-pull audio stage. This will make the set practically humless.

PARTS AND PRICES
MODELS 52, 53, 54, 57
60, 61, 62, 64, 67

Condensers

22-43	.25 Mfd. (R. F. Plate By-Pass).....	\$.75
22-61D	9 x 9-18 Mfd. (Filter).....	4.00
22-64	.03 " (Audio Tuning Condenser).....	.55
22-65	1. x 1. " (1st Audio Cathode By-Pass).....	2.00
22-66	1. x 1.x 1.x 1. Mfd.(R.F.Cathode,R.F.Screen, Detector Cathode, and 2nd Audio Cathode).....	1.75
22-67	.15 Mfd. (Audio Coupling).....	.75
22-69	.1 x .1 Mfd. By-Pass Condenser	1.60
22-70	.001 Mfd. (Detector Plate).....	.25

Resistors

63-105	6 M Ohm (Voltage Divider).....	1.00
63-108	50 M Ohm (Detector Cathode).....	.25
63-109	100 M Ohm (1st Audio Grid).....	.25
63-110	400 " (R. F. Cathode).....	.25
63-111	2 M " (2nd Audio Cathode).....	.25
63-112	4 M " (1st Audio Cathode).....	.25
63-113	250 M " (Det. Plate, 2nd Audio Grid).....	.25
63-114	10 Ohm (C.T.)(Filament Circuit).....	.25
63-121	100 M Ohm (1st Audio Plate).....	.25
63-226	Dual Volume Control and Switch Assembly (D.V. Chassis).....	2.50
63-227	Single " " " " "	1.25

Coils

S-440	R. F. Choke	.60
S-441	R. F. Coupling (6-turn).....	.60
S-441	R. F. Coupling (9-turn) D.V. Chassis	.60
S-451	Antenna Coil	1.00
S-452	1st and 2nd R. F. Plate coil	1.00
S-453	2nd R. F. Grid and Detector Grid Coil	1.00

Miscellaneous

26-13	Calibrated Dial Strip	.35
46-36	Control Knobs	.30
95-70	25 Cycle 110 V. Power Transformer	12.00
95-120	60 Cycle 110 V. " "	7.00
100-18	2½ V. Pilot Lamp	.12
136-2	2 Ampere Fuse	.06
145-1	Vernier Gear Arm.....	.15
146-1	Bakelite Dial Segment	.60
MS-88	Filter Choke	3.00
MS-89	Second Stage Audio Transformer (6-lead).....	4.50
MS-90	First " " " (5-lead).....	5.25
S-517	Vernier Shaft and Gear Assembly.....	1.00
49-27	Dynamic Speaker Complete	12.30
	Replacement Cones - Slate Color for Magnavox	3.25
	Silver " " Oxford	3.25
	Purple " " Symington.....	3.25
	Transformer coils only for Symington	1.25

PARTS AND PRICES
PAGE NO. 2

MODELS 52, 53, 54, 57
60, 61, 62, 64, 67


Miscellaneous Cont'd	
Complete output transformer for Oxford	\$2.00
" " " " Magnavox	\$2.00
Field Coils for Magnavox, Symington and Oxford.....	\$5.00

Note: Farrand Speakers (Tan Color) also used in these models. Parts no longer available.


Parts not listed are no longer available.

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
May 13, 1935



ZENITH RADIO CORP.
CHICAGO, ILLINOIS
4/21/30 MB
MODEL 70



SOCKET VOLTAGES				MODEL 70		
TYPE	POSITION	E _f	E _k	E _{g1}	E _{g2}	E _p
24	1st. R.F.	2.5	2.	0	60	180
24	2nd. R.F.	2.5	2.5	0	60	180
24	Det.	2.5	2.5	0	60	90
27	1st. A.F.	2.5	5.	0	-	65
27	2nd. A.F.	2.5	13	0	-	160
27	2nd. A.F.	2.5	13	0	-	160
45	PWR.	2.4	55	0	-	260
45	PWR	2.4	55	0	-	260

Line Voltage 110 V.

Aerial and Ground disconnected.

F - Filament

K - Cathode


G1 - Control Grid

G2 - Screen Grid

P - Plate

All voltages taken from points indicated to ground, using 1000 ohms per volt D.C. meter (except filaments), volume control full on.

To realign chassis turn dial to maximum reading. The pointer on escutcheon should read exactly 500. Now tune in a weak station, about 1400, on dial. Adjust the four trimmers on rear of gang (these may be reached through holes in rear of condenser shield) to maximum volume. The dial may be shifted to correct reading by the adjustment of all four of these trimmers in the same direction.



PARTS AND PRICES
MODELS 71, 72, 73 & 77
712, 722, 732, 772

Condensers

22-43	.25 Mfd.	(R.F. Plate By-pass)	\$.75
22-64	.03 "	(Audio Tuning Condenser)	.55
22-65	Dual 1. Mfd.	(1st Audio Cathode B-Pass)	2.00
22-66	Quad.1 "	(R.F.Cathode, R. F.Screen Grid, Detector Cathode, 2nd Audio Cathode)	1.75
22-67	.15 Mfd.	(Audio Coupling)	.75
22-70	.001 "	(Detector Plate)	.25
22-71	1. "	(Output Filament By-Pass)	1.10
22-72	8. "	(Electrolytic Filter)	1.25
22-73	16. "	(" ")	2.50
S-442	Variable GangNo Longer Available		-
S-443	Antenna Compensator		.50

Resistors

63-105	6000 Ohm Porcelain Voltage Divider	1.00
63-108	50 M Ohm 1 Watt (Detector Cathode)	.25
63-109	100 M " 1 " (1st Audio Grid)	.25
63-110	400 Ohm 1 " (R.F.Cathodes)	.25
63-111	2000 " 1 " (2nd Audio Cathode)	.25
63-112	4000 " 1 " (1st Audio Cathode)	.25
63-113	250 M " 1 " (Detector Plate, 2nd Audio Grid)	.25
63-114	10 " (Center Tap - Filament Circuit)	.25
63-121	100 M " 1 " (1st Audio Plate)	.25
63-226	Volume Control and Switch(Replaces S-617)	2.50

Coils

S-619	Antenna or 1st R.F.Grid Coil	.75
S-620	2nd R.F. and Detector Grid Coil	.75
S-621	1st and 2nd R.F. Plate Coil	.75
S-624	Antenna or 1st R.F. Primary	.50
S-440	R.F. Choke	.50
S-441	R.F. Coupling Coil (Specify whether 6 or 9 turns)	.50

Miscellaneous

26-13	Calibrated Dial Strip	.35
46-36	Control Knob	.30
95-70	25 Cycle 110 Volt Power Transformer	12.00
95-120	60 Cycle 110 " " "	7.00
100-18	2½ Volt Dial Lamp	.12
136-2	2 Ampere Fuse	.06
145-1	Vernier Gear Arm	.15
146-1	Bakelite Dial Segment	.60
S-517	Vernier Shaft and Gear Assembly	1.00
MS-88	Filter Choke	3.00
MS-89	Second Stage Audio Transformer (6-lead)	4.50
MS-90	First " " " (5-Lead)	5.25
49-27	Replacement Speaker Complete	12.30

PARTS AND PRICES
PAGE NO. 2

MODELS 71, 72, 73, 77
712, 722, 732, 772


Miscellaneous Cont'd

49-27	Replacement Cones - Slate Color for Magnavox	\$3.25
"	" Silver " " Oxford	3.25
"	" Purple " " Symington	3.25
	Transformer Coils only (LL-18) " Symington Speaker	1.25
	Complete Output Transformer for Oxford Speaker.....	2.00
	" " " " Magnavox Speaker.....	2.00
	Field Coils for Magnavox, Oxford and Symington Speakers.....	5.00

NOTE: Parts not listed are no longer available.

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
May 13, 1935




A. C. RECEIVERS

VOLTAGE READINGS AT SOCKETS USING WESTON 547 ANALYZER

Line Voltage 115. Fuse in 120 Volt Clips.

TYPE	POS- ITION	FIL. VOLTS	PLATE VOLTS	GRID VOLTS	SCREEN VOLTS	NORMAL PLATE M.A.	GRID TEST M. A.
224	1st R. F.	2.3	185	3.25	90	4	7
224	2nd R. F.	2.3	185	3.4	90	4	7.5
224	3rd R. F.	2.3	185	3.3	90	4	7.5
224	Det.	2.3	90	3	30	.25	.75
227	1st A. F.	2.3	170	12	—	6	7
245	P. P.	2.3	245	50	—	28	37
245	P. P.	2.3	245	50	—	28	37

Balance condenser gang at 1500 K.C. Use #6 Spintite wrench and small screw driver.



PARTS AND PRICES
FOR SUPER ZENITH RECEIVER MODELS 10, 11, 12 AND 102, 112, 122

20-7	Detector Choke.....	\$.50
20-8	R.F. Choke.....	.50
22-74	Single .1 mfd Condenser.....	.60
22-77	Dual .1 " "	.85
22-80	Variable Condenser.....	8.00
22-81	.01 mfd Condenser.....	.75
22-82	.001 " "	.25
22-83	.03 " "	.60
26-17	Celluloid Dial Strip.....	.40
46-42	Control Knobs.....	.25
52-23	Multicord.....	.90
57-255	Escutcheon Plate for Tone Control.....	.20
57-261	Escutcheon Plate for Dial.....	.35
57-262	Escutcheon Plate for On & Off Switch.....	.20
57-264	Escutcheon Plate for Volume Control.....	.20
57-265	Escutcheon Plate for Distance Control.....	.20
63-108	50M Ohm Resistor (Green).....	.25
63-110	400 " " (Yellow).....	.25
63-111	2M " " (Black).....	.25
63-113	250M " " (White).....	.25
63-126	600M " Tone Control.....	.75
63-127	1 megohm Resistor (Brown).....	.25
63-128	50M Ohm Volume Control.....	1.00
63-130	800 " Resistor (Black, Yellow Spot).....	.25
73-2	Set Screw for Control Knobs.....	.01
78-31	Five Prong Socket.....	.15
78-32	Four Prong Socket.....	.15
57-242	Socket Guide Plate for 78-31 & 78-32).....	.03
85-26	Three Point Antenna Switch.....	.50
85-27	A.C. On & Off Switch.....	.75
126-61	Tube Shield Can.....	.20
S-392	Antenna Series Condenser.....	.10
S-692	1st R.F. or Antenna Coil (Secondary).....	1.00
S-694	" " " " " (Primary)	.50
S-695	Multicord Plate & Terminal Assembly.....	1.50
S-710	2nd and 3rd R.F. and Detector Coils.....	1.00
S-715	Multicord Terminal Plate Only.....	1.25
S-704	Dial Drum Assembly.....	2.00
MS-140	Push Pull Input Transformer.....	3.50

Power Pack Z E -70 Jr.

22-71	1. mfd Condenser.....	1.00
22-72	8. " " (Electrolytic).....	1.25
63-114	10 Ohm C.T. Resistor.....	.25
63-124	10,450 Ohm Voltage Divider.....	1.25
78-32	Four Prong Socket.....	.15
57-242	" " " Location Plate.....	.03
95-83	117 V. 60 Cycle Power Transformer.....	8.00
95-84	117 V. 25 " " "	15.00

PARTS AND PRICES
PAGE 2

MODELS 10, 11, 12
AND 102, 112, 122


Power Pack ZE-70 Jr. Cont'd.

136-2	2 Amp. Fuse.....	\$.06
MS-84	Power Receptacle & Fuse Plate.....	.50
MS-141	Filter Choke	3.00
S-696	Top Terminal Strips.....(Five).....	.50
S-698	Bottom Terminal Strips...(Four).....	.50

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.



ZENITH RADIO CORPORATION

December 18, 1933.



ZENITH RADIO CORP.
CHICAGO, ILL.
MODEL 80 AUG 1963/1
HYPERMETRON

©
FIXED CONDENSERS MARKED
INCLOSED IN 1 CONTAINER MARK
P 22-59



PARTS AND PRICES

HYPERMETRON

Variable Condenser Assembly

22-79	Five Gang Variable Condenser.....	\$16.00
S-829	Dial Drum Assembly.....	1.50
26-21	Calibrated Dial Strip.....	.20
S-703	Dial Lamp Bracket.....	.45
100-18	2½ Volt Dial Lamp.....	.12
11-2	Dial Control Cable..... per ft.....	.10
80-70	Dial Control Cable Tension Spring.....	.01

Fixed Condensers

22-81	Single .01 Mfd. Condenser (Tone Control Condenser).....	.75
22-82	Single .001 " " (Detector Plate).....	.25
22-91	Single .03 " " (Audio Coupling).....	.45
22-92	Single .5 " " (Det. Cathode Bypass).....	.60
22-99	Dual .1 " " (2nd RF & Det. Bypass).....	.65
S-392	Antenna Series Condenser.....	.10

Resistors

63-113	250M Ohm Resistor... (Red, Green End, Yellow Dot).....	.25
63-121	100M " " ... (Pink).....	.25
63-131	400 " " ... (Yellow, Black End, Brown Dot).....	.25
63-136	50M " " ... (Green, Black End, Orange Dot).....	.25
63-143	4M " " ... (Yellow, Black End, Red Dot).....	.25
63-145	800 " " ... (Gray, Black End, Brown Dot).....	.25
63-146	2000 " " ... (Red, Black End, Red Dot).....	.25

R.F. Coils

S-441	R.F. Coupling Coil.....	1.00
S-836	Preselector Coil..... (Coil Only).....	1.40
S-837	1st R. F. Coil..... (" ").....	1.00
S-838	2nd, 3rd R. F. & Det. Coils..... (" ").....	1.00
20-7	Detector Choke.....	.50
20-8	R.F. Choke.....	.50

Shields & Bases

4-87	Tube Shield Can Base.....	.05
126-62	Coil " " ".....	.05
126-59	R. F. Coil Shield Can.....	.25
126-61	Tube Shield Can.....	.20
MS-153	Variable Condenser Shield.....	.75

Miscellaneous

44-4	Phono Connector Base.....	.15
78-30	Five Prong Floating Socket.....	.20
78-31	Five Prong Stationary Socket.....	.20
78-32	Four Prong Stationary Socket.....	.20
57-161	UY Socket Guide Plate.....	.01
57-242	Four & Five Prong Socket Guide Plates.....	.03

PARTS AND PRICES

- 2 -

HYPERMETRON

Miscellaneous Cont'd

63-128	Volume Control.....	\$ 1.00
63-147	Tone Control.....	1.00
85-26	Three Point Switch Base Less Shaft.....	.45
143-9	Three Point Switch Bushing with Contact Arm.....	.35
117-31	Three Point Switch Lever Arm.....	.01
S-695	Multicord & Terminal Plate Assembly.....	1.50
S-715	Multicord Terminal Plate Only.....	.50
52-23	Multicord only.....	1.25
MS-147	1st Stage Push Pull Transformer...(5 Lead).....	4.00
MS-148	2nd Stage Push Pull Transformer...(6 Lead).....	4.25

Power Supply - ZE 80

22-71	1. Mf. Condenser.....(Power Bias).....	1.10
22-72	8. " "(Electrolytic)....	1.50
22-73	16. " "(Electrolytic)....	3.00
Note: 16 Mf. Condenser can be identified by Blue marking on anode....		
63-114	10 Ohm Center Tap Resistor.....	.25
63-124	10,450 Ohm Voltage Divider.....	1.35
57-226	Bias Plate.....	.04
57-242	Bias Socket & Guide Plate.....	.01
78-32	Four Prong Socket for Rectifier.....	.15
95-79	Power Transformer.....(60 Cycle).....	7.50
95-93	Power Transformer.....(25 Cycle).....	12.00
136-2	2 Amp Fuse.....	.06
S-696	Terminal Strip Assembly.....(Five).....	.50
S-698	Terminal Strip Assembly.....(Four).....	.50
S-700	Fuse Receptacle & A.C. Outlet Plate.....	.20
MS-149	Power Choke.....	3.50

Cabinet Parts

46-49	Volume & Tone Control Knobs.....	.30
46-48	Tuning Knob.....	.30
57-262	A. C. Switch Escutcheon Plate.....	.20
57-281	Dial Escutcheon Plate.....	.40
85-27	On & Off Switch.....	.75
93-138	Felt Washer for Knobs.....	.01

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO THE REGULAR PARTS DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
April 9, 1934

PARTS & PRICES

MODELS A B C & D CHASSIS

CONDENSERS

22-85	Four Gang Variable.....	7.00
S-759	Dial Drum Assembly.....	.80
12-210	Dial Lamp Bracket.....	.15
S-769	Dial Lamp Socket.....	.15
100-18	Dial Lamp.....	.25
11-2	Pulley String.....	.05 net
80-69	Dial String Tension Spring.....	.01
22-81	.01 mf Bypass.....(Detector Screen).....	.85
82	.001 " "(Detector Plage).....	.30
84	2. " Filter.....	3.00
86	.1 " Bypass (Single).....	.60
87	8. " Electrolytic.....	2.50
88	.25 " Bypass.....(Tone Control).....	.75
89	.1 " Bypass (Double).....(Screen Grid & Cathode)...	.85
90	.1 " Bypass (Single).....(1st R.F. Plate).....	.55
91	.03 " Audic Coupling.....	.50
92	.5 " Bypass.....(Detector & Cathode).....	.75
93	.5 " Output.....	1.00
94	.03 " Bypass.....(1st R.F.).....	.30

RESISTORS

63-131	400 ohm	1st R F Bias.....(Yellow Brown Dot).....	.35
132	900 "	Power Bias.....(White " ").....	.35
133	25M "	1st,2nd R.F.....(Red Orange ")Large...	.35
134	35M "	Screen Grid.....(Orange).....	.35
135	25M "	Detector Bias.....(Red Orange Dot)Small..	.35
136	50M "	Detector Plate.....(Green).....	.35
137	250M "	Detector Plate.....(Red Yellow Dot).....	.35
138	350M "	Detector Screen.....(Orange Yellow ").....	.35
139	500M "	Detector Screen.....(Green Yellow ").....	.35
140	1 Meg "	Power & 1st R.F. Grid..(Brown).....	.35
141	50M "	Volume Control.....	1.25
142	50M "	Tone Control & On & Off Switch.....	2.10

R F COILS

S-766	#1 Pre-Selector Coil.....(Less Mtg.Base & Can).....	1.40
S-767	#3 & 4 Coils.....(Less Choke Mtg.Base & Can)....	1.40
S-768	#2 Coil.....(Less Mtg.Base & Can).....	1.40

SHIELDS

MS-144	Tube Shield Assembly.....	.30
S-771	Coil Shield Base.....	.20
126-59	Coil Shield Top.....	.25
126-66	Variable Condenser Shield.....	.15

MISCELLANEOUS

20-7	Detector Plate Choke.....	.50
20-8	R.F. Plate Choke.....	.50
45-46	Control Knobs.....	.25
49-30	Electro Dynamic Speaker.....	11.50
57-269	Escutcheon Plate.....	.40
78-34	Four Prong Socket.....	.15
78-35	Five Prong Socket.....	.15
83-221	Speaker Terminal Strip.....	.15
95-87	Power Transformer.....(60 Cycle).....	5.00
95-88	Filter Choke.....	1.75
95-90	Power Transformer.....(25 Cycle).....	9.50

ALL PRICES SUEJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.



ZENITH RADIO CORP
CHICAGO, ILL.
MODEL 2009C.
MODEL 1

PARTS & PRICES
MODEL "L" CHASSIS

Variable Condenser Assembly

22-101	Three Gang Condenser.....	\$4.00
S-861	Dial Drum Assembly.....	1.00
S-769	Pilot Lamp Bracket & Socket.....	.15
100-18	2½ volt Lamp.....	.12
11-2	Pulley String.....per.ft.	.10
80-69	Dial String Tension Spring.....	.01

Fixed Condensers

22-82	.001 mf. Condenser.....(Detector Plate).....	.25
22-87	8. " "(Electrolytic High Voltage)....	1.50
22-102	8. " "(Electrolytic Low Voltage).....	1.25
Note: High Voltage Condenser Identified by Red Dot On Anode		
22-91	.03 mf. Condenser.....(Audio Coupling).....	.45
22-100	.08 " "(Filter Condenser).....	.50
22-103	Five Section By-pass Condenser.....	1.75
S-392	Antenna Series Condenser.....	.25

Resistors

63-135	25M Ohm Resistor 1 Watt (Red, Green End, Orange Dot).....	.25
63-136	50M Ohm Resistor ½ Watt (Green, Black " " ").....	.25
63-137	250M " " ¼ " (Red, Green " Yellow ").....	.25
63-140	1 Meg " " ½ " (Brown, Black " Green ").....	.25
63-148	1000 " "(Metal Mounting-Large).....	.25
63-149	400 " "(" " -Small).....	.20
63-150	10M " " ½ Watt (Brown, Black End, Orange Dot)....	.25
63-151	15M " " 1 " (Brown, Green End " ")....	.25
63-152	43M " " ½ " (Yellow, Orange End " ")....	.25
63-153	10M " Volume Control.....	1.10

R. F. Coils

S-857	1st R.F.Coil (Antenna).....(Coil only).....	1.30
S-859	2nd " " " (Intermediate)....(" ").....	1.30
S-865	3rd " " " (Detector).....(" ").....	1.30
20-8	R. F. Choke.....	.50


Shields

126-59	R. F. Coil Shield Can.....	.25
126-68	Condenser Shield.....	.15
MS-163	Tube Shield.....	.25
S-771	Coil Mounting Base.....	.20

Miscellaneous

26-20	Calibrated Dial Strip.....	.25
46-50	Knobs for Switch & Volume Control.....	.20
46-51	Knob for Dial.....	.20
49-31	Electro Dynamic Speaker.....	8.00
57-269	Escutcheon Plate.....	.40
78-34	Four Prong Socket.....	.15
78-35	Five " "	.15
83-226	Speaker Terminal Strip.....	.15
85-29	On & Off Switch.....	.55
95-91	Power Transformer.....(60 cycle).....	5.00
95-92	Power Transformer.....(25 cycle).....	5.00

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO
THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS FOR LIKE PARTS 2/9/34.



PARTS & PRICES
MODEL "LP" CHASSIS

Variable Condenser Assembly

22-101	Three gang condenser	5.00
S-861	Dial drum assembly	.80
S-769	Pilot lamp bracket and socket	.15
00-18	2½ volt lamp	.25
11-2	Pulley string	Net .05
80-69	Dial string tension spring	.01

Fixed Condensers

22-91	.03 mfd. condenser	(audio coupling)	.50
S-392	Antenna series condenser		.25
22-103	Five section bypass condenser		2.00
22-108	.002 mfd. condenser	(bypass)	.35
22-117	.5 " "	" "	.50
22-118	6. " "	(electrolytic low voltage)	2.25
22-119	6. " "	(" high ")	2.50

Resistors

63-135	25M ohm resistor	(Red, Green end, Or ange Dot)	.30
63-137	250M " "	(" " " Yellow ")	.30
63-151	15M " "	(Brown " " Orange ")	.30
63-152	43M " "	(Yellow Orange " ")	.30
63-159	4M " "	(" Black end Red ")	.30
63-162	100 " "	(Flat wire wound black ")	.15
63-163	320 " "	(" " " Red ")	.25
63-164	Volume control		1.10

Coils

S-857	1st R.F.coil (antenna)	(Coil Only)	1.30
S-859	2nd " " " (intermediate)	(" ")	1.30
S-865	3rd " " " (detector)	(" ")	1.30
20-8	R.F.choke		.50


Shields

26-59	R.F. coil shield can	.25
26-68	Condenser shield	.15
MS-163	Tube shield	.25
S-771	Coil mounting base	.20

Miscellaneous

26-20	Calibrated dial strip	.10
46-50	Knobs for switch & volume control	.20
46-51	Knob for dial	.20
49-34	Dynamic speaker	10.50
57-269	Escutcheon plate	.40
78-34	Four prong socket	.15
78-35	Five " "	.15
78-39	" " Pentode socket	.15
83-226	Speaker terminal strip	.15
85-29	Off & On switch	.55
95-91	Power transformer	(60 cycle) 4.50
95-92	" "	(25 ") 8.50

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE




Socket Voltages

Type	Position	Fil. Volts	Plate Volts	Control Grid Volts	Cathode Volts	Plate M.A.	S.G. Volts
Z51	R.F.	2.25	170	---.4	0	4.5	64
Z51	1st Det.	2.25	165	--1.5	1.5	3.	62
Z27	Osc.	2.1	55	0	0	4.5	0
Z51	I.F.	2.3	180	--5.6	0	.75	80
Z27	2nd Det.	2.15	160	--14.5	8.5	.80	0
Z47	Power	2.3	250	---15	0	28.	250
Z24	A. V. C.	2.1	8	---.5	0	0	40
Z80	Rect.	4.7	0	0	0	34. ea	0

Balancing Chassis

- (1) Remove oscillator tube and balance intermediate transformers (through openings underneath chassis) at 175 kilocycles with service oscillator connected to grid of first detector and ground.
- (2) Connect service oscillator to antenna and ground and set at 1500 kilocycles. Insert oscillator tube and set receiver dial at 1500. Adjust oscillator trimmer on gang for greatest output. Adjust first detector trimmer on gang to resonance.
- (3) Set service oscillator at 550 kilocycles. Adjust oscillator padder (through opening in side of chassis) meanwhile moving dial to and fro past 550 K.C. to combination giving greatest output.
- (4) Repeat operation #2.

Tube Layout



TUBE LAYOUT
showing type number, position and circuit function of each.



PARTS AND PRICES
Chassis 2012 - 2012J
and 2012-4J

Models AH, RH CH
090, 90, V-8

Resistors

63-121	100 M	ohm	Detector Plate	(Brown,black end,yellow dot).. \$.25
63-131	400	"	1st Det.Cathode	(Yellow,black end,brown dot).... .25
63-135	25 M	"		(Red,green end,orange dot)..... .25
63-136	50 M	"	Power Tube Grid	(Green,black end,orange dot).... .25
63-139	500 M	"	A.V.C.Plate	(Green,black end,yellow dot).... .25
63-140	1 megohm		Osc. Grid	(Brown,black end,green dot)..... .25
63-144	3	"	A.V.C. Grid	(Orange,black end,green dot).... .25
63-151	15 M	ohm	Voltage Divider	(Brown,green end,orange dot).... .25
63-155	1 M	"	R.F.1st Det.I.F.	(Brown, black end,red dot)..... .25
63-156	10 M	"	Voltage Divider	(Brown,black end,orange dot).... .25
63-157	100	"	Voltage Divider	(Brown,black end,brown dot)..... .25
63-158	1700	"	"	(Brown,purple end,red dot)..... .25
63-160	100 M	"	Power Tube Bias	(Brown,black end, yellow dot).. .25
63-154	Tone Control			1.00
63-161	Volume Control and Switch Assembly			1.25

Condansers

22-82	.001	Mfd.	Detector Plate	.25
22-92	.5	"	2nd Det. Cathode	.60
22-99	.1	"	(Dual) See Footnote	.65
22-104	.0001	"	A.V.C.Coupling	.20
22-107	.5	"	See Footnote	.80
22-108	.001	"	Padder Fixed	.30
22-110	.1	"	R.F.Crid Return	.45
22-111	.03	"	Tone Control	.20
22-112	.1	"	Audio Coupling	.25
22-115	.1	"	1st Det.Grid	.20
22-116	3-gang Condenser			4.75
22-118	6.	Mfd.	Electrolytic - Low Voltage	1.25
22-119	6.	"	" " High "	1.25
22-120	Trimmer used with Part No.22-108			.25
22-121	8.	Mfd.	Plate Filter	1.50

Miscellaneous

S-905	Dial Drum Assembly	1.10
S-911	Antenna Series Condenser Assembly	.85
S-912	I.F. Coil - Complete with base mounting and shield	2.50
S-916	Antenna Coil Assembly	.75
S-917	1st Det. Coil - Complete with choke and coupling band	1.25
S-918	Oscillator Coil - Complete with plate and pick up winding ...	1.25
S-919	2nd Det. Plate Choke and Bracket Assembly	.60

Note - #22-99 - (2 used) - Bypassing osc.cathode,screen grids, and A.V.C. Plate.
 Note - #22-107-(2 used)-Bypassing power tube,bias resistor & power filter choke.
 Note - #22-115-(3 used)-Bypassing 1st det.grid return,I.F.grid return and
 A.V.C.cathode.

PARTS AND PRICES

-2-

Models AH, RH, CH,
090, 90, V-8

Miscellaneous Cont'd

S-933	Multicord and Terminal Strip for 2012 Chassis	\$.65
S-934	Multicord and Terminal Strip for 2012J Chassis	.75
S-963	Dial Pointer Mask Bracket and Mask Assembly	.25
S-964	Magnavision Escutcheon Plate with Lens	1.50
MS-164	Choke (Filter)	1.50
11-3	Pulley String Cable (27 in.)	Net .05
12-219	Dial Lamp Bracket	.05
26-23-	Celluloid Dial Strip	.15
46-52	Knobs for Volume Control, Tone Control, and Tuning	.25
49-34	Dynamic Speaker for Model AH.....	9.75
49-36	Dynamic Speaker for Model CH.....	11.50
73-11	Knob Set Screws	.03
78-36	5-prong Socket marked "Z-51"	.20
78-37	5-prong Socket " " "Z-27"	.20
78-38	5-prong Socket " " "Z-24"	.20
78-39	5-prong Socket " " "Z-47"	.20
78-40	4-prong Socket " " "Z-80"	.20
95-95	Power Transformer (60 cycle, 110 volt)	4.75
95-98	Power Transformer (25 cycle, 110 volt)	7.75
95-99	Power Transformer (60 cycle, 220 volt)	5.50
100-18	2 $\frac{1}{2}$ -volt Dial Lamp	.12

Note - The intermediate coils are peaked at the factory on an elaborate temperature control crystal oscillator, therefore, the vernier adjustments should not be changed or tampered with.

Superheterodyne 8-Tube Chassis 2012-4J

090 - 90 - V-8

Note - The above chassis are practically the same as the AH, RH and CH, excepting for the following changes in parts:

Four-gang condenser instead of three-gang. The fourth section tunes the pre-selector stage employing an additional coil (S-916). The original 8 Mfd. filter condenser mounted at the side of the condenser gang is removed and installed below the chassis. No mounting base is used, therefore, it bears a new part number, namely 22-136. The variable and fixed padder assembly is replaced by variable unit in the 90 and 090, part #22-129. A 4 $\frac{1}{2}$ megohm resistor is added for provision of the local-distance switch.


85-33	Local Distance Switch.....	\$.65
S-916	Preslector Coil	.75
S-2000	Escutcheon Plate	1.50
46-56	Control Knob	.20
49-36	Dynamic Speaker	11.50
63-188	4 $\frac{1}{2}$ megohm Resistor.....	.25
22-108	Bypass Condenser	.30
22-134	Four-Gang Condenser	5.50
22-129	Padder Condenser	.40
22-136	8 mfd. Electrolytic Condenser..	1.50

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
August 13, 1935

SERVICE DATA

for



A. C.

SUPERHETERODYNE RECEIVERS

MODELS 91 and 92

No. 4A

Made by

ZENITH RADIO CORPORATION

3620 IRON ST.

JULY, 1931

CHICAGO, ILL., U. S. A.



GENERAL

Before an analysis is made of the receiver, in locating trouble, the serviceman should first carefully inspect the antenna and ground system which is being employed. The antenna connection may be broken or corroded, or may be found to be grounding at some point along its length. This is the cause of many complaints where intermittent or fading of signals is experienced. If the antenna has been in use for a considerable length of time the lead-in may have broken from the aerial wire or become parted inside the insulation. This is especially true on apartment buildings where a multitude of aerials are employed, any of which may have broken and fallen upon another. If a lightning arrester is used it should also be inspected.

A poor ground connection is also a frequent cause for complaint. It should be carefully inspected and repaired if necessary. When there is a condition of noisy reception the serviceman should first disconnect the antenna and ground in order to make certain that it is not arising from an outside source.

Our experience has taught us that ninety percent of service complaints can be traced to defective tubes. The fact that they light gives no indication whatsoever of their operating condition. After the antenna and ground have been gone over, each tube should be carefully tested and those found defective should be replaced.

In making replacements we warn against the use of any other than Zenith Quality Tubes. Those of other manufacture, in some cases, vary from our tube characteristics and will, consequently, impair proper operation of the receiver.

The Service Division of the Zenith Radio Corporation will be pleased to be of further assistance should any problem arise not covered by this manual.

INDEX

	Page
Automatic Volume Control.....	4
Balancing Chassis	6
Function of the Superheterodyne.....	3
Operation—Models 91 and 92.....	4
Replacement Parts List.....	10 and 11
Schematic Wiring Diagram.....	5
Service Data Chart.....	8 and 9
Socket Voltages	7
Tube Lay-Out	7

ZENITH RADIO CORPORATION

Function of the Superheterodyne

Operation of the present day Superheterodyne, as in the case of all previous Superheterodynes, depends entirely on the principle of beat frequencies. A beat frequency is the result of two signals of different frequencies mixing to form a third frequency. To explain this more clearly let us suppose we hear a vibration of one definite frequency and at the same time a second and slightly different vibration is set in motion. In addition to the two separate vibrations we would hear the beat frequency of these or a third vibration equal to the difference in their frequency or pitch. This is essentially what happens in a Superheterodyne except that the frequencies involved are not audible. The beat frequency, is produced by action of an oscillator frequency mixing with the incoming signal to form an intermediate frequency which then undergoes further amplification.

It is well known that R. F. Circuits become unstable and have a greater tendency to oscillate as the frequency is increased. In fact, a point may be reached in the usual T. R. F. circuit where even a screen grid tube will prove extremely inefficient. In the Superheterodyne these undesirable conditions are overcome by amplifying the signal at a low but constant frequency.

The sketch in figure 1 at A indicates the action which takes place in the usual T. R. F. set. While figure 1 at B shows that of a Superheterodyne.




Fig. 1

In the design of a modern Superheterodyne a definite frequency is first chosen to serve in the intermediate amplifier. It is always one which will give the least reaction to the other essentials of the circuit in the form of double-spot tuning, harmonics, etc. Now in order to generate the frequency which has been decided upon the oscillator circuit must have that separation from the frequency of the incoming signal. Supposing we have taken 175 K.C. for the frequency at which we wish our intermediates to operate. Now we have an incoming signal say at 600 kilocycles. The oscillator must be tuned to either 775 K.C. or 425 K.C. to beat with it and create the third or intermediate frequency of 175 K.C. In order to simplify oscillator design, the higher frequency is most usually employed.

The oscillator tuning is made to follow the 1st detector always maintaining a difference of 175 K.C. and for this reason the intermediate frequency remains constant and we have equal amplification for any signal impressed upon the antenna, regardless of its position in the broadcast band. This, however, does not mean that all stations will be received with equal volume since the intensity generated is governed by the initial strength of the signal to which the set is tuned.

In modern Superheterodynes we use an ordinary tuned radio frequency stage before the 1st detector in order to improve selectivity and sensitivity before the intermediate frequency is formed.

In a summary of the foregoing we have a signal entering the antenna amplified at its broadcast frequency by the R. F. tube followed by the 1st detector, which due to the action of the oscillator tube, converts it to a lower frequency, namely, 175 K. C. for further amplification in the intermediate stages following. The result of this action is a third R. F. signal of a frequency equal to that of the separation. This signal is amplified by the intermediate frequency tube. It is then rectified by a second detector tube and followed by the usual audio amplifier.



OPERATION

MODELS 91 and 92

The Zenith Models 91 and 92 uses ten tubes in a modern Superheterodyne circuit, employing many refinements. Among these being an antenna resonator, pre-selector stage, four tuned circuits, automatic volume control, and push-pull audio amplification. The following is a list of the various types of tubes used and the circuit duty of each.

R. F.—1 Z-51 Multi-Mu	1st A. F.—1 Z-27
1st Detector—1 Z-51 Multi-Mu	2nd A. F.—2 Z-45
Oscillator—1 Z-27	A. V. C.—1 Z-24
I. F.—1 Z-51	Rectifier—1 Z-80
2nd Detector—1 Z-27	

In order to obtain a thorough understanding of how the ten tube Superheterodyne operates, the circuit should be followed from the antenna. A tuned coil and condenser forms the pre-selector stage which is coupled at one end to the antenna through the variable antenna compensating condenser, and from the other end direct to ground. The pre-selector coil is placed in inductive relation to the 1st R. F. tuning coil and condenser so that a transfer of energy occurs from one to the other. The 1st R. F. tuned grid circuit returns its R. F. energy through the path of least resistance, namely a fixed condenser between the coil and ground. The plate circuit of the R. F. stage is capacity coupled to the 1st detector tuned grid circuit. A section of the variable condenser and a coil is also employed here which returns to ground through a fixed condenser in the same manner as the R. F. grid circuit. It should be noted that a pick-up coil is placed in series with the 1st detector cathode by which energy is absorbed and mixed with the signal generated in the oscillator circuit. An oscillator, operates at 175 kilocycles higher in frequency than the R. F. or 1st detector, and employs a grid coil and tuning condenser and also a tickler winding. A small series or padding condenser is connected between the variable condenser section and the oscillator coil return which enables the oscillator circuit to track accurately with that of the other tuned circuits over the entire broadcast scale. (See balancing.)

After the oscillator frequency has mixed with the incoming signal in the 1st detector it is tuned to an intermediate frequency of 175 kilocycles in the 1st detector plate circuit. The 1st detector tuned plate coil is inductively coupled to a tuned grid coil of the intermediate frequency amplifier. This coil is also tuned to a frequency of 175 kilocycles. Remaining at this same frequency the signal is transferred from the intermediate frequency amplifier to the 2nd detector by means of a tuned plate coil inductively coupled to a tuned grid coil in the 2nd detector grid circuit. The 2nd detector is resistance coupled to a Z-27 1st A. F. stage which is, in turn, transformer coupled to a pair of push-pull Z-45's. The tone control, consisting essentially of a variable resistance and fixed condenser, is connected from grid to grid of the Z-45 tubes.

Automatic Volume Control

A Z-24 automatic volume control tube keeps the volume of the incoming signal constant by varying the grid bias voltage on the 1st R. F., 1st detector, and I. F. stages, in relation to the change of R. F. energy amplified before the 2nd detector. The three grid returns mentioned are coupled to the plate of the automatic volume control tube through three limiting resistors, while the 2nd detector grid couples to the volume control tube grid through a small fixed condenser. Any variation in signal strength on the 2nd detector grid is transferred to the automatic volume control tube which, proportionately varies the voltage drop across the volume control tube plate resistor which changes the bias of the three tubes mentioned.

The local distance switch simply shunts a resistor from plate to cathode of the automatic volume control tube when in the local position, thereby placing a constant bias on the three R. F. stages. This has the effect of minimizing the automatic volume control action and, consequently, subdues noise between stations. When the local distance switch is in the distance position it opens the external resistor circuit, thereby, allowing the volume control tube to operate normally.



Balancing Chassis

Every Zenith Superheterodyne Receiver is carefully balanced on laboratory equipment before leaving the factory and should not require further attention in this respect. However, in the event that some part of the R. F. circuit has been changed, or the adjustments shifted by mishandling, the chassis may be rebalanced as follows:

If an oscillator is available more accurate results will be obtained. It should be accurately calibrated from 1500 to 550 kilocycles and should also have provision for generating a 175 kilocycle signal. In cases where an oscillator is not available a fairly good result may be had by listening to stations which operate as nearly as possible to the extreme ends of the dial. Although an output meter will give most accurate results, satisfactory adjustments can be made simply by listening to the speaker.

The chassis should be removed from the cabinet so that all adjustments are easily accessible. Next place the test oscillator in operation and connect it direct to the antenna and ground posts of the receiver. It should then be set to 1500 kilocycles and the receiver tuned to the same reading on the dial. If the oscillator is not accurate the stations will not be received on their proper calibration. If a station is used for this purpose, the dial pointer should first be set to the exact frequency of the station being received. Beginning with the variable condenser tuning section at the extreme left, which tunes the oscillator circuit, the trimmer should be regulated for maximum response, in either the loud speaker or output meter. It will be noticed that the second section does not employ a vernier adjustment. This stage is resonated by adjusting the antenna compensator knob as explained in the instruction card. The third, or 1st R. F. trimmer, is adjusted in the same manner as the oscillator. If at any time the volume reaches a very high level, so that it is not possible to determine slight changes, it should be reduced by means of the volume control knob so as to be barely audible. The fourth, or 1st detector section, is next in order and its trimmer should also be adjusted for resonance.




FIG. 3


After the vernier adjustments have been completed the test oscillator should be set at 550 kilocycles and the dial of the receiver turned until the oscillator signal is tuned in. Now the oscillator padding condenser (see fig. 3) should be very carefully adjusted with a screw driver for maximum output of the receiver, while rocking the tuning condenser back and forth over the signal. This padding adjustment brings the oscillating circuit of the receiver in resonance with the remaining tuned circuits and, thereby, enables it to tract accurately over the entire scale. The receiver will now operate at full efficiency and all stations will be received at their proper calibration. If this is not found to be entirely so, the entire balancing operation should be repeated.

The intermediate transformers used in the ten tube Superheterodyne have been accurately peaked at 175 kilocycles on a temperature controlled crystal oscillator before leaving the factory. It is not recommended that their adjustments be tampered with unless an oscillator is available which is very accurately calibrated at 175 kilocycles, or unless the serviceman is absolutely certain the trouble lies in their adjustment. However, if it is necessary to check the adjustments, the 175 K. C. test oscillator may be connected to the grid terminal of the 1st detector through a .00025 fixed condenser. The ground lead of the test oscillator is connected to the ground post of the receiver. The oscillator tube must be removed from the chassis while this operation is being performed. Four adjusting screws are provided under the chassis directly beneath the intermediate transformers, which tune the plate circuit of the 1st detector, grid and plate circuits of the I. F. stage, and grid circuit of the second detector. (See wiring diagram.) Beginning with the 2nd detector grid vernier, each adjusting screw should, in turn, be set for maximum signal output from the speaker or output meter. For best results the verniers should be gone over twice in the same rotation always keeping the output from the test oscillator at the weakest possible strength in order to determine slight variations in volume.

Socket Voltages

Type	Position	Fil. Volts	Plate Volts	Control Grid Volts	Cathode Volts	Plate M. A.	S. G. Volts
Z-51	1st. R. F.	2.25	175	.2	0	7.	100
Z-51	1st. Det.	2.25	175	3.5	.4	3.5	90
Z-27	Osc.	2.2	70	0	0	8.5	0
Z-51	I. F.	2.2	200	4.	0	2.5	115
Z-27	2nd. Det.	2.2	115	0	9.	.5	0
Z-27	1st. Aud.	2.2	145	0	13.	6.5	0
Z-45	P. P.	2.2	275	54.	0	30.	0
Z-45	P. P.	2.2	275	54	0	30.	0
Z-24	A. V. C.	2.2	35	.4	0	0	54
Z-80	Rect.	4.8	355	0	0	76.	0

Voltage readings taken with a Weston type 566 tester. Manual volume control in maximum position and antenna and ground disconnected. Line voltage 112.



TUBE LAYOUT - Showing Position and Circuit Function of each.



SERVICE DATA CHART

Before using the service data chart, the service man should make certain that the tubes and antenna and ground system are not at fault.

<i>Nature of Trouble</i>	<i>Possible Cause</i>	<i>Remedy</i>
No Signals	Defective A. C. Switch. No power at socket outlet. One or more defective tubes. Shorted antenna series condenser. Shorted oscillator padding condenser. Open windings or broken connections on oscillator or R. F. coils. Shorted section of variable condenser gang. Shorted trimmer on variable condenser gang. Open tuning meter. Grounded volume control. 2nd detector choke grounded or open.	Replace. Check line fuses and socket voltage. Test and replace. Adjust to relieve short. Inspect and adjust or replace if necessary. Inspect and resolder or replace. Clean all sections with a pipe cleaner to remove metal slivers. Adjust to relieve short. Repair connections or replace. Inspect all volume control leads and respace control from chassis. Remove choke shield and adjust or replace.
Oscillation (Over entire scale)	Open by-pass condenser. Grounded resistor. Poor ground returns. Open oscillator plate coil. Broken connection in oscillator circuit. Defective oscillator tube.	Replace. Space from chassis. Resolder and tighten. Replace oscillator coil. Trace and repair or resolder. Replace.
Oscillation (Low frequency end)	Variable condenser cradle not grounding properly.	Solder three pigtail wires from each end and from center of cradle direct to chassis on the under side.
Hum	Open or shorted power bias resistor. Loose transformer laminations. Grounded pilot light socket (2.5 volt). Grounded filament lead. Shorted filter choke. Defective electrolytic condenser. Defective tube.	Replace. Tighten lamination bolts. Turn socket contacts away from dial bracket. Trace filament wiring and remove ground. Check leads or replace choke. Replace. Locate and replace.
Tuning meter does not read	Open meter. Grounded meter. Open R. F. coil. Grounded volume control.	Replace. Replace. Resolder or replace. Respace from chassis and check connections.
Manual volume control does not operate	Defective A.V.C. tube. Shorted or grounded volume control. Rosin or broken joint in A.V.C. circuit. Shorted I.F. transformer.	Replace. Respace from chassis and check connections or replace. Repair or resolder. Replace I.F. unit.



SERVICE DATA CHART

<i>Nature of Trouble—Cont.</i>	<i>Possible Cause—Cont.</i>	<i>Remedy—Cont.</i>
Weak reception	Resistors touching each other on resistor strip. Grounded resistor. High resistance joint on R. F. coils. Defective padding condenser. Padding condenser not set properly. Chassis out of balance. Antenna Compensator not adjusted properly. Open cathode winding on oscillator coil. Defective tubes.	Respace. Space from chassis. Resolder where necessary. Replace. See "Balancing." See "Balancing." See "Balancing." Repair or replace. Replace.
Flutter or motor-boating	Filament lead cutting into grid terminal of 2nd detector. Oscillation. Grounded resistor. Poor ground connections. Open by-pass condenser in audio circuit. Open grid circuit in audio circuit. Defective local-distance switch.	Respace from grid terminal. See paragraph on "Oscillation." Respace from chassis. Tighten resistor brackets to chassis and resolder ground return connections. Replace. Defective push-pull transformer or rosin joint. Repair or replace.
Fading	Defective A.V.C. tube. Other tubes defective. Resistor mounting loose on chassis. Poor ground return. Defective local-distance switch. Defective by-pass condenser. Rosin joint on R. F. coils or variable condenser.	Replace. Test and replace. Tighten securely. Tighten and resolder all grounds in chassis. Repair or replace. Locate and replace. Resolder.
Intermittent reception	Loose resistor mounting. Defective by-pass condenser. Broken strands on R. F. coils. Rosin or broken connection. Defective A. C. switch. Defective local-distance switch. Grounded resistor. Defective tubes.	Tighten mounting screws securely. Locate and replace. Resolder. Check all connections and resolder where necessary. Replace. Repair or replace. Space resistor from chassis. Replace.
Dial off calibration	Chassis out of balance. Dial strip bracket pressed against front of cabinet. Dial cam and drum assembly loose on condenser shaft.	See "Balancing." Space chassis from front of cabinet. Tighten securely.

REPLACEMENT PARTS




FIG. 5

CONDENSERS

22- 82	.001	Mfd.	(2nd Det. Plate)	\$.30
22-110	.1	Mfd.	(R. F.)	.50
22-111	.03	Mfd.	(A.V.C. Plate)	.30
22-112	.1	Mfd.	(2 Used. See Footnote)	.35
22-113	.5	Mfd.	(3 Used. See Footnote)	.50
22-115	.1	Mfd.	(3 Used. See Footnote)	.30
22-119	6.	Mfd.	(High Voltage Electrolytic)	1.50
22-122	Four Gang Variable			7.00
22-125	8.	Mfd.	(Low Voltage Electrolytic. 2 Used)	1.50
22-126	.006	Mfd.	(Tone Control)	.55
22-127	.000025	Mfd.	(A.V.C. Coupling)	.35
22-129	Oscillator, Padding			.75

RESISTORS

63-111	2M	Ohm	1	Watt.	(1st A. F. Cathode)	\$.30
63-121	100M	Ohm	1	Watt.	(2nd Det. Plate)	.30
63-131	400	Ohm	1/2	Watt.	(A.V.C. Voltage Divider)	.30
63-135	25M	Ohm	1/2	Watt.	(2nd Detector Cathode)	.30
63-137	250M	Ohm	1/2	Watt.	(1st A. F. Grid)	.30
63-140	1 Meg.	Ohm	1/2	Watt.	(Oscillator Grid)	.30
63-144	3 Meg.	Ohm	1/2	Watt.	(A.V.C. Grid)	.30
63-146	2M	Ohm	1/2	Watt.	(1st A. F. Cathode)	.30
63-166	1400	Ohm	1/4	Watt.	(3 Used. See Footnote)	.30
63-167	8M	Ohm	1	Watt.	(A.V.C. Divider)	.30
63-168	3600	Ohm	2	Watt.	(Plate Voltage Divider)	.50
63-169	400M	Ohm	1/2	Watt.	(A.V.C. Plate)	.30
63-170	2800	Ohm	2	Watt.	(Plate Voltage Divider)	.50
63-171	Manual Volume Control and Switch Assembly					1.65
63-172	Tone Control					1.00
63-173	750	Ohm		Metal Mounting	(Power Tube Bias)	.40
63-180	1M	Ohm	1/2	Watt.	(1st Detector Cathode)	.30
63-188	4 1/2 Meg.	Ohm	1/2	Watt.	(A.V.C. Plate)	.30

Note: All resistors employed in this receiver are marked in accordance with R. M. A. standards. Color code charts may be obtained by writing direct to the Erie Resistor Corp., Erie, Pa.

S-912	Intermediate Transformer Complete (2 Used) (Specify with or without grid lead)	\$2.50
S-916	Antenna and 1st R. F. Coils	.75
S-997	1st Detector Complete	1.25
S-999	Oscillator Coil Complete	1.25

Note: 22-112 Filter Choke By-pass and 1st Audio Coupling Condensers.
 22-113 1st R. F., 1st Det. and I. F. Screen. 2nd Det. and A. F. Cathode.
 22-115 2nd Det. and I. F. Grid Return. 1st Det. Cathode.
 63-166 1st R. F., 1st Det. and I. F. Grid Return Resistor.

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

REPLACEMENT PARTS




FIG. 6
DIAL ASSEMBLY

6-14	Pointer Arm Bearing.....	\$.20
15-12	Dial Light Cap.....	.35
76-107	Dial Elevator Shaft.....	.10
80-72	Pointer Arm Tension Spring.....	.08
94-119	Roller Bushings.....	.08
100-18	2½V Meter Lamp.....	.25
100-20	3¼V Dial Lamp.....	.70
122-4	Tuning Meter and Cord.....	2.25
148-3	Dial Elevator Arm.....	.35
S-1003	Dial Lamp Socket and Clip (less Lamps).....	.60
S-1009	Tuning Shaft and Bracket Assembly.....	1.50
S-1010	Drum Gear and Cam.....	.85
S-1105	Dial Strip and Bracket Assembly.....	.60
S-1106	Dial Pointer and Reflector Plate.....	1.50

MISCELLANEOUS

19-21	Grid Lead Clips.....	\$.02
20-7	2nd Detector Plate Choke.....	.50
24-24	Electrolytic Condenser Cover.....	.02
46-53	Knobs (3 Used).....	.25
46-54	Knobs.....	.20
49-37J	Dynamic Speaker.....	15.00
57-308	Escutcheon Plate for Dial.....	.80
57-309	Escutcheon Plate for Meter.....	.35
73-8	Dial Drum Bushing Set Screw.....	.02
73-11	Knob Set Screws.....	.03
78-28	Stationary Automatic Pilot Lamp Socket.....	.35
78-36	Z-51 Socket.....	.20
78-37	Z-27 Socket.....	.20
78-38	Z-24 Socket.....	.20
78-40	Z-80 Socket.....	.20
78-41	Z-45 Socket.....	.20
85-31	Local Distance Switch.....	.85
93-152	Volume Control Washer (Large Insulating).....	.05
93-153	Volume Control Washer (Small Insulating).....	.01
93-154	Cup Washer for Electrolytic Condenser.....	.05
93-155	Insulating Washer.....	.05
95-100	60 Cycle Power Transformer.....	7.00
95-106	25 Cycle Power Transformer.....	11.50
112-10	Tube Shield Thumb Screw.....	.05
S-458	A. C. Line Cord and Plug.....	.40
S-998	Speaker Cord and Connector Strip.....	.75
S-1004	Antenna Series Condenser and Binding Post Assembly.....	1.15
MS-173	Five Lead Push Pull Transformer.....	4.50
MS-174	Power Choke.....	3.50

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.



(SUPPLEMENT TO SERVICE MANUAL 4A)

GENERAL

This supplement covers an improvement in the 10-tube Superheterodyne. It is confined entirely to the Manual volume control circuit as may be seen by comparing the diagram on page three with the schematic shown on page 5 of the 4A service manual. In all receivers produced, bearing serial number 373,334 on Model 91 and 301,394 on Model 92 or higher, this change is incorporated.

The manual control has been removed from the A. V. C. cathode and placed in the grid circuit of the 1st A. F. stage. A tapped resistor takes the place of the original control. By use of this new system, the automatic volume control operates independently and at full efficiency, manual volume being controlled by varying the audio output.

It should be noted that since the A. V. C. or R. F. circuit remains constant, the tuning meter will show maximum swing on the station at any manual control setting. Originally the meter action decreased as the volume was lowered.

All voltages, tube locations and parts listed in the 4A Manual apply directly and are to be used when servicing either type set. The balancing process remains unchanged. The parts list show previously, except for the substitutions given below, should be used when ordering replacement components.

PARTS CHANGE

(Receivers bearing No. 373,334 on Model 91 and No. 301,394 on Model 92, or higher.)

1 Audio Volume control, part No. 63-212, List	\$1.65
1 Center tapped resistor, part No. 63-210, List	\$0.50

Deduct the 63-171 volume control.

ZENITH RADIO CORPORATION




Fig. 1 - CIRCUIT DIAGRAM - MODELS 91-92 (Serial Nos. after 373,334 and 301,394 respectively)



Supplement to Service Manuals No. 4A & 4B

for

MODELS 91 - 92

All ten-tube Zenith Superheterodynes produced after the following serial numbers will incorporate a variable Sensitivity Control in place of the original Local-Distance switch.

Model 91 No. 375,532

Model 92 No. 302,007

The diagram on the reverse side indicates its position as being connected into the I. F. cathode. In addition to the control unit the first detector coil has been replaced by one having slightly different construction to provide equal sensitivity over the entire tuning range. It is not advisable to make this change in receivers subsequent to the numbers given for the reason that each complete set of chassis coils must be inductively matched, otherwise the efficiency of the receiver will be seriously affected.

With exception of the above all data given in the 4A manual, such as method of balancing, tube layout, etc., should be followed closely when repairs or adjustments are necessary.

The followings alteration makes the 4A parts list directly applicable to the improved models:

DEDUCT

No.	Description	List
1 85-31	Local-Distance switch	.85
1 S-997	First detector coil	1.25
1 63-224	8 meg. resistor	.30
1 63-135	25,000 ohm resistor	.30

ADD


1 63-228	Sensitivity Control	1.00
1 S-2104	Detector Coil Assembly	1.25
1 22-115	Bypass condenser	.30
1 63-136	50,000 ohm resistor	.30

ZENITH RADIO CORPORATION

3620 IRON ST.


DECEMBER, 1931

CHICAGO, ILL., U. S. A.



SERVICE DATA

for



14 TUBE A. C.

SUPERHETERODYNE

RECEIVERS

MODEL 103

No. 5A

Made by

ZENITH RADIO CORPORATION

3620 IRON ST.

SEPTEMBER, 1931

CHICAGO, ILL., U. S. A.



GENERAL

This No. 5A Service Manual is published as a supplement to No. 4A, which covers in detail the Zenith ten-tube Superheterodyne models. Since circuit action of the fourteen tube receiver is fundamentally the same as the ten, function of the Superheterodyne is not repeated in the following pages. Many refinements over the Models 91 and 92 are to be found in the Model 103. However, since they take the form of additional R. F. and audio stages, they need not be considered as independent subjects.

The "Service Data Chart" outlined in manual 4A should be consulted in determining the reason for complaint, since it applies directly to the fourteen tube set. Of course, the usual service procedure with respect to antenna, ground and tubes should always come first in order.

It should be noted that the line fuse provided in the rear of the chassis has two positions. The fuse should normally be used in the "Regulator Tube In" position. If the regulator tube becomes defective and a replacement is not immediately available, the fuse may be placed in the "Regulator Tube Out" clips. Do not leave the voltage regulator tube out permanently since line fluctuation or high voltage may cause damage to the tubes or power transformer.

OPERATION

The Model 103 employs a preselctor and two R. F. amplifiers before the 1st detector. The first Multi-mu R. F. stage is tuned while the 2nd stage is impedance coupled or untuned. The first detector is coupled through its cathode to the oscillator and the plate circuit tuned to the intermediate frequency of 175 K. C. Two Multi-mu intermediate stages follow and supply energy to the Z-27 second detector. Its grid is also tuned to the intermediate frequency. The second detector is transformer coupled to a pair of push-pull Z-27's which in turn feed the Z-45 push-pull output stage.

It should be noted that the phonograph pick-up switch and jacks are connected in the grid return circuit of the second detector, consequently a howl will be heard if the phono switch is thrown to the phono position without a phono pick-up having been attached. Be sure this action is taken into consideration when servicing the receiver or if there is a complaint of very weak reception accompanied by a very peculiar howl.

ZENITH RADIO CORPORATION




Fig. 1

Balancing Chassis

Each Zenith Superheterodyne receiver is carefully balanced on a temperature controlled Crystal Oscillator before leaving the factory and should require no further attention in this respect. However, in the event that a part of the R. F. circuit has been changed or the phasing adjustments shifted by mishandling, the chassis may be re-balanced as follows:

A test oscillator will give more accurate results and is, therefore, recommended in preference to use of a broadcast signal. It should be calibrated from 1500 to 550 K. C. and also provide a 175 K. C. signal. An output meter is not required since the tuning meter on the set is connected to the intermediate stages in such a way that it shows a variation during adjustment of any R. F. or intermediate circuit of the set. It is only necessary to watch the tuning meter for greatest swing to the right when adjusting the R. F. and I. F. trimmer condensers.

The chassis should be removed from the cabinet for this operation so that all adjustments are easily accessible. The test oscillator should be set to 1500 K. C. and attached to the antenna and ground posts. If a broadcast signal is used, tune to a station as near to 1500 K. C. as it is possible to hear. In this case the dial must point to the exact frequency on which the station operates.




Fig. 2

First turn the trimmer provided on the oscillator section of the condenser gang (See fig. 2) and peak for greatest deflection, to the right, of the tuning meter. The second section from the left tunes the 1st R. F. stage and is next in order. Also peak for the greatest swing of the meter. The preselector or third, and the 1st detector or fourth sections follow in turn and are adjusted in the same manner. The second R. F. stage is of the fixed impedance type, and therefore requires no adjustment. The untuned coils are concealed beneath the chassis in a small round shield.

When the trimmers have been resonated, set the dial to 550 K. C. and tune the test oscillator until it is heard clearly in the speaker. This may also be done by tuning to a station at or near 550 K. C. Turn the oscillator padding condenser screw for greatest swing to the right on the tuning meter, while rocking the dial back and forth over the signal. The padder adjusting screw will be found on the left side of the chassis base when looking from the front. (See Figure 2.)

The six intermediate adjusting screws provided beneath the chassis, directly under the intermediate transformers (See fig. 5) are to be used only when it is absolutely certain that trouble lies at that point. If it is necessary to change the setting connect an accurate 175 K. C. test oscillator to the ground post and to the 1st detector grid cap through a .00025 mfd. fixed condenser. The oscillator tube must be removed for this operation. Beginning with the first detector plate screw (the one farthest to the left when viewing the chassis from underneath with the control shafts at the top) each one is tuned for maximum swing of the tuning meter. The procedure applies to all but the last or second detector grid vernier. The meter is not effected by this circuit, therefore, it will be necessary to turn it to a point which gives greatest volume from the speaker.

Socket Voltages

Type	Position	Fil. Volts	Plate Volts	Control Grid Volts	Cathode Volts	Plate M. A.	S. G. Volts
Z-51	1st. R. F.	2.2	185	— 9.	0.	2.5	80
Z-51	2nd. R. F.	2.2	200	— 3.9	0.	3.	84
Z-24	1st Det.	2.2	185	0.	+ 7.	.25	70
Z-27	Osc.	2.2	80	0.	0.	7.	0
Z-51	I. F.	2.2	185	— 4.	0.	3.	90
Z-51	I. F.	2.2	185	— 4.	0.	2.	90
Z-27	2nd. Det.	2.2	185	0.	+17.5	.5	0
Z-27	1st. P. P.	2.2	165	0.	+12.5	3.	0
Z-27	1st. P. P.	2.2	165	0.	+12.5	3.	0
Z-45	2nd. P. P.	2.3	240	—48.	0.	36.	0
Z-45	2nd. P. P.	2.3	240	—48.	0.	36.	0
Z-24	A. V. C.	2.3	30	— .4	0.	0.	45
Z-80	Rect.	5	350	0.	0.	70.	0
	Vol. Reg.	Con-	tin-	uity	test	only.	

Voltage readings taken with a Weston model 566 type 3 tester. Manual volume control in maximum position and antenna and ground disconnected. Line voltage 112

Fig. 3




Fig. 4 TUBE LAYOUT - Showing Position and Circuit Function of each.

Replacement Parts




Fig. 5

CONDENSERS

22-82	.001	Mfd.	(2nd Detector Plate)	\$.30
22-89	.1	Mfd.	(2 used, see footnote)	.35
22-90	.1	Mfd.	(2 used, see footnote)	.55
22-107	.1	Mfd.	(5 used, see footnote)	.85
22-112	.1	Mfd.	(Choke Bypass)	.35
22-119	6.	Mfd.	(Electrolytic)	2.50
22-123	Four Gang Variable			10.00
22-125	8.	Mfd.	(Electrolytic)	1.50
22-126	.006	Mfd.	(Tone Control)	.55
22-127	.000025	Mfd.	(A. V. C. Coupling)	.35
22-129	Padder			.75
22-130	.0001	Mfd.	(R. F. Coupling)	.20

RESISTORS

63-135	25M	Ohm.	(1st, 2nd Detector Cathode)	.30
63-140	1 Meg	Ohm.	(Oscillator Grid)	.30
63-146	2M	Ohm.	(2nd Detector and A. F.)	.30
63-166	1400	Ohm.	(R. F. and I. F. Grid Return)	.30
63-169	400M	Ohm.	(A. V. C. Plate)	.30
63-182	16400	Ohm.	(A. V. C. Divider, Metal Mtg.)	.75
63-183	6M	Ohm.	(Voltage Divider, see footnote)	.65
63-184	750	Ohm.	(Power Bias)	.30
63-186	5M	Ohm.	(2nd Detector Grid)	.30
63-192	Volume Control and Switch Assembly			1.75
63-193	Tone Control			1.00
63-144	3 Meg	Ohm.	(A. V. C. Grid)	.30

COILS

20-8	2nd R. F. Plate Choke			.50
20-12	Antenna Choke			.50
S-919	2nd Detector Plate Choke and Bracket			.60
S-1063	Pre-Selector	(Coil Only)		2.00
S-1073	1st R. F.	(Coil Only)		.90
S-1065	1st Detector	(Coil Only)		1.80
S-1060	I. F. Transformer (Specify with or without Grid Lead)			2.85
S-1067	Oscillator	(Coil Only)		1.65
S-1068	2nd R. F. Untuned Transformer			2.00
S-1072	Coupling Coil			.90

Note: 22-89 1st, 2nd, R. F. and 1st, 2nd, I. F. Grids.
 22-90 1st Detector Cathode and A. V. C. Plate.
 22-107 2nd Detector Cathode, 1st A. F. Bias, I. F. Plate and Voltage Divider.
 63-183 Specify—Porcelain or Metal Mounted Type.

IMPORTANT: GIVE SERIAL NUMBER OF RECEIVER ON ALL PARTS ORDERS.
ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

Replacement Parts




Fig. 6

DIAL ASSEMBLY

8-1003	Dial Light Socket and Clip (less lamp)	\$.60
8-1009	Tuning Shaft and Bracket Assembly	1.50
8-1010	Drum Gear and Cam	.85
8-1106	Dial Pointer and Reflector Plate	1.50
8-1110	Dial Strip and Bracket	.85
6-14	Pointer Arm Bearing	.20
15-12	Dial Light Clip	.35
76-110	Dial Elevator Shaft	.10
80-72	Pointer Arm Tension Spring	.08
94-119	Roller Bearings	.08
100-18	2 1/2 volt Meter Lamp	.25
100-20	3 1/4 volt Dial Lamp	.60
122-4	Tuning Meter and Cord	2.25
148-8	Dial Elevator Arm	.35

MISCELLANEOUS

19-21	Grid Clip	.02
44-4	Phono Jack Base Assembly	.30
46-49	Tuning Knob	.25
46-55	Control Knob (3 used)	.20
49-88	Dynamic Speaker	25.00
52-25	Speaker Multicord	.45
57-308	Dial Escutcheon Plate	.80
57-309	Meter Escutcheon Plate	.85
73-8	Small Set Screw for Auto Coupling	.01
78-86	Z-51 Socket	.20
78-87	Z-27 Socket	.20
78-88	Z-24 Socket	.20
78-40	Z-80 Socket	.20
78-41	Z-45 Socket	.20
78-42	Amperite Socket	.15
83-252	Speaker Multicord Terminal Strip	.20
85-24	Phono Switch	.75
85-32	Local Distance and Mute Switch	1.00
93-147	Electrolytic Condenser Insulating Washer	.02
95-102	110 volt 60 cycle Power Transformer	8.00
95-116	110 volt 25 cycle Power Transformer	13.50
114-6	Large Set Screw for Auto Coupling	.05
136-2	2 amp Fuse	.10
148-11	Auto Coupling Collar	.35
S-1037	Auto Control Shaft Assembly	.90
MS-176	Power Choke	4.00
MS-177	Audio Transformer (Six Lead)	5.50
MS-178	Audio Transformer (Five Lead)	5.50

IMPORTANT: GIVE SERIAL NUMBER OF RECEIVER ON ALL PARTS ORDERS.

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.



GENERAL

This supplement covers an improvement in the Model 103, fourteen tube Superheterodyne. It is confined entirely to the Manual volume control circuit as may be seen by comparing the diagram on page three with the schematic shown on the same page of the 5A Service Manual. In all receivers produced bearing serial number 450,451 or higher this change is incorporated.

The manual control has been removed from the A. V. C. cathode and placed in the grid circuit of the 1st A. F. stage. A tapped resistor takes the place of the original control. By use of this new system, the automatic volume control operates independently and at full efficiency, manual volume being controlled by varying the audio output.

It should be noted that since the A. V. C. or R. F. circuit remains constant, the tuning meter will show maximum swing on the station at any manual control setting. Originally the meter action decreased as the volume was lowered.


All voltages, tube locations, and parts listed in the 5A Manual apply directly and are to be used when servicing either type set. The balancing process remains unchanged. The parts list shown previously, except for the substitutions given below, should be used when ordering replacement components.

PARTS CHANGE

(Receivers bearing No. 450, 451 or higher, only)

1 Double section Audio Volume Control, part No. 63-213	
List	\$3.00
1 Center tapped resistor, part No. 63-211	
List	\$0.50
Deduct the 63-171 volume control.	

ZENITH RADIO CORPORATION



ZENITH RADIO CORP.
CHICAGO, ILL.
14 TUBE SUPERHETERODYNE
MODEL 451

CIRCUIT DIAGRAM
(SERIAL NOS. AFTER 450,451 ONLY)

SERVICE BULLETIN

No. 5C

Supplement to Service Manuals No. 5A & 5B

for

MODEL 103

All Zenith fourteen-tube Superheterodynes after serial number 451,260, incorporate a variable Sensitivity Control in place of the original Local-Distance switch. This improvement gives more flexible adjustment of the sensitivity thereby reducing the noise between stations for the type of reception desired. Since it constitutes only a few minor parts changes the 5A and 5B service manuals may be followed in making repairs or adjustments.

The change consists essentially of inserting a variable bias resistor into the I. F. cathode returns and transfer of the tuning meter from the I. F. to the R. F. circuit. It is absolutely essential that the meter be changed in the event that this improvement is added in the field, otherwise practically no reading will be obtained when the sensitivity control is used in a lower position.

It should be also noted that the 22-107 bypass condenser, employed in receivers subsequent to number 451,260, has been omitted from the plate to screen circuit and is now used to bypass the I. F. cathodes. A 2,000 ohm limiting resistor is connected in series from this point to the sensitivity control.

In addition to the improvements listed the A. V. C. coupling condenser No. 22-127 has been transferred from the plate of the second I. F. stage to the grid of the second detector. The 400 ohm resistor 63-131 in series with the 63-182 divider lowers the overall sensitivity to a more controllable level.

With the following changes, the parts list given in the 5A and 5B manuals will apply directly.

DEDUCT

No.	Description	List
1 85-32	Local-Distance switch	.85
1 63-144	3 megohm $\frac{1}{2}$ watt resistor	.30

ADD


1 63-228	Sensitivity Control	1.00
1 63-131	400 ohm $\frac{1}{2}$ watt resistor	.30
1 63-146	2,000 ohm $\frac{1}{2}$ watt resistor	.30


ZENITH RADIO CORPORATION

3620 IRON ST.

DECEMBER, 1931

CHICAGO, ILL., U. S. A.







PARTS LIST MODEL BH

Variable Condenser Assembly

22-134	Four Gang Condenser.....	\$ 6.00
S-905	Dial Drum Assembly.....	1.10
S-769	Pilot Lamp Bracket and Socket.....	.15
X0-18	2½ Volt Pilot Lamp.....	.25
11-3	Pulley String (27").....net	.10
30-69	Dial String Tension Spring.....	.01
S-963	Dial Pointer Mask and Bracket.....	.25

Fixed Condensers

22-108	.002 mfd.....(2nd Detector Plate).....	.35
22-112	.1 "(Audio Coupling).....	.35
22-113	.5 "(See Footnote).....	.50
22-115	.1 "(See Footnote).....	.35
22-129	Padder Condenser.....(Variable).....	.75
22-132	4. mfd.....450 Volt.....(Filter).....	.85
22-133	2. "450 Volt.....(Filter).....	.80
22-137	.05 "(See Footnote).....	.25
22-138	.2 "(Pentode Grid).....	.25

Resistors

53-135	25M ohm.....(See Footnote).....	.30
53-139	500M "(Pentode Bias).....	.30
53-140	1meg"(Oscillator Grid).....	.30
53-160	100M "(See Footnote).....	.30
53-181	Volume Control and Switch.....	1.50
53-195	12M ohm.....(Voltage Divider).....	.50
53-196	6M "(Voltage Divider).....	.50
53-197	17M "(R.F. & I.F. Screen).....	.30
53-198	30M "(1st Detector Screen).....	.30
53-199	150 "Wire Wound.....(R.F. & I.F. Cathode).....	.30
53-200	Tone Control.....	1.00

Coils


S-916	Pre-Selector or 1st R. F.....	.75
S-917	1st Detector Coil Complete with Choke and Band.....	1.25
S-918	Oscillator Coil Complete.....	1.25
S-912	Intermediate Transformer (Specify with or without Grid Lead)....	2.50
S-919	2nd Detector Plate Choke.....	.60

Miscellaneous

49-39	Dynamic Speaker.....	9.50
MS-179	Filter Choke.....	1.00
95-108	60 Cycle Power Transformer.....	4.50
95-111	25 Cycle Power Transformer.....	6.75
95-112	220 Volt Power Transformer.....	6.75
S-911	Antenna Series Condenser Assembly.....	.85
26-23	Calibrated Dial Strip.....	.20
46-56	Control Knobs.....	.25
93-228	Speaker Terminal Strip.....	.15
52-27	Speaker Cord.....	.25
78-36	Z-51 Tube Socket.....	.20
78-37	Z-27 Tube Socket.....	.20
78-38	Z-24 Tube Socket.....	.20
78-39	Z-47 Tube Socket.....	.20
78-40	Z-80 Tube Socket.....	.20

Note:	22-113 - Two used - Bypass 1st Detector Screen and 2nd Detector Cathode.
Note:	22-115 - Two used - Bypass R. F. - I. F. Screens and 1st R. F. Cathode.
Note:	22-137 - Two used - Tone Control and 1st Detector Cathode.
Note:	63-160 - Three used - 2nd Detector Plate, Pentode Grid and Pentode Bias.
Note:	63-135 - Two used - 1st and 2nd Detector Cathodes.

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.



PARTS AND PRICES

MODELS LH WH MH

Variable Condenser Assembly

22-134	Four Gang Condenser.....	\$ 6.00
S-1191	Dial Drum Assembly.....	.80
11-3	Pulley String.....per ft	.10
26-28	Dial Strip.....	.10
80-69	Dial String Cable Tension Spring.....	.01
100-18	2½ volt Pilot Lamp.....	.25
S-769	Dial Lamp Socket Assembly (Less Lamp).....	.15

Fixed Condensers

22-82	.001 mfd.....(2nd Detector Plate).....	.30
22-113	.5 "(2nd Detector Cathode).....	.50
22-115	.1 "(R.F. & I.F. Cathode).....	.35
22-117	.5 "(R.F. & 1st Detector Screen)...	.50
22-129	Padder.....	.75
22-131	6. mfd.....(Power Filter).....	1.25
* 22-137	.05 "(3 used, see footnote).....	.25
22-138	.2 "(Power Grid).....	.25
22-140	8. "(Power Filter).....	1.50

Resistors

63-135	25M ohm.....(1st, 2nd Detector Cathode).....	.30
63-139	500M "(Power Grid).....	.30
63-140	1meg "(Oscillator Grid).....	.30
63-160	100M "(2nd Det. Plate & Power Grid)...	.30
63-199	250 "(R.F. & I.F. Cathode, Flexible)...	.30
63-200	Tone Control.....	1.00
63-207	10M ohm.....(Voltage Divider, Wire Wound)...	.35
63-208	12M "(Voltage Divider).....	.30
63-209	Volume Control and Switch Assembly.....	1.25

Coils

S-919	2nd Detector Plate Coil.....	.60
S-1179	R. F. Pre-Selector.....	1.50
S-1180	Oscillator Coil.....	.90
S-1181	Detector Coil.....	.90
S-1185	2nd I. F. Transformer.....(175 K. C.).....	1.50
S-1186	1st I. F. Transformer.....(175 K. C.).....	1.40
S-1193	R. F. Plate Choke and Bracket.....	.50


Miscellaneous

49-40	Dynamic Speaker for LH and WH.....	8.00
49-41	Dynamic Speaker for MH.....	8.50
46-58	Control Knobs, all sets, three used.....	.10
52-27	Speaker Cable.....	.25
57-326	Escutcheon Plate, all sets.....	.30
78-36	Z-51 Tube Socket.....	.20
78-37	Z-27 " ".....	.20
78-38	Z-24 " ".....	.20
78-39	Z-47 " ".....	.20
78-40	Z-80 " ".....	.20
83-228	Speaker Cable Terminal Strip.....	.15
93-138	Felt Washer for Control Knob.....	.01
95-117	60 cycle 110 volt Power Transformer).....(Specify with or	4.50
95-118	25 cycle 110 volt Power Transformer)..... without fuse	6.75
95-121	60 cycle 220 volt Power Transformer).....clip assembly).	6.75
136-2	2 amp Fuses.....	.10
S-1151	Heat Insulating Shield.....	.30
S-1183	Antenna and Ground Mounting Plate Complete.....	.25
S-1184	Variable Condenser Shield.....	.85
MS-180	Tube Shield Assembly.....	.60

IMPORTANT: GIVE SERIAL NUMBER OF RECEIVER ON ALL PARTS ORDERS.

* A. F. COUPLING, TONE CONTROL, AND 1ST DETECTOR CATHODE.

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.



MEAN FREQUENCY 175 K.C.

TO THE VEST AG,



Socket Voltages

Models 210-220-221


Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	R.F.	2.35	248	3	115	3	9.5
Z-24	1st Det.	2.35	248	22	115	-	.4
Z-27	Osc.	2.35	118	-	-	-	3.
Z-58	I.F.	2.35	248	3	115	3	8.
Z-27	2nd Det.	2.35	110	50	-	-	.4
Z-47	Power	2.35	226	-	245	-	38.
Z-80	Rect.	4.8	350	-	-	-	32.

Line 115 Volts

All Controls Maximum

(All readings, with exception of heaters, taken from socket connections to ground. Use 1,000 ohm per volt D. C. meter.)

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator padder at 600 K.C.



TUBE LAYOUT MODELS 210-220-221

PARTS AND PRICES
MODELS 210 220

Variable Condenser Assembly

22-159	Four Gang Condenser.....	\$6.00
S-2121	Dial Drum Assembly.....	.80
11-3	Pulley String.....per ft.	.10
26-34	Dial Strip.....	.25
100-18	2 $\frac{1}{2}$ volt Pilot Lamp.....	.12
S-769	Dial Lamp Socket Assembly (Less Lamp).....	.15

Fixed Condensers

22-82	.001 mfd.....(2nd Detector Plate).....	.25
22-111	.03 "(Filter Choke Bypass).....	.20
22-113	.5 "(2nd Detector Cathode).....	.30
22-115	.1 "(R.F. & I. F. Cathode).....	.20
22-117	.5 "(R.F. & I. F. Detector Screen).....	.30
22-161	Padder	.45
22-156	6. mfd.....(Power Filter).....	1.25
* 22-137	.5 "(3 used, see footnote).....	.15
22-138	.2 "(Power Grid).....	.25
22-157	8. "(Power Filter).....	1.50

Resistors

63-135	25M ohm.....(1st, 2nd Detector Cathode).....	.25
63-139	500M "(Power Grid).....	.25
63-140	1Meg "(Oscillator Grid).....	.25
63-160	100M "(2nd Det.Plate & Power Grid).....	.25
63-199	150 "(R.F. & I.F.Cathode, Flexible).....	.25
63-200	Tone Control.....	.80
63-207	10M ohm.....(Voltage Divider, Wire Wound).....	.30
63-208	12M "(Voltage Divider).....	.25
63-209	Volume control and switch assembly.....	1.25

Coils

S-919	2nd Detector Choke.....	.60
S-2125	Detector Coil.....	.90
S-2126	Oscillator Coil.....	.90
S-2127	R.F. Pre-selector.....	1.50
S-1186	1st I.F. Transformer.....(175 K.C.).....	1.40
S-2136	2nd I.F. Transformer.....(175 K.C.).....	1.30

Miscellaneous

49-44	Dynamic Speaker	8.00
-------	-----------------------	------

* A.F.COUPLING, TONE CONTROL, AND FIRST DETECTOR CATHODE.

Miscellaneous (Cont'd)

46-58	Control Knobs, all sets, three used.....	\$.15
52-27	Speaker Cable.....	.25
57-326	Escutcheon Plate, all sets.....	.30
78-37	Z-27 Tube Socket.....	.20
78-38	Z-24 Tube Socket.....	.20
78-39	Z-27 Tube Socket.....	.20
78-40	Z-80 Tube Socket.....	.20
78-54	Z-58 Tube Socket.....	.20
83-228	Speaker Cable Terminal Strip.....	.15
93-138	Felt Washer for Control Knob.....	.01
95-127	60 cycle 110 volt Power Transformer.....	4.75
95-172	25 cycle all voltage Power Transformer.....	7.75
136-2	2 amp Fuse.....	.06
136-4	1 amp Fuse.....	.06
S-1183	Antenna and Ground Mounting Plate Complete.....	.25
S-2120	Variable Condenser Shield.....	.85
S-2124	Heat Insulating Shield.....	.30
MS-187	Tube Shield Assembly.....	.60

IMPORTANT: GIVE SERIAL NUMBER OF RECEIVER ON ALL PART ORDERS

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PARTS LISTS FOR LIKE PARTS.

ZENITH RADIO CORPORATION
May 21, 1934



Socket Voltages

Models 215-216-225

Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	R.F.	2.5	270	8	107	8	5.8
Z-58	1st Det.	2.5	270	10	107	10	4.7
Z-56	Osc.	2.5	140	0	-	-	4.8
Z-58	I.F.	2.5	170	8	107	8	5.5
Z-55	2nd Det. AVC	2.5	70	7	-	-	1.4
Z-59	Power	2.5	250	0	250	0	26.
Z-80	Rect.	5.	360ea	-	-	-	34.ea.

Line 115 Volts

All Controls Maximum

(All readings, with exception of heaters and rectifier plates taken from socket connections to ground. Use 1,000 ohm per volt D.C. meter. Antenna disconnected).

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator padder at 600 K.C.




FIG. 2. POSITION OF TUBES.
MODELS 215-225-216

PARTS AND PRICES

MODELS 215 216 225
CHASSIS 2044

Variable Condenser Assembly

11-3	Dial Cord.....	per ft.	\$.10
22-166	Three Gang Variable Condenser.....		3.50
26-38	Celluloid Dial Strip.....		.25
80-69	Dial Cord Tension Spring.....		.01
80-89	Dial Cord Guide Spring.....		.01
100-18	2½ Volt Dial Lamp.....		.12
S-2238	Dial Drum Assembly.....		.80

Fixed Condensers

22-82	.001 mfd. 500 volt	(2nd Det. Plate).....	.25
* 22-115	.1 " 200 "	(5 Used. See Footnote).....	.20
22-117	.5 " 300 "	(Screen Bypass).....	.30
22-137	.05 " 400 "	(Oscillator Plate).....	.15
22-147	.0005 " 600 "	(2nd Det. Cathode).....	.15
22-161	Padder.....		.45
* 22-170	.1 mfd. 400 volt	(Four Used. See Footnote).....	.25
22-171	.05 " 600 "	(Tone Control).....	.20
22-173	8. " 500 "	(Filter).....	1.50
22-196	.01 " 600 "	(Tone Control).....	.15

Resistors

63-121	100M ohm.....	(2nd Det. Plate).....	.25
63-136	50M "	(RF Grid, 2nd Det. Plate).....	.25
63-137	250M "	(Osc. Bias, Power Grid).....	.25
63-140	1Meg "	(Grid).....	.25
63-160	100M "	(2nd Det.).....	.25
63-232	Tone Control.....		.75
63-235	Volume Control.....		1.25
63-239	24M ohm.....	(Oscillator Plate).....	.25
63-244	500 "	(1st Det. Cathode).....	.20
63-254	5M "	(2nd Det. Grid).....	.25
63-255	Sensitivity Control.....		.60
63-256	6950 ohm.....	(Voltage Divider).....	.45
63-257	8350 "	(Voltage Divider).....	.40
63-258	490 "	(1st Det. & I.F. Grid Return).....	.20

Coils - Chokes

20-30	Antenna Coil.....		.75
20-31	Oscillator Coil.....		.85
20-32	Detector Coil.....		1.00
* 22-115	R.F. Grid; R.F. 1st Det. and I.F. Cathode; 1st Det. Suppressor; 1st Det. I.F. Grid Return and Power Choke.		
* 22-170	2nd Det. Plate; 2nd Det. Grid Filter & Audio Coupling.		

PARTS AND PRICES

- PAGE 2 -

MODELS 215 216 225

CHASSIS 2044

Coils - Chokes Cont'd


S-2118	1st I.F. Coil Assembly..(Without Grid Lead).....	\$1.75
S-2611	2nd I.F. Coil Assembly..(With Grid Lead).....	1.75
S-2252	Detector Plate Choke.....	.60

Miscellaneous

46-61	Large Tuning Knob.....	.25
46-62	Small Control Knob.....	.25
49-55	Dynamic Speaker for Model 215 and 216.....	7.00
49-56	Dynamic Speaker for Model 225.....	8.00
52-37	Speaker Multicable.....	.25
57-370	Escutcheon Plate.....	.30
78-56	Type 59 Tube Socket.....	.15
78-57	Type 56 Tube Socket.....	.15
78-58	Type 58 Tube Socket.....	.15
78-60	Type 30 Tube Socket.....	.15
78-61	Type 55 Tube Socket.....	.15
93-167	Upper Cushion Washer for Chassis Mounting.....	.01
95-153	Regular 117 volt 60 cycle Power Transformer.....	5.25
95-173	25 cycle all voltage Power Transformer.....	7.75
126-109	Tube Shields.....	.10
15-16	Tube Shield Cap in AVC Tube.....	.05
136-2	2 Amp Fuse.....	.06
136-4	1 Amp Fuse.....	.06

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PARTS LISTS FOR LIKE PARTS.

ZENITH RADIO CORPORATION
May 21, 1934



I. F. FREQUENCY
175 K. C.

ZENITH RADIO CORP.
CHICAGO, ILL.
8-TUBE SUPERHETERODYNE
MODELS 230-240-244-245
CHASSIS 2036

REVISED 9-17-32

95-140 60~
95-141 25~

T0-115-0R-230-VOLT A.C.



Socket Voltages

Models 230-240-245


Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	R.F.	2.4	190	0	95	0	7.
Z-58	1st Det.	2.4	190	2.3	95	2.3	4.
Z-56	Osc.	2.4	100	0	-	-	4.
Z-58	I.F.	2.4	190	0	90	0	2.
Z-57	2nd Det.	2.4	90	-60	70	-60	.2
Z-57	A.V.C.	2.4	-10	-65	-2	-65	0
Z-59	Power	2.4	175	-70	165	-70	25
Z-80	Rect.	5.	*350	-	-	-	*36

Line 115 Volts

All Controls Maximum

(All readings, with exception of heaters, taken from socket connections to ground.
Use 1,000 ohm per volt D. C. meter.)

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator pad-
der at 600 K.C.



PARTS AND PRICES

MODELS 230 240 244 245

Dial Assembly

S-769	Dial Lamp Socket and Bracket (less lamp).....	\$.15
S-2238	Dial Drum Assembly.....	.80
S-2248	Small Hypoid Gear Complete with Drive Shaft.....	1.25
11-3	Pulley String.....per ft.	.10
26-36	Celluloid Dial Strip.....	.30
34-23	Hypoid Drum Gear (large).....	1.00
34-24	Hypoid Drum Gear (small).....	1.00
80-69	Dial String Tension Spring.....	.01

Condensers

22-112	.1 mfd 300 V.(2nd Detector Screen & Power Grid).....	.25
22-115	.5 "(R.F.1st Detector & I.F. Grid Return)....	.30
* 22-115	.1 " 200 V.(Four used, see below).....	.20
22-117	.5 "(R.F.1st Detector & I.F. Screen).....	.30
22-137	.05 " 400 V.(Oscillator Plate).....	.15
22-147	.0005 " 600 V.(2nd Detector Plate & AVC Screen).....	.20
22-161	Padder.....	.45
22-166	Three Gang Variable.....	3.50
22-170	.1 mfd 400 V.(R.F.& 1st Detector Plate, 2nd Det. Plate).	.25
22-171	.05 " 600 V.(Tone Control).....	.20
22-172	2. " 450 V.(Filter).....	.80
22-173	8. " 500 V.(Filter).....	1.50
22-175	.002 " 600 V.(A.V.C.Plate).....	.25

Resistors

63-121	100M ohm 1 Watt.....(2nd detector plate).....	.25
63-135	25M " $\frac{1}{2}$ "(2nd detector cathode).....	.25
63-136	50M " $\frac{1}{2}$ "(2nd detector grid return).....	.25
63-137	250M " $\frac{1}{2}$ "(Oscillator & Power Grid).....	.25
63-140	1 meg " $\frac{1}{2}$ "(A.V.C. Screen).....	.25
63-160	100M " $\frac{1}{2}$ "(A.V.C.Plate, 2nd Detector Screen)	.25
63-169	400M " $\frac{1}{2}$ "(A.V.C.Grid).....	.25
63-232	Manual Tone Control.....	.75
63-233	Manual Sensitivity Control.....	.75
63-235	Manual Volume Control.....	1.25
63-239	24M ohm 1 Watt.....(Oscillator Plate).....	.25
63-241	5M " 1 "(R. F. 1st Detector, I.F. Screen).....	.25
63-244	500 " $\frac{1}{4}$ "(1st Detector Cathode).....	.20
63-251	Voltage Divider.....(six tap).....	.65
63-252	Voltage Divider.....(five tap).....	.60

Chokes and Coils

S-2118	I.F. Coil Assembly.....	1.75
S-2437	Antenna Coil Assembly.....	.75
S-2438	Oscillator Coil Assembly.....	.85
S-2439	Detector Coil Assembly.....	1.00
S-2252	Plate Choke.....	.50
S-919	2nd Detector Choke.....	.50
* 22-115	I.F. Cathode, 2nd Det. Grid Ret. 1st and 2nd Det. Cathodes..	

PARTS AND PRICES

(Page - 2)

MODELS 230 240 244 245

Miscellaneous

46-49	Large Knob for Model 240 - 245.....	\$.20
46-55	Small Knob for Model 240 - 245.....	.15
46-61	Large Knob for Model 230.....	.25
46-62	Small Knob for Model 230.....	.25
49-45	Dynamic Speaker for Model 240 -245 (without transformer)..	6.00
49-46	Dynamic Speaker for Model 240 -245(with transformer).....	8.00
49-49	Dynamic Speaker for Model 230.....	7.00
52-32	Speaker Multicord.....	.35
57-326	Escutcheon Plate for Model 230.....	.30
57-353	Escutcheon Plate for Model 240 -245.....	.30
78-56	59, 7 Prong Tube Socket.....	.15
78-57	56, 5 Prong Tube Socket.....	.15
78-58	58, 6 Prong Tube Socket.....	.15
78-59	57, 6 Prong Tube Socket.....	.15
78-60	80, 4 Prong Tube Socket.....	.15
95-140	110 Volt 50 - 60 Cycle Power Transformer.....	5.00
95-170	All Voltage 25-30 Cycle Power Transformer.....	8.50
100-18	2½ Volt Dial Lamp.....	.12
136-2	2 amp Fuse.....(For 110 Volt Transformer).....	.06
136-4	1 amp Fuse.....(For 220 Volt Transformer).....	.06
126-109	Tube Shield.....(Small).....	.10
MS-196	Tube Shield.....(Large for Model 240-245 only).....	1.25
S-1183	Antenna and Ground Mounting Plate Assembly.....	.25

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO
ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PARTS LISTS
FOR LIKE PARTS.

January 15, 1934

PARTS AND PRICES
STANDARD AND SHORT WAVE RECEIVERS
MODELS 250 - 260 - 272

Dial Assembly

11-3	Dial Cord.....	per ft.	\$.10
12-251	Dial Slide Support Bracket.....		1.25
61-23	Dial Cord Pulley.....		.15
73-8	Dial Collar Set Screw.....		.01
80-77	Dial Cord Tension Spring.....		.01
84-41	Dial Lamp Support Slide.....		.60
S-2137	Dial Pointer Mask Assembly.....		1.70
S-2164	Dial Vernier Tuning Shaft and Bracket.....		1.50
S-2165	Dial Gear and Bushing Assembly.....		1.50
S-2166	Dial Strip Support and Strip Assembly.....		2.00

Condensers

22-82	.001 Mfd 500 volt.....	(Power Plate).....	.20
22-111	.03 " 600 "	(Filter).....	.20
22-112	.1 " 300 "	(S.W. Det. Screen).....	.25
22-113	.5 " 200 "	(2nd Det. Plate).....	.35
* 22-115	.1 " 200 "	(3 Used, See Below).....	.35
22-117	.5 " 300 "	(R.F.Det. & I.F.Screen).....	.50
* 22-137	.05 " 400 "	(3 Used, See Below).....	.25
22-138	.2 " 200 "	(Power Grid).....	.25
* 22-147	.0005 " 600 "	(2 Used, See Below).....	.25
22-153	Short Wave Variable Trimmer.....		1.00
22-155	Three Gang Variable Trimmer.....		2.40
22-156	6. Mfd Electrolytic.....	(Filter).....	1.25
22-157	8. " Electrolytic.....	(Filter).....	1.50
22-158	Three Section Padder.....		.75
22-160	Five Gang Variable Tuning Condenser.....		7.00
22-161	Single Padder.....		.45
22-162	.0001Mfd 600 volt.....		.20

Resistors

63-121	100M ohm 1 watt.....	(Det. Plate).....	.25
63-135	25M " $\frac{1}{2}$ "	(2 Used, 1st & 2nd Det. Cathode).....	.25
63-139	500M " $\frac{1}{2}$ "	(2 Used, Power Grid, Osc. Grid).....	.25
63-146	2M " $\frac{1}{2}$ "	(S.W.Osc. Grid, 2nd Det. Cathode)....	.25
63-160	100M " $\frac{1}{2}$ "	(Power Grid).....	.25
63-167	8M " 1 "	(S. W. Det. Cathode).....	.25
63-199	150 "	(R.F., I.F. Cathode).....	.25
63-200	Tone Control.....		.80
63-207	10M ohm $\frac{1}{2}$ watt.....	(Voltage Divider).....	.30
63-208	12M "	(Voltage Divider).....	.25
63-209	Volume Control and Switch Assembly.....		1.25
63-230	15M ohm	(S. W. Det. Screen).....	.35

- * 22-115 S.W.Coupling, S.W.Oscillating Filter, and R.F.Cathode
- * 22-137 1st Detector Cathode, Audio Coupling, and Tone Control
- * 22-147 2nd Detector Plate

- Page 2 -
PARTS AND PRICES
MODELS 250 - 260 - 272

Coils - Chokes

S-919	2nd Detector Plate Choke.....	\$.60
S-1193	S.W. Detector Plate Choke.....	.50
S-2117	2nd I.F. Coil Assembly.....(No Grid Lead).....	1.75
S-2118	1st I.F. Coil Assembly.....(With Grid Lead).....	1.75
S-2161	Detector S. W. Coil.....(Mounted above Chassis).....	1.25
S-2162	Oscillator S. W. Coil.....(Mounted under Chassis).....	1.25
S-2167	1st R.F. Coil Assembly.....	1.25
S-2169	Oscillator Coil L.W.....	.80
S-2171	1st Detector Coil L.W.....	1.25

Miscellaneous

8-25	Antenna and Ground Binding Post Assembly.....	.20
44-4	Phono Jack Receptacle Assembly.....	.15
46-59	Large Knob.....	.15
46-60	Small Knob.....	.15
49-44	Dynamic Speaker.....	8.00
57-342	Escutcheon Plate.....	.60
78-39	Z-47 Tube Socket.....	.15
78-40	Z-80 Tube Socket.....	.15
78-54	Z-58 Tube Socket.....	.15
78-55	Z-57 Tube Socket.....	.15
83-218	Single Terminal Soldering Brackets.....	.05
83-228	Speaker Cable Terminal Strip.....	.15
83-260	Double Terminal Mounting Brackets.....	.07
85-24	Radio Phono Switch.....	.60
85-36	S.W. Selector Band Switch.....	2.00
93-167	Rubber Cushion for Chassis Mounting (Upper).....	.01
93-168	Rubber Cushion for Chassis Mounting (Lower).....	.01
93-170	Metal Washer for Chassis Mounting.....	.02
95-129	Combination 110-220 volt, 60 cycle Power Transformer.....	6.00
95-131	Regular 110 volt, 25 cycle Power Transformer.....	8.00
100-18	2½ volt Pilot Lamp.....	.12
112-6	Speaker Mounting Screw 8/32 x 1¼".....	.01
136-2	2 amp Fuse.....	.06
136-4	1 amp Fuse.....	.06

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

VOLTAGE READINGS - MODELS 530 531 533

Antenna Disconnected

Meter 1000 Ohms Per Volt

Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	1st R.F.	2.5	175	2.2	75	2.2	5.7
Z-58	1st Det.	2.5	190	4.5	75	4.5	2.3
Z-56	Osc.	2.5	100	0	-	-	3.5
Z-58	1st I.F.	2.5	200	2.2	75	2.2	5.5
Z-56	2nd Det.	2.5	110	10	-	-	.3
Z-56	1st Audio	2.5	170	80	-	-	.8
Z-57	A.V.C.	2.5	-	-85	-	-85	-
Z-57	Q.A.V.C.	2.5	30	13	75	13	-
Z-59	Driver	2.5	190	20	190	190	13
Z-59	Power	2.5	195	-70	195	195	22
Z-59	Power	2.5	195	-70	195	195	22
Z-80	Rect.	5.0	360	-	-	-	65


Line Voltage 115

(Reading to Ground)

Volume control maximum

(All readings, with exception of heaters, taken from socket connections to ground.
Use 1,000 ohm per volt D. C. meter.)

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator
padder at 600 K.C.



Tube Position

PARTS AND PRICES

MODELS 530 531 533
CHASSIS 2038

Dial and Meter Assembly

11-3	Dial Pulley String.....per ft.	\$.10
26-38	Calibrated Dial Strip.....	.15
80-69	Dial Cord Tension Spring.....	.01
80-85	Volume and Tone Control Dial Tension Spring.....	.01
83-274	Volume Control Dial Strip.....	.10
83-275	Tone Control Dial Strip.....	.10
100-18	2½ Volt Pilot Lamp.....	.12
122-5	Shadowgraph Meter.....	2.00

Condensers

22-112	.1 mfd 300 volt...(Filter).....	.25
*22-115	.1 " 200 " ...(Eight Used, See Below).....	.35
22-117	.5 " 300 " ...(Filter).....	.50
22-127	.000025 600 " ...(A.V.C. Grid).....	.35
22-137	.05 mfd 400 " ...(Oscillator Plate).....	.25
22-142	.4 " 300 " ...(Filter 25 Cycle Only).....	.40
22-147	.0005" 600 " ...(2nd Detector Plate).....	.20
22-161	Padder.....	.45
22-165	Three Gang Variable.....	3.50
22-167	8. mfd 500 volt...(Filter).....	1.50
22-169	8. " 50 " ...(2nd Det. Cathode, Driver Cathode & 1st Audio Cathode).....	.55
22-170	.1 " 400 " ...(1st Det. Plate, Tone Control).....	.25
22-175	.002 " 600 " ...(1st Audio Plate).....	.25
22-177	.2 " 400 " ...(2nd Det. Plate, 1st Audio Grid, 1st Audio Plate).....	.25

Resistors

63-121	100M ohm 1 watt...(2nd Detector Plate).....	.25
63-137	250M " ¼ " ...(Driver Grid).....	.25
63-140	1 meg" ½ " ...(A.V.C. Grid & Cathode).....	.25
63-169	400 " ½ " ...(A.V.C. & Q.A.V.C. Plate).....	.25
63-231	Volume Control & Switch Assembly.....	1.40
63-232	Tone Control.....	.75
63-236	500 ohm ...(Wide Metal) (Power Tube Bias).....	.25
63-237	1500 " ...(Narrow Metal) (Driver Tube Bias).....	.25
63-239	24M " 1 watt...(Osc. & 1st Audio Plate).....	.25
63-240	1900 " ¼ " ...(R.F. 1st Det. & I.F. Grids).....	.25
63-242	2500 " ½ " ...(A.V.C. Cathode).....	.25
63-243	18M " 1 " ...(A.V.C. Cathode).....	.25
63-244	500 " ¼ " ...(Acoustic Filter).....	.25
63-245	1500 " ¼ " ...(1st Detector Cathode).....	.25
63-246	150 " ¼ " ...(R.F. Cathode).....	.25
63-247	8M " ¼ " ...(1st Audio Cathode).....	.25
63-248	50M " 1 " ...(2nd Det. Plate & Cathode).....	.25
63-249	Sensitivity & Quiet Control.....	.75

*22-115 R.F. 1st Detector, I.F. Grid Returns, A.V.C. Plate, A.V.C. Cathode, 1st Detector Cathode, R.F. Cathode, and Acoustic Filter.

PARTS AND PRICES
(Page - 2)

MODELS 530 531 533
CHASSIS 2038


Coils

20-33	Antenna Coil.....	\$.75
20-34	Oscillator Coil.....	.85
20-35	Detector Coil.....	1.00
95-133	1st I.F. Transformer with Grid Lead.....	1.25
95-139	2nd I.F. Transformer without Grid Lead.....	1.25

Miscellaneous

46-61	Large Knobs.....	.20
46-62	Small Knobs.....	.10
49-52	Dynamic Speaker (With Transformer).....	8.25
49-53	Dynamic Speaker (Without Transformer).....	7.00
52-34	Speaker Multicord.....	.45
57-343	Escutcheon Plate.....	.50
78-56	Type 59 Socket.....	.15
78-57	Type 56 Socket.....	.15
78-58	Type 58 Socket.....	.15
78-59	Type 57 Socket.....	.15
78-60	Type 80 Socket.....	.15
93-167	Upper Cushion Washer for Chassis Mounting.....	.01
93-168	Lower Cushion Washer for Chassis Mounting.....	.01
95-142	115 volt 25 cycle Power Transformer.....	7.25
95-143	115 volt 60 cycle Power Transformer.....	5.25
95-149	Acoustic Filter Choke.....	.30
106-129	Small Tube Shield.....	.10
MS-200	Push Pull Input Transformer.....	3.50
MS-201	Power Filter Choke.....	3.25

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.



WIRING DIAGRAM
MODEL 563

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS
DATE 7-24-29 K.C.T.



Socket Voltages

Models 410-411-420



Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	R.F.	2.5	220	0	100	0	5.2
Z-58	1st Det.	2.5	220	+2	100	+2	3.
Z-56	Osc.	2.5	120	0	0	*	4.
Z-58	I.F.	2.5	220	0	100	0	6.
Z-56	2nd Det.	2.5	120	20	0	*	.75
Z-57	A.V.C.	2.5	-40	-75	-2	-75	0
Z-59	Driver	2.5	220	+25	220	+220	8.2
Z-59	Power	2.5	230	-65	230	+230	25.
Z-59	Power	2.5	230	-65	230	+230	25.
Z-80	Rect.	5.0	400*				62.5*

Line 115 Volts


All Controls Maximum

(All readings, with exception of heaters, taken from socket connections to ground. Use 1,000 ohm per volt D. C. meter).


BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator padder at 600 K.C.



SOCKET CONNECTIONS



Model 420



Models 410-411

SOCKET LAYOUT

PARTS AND PRICES
MODELS 410 411 420
CHASSIS #2030 - 2043

Dial and Meter Assembly

11-3	Dial Pulley String.....per ft.	\$.10
26-37	Dial Strip.....	.15
34-23	Large Hypoid Gear (Model 420 Only).....	.30
34-24	Small Hypoid Gear (Model 420 Only).....	.15
59-16	Volume Control Pointer.....	1.00
59-17	Tone Control Pointer.....	1.00
80-69	Dial String Tension Spring.....	.01
80-84	Volume and Tone Control Pointer Spring.....	.01
80-86	Volume and Tone Control Friction Spring.....	.01
83-272	Volume Control Dial Strip.....	.10
83-273	Tone Control Dial Strip.....	.10
83-277	Pointer Guide Strip.....	.01
100-18	Pilot Lamp.....	.12
122-6	Shadowgraph Meter.....	2.00
S-2255	Tone Control Pointer Cam.....	.25
S-2256	Volume Control Pointer Cam.....	.25
S-2265	Dial Drum Assembly.....	1.00

Condensers

22-112	.1 mfd 300 volt (Filter).....	.25
22-115	.1 " 200 " (Six used, see footnote).....	.35
22-117	.5 " 200 " (Filter).....	.50
22-127	.000025 600 " (A. V. C. Grid).....	.35
22-137	.05mfd 400 " (Oscillator Plate).....	.25
22-142	.4 " 300 " (Filter 25 Cycle Only).....	.40
22-147	.0005 600 " (2nd Detector Plate).....	.20
22-161	Padder.....	.45
22-166	Three Gang Variable.....	3.50
22-167	8. mfd 500 volt (Filter).....	1.50
22-169	8. " 50 " (2nd Det. and Driver Cathodes).....	.55
22-170	.1 " 400 " (1st Det. plate, Audio Coup., Tone Control)..	.25
22-175	.002" 600 " (1st Det. cathode - Models 410-411 only).....	.20

Resistors

63-121	100M ohm 1 watt (2nd Detector Plate).....	.25
63-135	50M " 1 " (2nd Detector Cathode).....	.25
63-137	250M " $\frac{1}{2}$ " (Oscillator Grid).....	.25
63-140	1 meg" $\frac{1}{2}$ " (A. V. C. Grid).....	.25
63-169	400 " $\frac{1}{2}$ " (A. V. C. Plate).....	.25
63-231	Volume Control Assembly.....	1.25
63-232	Tone Control Assembly.....	.75
63-233	Sensitivity Control.....	.75
63-236	500 ohm.....(Power Bias) (Wide Metal).....	.25
63-237	1500 "(Driver Bias) (Narrow Metal).....	.25
63-238	1M " $\frac{1}{4}$ watt (1st Detector Cathode).....	.25
63-239	24M " 1 " (Oscillator Plate).....	.25
63-240	1900 " $\frac{1}{4}$ " (R.F., 1st Detector and I.F. Grids).....	.25
63-242	2500 " $\frac{1}{2}$ " (A. V. C. Cathode).....	.25
63-243	18M " 1 " (A. V. C. Cathode).....	.25
63-244	500 " $\frac{1}{4}$ " (Acoustic Filter).....	.25

*22-115 R. F., 1st Detector, I. F. Grid Return, I. F. Cathode, Accustic Filter, (1st Detector Cathode Model 420 Only).

PARTS AND PRICES
MODELS 410 411 420

CHASSIS #2030 2043
PAGE - 2 -

Coils

20-30	Antenna Coil.....	\$.75
20-31	Oscillator Coil.....	.85
20-32	Detector Coil.....	1.00
S-2252	Plate Choke and Bracket.....	.50
95-132	1st I. F. Transformer (With Grid Lead).....	1.25
95-138	2nd I. F. Transformer (Without Grid Lead).....	1.25
Miscellaneous		
46-49	Large Control Knob.....	.20
46-55	Small Control Knob.....	.15
49-47	Dynamic Speaker with Transformer.....	7.00
49-48	Dynamic Speaker without Transformer.....	8.25
52-35	Speaker Multicord.....	.35
57-341	Escutcheon Plate.....	.35
78-56	Type 59 Socket.....	.15
78-57	Type 56 Socket.....	.15
78-58	Type 58 Socket.....	.15
78-59	Type 57 Socket.....	.15
78-60	Type 80 Socket.....	.15
93-167	Upper Cushion Washer for Chassis Mounting.....	.01
93-168	Lower Cushion Washer for Chassis Mounting.....	.01
95-134	115 Volt 50-60 Cycle Power Transformer.....	5.50
95-136	115 Volt 25-30 Cycle Power Transformer.....	7.75
95-149	Acoustic Filter Choke.....	.30
126-109	Small Tube Shield.....	.10
136-2	2 amp Fuse.....	.06
MS-174	Power Choke (Model 420 Only).....	3.25
MS-200	Push Pull Input Transformer.....	3.50
MS-201	Power Choke (Models 410-411 Only).....	3.25

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
September 10th, 1932.



Socket Voltages

Models 430-440


Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	1st R.F.	2.5	175	2.2	75	2.2	5.7
Z-58	1st Det.	2.5	190	4.5	75	4.5	2.3
Z-56	Csc.	2.5	100	0	-	-	3.5
Z-58	1st I.F.	2.5	200	2.2	75	2.2	5.5
Z-56	2nd Det.	2.5	110	10	-	-	.3
Z-56	1st Audio	2.5	170	80	-	-	.8
Z-57	A.V.C.	2.5	-	-85	-	-85	-
Z-57	Q.A.V.C.	2.5	30	13	75	13	-
Z-59	Driver	2.5	190	20	190	190	13
Z-59	Power	2.5	195	-70	195	195	22
Z-59	Power	2.5	195	-70	195	195	22
Z-80	Rect.	5.0	360	-	-	-	65

Line 115 Volts

All Controls Maximum

(All readings, with exception of heaters, taken from socket connections to ground.
Use 1,000 ohm per volt D. C. meter.)

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator pad-
der at 600 K.C.



TUBE LAYOUT MODELS 430-440

PARTS AND PRICES

MODELS 430 440

CHASSIS 2033

Dial and Meter Assembly

11-3	Dial String.....per ft....	\$.10
26-37	Dial Strip.....	.25
34-23	Large Hypoid Gear.....	.30
34-24	Small Hypoid Gear.....	.15
59-16	Volume Control Pointer.....	1.00
59-17	Tone Control Pointer.....	1.00
80-69	Dial String Tension Spring.....	.01
80-84	Volume and Tone Control Pointer Spring.....	.01
80-86	Volume and Tone Control Friction Spring.....	.01
83-272	Volume Control Dial Strip.....	.10
83-273	Tone Control Dial Strip.....	.10
83-277	Pointer Guide Strip.....	.01
100-18	Pilot Lamp.....	.12
122-6	Shadowgraph Meter.....	2.00
S-2255	Tone Control Pointer Cam.....	.25
S-2256	Volume Control Pointer Cam.....	.25
S-2265	Dial Drum Assembly.....	1.00

Condensers

22-112	.1	mfd	300 volt (Filter).....	.25
*22-115	.1	"	200 " (Eight used, see footnote).....	.20
22-117	.5	"	300 " (Filter).....	.30
22-127	.000025		600 " (A.V.C.Grid).....	.35
22-137	.05	"	400 " (Oscillator Plate).....	.15
22-142	.4	"	300 " (Filter-25 cycle only).....	.40
22-147	.0005	"	600 " (2nd Detector Plate).....	.20
22-161			Padder.....	.45
22-166			Three Gang Variable.....	3.50
22-167	8.	mfd	500 volt (Filter).....	1.50
22-169	8.	"	50 " (2nd Detector Cathode, Driver Cathode & 1st Audio Cathode).....	.85
22-170	.1	"	400 " (1st Detector Plate, Tone Control)....	.25
22-175	.002	"	600 " (1st Audio Plate).....	.25
22-177	.2	"	400 " (2nd Detector Plate, 1st Audio Grid, 1st Audio Plate).....	.25

Resistors

63-121	100M	Ohm, 1 Watt (2nd Detector Plate).....	.25
63-169	400	" $\frac{1}{2}$ " (A.V.C. & Q.A.V.C. Plates).....	.25
63-231		Volume Control and Switch Assembly.....	1.25
63-232		Tone Control Assembly.....	.75
63-236	500	Ohm (wide metal) (Power Tube Bias).....	.25
63-237	1500	" (narrow metal) (Driver Tube Bias).....	.25
63-137	250M	" ($\frac{1}{2}$ Watt) (Driver Grid).....	.25
63-239	24M	" 1 Watt (Oscillator & 1st Audio Plate).....	.25
63-240	1900	" $\frac{1}{4}$ " (R.F., 1st Detector & I.F. Grid).....	.20

* See note on next page.

Resistors Cont'd

63-242	2500 Ohm $\frac{1}{2}$ Watt(A.V.C. Cathode).....	\$.25
63-243	18M " 1 " (A.V.C. Cathode).....	.25
63-244	500 " $\frac{1}{4}$ " (Acoustic Filter).....	.20
63-245	1500 " $\frac{1}{4}$ " (1st Detector Cathode).....	.20
63-246	150 " $\frac{1}{4}$ " (R.F. Cathode).....	.20
63-247	8M " $\frac{1}{4}$ " (1st Audio Cathode).....	.20
63-248	50M " 1 " (2nd Detector Plate & Cathode).....	.25
63-250	Sensitivity and Quiet Control.....	.75
63-140	1 megohm $\frac{1}{2}$ Watt(A.V.C. Grid & Cathode).....	.20

Coils

20-30	Antenna Coil.....	.75
20-31	Oscillator Coil.....	.85
20-32	Detector Coil.....	1.00
95-132	1st I.F. Transformer with Grid Lead.....	1.25
95-138	2nd I.F. Transformer without Grid Lead.....	1.25


Miscellaneous

46-49	Large Control Knob.....	.20
46-55	Small Control Knob.....	.15
49-50	Dynamic Speaker (without transformer).....	8.00
49-51	Dynamic Speaker (with transformer).....	10.00
52-33	Speaker Multicord.....	.50
57-341	Escutcheon Plate.....	.50
78-56	Seven Prong Socket type 59.....	.15
78-57	Five Prong Socket type 56.....	.15
78-58	Six Prong Socket type 58.....	.15
78-59	Six Prong Socket type 57.....	.15
78-60	Four Prong Socket type 80.....	.15
93-167	Upper Cushion Washer for Chassis Mounting.....	.01
93-168	Lower Cushion Washer for Chassis Mounting.....	.01
95-135	115 volt 50-60 cycle Power Transformer.....	7.00
95-137	115 volt 25-30 cycle Power Transformer.....	9.00
126-109	Small Tube Shield.....	.10
136-2	2 amp Fuse for 115 volt sets.....	.06
136-4	1 amp Fuse for 230 volt sets.....	.06
MS-174	Power Choke.....	3.25
Ms-195	Large Tube Shield Assembly.....	1.25
MS-200	Audio Transformer.....	3.50

* 22-115 R.F.,1st Detector,I.F. Grid Return, A.V.C. Plate, A.V.C. Cathode,1st Detector Cathode, R.F.Cathode, & Acoustic Filter.

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
December 18, 1933.



INTEROCEAN RADIO CORP.

CHICAGO, ILL.

10-TUBE SUPERHETERODYNE.

MODELS 520 521

CHASSIS 2035

$$\begin{array}{r} 95-144 \\ \hline 95-145 \end{array} \quad \begin{array}{r} 25-30 \\ \hline 50-60 \end{array} \quad \begin{array}{r} \text{CYCLE} \\ \hline \text{CYCLE} \end{array}$$

TO 115 OR 230 VOLT A.C.

VOLTAGE READINGS - MODELS 520 521

Antenna Disconnected


Meter 1000 Ohms Per Volt

Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Plate Current
Z-58	R.F.	2.5	220	0	100	5.2
Z-58	1st Det.	2.5	220	+2	100	3.
Z-56	Osc.	2.5	120	0	0	4.
Z-58	I.F.	2.5	220	0	100	6.
Z-56	2nd Det.	2.5	120	20	0	.75
Z-57	A.V.C.	2.5	-40	-75	-2	0
Z-59	Driver	2.5	220	+25	220	8.2
Z-59	Power	2.5	230	-65	230	25.
Z-59	Power	2.5	230	-65	230	25.
Z-80	Rect.	5.0	400*			62.5*

Line voltage 115


(Reading to Ground)

Volume control maximum



Six and seven prong socket connections

(Bottom of socket)



Tube Position

PARTS AND PRICES
MODELS 520 521
CHASSIS NO. 2035

Dial and Meter Assembly

11-3	Dial Pulley String.....per ft.	\$.25
26-38	Calibrated Dial Strip.....	.15
80-69	Dial Cord Tension Spring.....	.01
80-85	Volume and Tone Control Dial Tension Spring.....	.01
83-274	Volume Control Dial Strip.....	.10
83-275	Tone Control Dial Strip.....	.10
100-18	2.5 Volt Pilot Lamp.....	.12
122-5	Shadowgraph Meter.....	2.00

Condensers

22-112	.1 mfd 300 Volt (Filter).....	.25
22-115	.1 " 200 " (5 used, see footnote).....	.35
22-117	.5 " 300 " (Filter).....	.50
22-137	.05 " 400 " (Oscillator Plate).....	.25
22-142	.4 " 300 " (Filter, 25 Cycle Only).....	.40
22-147	.0005 600 " (2nd Detector Plate).....	.20
22-161	Padder.....	.45
22-165	Three Gang Variable.....	3.50
22-167	8. mfd 500 Volt (Filter).....	1.50
22-169	8. " 50 " (2nd Detector Cathode, Driver Cathode, and 1st Audio Cathode).....	.55
22-170	.1 " 400 " (1st Detector Plate, Audio Coupling and Tone Control).....	.25

Resistors

63-121	100M Ohm 1 Watt (2nd Detector Plate).....	.25
63-135	50M " 1 " (2nd Detector Cathode).....	.25
63-137	250M " $\frac{1}{2}$ " (Oscillator Grid).....	.25
63-140	1 Meg " $\frac{1}{2}$ " (A. V. C. Grid).....	.25
63-169	400 " $\frac{1}{2}$ " (A. V. C. Plate).....	.25
63-231	Volume Control Assembly.....	1.25
63-232	Tone Control Assembly.....	.75
63-234	Sensitivity Control.....	.75
63-236	500 Ohm.....(Power Bias) (Wide Metal).....	.25
63-237	1500 "(Driver Bias) (Narrow Metal).....	.25
63-238	1000 " $\frac{1}{2}$ Watt (1st Detector Cathode).....	.25
63-239	24M " 1 " (Oscillator Plate).....	.25
63-240	1900 " $\frac{1}{2}$ " (R.F., 1st Detector & I.F. Grids).....	.25
63-242	2500 " $\frac{1}{2}$ " (A. V. C. Cathode).....	.25
63-243	18M " 1 " (A. V. C. Cathode).....	.25
63-244	500 " $\frac{1}{2}$ " (Acoustic Filter).....	.25

Coils

20-33	Antenna Coil.....	.75
20-34	Oscillator Coil.....	.85
20-35	Detector Coil.....	1.00
S-2252	2nd Detector Plate Choke and Bracket.....	.50
95-133	1st I. F. Transformer (with Grid Lead).....	1.25
95-139	2nd I. F. Transformer (without Grid Lead).....	1.25

*22-115 R. F., 1st Detector, I. F. Grid Returns, I. F. Cathode, and
Acoustic Filter.

PARTS AND PRICES
MODELS 520 521


CHASSIS NO. 2035

Miscellaneous

46-61	Large Control Knob.....	\$.25
46-62	Small Control Knob.....	.15
49-47	Dynamic Speaker with Transformer.....	7.00
49-48	Dynamic Speaker without Transformer.....	8.25
52-31	Speaker Multicord.....	.35
57-343	Escutcheon Plate.....	.50
78-56	Type 59 Socket.....	.15
78-57	Type 56 Socket.....	.15
78-58	Type 58 Socket.....	.15
78-59	Type 57 Socket.....	.15
78-60	Type 80 Socket.....	.15
93-167	Upper Cushion Washer for Chassis Mounting.....	.01
93-168	Lower Cushion Washer for Chassis Mounting.....	.01
95-144	115 Volt 25-30 Cycle Power Transformer.....	7.25
95-145	115 Volt 50-60 Cycle Power Transformer.....	5.00
95-149	Acoustic Filter Choke.....	.30
106-129	Small Tube Shield.....	.10
136-2	2 amp Fuse.....	.06
MS-200	Push Pull Input Transformer.....	3.50
MS-201	Power Filter Choke.....	3.25

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

INTEROCEAN RADIO CORPORATION



SOCKET VOLTAGES


Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	R.F.	2.4	190	0	95	0	7.
Z-58	1st Det.	2.4	190	2.3	95	2.3	4.
Z-56	Osc.	2.4	100	0	-	-	4.
Z-58	I.F.	2.4	190	0	90	0	2.
Z-57	2nd Det.	2.4	90	-60	70	-60	.2
Z-57	A.V.C.	2.4	-10	-65	-2	-65	0
Z-59	Power	2.4	175	-70	165	-70	25
Z-80	Rect.	5.	*350	-	-	-	*36

Line 115 Volts

All Controls Maximum

(All readings, with exception of heaters, taken from socket connections to ground.
Use 1,000 ohm per volt D. C. meter.)

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator pad-
der at 600 K.C.



TUBE POSITION

PARTS AND PRICES

CHASSIS 2037

Dial and Meter Assembly

11-3	Pulley String.....per ft.....	\$.10
26-38	Dial Drum Strip.....	.10
61-19	Tuning Shaft Pulley (small idler).....	.05
61-22	Tuning Shaft Pulley (large idler).....	.10
80-65	Dial Drum Pulley Tension Spring.....	.01
80-69	Volume and Tone Control Tension Spring.....	.01
100-18	2½ volt Pilot Lamp.....	.12
122-5	Shadow Meter.....(Not Used On Model 516)	2.00
S-2242	Volume Control Dial Assembly.....(" " " " ")	.35
S-2243	Tone Control Dial Assembly.....(" " " " ")	.35

Condensers

22-112	.1 mfd 300 volt(2nd Detector Screen & Power Grid).....	.25
22-113	.5 "(R.F.1st Detector & I.F.Grid Return).....	.30
* 22-115	.1 " 200 vclt(Four used, see below).....	.20
22-117	.5 "(R.F.1st Detector, & I.F.Screen).....	.30
22-137	.05 " 400 volt(Oscillator Plate).....	.15
22-147	.0005 600 volt(2nd Detector Plate & A.V.C.Screen).....	.15
22-161	Padder.....	.45
22-165	Three-Gang Variable.....	3.50
22-170	.1 mfd 400 volt(R.F.& 1st Det. Plate, 2nd Det. Plate)....	.25
22-171	.05 " 600 volt(Tone Control).....	.20
22-172	2. " 450 volt(Filter).....	.80
22-173	8. " 500 volt(Filter).....	1.50

Resistors

63-121	100M ohm, 1 Watt (2nd Detector Plate).....	.25
63-135	25M " ½ " (2nd Detector Cathode).....	.25
63-137	250M " ½ " (Oscillator & Power Grid).....	.25
63-140	1 meg " ½ " (A.V.C.Screen).....	.25
63-160	100M " ½ " (A.V.C.Plate).....	.25
63-169	400M " ½ " (A.V.C.Grid).....	.25
63-232	Manual Tone Control.....	.70
63-234	Manual Sensitivity Control.....	.70
63-235	Manual Volume Control.....	1.25
63-239	24M ohm 1 Watt (Oscillator Plate).....	.25
63-244	500M " ¼ " (1st Detector Cathode).....	.20
63-251	Voltage Divider (six tap).....	.65
63-252	Voltage Divider (five tap).....	.60

Coils and Chokes

20-30	Antenna Coil.....	.75
20-31	Oscillator Coil.....	.85
20-35	Detector Coil.....	1.00
95-133	1st & 2nd I. F. Transformer.....	1.25
S-2252	Plate Choke and Bracket.....	.50

* 22-115	I.F.Cathode, 2d. Det. Grid Ret. 1st & 2d. Det. Cathodes.....	
----------	--	--

PARTS AND PRICES

CHASSIS 2037

Miscellaneous

46-46	Large Knob.....	\$.20
46-62	Small Knob.....	.20
49-45	Dynamic Speaker for Models 500, 516 without transformer....	6.00
49-46	Dynamic Speaker for Models 500, 516 with transformer.....	8.00
49-49	Dynamic Speaker for Model 517.....	7.00
52-32	Speaker Multicord.....	.35
57-343	Escutcheon Plate.....	.50
78-56	59 Seven-Prong Socket.....	.15
78-57	56 Five-Prong Socket.....	.15
78-58	58 Six-Prong Socket.....	.15
78-59	57 Six-Prong Socket.....	.15
78-60	80 Four-Prong Socket.....	.15
95-146	115 volt 25 cycle Power Transformer.....	8.50
95-147	115 volt 60 cycle Power Transformer.....	5.00
136-109	Tube Shield.....	.10
136-2	2 amp Fuse.....	.06

ZENITH RADIO CORPORATION

April 2, 1934





Socket Voltages

770 - 775 - 780 -476-476A


Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	1st R.F.	2.5	175	2.2	75	2.2	5.7
Z-58	1st Det.	2.5	190	4.5	75	4.5	2.3
Z-56	Osc.	2.5	100	0	-	-	3.5
Z-58	1st I.F.	2.5	200	2.2	75	2.2	5.5
Z-56	2nd Det.	2.5	110	10	-	-	.3
Z-56	1st Audio	2.5	170	80	-	-	.8
Z-57	A.V.C.	2.5	-	-85	-	-85	-
Z-57	Q.A.V.C.	2.5	30	13	75	13	-
Z-59	Driver	2.5	190	20	190	190	13
Z-59	Power	2.5	195	-70	195	195	22
Z-59	Power	2.5	195	-70	195	195	22
Z-80	Rect.	5.0	360	-	-	-	65

Line 115 Volts

All Controls Maximum

(All readings, with exception of heaters, taken from socket connections to ground.
Use 1,000 ohm per volt D. C. meter.)

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. and oscillator pad-
der at 600 K.C.



TUBE LAYOUT

PARTS AND PRICES
MODELS 770 775 780 476 476 A
CHASSIS NO. 2032

Dial and Meter Assembly

11-3	Dial String.....	per ft...	\$.10
26-39	Dial Strip.....		.25
59-16	Volume Control Pointer.....		1.00
59-17	Tone Control Pointer.....		1.00
80-69	Dial String Tension Spring.....		.01
80-84	Volume and Tone Control Pointer Spring.....		.01
80-86	Volume and Tone Control Friction Spring.....		.01
80-89	Dial Cord Guide Spring.....		.01
83-272	Volume Control Dial Strip.....		.10
83-273	Tone Control Dial Strip.....		.10
83-277	Pointer Guide Strip.....		.01
100-18	Pilot Lamp.....		.12
122-5	Shadowgraph Meter.....		2.00
S-2254	Dial Drum Assembly.....		1.00
S-2255	Tone Control Pointer Cam.....		.25
S-2256	Volume Control Pointer Cam.....		.25

Condensers

22-112	.1	mfd	300 volt (filter).....	.25
* 22-115	.1	"	200 " (eight used, see footnote).....	.20
22-117	.5	"	300 " (filter).....	.30
22-127	.000025		600 " (A.V.C. Grid).....	.35
22-137	.05	mfd	400 " (oscillator plate).....	.15
22-142	.4	"	300 " (filter - 25 cycle only).....	.40
22-147	.0005	"	600 " (2d detector plate - 2 used).....	.15
22-161			Padder.....	.45
22-166			Three Gang Variable.....	3.50
22-169	8.	mfd	50 volt (2d detector cathode & 1st audio cathode).....	.85
22-170	.1	"	400 " (1st detector plate, tone control).....	.25
22-175	.002	"	600 " (1st audio plate).....	.30
22-177	.2	"	400 " (2d det. plate, 1st audio grid, 1st audio plate).....	.25
22-240	8.	"	500 " (filter).....	1.50
22-241			Dual 8 mfd 500 volt (filter).....	3.00

Resistors

63-121	100M	ohm	1 watt (2d detector plate).....	.25
63-137	250M	"	$\frac{1}{2}$ " (driver grid).....	.25
63-169	400	"	$\frac{1}{2}$ " (A.V.C. & Q.A.V.C. plates).....	.25
63-231			Volume Control and Switch Assembly.....	1.25
63-232			Tone Control Assembly.....	.75
63-236	500	ohm	(wide metal) (power tube bias).....	.25
63-237	1500	"	(narrow metal) (driver tube bias).....	.25
63-239	24M	"	1 watt (oscillator & 1st audio plate).....	.25
63-240	1900	"	$\frac{1}{2}$ " (R. F., 1st detector & I.F. grid).....	.20
* 22-115			R.F., 1st detector, I.F. grid return, A.V.C. plate, A.V.C. cathode, 1st detector cathode, R.F. cathode, & acoustic filter.	

Resistors Cont'd

63-242	2500 ohm $\frac{1}{2}$ watt	(A.V.C. cathode).....	\$.25
63-243	18 M " 1 "	(A.V.C.cathode).....	.25
63-245	1500 " $\frac{1}{4}$ "	(1st detector cathode).....	.20
63-246	150 " $\frac{1}{4}$ "	(R.F.cathode).....	.20
63-247	8M " $\frac{1}{4}$ "	(1st audio cathode).....	.20
63-248	50M " 1 "	(2d detector plate & cathode).....	.25
63-250	Sensitivity and Quiet Control.....		.75
63-259	2600 ohm $\frac{1}{2}$ watt	(acoustic filter).....	.20
63-140	1 meg ohm $\frac{1}{2}$ "	(A.V.C. grid and cathode).....	.20

Coils


20-30	Antenna Coil.....	.75
20-31	Oscillator Coil.....	.85
20-32	Detector Coil.....	1.00
95-132	1st I.F. Transformer with grid lead.....	1.25
95-138	2d I.F. Transformer without grid lead.....	1.25

Miscellaneous

46-49	Large Control Knob.....	.20
46-55	Small Control Knob.....	.15
49-52	Dynamic Speaker (with transformer).....	10.00
49-53	Dynamic Speaker (without transformer).....	6.50
52-33	Speaker Multicord.....	.50
57-341	Escutcheon Plate.....	.50
78-56	Seven prong Socket type 59.....	.15
78-57	Five " " " 56.....	.15
78-58	Six " " " 58.....	.15
78-59	Six " " " 57.....	.15
78-60	Four " " " 80.....	.15
93-167	Upper Cushion Washer for Chassis Mounting.....	.01
93-168	Lower Cushion Washer for Chassis Mounting.....	.01
95-195	115 volt 50-60 cycle Power Transformer.....	7.00
95-196	115 volt 25-30 cycle Power Transformer.....	9.00
126-109	Small Tube Shield.....	.10
136-2	2 amp Fuse for 115 volt sets.....	.06
136-4	1 amp Fuse for 230 volt sets.....	.06
MS-174	Power Choke.....	3.25
MS-195	Large Tube Shield Assembly.....	1.25
MS-200	Audio Transformer.....	3.50

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO
ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PRICE LISTS
FOR LIKE PARTS.

November 21, 1933



Socket Voltages

770B - 775B - 476B


Tube Type	Position	Fil. Volt.	Plate Volt.	Cath. Volt.	Screen Volt.	Supp. Volt.	Plate Current
Z-58	1st R.F.	2.5	200	2.2	82	2.2	4.6
Z-58	1st Det.	2.5	200	5.0	82	5.0	2.4
Z-56	Osc.	2.5	80	6.0	---	---	5.4
Z-58	1st I.F.	2.5	210	2.2	82	2.2	5.2
Z-56	2nd Det.	2.5	0	0	---	---	0
Z-56	A.V.C.	2.5	0	5.0	---	---	0
Z-56	1st A.F.	2.5	120	5.0	---	---	3.0
Z-56	Driver	2.5	200	9.0	---	---	3.0
Z-56	Driver	2.5	200	9.0	---	---	3.0
Z-59	Power	2.5	310	30.0	310	310	24.0
Z-59	Power	2.5	310	30.0	310	310	24.0
Z-80	Rect.	5.0	360	---	---	---	62.5

Line 115 Volts

All Controls Maximum

(All readings, with exception of heaters, taken from socket connections to ground. Use 1,000 ohm per volt D.C. meter.)

BALANCE I.F. frequency at 175 K.C. Condenser gang at 1500 K.C. No padder adjustment required.



TUBE LAYOUT

PARTS AND PRICES
MODELS 770B 775B 476B
CHASSIS NO.2059

Dial and Meter Assembly

11-3	Dial String	per ft..	\$.10
59-16	Volume Control Pointer		1.00
59-17	Tone Control Pointer		1.00
61-22	Dial Vernier Pulley		.05
80-69	Pulley String Tension Spring		.01
80-84	Volume and Tone Control Pointer Spring		.01
80-86	" " " " Friction "		.01
83-272	Tone Control Dial Strip.....		.10
83-273	" " " " "		.10
83-277	Pointer Guide Strip		.01
83-315	Calibrated Dial Strip		.25
100-18	2½ V Pilot Lamp		.12
122-5	Shadowgraph Meter.....		2.00
S-769	Dial Lamp Socket Assembly (Less Lamp).....		.15
S-2255	Tone Control Cam Bushing Assembly		.25
S-2256	Volume " " " "		.25

Condensers

22-147	.0005 mfd	600 volt	(2nd Detector Grid).....	.20
22-162	.0001 "	600 "	(A.V.C.Plate & 2nd Detector Grid).....	.20
22-175	.002 "	600 "	(1st Audio Plate).....	.25
22-177	.2 "	400 "	(Audio Coupling).....	.25
22-190	.1 "	200 "	(1st Detector, I F, Cathodes & Driver Grid.	.20
22-199	.5 "	200 "	(R F Cathode).....	.35
22-213	.05 "	200 "	(R F, 2nd Detector & A.V.C. Grids).....	.20
22-224	.1 "	300 "	(R F & 1st Detector Plates).....	.15
22-225	5. "	25 "	(1st Audio Cathode).....	.65
22-226	Three Gang Variable			3.00
22-228	.5 mfd	300 volt	(R F, 1st Detector & I F Screens).....	.35
22-230	Dual 8 "	500 "	(Filter).....	2.50
22-247	Single 8 mfd	450 "	(").....	1.50

Resistors

63-135	25 M ohm	½ Watt	(1st Audio Plate).....	.25
63-230	15 M "	2½ "	(R F, 1st Detector & I F Screens).....	.35
63-240	1900 "	½ "	(1st Audio Cathode).....	.20
63-271	1 meg "	½ "	(A.V.C. Grid).....	.20
63-278	99 M "	½ "	(2nd Detector	.20
63-295	120 M "	½ "	(R F Grid).....	.20
63-300	990 "	½ "	(1st Detector Cathode).....	.20
63-305	160 "	½ "	(R F Cathode).....	.20
63-306	Volume Control Assembly (500 M ohm).....			1.25
63-314	700 ohm Tapped Metal (Voltage Divider).....			.35
63-315	Tone Control (50 M ohms)			.70
63-316	Sensitivity Control (50 M ohms).....			.65

Coils

20-45	R F Coil Assembly	\$.75
20-46	Detector Oscillator Coil Assembly.....	1.25
95-206	1st I F Transformer.....	1.50
95-207	2nd " " "	1.50


Miscellaneous

44-4	Phono Receptacle Assembly	.15
46-49	Large Wooden Knob (One Used).....	.20
46-55	Small " " (Three ").....	.15
49-66	#1 Dynamic Speaker (With Transformer).....	12.00
49-67	#2 " " (Without ").....	8.00
57-341	Escutcheon Plate	.50
78-84	#56 Tube Socket	.10
78-85	#58 " "	.10
78-86	#59 " "	.10
78-87	#80 " "	.10
85-43	Phono Radio Switch.....	.60
93-167	Chassis Mounting Cushion Washers.....	.01
95-204	117 volt 50-60 Cycle Power Transformer.....	6.00
95-205	All Voltage 25 Cycle " "	8.75
126-109	Tube Shield	.10
126-127	" "	.10
MS-174	Filter Choke Assembly	3.25
MS-200	Audio Transformer.....	3.50
S-2736	Binding Post Assembly.....	.60

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO
ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PARTS LISTS
FOR LIKE PARTS.

November 14, 1935.

R.F.	1ST. DET.	1ST. I.F.	2ND. I.F.	2ND. DET.	POWER
58	58	58	58	59	59
				2A-6	




STANDARD AND SHORT WAVE - 8 TUBE SUPERHETERODYNE

TYPE	POSITION	E_f	E_k	E_g^1	E_g^2	E_g^3	E_p
58	R.F.	2.5	5	0	100	5	255
58	1st Det.	2.5	3.5	0	100	3.5	249
56	Osc.	2.5	0	24	—	—	90
58	1st I.F.	2.5	3	0	104	3	255
58	2nd I.F.	2.5	3	0	104	3	249
2A6	2nd Det.	2.5	8.5	7	—	—	70
59	Pwr.	2.5	18	0	234	18	234
80	Rect.	5.	—	—	—	—	360

E_f - filament E_k - cathode E_g^1 - control grid E_g^2 - screen grid
 E_g^3 - suppressor grid E_p - plate

All voltage readings taken from indicated points to ground with 1000 ohms per volt D.C. meter.

First set I.F. trimmers with an accurate 485 K.C. test oscillator connected to the grid of the 1st detector and ground. Remove oscillator tube and turn I.F. adjusting screws indicated on the diagram below. Insert oscillator tube and connect the test oscillator to the aerial and ground posts. Set the test oscillator and dial to 1500 K.C. and turn the three trimmers on the tuning condenser to resonance, then set the test oscillator and dial to 600 K.C. and adjust the padder condenser for maximum output. Repeat the entire procedure for greater accuracy.



Showing position and circuit function of each. Note location of padder and trimmer adjusting screws.

PARTS AND PRICES
STANDARD AND SHORT WAVE RECEIVER
CHASSIS NOS. 2056 - 2056I

Dial Assembly

11-3	Dial Cord.....	per ft...	\$.10
12-297	Dial Lamp Bracket.....		.05
34-21	Hypoid Tuning Gear.....		.45
73-8	Dial Hub Set Screw.....		.02
80-93	Dial Mask Special Spring.....		.25
100-18	2½ volt Dial Lamp.....		.12
S-2677	Pointer Dial Lamp and Clip Assembly.....		.45
S-2678	Tuning Shaft and Bracket Assembly.....		.80
S-2679	Dial Strip and Support Assembly (for 2056 Chassis).....		1.00
S-2697	Dial Strip and Support Assembly (for 2056I Chassis).....		1.00

Condensers

22-162	.001 mfd 600 volt (band switch and 2A6 diode).....		.20
22-197	Three Gang Variable Condenser.....		3.25
22-203	10. mfd 25 volt(power cathode).....		.75
22-204	8. x 8.mfd 500 volt(filter).....		3.00
22-205	Padder.....		.35
22-206	.01 x .05 mfd 600 volt(tone control).....		.25
22-207	.1 x .1 mfd 200 volt(R.F.cathode & 1st det.cathode).....		.25
22-208	.01 x .0005 mfd 200 volt(2d detector cathode).....		.20
22-209	.0005 x .0005 mfd 400 volt(2d detector plate).....		.20
22-210	.1 x .5 mfd 400 volt(2d I.F. plate and screen).....		.40
22-212	.05 mfd 400 volt(audio coupling).....		.20
22-213	.05 mfd 200 volt(R.F.cathode,I.F.cathode & 2d IF grid		.20
22-223	.01 mfd 300 volt(2d det.grid and oscillator plate)...		.15
22-224	.1 mfd 300 volt(2d detector plate).....		.15
22-242	.00075 mfd 600 volt(band switch).....		.20

Resistors

63-146	2M ohm $\frac{1}{2}$ watt.....(R.F.cathode)		.20
63-180	1M ohm $\frac{1}{2}$ watt.....(1st detector cathode).....		.20
63-240	1900 ohm $\frac{1}{2}$ watt.....(1st detector grid & I.F. plate)....		.20
63-258	490M ohm $\frac{1}{2}$ watt.....(2d detector diode).....		.20
63-265	220 ohm $\frac{1}{2}$ watt.....(R.F.cathode).....		.20
63-278	99M ohm $\frac{1}{2}$ watt.....(A.V.C & 2d detector plate).....		.20
63-280	49M ohm $\frac{1}{2}$ watt.....(oscillator grid).....		.20
63-284	Volume Control and Switch (500M ohm).....		1.25
63-285	Tone Control (50M ohm).....		.75
63-289	29M ohm 1 watt.....(oscillator plate).....		.20
63-308	15,290 ohm Voltage Divider.....		.85
63-309	Sensitivity Control....(5M ohm).....		.75

Coils - Chokes

22-32	Standard Wave Detector Coil Assembly.....		1.00
20-43	Antenna Coil Assembly.....		.75

PARTS AND PRICES
PAGE - 2.

CHASSIS NOS. 2056 - 2056I

Coils - Chokes Cont'd


95-181	1st I. F. Transformer.....	\$1.50
95-182	2nd I. F. Transformer.....	1.50
95-183	3rd I. F. Transformer.....	1.50
S-2252	Plate Choke Assembly.....	.50
S-2672	Short Wave Oscillator Coil.....	1.50
S-2673	Short Wave Detector Coil.....	1.50

Miscellaneous

4-118	Tube Shield Base.....	.05
8-25	Antenna Ground Binding Post Assembly.....	.20
19-4	Grid Cap.....	.03
44-4	Phono Receptacle Base.....	.15
46-59	Large Control Knob.....	.15
46-60	Small Control Knob.....	.15
49-44	Dynamic Speaker.....	8.00
	Cone and Voice Coil for above (#8304-3 hole mounting).....	3.00
	Output Transformer for 49 44 Speaker.....	2.50
57-342	Escutcheon Plate for 2056 Chassis.....	.60
78-56	7 prong tube Socket type 59.....	.15
78-57	6 prong tube Socket type 56.....	.15
78-85	6 prong tube Socket type 58.....	.15
78-87	4 prong tube Socket type 80.....	.15
78-88	6 prong tube Socket type 2A6.....	.15
83-288	Speaker Cable Terminal Strip.....	.15
85-24	Radio Phono Switch.....	.60
85-40	Two Gang Selector Switch.....	1.75
93-167	Rubber Cushion for Chassis Mounting (lower).....	.01
93-168	Rubber Cushion for Chassis Mounting (upper).....	.01
95-168	All Voltage 25-60 Cycle Power Transformer.....	8.00
126-109	Small Tube Shield.....	.10

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO
ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PRICE LISTS
FOR LIKE PARTS.

November 21, 1933




2051 CHASSIS

TYPE	POSITION	E_f	E_k	E_{g1}	E_{g2}	E_{g3}	E_p
58	R.F.	2.5	5	-2	5	75	255
58	1 - Det.	2.5	3.5	0	-16	75	249
56	Osc.	2.5	0	-24	--	--	90
58	1st I.F.	2.5	7.5	+2	7.5	104	249
58	2nd I.F.	2.5	7.5	+2	7.5	104	255
2A6	2nd Det.	2.5	1.5	0	--	--	170
59	Power	2.5	18	0	18	234	234
80	Rect.	5	--	--	--	--	360

E_f - filament E_k - cathode E_{g1} - control grid E_{g2} - suppressor grid
 E_{g3} - screen grid E_p - plate

All voltage readings taken from indicated points to ground with 1000 ohms per volt D.C. meter.

First adjust I.F. trimmers by attaching an accurate 485 K.C. test oscillator to the grid of the 1st detector and ground. Remove oscillator tube and turn I.F. adjusting screws indicated on the diagram below. Insert oscillator tube and connect the test oscillator to the aerial and ground posts. Set the test oscillator and dial to 1500 and turn the three trimmers on the tuning condenser to resonance, then turn the test oscillator and dial to 600 K.C. and set the padder condenser to a position which gives greatest output. Repeat the entire procedure for greater advantage.



Showing position and circuit function of each. Note location of padder and trimmer adjusting screws.

PARTS AND PRICES

CHASSIS NOS. 2051-2051A

STANDARD AND SHORT WAVE RECEIVER

Dial Assembly

11-2	Dial Cord.....	per ft.	\$.10
12-297	Dial Lamp Bracket.....		.05
73-19	Dial Bushing Set Screw.....		.01
S-2677	Dial Socket, Clip and Indicator Assembly (less lamp).....		.45
S-2678	Dial Tuning Shaft and Bracket Assembly.....		.80
S-2679	Dial Strip and Support Assembly.....(plain).....		1.00
S-2680	Dial Mask and Support Assembly.....		1.25
S-2697	Dial Strip and Support Assembly.....(colored).....		1.00

Condensers

22-82	.001 mfd 500 volt (band switch).....		.25
22-113	.05 " 200 " (1st detector cathode).....		.35
22-115	.01 " 400 " (oscillator plate & 2nd detector grid).....		.35
22-147	.0005 " 600 " (band switch).....		.25
22-162	.0001 " 500 " (band switch).....		.20
22-197	Variable Condenser.....		2.75
22-203	10. mfd 25 volt (power cathode).....		.60
22-204	Dual 8 " 500 " (filter).....		2.00
22-205	Oscillator Padder.....		.35
22-206	Dual .01 mfd 600 volt (tone control).....		.25
22-207	Dual .1 " 200 " (R.F., 1st det. I. F. grid & cathode).....		.25
22-208	Dual .01 & .0005 mfd 400 volt (2nd det. grid & cathode).....		.20
22-209	Dual .01 mfd 400 volt (2nd det. plate).....		.20
22-210	Dual .1 & .5 mfd 400 volt (2nd I. F. screens & plate).....		.35
22-211	.1 mfd 300 volt (2nd detector plate).....		.20
22-212	.05 " 400 " (audio coupling).....		.20

Resistors

63-136	50M ohm $\frac{1}{2}$ watt... (2nd detector plate).....		.20
63-146	2M " $\frac{1}{2}$ " ... (R. F. cathode).....		.20
63-180	1M " $\frac{1}{2}$ " ... (1st detector cathode).....		.20
63-240	1900 " $\frac{1}{4}$ " ... (1st detector grid & 2nd I.F. plate).....		.20
63-258	490M " $\frac{1}{4}$ " ... (2nd detector anode).....		.20
63-260	100M " $\frac{1}{4}$ " ... (power grid).....		.20
63-265	220 " $\frac{1}{2}$ " ... (I. F. Cathodes).....		.20
63-271	1 meg " $\frac{1}{4}$ " ... (2nd detector grid).....		.20
63-275	15500 " ... (voltage divider).....		.70
63-278	99M " $\frac{1}{4}$ " ... (R.F. & 1st detector grid return).....		.20
63-280	49M " $\frac{1}{4}$ " ... (oscillator bias).....		.20
63-284	500M " Volume Control.....		1.00
63-285	50M " Tone Control.....		.75
63-286	50M " Sensitivity Control.....		.75
63-288	19M " $\frac{1}{4}$ watt... (R. F. & 1st detector screens).....		.20
63-289	29M " 1 " ... (oscillator plate).....		.20
63-307	40 " 1 " ... (2nd detector cathode) ..metal.....		.15

PARTS AND PRICES
CONT'D

CHASSIS NOS. 2051-2051A

Coils - Chokes

20-32	Standard Wave Detector Coil.....	\$ 1.00
20-43	Antenna Coil.....	.75
95-181	1st I. F. Transformer.....(485 kilocycle).....	1.25
95-182	2nd I. F. Transformer.....(485 kilocycle).....	1.25
95-184	3rd I. F. Transformer.....(485 kilocycle).....	1.25
S-2252	Plate Choke and Bracket Assembly.....	.50
S-2672	Short Wave Oscillator Coil.....	1.25
S-2673	Short Wave Detector Coil.....	1.25

Miscellaneous

4-118	Tube Shield Base.....	.05
8-25	Antenna and Ground Binding Post Assembly.....	.20
44-4	Phono Connector Jack.....	.15
46-59	Large Control Knob.....	.15
46-60	Small Control Knob.....	.15
49-44	Dynamic Speaker.....	8.00
	Cone and Voice Coil for above #8304 (3 hole mounting spider).....	3.00
	Output Transformer for 49-44 Speaker.....	2.00
57-342	Escutcheon Plate.....	.60
78-56	7 prong Socket #59.....	.15
78-57	5 " " #56.....	.15
78-58	6 " " #58.....	.15
78-60	4 " " #80.....	.15
78-61	6 " " #55.....	.15
83-228	Connector Strip for Speaker Cord.....	.15
85-40	Two Gang Selector Switch.....	1.50
93-167	Rubber Cushion for Chassis Mounting (lower).....	.01
93-168	Rubber Cushion for Chassis Mounting (upper).....	.01
95-168	All Voltage, All Cycle Power Transformer.....	6.00
100-18	2½ volt Dial Lamp.....	.12
126-109	Tube Shield.....	.10

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT
NOTICE.

Socket Voltages


2052 Chassis

TYPE	POSITION	E_f	E_k	E_{g1}	E_{g2}	E_{g3}	E_p
57	1st Det.	2.5	$\neq 5$	0	0	95	220
56	Osc.	2.5	0	-22	—	—	120
58	I.F.	2.5	$\neq 1$	0	$\neq 1$	95	220
2A6	2nd Det.	2.5	$\neq 1.5$	0	—	—	150
59	PWR	2.5	0	-11	0	220	210
80	Rect.	5.	—	—	—	—	280

E_f - filament E_k - cathode E_{g1} - control grid E_{g2} - suppressor grid
 E_{g3} - screen grid P - plate

All measurements taken from points indicated to ground with 1000 ohm per volt D.C. meter. (except filaments)

Balance I.F. frequency at 485 K.C., condenser gang at 1500 K.C. and oscillator padder at 600 K.C.



Tube Position

MODELS 705 706 707 711 750 712
CHASSIS NOS. 2052 A B & C

MODELS 705 706 707 CHASSIS 2052A

Condensers

22-190	Dual .1 mfd 200 volt (1st det.suppressor & power grid).....	\$.15
22-205	Padder.....	.35
22-217	Dual 8 mfd. 500 volt (filters).....	3.00
22-218	Two Gang Variable.....	2.00
** 22-220	Dual .05 mfd & .05 mfd 200 volt(1st det.& I.F.cathodes)....	.20
22-221	Dual .02 mfd & .001 mfd 300 " (2nd det.plate).....	.20
22-223	.01 mfd 300 volt.....(oscillator & power plates).	.15
22-224	.1 mfd 300 volt.....(1st det.& I.F.screens).....	.15
22-225	5. mfd 25 volt.....(2nd det.cathode).....	.65
22-222	Dual .02 Mfd. x .001 Mfd.	.25

Resistors

63-258	490M ohm $\frac{1}{4}$ watt.....(power grid).....	.20
63-290	260M ohm $\frac{1}{4}$ watt.....(oscillator grid).....	.20
63-291	29M ohm $\frac{1}{4}$ watt.....(oscillator plate).....	.20
63-292	5400 ohm $\frac{1}{4}$ watt.....(1st & 2d det.cathode).	.20
63-293	990M ohm $\frac{1}{4}$ watt.....(1st det.suppressor)...	.20
63-294	100 ohm $\frac{1}{4}$ watt.....(I.F.cathode).....	.20
63-295	120M ohm $\frac{1}{4}$ watt.....(2nd det.grid).....	.20
63-296	220M ohm $\frac{1}{4}$ watt.....(2nd det.plate).....	.20
63-297	30M ohm $\frac{1}{2}$ watt.....(voltage divider).....	.40
63-298	250 ohm $1\frac{1}{2}$ watt.....(voltage divider).....	.25
63-299	Volume Control and Switch.....(Also 63-312).....	1.10

Coils

20-44	R.F. and Oscillator Assembly.....	.85
95-187	2nd I.F.Transformer(leads at top).....	1.35
95-188	1st I.F.Transformer(leads at bottom).....	1.35

Miscellaneous

4-133	Tube Shield Base.....	.05
12-302	Speaker Mounting Bracket.....	.01
26-42	Dial and Friction Gear Assembly.....	.50
46-67	Control Knob.....	.15
*49-58	6" Dynamic Speaker.....(Also 49-70).....	6.00
	Cone and Voice Coil for Above.....	2.50
	Output Transformer for 49-58.....	1.50
57-403	Zenith Name Plate.....	.10
57-404	Escutcheon Plate for Dial.....	.10
57-406	Chassis Base Plate.....	.50
78-77	59 tube socket.....	.10
78-78	2A6 " "	.10
79-79	58 " "	.10
78-80	57 " "	.10
** Replaced by two #22-250 .05 Mfd. condensers		.15

Miscellaneous cont'd

78-81	56 tube socket	\$.10
78-82	80 tube socket	.10
78-76	Dial Lamp Socket and Clip.....	.10
91-138	30' Antenna Wire.....	.30
95-185	117 volt 50-60 cycle Power Transformer.....	3.00
95-189	All Voltage 25-60 cycle Power Transformer	6.00
100-18	2½ volt Dial Lamp	.12
126-127	Tube Shield.....	.10
S-458	8' Cord and Plug Assembly.....	.30

Model 711 Chassis No. 2052B

Same as Chassis No. 2052A with additional parts as follows:

22-224	.1 mfd 300 volt Condenser.....	.15
57-405	Shadowmeter Escutcheon Plate.....	.10
100-18	Shadowmeter Pilot Lamp	.12
122-5	Shadowmeter.....	2.00

Model 750 Chassis No. 2052C

Same as Chassis No. 2052B, excepting speaker 49-58 (6") is deducted and speaker 49-59 (8") is added.

49-59	8" Dynamic Speaker.....	7.50
	Cone and Voice Coil for Above.....	3.00
	Output Transformer for 49-59.....	2.00

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO
ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PRICE LISTS
FOR LIKE PARTS.

* NOTE: When Ordering Speaker Parts Specify Whether They Are Required For
Jensen or Utah Speakers.

November 21, 1933




SOCKET VOLTAGES

MODELS 715 - 755

TYPE	POSITION	FIL.	CATH.	GRID	SCREEN	SUPP.	PLATE
58	R.F.	2.5	10	0	83	10	258
58	1st Det.	2.5	12	5	83	12	260
56	Osc.	2.5	8	0	--	--	80
58	I.F.	2.5	11	2	83	11	258
55	2nd Det.	2.5	8	0	--	--	126
59	Power	2.5	21	0	255	21	249
59	Power	2.5	21	0	255	21	249
80	Rect.	5.	--	-	--	--	372

Measurements taken from points indicated to ground. Line voltage - 117.
All controls in maximum position and with Antenna and Ground disconnected.

Adjust I.F. frequency at 175 K.C. and condenser gang at 1500 K.C. No
padder adjustment necessary.



TUBE POSITION

PARTS AND PRICES
MODELS 755 756 474
CHASSIS NO. 2053 B

Condensers

22-82	.001 mfd. 600 volt.....	\$.25
22-168	Dual 8 mfd. 500 volt.....	3.00
22-169	8 mfd. 50 volt.....	.55
22-199	.5 mfd. 200 volt.....	.25
22-213	.05 mfd. 200 volt.....	.30
22-221	Dual .0005 mfd and .02 mfd. 400 volt.....	.20
22-226	Three Gang Variable.....	2.50
22-227	Dual .1 mfd. 300 volt.....	.25
22-228	.5 mfd. 300 volt.....	.30
22-229	.005 mfd. 600 volt.....	.10

Resistors

63-232	50M ohm Tone Control.....	.75
63-239	24M ohm 1 watt carbon.....	.25
63-255	1500 ohm Sensitivity Control.....	.60
63-258	490 ohm $\frac{1}{4}$ watt carbon.....	.20
63-295	120M ohm $\frac{1}{4}$ watt carbon.....	.20
63-300	990 ohm $\frac{1}{4}$ watt carbon.....	.20
63-301	15M ohm $2\frac{1}{4}$ watt metal.....	.25
63-302	1500 and 375 ohm 5 watt metal.....	.25
63-303	700 ohm $\frac{1}{4}$ watt carbon.....	.20
63-306	500M ohm Volume Control and Switch Assembly.....	1.25

Coils

20-45	R. F. Coil Assembly.....	.50
20-46	Detector and Oscillator Coil Assembly.....	.80
95-191	1st I. F. Coil Assembly.....	1.10
95-192	2nd I. F. Coil Assembly.....	1.10

Miscellaneous

4-134	Tube Shield Base.....	.05
11-3	Pulley String.....per ft	.10
46-49	Large Knob.....	.20
46-55	Small Knob.....	.15
49-61	8" Dynamic Speaker.....	6.50
	Output Transformer for 49-61 Speaker.....	2.00
	Cone and Voice Coil for 49-61 Speaker.....	2.00
	Field Coil for 49-61 Speaker.....	2.00
57-408	Escutcheon Plate.....	.30
78-83	55 Tube Socket.....	.10
78-84	56 Tube Socket.....	.10
78-85	58 Tube Socket.....	.10
78-86	59 Tube Socket.....	.10
78-87	80 Tube Socket.....	.10
80-69	Dial String Tension Spring.....	.01
83-315	Celluloid Dial Strip.....	.20

PARTS AND PRICES

Page No. 2

MODELS 755 756 474


CHASSIS NO. 2053 B

Miscellaneous Con'd

95-190	117 volt 50-60 cycle Power Transformer.....	\$ 4.00
95-193	Audio Transformer.....	1.10
95-194	117, 125, 140, 250 volt, 25 cycle Power Transformer...	6.00
100-18	2½ volt Dial Lamp.....	.12
122-7	Shadowgraph Meter.....	1.75
126-127	Tube Shield.....	.10
S-769	Dial Lamp Socket Assembly (less lamp).....	.15
S-2710	Dial Drum Assembly.....	.80

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE
WITHOUT NOTICE.

ZENITH RADIO CORPORATION
JUNE 10TH, 1933.



I.F. FREQUENCY 175 K.C.

MODEL 760

2054 CHASSIS

ZENITH RADIO CORP.
CHICAGO, ILL. U.S.A.
R. 60 5-15-32




SOCKET VOLTAGES

MODEL 760

TYPE	POSITION	FIL.	CATH.	GRID	SCREEN	SUPP.	PLATE
58	R.F.	2.5	3	0	100	3	260
58	1st Det.	2.5	4	5	100	4	275
56	Osc.	2.5	7	0	-	-	100
58	I.F.	2.5	3	2	100	3	255
56	2nd Det.	2.5	0	0	-	-	0
56	1st Audio	2.5	7	0	-	-	150
59	Power	2.5	20	0	270	20	260
59	Power	2.5	20	0	270	20	260
80	Rect.	5.	-	-	-	-	364

Measurements taken from points indicated to ground. Line voltage - 117.
All controls in maximum position and with Antenna and Ground disconnected.

Adjust I.F. frequency at 175 K.C. and condenser gang at 1500 K.C. No
padder adjustment necessary.



TUBE POSITION

PARTS AND PRICES
MODELS 475 760
CHASSIS NO. 2054 B

Dial and Meter Assembly

11-3	Pulley String.....per ft.	\$.10
59-16	Volume Control Pointer Arm.....	1.00
59-17	Tone Control Pointer Arm.....	1.00
80-69	Dial Cable Tension Spring.....	.01
80-86	Tension Springs for Volume and Tone Control Arms.....	.01
83-272	Volume Control Dial Strip.....	.10
83-273	Tone Control Dial Strip.....	.10
83-277	Pointer Guide Strips.....	.01
83-315	Dial Strip for Dial Drum.....	.20
100-18	2½ volt Pilot Lamp.....	.12
122-7	Shadowgraph Meter.....	1.75
S-2710	Complete Dial Drum Assembly.....	1.00

Condensers

22-82	.001 mfd 500 volt.....(audio plate).....	.20
* 22-168	Dual 8 mfd 500 volt.....(filter).....	3.00
22-169	8. mfd 50 volt.....(audio cathode).....	.55
22-196	.01 mfd 600 volt.....(tone control).....	.15
22-199	.5 mfd 200 volt.....(R.F. cathode).....	.25
22-213	.05 mfd 200 volt.....(R.F. & I.F. grid).....	.30
22-221	.0005 & .02 mfd 400 volt..(2nd detector grid).....	.20
22-226	3 Gang Variable.....	2.50
22-228	.5 mfd 500 volt.....(1st audio plate).....	.30
22-229	.005 mfd 600 volt.....(power plates).....	.10

Resistors

63-232	500M ohm Tone Control.....	.75
63-239	24M ohm 1 watt.....(audio plate).....	.25
63-258	490M ohm ¼ watt.....(A.V.C. bias).....	.20
63-265	220 ohm ¼ watt.....(I. F. cathode).....	.20
63-295	120M ohm ¼ watt.....(R.F. & 2nd detector grids)	.20
63-300	990M ohm ¼ watt.....(oscillator bias).....	.20
63-301	15M ohm 2½ watt.....(voltage divider).....	.25
63-302	1875 ohm (tapped at 375 ohm)(voltage divider).....	.25
63-304	800 ohm Sensitivity Control.....	.60
63-305	160 ohm ¼ watt.....(R. F. bias).....	.20
63-306	500M ohm Volume Control and Switch Assembly.....	1.25

Coils

20-45	R. F. Coil Assembly.....	.50
20-46	Detector Oscillator Coil Assembly.....	.80
95-191	1st I. F. Coil Assembly.....	1.10
95-192	2nd I. F. Coil Assembly.....	1.10

- * Part No. 22-168 condenser is in cardboard container. Later production sets incorporated condenser No. 22-230 which is in metal can. 2.00

PARTS AND PRICES

Page No. 2

MODELS 475 760

CHASSIS 2054B

Miscellaneous

46-49	Large Control Knob.....	\$.20
46-55	Small Control Knob.....	.15
49-62	Dynamic Speaker with Transformer.....	7.00
49-63	Dynamic Speaker without Transformer.....	5.00
	Output Transformer for 49-62 Speaker.....	2.00
	Cone and Voice Coil Assemblies for 49-62 and 49-63.....	2.00
	Field Coils for 49-62 and 49-63 Speakers.....	2.00
57-341	Escutcheon Plate.....	.35
78-84	Type 56 Tube Socket.....	.10
78-85	Type 58 Tube Socket.....	.10
78-86	Type 59 Tube Socket.....	.10
78-87	Type 80 Tube Socket.....	.10
95-190	117 volt, 50-60 cycle Power Transformer.....	4.00
95-193	P. P. Audio Transformer.....	1.10
95-194	117, 125, 140, 250 volt, 25 cycle Power Transformer....	6.00
126-127	Tube Shield.....	.10
136-2	2 amp Fuse.....	.06

ALL PRICES ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE
WITHOUT NOTICE.

ZENITH RADIO CORPORATION
JULY 5TH, 1933.

SERVICE MANUAL MODEL 701

OPERATING INSTRUCTIONS

1. Carefully remove antenna wire from its compartment and stretch out full length. A properly erected well insulated outdoor antenna about 75 feet in length, including lead-in is recommended for permanent installations. A GROUND IS NOT REQUIRED.
2. After making certain that power supply is 110 volts, insert plug in receptacle.
3. Rotating VOLUME control clockwise (right) from off position turns power switch on, continued rotation increases volume. IF SET DOES NOT OPERATE IN ONE MINUTE ON DIRECT CURRENT REVERSE PLUG IN RECEPTACLE.
4. Advance volume control three-quarter turn, then select the desired station. Tune this station to the loudest point on the scale, then raise or lower volume with VOLUME control. Never regulate volume by detuning station selector, always adjust VOLUME control.

FIVE TUBES, 2-6D6, 1-75, 1-43, 1-25Z5.

SERVICE SUGGESTIONS


NOTE—CONNECTING CORD OF SET GETS WARM IN NORMAL OPERATION. DO NOT BECOME ALARMED.

Make sure that all tubes are pushed firmly in their proper sockets and that the clips are securely fastened to the caps on the tops of the tubes.

That the aerial is stretched out and that the connections to an outdoor antenna (if used) are good.

If necessary to change tubes or service chassis, UNDER NO CIRCUMSTANCES REMOVE BACK OR CHASSIS WITHOUT FIRST REMOVING PLUG FROM LIGHT SOCKET.

To remove chassis from cabinet, pull off knobs from front, remove back (held with screws to case). Remove four mounting screws, then chassis can be slipped out of case.




Schematic circuit diagram Model 701 AC-DC Superheterodyne, with automatic volume control

Should it be necessary, at any time, to rebalance this set the procedure is as follows: Attach a 456 kilocycle oscillator to the grid of the 6D6 tube in back of the variable condenser and adjust the trimming condensers of the I. F. transformers to maximum deflection on an output meter connected across the primary of the speaker input transformer. While adjusting these trimmers, the variable condenser should be at the maximum capacity position—at the extreme right of its rotation.

Next disconnect the antenna wire and connect an oscillator in series with a 75 mmf. condenser to the antenna coil. Rotate the condenser plates to the minimum capacity position—extreme left turn, and adjust the trimmer condenser of the rear section of the variable condenser to resonance with an oscillator set at 1725 kilocycles, then adjust the condenser of the front section of the variable condenser to resonance. Align at 1400—1200—1000—800—600—530 kilocycles, bend slotted plates of variable condenser if necessary.

PARTS LIST

Part No.	Description	List Price
A 103	Same	
C 145	.1—300 Volt Condenser.....	\$0.25 ea.
C 155	.0005 Mica Condenser.....	.20 ea.
C 521	Two Gang Condenser.....	2.50 ea.
C 522	.01—400 Volt Condenser.....	.25 ea.
C 523	600 Ohm Choke Coil.....	1.25 ea.
C 524A	Antenna Coil	.80 ea.
C 524B	Oscillator Coil	.70 ea.
C 524C	I. F. Transformer.....	1.25 ea.
C 524D	I. F. Transformer.....	1.25 ea.
C 525	5-25-10 Electrolytic Condenser.....	2.00 ea.
C 526	By-Pass Condenser Block.....	1.50 ea.
C 527	Special Cord and Plug.....	1.25 ea.
K 214	Knobs	.40 ea.
R 268	2480 Ohm Resistor.....	.50 ea.
R 270	250 Ohm—Wire Wound Resistor.....	.25 ea.
V 601	Volume Control	1.35 ea.
W427	Antenna Wire	.30 ea.
	All carbon resistors.....	.20 ea.
	All sockets	.20 ea.
	Dynamic speakers	5.00 ea.
	Cabinets	2.50 ea.
	Carrying cases	2.00 ea.
	Adapters for 220 volt operation.....	2.25 ea.



ZENITH RADIO CORPORATION


3620 Iron Street

Chicago, Illinois

slotted plates of variable condenser if necessary. To adjust long wave, 1000-2000 meters, with switch lever down, set variable at maximum capacity, extreme right turn, and tune generator to maximum output, then peak long wave padder (hexagon nut of L. W. Padder), at the same time tuning oscillator until maximum output is attained. Attach oscillator leads to grid of 6A7 ground, set variable condenser at minimum capacity, extreme left turn, and adjust oscillator to resonance with set. Remove oscillator lead from grid of 6A7 and attach to antenna lead, then adjust long wave R.F. trimmer to maximum output (set screw adjustment of L. W. Padder). Do not disturb either oscillator or variable condenser while making this adjustment.

PARTS LIST

Part No.	Description	List Price
C 145	.1—300 Volt Condenser.....	\$0.25 ea.
C 155	.0005 Mica Condenser.....	.20 ea.
C 521	Two Gang Condenser.....	2.50 ea.
C 522	.01—400 Volt Condenser.....	.25 ea.
C 523	600 Ohm Choke Coil.....	1.25 ea.
C 538	5-25-5 Electrolytic Condenser.....	2.00 ea.
C 548	Padding Condenser.....	.75 ea.
C 525B	5-25-10 Electrolytic Condenser.....	2.00 ea.
C 524C	I. F. Transformer.....	1.25 ea.
C 524D	I. F. Transformer.....	1.25 ea.
C 524E	Combination Antenna Coil.....	1.25 ea.
C 524F	Combination Oscillator Coil.....	1.10 ea.
C 527	Special Cord and Plug.....	1.25 ea.
C 531	Dual .05 Condenser.....	.30 ea.
C 534	Dual .1-.025 Condenser.....	.30 ea.
K 214	Knobs.....	.40 ea.
R 270	250 Ohm—Wire Wound Resistor.....	.25 ea.
R 278	7700 Ohm Resistor.....	.50 ea.
S 336	Wave Change Switch.....	.60 ea.
V 601	Volume Control.....	1.35 ea.
	All carbon resistors.....	.20 ea.
	All sockets.....	.20 ea.
	Dynamic speakers.....	5.00 ea.
	Cabinets.....	2.50 ea.
	Carrying cases.....	2.00 ea.
	Adapters for 220 volt operation.....	2.25 ea.



ZENITH RADIO CORPORATION

3620 Iron Street

Chicago, Illinois

SERVICE BULLETIN



Automobile Receiver

Model 460

NOV., 1933

1. Installation

There are certain problems, in connection with every Auto Radio Installation, which are not common to the average home receiver. They may be classed as follows:

1. Antenna
2. Installation
3. Motor Noise Suppression

In order to insure complete satisfaction to the car owner, each subject must be given very careful consideration. The information contained in this bulletin should serve to simplify the work and at the same time stimulate confidence in the service man. A thorough study of the following pages is essential.

Antenna

Automobile manufacturers are realizing the general trend by the public in the use of a radio receiver in the car. As a consequence, practically all late models are equipped with a roof antenna which is suitable for broadcast reception. If there is any question as to whether the particular car in which the installation will be made is equipped with an antenna, the local sales agency will furnish this information. Where it is already incorporated, the lead-in will be found most generally under the instrument panel, beneath the right hand windshield post, and if not shielded, this should be done, at least between the point where it comes through the post over to where it attaches to the antenna cable on the control head. This shielding should be grounded to the instrument panel. Factory built antennas should first be checked with a continuity meter, in order to make certain that they are not grounded. It is possible that when the aerial was installed at the factory, it might have shorted to the body at some point inside the roof.

If the car is not equipped with an aerial, there are several means whereby suitable pickup may be provided. Among these are the plate antenna, the running board type, or the roof antenna. After repeated tests we have found that the last mentioned gives best results and is less likely to pick up motor interference.

A piece of copper screening approximately two and one-half feet square, placed between the headlining and the top covering, is very satisfactory. This is installed by first removing the upholstered moulding around the headlining and then dropping the headlining about half way from the front in sedans, or completely in a coupe. If it is found that chicken wire is used in the top construction, a piece should be cut out large enough to allow at least six inches spacing around the copper mesh, or if preferred, the chicken wire can simply be left in place and segregated around a portion two to two and a half feet square. A cut out around the edges of about six inches is satisfactory. The copper screen, or remaining portion of the chicken wire, should be securely tacked to the ribs and the lead-in wire soldered to the left front corner. The headlining should then be very carefully tacked back into position and the lead-in brought down the left hand corner post and behind the instrument panel.

In roadsters, or convertible models, where the antenna efficiency will become poor if installed in the top, the plate or running board system is advisable. It is important, however, that the lead-in be shielded and grounded in several places from the plate to the receiver, inasmuch as they are more apt to pick up motor noises.

Never bring the lead-in through the motor compartment, since it will always result in motor noise which it will be impossible to eliminate. Also, when making the installation, be sure that the battery lead from the receiver does not go out to the motor compartment and that it is attached directly to the battery and not at the ammeter or starter.

Receiver

Although installation of the receiver itself is covered in the instruction manual, there are several suggestions which will prove helpful to the serviceman.

In some cases it might be found that the control head cannot be mounted parallel to the steering column because of insufficient space between the wheel and the instrument panel and, if mounted horizontally, it blocks essential instruments from the driver's vision. Where this is true it may be placed in the glove compartment. This is done by removing the glove compartment from the instrument panel and screwing the control head direct to the bottom without using the mounting clamps. If the control head does not go back far enough to allow room for the door to close, the rear end of the box can be cut off and the head allowed to protrude from the rear.

The best place for the speaker chassis unit is, of course, on the steering column, beneath the instrument panel. However, if space is not available or some of the control rods are in the way, it should be fastened to the bulkhead. The speaker chassis may be set either in the normal position or upside down, without interfering with its performance. The three carriage bolts and carriage bolt brackets, in connection with the wooden mounting blocks, give a very satisfactory and firm method of support.

Inasmuch as the battery cable has a grounded shield, it should not be placed behind the instrument panel in such a way that it might accidentally touch the ammeter or any other hot battery terminal so as to cause a short circuit. The cable should be placed as close as possible to the dashboard and taped to some solid member, to hold it securely.

The shielded lead on the control head cable must be attached to the instrument panel, or other grounded part of the car. This may be done underneath, so as to keep it out of sight.

2. Motor Noise Suppression

Every automobile generates high frequency electrical interference by virtue of the ignition coil, distributor and spark plugs. In order to receive any degree of satisfaction from an automobile receiver, the interference so generated must be eliminated by means of suppression. Each car, however, presents an individual problem where the serviceman must use his own ingenuity in addition to certain definite instructions. We offer the following as a result of actual experience, and believe that if followed carefully, motor noise in any car can be overcome.

The first essential procedure is to apply the standard suppression parts furnished in each kit. This consists of placing a resistor on each spark plug and on the center high tension lead at the distributor. Since all high tension wires act as small antennas or radiators, they should be kept down as close to the motor as possible. Do not attach the suppressors in an upright position. Always try to keep them horizontal, or as near to the block as conditions will permit. Next in importance is the generator condenser. This filters a high pitched whining noise, which would otherwise be heard without it, as the motor is accelerated. Next in order is the ignition coil condenser. It is very essential that it be placed on the proper low tension coil connection. This can be determined by testing each side of the primary with a screw driver held in the hand by the metal part. One will give off a slight high frequency spark, while the other side will appear to be cold. This test is made with the motor running. The condenser is attached from the cold (battery side) side to ground. Placing the condenser on the wrong side of the coil will seriously affect the car's operation and tend to make the motor noise more pronounced. **THIS IS IMPORTANT.** Reversing the primary leads will sometimes reduce motor noise, especially if they were incorrectly wired at the factory.

After standard suppression has been applied and the hood clamped down to prevent radiation, the receiver should be turned on and the dial tuned off a station, with the volume control at maximum. If the motor noise is still objectionable, the next step is to determine whether the interference is originating through chassis pickup or from the antenna.

To check for chassis pickup, the antenna should be disconnected and the leads on the control head cable shorted. The motor is then started and if any noise is heard, it is originating through the battery circuit and will require isolation of certain of the car wires. Chassis pickup can be reduced effectively also by shortening the gap in the distributor head. To do this, solder is applied to the end of the rotor arm, after which it is placed back in position and the distributor cap reset. With the crank, the motor should be turned over slowly, in order to clean the excess solder. As an additional precaution, the breaker points should be thoroughly cleaned, or new points installed if they are burned or badly worn.

Where the low tension leads are all bunched together with the high tension wires in a sleeve under the instrument panel, they should be separated and the high tension leads brought out through another hole. Sometimes a .1 mfd. condenser on the distributor low tension side of the coil is also effective.

Cars with floating power must have the motor bonded to the bulkhead and again to the frame at the radiator, to provide a direct path for the high tension interference developed in the ignition system. $\frac{5}{8}$ " copper braid will be found satisfactory.

If the coil is mounted inside the driving compartment, it might be necessary to shield the high tension lead. This cannot be done effectively, however, if the wire has rubber insulation. Where the car is so equipped, this wire should be removed and Packard cable of the same length substituted. This allows shielding without corona effects and consequent interruption of car performance. When applying the shield over this wire be sure that it terminates at least an inch and a half from both the coil and the distributor; otherwise, it might have a tendency to break down. The shield must be grounded to the instrument panel, dashboard or motor block. The other high tension leads to the spark plugs are not to be shielded. So far there has never been a case where this procedure was required. It would therefore only involve considerable work to no advantage.

Be sure to keep the battery cable from the receiver out of the motor compartment. It should run under the floor mat, on the driver side, and attach directly to the battery. Running this cable through the motor side has been found to be the cause of ignition interference.

This procedure should eliminate all possibility of chassis pickup, after which the antenna lead can be connected to the control head cable. Any motor noise picked up from this point on is being absorbed entirely by the antenna. The first precaution, if it exists, is to check the dome light wiring. It is known that these leads pick up motor noise and carry it to the aerial from around the dash compartment. Removing the dome light wire from the ammeter, or connecting a low resistance RF choke at this point will overcome the difficulty.

If the car has a wooden bulkhead, it will be found necessary to line it on the motor side with thin sheet lead, or other conductor. This will prevent interference from entering the inside of the car and from there being picked up by the antenna. Occasionally it will be found that the copper tubing which runs from the motor to the windshield wiper carries the interference to the antenna. This can be eliminated by bonding the windshield pipe at the dashboard with a short piece of copper braid. The same procedure might also be necessary with respect to the oil line, brake rod, spark and gas controls, or other metal conductors which pick up high frequency interference from the motor compartment.

No absolute rule for complete motor interference elimination can be specified inasmuch as sometimes two cars of the same make are likely to require bonding or shielding at different points. However, the foregoing suggestions, in addition to some ingenuity on the part of the radio man, will in every case prove effective.

3. Service Circuit

Model 460 employs a seven tube Superheterodyn automatic volume control circuit with the following tubes:

1—6C6	Combination 1st detector and oscillator
2—6D6	1st and 2nd I.F. amplifiers
1—85	A.V.C. 2nd detector
2—89	Push pull power output
1—6Z4	Rectifier

The table on page 4 specifies the socket voltage and figure 1, page 5, the relative tube position.

The antenna circuit is inductively coupled to the type 6C6 through coil 20-40. This tube acts as the first detector and, through plate feed-back and inductance 2039, as an oscillator. An I.F. frequency of 485 K.C. is developed and transferred from the control head to the speaker chassis through the connecting cable. Part of the first I.F. transformer 95-160 is in the head, while the secondary 95-159 is contained in the chassis. A 6D6 in the first I.F. stage feeds another 6D6 in the second I.F. stage through another I.F. transformer. The third I.F. transformer, 95-162, couples to a half wave dual diode triode type 85. A.V.C. action and 2nd detection takes place at this point and the audio signal is transformer coupled to a pair of type 89's in the push-pull output stage.

The power supply is of the built-in vibrator type, using a tube 6Z4, step-up transformer and buzzer in a full wave rectifier circuit. Choke 95-164 and condensers 22-183 are the essential filter components. The volume control, although in the control head, is wired in the cathode circuit of the 2nd detector.

The following is a list of performance factors which information may be of assistance where accurate measurements are essential.

Intermediate Frequency	485 K.C.
Sensitivity in Microvolts	1.5
Power in Milliwatts	2200
Power Consumption in Watts	36

Test Procedure

In the event that trouble develops it is advisable to first inspect the battery and antenna. A battery with a defective cell or in a run down condition will supply insufficient voltage to the receiver with a serious drop in efficiency. Check it for voltage and specific gravity.

Next inspect the antenna. The metal windshield moulding may have cut the insulation and shorted the wire. A continuity test will quickly determine its condition. In the case of under car systems inspect the insulators closely, since corrosion or road dirt is likely to create high leakage to the car frame.

If the receiver is entirely inoperative the fuse should be examined. It is contained in an insulated holder at the "Hot" battery terminal. Be sure to replace the spaghetti insulator over the fuse if necessary to change it. The next important step is to very carefully check the tubes both in the control head and speaker chassis. This has been found to be the most common cause of service in an auto receiver. The extreme vibration to which the tubes are subjected will occasionally develop a short in the elements in spite of the precautions that have been taken in their construction. A loud hum and lack of sensitivity can usually be attributed to a defective 6C6. Microphonic howl can be traced to the 89's. Replacement is recommended for such complaints, since the average tube checker will not show up this condition. An intermittent cutting out accompanied with rasping and other noises will usually be found in either of the 6D6's. The chassis may be taken out for inspection by simply removing the cable plug and three round-head hexagon nuts on the front of the case.

If further inspection indicates that the difficulty lies in the parts or wiring, a voltage reading at all sockets should be taken. They should coincide closely with the values given in the table. It is also advisable to check for continuity in the I.F. transformers both at the control head and in the speaker chassis.

Where the set lacks volume or sensitivity check the power output tubes and the overall alignment of the I.F., R.F. and padder adjustments as specified under "Alignment." Always make certain that the volume and sensitivity controls are in maximum position when making a service inspection.

TUBE OPERATING VOLTAGES

Position	Tube	Ef	Ek	Eg ¹	Eg ²	Eg ³	Ep
1st Detector	6C6	4.8	6.5	0	6.5	120	150
1st I.F. Amp.	6D6	5.3	10.5	*	10.5	103.5	165
2nd I.F. Amp.	6D6	5.3	10.5	*	10.5	103.5	165
2nd Detector	85	5.3	8.	0	--	—	156
P. P. Audio	89	5.3	17.	0	17	165	165
	89	5.3	17	0	17	165	165

f—Filament. k—Cathode. g¹—Control grid. g²—Suppressor grid. g³—Screen grid. p—Plate.

*Depends on applied signal strength. All voltages measured from indicated points to ground.

Alignment

Every Zenith Automobile receiver is balanced on an accurate, temperature controlled crystal oscillator before leaving the factory and unless a part is changed or the calibration has shifted, the adjustments should not be tampered with. Where it is absolutely necessary, however, a good test oscillator capable of delivering a modulated signal at 1500, 600 and 485 K.C. will be required.

To balance the I.F. circuit remove the cap and lead from the grid of the 6C6 tube in the control head and attach the test oscillator to the grid and to ground. Set to 485 K.C. and first adjust the primary I.F. trimmer shown (A) in Figure 1. Next trim the secondary (B). Now turn the plate trimmer (C) on the side of the chassis base to resonance, with a No. 4 Spintite wrench. Its (2nd I.F.) transformer is directly above the adjustment. Set the screw (D) in the top of the transformer shield to resonance also. The third I.F. transformer is adjusted through a hole in the rear of the chassis and also on top of the transformer indicated at E and F. This completes the I.F. circuit. Replace the grid lead on the 6C6 and screw the metal cap back in position.

Next attach the test oscillator to the antenna and ground lead of the control head and set it to 1500 K.C. Remove the control head cover and set the variable condenser trimmers (G and H) to a point where the 1500 K.C. signal is loudest at that frequency on the dial. Then set the test oscillator to 600 K.C. and rock the dial slowly at that frequency; at the same time turn the padder condenser adjusting screw. This trimmer is reached by removing the button plug on the bottom of the control head. The adjustments should be gone over twice to insure greater precision. Provided the test equipment is dependable, the entire receiver will now be in proper alignment and the calibration very accurate.




Fig. 1



Parts and Prices

Zenith Automobile Set Model 460

CONTROL HEAD ASSEMBLY

15-15	Control Box Tube Cap.....	\$0.25
20-39	Oscillator Coil	.75
20-40	Antenna Coil	1.00
20-41	Filament Choke	.20
22-147	.0005 mfd. Condenser..... (Cathode Bypass)	.15
22-180	Variable Condenser	2.00
22-192	7 Plate Series Trimmer Condenser..... (R. F. Coupling)	.45
22-201	.1 mfd. 200 volt Condenser..... (Screen Bypass)	.15
34-26	Hypoid Pinion Gear	.10
46-66	Control Knob	.15
52-38	Multicord Cable and Female Plug Assembly.....	4.00
52-39	Antenna Cable	.30
57-373	Escutcheon Plate	.40
63-260	100M ohm $\frac{1}{4}$ watt Resistor..... (Screen)	.20
63-261	9900 ohm $\frac{1}{4}$ watt Resistor..... (Plate)	.20
63-262	7M ohm $\frac{1}{4}$ watt Resistor..... (Cathode)	.20
63-276	500M ohm Volume Control	.65
78-68	6-C-6 Tube Socket	.10
80-90	Tuning Shaft Spring	.01
85-38	On and Off Switch.....	1.00
100-23	6.3 volt Dial Lamp.....	.20
126-121	Dial Lamp Shield.....	.10
126-122	Detector and Oscillator Coil Shields.....	.15
136-5	10 amp. Auto Fuse.....	.12
S-2638	Dial Light Socket Assembly..... (Less Lamp)	.15
S-2640	Dial and Hypoid Gear Assembly.....	1.00
6-C-6	1st Detector Oscillator Tube.....	1.80

SPEAKER CHASSIS ASSEMBLY

15-16	Tube Shield Cap	.10
22-82	.001 mfd. Condenser..... (2nd Det. Cathode).....	.25
22-175	.002 mfd. Condenser..... (1st I.F. Grids and Power Plates).....	.25
22-183	2-8 mfd. Condenser..... (Filter Block)	2.00
22-184	Condenser Block..... (Three .1 and two .25 mfd.)	1.50
22-185	.01 mfd. 200 volt Condenser..... (2nd Det. Anode and Grid)	.15
22-186	.02 mfd. 800 volt Condenser..... (Rectifier Plates)	.25
22-187	.5 mfd. 200 volt Condenser..... (Rectifier Filaments)	.50
22-190	.1 mfd. 200 volt Condenser..... (1st I.F. Cathodes).....	.15
22-191	3 Plate I.F. Trimmer 25-125 M M F..... (1st and 2nd I.F. Plate)	.30
22-195	10 mfd. 25 volt Condenser..... (2nd Detector Cathode).....	.55
22-199	.5 mfd. 200 volt Condenser..... (1st I.F. Grid).....	.30
22-200	.06 mfd. 200 volt Condenser..... (Tone Control).....	.15
22-201	.1 mfd. 200 volt Condenser..... (Vibrator Filter)	.15
46-66	Control Knob	.15
49-57	Dynamic Speaker	6.50
58-16	Female Battery Plug	.12
63-253	50M ohm Tone Control.....	.75
63-258	490M ohm $\frac{1}{4}$ watt Resistor..... (1st I.F. Grid)	.20
63-260	100M ohm $\frac{1}{4}$ watt Resistor..... (2nd Det. Anode)	.20
63-262	7M ohm $\frac{1}{4}$ watt Resistor..... (Det. Osc. Plate)	.20
63-263	30M ohm $\frac{1}{2}$ watt Resistor..... (I.F. Screens)	.20
63-264	240M ohm $\frac{1}{4}$ watt Resistor..... (1st I.F. Grid).....	.20
63-271	1 megohm $\frac{1}{4}$ watt Resistor..... (2nd Det. Anode)	.20
63-273	1800 ohm $\frac{1}{4}$ watt Resistor..... (2nd Det. Cathode).....	.20
63-274	800 ohm $\frac{1}{4}$ watt Resistor..... (Power Bias)	.20
63-282	2200 ohm $\frac{1}{4}$ watt Resistor..... (I.F. Cathode)	.20
63-283	20M ohm Sensitivity Control.....	.75

Parts and Prices (cont'd)

78-64	85 Tube Socket.....	.10
78-65	89 Tube Socket.....	.20
78-67	6-Z-4 Tube Socket.....	.10
78-69	6-D-6 Tube Socket.....	.10
93-177	Cushion Washer for Vibrator Mounting.....	.10
95-159	1st I.F. Grid Coil Assembly.....	.90
95-161	2nd I.F. Transformer.....	1.25
95-162	3rd I.F. Transformer.....	1.25
95-163	Rectifier Transformer.....	2.25
95-164	Power Choke.....	1.50
95-165	Push Pull Input Transformer.....	2.00
110-21	Grill Cloth.....	.05
126-123	Tube Shield.....	.10
190-1	Vibrator Assembly.....	8.00
S-2650	Vibrator Choke Assembly.....	.25
6-Z-4	Rectifier Tube..... (1 used)	1.75
6-D-6	I. F. Tube..... (2 used)	1.80
85	A. V. C. 2nd Detector Tube..... (1 used)	1.60
89	Power Output Tube..... (2 used)	1.80

STANDARD SUPPRESSOR EQUIPMENT

2-193	.5 mfd. 200 volt Ignition Coil Condenser.....	.45
22-194	.5 mfd. 200 volt Generator Coil Condenser.....	.50
63-268	Spark Plug Suppressor.....	.45
63-269	Distributor Suppressor.....	.45

STANDARD MOUNTING PARTS

17-20	Mounting Clamp for Control Head.....	.25
15-14	Mounting Clamp Cap for above.....	.25
69-17	8/32x5/16" R H Machine Screws, C.....	.20
69-40	8/32x1" R H Machine Screws, C.....	.20
69-93	8/32x7/16" R H Machine Screws, C.....	.20
73-17	Headless Set Screws.....	.01
93-126	No. 8 Shakeproof Washers, C.....	.20
93-143	3/8" Internal Shakeproof Washers, C.....	.30
94-143	Fibre Clamp Bushing.....	.10
144-11	5/16x3" Carriage Bolts and Nuts, C.....	.20
147-12	Wooden Spacer Blocks.....	.01

SPECIAL MOUNTING PARTS

S-2704	Parallel Steering Column..... (consists of following)	1.00
15-14	Clamp Caps..... (2 used)	.20
17-20	Mounting Clamps..... (2 used)	.20
69-40	8/32x1" R H Machine Screws..... (8 used), C.....	.35
69-93	8/32x7/16" R H Machine Screws..... (8 used), C.....	.35
73-17	Headless Set Screws..... (2 used)	.01
93-126	No. 8 Shakeproof Lockwasher..... (8 used), C.....	.35
94-143	Fibre Clamp Bushing..... (4 used)	.10
S-2705	Swivel Steering Column..... (consists of following)	1.00
12-293	Swivel Mounting Brackets..... (2 used)	.20
17-21	Swivel Mounting Clamps..... (2 used)	.20
54-65	Forged Winged Nuts..... (6 used)	.02
93-127	No. 10 Shakeproof Washers..... (6 used), C.....	.35
118-8	Connecting Links..... (2 used)	.10
144-12	3/16x3/4" Carriage Bolts..... (6 used), C.....	.20

All prices are subject to regular discount and change without notice.
These prices supersede all previous quotations on like parts.

Nov., 1933



Supplement to Model 460 Service Bulletin

JULY, 1933

All Zenith Auto Radio receivers after serial number 502101 on the control head and number 202101 on the speaker chassis incorporate the following changes:

1. Power transformer
2. I. F. transformers
3. Diode circuit
4. A. V. C. circuit
5. I. F. Bias resistors

The circuit diagram on the reverse side of this sheet shows the improvements alphabetically as listed below.

- A—Was part #22-184. Replaced by part #22-198 (Same electrical specifications with slightly smaller container)
- B—Was part #95-163. Replaced by part #95-197.
- C—I. F. transformers #95-159, #95-161, and #95-162 replaced by numbers 95-198, 95-199 and 95-200 respectively.
- D—Bias resistors #63-282 (2200 ohms) replaced by #63-265 (220 ohms each)
- E—Diode split and A. V. C. return wiring altered (See diagram)

(Since electrical specifications are identical, it is not necessary to replace part number 224-184 when converting earlier sets)

PARTS REMOVED

- | | |
|----------------------------|-----------------------------|
| 1 95-163 Power transformer | 1 95-162 I. F. transformer |
| 1 95-159 I. F. transformer | 2 63-282 2200 ohm resistors |
| 1 95-161 I. F. transformer | 1 22-184 condenser block |

PARTS ADDED

- | | |
|----------------------------|-------------------------------|
| 1 95-197 Power transformer | 1 22-162 .0001 mfd. condenser |
| 1 95-198 I. F. transformer | 1 63-258 490,000 ohm resistor |
| 1 95-199 I. F. transformer | 2 63-265 220 ohm resistors |
| 1 95-200 I. F. transformer | |

TUBE OPERATING VOLTAGES

Position	Tube	Ef	Ek	Eg ¹	Eg ²	Eg ³	Ep
1st Detector	6C6	5.6	7	0	7	125	180
1st I.F. Amp.	6D6	5.3	1.8	*	1.8	110	200
2nd I.F. Amp.	6D6	5.3	1.8	*	1.8	110	200
2nd Detector	85	5.3	8.	0	--	—	185
P. P. Audio	89	5.3	20	0	20	200	200
	89	5.3	20	0	20	200	200

f—Filament. k—Cathode. g¹—Control grid. g²—Suppressor grid. g³—Screen grid. p—Plate.

*Depends on applied signal strength. All voltages measured from indicated points to ground.

Tube equipment and all other components remain unchanged.

ZENITH RADIO CORPORATION


(over)

CHICAGO, ILL.

Zenith Radio Corporation

Service Bulletin

MODELS 835 - 880



CHASSIS 1001-1001A

SERVICE NOTES

Dial Slips or Binds. Tighten lugs on planetary drive. See that both pointers are free. Make sure gang is squarely lined up with dial.

Off Calibration. Check for loose set screws on dial assembly to condenser shaft. Black pointer may be loose on shaft. Check alignment as outlined in Alignment Procedure.

Poor Tone. Defective tubes in audio. One side of push-pull circuit faulty. Check audio and output transformers. See A.V.C. blocking.

Insensitive. Out of alignment, weak tubes or defective by-pass condenser.

Shadowgraph Inoperative. Weak 76 tube, burnt out shadowgraph, open resistor in 76 plate circuit.

Distortion at Medium Volume. Defective 75 tube, defective volume control. Separate green volume control-lead and speaker-lead close to grid of 42 tube.

Insensitive on Any Short Wave Band. Check alignment, make sure R.F.circuit is not aligned to image frequency. Change 6A7 tube. Change position of fixed condensers adjacent to rear section of wave change switch. Location of these condensers in relation to each other and their distance from the chassis will effect dial calibration and sensitivity, especially on the Blue Band.

Stops Oscillating Around 9 M.C. Change 6A7 tube, leakage in 50 mmfd. or .0029 mfd. condenser.

A.V.C. Blocks. Shorted resistor on antenna choke. C-14 padder shorted. Grounded R.F. grid circuit.

Oscillates on Broadcast. Check alignment. Push brown wire away from 6A7 socket. Grounded cathode on 1st I.F. or grounded to 600 K.C. padder. Check for open by-pass condenser.

Noisy. Shorting plates in gang condenser. Poor contact in band switch. Loose shields or shield bases. Static shields may be touching leads under gang condenser.

Overheats. Check pilot light and heater circuits for partial short or ground.

Flutters. Rearrange leads under chassis especially around 6A7.

Oscillates on Short Wave Bands. Make sure brown R.F. grid return lead is pushed away from 6A7 socket. Check for ground on any A.V.C.lead. Open by-pass condenser.

Tone Control Inoperative. Resin joint or poor contact on tone control switch. Defective condensers in tone control circuits.

Continuous Audio Whistle. Rearrange leads in audio circuit.

Alignment

The diagram on page 2 shows position of major components and aligning adjustments. It should be studied carefully before any attempt is made to adjust the various circuits. The Clough-Brengle type is the only commercial service oscillator found practical for this work.

Separate coils are used for each band. Mounted on the coils are individual trimmers that align each band, independent of the other bands.

Connect 485 K.C. service oscillator to grid of 6A7 and chassis ground. Adjust I.F. trimmers on rear of I.F. transformers for strongest signal.

Connect 485 K.C. service oscillator to antenna and ground. Turn dial to 540 K.C. on broadcast band and adjust wave trap trimmer on right rear side of chassis for weakest signal.

Broadcast - Black Band

Set service oscillator at 1400 K.C., remaining attached to antenna ground posts. Turn dial to same point and adjust #1 trimmer (top one on oscillator coil) to resonance. Adjust #1 R.F. trimmer (top one on R.F. coil); #1 detector trimmer (through hole in chassis base) and band pass trimmer (top front section of gang) all to resonance.

Set service oscillator at 600 K.C. Adjust padder (located in center rear of chassis) for correct dial reading.

Recheck 1400 K.C. alignment.

Orange Band

Set service oscillator at 4 M.C. (still attached to antenna and ground) and adjust trimmer #2 (2nd from top) on oscillator coil for correct dial reading. Adjust #2 R.F. trimmer (2nd from top on R.F. coil) and #2 detector trimmer (center hole through chassis) to resonance.

Brown Band

Loosen #3 detector trimmer (top one on detector coil). Set service oscillator at 10.5 M.C. Adjust #3 oscillator trimmer (third from top on oscillator coil) for correct dial reading. Adjust #3 R.F. trimmer (third from top of R.F. coil) and #3 detector trimmer (rear one through hole in top of chassis). Adjust #3 detector trimmer on coil to resonance.

Blue Band

Tighten #4 detector trimmer (bottom one on detector coil). Set service oscillator at 21 M.C. Adjust #4 oscillator trimmer (bottom one on oscillator coil) for correct dial reading. Adjust #4 R.F. trimmer (lower one on R.F. coil) and #4 detector trimmer (lower one on detector coil) to resonance.

It is very easy to mistake the image frequency for the fundamental on this band. Rotate dial and if shadowmeter narrows at any point, especially at 15 M.C., the band should be rebalanced.

Green Band

There are no adjustments to be made on this band.


Socket Voltage

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	R. F.	5.9	1.7	0	85	1.7	235
6A7	1st. Det.	5.9	2.5	0	95	-	235
	OSC.			-1	-	-	165
6D6	1st. I. F.	5.9	8	0	95	8	235
6D6	2nd. I. F.	5.9	8	0	95	8	230
75	2nd. Det. 1st. Aud.	5.9	1.5	0	-	-	155
37 or 76	Shadow-Met. Amp.	5.9	0	-1	-	-	98
42	2nd. Aud.	5.9	21	0	-	-	230
42	PWR.	5.9	33	0	-	-	340
42	PWR.	5.9	33	0	-	-	340
5Z3	Rect.	4.5	-	-	-	-	-

Line Voltage 112 Volts


Antenna and Ground Disconnected.

f - filament; k - cathode; g1 - control grid; g 2 - screen grid; g3 - suppressor grid; p - plate.



VOL. CON. TONE CON. BAND SW.
COIL TRIMMERS NUMBERED FROM TOP DOWN.

6D6
157 R.F.



DIAG. PART


No.	No.	DESCRIPTION
C1	22-250 05	- 200V
C2	22-289 00005-600V	
C3	22-285 00001-600V	
C4	22-185 01	- 200V
C5	22-327 02	- 200V
C6	22-292 500-1000MMF.	
C7	22-182 00025-600K	
C8	22-82 001	- 600V
C9	22-212 05	- 400V
C10	22-326 003	- 400V
C11	22-225 5	- 25V
C12	22-331 8	- 500V
C13	22-125 8	- 440V
C14	22-284 75	- 275MMF.
C15	22-190 1	- 200V
C16	22-333 4 GANG VAR	
C17	22-329 00097-600V	
C18	22-228 5	- 300V

C20	22-328 0029	- 600K
C21	22-147 0005-600V	
C22	22-325 2-35MMFD.	
C23	22-324 2-35	"
C24	22-323 2-35	"
C25	22-188 02	- 400V


R1	63-238	1000- $\frac{1}{2}$ W.
R3	63-253	490M- $\frac{1}{2}$ W.
R4	63-386	12M- $\frac{1}{2}$ W.
R5	63-281	29M- $\frac{1}{2}$ W.
R6	63-278	99M- $\frac{1}{2}$ W.
R7	63-329	670- $\frac{1}{2}$ W.
R8	63-380	100M- $\frac{1}{2}$ W.
R9	63-381	100M- $\frac{1}{2}$ W.
R10	63-290	260M- $\frac{1}{2}$ W.
R11	63-261	9900- $\frac{1}{2}$ W.
R12	63-352	2400- $\frac{1}{2}$ W.
R13	63-383	500-730
R14	63-293	19M- $\frac{1}{2}$ W.
R15	63-265	220- $\frac{1}{2}$ W.
R16	63-372	50M- $\frac{1}{2}$ W.
R17	63-376	250- $\frac{1}{2}$ W.
R18	63-388	19M- $\frac{1}{2}$ W.
R19	63-291	29M- $\frac{1}{2}$ W.

R20	63-384	500M V CONTROL
R21	63-361	5M- $\frac{1}{2}$ W.

3	20-85 BAND PASS COIL
4	20-64 WAVE TRAP
5	20-81 R.F. P. CHOKES
6	5-3079 DET. COIL
7	5-3080 OSC. COIL
8	5-3079 R.F. COIL
9	95-242 1ST I.F. TRANS.
10	95-242 2ND I.F. TRANS.
11	95-243 3RD I.F. TRANS.
12	95-241 POWER TRANS.
13	95-239 AUDIO TRANS.
14	95-240 FILTER CHOKE
15	5-3115 TUNING OSC. COIL
16	20-84 7" DET.



SWITCHES SHOWN IN BROADCAST POSITION.
I.F. FREQUENCY - 485 KC.



75
1ST AUDIO
2ND DET.
H.Y.C.

6D6
2ND I.F.

6D6
1ST I.F.

ZENITH RADIO CORP
CHICAGO, ILL.
CHASSIS MODEL 1001

WD 7 31 34



Parts and Prices

MODELS 835, 880, 881
and 1101

Chassis 1001

Dial Assembly

26-66	Complete Dial and Drive Assembly	\$7.50
26-67	Dial Scale only	.75
33-57	Dial Retaining Frame	.35
59-28	Large Z Pointer	.10
59-29	Split Second Pointer	.10
192-4	Dial Glass	.20
93-217	Dial Glass Cushion Washer	.10
76-151	Planetary Drive Assembly	2.00
32-3	Pulley Drive Belt	.15

Resistors

63-238	1 M	ohm	$\frac{1}{4}$	watt		.20
63-258	49M	"	$\frac{1}{4}$	"		.20
63-261	9900	"	$\frac{1}{4}$	"		.20
63-265	220	"	$\frac{1}{4}$	"		.20
63-278	99M	"	$\frac{1}{4}$	"		.20
63-281	29M	"	$\frac{1}{4}$	"		.20
63-288	19M	"	$\frac{1}{4}$	"		.20
63-290	260M	"	$\frac{1}{4}$	"		.20
63-291	29M	"	$\frac{1}{4}$	"		.20
63-361	5 M	"	$\frac{1}{4}$	"		.20
63-372	50M	"	$\frac{1}{4}$	"		.20
63-378	250	"	$\frac{1}{4}$	"		.20
63-379	670	"	$\frac{1}{4}$	"		.20
63-380	100M	"	1	"		.25
63-381	100M	"	$\frac{1}{2}$	"		.20
63-382	2400 - 4000	ohm		Candohm		.75
63-383	500 - 730	"		"		.30
63-384	500	ohm		Volume Control and Switch Assembly		1.00
63-386	12M	"	2	Watt		.30
63-388	19M	"	1	"		.25

Condensers

22-82	.001	Mfd.	600 V.		.25
22-125	8.	"	440 V.		1.00
22-147	.0005	"	600 V.		.15
22-182	.00025	"	600 V.		.12
22-185	.01	"	200 V.		.15
22-188	.02	"	400 V.		.15
22-190	.1	"	200 V.		.20
22-212	.05	"	400 V.		.20
22-225	5.	"	25 V.		.65
22-228	.5	"	300 V.		.35
22-250	.05	"	200 V.		.15
22-284	75 - 275	Mmfd.			.30
22-285	10	Mmfd.	600 V.		.15
22-289	50	Mmfd.	600 V.		.12

PARTS AND PRICES
PAGE NO.2

MODELS 835, 880, 881, 1101
Chassis 1001

Condensers Cont'd

22-292	500 - 1000 Mmfd.	\$.45
22-324	3-gang Adj. Condenser	.40
22-326	.003 Mfd. 400 V.	.15
22-327	.02 " 200 V.	.15
22-328	2900 Mmfd. 600 V.	.30
22-329	970 Mmfd. 600 V.	.20
22-331	8. Mmfd. 500 V.	1.25
22-333	4- gang Variable	5.00

Coils & Chokes

20-64	Wave Trap	.35
20-81	R. F. Plate Choke	.65
20-84	7-Meter Detector Coil Assembly.....	.10
20-85	Band Pass Coil Assembly	.60
95-242	1st and 2nd I. F. Coil Assembly	1.50
95-243	3rd I. F. Coil Assembly	1.50
S-3078	R. F. Coil Assembly	2.75
S-3079	Detector Coil Assembly	2.50
S-3080	Oscillator Coil Assembly	2.75
S-3115	7-Meter Oscillator Coil Assembly	.40

Miscellaneous

44-7	Phono Connector Jack (Export Models Only)	.15
46-94	Band Selector Switch Knob	.25
46-95	Tone and Volume Knobs	.25
46-96	Tuning Knob - Large	.25
46-97	Tuning Knob - Small	.20
49-91	10" Dynamic Speaker (Model 835)	10.00
	Cone and Voice Coil for 49-91	3.00
	Output Transformer for 49-91	2.00
	Field Coil for 49-91	2.00
49-92	12" Dynamic Speaker (Models 880, 881)	14.50
	Cone and Voice Coil for 49-92	3.25
	Output Transformer for 49-92	2.50
	Field Coil for 49-92	2.50
57-455	Dial Escutcheon Plate for Models 880, 881	.75
78-100	Tube Socket - 6D6	.10
78-101	" " 75	.10
78-102	" " 42	.10
78-106	" " 6A7	.10
78-109	" " 76	.10
78-110	" " 5Z3	.10
85-56	Phono Switch	.35
85-58	Band Selector Switch	4.00
85-60	4-position Tone Switch	.60
95-239	Push Pull Input Transformer	2.00
95-240	Power Filter Choke	2.00

PARTS AND PRICES
PAGE NO.3

MODELS 835, 880, 881, 1101
Chassis 1001

Miscellaneous Cont'd

95-241	117 V. 50/60 Cycle Power Transformer	\$5.75
95-246	All Voltage 25 Cycle " "	\$10.00
100-23	6.3 Volt Pilot Lamp	.15
122-9	Shadowgraph Meter	2.00
126-127	Tube Shields	.15

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

WARRANTY

The Zenith Radio Corporation guarantees each new ZENITH receiver and each new ZENITH QUALITY TUBE to be free from defects in workmanship and material.

Our obligation under this warranty is limited to making good at our factory any part or parts of the receiver which within ninety days from date of purchase shall be returned to us with transportation charges prepaid and which on examination shall be found to our satisfaction to have been thus defective. The ZENITH QUALITY TUBES used in this receiver are guaranteed against mechanical and electrical defects under the same warranty as the receiver. This warranty is expressly in lieu of all other warranties expressed or implied, and we neither assume nor authorize any representative or other person to assume for us any other liability in connection with the sale of ZENITH receivers or ZENITH QUALITY TUBES.


This warranty shall not apply to any receiver or tube which shall have been repaired or altered outside of our factory in any way so as, in our judgment, to affect its stability or reliability, nor which has been subject to misuse, negligence or accident, nor which has had the serial number or name altered, defaced or removed. Neither shall this warranty apply to any receiver in which other than ZENITH QUALITY TUBES have been used.

ZENITH RADIO CORPORATION.



ZENITH RADIO CORPORATION

3620 Iron Street
CHICAGO, ILL., U. S. A.



MODELS 825-827-829-870

CHASSIS 5701-2-3

ZENITH RADIO CORPORATION
CHICAGO, ILL. U.S.A.

SOCKET VOLTAGES
5701 - 2 - 3 CHASSIS

TYPE	POSITION	E _f	E _k	E _{g1}	E _{g2}	E _{g3}	E _p
6D6	R.F.	5.4	2.8	0	2.8	74	230
6D6	1st. Det.	5.4	7.8	0	7.8	74	230
37	Osc.	5.4	0	38	-	-	130
6D6	I.F.	5.4	2.8	0	2.8	74	230
74	2nd. Det.	5.4	1	0	-	-	125
42	PWR.	5.4	0	4	0	230	215
80	Rect.	4.2	-	-	-	-	235

Line Voltage 112 V.

Aerial and Ground disconnected.

F - Filament

K - Cathode

G1 - Control Grid

G2 - Suppressor Grid


G3 - Screen Grid

P - Plate

All measurements taken from points indicated to ground with 1000 ohms per volt D.C. meter (except filaments).

Balance I.F. transformers at 485 K.C., trimmers on condenser gang at 1500 K.C. and oscillator padder at 600 K.C.

The screw adjustment at the right hand rear of chassis is a wave trap for the elimination of code interference at the I.F. frequency. Connect 485 K.C. oscillator on antenna and adjust for weakest signal.


Tube Layout

PARTS AND PRICES

MODELS 825 827 870 829

MODEL 825

CHASSIS 5701

Condensers

22-82	.001 mfd.	600 volt	(1st Audio Plate, Oscillator).....	\$.25
22-147	.0005 "	600 "	(Volume Control Bypass).....	.15
22-170	.1 "	400 "	(1st Audio Plate).....	.25
22-188	.02 "	400 "	(Audio Coupling - 2 used).....	.15
22-199	.5 "	200 "	(R.F. Cathode).....	.30
22-205	200 - 500 mmfd.	Padder.....		.35
22-265	3-Gang Variable.....			3.00
22-276	.01 mfd.	400 volt	(R.F.Plate -Det.Cathode - Osc. Plate)..	.15
22-283	Dual 8 mfd.	450 volt	(for 5701 and 2 only) Filter.....	2.50
22-284	75-275 mmfd.	Trimmer	(Wave Trap).....	.30
22-286	.05 mfd.	200 volt	(R.F.Grid Return - Screen Bypass - I.F.Grid Return - 1st Det. Cathode).....	.15
22-287	.03 mfd.	600 volt	(Tone Control).....	.15
22-288	.003 mfd.	600 volt	(Oscillator Cathode).....	.15

Resistors

63-258	490M ohms	$\frac{1}{4}$ watt	(A.V.C.Filter - Power Grid).....	.20
63-265	220 "	$\frac{1}{4}$ watt	(R.F.Cathode).....	.20
63-278	99M "	$\frac{1}{4}$ watt	(1st Audio Plate - 2 used).....	.20
63-280	49M "	$\frac{1}{4}$ watt	(1st Det. A.V.C.).....	.20
63-289	29M "	1 watt	(Oscillator Plate).....	.25
63-290	260M "	$\frac{1}{4}$ watt	(Oscillator Grid).....	.20
63-293	990M "	$\frac{1}{4}$ watt	(1st Audio Grid).....	.20
63-305	160 "	$\frac{1}{4}$ watt	(Oscillator Plate).....	.20
63-313	3800 "	$\frac{1}{4}$ watt	(1st Det. Cathode).....	.20
63-338	Volume Control & Switch Assembly	(200M Ohms).....		1.00
63-351	Candohm Voltage Divider.....			.65
63-353	19M ohms	$\frac{1}{2}$ watt	(Tone Control).....	.20

Coils

20-64	Wave Trap Coil.....			.35
S-2889	R.F.Coil and Shield Assembly.....			.85
S-2891	Detector Coil and Shield Assembly.....			1.50
S-2893	Oscillator Coil and Shield Assembly.....			1.20
95-222	1st I.F. Transformer, 485 K.C.....			1.75
95-223	2nd I.F. Transformer, 485 K.C.....			1.75

Miscellaneous

19-44	Coat Tube Shield Clips.....			.03
46-77	Knob - Band Selector.....			.25
46-78	Knob - Tuning & Volume Control.....			.20
46-79	Knob - Tone Control.....			.20
49-76 J	Dynamic Speaker 6" (Also 49-80 Utah).....			5.50
49-76 C	Output Transformer (" " " ").....			1.50
49-76 A	Cone & Voice Coil (" " " ").....			2.00
49-76 B	Field Coil.....(" " " ").....			2.00
57-439	Escutcheon Plate for Dial.....			.20
57-440	Zenith Nameplate (5701 only).....			.10
78-69	6D6 Socket.....			.10

PARTS AND PRICES

MODELS 825 827 870 829

- PAGE 2 -

Miscellaneous Cont'd

78-70	80 Socket.....	\$.10
78-91	75 Socket.....	.10
78-92	42 Socket.....	.10
78-95	37 Socket.....	.10
78-76	Pilot Lamp Clip and Socket Assembly.....	.10
83-334	Antenna and Ground Terminal Strip.....	.12
85-45	2-Position Tone Control Switch.....	.35
85-46	2-Section Wave Change Switch.....	1.50
95-224	117 V.- 50/60 cycle Power Transformer.....	3.75
95-229	All Voltage - 25 Cycle Power Transformer.....	7.25
100-29	6 - 8 Volt Pilot Lamp (also Shadowmeter Lamp).....	.15
126-131	Coat Tube Shield with Rings.....	.10
26-51	Tuning Dial Complete.....	1.50

MODEL 827, CHASSIS #5702

Same as Chassis #5701 with additional parts as follows:

22-274	.05 mfd. 400 volt Condenser (Shadowgraph Filter).....	.15
57-407	Zenith Nameplate.....	.10
57-441	Shadowmeter Escutcheon Plate.....	.15
100-29	6-8 volt Pilot Lamp.....	.15
122-8	Shadowmeter.....	2.00

MODEL 870, CHASSIS #5703

Same as Chassis #5701 less 49-76 Speaker, 22-283 Condenser and S-2897

Tuning Dial and with additional parts as follows:

22-266	8-16 mfd. 500 volt Condenser.....	3.50
26-52	Aeroplane Dial Complete.....	2.75
57-442	Escutcheon Plate for Dial.....	.40
49-82	12" Dynamic Speaker.....	10.00
49-82 A	Cone and Voice Coil for 49-82.....	3.25
49-82 B	Output Transformer for 49-82.....	2.00
49-82 C	Field Coil for 49-82.....	2.00

MODEL 829, CHASSIS #5704

Same as Chassis #5703 less 49-82 Speaker and with additional parts as follows:

46-84	Knob - Band Switch	.25
46-85	Knob - Tuning and Volume	.20
46-86	Knob - Tone	.20
49-79	8" Dynamic Speaker	8.00
49-79 A	Cone and Voice Coil for 49-79	2.50
49-79 B	Output Transformer for 49-79	2.00
49-79 C	Field Coil for 49-79	2.00

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS ON OTHER PARTS LISTS FOR LIKE PARTS.

ZENITH RADIO CORPORATION

November 15, 1934


R.F. 6-D-6

I.F. DET. 6-D-6

I.F. 6-D-6

2ND DET. A.V.C. 7-5

POWER 4-2



DIAG PART NO. DESCRIPTION

C1	22-319	.005 MFD. 200V
C2	22-82	.001 " 600V
C3	22-155	.5 " 200V
C4	22-47	.0005 " 600V
C5	22-259	.05 " 200V
C6	22-212	.05 " 400V
C7	22-249	.01 " 400V
C8	22-168	.02 " 400V
C9	22-337	.015 " 200V
C10	22-170	.1 " 400V
C11	22-287	.03 " 600V
C12	22-592	500-1000 MFD. 200V
C13	22-175	.002 MFD. 600V
C14	22-358	.004 " 600V
C15	22-309	75-160 MFD. VARIABLE
C16	22-288	3.65 " 450 V
C17	22-322	8-8 MFD. 450 V
C18	22-321	8 " 450 V
C19	22-305	2-35 MFD. 200V

R1	63-235	120 M OHMS 1/2W
R2	63-265	220 " 1/2W
R3	63-351	170.55 " 1/2W @ 1000HZ
R4	63-355	160 " 1/2W
R5	63-373	194 " 1/2W
R6	63-353	194 " 1/2W
R7	63-313	3000 " 1/2W
R8	63-250	260 M " 1/2W
R9	63-258	490 M " 1/2W
R10	63-278	95 M " 1/2W
R11	63-293	950 M " 1/2W
R12	63-338	200 M OHMS 1/2W. CON.
R13	63-366	19 M " 1/2W

- 1 65-53 BAND CHANGE SWITCH
- 2 20-75 FILTER CHOKE
- 3 20-71 ANTENNA
- 4 S-2863 R.F. COIL ASSEMBLY
- 5 S-2864 DET.
- 6 S-2963 OSC.
- 7 S-244 I.F. TRANS.
- 8 S-245 I.F. TRANS.
- 9 20-85 R.F. COIL TRANS.
- 10 122-8 R.F. COIL TRANS.
- 11 49-76 6" SPEAKER
- 12 49-56 12" AUDITORIUM SPEAKER
- 13 49-97 12" AUDITORIUM SPEAKER
- 14 49-98 12" AUDITORIUM SPEAKER
- 15 85-36 TONE CONTROL SWITCH
- 16 95-234 POWER TRANSF.
- 17 95-225 25 CYCLE

I.F. FREQUENCY 252.5 K.C.
7 TUBE SUPERHETERODYNE
CHASSIS NOS. 5701-R, 5702-R, 5703-R

MODELS
S-829 - S-870
S-871 - 1170

ZENITH RADIO CORP.
CHICAGO ILL.

10-5-3280 APPROX. 10 MFD. COUP. COND.

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	R.F.	5.4	3	0	76	3	250
6D6	1st.Det.	5.4	6.2	0	76	6.2	250
75	Osc.	5.4	0	0	-	-	165
6D6	I.F.	5.4	6.2	0	76	6.2	250
75	2nd.Det. A.V.C. 1st.Aud.	5.4	1	0	-	-	125
42	PWR	5.4	0	-.5	-	250	240
80	Rect.	4.6	-	-	-	-	-

Line voltage 112

Antenna and Ground Disconnected

F - heaters; K - cathode; G1 - control grid; G2 - screen grid; G3 suppressor grid; P - plate.

Alignment


(1) Balance intermediate transformers at 252.5 K.C. with service oscillator connected to grid of first detector and ground.

(2) Adjust wave trap padder (located on rear of chassis at right side) at 252.5 K.C. for weakest signal with service oscillator connected to aerial and ground.

(3) Turn wave band switch clockwise to the highest frequency band. Set service oscillator at 15 megacycle (still connected to aerial and ground). Adjust trimmer on oscillator section of 3-gang condenser for correct dial reading at this frequency.

(4) Turn wave band switch counter-clockwise to standard broadcast. Adjust oscillator trimmer (located underneath chassis next to band switch) for correct dial reading at 1400 K.C. and balance R.F. and 1st detector trimmers on gang condenser for loudest signal at this frequency.

(5) Adjust broadcast oscillator padder (through hole in right side of chassis) at 600 K.C. meanwhile rocking dial pointer past this point on dial, to position giving loudest signal.



Tube Layout

PARTS AND PRICES
Chassis #5703R

MODELS S-829, S-870
S-871, 1170

Condensers

22-82	.001 Mfd.	200 V.		\$.25
22-147	.0005 Mfd.	600 V.		.15
22-170	.1 "	400 V.		.25
22-175	.002 "	600 V.		.25
22-188	.02 "	400 V.		.15
22-199	.5 "	200 V.		.30
22-212	.05 "	400 V.		.20
22-243	.01 "	400 V.		.15
22-250	.05 "	200 V.		.15
22-265	Variable Condenser Assembly			3.00
22-287	.03 Mfd.	600 V.		.15
22-292	Padder			.45
22-305	"			.15
22-309	"			.25
22-319	.0005 Mfd.	200 V.		.20
22-321	8. "	450 V.		1.25
22-322	8. x 8. Mfd.	450 V.		2.50
22-337	.015 Mfd.	200 V.		.15
22-338	.004 "	600 V.		.35

Resistors

63-258	490 K	Ohm	$\frac{1}{4}$ Watt		.20
63-265	220	"	"		.20
63-278	99K	"	"		.20
63-290	260M	"	"		.20
63-293	990K	"	"		.20
63-295	120M	"	"		.20
63-305	160	"	"		.20
63-313	3800	"	"		.20
63-338	200M	"	Volume Control Assembly		1.00
63-351	17,035	"	Candohm		.65
63-353	19M	"	$\frac{1}{2}$ Watt		.20
63-373	11K	"	"		.25

Coils and Chokes

20-71	Antenna Choke			.20
20-75	Filter Choke			.25
20-83	R.F. Plate Choke			.30
95-244	1st I.F. Transformer			1.50
95-245	2nd I.F. Transformer			1.50
S-2963	Oscillator Coil Assembly			1.00
S-2964	Detector Coil Assembly			1.25
S-2965	R.F. Coil Assembly			1.25

Miscellaneous

26-61	Complete Airplane Dial and Drive Assembly			2.75
46-85	Knobs for Volume and Tuning (Model S-829 only)			.20
46-88	" " " " " (" S-870 and S-871 only)....			.10
46-91	Band Selector Switch Knob (Model S-870 and S-871 only)....			.15

Miscellaneous Contd.

46-92	Band Selector Switch Knob (Model S-829 only).....	\$.20
49-79	8" Dynamic Speaker for Model S-829 only	8.00
49-79A	Cone and Voice Coil for 49-79	2.00
49-79B	Output Transformer for 49-79	2.00
49-79C	Field Coil for 49-79	2.00
49-97	12" Dynamic Speaker for S-870 and 1170	10.00
49-97A	Cone and Voice Coil for 49-97	3.25
49-97B	Output Transformer for 49-97	2.00
49-97C	Field Coil for 49-97	2.00
49-98	12" Auditorium Dynamic Speaker for Model S-871	12.00
49-98A	Cone and Voice Coil for 49-98	3.25
49-98B	Output Transformer for 49-98	2.50
49-98C	Field Coil for 49-98	2.00
57-442	Dial Escutcheon Plate	.40
78-69	6D6 Socket	.10
78-70	80 "	.10
78-91	75 "	.10
78-92	42 "	.10
78-111	76 "	.10
83-334	Antenna and Ground Terminal Strip	.12
85-45	Two-Position Tone Control Switch	.35
85-59	Wave Change Switch	1.50
95-234	117 V. 50-60 Cycle Power Transformer	3.75
95-229	25 Cycle All Voltage Power Transformer	7.25
100-23	6.3 Volt Pilot Lamp	.15
126-131	Goat Tube Shield	.10

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
October 23, 1934

5605

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	R.F.	5.6	2.4	0	70	2.4	200
6A7	1st. Det.	5.6	3	0	70	-	250
	Osc.			3.6	-	-	230
6D6	I.F.	5.6	2.6	0	70	2.6	250
75	2nd. Det.	5.6	1.4	0	-	-	148
	1st Audio						
42	PWR.	5.6	0	- .6	250	-	250
80	RECT.	4.6	-	-	-	-	300

Line Voltage 112


Antenna and Ground Disconnected

All measurements taken from point indicated to ground, using a 1000 ohm per volt D.C. meter (except heaters).

F - Filament; K - Cathode; g1 - Control Grid; g2 - Screen Grid; g3 - Suppressor Grid; p - Plate.

Alignment

1. Balance intermediate transformers at 252.5 K.C. with oscillator connected to grid of first detector and ground.
2. Adjust wave trap padder (located underneath chassis at rear right side) for weakest signal with 252.5 K.C. oscillator connected to aerial and ground.
3. Turn wave band switch clockwise to the highest frequency band. Connect 15,000 K.C. oscillator to aerial and ground. Balance oscillator trimmer on three-gang condenser for correct dial reading at this frequency.
4. Turn wave band switch counter-clockwise to standard broadcast position. Adjust broadcast oscillator trimmer (located underneath chassis at right center) for correct dial reading at 1400 K.C. and balance R. F. and 1st detector trimmers on three-gang condenser for loudest signal.
5. Adjust oscillator standard broadcast padder through hole in top center of chassis for correct dial reading at 600 K.C.



PARTS AND PRICES
MODELS 808 and 809
Chassis 5605

MODELS 808, 809, 860, 861

Dial Assembly

12-372	Bracket Shaft and Frame Assembly.....	\$.65
26-50	Dial Scale.....	.40
27-5	Celluloid Disc and Hub Assembly.....	.25
73-22	Set Screw.....	.03
59-27	Pointer.....	.15
93-207	Glass Cushion Washer.....	.05
192-3	Glass.....	.20

Condensers

22-82	.001 Mfd. 500 Volt (1st Audio Plate).....	.25
22-125	8. " 440 " (Power Filter).....	1.00
22-147	.0005 " 600 " (R.F. Plate Coupling).....	.15
22-170	.1 " 400 " (1st Audio Plate).....	.25
22-182	.00025 " 600 " (A.V.C. By-Pass).....	.12
22-185	.01 " 200 " (2nd Detector Cathode).....	.15
22-188	.02 " 400 " (1st and 2nd Audio Coupling).....	.15
22-229	.005 " 600 " (R.F. and 1st Det. A.V.C. By-Pass)....	.15
22-250	.05 " 200 " (Screens).....	.15
22-276	.01 " 400 " (Oscillator).....	.15
22-287	.03 " 600 " (Tone Control & Pwr. Grid).....	.15
22-289	50 Mmfd. 600 " (Oscillator Grid).....	.12
22-290	Three-Gang Variable.....	3.25
22-292	500-1000Mmfd. Padder (Oscillator).....	.45
22-304	.0036 Mfd. 600 Volt (Oscillator).....	.30
22-305	2 - 35 Mmfd. Padder (Oscillator).....	.15
22-306	2. Mfd. (Dry Electrolytic) (Oscillator B Filter).....	.80
22-309	50 - 120 Mmfd. Padder (Wave Trap).....	.25
22-318	8 - 2 Mfd. 450 Volt Filter	1.60

Resistors

63-258	490 M. Ohms $\frac{1}{4}$ Watt (A.V.C. Filter).....	.20
63-271	1 Megohm $\frac{1}{4}$ " (1st and 2nd Audio Grids).....	.20
63-278	99 M Ohms $\frac{1}{4}$ " (1st Audio Plates and Pwr. Grid).....	.20
63-280	49 M Ohms $\frac{1}{4}$ " (Oscillator Grid).....	.20
63-295	120 M Ohms $\frac{1}{4}$ " (R.F. Grid Return).....	.20
63-351	Candohm Voltage Divider.....	.65
63-353	19 M Ohms $\frac{1}{4}$ Watt (Tone Control and Osc. Filter).....	.20
63-355	51 M Ohms $\frac{1}{4}$ " (A.V.C. Load).....	.20
63-357	300 Ohms $\frac{1}{4}$ " (R.F. and I.F. Cathodes).....	.20
63-362	400 Ohms $\frac{1}{4}$ " (1st Detector Cathode).....	.20
63-366	Volume Control and Switch.....	.80
63-373	11 M Ohms $\frac{1}{2}$ Watt (R.F. and Osc. Plates).....	.25

Coils

20-71	Antenna Choke.....	.20
20-75	Wave Trap Choke.....	.25
95-227	1st I. F. Transformer (252.5 K.C.).....	1.50

Coils (Continued)

95-230	2nd I. F. Transformer (252.5 K.C.).....	\$ 1.50
S-2953	Oscillator Coil and Shield Assembly.....	1.00
S-2955	Antenna Coil and Shield Assembly.....	1.25
S-2957	Detector Coil and Shield Assembly.....	1.60

Miscellaneous

19-44	Goat Tube Shield Clips (For Moulded Socket).....	.03
19-50	" " " " " Wafer "	.03
46-87	Small Knob.....	.10
46-88	Large Knob (2 used).....	.10
46-90	Knob (with Color Indicator for Wave Change).....	.15
49-81	6" Dynamic Speaker.....	5.50
	Cone and Voice Coil for 49-81 Speaker.....	2.00
	Output Transformer for 49-81 Speaker.....	1.50
	Field Coil for 49-81 Speaker.....	2.00
57-435	Escutcheon Plate for Dial.....	.40
78-70	Moulded Socket for #80 Tube (Wafer Type #78-82).....	.10
78-91	" " " #75 " (" " #78-101).....	.10
78-92	" " " #42 " (" " #78-102).....	.10
78-96	" " " #6D6 " (" " #78-100).....	.10
78-105	" " " #6A7 " (" " #78-106).....	.10
85-47	Short Wave Selector Switch.....	1.10
85-48	Two-Position Tone Control Switch.....	.35
95-229	25 Cycle - All Voltage Power Transformer.....	6.50
100-23	6.3 Volt Pilot Lamps.....	.15
126-131	Goat Tube Shields.....	.10
S-3021	Power Transformer and Mtg. Plate Assemb. 117 V. 50/60 Cycle	4.00

MODELS 860 and 861

Chassis 5607

Same as Chassis 5605 excepting the following is added:

1	22-185	.01 Mfd. 200 Volt Condenser (Deduct 22-182 from 5605).....	.15
1	49-85	10" Dynamic Speaker (Deduct 49-81 6" Speaker).....	8.50
		Cone and Voice Coil for 49-85 Speaker.....	3.00
		Output Transformer for 49-85 Speaker.....	2.00
		Field Coil for 49-85 Speaker.....	2.00

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
July 13, 1934

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	R.F.	5.7	4.2	5	96	5	98
6A7	1st Det.	5.7	2.3	2	50	-	96
	Osc.			0	-	-	96
6D6	I. F.	5.7	4.1	5	96	5	96
75	2nd Det.	5.7	1.1	5	-	-	25
43	PWR.	24	0	-5	96	-	90
25Z5	RECT.	24	Spkr. Fld. 80	-	-	-	-

Line Voltage 112

Antenna and Ground Disconnected


All voltages measured from B-(negative side of C18) using a 1000 ohm per volt D.C. meter (except heaters).

F - Filament; K - Cathode; g1 - Control Grid; g2 - Screen Grid; g3 - Suppressor Grid; p - Plate.

Alignment

1. Balance intermediate transformers at 125 K.C. with service oscillator connected to grid of first detector and chassis.
2. Rotate wave-band switch clockwise to the short-wave position. Connect service oscillator to antenna and ground leads and set for 18750 K.C. Balance oscillator trimmer on gang for correct dial reading at 16 meters.
3. Turn wave-band switch to center or standard broadcast position. Adjust paddler condenser (located on top center of chassis next to gang) for correct dial reading at 500 meters (600 K.C.).
4. Balance oscillator trimmer (located underneath chassis at right center) for correct dial reading at 210 meters (1440 K.C.). Balance R.F. and 1st detector trimmers on gang to resonance
5. Turn switch counter-clockwise to long-wave position. Adjust oscillator paddler (located underneath chassis at rear right side) for correct dial reading at 2000 meters (150 K.C.).

NOTE: If howls are encountered on short-wave band the oscillator trimmer on gang is too tight.



Tube Position

PARTS AND PRICES

MODEL 812

Chassis 5608

Dial Assembly

12-372	Mtg. Bracket Dial Holder and Drive Shaft Assembly.....	\$.65
26-56	Airplane Dial Scale	.35
27-5	Celluloid Drive Disc and Hub Assembly	.25
59-27	Pointer	.15
73-22	Hex Hd. Set Screw for 27-5	.03
93-207	Cork Cushion Washer for Glass	.05
93-210	Small Celluloid Washer	.01
192-3	Glass	.20

Condensers

22-82	.001 Mfd. 600 Volt	.25
22-127	25 Mmfd. 600 "	.20
22-147	.0005 Mfd. 600 "	.15
22-161	900 - 1500 Mmfd. Padder	.45
22-162	.0001 Mfd. 600 Volt	.20
22-188	.02 " 400 "	.15
22-199	.5 " 200 "	.30
22-219	.03 " 200 "	.12
22-255	.25 " 200 "	.20
22-256	.1 " 200 "	.12
22-276	.01 " 400 "	.15
22-286	.05 " 200 "	.15
22-289	50 Mmfd. 600 "	.12
22-290	Three-gang Variable	3.25
22-305	2 - 35 Mmfd.	.15
22-307	5 -25 Mfd. 150 Volts Electrolytic	2.00
22-308	16 " 100 " "	.85
22-319	.005 " 200 "	.20
22-320	200 - 500 Mmfd.	.35

Resistors

63-244	500 Ohms $\frac{1}{4}$ Watt	.20
63-258	490M " $\frac{1}{4}$ "	.20
63-261	9900 " $\frac{1}{4}$ "	.20
63-278	99M " $\frac{1}{4}$ "	.20
63-280	49M " $\frac{1}{4}$ "	.20
63-293	990M " $\frac{1}{4}$ "	.20
63-295	120M " $\frac{1}{4}$ "	.20
63-326	4M " $\frac{1}{4}$ "	.20
63-362	400 " $\frac{1}{4}$ "	.20
63-366	200M " Volume Control and Switch Assembly	.80
63-372	50M " $\frac{1}{4}$ Watt	.20
63-374	50 " 2 "	.25
63-375	24M " $\frac{1}{4}$ "	.20
63-376	190M " $\frac{1}{4}$ "	.20

Coils

S-3016	Long Wave Oscillator Coil Assembly Complete	.85
S-3019	Detector Coil Assembly Complete	1.35

Coils (Contd.)

S-3020	R. F. Coil Assembly Complete	\$1.35
S-3067	Short Wave Oscillator Coil Assembly Complete	.40
20-76	R. F. Plate Impedance Coil	.25
20-82	Antenna Choke	.25
95-237	1st I. F. Transformer 125 K.C.	1.50
95-238	2nd I. F. " " " "	1.50

Miscellaneous

11-9	Line Cord and Plug Assembly 115 Volt AC-DC	.75
	(For Operation on Other Than 115 Volt see additional)	
19-51	Coat Tube Shield Clips	.03
44-7	Phono Receptacle	.15
46-87	Small Knob (1 used)	.10
46-88	Large Knob (2 used)	.10
46-90	Band Selector Switch Knob	.15
49-87	6" Dynamic Speaker	6.00
	Cone and Voice Coil for 49-87 Speaker	2.00
	Field Coil for 49-87 Speaker	2.00
	Output Transformer for 49-87 Speaker	2.00
57-435	Escutcheon Plate for Dial	.40
78-100	Wafer Type Socket for 6D6 Tube	.10
78-101	" " " " 75 "	.10
78-106	" " " " 6A7 "	.10
79-107	" " " " 43 "	.10
78-108	" " " " 25Z5 "	.10
85-48	Two-position Tone Control Switch	.35
85-56	Phono Switch	.35
85-57	Band Selector Switch	1.25
95-236	Power Filter Choke	.75
126-131	Coat Tube Shield with Ring	.10

Additional

11-6	Stepdown Resistor Cord for 150 Volt Operation	1.25
11-7	" " " " 220 " "	1.25
11-8	" " " " 250 " "	1.25

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
September 14, 1934


2ND DET.
AVC.
15

POWER
4.3

1F.
6-D-6

1F DET.
OSC.
6-A-7

RF
6-D-6



1F. FREQUENCY 252.5 KC.
6 TUBE SUPERHETERODYNE
CHASSIS NO. 5609 AC-D.C.
ZENITH RADIO CORP.
CHICAGO ILL.

MODELS 811-862-865-866-1162

PART DESCRIPTION

QTY	PART	DESCRIPTION
1	C1	22-225 20-100MFD 600V
1	C2	22-225 20-100MFD 600V
1	C3	22-225 20-100MFD 600V
1	C4	22-225 20-100MFD 600V
1	C5	22-225 20-100MFD 600V
1	C6	22-225 20-100MFD 600V
1	C7	22-225 20-100MFD 600V
1	C8	22-225 20-100MFD 600V
1	C9	22-225 20-100MFD 600V
1	C10	22-225 20-100MFD 600V
1	C11	22-225 20-100MFD 600V
1	C12	22-225 20-100MFD 600V
1	C13	22-225 20-100MFD 600V
1	C14	22-225 20-100MFD 600V
1	C15	22-225 20-100MFD 600V
1	C16	22-225 20-100MFD 600V
1	C17	22-225 20-100MFD 600V
1	C18	22-225 20-100MFD 600V
1	C19	22-225 20-100MFD 600V
1	C20	22-225 20-100MFD 600V
1	C21	22-225 20-100MFD 600V
1	C22	22-225 20-100MFD 600V
1	R1	43-225 400 OHMS 1W
1	R2	43-225 400 OHMS 1W
1	R3	43-225 400 OHMS 1W
1	R4	43-225 400 OHMS 1W
1	R5	43-225 400 OHMS 1W
1	R6	43-225 400 OHMS 1W
1	R7	43-225 400 OHMS 1W
1	R8	43-225 400 OHMS 1W
1	R9	43-225 400 OHMS 1W
1	R10	43-225 400 OHMS 1W
1	R11	43-225 400 OHMS 1W
1	R12	43-225 400 OHMS 1W
1	R13	43-225 400 OHMS 1W
1	R14	43-225 400 OHMS 1W
1	R15	43-225 400 OHMS 1W
1	R16	43-225 400 OHMS 1W

TUBE	POSITION	E _f	E _k	E _{g1}	E _{g2}	E _{g3}	E _p
6D6	R.F.	5.8	3		98	3	98
	1st Det.				60	-	98
6A7	Osc.	5.8	2.5	-1	-	-	90
6D6	I.F.	5.8	3		98	3	98
	2nd Det.						
75	A.V.C	5.8	.5		-	-	30
	1st Aud.						
43	PWR.	26	13.5	0	98	-	90
			-30				
25Z5	Rect.	26	-28	-	-	-	-


Line Voltage 112

Antenna and Ground Disconnected

F - Filament; K - Cathode; g1 - Control Grid; g2 - Screen Grid; g3 - Suppressor Grid; p - Plate

Alignment

1. Balance intermediate transformers at 252.5 K.C. with service oscillator connected to grid of 6A7 and chassis ground.
2. Adjust wave trap padder (located underneath chassis at rear right side) for weakest signal with 252.5 K.C. service oscillator connected to antenna and ground.
3. Turn wave-band switch clockwise to the highest frequency band. Set service oscillator at 15 M.C. - still connected to aerial and ground. Balance oscillator trimmer on gang condenser for correct dial reading at this frequency.
4. Turn wave-band switch counter clockwise to standard broadcast position. Adjust broadcast oscillator trimmer (located underneath chassis at right - center) for correct dial reading at 1400 K.C. and adjust R.F. and first detector trimmers on gang condenser for loudest signal.
5. Set service oscillator at 600 K.C. Adjust oscillator broadcast padder through hole in top of chassis, simultaneously rocking the dial back and forth for loudest signal.



Tube Position

PARTS AND PRICES
MODEL 811 - Chassis #5609
" 862 - Chassis #5610
" 1162 - " "

Dial Assembly

12-372	Mtg. Bracket, Dial Holder and Drive Assembly	\$.65
26-64	Airplane Dial Scale	.35
27-5	Celluloid Drive Disc and Hub Assembly	.25
59-27	Special Z pointer	.15
93-207	Cork Cushion Washer for Glass	.05
93-210	Small Celluloid Washer	.01
192-3	Glass	.20

Condensers

22-82	.001	Mfd.	600 V.		.25
22-127	25	Mmfd.	600 V.		.20
22-147	.0005	Mfd.	600 V.		.15
22-162	.0001	"	600 V.		.20
22-188	.02	"	400 V.		.15
22-190	.1	"	200 V.		.20
22-195	10.	"	25 V.		.55
22-199	.5	"	200 V.		.30
22-243	.01	"	400 V.		.15
22-250	.05	"	200 V.		.15
22-290	Three-Gang Variable				3.25
22-292	500-1000 Mmfd.				.45
22-305	2-35 "				.15
22-307	5. x 25.	Mfd.	150 V.		2.00
22-308	16.	Mfd.	100 V.		.85
22-309	75 - 180 Mmfd. Padder				.25
22-319	.005	Mfd.	200 V.		.20
22-338	.004	"	600 V.		.35
22-339	.0017	"	600 V.		.25

Resistors

63-244	500	Ohm	$\frac{1}{2}$ Watt		.20
63-258	490M	"	"		.20
63-260	100M	"	"		.20
63-278	99 M	"	"		.20
63-280	49 M	"	"		.20
63-287	700	"	"		.20
63-293	990M	"	"		.20
63-295	120M	"	"		.20
63-326	4 M	"	"		.20
63-362	400	"	"		.20
63-366	200M	"	Volume Control and Switch Assembly		.90
63-372	50M	"	$\frac{1}{2}$ Watt		.20
63-374	50	"	2 "(Wire Wound).....		.25
63-375	24M	"	$\frac{1}{4}$ "		.20

Coils - Chokes

20-71	Antenna Choke	.20
20-75	Antenna Filter Choke	.25

PARTS AND PRICES

Chassis 5609

5610

Coils - Chokes Contd.

20-76	R.F. Plate Impedance Coil	\$.25
95-247	1st I.F. Transformer (252 K.C.)	1.50
95-248	2nd I.F. " (" " ")	1.50
S-3121	H.F. Oscillator Coil Assembly	.60
S-3122	R.F. Coil Assembly	1.50
S-3123	Police and Broadcast Coil Assembly	1.00
S-3124	Detector Coil Assembly	1.35

Miscellaneous

11-6	Step-down Resistance Cord Assembly 150 V. - 110 V.	1.25
11-7	" " " " " 220 V. - 110 V.	1.25
11-8	" " " " " 250 V. - 110 V.	1.25
11-9	Regular 110 V. AC-DC Line Cord and Plug	.75
44-7	Phono Jack (European Models Only)	.15
46-87	Small Knob	.10
46-88	Large Knob	.10
46-90	Band Selector Knob	.15
49-93	6" Dynamic Speaker (Model 811 only)	6.50
	Cone and Voice Coil for 49-93 Speaker	2.00
	Output Transformer for 49-93 speaker	2.00
	Field Coil for 49-93 speaker	2.00
49-94	12" Dynamic Speaker (Models 862, 1162)	10.00
	Cone and Voice Coil for 49-94 Speaker	3.25
	Output Transformer for 49-94 Speaker	2.00
	Field Coil for 49-94 Speaker	2.00
57-435	Escutcheon Plate	.40
78-100	Tube Socket 6D6	.10
78-101	" " 75	.10
78-106	" " 6A7	.10
78-107	" " 43	.10
78-108	" " 25Z5	.10
85-48	Two-Position Tone Control Switch	.35
85-56	Phono Switch (European Models Only)	.35
85-57	Band Selector Switch	1.25
95-249	Power Filter Choke	1.00
100-23	6.3 V. Pilot Lamps	.15
126-131	Goat Tube Shield	.10

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. ALSO ALL PRICES QUOTED HERE SUPERSEDE PREVIOUS QUOTATIONS IN OTHER PARTS LISTS FOR LIKE PARTS.

ZENITH RADIO CORPORATION

October 19, 1934

SOCKET VOLTAGES

Chassis 5502

TUBE	POSITION	E _f	E _k	E _{g1}	E _{g2}	E _{g3}	E _p
6F7	Mixer	5.8	8	0	76	--	240
	Osc.			1		-	125
6D6	I.F.	5.8	2.3	0	76	2.3	240
75	Det.	5.8	1.2	0	--	--	130
42	Pwr.	5.8	0	-10	240	--	220
80	Rect.	4.6	--	--	--	--	--


Line Voltage 112 V.

Ant. and Gnd. Disconnected.

f - filament; k - cathode; g1 - control grid; g2 - screen grid; g3 - suppressor grid; p - plate.

All measurements taken from points indicated to ground with a 1,000 ohms per volt D.C. meter (except filaments).

Balance I. F. transformers at 252.5 K.C.; trimmers on gang at 1500 K.C.; and oscillator padder at 600 K.C., with wave switch on broadcast position. No adjustments necessary on short wave bands.



PARTS AND PRICES
MODEL 805 - 845
Chassis 5502

Condensers

22-82	.001	Mfd.	500 Volt	(1st Audio Plate).....	\$.25
22-125	8.	"	440 "	(Filter).....	1.00
22-170	.1	"	400 "	(1st Audio Plate).....	.25
22-182	.000025	"	600 "	(A.V.C. By-Pass).....	.12
22-185	.01	"	200 "	(2nd Detector Cathode).....	.15
22-188	.02	"	400 "	(1st & 2nd Audio Coupling).....	.15
22-250	.05	"	200 "	(1st Det., I.F. Cathode, & A.V.C.).....	.15
22-276	.01	"	400 "	(Oscillator Plate).....	.15
22-285	10	Mmfd.	600 "	(Oscillator Tuned Circuit).....	.15
22-287	.03	Mfd.	600 "	(Tone Control).....	.15
22-290	Three-Gang Variable.....				3.25
22-292	Padder.....				.45
22-293	2600	Mmfd.	600 Volt	(Oscillator Padder).....	.30

Resistors

63-245	1500	Ohm	$\frac{1}{4}$ Watt	(1st Det. Cathode).....	.20
63-258	490M	"	$\frac{1}{4}$ "	(A.V.C. Filter).....	.20
63-278	99M	"	$\frac{1}{4}$ "	(1st Audio Plate).....	.20
63-290	260M	"	$\frac{1}{4}$ "	(Oscillator Grid).....	.20
63-291	29M	"	$\frac{1}{4}$ "	(Oscillator Plate).....	.20
63-293	990M	"	$\frac{1}{4}$ "	(Power & 1st Audio Grids).....	.20
* 63-296	220M	"	$\frac{1}{4}$ "	(Diode - See Footnote).....	.20
63-351	Candohm Voltage Divider				.65
63-353	19M	Ohm	$\frac{1}{4}$ Watt	(Tone Control).....	.20
63-355	51M	"	$\frac{1}{4}$ "	(Oscillator Grid).....	.20
* 63-356	Volume Control & Switch Assembly (Terminal Type).....				.80
63-357	300	Ohm	$\frac{1}{4}$ Watt	(I.F. Cathode).....	.20
63-366	Volume Control & Switch Assembly (Wire-Lead Type).....				.90

Coils

S-2931	Oscillator Coil Assembly Complete with Can.....				1.00
S-2933	Selector	"	"	" "	1.75
95-227	1st I. F. Transformer	"	"	" "	1.50
95-230	2nd I.F. Transformer	"	"	" "	1.50

Miscellaneous

19-44	Goat Tube Shield Clip (for Moulded Sockets).....				.03
19-50	"	"	"	(for Wafer Sockets).....	.03
46-82	Control Knobs.....				.10
26-49	Dial Assembly Complete				.75

- * 63-296 Used only in sets incorporating 63-356 Volume Controls
63-356 " " " " " 63-296 Resistors

Miscellaneous Cont'd

49-81	6" Dynamic Speaker.....	\$5.50
	Cone and Voice Coil for 49-81 Speaker.....	2.00
	Output Transformer " " " ".....	1.50
	Field Coil " " " ".....	2.00
57-436	Escutcheon Plate for Dial.....	.25
78-70	Modlled Socket for #80 Tube (Wafer Type 78-82).....	.10
78-91	" " " #75 " (" " 78-101).....	.10
78-92	" " " #42 " (" " 78-102).....	.10
78-96	" " " #6D6 " (" " 78-100).....	.10
78-97	" " " #6F7 " (" " 78-103).....	.10
85-48	Two Position Tone Control Switch.....	.35
85-53	Wave-Change Switch.....	.60
100-23	6 V.- 8 V. Pilot Lamp.....	.15
126-123	Goat Tube Shields with Rings.....	.10
* S-302	117 V. 50-60 Cycle Power Transformer (Upright Type).....	4.00
95-229	25 Cycle, All Voltage, Power Transformer.....	6.50

* First production models used inverted type. Replace with upright type transformer with mounting plate.

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.


ZENITH RADIO CORPORATION
June 28, 1934.

2ND DET.
A.V.C.
1ST A.F.
7-5

POWER
4-2

I.F.
6-D-6

1ST DET.
OSC.
6-A-7



TWO BANDS { 538 KC - 1550 KC
5610 KC - 17850 KC

I.F. FREQUENCY 252.5 K.C.
5 TUBE SUPERHETERODYNE
CHASSIS NOS. 5504 & 5505
ZENITH RADIO CORP.
CHICAGO ILL.

MODELS 806-807-S847-850

DIAG PART NO. DESCRIPTION

C1	22-250	365 MFD. 100V
C2	22-250	.05 MFD. 500V
C3	22-250	.05 MFD. 500V
C4	22-310	2 MFD. 200V
C5	22-182	200000 - 600V
C6	22-312	.01 - 200V
C7	22-188	.02 - 400V
C8	22-82	.001 - 500V
C9	22-170	.1 - 400V
C10	22-287	.03 - 600V
C11	22-82	.001 - 500V
C12	22-305	2-35 MFD. 100V
C13	22-292	.001 MFD. 400V
C14	22-125	8 - 440V
C15	22-229	.005 - 600V
R1	63-270	99M OHMS 1/2W
R2	63-357	300M - 1/2W
R3	63-258	480M - 1/2W
R4	63-253	550M - 1/2W
R5	63-353	19M - 1/2W
R6	63-373	11M - 1/2W
R7	63-366	200M - 1/2W
R8	63-351	170000 - 1/2W
1	3-3042	SELECTOR-DET. COIL
2	85-55	SMART WAVE SWITCH
3	3-3040	OSC. COIL ASSEM.
4	35-244	181/2" TRANS.
5	35-245	200/1" TRANS.
6	40-81	200/1" TRANS.
7	40-81	SPEAKER 1000 OHM FIELD
8	85-48	1000 OHM FIELD
9	35-234	POWER TRANS. 30-40 CYCLE
10	35-229	25 CYCLE

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6A7	1st Det.	5.8	5.2	0	80	-	260
	Osc.			.6	-	-	210
6D6	I.F.	5.8	5.2	0	80	5.2	260
75	2nd Det.	5.8	1.5	0	-	-	135
42	PWR.	5.8	0	-.7	260	-	245
80	RECT.	4.8	-	-	-	-	-

Line Voltage 112


Antenna and Ground Disconnected

All measurements taken from point indicated to ground, using a 1000 ohm per volt D.C. meter (except filaments).

F - Filament; K - Cathode; g1 - Control Grid; g2 - Screen Grid; g3 - Suppressor Grid; p - Plate.

Alignment

1. Balance I.F. transformers at 252.5 K.C. with test oscillator connected to control grid of 6A7 and ground.
2. Connect test oscillator to antenna and ground leads.
3. Adjust broadcast padder (located next to gang on top of chassis) for correct dial reading at 600 K.C.
4. Adjust trimmer on oscillator section of gang for correct dial reading at 15 M.C. Adjust detector trimmers (located between gang and coil shield on top of chassis) for maximum signal.
5. Adjust oscillator trimmer (located on right side underneath chassis) for correct dial reading at 1400 K.C. - also adjust preselector and detector trimmers on gang for maximum signal.
6. Readjust broadcast padder for correct dial setting.



Tube Position

PARTS AND PRICES
MODEL 806
Chassis 5504

MODELS 806, S-847,
807, 850

Condensers

22-82	.001	Mfd.	500 Volt (1st Audio Plate, Osc. Plate).....	\$.25
22-125	8.	"	440 Volt (Filter).....	1.00
22-127	25	Mmfd.	500 Volt (Osc. Grid.).....	.15
22-170	.1	Mfd.	400 Volt (1st Audio bypass).....	.25
22-182	.000025	"	600 Volt (A.V.C. Bypass).....	.12
22-188	.02	"	400 Volt (1st & 2nd Audio Coupling).....	.15
22-229	.005	"	600 Volt (Osc. Grid).....	.15
22-250	.05	"	200 Volt (1st Det. I. F. Screen, A.V.C.).....	.15
22-287	.03	"	600 Volt (Tone Control).....	.15
22-290	Three-gang variable			3.25
22-292	Padder			.45
22-305	.35	Mmfd.	Padder (Osc. Grid).....	.15
22-310	.2	Mfd.	200 Volt (1st I.F. Cathode).....	.15
22-312	.01	"	200 Volt (2nd Detector Cathode).....	.10

Resistors

63-258	490 M Ohms	$\frac{1}{4}$ Watt	(A.V.C. Filter).....	.20
63-278	99 M "	$\frac{1}{4}$ Watt	(1st Aduio Plate, Osc. Grid).....	.20
63-293	990 M "	$\frac{1}{4}$ Watt	(Power & 1st Audio Grid).....	.20
63-351	Candohm Voltage Divider			.65
63-353	19 M Ohms	$\frac{1}{4}$ Watt	(Tone Control).....	.20
63-357	300 "	$\frac{1}{4}$ Watt	(I.F.Cathode & 1st Detector Cathode).....	.20
63-366	Volume Control and Switch			.90
63-373	11 M Ohms	$\frac{1}{2}$ Watt	(Osc. Plate).....	.25

Coils

S-3048	Oscillator Coil and Shield Assembly			1.00
S-3049	Selector Coil and Shield Assembly			1.75
95-227	1st I. F. Transformer Complete with Shield			1.50
95-230	2nd I. F. Transformer " " "			1.50

Miscellaneous

19-51	Goat Tube Shield Clips.....			.03
46-82	Control Knobs (4 used).....			.10
49-81	6" Dynamic Speaker			5.50
	Cone and Voice Coil for 49-81 Speaker			2.00
	Output Transformer for 49-81 Speaker			1.50
	Field Coil for 49-81 Speaker			2.00
57-436	Escutcheon Plate for Dial			.25
78-82	Wafer Socket for Type 80 Tube			.10
78-100	"	"	" " 6D6 "	.10
78-101	"	"	" " 75 "	.10
78-102	"	"	" " 42 "	.10
78-106	"	"	" " 6A7 "	.10
85-48	Two-position Tone Control Switch			.35
85-55	Wave Change Switch			.35
95-229	25 Cycle all-voltage Power Transformer			6.50

PARTS AND PRICES
PAGE No. 2

MODELS 806, S-847
807, 850

Miscellaneous Contd.

100-23	6.3 Volt Pilot Lamp	\$.15
126-131	Goat Tube Shield with Rings	.10
S-2940	Speaker Cord Assembly	.20
S-3021	#95-234 Power Transformer and Mtg. Plate - 117 V. - 60 Cycle.	4.00
S-3061	Dial Strip and Drive Assembly	.85

MODEL S-847

Chassis 5507

Same as Chassis 5504 less #49-81 Speaker and with #49-79 Speaker Added

49-79	8" Dynamic Speaker	8.00
	Cone and Voice Coil for #49-79 Speaker	2.50
	Output Transformer " " " "	2.00
	Field Coil " " " "	2.00

MODEL 807

Chassis 5506

Same as Chassis 5504 less S-3061 Dial, 46-82 Knobs and 57-436 Escutcheon and addition of the following:

12-372	Tuning Shaft, Bracket and Frame Assembly	.65
26-54	Dial Scale	.25
27-5	Celluloid Drive Disc and Hub Assembly	.25
46-87	Small Knob (1 used)	.10
46-88	Large Knob (3 used)	.10
57-435	Escutcheon Plate for Airplane Dial	.40
59-27	Pointer for Dial	.15
73-22	Set Screw for 27-5	.03
93-207	Cork Cushion Washer for Glass	.05
192-3	Glass for Dial	.20

MODEL 850



Chassis 5505

Same as Chassis 5506 less 49-81 Speaker and addition of 49-79 Speaker

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
September 12, 1934

SERVICE MANUAL MODEL 801



INTERMEDIATE FREQUENCY 456 K. C.

SERVICE SUGGESTIONS:

NOTE—CONNECTING CORD OF SET GETS WARM IN NORMAL OPERATION. DO NOT BECOME ALARMED.

Make sure that all tubes are pushed firmly in their proper sockets and that the clips are securely fastened to the caps on the tops of the tubes.

That the aerial is stretched out and that the connections to an outdoor antenna (if used) are good.

If necessary to change tubes or service chassis. UNDER NO CIRCUMSTANCES REMOVE BACK OR CHASSIS WITHOUT FIRST REMOVING PLUG FROM LIGHT SOCKET.

To remove chassis from cabinet, pull off knobs from front, remove back (held with screws to case). Remove four mounting screws, then chassis can be slipped out of case.

ZENITH RADIO CORPORATION

3620 Iron Street

Chicago, Illinois



SERVICE NOTES

Should it be at any time necessary to rebalance this set, the correct procedure is as follows:

1. Volume control on full during all alignment.
2. Variable condenser in minimum capacity position, plates open, at start of all aligning.

I.F. ALIGNMENT

1. To peak I.F. transformers, connect oscillator set at 456 kilocycles to the grid of the 6D6 tube directly in back of the variable condenser and adjust the trimming condensers of the I.F. transformers to resonance (Maximum deflection on an output meter connected across the primary of the speaker input transformer).

Each I.F. trimmer has two adjustments, one nut and one screw, both of which are adjustable from the top.

BROADCAST BAND ALIGNMENT

1. Disconnect antenna wire and connect oscillator in series with a 75 mmfd. condenser to the antenna coil. With the variable condenser set at its minimum capacity position, at the extreme right of its rotation, and with an oscillator output adjusted to 1720 kilocycles, adjust trimmer of oscillator section of variable condenser (rear section) to resonance (maximum deflection on an output meter connected across the primary of the speaker input transformer). Next adjust the trimmer condenser of the front section of the variable condenser to resonance.
2. Check alignment at 1400-1200-1000-800-600-530 kilocycles, bending the slotted plates of the front section of the variable condenser only if absolutely necessary.

PARTS LIST

When ordering parts, always specify part and model number as well as serial number of chassis.

<u>Part No.</u>	<u>Description</u>	<u>List Price</u>	<u>Part No.</u>	<u>Description</u>	<u>List Price</u>
101-1	Volume Control with Switch	1.35 ea.	W-427	Aerial Wire (20 Ft.)	.30 ea.
106-1	40 Ohm Resistor-10%	.30 ea.	1101	Pilot Light Socket	.10 ea.
107-1	126 Ohm Special Cord and Plug	1.25 ea.	1116	Two Gang Variable Condenser	2.50 ea.
C-523	600 Ohm Choke	1.25 ea.		All Carbon Resistors	.20 ea.
C-524A	Antenna Coil	.80 ea.		All Single Section Tubular Paper By-Pass Cond.	.25 ea.
C-524B	Oscillator Coil	.70 ea.		All Dual Section Tubular Paper By-Pass Condensers	.50 ea.
C-524C	Input I.F. Transformer	1.25 ea.		All Molded Mica Condensers.	.25 ea.
C-524D	Output I.F. Transformer	1.25 ea.		All Sockets	.20 ea.
C-525C	5-25 Mfd. Electrolytic Condenser	1.50 ea.		Dynamic Speaker	5.00 ea.
C-525D	5 Mfd. Electrolytic Condenser	.50 ea.		Cabinet	6.00 ea.
R-268	2480 Ohm Resistor	.50 ea.		Carrying Case	2.50 ea.
R-270	250 Ohm Wire Wound Resistor	.25 ea.		Adapters for 220 Volt Operation	2.25 ea.

Prices subject to change without notice.

All resistors are RMA color coded - specify value and/or resistor number (per schematic diagram) and model number.

When ordering condensers, specify part number, model number and/or capacitor (per schematic diagram) and model number.



PARTS AND PRICES
Chassis #5614

MODELS 908
960
961
1117

Dial Assembly

S-3421	Complete Split Second Dial Assembly	\$3.75
26-79	Dial Scale Only	.40
59-32	Split Second Pointer	.10
59-33	Special "Z" Pointer	.20
93-231	Glass Cushion Washer	.05
192-6	Dial Glass	.20

Resistors

63-258	490 M Ohm $\frac{1}{4}$ Watt	.20
63-271	1 Megohm $\frac{1}{4}$ Watt	.20
63-278	99 M Ohm $\frac{1}{4}$ Watt	.20
63-280	49 M Ohm $\frac{1}{4}$ Watt	.20
63-295	120 M Ohm $\frac{1}{4}$ Watt	.20
63-316	50 M Tone Control	.65
63-351	17,035 Ohm Candohm	.65
63-353	19 M Ohm $\frac{1}{2}$ Watt	.20
63-355	51 M Ohm $\frac{1}{4}$ "	.20
63-357	300 Ohm $\frac{1}{4}$ "	.20
63-362	400 " $\frac{1}{4}$ "	.20
63-366	200 M Volume Control Assembly	.90
63-373	11 M Ohm $\frac{1}{2}$ Watt	.25

Condensers

22-82	.001 Mfd. 600 Volt	.25
22-147	.0005 " " "	.15
22-170	.1 " 400 "	.25
22-182	.00025 " 600 "	.12
22-185	.01 " 200 "	.15
22-188	.02 " 400 "	.15
22-229	.005 " 600 "	.15
22-250	.05 " 200 "	.15
22-287	.03 " 600 "	.15
22-289	50 Mmfd 600 "	.12
22-292	.001 Mfd. Padder	.45
22-304	.0036 " 600 Volt	.30
22-305	2 - 35 " Padder	.15
22-309	75 - 180 Mmfd. Variable Padder	.25
22-380	Variable Condenser Assembly	3.50
22-385	8 x 8 x 2 Mfd. Filter Condenser	2.00

Coils and Chokes

20-71	Antenna Choke	.20
20-75	Wave Trap Choke	.25
95-244	1st I.F. Transformer	1.50
95-245	2nd I.F. Transformer	1.50
S-2957	Detector Coil Assembly	1.60

PARTS AND PRICES
PAGE No.2

MODELS 908
960
961
1117

Coils and Chokes Cont'd

S-2955	Antenna Coil Assembly	\$1.25
S-2953	Oscillator Coil Assembly	1.00

Miscellaneous

46-108	Band Selector Switch Knob (960-961)	.15
46-109	Tuning Control Knob	.10
46-110	Tone Control Knob	.10
46-111	Volume Control Knob	.10
46-112	Band Selector Switch Knob (908)	.15
49-79	8" Dynamic Speaker for Model 908	8.00
	Cone and Voice Coil for 49-79	2.50
	Output Transformer for 49-79	2.00
	Field Coil for 49-79	2.00
49-85	10" Dynamic Speaker	8.50
	Cone and Voice Coil for 49-85	3.00
	Output Transformer for 49-85	2.00
	Field Coil for 49-85	2.00
57-483	Dial Escutcheon Plate	.45
78-82	Type 80 Tube Socket	.10
78-100	Type 6D6 " "	.10
78-101	Type 75 " "	.10
78-102	Type 42 " "	.10
78-103	Type 6A7 " "	.10
85-47	Wave Change Switch	1.10
85-56	Phono Switch (25 Cycle only)	.35
95-229	All Voltage 25 Cycle Power Transformer	6.50
95-234	117 Volt 50/60 Cycle Power Transformer	3.75
100-23	Pilot Lamp	.15
126-131	Goat Tube Shield	.10

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.


ZENITH RADIO CORPORATION
January 31, 1935

2ND DET.
F.V.C.
1ST A.F.
75

I.F.
G-D-G

1ST DET.
O.S.C.
G-H-7

1ST R.F.
G-D-G



6TUBE SUPERHETERODYNE
I.F. FREQUENCY 252.5 KC.
CHASSIS No 5618

ZENITH RADIO CORP.
CHICAGO, ILL.

MODELS 5908 - 5961

DIAG PART

DESCRIPTION

No	No	DESCRIPTION
C1	22-82	.001 MFD. 600K
C2	22-316	.0021 - 600K
C3	22-350	.05 - 600K
C4	22-382	.24 MFD. 600K
C5	22-305	2-35 MFD. PHOSPHOR
C6	22-384	.0015 MFD. 600K
C7	22-188	.02 MFD. 400K
C9	22-165	.01 - 200K
C10	22-182	.00025 MFD. 600K
C11	22-170	.1 - 400K
C12	22-287	.03 - 600K
C13	22-359	350-750 MFD. PHOSPHOR
C14	22-309	75 - 180 - 600K
C15	22-147	.0005 MFD. 600K
C16	22-386	.43 MFD. 600K
C17	22-387	.0019 MFD. 600K
C18	22-385	.2 MFD. 450V
C19	22-385	.2 MFD. 450V
C20	22-385	.8 MFD. 450V

1535-40	ANT. COIL ASSEMBLY
2 85-61	SHORT WAVE SWITCH
3 535-42	DET. COIL ASSEMBLY
4 535-36	O.S.C.
5 95-244	1ST I.F. TRANS.
6 95-245	2ND I.F.
7 49-79	SPEAKER-1000-ohm FIELD (5908)
8 535-65	POWER TRANS. 25 CYCLE.
9 95-234	ANT. CHOKE
10 95-229	11 20-71
11 20-71	WAVE TRAP CHOKE
12 20-75	PHONO-RADIO SWITCH
13 85-56	PHONO-JACK
14 44-7	12-5 FEATHER 1000-ohm FIELD (5961)
15 49-97	

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	R.F.	5.6	2.4	0	70	2.4	200
6A7	1st.Det.			0	70	-	250
	Osc.	5.6	3	3.6	-	-	230
6D6	I.F.	5.6	2.6	0	70	2.6	250
75	2nd.Det.						
	1st Audio	5.6	1.4	0	-	-	148
42	PWR.	5.6	0	- .6	250	-	250
80	RECT.	4.6	-	-	-	-	-


Line Voltage 112

Antenna and Ground Disconnected

All measurements taken from point indicated to ground, using a 1000 ohm per volt D.C. meter (except heaters). F - filament; K - cathode; g1 - control grid; g2 - screen grid; g3 - suppressor grid; p - plate.

Alignment

1. Balance intermediate transformers at 252.5 K.C. with oscillator connected to grid of first detector and ground.
2. Adjust wave trap padder (located underneath chassis at rear right side) for weakest signal with 252.5 K.C. oscillator connected to aerial and ground.
3. Turn wave band switch clockwise to the highest frequency band. Connect 17,500 K.C. oscillator to aerial and ground. Balance oscillator trimmer on three-gang condenser for correct dial reading at this frequency.
4. Turn wave band switch counter-clockwise to standard broadcast position. Adjust broadcast oscillator trimmer (located underneath chassis at right center) for correct dial reading at 1400 K.C. and balance R.F. and 1st detector trimmers on three-gang condenser for loudest signal.
5. Adjust oscillator padder (located next to oscillator section of gang on top of chassis) while rocking pointer back and forth past 600 K.C. for combination giving maximum output.
6. Recheck 1400 K.C.



TUBE-POSITION

Tube Position

PARTS AND PRICES

Models S-908

909

Chassis 5618

S-961

1167

Dial Assembly

S-3552	Complete split second dial assembly	\$3.75
26-84	Dial scale only	.40
59-32	Split second pointer	.10
59-33	Special Z pointer	.20
93-231	Glass cushion washer	.05
192-6	Dial glass	.20

Resistors

63-258	490 M ohms	$\frac{1}{4}$ Watt		.20
63-271	1 Megohm	"		.20
63-278	99 M ohm	"		.20
63-280	49 M "	"		.20
63-295	120 M "	"		.20
63-316	Tone control (50 M ohms)			.65
63-351	17,035 ohm candohm			.65
63-353	19 M "	$\frac{1}{2}$ Watt		.20
63-355	51 M "	"		.20
63-357	300 "	"		.20
63-362	400 "	"		.20
63-366	Volume control assembly (200 M ohm)			.90
63-373	11 M ohm	$\frac{1}{2}$ Watt		.25

Condensers

22-82	.001 Mfd.	600 V.		.25
22-147	.0005 "	600 V.		.15
22-170	.1 "	400 V.		.25
22-182	.00025 "	600 V.		.12
22-185	.01 "	200 V.		.15
22-188	.02 "	400 V.		.15
22-250	.05 "	200 V.		.15
22-287	.03 "	600 V.		.15
22-305	2-35 Mfd.	Padder		.15
22-309	75-180 "	"		.25
22-359	350-750 "	"		.45
22-376	.0021 Mfd.	600 V.		.20
22-382	24 Mfd.	600 V.		.15
22-384	.0015 Mfd.	600 V.		.20
22-385	8-2-8 Mfd.	450 V. filter		2.00
22-386	Variable gang assembly			3.50
22-387	.0019 Mfd.	600 V.		.20

Coils and Chokes

20-71	Antenna Choke	.20
20-75	Wave trap choke	.25
95-244	1st I.F. transformer	1.50
95-245	2nd I.F. transformer	1.50
S-3536	Oscillator coil assembly	1.25

PARTS AND PRICES
PAGE No.2

Models S-908, 909, S-961, 1167
Chassis 5618

Coils and Chokes (Cont'd)

S-3540	Antenna coil assembly	\$1.75
S-3542	Detector " "	2.00
Miscellaneous		
46-108	Band selector switch knob (Models 909, S-961, 1167).....	.15
46-109	Tuning control knob	.10
46-110	Tone control knob	.10
46-111	Volume control knob	.10
46-112	Band selector switch knob (Model S-908)	.15
49-79	8" Dynamic speaker for S-908, 909	8.00
	Cone and voice coil for 49-79	2.50
	Output transformer for 49-79	2.00
	Field coil for 49-79	2.00
49-97	12" Dynamic speaker for S-961, 1167	10.00
	Cone and voice coil for 49-97	3.25
	Output transformer for 49-97	2.00
	Field coil for 49-97	2.00
57-483	Dial escutcheon plate	.45
78-82	Type 80 tube socket	.10
78-100	" 6D6 " "	.10
78-101	" 75 " "	.10
78-102	" 42 " "	.10
78-106	" 6A7 " "	.10
85-56	Phono switch (25 cycle)	.35
85-61	Band selector switch	1.10
95-229	All voltage, 25 cycle power transformer	6.50
100-23	Pilot lamp	.15
126-131	Goat tube shield	.10
S-3021	#95-234 power transformer and mounting plate, 117 V., 60 C.	4.00

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
MARCH 13, 1935

TUBE	POSITION	Rf	Rk	Eg1	Eg2	Eg3	Ep
6A7	1st Det.	5.8	4	0	80	-	260
	Osc.			.6	-	-	210
6D6	I.F.	5.8	5.2	0	80	5.2	260
75	2nd Det.	5.8	1.5	0	-	-	135
42	PWR.	5.8	0	-.7	260	-	245
80	RECT.	4.8	-	-	-	-	-

Line Voltage 112


Antenna and Ground Disconnected.

All measurements taken from point indicated to ground, using a 1000 ohm per volt D.C. meter (except filaments).

F- Filament; K - Cathode; G1 - Control Grid; G2 - Screen Grid; G3 - Suppressor Grid; P - Plate

Alignment

1. Balance I.F. transformers at 252.5 K.C. with test oscillator connected to control grid of 6A7 and ground.
2. Turn band switch to C band. Connect test oscillator to antenna and ground leads. Set test oscillator at 15 Megacycles. Adjust oscillator trimmer on gang condenser for correct dial reading.
3. Adjust detector trimmer (located on top of chassis between front section of gang condenser and coil) for maximum output.
4. Turn band switch to A band. Adjust oscillator trimmer (located on right side underneath chassis) for correct dial reading at 1400 K.C. also adjust preselector and detector trimmers on gang for maximum output.
5. Adjust oscillator padder (next to oscillator section of gang on top of chassis) while rocking pointer back and forth past 600 K.C. to the combination giving greatest output.
6. Recheck 1400 K.C.



TUBE POSITION



PARTS AND PRICES
Chassis #5508 & #5509

MODELS 945, 950

Dial Assembly

S-3403	Complete Split Second Dial Assembly.....	\$3.75
26-78	Dial Scale Only	.40
59-27	Special "Z" Pointer	.15
59-32	Split Second Pointer	.10
93-231	Dial Glass Cushion Washer.....	.05
192-6	Dial Glass	.20

Resistors

63-258	490 M Ohm $\frac{1}{4}$ Watt	.20
63-278	99 M Ohm $\frac{1}{4}$ Watt	.20
63-280	49 M Ohm $\frac{1}{4}$ Watt	.20
63-293	990 M Ohm $\frac{1}{4}$ Watt	.20
63-316	50 M Ohm Tone Control	.65
63-351	17,035 Ohm Candohm	.55
63-353	19 M Ohm $\frac{1}{2}$ Watt	.20
63-366	200 M Volume Control Assembly	.90
63-373	11 M Ohm $\frac{1}{2}$ Watt	.25
63-377	170 Ohm $\frac{1}{4}$ Watt	.20

Condensers

22-82	.001 Mfd. 600 volt	.25
22-125	8 " 440 "	1.00
22-127	25 Mmfd. 600 "	.20
22-170	.1 Mfd. 400 "	.25
22-182	.00025 Mmfd. 600 Volt	.12
22-185	.01 Mfd. 200 Volt	.15
22-188	.02 " 400 "	.15
22-199	.5 " 200 "	.35
22-243	.01 " 400 "	.15
22-250	.05 " 200 "	.15
22-292	500-1000 Mmfd. Padder	.45
22-304	.0036 Mmfd. 600 Volt	.30
22-305	2 - 35 Mmfd. Padder	.15

Coils, Etc.

95-244	1st I.F. Transformer	1.50
95-245	2nd I.F. Transformer	1.50
S-3129	Oscillator Coil Assembly	1.00
S-3397	Selector Detector Coil Assembly	2.00
S-3377	16 Meter Detector Coil Assembly	.65

Miscellaneous

46-108	Band Selector Knob	.15
46-109	Tuning Control Knob	.10
46-110	Tone Control Knob	.10
46-111	Volume Control Knob	.10

PARTS AND PRICES
PAGE No.2

MODELS 945, 950

Miscellaneous Cont'd

49-79	8" Dynamic Speaker for Model 945	\$8.00
	Cone and Voice Coil for Model 945	2.50
	Output Transformer for Model 945	2.00
	Field Coil for Model 945	2.00
49-85	10" Dynamic Speaker for Model 950	8.50
	Cone and Voice Coil for Model 950	3.00
	Output Transformer for Model 950	2.00
	Field Coils for Model 950	2.00
57-483	Dial Escutcheon Plate	.45
78-82	Type 80 Tube Socket	.10
78-100	" 6D6 " "	.10
78-101	" 75 " "	.10
78-102	" 42 " "	.10
78-106	" 6A7 " "	.10
85-62	Wave Change Switch	.80
95-229	Power Transformer 25 Cycle	6.50
95-234	Power Transformer 50/60 Cycle	3.75
100-23	6.3 Volt Pilot Lamp	.15
126-131	Goat Tube Shield	.10

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

January 31, 1935

ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

WARRANTY

The Zenith Radio Corporation guarantees each new ZENITH receiver and each new ZENITH QUALITY TUBE to be free from defects in workmanship and material.

Our obligation under this warranty is limited to making good at our factory any part or parts of the receiver which within ninety days from date of purchase shall be returned to us with transportation charges prepaid and which on examination shall be found to our satisfaction to have been thus defective. The ZENITH QUALITY TUBES used in this receiver are guaranteed against mechanical and electrical defects under the same warranty as the receiver. This warranty is expressly in lieu of all other warranties expressed or implied, and we neither assume nor authorize any representative or other person to assume for us any other liability in connection with the sale of ZENITH receivers or ZENITH QUALITY TUBES.


This warranty shall not apply to any receiver or tube which shall have been repaired or altered outside of our factory in any way so as, in our judgment, to affect its stability or reliability, nor which has been subject to misuse, negligence or accident, nor which has had the serial number or name altered, defaced or removed. Neither shall this warranty apply to any receiver in which other than ZENITH QUALITY TUBES have been used.

ZENITH RADIO CORPORATION.

50
I.F.

2A7
1ST DET-OSC

50
R.F.



DR. PART DESCRIPTION

No.	Part	Description
1	53399	RF COIL
2	53399	1ST DET. COIL
3	53399	OSC. COIL
4	53399	1ST AUDIO COIL
5	53399	2ND AUDIO COIL
6	53399	1ST AUDIO CHOME
7	53399	2ND AUDIO CHOME
8	53399	1ST AUDIO CHOME
9	53399	2ND AUDIO CHOME
10	53399	1ST AUDIO CHOME
11	53399	2ND AUDIO CHOME
12	53399	1ST AUDIO CHOME
13	53399	2ND AUDIO CHOME
14	53399	1ST AUDIO CHOME
15	53399	2ND AUDIO CHOME
16	53399	1ST AUDIO CHOME
17	53399	2ND AUDIO CHOME
18	53399	1ST AUDIO CHOME
19	53399	2ND AUDIO CHOME
20	53399	1ST AUDIO CHOME
21	53399	2ND AUDIO CHOME
22	53399	1ST AUDIO CHOME
23	53399	2ND AUDIO CHOME
24	53399	1ST AUDIO CHOME
25	53399	2ND AUDIO CHOME
26	53399	1ST AUDIO CHOME
27	53399	2ND AUDIO CHOME
28	53399	1ST AUDIO CHOME
29	53399	2ND AUDIO CHOME
30	53399	1ST AUDIO CHOME
31	53399	2ND AUDIO CHOME
32	53399	1ST AUDIO CHOME
33	53399	2ND AUDIO CHOME
34	53399	1ST AUDIO CHOME
35	53399	2ND AUDIO CHOME
36	53399	1ST AUDIO CHOME
37	53399	2ND AUDIO CHOME
38	53399	1ST AUDIO CHOME
39	53399	2ND AUDIO CHOME
40	53399	1ST AUDIO CHOME
41	53399	2ND AUDIO CHOME
42	53399	1ST AUDIO CHOME
43	53399	2ND AUDIO CHOME
44	53399	1ST AUDIO CHOME
45	53399	2ND AUDIO CHOME
46	53399	1ST AUDIO CHOME
47	53399	2ND AUDIO CHOME
48	53399	1ST AUDIO CHOME
49	53399	2ND AUDIO CHOME
50	53399	1ST AUDIO CHOME
51	53399	2ND AUDIO CHOME
52	53399	1ST AUDIO CHOME
53	53399	2ND AUDIO CHOME
54	53399	1ST AUDIO CHOME
55	53399	2ND AUDIO CHOME
56	53399	1ST AUDIO CHOME
57	53399	2ND AUDIO CHOME
58	53399	1ST AUDIO CHOME
59	53399	2ND AUDIO CHOME
60	53399	1ST AUDIO CHOME
61	53399	2ND AUDIO CHOME
62	53399	1ST AUDIO CHOME
63	53399	2ND AUDIO CHOME
64	53399	1ST AUDIO CHOME
65	53399	2ND AUDIO CHOME
66	53399	1ST AUDIO CHOME
67	53399	2ND AUDIO CHOME
68	53399	1ST AUDIO CHOME
69	53399	2ND AUDIO CHOME
70	53399	1ST AUDIO CHOME
71	53399	2ND AUDIO CHOME
72	53399	1ST AUDIO CHOME
73	53399	2ND AUDIO CHOME
74	53399	1ST AUDIO CHOME
75	53399	2ND AUDIO CHOME
76	53399	1ST AUDIO CHOME
77	53399	2ND AUDIO CHOME
78	53399	1ST AUDIO CHOME
79	53399	2ND AUDIO CHOME
80	53399	1ST AUDIO CHOME
81	53399	2ND AUDIO CHOME
82	53399	1ST AUDIO CHOME
83	53399	2ND AUDIO CHOME
84	53399	1ST AUDIO CHOME
85	53399	2ND AUDIO CHOME
86	53399	1ST AUDIO CHOME
87	53399	2ND AUDIO CHOME
88	53399	1ST AUDIO CHOME
89	53399	2ND AUDIO CHOME
90	53399	1ST AUDIO CHOME
91	53399	2ND AUDIO CHOME
92	53399	1ST AUDIO CHOME
93	53399	2ND AUDIO CHOME
94	53399	1ST AUDIO CHOME
95	53399	2ND AUDIO CHOME
96	53399	1ST AUDIO CHOME
97	53399	2ND AUDIO CHOME
98	53399	1ST AUDIO CHOME
99	53399	2ND AUDIO CHOME
100	53399	1ST AUDIO CHOME

IF FREQUENCY 175 KC.
2-TUBE SUPERHETERODYNE
CHASSIS NO. 5902

ZENITH RADIO CORP.
CHICAGO, ILL. U.S.A.

MODELS 970-975

NOTE: 50-60 CYCLE TRANSFORMER

TUBE	POSITION	Ef.	Ek	Eg1	Eg2	Eg3	Ep
58	R.F.	2.6	A 14 B 9.5 C 3 D 3	0	110	A 14 B 9.5 C 3 D 3	250
2A7	1st Det.	2.6	3	0	110	-	250
	Osc.			-1	-	-	180
58	I.F.	2.6	2.8	0	110	2.8	250
56	2nd Det.	2.6	0	0	-	-	0
56	1st Aud.	2.6	6	0	-	-	120
56	2nd Aud.	2.6	13.5	0	-	-	250
2A5	PWR.	2.6	18	0	250	-	250
2A5	PWR.	2.6	18	0	250	-	250
80	Rect.	4.6	-	-	-	-	-

Line 116 V.

Antenna and Ground Disconnected

F - filament; K - cathode; G1 - control grid; G2 - screen grid; G3 - suppressor grid; P - plate.

Alignment

The diagram on page 3 shows position of major components and aligning adjustments. It should be studied carefully before any attempt is made to adjust the various circuits. A suitable high frequency service oscillator capable of excellent attenuation is required and no adjustments should be made without one. Separate coils are used for each band. Mounted on the coils are individual trimmers that align each band, independent of the other bands.

(I.F.) - Connect 175 K.C. service oscillator to grid of 6A7 and chassis ground. Adjust I.F. trimmers to point of maximum output.

(A) - Set service oscillator at 1400 K.C. and connect to antenna and ground leads. Place pointer at 1400 K.C. on dial and first adjust top trimmer on oscillator coil, then top trimmer on detector coil and top trimmer on R.F. coil to resonance. There is no 600 K.C. adjustment necessary.

(B) - Set service oscillator at 3 megacycle. Adjust second from top trimmer on oscillator coil to secure correct dial reading. Adjust second from top trimmers on detector and R.F. coils to resonance.

(C) - Set service oscillator at 6 megacycle. Adjust third from top trimmer on oscillator coil to secure correct dial reading. Adjust third from top trimmers on detector and R.F. coils to resonance.

(D) - Set service oscillator at 18 megacycle. Adjust bottom trimmer on oscillator coil to secure correct dial reading. Adjust bottom trimmers on detector and R.F. coils to resonance. Check for scale at 9 megacycle, if off, either twist or untwist blue wire loop on rear section of gang-switch and rebalance.

NOTE: It may be possible to obtain two settings on the oscillator and detector trimmers, particularly on bands C and D. If this occurs the oscillator should always be left on the loosest setting and the detector on the tightest one. Otherwise, reception over the band will be very erratic.

SERVICE HINTS ON CHASSIS 5902

Hums - Defective 56, 2A5 or 58 tube. Open condenser or defective filter. Yellow and white resistor shorted to brown, white tip, orange, at band switch.

Cuts out - No plate click on 2A5 when tube is removed from socket. Check bias candohm resistor R6 for open.

Audio howl or tendency to oscillate at center of volume control, particularly on end of one of the S.W. bands caused by coupling of #2 I.F. red plate wire. Remove the wire from aeroplane lug at .02 condensers. Lengthen I.F. wire about 2 inches and re-route this wire on other side of 8 mfd. condenser, connecting to plate choke. This places I.F. in the same circuit but reduces coupling tendency. May be necessary to repeak I.F.

Weak on C band - Open one 22-224.

Dead on B.C. - 58 Grid cap - 1st R.F. will read approximately 10,000 ohms to ground. Signal will come through if aerial is placed on grid of 58 R.F. tube. This is very difficult to locate, band switch has high resistance short across red R.F. coil lug to 9900 ohm resistor lug, may be necessary to replace band switch.

Set smokes - Grounded filament or 300 ohm across .1 is shorted to 22-188 - .02 condenser in I.F. plate circuit.

Distorted - Check tubes and speaker, balance, resistors and bypass condensers. If voltage across red black speaker wires read approximately 160 instead of 120 volts, and 1 - 2A5 excessively hot, check bias candohm for ground on both ends. Also check push-pull transformer for open or short.

Weak 9 Megacycles - D band - Check for open or leaky .0011 micamold on band switch.

Noisy on S.W. - Check static shields making contact with gang, poor contact on Band Switch.

Mushy on full volume. Tendency to oscillate on edge of carrier. Check C9 .0005 micamold condenser for open.

Dead, or very distorted on strong signal only. Check for open R 4 100,000 ohm resistor on 56 tube - 2nd detector and A.V.C.

Weak and distorted - Check R 13 49,000 ohms for open.

Too much audio hiss and flutter on broadcast, .005 - C15 across 2A5 open. Weak audio if condenser is shorted or leaky.

Too much highs. Check C 14 .00075 from 2A5 to ground for open. Set dead if shorted.

Weak - Audio lacks bass. Poor quality. Check 1500 ohm resistor and 22-225 in 56 circuits for open or shorts.

Dead - 280 plates red - Check filter and plate circuits for shorts or grounds.

Carrier hum, on stations. Usually caused by static shield in power transformer not being grounded. Check tubes and by-passes first. If carrier hum still present, replace power transformer.

Weak and Distorted - A.V.C. seems to block. C5 near 2nd I.F. shorted.

Weak and Oscillates on B.C. - Open antenna coil or open .001 - C1 grounded. Also set will be weak on R.F.

Weak on D and dead at 3 Meg. Stops oscillating around 10-11. Check C8 micamold .000025 for open or high leakage. Check tubes and coils for opens.

Weak on all S.W. bands. Check C2 .0011 micamold for open or high leakage.

Microphonic - Try tubes, put cotton in oscillator coil to suppress grid wire vibrations. Check by-passes.

Dead on B.C. - Shorted coil trimmer condenser, usually oscillator coil.

Balance procedure must be done very carefully on this model, and tubes checked carefully in particular for satisfactory S.W. operation. In addition to above, an occasional open coil or shorted trimmer will cause either weak or no reception on one or more bands. Check for poor contacts on band switch, rosin or loose connections.

Oscillates on S.W. - Ground 56 detector cathode directly at socket prong. Remove black ground wire to #2 I.F. ground at C5 condenser

MODELS 970, 975
Chassis #5902

Dial Assembly

26-71	Complete Split Second Dial Assembly	\$6.50
26-72	Dial Scale Only	.75
32-4	Dial Drive Belt	.20
33-60	Dial Glass Frame	.35
59-28	Large Z Pointer (black)	.10
59-29	Split Second Pointer (red)	.10
93-232	Dial Glass Cushion Washer	.10
192-4	Dial Glass	.20
132-9	Dial Glass Retaining Ring	.03

Resistors

63-242	2500 Ohm $\frac{1}{4}$ Watt	.20
63-245	1500 " $\frac{1}{4}$ "	.20
63-258	490M " $\frac{1}{4}$ "	.20
63-260	100M " $\frac{1}{4}$ "	.20
63-263	30M " $\frac{1}{4}$ "	.20
63-280	49M " $\frac{1}{4}$ "	.20
63-302	375 - 1500 Candohm	.40
63-318	30M Ohm $\frac{1}{4}$ Watt	.20
63-353	19M " $\frac{1}{4}$ "	.20
63-357	300 " $\frac{1}{4}$ "	.20
63-372	50M " $\frac{1}{4}$ "	.20
63-385	300M " $\frac{1}{4}$ "	.20
63-386	12M " 2 "	.30
63-392	Volume Control Assembly	1.25
63-393	Tone Control Assembly	.75

Condensers

22-82	.001 Mfd. 600 V.	.25
22-112	.1 " 300 V.	.25
22-125	8. " 440 V.	1.00
22-127	.000025 " 600 V.	.20
22-147	.0005 " 600 V.	.15
22-162	.0001 " 600 V.	.20
22-182	.00025 " 600 V.	.12
22-188	.02 " 400 V.	.15
22-212	.05 " 400 V.	.20
22-225	5. " 25 V.	.65
22-228	.5 " 300 V.	.35
22-229	.005 " 600 V.	.15
22-230	8. x 8. " 450 V.	2.50
22-250	.05 " 200 V.	.15
22-289	.00005 " 600 V.	.12
22-325	2 - 35 Mmfd.	.45
22-343	3-Gang Variable	3.00
22-345	.0011 Mfd. 600 V.	.15
22-346	.00075 Mfd. 600 V.	.15

Coils & Chokes

20-81	R.F. Plate Choke	.65
-------	------------------------	-----

MODELS 970, 975 (Ch. #5902)

95-206	1st I.F. Transformer	\$1.50
95-207	2nd I.F. "	1.50
S-3297	Oscillator Coil Assembly	2.75
S-3298	1st Detector Coil Assembly	2.60
S-3299	R.F. Coil Assembly	3.00

44-7	Phono Connector Jack (Export Models Only)	.15
46-49	Knob, large control	.20
46-55	Knob, small control	.15
46-102	Knob for Band Selector	.20
49-62	Dynamic Speaker With Transformer	8.50
49-63	" " Without "	6.25
	Output Transformer for 49-62	2.50
	Cone & Voice Coil for 49-62 or 49-63	2.50
	Field Coil for 49-62 or 49-63	2.00
57-475	Dial Escutcheon Plate	.70
78-84	Tube Socket 56	.10
78-85	" " 58	.10
78-86	" " 59	.10
78-87	" " 80	.10
78-112	" " 2A7	.10
85-56	Phono Switch (Export Models Only)	.35
85-65	Band Selector Switch	2.50
95-190	117 V. 50/60 Cycle Power Transformer	5.00
95-193	Push Pull Audio Transformer	1.50
95-194	All Voltage 25 Cycle Power Transformer	7.00
95-261	Power Choke	1.00
100-18	2.5 V. Pilot Lamp	.12
126-127	Tube Shields	.10

198

Service Bulletin



MODELS

980 - 985 - 990

Chassis

1201 - 1201A

SERVICE NOTES

Dial Slips or Birds. Tighten lugs on planetary drive. See that both pointers are free. Make sure gang is squarely lired up with dial.
Off Calibration. Check for loose set screws on dial assembly to condenser shaft. Black pointer may be loose on shaft. Check alignment as outlined in Alignment Procedure.

Poor Tone. Defective tubes in audio. One side of push-pull circuit faulty. Check audio and output transformers. See A.V.C. blocking.

Insensitive. Out of alignment, weak tubes or defective by-pass condenser.

Shadowgraph Inoperative. Weak 76 tube, burnt out shadowgraph, open resistor in 76 plate circuit.

Distortion at Medium Volume. Defective 75 tube, defective volume control. Separate green volume control-lead and speaker-lead close to grid of 42 tube.

Insensitive on Any Short Wave Band. Check alignment, make sure R.F. circuit is not aligned to image frequency. Change 6A7 tube. Change position of fixed condensers adjacent to rear section of wave change switch. Location of these condensers in relation to each other and their distance from the chassis will affect dial calibration and sensitivity.

Stops Oscillating Around 9 M.C. Change 6A7 tube, leakage in 50 Mmfd. or .0029 Mfd. condenser.

A.V.C.Blocks. Shorted resistor on antenna choke. C-14 padder shorted.

Grounded R.F. grid circuit.

Oscillates on Broadcast. Check alignment. Push brown wire away from 6A7 socket. Grounded cathode on 1st I.F. or grounded to 600 K.C. padder. Check for open by-pass condenser.

Noisy. Shorting plates in gang condenser. Poor contact in band switch. Loose shields or shield bases. Static shields may be touching leads under gang condenser.

Overheats. Check pilot light and heater circuits for partial short or ground.

Hum on D and E Bands. Antenna lead too close to AC line or 5Z3 socket short in 6D6 in R.F. socket.

Flutters. Rearrange leads adjacent to 6A7 socket. Open antenna coil. Push yellow band pass lead away from detector trimmer assembly and yellow choke leads. Replace 6D6 in R.F. socket.

Oscillates on Short Wave Bands. Make sure brown R.F. grid return lead is pushed away from 6A7 socket. Check for ground or any A.V.C. lead. Open by-pass condenser.

Tone Control Inoperative. Loose ground lug or 63-430 cardohm. Defective condensers in tone control circuit.

Whistles. Rearrange leads in audio circuits. Speaker wires couple with 1st I.F.

Warning. The wiring to the switch is a part of the tuned circuit on the "E" band. Do not change the position of any leads.

Alignment

The diagram on page 2 shows position of major components and aligning adjustments. It should be studied carefully before any attempt is made to adjust the various circuits. The Clough-Brengle type is the only commercial service oscillator found practical for this work.

Separate coils are used for each band. Mounted on the coils are individual trimmers that align each band, independent of the other bands.

Connect 485 K.C. service oscillator to grid of 6A7 and chassis ground. Adjust I.F. trimmers on rear of I.F. transformers for strongest signal.

Connect 485 K.C. service oscillator to antenna and ground. Turn dial to 540 K.C. on broadcast band and adjust wave trap trimmer on right rear side of chassis for weakest signal.

Broadcast - "A" Band

Set service oscillator at 1400 K.C., remaining attached to antenna ground posts. Turn dial to same point and adjust #1 trimmer (top one on oscillator coil) to resonance. Adjust #1 R.F. trimmer (top one on R.F. coil); #1 detector trimmer (through hole in chassis base) and band pass trimmer (top front section of gang) all to resonance.

Set service oscillator at 600 K.C. Adjust paddler (located in center rear of chassis) for correct dial reading.

Recheck 1400 K.C. alignment.

"B" Band

Set service oscillator at 4 M.C. (still attached to antenna and ground) and adjust trimmer #2 (2nd from top) on oscillator coil for correct dial reading. Adjust #2 R.F. trimmer (2nd from top on R.F. coil) and #2 detector trimmer (center hole through chassis) to resonance.

"C" Band

Loosen #3 detector trimmer (top one on detector coil). Set service oscillator at 10.5 M.C. Adjust #3 oscillator trimmer (third from top on oscillator coil) for correct dial reading. Adjust #3 R.F. trimmer (third from top of R.F. coil) and #3 detector trimmer (rear one through hole in top of chassis). Adjust #3 detector trimmer on coil to resonance.

"D" Band

Tighten #4 detector trimmer (bottom one on detector coil). Set service oscillator at 21 M.C. Adjust #4 oscillator trimmer (bottom one on oscillator coil) for correct dial reading. Adjust #4 R.F. trimmer (lower one on R.F. coil) and #4 detector trimmer (lower one on detector coil) to resonance.

It is very easy to mistake the image frequency for the fundamental on this band. Rotate dial and if shadowmeter narrows at any point, especially at 15 M.C., the band should be rebalanced.

"E" Band

There are no adjustments to be made on this band.


Socket Voltages


TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	R.F.	5.8	1	0	78	1	220
6A7	1st Det.	5.8	1.5	0	86	-	220
	Osc.			-10	-	-	220
6D6	1st I.F.	5.8	7	0	86	7	220
6D6	2nd I.F.	5.8	7	0	86	7	220
76	2nd Det.	5.8	0	0	-	-	0
76	Shadow-meter AMP.	5.8	10	0	-	-	210
76	1st Aud.	5.8	11	0	-	-	210
76	P.P. Driver	5.8	11	0	-	-	220
76	P.P. Driver	5.8	11	0	-	-	220
42	P.W.R.	5.8	26	0	260	-	260
42	P.W.R.	5.8	26	0	260	-	260
5Z3	RECT.	4.8	-	-	-	-	-

Line Voltage 110 Volts

Antenna and Ground Disconnected.

f - filament; k - cathode; g1 - control grid; g2 - screen grid; g3 - suppressor grid; p - plate.





DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION
-----------	----------	-------------	-----------	----------	-------------


C1	22-250	.05 - 200V.
C2	22-289	.00005 - 600V.
C3	22-285	.00001 - 600V.
C4	22-185	.01 200V.
C5	22-219	.03 200V.
C6	22-292	500-1000 MMFD.
C7	22-182	.00025 600V.
C8	22-82	.001 600V.
C9	22-212	.05 400V.
C10	22-127	.000025 600V.

C12	22-331	8 500V.
C13	22-125	8 440V.
C14	22-284	15-275 MMFD.
C15	22-190	.1 200V.
C16	22-333	46ANG VAR.
C17	22-341	.00092 - 600V.
C18	22-228	.5 300V.
C19	22-243	.01 400V.
C20	22-342	.0029 600V.
C21	22-147	.0005 600V.
C22	22-325	2-35 MMFD.
C23	22-324	2-35 "
C24	22-323	2-35 "
C25	22-188	.02 400V.

R1	63-238	1000 ~ 1/2W.
R2	63-291	29M ~ 1/2W.
R3	63-258	490M ~ 1/2W.
R4	63-410	1200 ~ 1/2W.
R5	63-281	29M ~ 1/2W.
R6	63-278	99M ~ 1/2W.
R8	63-245	1500 ~ 1/2W.

R11	63-261	9900 ~ 1/2W.
R12	63-431	2400-4000 ~ GRD OHM
R13	63-430	300-730 ~ "
R14	63-384	500M ~ VOL. CON.
R15	63-377	170 ~ 1/2W.
R16	63-372	50M ~ 1/2W.
R17	63-305	160 ~ 1/2W.
R18	63-388	19M ~ 1/2W.


1	20-64	WAVE TRAP COIL
2	5-3078	R.F. COIL
3	20-85	BAND PASS COIL
4	20-81	R.F. PL. CHOKE
5	5-3537	DET. COIL
6	20-84	7METER DET. COIL
7	5-3080	OSC. COIL
8	5-3115	7METER OSC. COIL
9	95-242	1ST I.F. TRANS.
10	95-242	2ND I.F. TRANS.
11	95-243	3RD I.F. TRANS.
12	95-241	POWER TRANS.-50-60W
13	95-269	AUDIO TRANS.
14	95-240	FILTER CHOKE
15	85-39	PHONO. SWITCH
16	20-88	ANT. CHOKE
17	49-107	5 SPEAKER - 6" } MOD. 985-990
18	49-108	" 12" }
19	49-107	SPKR. FIELD
20	49-108	" "
21	95-268	DRIVER TRANS.
22	49-92	SPEAKER - 12" MOD. 980
23	49-92	SPKR FIELD
24	85-60	TONE C. SWITCH
25	95-246	POWER TRANS. 25 CYCLE
26	85-58	BAND SELECTOR SWITCH
27	5-3538	PL. CHOKE



6A7
1ST DET. OSC.

6D6
1ST I.F.

6D6
2ND I.F.




ITEMS 17 AND 19 USED ON DOUBLE
SPEAKER MODELS ONLY - FOR SINGLE
SPEAKER MODELS CONNECT R12
4M OHMS AND R12 2400 OHMS
TOGETHER.

SWITCH SECTIONS SHOWN IN
BROADCAST POSITION.
SWITCH SECTIONS ARE NUMBERED
FROM FRONT TO REAR OF
CHASSIS.

765
PUSH-PULL DRIVER

76
1ST AUDIO

76
2ND DET.



12 TUBE
SUPERHETERODYNE
I.F. FREQUENCY 485 KC.
CHASSIS MODEL
Nº 1201
Nº 1201-L

ZENITH RADIO CORP.
CHICAGO, ILL.

MODEL 980-1201 CHASSIS.
985-990-1201-L CHASSIS.

NO. 12-22-34.



Parts and Prices

Models 980, 985, 990

Chassis 1201

Dial Assembly

S-3424	Complete Split Second Dial Assembly.....	\$7.50
26-80	Dial Scale Only	.75
32-3	Drive Belt	.20
33-62	Dial Glass Frame	.40
59-28	Large "Z" Pointer	.10
59-29	Split Second Pointer	.10
75-151	Planetary Drive Assembly	2.00
93-217	Dial Glass Cushion Washer	.10
100-23	6.3 Volt Pilot Lamp	.15
122-9	Shadowgraph Meter	2.00
192-4	Dial Glass	.20

Resistors

63-238	1 M Ohm $\frac{1}{4}$ Watt	.20
63-245	1500 " $\frac{1}{4}$ "	.20
63-258	490 M " $\frac{1}{4}$ "	.20
63-261	9900 " $\frac{1}{4}$ "	.20
63-278	99 M " $\frac{1}{4}$ "	.20
63-281	29 M " $\frac{1}{4}$ "	.20
63-291	29 M " $\frac{1}{2}$ "	.20
63-305	160 " $\frac{1}{4}$ "	.20
63-361	5 M " $\frac{1}{4}$ "	.20
63-372	50 M " $\frac{1}{4}$ "	.20
63-377	170 M " $\frac{1}{4}$ "	.20
63-384	500 M " Volume Control Assembly	1.00
63-388	19 M " 1 Watt Resistor	.25
63-410	1200 " $\frac{1}{4}$ " "	.20
63-430	300-730 Ohm Candohm	.30
63-431	2400-4000 Ohm Candohm	.80

Condensers

22-82	.001 Mfd. 600 V.	.25
22-125	8. " 440 V.	1.00
22-127	.000025 Mfd. 600 V.	.15
22-147	.0005 Mfd. 600 V.	.15
22-182	.00025 Mfd. 600 V.	.12
22-185	.01 Mfd. 200 V.	.20
22-188	.02 " 400 V.	.15
22-190	.1 Mfd. 200 V.	.20
22-212	.05 " 400 V.	.20
22-219	.03 " 200 V.	.15
22-228	.5 " 300 V.	.35
22-243	.01 " 400 V.	.15
22-250	.05 " 200 V.	.15
22-284	75 - 275 Mmfd. Padder	.30



PARTS AND PRICES

PAGE NO. 2

MODELS 980, 985, 990

Condensers Cont'd

22-285	.00001 Mfd. 600 V.	\$.15
22-289	.00005 Mfd. 600 V.	.12
22-292	500-1000 Mmfd. Padder	.45
22-323	2 - 35 Mmfd. Padder	.25
22-324	2 - 35 Mmfd. Padder	.40
22-325	2 - 35 Mmfd. Padder	.40
22-331	8. Mfd. 500 V.	1.25
22-333	Four Gang Variable Condenser	5.00
22-341	920 Mmfd. 600 V.	.15
22-342	.0029 Mfd. 600 V.	.25

Coils, Chokes, Etc.

20-64	Wave Trap Coil	.35
20-81	R.F. Plate Choke	.65
20-84	7-Meter Detector Coil	.10
20-85	Band Pass Coil	.60
20-88	Antenna Choke	.25
95-242	1st and 2nd I.F. Transformer	1.50
95-243	3rd I.F. Transformer	1.50
S-3538	Plate Choke	.40

Miscellaneous

44-7	Phono Connector Jack (Export Models Only)	.15
46-97	Tuning Knob (Small).....	.20
46-111	Volume Control Knob	.10
46-113	Wave Change Switch Knob	.25
46-114	Tuning Knob (Large)	.25
49-92	12" Auditorium Speaker (Model 980)	14.50
	Cone and Voice Coil Assembly for 49-92.....	3.25
	Output Transformer for 49-92	2.50
	Field Coil for 49-92.....	2.50
49-107	6" Dynamic Speaker for (Models 985, 990).....	5.50
	Cone and Voice Coil Assembly for 49-107	2.00
	Output Transformer for 49-107	2.00
	Field Coil for 49-107.....	2.00
49-108	12" Auditorium Speaker for (Models 985, 990)	25.00
	Cone and Voice Coil Assembly for 49-108	5.00
	Output Transformer for 49-108	3.50
	Field Coil for 49-108	7.00
57-486	Dial Escutcheon Plate	.40
78-100	6D6 Tube Socket	.10
78-102	42 Tube Socket	.10
78-106	6A7 Tube Socket	.10
78-109	76 Tube Socket	.10



PARTS AND PRICES
PAGE NO.3

MODELS 980, 985, 990

Miscellaneous Cont'd

73-110	5Z3 Tube Socket	\$.10
83-334	Antenna and Ground Terminal Strip	.10
85-39	D.P.D.T. Phono Switch (Export Models Only)	.75
95-58	Wave Change Switch	4.00
85-60	4-Position Tone Control Switch	.60
95-240	Power Filter Choke	2.00
95-241	117 V 50/60 Cycle Power Transformer	5.75
95-246	All Voltage 25 Cycle Power Transformer	10.00
95-268	Driver Transformer	2.00
95-269	1st Audio Transformer	2.00
126-109	Tube Shield (small)	.10
126-127	Tube Shield (large)	.15

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

January 29, 1935

ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

WARRANTY

The Zenith Radio Corporation guarantees each new ZENITH receiver and each new ZENITH QUALITY TUBE to be free from defects in workmanship and material.

Our obligation under this warranty is limited to making good at our factory any part or parts of the receiver which within ninety days from date of purchase shall be returned to us with transportation charges prepaid and which on examination shall be found to our satisfaction to have been thus defective. The ZENITH QUALITY TUBES used in this receiver are guaranteed against mechanical and electrical defects under the same warranty as the receiver. This warranty is expressly in lieu of all other warranties expressed or implied, and we neither assume nor authorize any representative or other person to assume for us any other liability in connection with the sale of ZENITH receivers or ZENITH QUALITY TUBES.

This warranty shall not apply to any receiver or tube which shall have been repaired or altered outside of our factory in any way so as, in our judgment, to affect its stability or reliability, nor which has been subject to misuse, negligence or accident, nor which has had the serial number or name altered, defaced or removed. Neither shall this warranty apply to any receiver in which other than ZENITH QUALITY TUBES have been used.

ZENITH RADIO CORPORATION.

INSTALLATION AND SERVICE INSTRUCTIONS



AUTO RADIO

MODEL 7

INSTALLATION: Determine most satisfactory or desirable mounting position. In most cases it will be found that the receiver can be mounted on the car bulk head, above and to the right of the steering post. Use the paper template which is the same size as set and mark location for the mounting bolt. Then drill two one-half inch ($\frac{1}{2}$ ") holes, making certain that the paint around the hole on the engine side of fire wall or bulk head is scraped clean to insure a good ground connection between the receiver and the frame of the car. Insert bolts through dash, with lockwasher and nut on engine side, then hang receiver over bolt heads and tighten nuts securely.

Mount the remote control unit on steering column by means of mounting bracket. Two flexible shafts are furnished, one with a slotted fitting on one end, which is the volume control shaft. The other is the selector shaft, with key fitting at one end. Make certain that the outer casings of flexible shafts go into remote control bushings for approximately five-sixteenths of an inch and tighten set screws to secure cables. If cables are pushed too far into remote control head, shafts will not turn freely. Always try to install drive shafts in as straight a line as possible from remote control to set. **AVOID SHARP BENDS IN CABLES.** 18" cables are supplied with receiver. 24", 30" or 36" cables may be obtained from the factory.

After the control unit and cables have been connected to the set, the dial pointer must be adjusted. To do this, slowly rotate the tuning control knob to either right or left until a definite stop is reached, do not force the knob after the stop, as this will damage the control mechanism. Now rotate the knob slowly in the opposite direction until the other stop is reached. The pointer will usually come to the end of the dial strip before the stop is reached. In the later type control heads the pointer is adjusted to the correct frequency by means of a screw on the rear of the head.

The battery cable, (red wire with fuse receptacle at one end and terminal lug at other end)—must be connected to battery terminal of the ammeter. At the same time connect ammeter condenser to battery terminal of ammeter, and to any convenient grounded screw on back of instrument panel. Make certain that insulating sleeve is slipped over fuse when fuse is placed in receptacle, before inserting in receiver. When connected properly, the discharge due to current drawn by the receiver should not indicate on the ammeter. This is important, since if improperly connected, as shown by the deflection of ammeter, motor interference may be encountered. The pilot light assembly, a shielded cable, plugs in to set and to the rear of the remote control unit. The antenna is connected to the receiver by means of the antenna cable. The antenna wire is the single black wire projecting from the end of the cable. Splice this wire to the roof antenna lead and ground the pig-tail shielding as close to the corner post of the car as possible.

ANTENNA: For very best results an antenna in the top of the car must be used. Practically all 1933 and 1934 cars are so equipped with the lead-in brought down one of the corner posts. Running board or other undercar antennas are not recommended since they are subject to all weather conditions and require constant attention. If the car in which the receiver is to be installed does not have a top antenna the first consideration is to have one built in. This should be done by the nearest authorized Zenith service station or someone capable of removing and replacing the top upholstery with previous training in this type of work.

In order to reduce electrical interference it is highly advisable to shield the antenna lead-in from as high as possible in the corner post to the antenna cable of the receiver with the shield grounded to the instrument panel. After all connections have been made and the set placed in operation it may be found necessary to balance the set to the antenna. This is accomplished as follows: With the receiver tuned to a very weak station, at between 130 to 140 on the dial, adjust the antenna trimmer with a screwdriver until maximum volume is attained. To reach the antenna trimmer remove the plug button from the top of the case.

The antenna is connected to the receiver by means of the antenna cable. The antenna wire is the single black lead projecting from the end of the cable. The white pigtail must be attached to the lead-in shield or otherwise grounded as near to the corner post as possible.

OPERATION: Place key (knob) in lock on left side of remote tuning unit. After waiting approximately forty-five seconds for tubes to heat, rotate station selector (right hand knob) until a desirable program is heard. Always adjust volume with the volume control, never by de-tuning the selector control. De-tuning will very seriously affect the tone quality of the receiver. Do not leave the receiver turned on over night or while not in the car as the battery might become discharged and cause difficulty in starting. In any event the charging rate of the generator should be advanced to about sixteen amperes to offset the current drain of the receiver. This receiver is equipped with automatic volume control which counteracts fading, blasting of locals while tuning and maintain the same volume level without repeated adjustment of the manual volume control knob. However, regardless of the automatic volume control efficiency there are certain "dead spots" such as under a totally shielded viaduct or bridge where reception is practically impossible. Some fading is to be expected under such conditions.

MOTOR NOISE: Disconnect the high tension leads to spark plugs and connect a plug resistor to the top of each spark plug. Next remove the high tension lead from coil to distributor and insert distributor suppressor. For cap type distributor, exchange the standard distributor suppressor from your dealer for special screw type. In some few cases, such as Buicks

It is necessary to use screw type suppressors. Cut lead about two inches from distributor and screw one end of suppressor into the wire attached to distributor, screw wire from coil into other end of suppressor. Generator condenser is connected to generator side of the cutout. The ground side can be fastened to the generator housing under the same screw that holds the relay housing to the generator. In some cases, an additional condenser (obtainable from your dealer) must be installed between the battery side of ignition coil and the car frame. If after connecting suppressors and condensers as outlined above there is still motor noise, proceed as follows:

Shield and ground the center high tension lead.

Bond flexible shaft leads, such as free wheeling, which run close to distributor, radiating ignition interference which is picked up by the antenna inside of car.

In cars using wooden floor boards, place a grounded copper screen under toe board.

If there is an excessive gap between the distributor rotor and the high tension contacts, replace it with a special radio rotor arm or build up the end with solder and dress with a file so that its original shape is retained. The rotor should not brush or wipe the contacts, but should just clear them.

In some cases, such as the V-8 Ford, it is necessary to pull the battery and primary leads out of metal tube which houses the high tension leads. Shield and ground these leads. Also on V-8 Fords it is necessary to install a condenser at the primary terminal of the coil housing.

Additional suppressors can be obtained from your dealer if required for larger motors.

The ignition system of car must be kept in good condition. Fouled plugs or plugs with improperly adjusted gaps will affect the operation of receiver as well as of the automobile. Burned or poorly adjusted breaker points will also impair the performance. It is advisable to advance the generator charging rate in order to compensate for the additional drain of the receiver on car storage battery. A charging rate of approximately 18 amperes should be sufficient.

It is sometimes necessary to also connect a condenser between the hot side of the dome light lead and ground, keeping it as near to the corner post as possible.

SERVICE: The Model 7 Auto Radio is a modern five-tube superheterodyne with the following tube complement. 1-6D6 R.F. amplifier; 1-6C6 1st detector-oscillator; 1-75 2nd detector-A.V.C.; 1-42 power amplifier and 1-84 rectifier. Use only Zenith Quality tubes for replacement as the stability might be affected otherwise. Both the top and bottom covers may be removed thereby making the chassis easily accessible for service.

Should it ever be necessary or desirable to re-align this receiver, the proper method is as follows:

Adjustments can be made with the receiver mounted in the case, being necessary only to remove the top cover.

I. F. ALIGNMENT:

1. With variable condenser at its maximum capacity position and with volume control full on, connect in series with a .1 mfd. condenser, an oscillator set at 175 kilocycles to the grid cap of the 6C6 tube.
2. Adjust trimming condensers I. F. transformer, part number 7108-19 (see top view of chassis) to resonance with oscillator, as indicated on an output meter connected across the primary terminals of the speaker input transformer. Maximum deflection on the meter indicates resonance.

Note: The I. F. transformer has two trimmers, both of which are adjustable through the rear of the case.

FREQUENCY ALIGNMENT:

1. Attach oscillator connected in series with a 200 mmfd. condenser to the antenna lead and with the variable condenser at its minimum capacity position (extreme right of its rotation) and with an oscillator set at 1550 kilocycles, adjust condenser trimmer of oscillator section (shaft end) to resonance.
2. Re-set oscillator to 1400 kilocycles, rotate variable condenser to pick up signal, adjust antenna and R. F. trimmers to resonance.
3. Check alignment at 1200-1000-800-600-530 kilocycles by setting oscillator to these frequencies and picking up signal by rotating condenser.
4. Bend slotted plates of antenna and R. F. sections only if necessary. **UNDER NO CIRCUMSTANCES BEND PLATES OF OSCILLATOR SECTION.**

NOTE: Voltages from chassis to different points are indicated on the socket voltage table, and should be measured with a volt meter having a resistance of 1000 ohms per volt.

Failure to operate, noisy or weak reception, may be due to defective tubes or poor contact between cap on top of tube and grid clip.

Tubes may be checked by replacing with another tube which is known to be good.

If fuse blows out frequently, and insulating sleeve has been properly placed over fuse, the trouble probably is in the vibrator and vibrator should be replaced.


NEVER ATTEMPT TO ADJUST VIBRATOR POINTS.

SOCKET VOLTAGES


TUBE	POSITION	Ef	Ek	Eg ¹	Eg ²	Eg ³	Ep
6D6	R.F.	5.9	1.5	0.	98	1.5	240
6C6	DET.-OSC.	5.9	17.	15.	98	— .5	98
75	1st AUD.	5.9	.5	0	—	—	80
42	PWR.	5.9	0	—5	240	0	220
84	RECT.	5.9	240	—	—	—	—

Ef—Filament. Ek—Cathode. Eg¹—Control Grid. Eg²—Screen Grid. Eg³—Suppressor Grid. Ep—Plate.

ALL VOLTAGES MEASURED FROM INDICATED POINTS TO GROUND.



CIRCUIT DIAGRAM - MODEL 7



TUBE POSITION

Warranty

The Zenith Radio Corporation guarantees each new ZENITH receiver and each new ZENITH QUALITY TUBE to be free from defects in workmanship and material.

Our obligation under this warranty is limited to making good at our factory any part or parts of the receiver which within thirty days shall be returned to us with transportation charges prepaid and which on examination shall be found to our satisfaction to have been thus defective. This warranty is expressly in lieu of all other warranties expressed or implied, and we neither assume nor authorize any representative or other person to assume for us any other liability in connection with the sale of ZENITH receivers or ZENITH QUALITY TUBES.

This warranty shall not apply to any receiver or tube which shall have been repaired or altered outside of our factory in any way so as, in our judgment, to affect its stability or reliability, nor which has been subject to misuse, negligence or accident, nor which has had the serial number or name altered, defaced or removed. Neither shall this warranty apply to any receiver in which other than ZENITH QUALITY TUBES have been used.

ZENITH RADIO CORPORATION.

PARTS LIST

ZENITH JR. MODEL 7

		Condensers	List Price
Part No.	Description		
7100-4	.1 Mfd. 200 V		\$.15
7100-8	.015 Mfd. 1400 V		.25
7100-9	.05 Mfd. 200 V		.15
7100-11	.01 Mfd. 400 V		.15
7100-12	.003 Mfd. 600 V		.25
7129-1	.001 Mfd. 600 V		.20
7129-6	.002 Mfd. 600 V		.20
7129-12	.00025 Mfd. 600 V		.20
7145-4	.21 Mfd. Block		.65
7148-2	1. Mfd. 120 V		.60
7119-4	8. x 8. Mfd. 350 V		2.25
7102-7	2-Gang Variable		3.25

		Resistors	
7101-9	Volume Control Assembly		1.00
7106-6	200 Ohm C.T. Wire Wound		.20
7106-14	5800 Ohm C.T. Wire Wound		.45
7130-3	500M Ohm 1/3 Watt Carbon		.20
7130-11	250M Ohm 1/3 Watt Carbon		.20
7130-15	301M Ohm 1/3 Watt Carbon		.20
7130-19	1 Megohm 1/3 Watt Carbon		.20
7130-30	25M Ohm 1 Watt Carbon		.25

		Coils—Chokes	
7105-3	A. Choke		.75
7108-19	I. F. Coil Complete		1.50
7109-7	R. F. Coil Complete		.65
7116-7	Oscillator Coil and Bracket Assembly		.65
7111-12	Antenna Coil		1.20

		Miscellaneous	
7146-1	Steering Column Mounting Bracket Assembly		.30
7152-2	Zenith Jr. Control Head Assembly (Less Cables)		4.00
7116-6	Pilot Lamp Cable & Bracket Assembly		.50
7116-5	6 V. - 8 V. Pilot Lamp		.15
7149-18	18" Volume Control Cable Assembly		.67
7150-18	18" Tuning Control Cable Assembly		.67
7104-6	Power Transformer		2.50
7105-4	Filter Choke		.80
	All Sockets		.10
7142-1	Vibrator		5.00
7146-2	Cable Clamp Bushing & Bracket Assembly		.20
7167-1	5" Dynamic Speaker		4.75
7152-1	Antenna Cable		.30
7152-2	A Battery Cable		.25
7148-1	.5 Mfd. 200 V. Generator Condenser		.50
7148-3	.5 Mfd. 200 V. Ammeter Condenser		.45
7168-1	15M Ohm Spark Plug Suppressor		.30
7168-2	15M Ohm Distributor Plug Suppressor		.30
7135-5	3" Carriage Bolt and Nut		.05
7169-1	15 Ampere Fuse		.06

ALL PRICES ARE LIST, SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE. USE ONLY GENUINE ZENITH PARTS FOR REPLACEMENT.

ZENITH RADIO CORPORATION
 3620 Iron Street
 Chicago, U. S. A.

SERVICE MANUAL



AUTOMOBILE RECEIVER

FEB., 1934

Model 462

Installation

There are certain problems in connection with every automobile radio installation not common to the average home receiver. They may be classed as follows:

- a. Antenna
- b. Receiver
- c. Motor Noise Suppression

In order to insure complete satisfaction to the car owner, each subject must be given careful consideration. The following information should serve to simplify the job and at the same time give the service man more confidence in his work.

Antenna

Practically all late model automobiles are equipped with a top antenna suitable for broadcast reception. If there is any question as to whether the particular car in which the installation is being made is equipped with an antenna, the local sales agency will furnish this information. Where it is incorporated, the lead-in will be found most generally under the instrument panel, beneath the right or left windshield post. The lead-in must be shielded at least from where it comes out of the post to the receiver. This shielding should then be grounded to the instrument panel or bulkhead. Car antennas should always be checked with a continuity meter for high resistance leakage or short circuit. Either of these conditions will seriously affect the efficiency of the receiver.

If the car does not have an antenna, a standard plate or strap may be used. However by far the best results will be obtained if the antenna is constructed in the top. A piece of copper screen approximately two and one half feet square, tacked to the top ribs between the head-lining and the top covering, will prove satisfactory. Remove the upholstered moulding from the front and sides and drop the head-lining about half way back in sedans or the total length in coupes. The lead-in is soldered to a front corner and brought down the corresponding post. Shield this wire over its entire length but be careful that the shield does not touch the copper screen. If the top is re-enforced with chicken wire, it can be used as an antenna by cutting about three inches away around four sides of a portion two feet square. The lead-in is of course attached in the same manner as in the case of the copper screen.

In roadsters or convertible models a plate or strap type antenna is advisable since the efficiency of a top system is poor especially when folded back against the body. It is important, however, to shield the lead-in since more motor noise is apt to be intercepted. Never bring the lead-in through the motor compartment as it will inevitably feed a great deal of motor interference to the receiver.

Receiver

The first step in the installation of the receiver is to select a suitable spot on the bulkhead, inside the driver's compartment, where it will not interfere with the operating controls of the car.

Provisions have been made for rear mounting with the speaker facing the occupants of the car, or for side mounting with the speaker facing directly across the car. The preferred position is high up on the left hand side of the bulkhead, with the speaker facing to the right. This will leave the right hand side of the bulkhead free for heaters, etc.

The remote tuning unit must be clamped to the lower edge of the instrument board in such position that the control cables are not cramped or bent sharply, as it would otherwise interfere with the free operation of the control knobs.

After a suitable location has been selected for both the receiver and the remote control unit, three 1/2" holes should be drilled through the bulkhead, spotting them by means of the drilling template supplied with each set. (Be sure the proper side of the template is used, depending upon the mounting position of the set.)

The carriage bolts are next placed through the carriage bolt brackets and fastened to the receiver by two 10/32x1/4" round head machine screws each, in the tapped holes provided on the side or rear of the chassis case for this purpose. Wooden spacers are supplied with each kit to compensate for different thicknesses of the bulkhead, or variations in its surface. Usually it is advisable to employ one block for each bolt on the inside of the car and another on the outside.

The battery cable can be identified as the larger of the two wires that come out through the speaker panel. It is in two sections, being divided so a fuse can be connected in series with it. Connect the hot lead of this battery cable to the battery side of the ammeter (the side that does not register current drain), or to the battery terminal of the ignition coil. The cold lead is to be grounded under any convenient screw on the instrument panel. **THESE INSTRUCTIONS APPLY REGARDLESS OF THE POLARITY OF THE BATTERY.**

The antenna connection will be found at the rear of the receiver.

Insert the free end of the remote tuning cable (right hand knob) in the upper hole on the speaker panel, making sure the wedge shaped tip falls into the slotted connector before tightening the cable clamp screw. Insert the free end of the volume control cable in the lower hole, taking the same precautions.

When installing cables, it is essential that the cable armour be inserted in the clamp far enough that the tightening process does not crimp the end of the armour, causing the control shaft to bind. This precaution should also be taken when fastening the other end of the cable in the control head. The end of the cable armour must extend beyond the set screw. To prevent creeping or backlash of the controls, the control cables should be securely fastened at several points throughout their lengths to any stationary object under the instrument panel.

If the operating controls turn too hard, it may be necessary to loosen the two screws that hold each cable clamp to the speaker panel and shift the clamp slightly to align it properly with the hole in the panel, re-tightening the screws when the correct alignment is determined.

Clamp the remote control head to the lower edge of the instrument panel, using the two thumb nuts to fasten it securely. Be sure it is mounted in such a position that the cables do not make sharp bends.

Connect the dial light cable from the control head to the smaller of the two cables which come out of the speaker panel.

To place the dial on scale proceed as follows:

1. Tune in a station of known frequency on the high frequency end of the scale. (Between 1300 K.C. and 1500 K.C.)
2. Loosen the set screw and remove the tuning knob.
3. Loosen 2 set screws in the tuning shaft bushing. This permits the bushing and pointer to be turned without changing the variable condenser setting.
4. Turn the bushing until the pointer registers the exact frequency of the station that is being received.
5. Tighten the set screws and put the tuning knob back in place.

The dial should now track accurately throughout the scale.

Motor Noise Suppression

Every automobile generates high frequency electrical interference by virtue of the ignition coil, distributor and spark plugs. In order to receive any degree of satisfaction from an automobile receiver, the interference so generated must be eliminated by means of suppression. Each car, however, presents an individual problem where the serviceman must use his own ingenuity in addition to certain definite instructions. We offer the following as a result of actual experience, and believe that if followed carefully, motor noise in any car can be overcome.

The first essential procedure is to apply the standard suppression parts furnished in each kit. This consists of placing a resistor on each spark plug and on the center high tension lead at the distributor. Since all high tension wires act as small antennas or radiators, they should be kept down as close to the motor as possible. Do not attach the suppressors in an upright position. Always try to keep them horizontal, or as near to the block as conditions will permit. Next in importance is the generator condenser. This filters a high pitched whining noise, which would otherwise be heard without it, as the motor is accelerated. Next in order is the ignition coil condenser. It is very essential that it be placed on the proper low tension coil connection. This can be determined by testing each side of the primary with a screw driver held in the hand by the metal part. One will give off a slight high frequency spark, while the other side will appear to be cold. This test is made with the motor running. The condenser is attached from the cold (battery side) side to ground. Placing the condenser on the wrong side of the coil will seriously affect the car's operation and tend to make the motor noise more pronounced. **THIS IS IMPORTANT.** Reversing the primary leads will sometimes reduce motor noise.

After standard suppression has been applied and the hood clamped down to prevent radiation, the receiver should be turned on and the dial tuned off a station, with the volume control at maximum. If the motor noise is still objectionable, the next step is to determine whether the interference is originating through chassis pickup or from the antenna.

To check for chassis pickup, the antenna should be disconnected and the lead grounded. The motor is then started and if any noise is heard, it is originating through the battery circuit and will require isolation of certain of the car wires. Chassis pickup can be reduced effectively also by shortening the gap in the distributor head. To do this, solder is applied to the end of the rotor arm, after which it is placed back

in position and the distributor cap reset. With the crank, the motor should be turned over slowly, in order to clean the excess solder. As an additional precaution, the breaker points should be thoroughly cleaned, or new points installed if they are burned or badly worn.

Where the low tension leads are all bunched together with the high tension wires in a sleeve under the instrument panel, they should be separated and the high tension leads brought out through another hole. Sometimes a .1 mfd. condenser on the distributor low tension side of the coil is also effective. A condenser should be used at the electrical connection of all gauges such as oil, water, gas, etc.

Cars with rubber mounted motors must have the motor bonded to the bulkhead and again to the frame at the radiator, to provide a direct path for the high tension interference developed in the ignition system. $\frac{3}{8}$ " copper braid will be found satisfactory.

If the coil is mounted inside the driving compartment, it might be necessary to shield the high tension lead. This cannot be done effectively, however, if the wire has rubber insulation. Where the car is so equipped, this wire should be removed and Packard cable of the same length substituted. This allows shielding without corona effects and consequent interruption of car performance. When applying the shield over this wire be sure that it terminates at least an inch and a half from both the coil and the distributor; otherwise, it might have a tendency to break down. The shield must be grounded to the instrument panel, dashboard or motor block. The other high tension leads to the spark plugs are not to be shielded. So far there has never been a case where this procedure was required. It would therefore only involve considerable work to no advantage.

Be sure to keep the battery cable from the receiver out of the motor compartment. Running this cable through the motor side has been found to be the cause of ignition interference.

This procedure should eliminate all possibility of chassis pickup, after which the antenna lead can be connected. Any motor noise picked up from this point on is being absorbed entirely by the antenna. The first precaution, if it exists, is to check the dome light wiring. It is known that these leads pick up motor noise and carry it to the aerial from around the dash compartment. Removing the dome light wire from the ammeter, or connecting a low resistance RF choke at this point will overcome the difficulty.

If the car has a wooden bulkhead, it will be found necessary to line it on the motor side with thin sheet lead, or other conductor. This will prevent interference from entering the inside of the car and from there being picked up by the antenna. Occasionally it will be found that the copper tubing which runs from the motor to the windshield wiper carries the interference to the antenna. This can be eliminated by bonding the windshield pipe at the dashboard with a short piece of copper braid. The same procedure might also be necessary with respect to the oil line, brake rod, spark and gas controls, or other metal conductors which pick up high frequency interference from the motor compartment.

No absolute rule for complete motor interference elimination can be specified inasmuch as sometimes two cars of the same make are likely to require bonding or shielding at different points. However, the foregoing suggestions, in addition to some ingenuity on the part of the radio man, will in every case prove effective.

Service

This receiver employs a six tube superheterodyne circuit of the following tube complement:

- 1—6C6 Radio Frequency Amplifier
- 1—6F7 1st Detector and Oscillator
- 1—6D6 Intermediate Amplifier
- 1—75 2nd Detector
- 1—42 Power Amplifier
- 1—6Z4 Rectifier

The following subjects cover in an elementary manner the possible complaints encountered in ordinary service and the corresponding corrections. It is suggested that they be considered in the order listed when making a preliminary examination.

- | | |
|----------------|---------------------------|
| 1. Inoperative | 5. Dial off Calibration |
| 2. Weak | 6. Intermittent Operation |
| 3. Distortion | 7. Motor Noise |
| 4. Rattles | 8. Noisy Reception |

After the trouble has been isolated, the following procedure will prove effective. (Consult illustrations)

1. INOPERATIVE

- (a) Examine fuse and replace if open.
If fuses continue to blow, a probable short circuit exists in the power supply unit or chassis wiring.
- (b) Defective tube—replace those that do not check normal.
- (c) Loose or corroded radio supply connection.
- (d) Broken wire in chassis.
- (e) Tube out of socket.

2. WEAK

- (a) Defective tube.
- (b) Shorted antenna.
- (c) Weak storage battery.

- (d) Defective speaker.
 - (e) Defective vibrator assembly.
 - (f) Broken connection.
3. DISTORTION
- (a) Defective speaker.
 - (b) Defective tube (42, 75 or 6Z4).
 - (c) Defective vibrator.
4. RATTLES
- (a) Loose tube shields.
 - (b) Loose speaker or case screws.
 - (c) Defective speaker.
 - (d) Loose instruments, wires, rods, etc. on dash.
5. DIAL OFF CALIBRATION
- (a) See paragraph on resetting indicator in "Alignment."
6. INTERMITTENT
- (a) Loose radio supply connection.
 - (b) Defective tubes.
 - (c) Loose connection in receiver chassis.
 - (d) Broken tube socket.
 - (e) Short in antenna or lead-in.
7. MOTOR NOISE
- (a) Defective suppressor.
 - (b) Broken lead or defective by-pass condenser at generator, coil or gauge.
 - (c) Open ground to lead-in shielding.
8. NOISY RECEPTION
- (a) See "motor noise."
 - (b) Defective vibrator.
 - (c) Loose antenna connection at receiver.
 - (d) Loose fuse holder.
 - (e) Defective tubes.
 - (f) Loose tube shields.
 - (g) Antenna shorting to frame of car.
 - (h) Natural atmospheric or electrical disturbances.
 - (i) Loose or defective wiring in high or low tension car wiring.

To Replace Power Supply Unit:

1. Unsolder two red leads from rectifier (6Z4) socket; blue lead from terminal strip near tone control and black lead from green terminal on electrolytic condenser. (Leads mentioned feed through the chassis base beneath power supply unit).
2. Remove the 4-8/32 screws which hold power supply unit in place beneath chassis base.

To Replace Speaker:

1. Remove 4-6/32 screws at lower left and right hand corners of front panel.
2. Unsolder speaker leads from terminal strip and 42 socket on under side of chassis.
3. Remove 4-6/32 speaker screws from around grill on panel.

Tubes:

Tubes should be checked on a standard test panel and conform to the corresponding tolerances.

To Remove Receiver from Car:

1. Loosen cable clamp screws at receiver and remove cables.
2. Disconnect battery, dial light and antenna cables.
3. Remove 3 5/16" nuts from carriage bolts, which hold chassis to bulkhead.

To Replace Dial Light:

1. Lower control head below bottom edge of instrument panel.
2. Remove one screw from dial light bracket (on rear of control head).
3. Remove bracket and install new dial light.

The following is a list of performance factors that will be of value where it is desired to make accurate measurements:

Intermediate Frequency—252½ K.C.
 Sensitivity in Microvolts—1
 Power Output in Milliwatts—2500
 Power consumption—40 watts at 6 volts.

Tube Operating Voltages:

Position	Tube	Ef	Ek	Eg ¹	Eg ²	Eg ³	Ep
R. F. Amplifier	6C6	5.6	1.5	*	1.5	72	174
1st Det.-Osc.	6F7	5.6	3.5	0	3.5	72	Det. 174 Osc. 130
1. F. Amplifier	6D6	5.6	1.5	*	1.5	72	174
2nd Det. A. V. C.	75	5.6	1.2	0	0	—	156
Power Amp.	42	5.6	0	—11.5	0	174.6	165
Rectifier	6Z4	5.6	174.6	—	—	—	—

f—Filament; k—Cathode; g¹—Control Grid; g²—Suppressor Grid; g³—Screen Grid; p—Plate; *—Depends on applied signal strength. All voltages measured from indicated points to ground. Battery voltage 6 volts.

Alignment

Every Zenith automobile receiver is balanced on an accurate crystal controlled oscillator before leaving the factory; and, unless a part is changed or the calibration has shifted, the adjustments should never be tampered with. Where it is absolutely necessary, however, a good test oscillator capable of delivering a modulated signal at 1500, 600 and 252½ K. C. will be essential.

Before attempting to make any adjustments, the dial indicator must be set to 540 K. C. with the tuning condenser plates in full mesh. This is done as follows:

1. Turn control knob toward the left until the stop is reached.
2. Remove tuning knob.
3. Loosen two set screws in tuning shaft bushing (under knob).
4. Turn bushing until dial reads 540 K. C.
5. Tighten set screws and replace tuning knob.

The receiver may now be aligned and will dial accurately when the operation is completed.

To balance the I.F. circuit, remove the grid lead from the 6F7 and connect the 252½ K.C. test oscillator signal to the grid of the tube and to ground. Adjust the 1st I.F. primary trimmer to maximum output from either the speaker or an output meter. Follow in the same manner with the secondary, and the primary and secondary of the 2nd I.F. transformer. This completes the I.F. circuit. Place the grid lead back on the 6F7 tube.

Next attach the test oscillator to the antenna and ground leads and set it to 1500 K.C. Turn the dial indicator to 1500 and adjust the oscillator, detector and R.F. trimmers, on the condenser gang, for maximum output. Set the test oscillator to 600 K.C. and rock the pointer slowly over the same frequency on the dial at the same time adjust the padder condenser for greatest signal strength. All adjustments should be gone over twice—at least twice—to insure greatest accuracy.





Fig. 1







FIGURE 3

Parts and Prices

S-2814	Chassis Case Assembly		\$ 2.30
MS-217	Front Panel & Grill Assembly		.55
S-2803	Control Cable Sleeve Clamp		2.52C
54-67	No. 8-32 x 11/32" Square Stud Nuts	(Used with S-2803)	.20C
69-102	No. 8-32 x 3/4" Rd. Hd. Mach. Screws	(Used with S-2803)	.28C
49-65	Dynamic Speaker Complete		5.50
49-65A	Cone & Voice Coil for 49-65		2.30
49-65B	Field Coil for 49-65		1.00
49-65C	Output Transformer for 49-65		1.50
110-23	Speaker Grill Cloth for Front Panel		.10
83-329	Sponge Rubber Baffle Strips for Speaker Mtg.		.12
112-44	No. 6-32 x 3/4" Black Speaker Mtg. Screws		.20C
93-125	No. 6 Lock Washers		.18C
54-34	No. 6-32 x 1/4" Hex Nuts		.18C
22-235	Three Gang Variable Condenser		3.25
20-57	R. F. Coil Assembly Complete with Can & Connector		1.30
20-58	Oscillator Coil Complete with Can		1.20
20-59	Detector Coil Complete with Can		1.30
95-218	1st I.F. Transformer Complete with Can		1.50
95-219	2nd I.F. Transformer Complete with Can		1.50
95-211	Filter Choke		.75
S-2779	Complete Power Unit Assembly		10.50
S-2778	Vibrator Isolation Choke	(Part of Power Unit Assembly)	.15
22-251	.5 Mfd. 100 volt Condenser	(Part of Power Unit Assembly)	.35
22-186	.02 Mfd. 800 volt Condenser	(Part of Power Unit Assembly)	.25
63-323	200 Ohm 1/4 Watt C.T. Resistor	(Part of Power Unit Assembly)	.20
95-220	Rectifier Transformer	(Part of Power Unit Assembly)	2.00
190-2	Rectifier Vibrator	(Part of Power Unit Assembly)	3.75
24-50	Power Unit Cover	(Part of Power Unit Assembly)	.10
MISCELLANEOUS CONDENSERS			
22-82	.001 Mfd. 600 Volt	(Osc. Plate & 2nd Detector Diode)	.25
22-162	.0001 Mfd. 600 Volt	(Power Grid)	.12
22-182	.00025 Mfd. 600 Volt	(Fixed Padder)	.12
22-185	.01 Mfd. 200 Volt	(2nd Detector Diode)	.15
22-190	.1 Mfd. 200 Volt	(R.F. Screen)	.15
22-219	.03 Mfd. 200 Volt	(Tone Control)	.15
22-228	.5 Mfd. 300 Volt	(Rectifier Filament)	.30
22-229	.005 Mfd. 600 Volt	(Power Plate)	.15
22-234	Padder Condenser Assembly		.45
22-236	Three Section Filter	(See Diagram)	2.75
22-250	.05 Mfd. 200 Volt	(R.F. 1st Detector, I.F. Grid Return)	
		(Audio Coupling and Power Grid)	.15
22-255	.25 Mfd. 25 Volt	(R.F. Cathode)	.20
22-256	.1 Mfd. 25 Volt	(Oscillator Cathode)	.15
MISCELLANEOUS RESISTORS			
63-264	240M Ohms 1/4 Watts	(R.F. 1st Det. Grid Return & 2nd Det. Diode)	\$.20
63-271	1 Megohm 1/4 Watts	(Oscillator Grid)	.20
63-278	99 M Ohms 1/4 Watts	(Diode)	.20
63-280	49M Ohms 1/4 Watts	(2nd Detector Plate)	.20
63-296	220M Ohms 1/4 Watts	(Power Grid)	.20
63-300	990 Ohms 1/4 Watts	(1st Detector Cathode)	.20
63-317	40M Ohms 1/2 Watts	(R.F. Screen)	.25
63-318	30M Ohms 1/4 Watts	(Oscillator Plate)	.20
63-321	500M Ohms (Volume Control & Bushing Assembly)		1.00
63-322	120 Ohms 1/4 Watts	(R.F. Cathode)	.20
63-325	150M Ohms 1/4 Watts	(Power Grid)	.20



- 16. Antenna Connector (Female)
- 17. Volume Control and Switch
- 18. Padder Condenser
- 19. Filter Choke
- 20. Tone Control
- 21. Filter Condenser

GURE

4

MISCELLANEOUS RESISTORS (Cont.)

3-326	4M Ohms 1/4 Watts	(2nd Detector Cathode)	.20
3-330	50M Ohms (Tone Control Unit)		.75

CONTROL HEAD ASSEMBLY

0-5	Complete Head with Knobs, Panel Mtg. Bracket and 24" Cables	6.00
0-8	Complete Head with Knobs, Column Mtg. Bracket and 30" Cables	6.78
2-322	Panel Mtg. Bracket only (Standard)	.22
2-46	2" x 10/24 Thumb Screws for Above	.03
6-74	Volume Control Key Knob	.30
6-75	Tuning Control Knob	.20
S-2818	Pilot Lamp Cable & Bracket Assembly	.80
0-27	6-8 Volt Pilot Lamps	.15
6-6	15 Ampere Fuse	.04
8-26	Fuse Insulating Sleeve	.01
S-2819	Bushing & Gear Assembly	.80
S-2820	Pointer Gear & Shaft Assembly	.80
S-2821	Dial Scale, Mask & Frame Assembly	.80
1-2	Glass	.12
7-427	Cover Plate	.50
7-20	Pointer	.10

MISCELLANEOUS PARTS

6-71	Rubber Tone Control Knob	.05
2-42	"A" Battery Cable on Chassis	.20
2-44	A Battery Cable and Fuse Receptacle	.55
8-21	D.-R. Antenna Connector Cap	.01
8-22	D.-R. Spring	.005
8-23	D.-R. Body (Outside Connector)	.01
8-24	D.-R. Bushing and Ferrule	.01
8-25	D.-R. Washer	.005
8-67	6Z4 Tube Socket	.10
8-68	6C6 Tube Socket	.10
8-69	6D6 Tube Socket	.10
8-89	6F7 Tube Socket	.10
8-91	75 Tube Socket	.10
3-92	42 Tube Socket	.10
6-123	Shielded Antenna Loom	.25
6-127	Tube Shield, Plain	.10
S-2787	Tube Shield, with Flexible Lead	.15
8-2	Rubber Band for Tubes	.02
S-2810	Pilot Lamp Cable on Chassis	.10

SUPPRESSOR AND MOUNTING EQUIPMENT

2-193	.5 Mfd. 200 Volt Ignition Coil Condenser	.45
2-194	.5 Mfd. 200 Volt Generator Coil Condenser	.50
3-334	15M Ohm Spark Plug Suppressor	.35
3-335	15M Ohm Distributor Suppressor	.35
2-323	Special Control Head Steering Column Mtg. Assembly	.67
5-125	Volume Control Cable Assembly 20" length	\$ 1.30
5-126	Volume Control Cable Assembly 24" length	1.30
5-127	Volume Control Cable Assembly 30" length	1.60
5-128	Volume Control Cable Assembly 36" length	1.90
5-129	Tuning Control Cable Assembly 20" length	1.20
5-130	Tuning Control Cable Assembly 24" length	1.20
5-131	Tuning Control Cable Assembly 30" length	1.50
5-132	Tuning Control Cable Assembly 36" length	1.80
2-321	Chassis Box Mtg. Bracket	.02
3-104	10/32 x 1/4 Black Machine Screws	.35C
3-127	No. 10 Shakeproof Lock Washer	.35C
3-143	3/8" Shakeproof Lock Washer	.30C
4-11	3" Carriage Bolt & Nut	.20C
7-12	Wooden Spacer Block	.01

All prices subject to regular discount and change without notice.

February 8, 1934



MODEL 663-4 CHASSIS 551Q

ZENITH RADIO CORPORATION

CHICAGO, ILL.

[illegible]

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6A7	1st Det.	5.8	4	0	97	-	205
	Osc.			0	-	-	175
6D6	I. F.	5.8	4	0	97	4	217
75	2nd Det. A. V. C. 1st Audio	5.8	1.1	0	-	-	160
41	PWR.	5.8	0	-15	225	-	215
6Z4	RECT.	5.8		225	-	-	-


Line Voltage - 6 V.

Ef - heaters; Ek - cathode; Eg1 - control grid; Eg2 - screen grid; Eg3 suppressor grid; Ep - plate.

All measurements taken from point indicated to ground, using a 1000 ohm per volt D.C. meter.

Alignment

- (1) Balance I. F. transformers at 456 K. C. with signal generator connected to grid of 6A7 and ground.
- (2) Connect signal generator to antenna and ground. Adjust oscillator trimmer on gang for correct dial reading at 1400 K.C. Adjust detector trimmer for greatest output.
- (3) Adjust oscillator padder while rocking pointer forward and backward past 600 K.C. to combination giving greatest output.
- (4) Realign 1400 K.C. trimmers on gang.
- (5) Set signal generator at 456 K.C. and gang at 600 K.C. Adjust wave trap trimmer for minimum signal.



MODEL 624
CHASSIS 5510

Tube Position

PARTS AND PRICES

MODEL 664

Chassis #5510

Resistors (Chassis Only)

63-260	100 M	Ohm	$\frac{1}{4}$ Watt		\$.20
63-263	30 M	"	"		.20
63-271	1 Megohm	"	"		.20
63-288	19 M	Ohm	"		.20
63-357	300	"	"		.20
63-394	200	"	"		.20
63-400	250 M	"	"		.20
63-401	500 M	"	"		.20
63-410	1200	"	"		.20
63-433	250	"	" , 24 M Ohm $\frac{1}{2}$ Watt, 15M Ohm $1\frac{1}{2}$ Watt.....		.65
63-434	500 M	"	Volume Control		1.00
63-436	750 M	"	$\frac{1}{4}$ Watt		.20

Condensers (Chassis Only)

22-82	.001 Mfd.	600 V.		.25
22-147	.0005 "	600 V.		.15
22-162	.0001 "	600 V.		.20
22-170	.1 "	400 V.		.15
22-182	.00025 "	600 V.		.12
22-185	.01 "	200 V.		.15
22-190	.1 "	200 V.		.20
22-212	.05 "	400 V.		.20
22-250	.05 "	200 V.		.15
22-251	.5 "	200 V.		.40
22-280	.5 "	200 V.		.25
22-327	.02 "	200 V.		.15
22-354	.007 "	800 V.		.20
22-355	.01 "	1400 V.		.20
22-358	.002 "	600 V.		.20
22-388	4. x 8. Mfd.	350 V.		1.50
22-389	Variable Gang Assembly			4.00
22-390	200-400 Mmfd.			.40
22-391	1000-1950 Mmfd.			.75
22-393	.00025 Mfd. -	600 V.		.12
22-413	.006 "	600 V.		.15

Coils, Chokes and Miscellaneous Chassis Parts

20-103	Filament Choke.....	.15
20-106	Oscillator Coil	.50
20-107	Antenna Choke	.25
20-110	Motor Noise Filter Coil only	.25
52-44	"A" Battery Cable with Fuse Receptacle	.60
52-59	Antenna Shielded Loom	.50
52-66	"A" Battery Cable Lead on Chassis	.25
54-76	1/4" x 20 Knurled Coupling Shaft Nuts	.08
78-100	Socket for 6D6 Tube	.10
78-101	" " 75 "	.10
78-106	" " 6A7 "	.10

PARTS AND PRICES

MODEL 664
Chassis #5510

Coils, Chokes and Miscellaneous Chassis Parts Cont'd

78-114	Socket for 6Z4	\$.10
78-115	" " Vibrator	.10
78-126	" " 41 Tube	.10
95-273	Power Transformer	2.00
95-275	2nd I. F. Transformer	1.25
95-276	Hum Filter Choke	.60
190-4	Vibrator	5.00
S-2778	R. F. Choke	.15
S-3603	Motor Noise Filter Assemb. complete with Case & "A" Bat. lead.	1.50
S-3609	1st I. F. Transformer Assembly	1.35
S-3622	Antenna Coil Assembly	2.00

Case Assembly

93-220	Bakelite Washer for Chassis Mounting Screws	.02
94-185	Rubber Bushing " " " "	.02
97-75	#10-32 x 1/4" Wing Screws for Top Cover	.02
97-76	Wing Screw for Ground Connection	.02
112-69	Chassis Mounting Screws	.02
114-27	#8 x 1/4" Black Screws for Bottom Cover	.01
MS-261	Chassis Box Body less Covers	1.50
S-3601	Chassis Box Top Cover.....	1.00
24-93	Chassis Box Bottom Cover	.85

Speaker Parts

49-111	"6 Dynamic Speaker with Output Transformer	5.00
	Cone and Voice Coil for 49-111	2.30
	Output Transformer for 49-111	2.00
	Field Coil for 49-111	2.00

Remote Control Unit

170-15	Zenith Remote Control Unit with Knobs, Mounting Bracket and Pilot Lamp Cable less Shafts	4.50
12-423	Complete Steering Mounting Bracket Assembly	.60
17-29	Mounting Clamp only	.35
83-395	Mounting Strip only	.20
93-183	1/4" Shakeproof Washer only	.01
112-85	Mounting Clamp Screws (small)	.03
112-86	" " " (large)	.05
26-90	Dial Scale and Cup Assembly	.30
46-121	Volume and Tuning Knobs	.20
73-21	Headless Set Screw for 46-121	.02
80-110	Tension Springs for 46-121	.01
52-72	Dial Lamp Cable Assembly	.30
59-37	Dial Pointer	.10
80-110	Tuning Knob Spring	.01
100-29	6-8 V. Dial Lamp	.15
112-83	Set Screw for Volume Control Coupling Housing	.01
112-84	" " " Tuning " " " "	.01
192-9	Dial Glass	.12

PARTS AND PRICES

MODEL 664
Chassis #5510

Remote Control Unit Cont'd

196-3	Dial Glass Gasket	\$.03
76-171	18" Tuning Cable and Shaft Assembly	1.00
76-174	18" Volume Cable and Shaft Assembly	1.00
76-172	24" Tuning Cable and Shaft Assembly	1.25
76-175	24" Volume Cable and Shaft Assembly	1.25
76-173	30" Tuning " " " "	1.50
76-176	30" Volume " " " "	1.50

Mounting Parts

22-193	.5 Mfd. Ignition Coil Condenser	.45
22-194	.5 " Generator " "	.50
52-44	"A" Battery Cable	.60
57-478	Set Mounting Plate	.25
58-26	Fuse Bushing	.01
63-336	Distributor Suppressor	.35
63-429	Spark Plug Suppressor (optional)	.30
69-84	10/32 x 1/4 R.H.M. Screws for 57-478	.30
93-127	#10 Shakeproof Lockwasher	.35
93-222	7/16 " "	.01
93-233	Mounting Bolt Washer	.02
136-6	15 Ampere Fuse	.06
144-14	7/16 x 3" Carriage Bolt and Nut	.05
196-1	Mounting Plate Gasket.....	.03

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
Chicago, Illinois, U.S.A.
May 13, 1935

SERVICE MANUAL



AUTO RADIO

ZENITH RADIO CORPORATION

CHICAGO, U. S. A.

MODEL 666

FEB. 1935

General

The 1935 Model 666 Zenith Auto Radio is a six tube Superheterodyne of extreme sensitivity yet requiring no spark plug suppressors for quiet operation in an automobile. This is accomplished by an exclusive method of floating the entire chassis independently of the case and incorporating a unique "A" filter within the receiver. It is especially adapted to undercar aerials as required on many of the 1935 cars with "turret" tops. Note the autodyne type of detector-oscillator circuit. This arrangement is not only highly efficient but also minimizes tube trouble in that portion of the circuit. The following service instruction should be followed carefully especially as regards "motor noise" and "antenna."

The circuit employed is a 6 tube Superheterodyne with the following tube compliment:

- 1—6D6 R. F. Amplifier
- 1—6C6 1st Detector and Oscillator
- 1—6D6 I. F. Amplifier
- 1—75 A. V. C. and 2nd Detector
- 1—42 Power Amplifier
- 1—84 Rectifier

Installation

MOUNTING RECEIVER. The receiver must be mounted on the inside of the driving compartment on the fire wall in either a horizontal or vertical position. First, use the template on the inside of the instruction folder as a means of size and determine best position of receiver on the fire wall. Next, fasten the mounting plate to the rear of the receiver case in such a manner as to allow the mounting slot to extend downward. This is important inasmuch as the receiver must rest its weight on the mounting bolt. If the plate is not put on in this manner the receiver might slide out through vibration of the automobile. Again using the template, punch the center for hole A, B, C, or D, as the case might require. Only one hole is used, depending upon the position in which the mounting plate is fastened to the receiver case. All bolt holes in the mounting plate are so arranged that it may be fastened in any one of the four positions. After the center punch mark is made, drill a 9/16 inch hole in the bulkhead, insert the square head of the mounting bolt in the slot and push the entire assembly tight against the bulkhead, pulling it up securely by tightening the large hex nut on the motor side of the bulkhead. The large metal washer furnished should be used under the nut.

MOUNTING CONTROL HEAD. Fasten the control head to the mounting clamp and mount the complete control unit on the steering column, using the bronze strap and screw provided for this purpose. If there is not enough friction between the steering column clamp and the steering column to prevent the control from shifting, a single layer of tape under the band will be effective.

Loosen the two knurled chuck nuts on the cable connectors at the receiver and insert the tuning cable (controlled by the right-hand knob) in the center chuck. Revolve the knob as this is being done in order to match the cable insert with the tuning condenser. Next, securely tighten the chuck nut. Fasten the volume control cable in the outer chuck, also revolving the control knob until the connector slips into the volume control receptacle. Screw down the chuck nut. The dial is set on calibration by tuning in a station of known frequency after the set is completely installed and then simply turning the indicator independently by adjustment of the screw in the rear of the control head to a point where the station is heard at its proper location on the dial.

Connect the dial light cable from the control head to the pin jack on the control cable side of the receiver. The shield over this lead must be securely fastened under the wing nut next to the pilot light jack.

Insert the fuse and insulating sleeve into the fuse receptacle of the "A" cable and connect this to the "A" lead of the receiver. Attach this lead to the ammeter, grounding the shield securely at some point under the instrument panel. The polarity of the battery need not be considered when making these connections, however, when making a ground contact scrape away any corrosion or paint in order to insure a good electrical contact.

Antenna

ANTENNA. Some automobiles are factory equipped with a roof antenna. If this is the case the lead should be checked to make certain that it is not grounded, and after being shielded by large loom from the post connect it to the antenna lead of the receiver. Be sure the shield over this lead is fastened to the shield on the antenna lead of the set and carefully grounded either to the instrument panel or to some portion of the frame in that immediate location. Where the car is not furnished with an antenna, such as convertible models or some of the 1935 series with an all metal top, an under-car antenna must be used. Your dealer can give you his recommendations on this subject but it is well to remember that the lead from an under-car antenna must be very thoroughly shielded from the aerial to the antenna connection in the receiver and grounded in several places. Only large size loom allowing separation between the shield and the antenna lead of at least $\frac{1}{4}$ of an inch will prove satisfactory. In no case should the lead be simply shielded without space between it and the wire as it will increase the antenna capacity to a point where its efficiency drops very noticeably.

Ignition Interference

All automobiles develop high frequency disturbance through radiation from the coil, distributor and plugs and it is necessary to minimize this interference by means of suppression. A suppressor is placed in the center distributor lead and, if necessary, on each spark plug. By-pass condensers must be used on the generator, coil and at all electrical gauges and the leads kept as short as possible. Each car, however, presents an individual problem where the technician must use some ingenuity, carefully following instructions.

Apply the standard suppression parts furnished with the receiver. This consists of a resistor for the distributor in addition to a coil condenser and a generator condenser. Lay all high tension leads close to the motor to lessen the possibility of radiation. Be sure the coil condenser is connected from the BATTERY side to ground. The points will become burned and pitted if placed on the coil side. Apply additional condensers to oil, water, gas or other electrical gauges. Carefully shield the aerial lead-in to the receiver, from the running board or the wind-shield post, with large loom and copper shielding. The capacity here MUST be as low as possible. The lead-in shield is grounded at the outer edge of the running board or at a point on the frame as close as possible to the lead-in post if a top antenna is used. Bond the instrument panel thoroughly to the car frame and body on each side.

After the hood is clamped in place to prevent radiation, the receiver should be turned on and dial tuned off a station with the volume control at maximum.

If motor noise is prevalent determine whether it is being conducted through the chassis or from the antenna. This test is made by disconnecting the antenna and grounding it to the shield. If ignition noise is heard upon again starting the motor it indicates chassis pickup which may be removed as follows:

Check distributor points and clean. Set to between .013" minimum and .015" maximum clearance. Next build-up the distributor rotor arm to a clearance of between .002" to .004" clearance to the distributor cap contacts. Solder may be used for this purpose, but it will eventually burn off and the noise will return. In the event low tension leads are bunched or in the same pipe housing with high tension leads, they should be separated as far as possible or removed from the same pipe. Removal and segregation is very effective. In some cases it might be necessary to shield and bond the low tension coil or distributor leads.

Motors mounted on rubber must be bonded with heavy braid to produce a short path to ground in order to break any radiating oscillatory circuit. Such bonds should be placed between the front motor support and frame and between the radiator top hose pipe and to the cylinder head where the water jacket is bolted. Move control cables slightly so that inner shaft contacts outer armour and tape in position under instrument panel.

When chassis pickup has been reduced to a minimum the antenna is then re-connected. Be sure the lead-in shield is grounded as previously mentioned.

Where a running board antenna is used it must be installed under the board farthest from the distributor and high tension system. If a top antenna is used it is usually necessary to by-pass the dome light lead. This should be done as close as possible to the windshield post through which it is wired. It will NOT help remove noise from this source if connected at any distance from the post. Another method is to break the dome lead and install an auxiliary switch at this point. In that case the condenser is not necessary. In many cases a condenser from one side of the ammeter to ground is very effective. Be sure to keep the radio battery cable out of the motor compartment. Running this cable through the motor side may cause severe interference.

The suggestions given need not all be necessary for a satisfactory installation. Therefore, they should be followed in order until the most effective remedy has been found. In any event, these rules should prove helpful in all cases. Spark plug suppressors are not required or furnished due to the added filtering incorporated in the 1935 Receiver. They should be applied only in extremely stubborn cases as a last resort after all bonding and filtering instructions have been followed.

Service

The Model 666 Autoradio receiver employs the following tubes in position shown on "Tube Layout," 6D6 R. F. Amplifier, 6C6 1st Detector and Oscillator, 6D6 I. F. Amplifier, 75 A. V. C. and 2nd Detector, 42 Power Amplifier and 84 Rectifier. The following subjects cover in an elementary manner the ordinary complaints encountered in service and in the corresponding corrections. It is suggested they be considered in the order listed when making a preliminary examination.

- | | |
|----------------|---------------------------|
| 1. Inoperative | 5. Dial off calibration |
| 2. Weak | 6. Intermittent operation |
| 3. Distortion | 7. Ignition noise |
| 4. Rattles | 8. Noisy reception |

After the trouble has been isolated the following procedure will prove effective. (Consult illustrations.)

1. Inoperative

- (a) Examine fuse and replace if blown. Make certain fuse insulating sleeve is over fuse. If fuse continues to blow, look for short in chassis wiring, defective tube or defective vibrator.
- (b) Defective tube—check all tubes on a tube tester and replace any that are shorted or below normal reading.
- (c) Loose or broken receiver battery cable.
- (d) Broken lead in chassis.
- (e) Tube or vibrator out of socket.
- (f) Broken antenna wire or antenna grounded.
- (g) Speaker plugs loose or out of receiver.

2. Weak

- (a) Grounded or partially grounded antenna.
- (b) Defective tube.
- (c) Weak storage battery.
- (d) Broken connection.
- (e) Defective vibrator.
- (f) Defective speaker.

3. Distortion

- (a) Defective tube.
- (b) Defective speaker.
- (c) Defective vibrator.

4. Rattles

- (a) Loose wires, rods, instruments, screws, washers, etc., on instrument panel or dash.
- (b) Loose speaker or speaker bolts.
- (c) Dirt in speaker.
- (d) Speaker voice coil warped.

5. Dial off calibration

- (a) See paragraph on resetting indicator under "Alignment".

6. Intermittent operation

- (a) Loose radio supply connection.
- (b) Short in antenna or lead-in.
- (c) Defective tubes.
- (d) Loose speaker connector.
- (e) Loose or defective vibrator.
- (f) Loose connection in receiver chassis.

7. Ignition interference

- (a) Suppressor defective or missing entirely.
- (b) Defective condenser at coil, ammeter or electrical gauges.
- (c) Lead-in shield not grounded.
- (d) Motor bonds broken or not tight electrically.
- (e) Chassis to case grounds broken.
- (f) Motor noise filter in set defective.
- (g) Pilot lamp shielding disconnected or broken.

8. Noisy reception

- (a) See "Ignition Interference"
- (b) Defective vibrator.
- (c) Loose antenna connection.
- (d) Loose fuse holder.
- (e) Defective tubes.
- (f) Loose tube shields.
- (g) Antenna shorting to frame of car.
- (h) Natural atmospheric or electrical disturbances.
- (i) Loose or defective high or low tension wiring.

To Remove Receiver from Car

- 1. Disconnect antenna lead from receiver.
- 2. Disconnect "A" lead at fuse receptacle.
- 3. Remove tuning cables by loosening knurled cable clamps at receiver.
- 4. Take out pilot light lead and shield connection.
- 5. Loosen mounting bolt on motor side and lift receiver out.

To Remove Chassis from Case

(Chassis does NOT have to be removed from case for ordinary repairs or service as removal of top lid permits easy access to tubes and vibrator.)

- 1. Remove top and bottom covers.
- 2. Remove ground lug from "A" filter.
- 3. Remove hot lead from "A" filter.
- 4. Disconnect "A" filter bond from case.
- 5. Remove leads from speaker jacks and ground lead to outer case.
- 6. Disconnect three bonds from chassis to case on bottom side.
- 7. Remove four rubber mounting screws from sides of case.

Following is a list of performance factors that will be of value in making accurate measurements.

Intermediate Frequency 252.5 K. C.

Sensitivity in Microvolts 1 to 1½

Power output in Milliwatts 3000

Power consumption—40 watts at 6 volts

Tube Operating Voltages:

Position	Tube	EF	EK	EG ¹	EG ²	EG ³	EP
R. F. Amplifier	6D6	5.6	4.1	*	4.1	76	200
1st Det.-Osc.	6C6	5.6	4.5	0	4.5	76	200
I. F. Amplifier	6D6	5.6	4.1	*	4.1	76	200
2nd Det. A. V. C.	75	5.6	1.3	0	0	—	165
Power Amp.	42	5.6	0	3	0	200	192
Rectifier	6Z4	5.6	200	—	—	—	—

f—Filament; k—Cathode; g¹—Control Grid; g²—Suppressor Grid; g³—Screen Grid; p—Plate; *—Depends on applied signal strength. All voltages measured from indicated points to ground. Battery voltage 6 volts. (Check voltages with condenser gang in full mesh.)

Alignment

Every Zenith automobile receiver is balanced on an accurate crystal controlled oscillator before leaving the factory and, unless a part is changed or the calibration has shifted, the adjustments should never be tampered with. Where it is absolutely necessary, however, a good test oscillator capable of delivering a modulated signal at 1600, 1400, 600 and 252½ K. C. will be essential. Proceed as follows:

I. F. Alignment:

To balance the I. F. Circuit, connect the 252½ K. C. test oscillator signal to the grid of the 6C6 tube through a 0.5 mfd. condenser and to ground. Adjust the 1st I. F. primary trimmer to maximum output from either the speaker or an output meter. Follow in the same manner with the secondary, and the primary and secondary of the 2nd I. F. transformer. This completes the I. F. circuit adjustment.

R. F. Alignment:

1. Next attach the test oscillator thru a 150 mmf. condenser to the antenna and ground leads.
2. Turn condenser plates completely out of mesh.
3. Set test oscillator to 1600 K. C.
4. Adjust the oscillator condenser trimmer (see fig. 1) to approximate resonance at 1600. Disregard dial setting for this operation.
5. Set test oscillator to 1400 K. C. and turn gang condenser to resonance and peak the three trimmers accurately. Now set pointer on dial to 1400 K. C. by turning indicator screw in rear center of head.
6. Set test oscillator to 600 K. C. and tune set to pick up the signal. Rock the dial over this point while adjusting the padder condenser (see fig. 1) for greatest output.

If the dial is off calibration at the low frequency end after this is done the indicator may be moved slightly in either direction to give a uniform accuracy over the entire scale.





Fig. 1—TUBE POSITION



Fig. 2



TOP OF CHASSIS WITH SPEAKER REMOVED

Parts and Prices

Chassis No. 5616

RESISTORS (CHASSIS ONLY)

Part Number	Description	Price
63-396	10M Ohm ¼ Watt.....	.20
63-398	40M Ohm ½ Watt.....	.20
63-400	250M Ohm ¼ Watt.....	.20
63-401	500M Ohm ¼ Watt.....	.20
63-402	500M Ohm Vol. Control & Switch Ass'mbly	1.00
63-420	500 Ohm ¼ Watt.....	.20
63-421	700 Ohm ¼ Watt.....	.20
63-422	200 Ohm ½ Watt.....	.20
63-423	600 Ohm ¼ Watt.....	.20
63-424	35M Ohm 1 Watt.....	.20
63-425	75M Ohm ¼ Watt.....	.20
63-428	1200 Ohm ¼ Watt.....	.20


CONDENSERS (CHASSIS ONLY)

22-82	.001 Mfd. 600 V.....	.25
22-162	.0001 Mfd. 600 V.....	.20
22-170	.1 Mfd. 400 V.....	.15
22-190	.1 Mfd. 200 V.....	.20
22-182	.00025 Mfd. 600 V.....	.12
22-212	.05 Mfd. 400 V.....	.20
22-250	.05 Mfd. 200 V.....	.15
22-251	.5 Mfd. 100 V.....	.40
22-327	.02 Mfd. 200 V.....	.15
22-344	Three-Gang Variable.....	4.00
22-347	4. x S. Mfd. 350 V.....	1.75
22-348	.001 Mfd. 600 V.....	.20

22-350	.25 Mfd. 120 V.....	.20
22-354	.007 Mfd. 750 V.....	.20
22-355	.01 Mfd. 1400 V.....	.20
22-357	.01 x .02 Mfd. 750 V.....	.50
22-358	.002 Mfd. 600 V.....	.20
22-359	Padder.....	.45

MISCELLANEOUS CHASSIS PARTS COILS AND CHOKES

20-96	Antenna Coil Assembly.....	.60
20-97	R. F. Coil Assembly.....	.75
20-98	Oscillator Coil Assembly.....	.60
20-103	Filament "A" Choke.....	.15
95-262	1st I. F. Transformer.....	1.25
95-263	2nd I. F. Transformer.....	1.25
S-2778	R. F. Choke.....	.15
S-3364	Motor Noise Filter.....	1.00
46-101	Tone Control Knob (Knob Spring only, see 80-107).....	.10
52-44	"A" Battery Cable.....	.65
52-59	Antenna Cable.....	.50
54-76	¼ x 20 Knurled Coupling Shaft Nuts..	.08
78-100	Socket 6D6.....	.10
78-101	Socket 75.....	.10
78-102	Socket 42.....	.10
78-113	Socket 6D6.....	.10
78-114	Socket 6Z4.....	.10
78-115	Socket Vibrator.....	.10
80-107	Tone Control Knob Spring.....	.01
85-66	Tone Control Switch.....	.40



BOTTOM OF CHASSIS

Parts and Prices, Cont.

MISCELLANEOUS CHASSIS PARTS (Contd.)

Part Number	Description	Price
93-125	No. 6 Lock Washers	\$.15C
93-220	Bakelite Washer for Chassis Mtg. Screws	.02
94-185	Rubber Bushing for Chassis Mtg. Screws	.02
95-258	Power Transformer	2.00
95-259	Hum Filter Choke	.75
97-75	10/32 x 3/4 Wing Screw for Box Cover	.02
114-27	No. 8 x 3/4 Chassis Box Screws	.01
190-4	Vibrator	5.00
MS-330	Chassis Box Top Cover and Clip Assem.	1.00
24-88	Chassis Box Bottom	.85
MS-256	Chassis Box Body Less Cover and Top	1.50

SPEAKER

*49-100	6" Dynamic Speaker (with output transformer)	5.00
	Cone & Voice Coil Assemb.	2.30
	Field Coil	2.00

REMOTE CONTROL UNIT

170-12	Zenith Control Unit (with knobs and mounting brackets—less cable)	\$ 5.00
7-5	Control Unit Bezel	.10
26-83	Zenith Dial Scale Assembly	.30
46-117	Volume and Tuning Knobs	.20
52-63	Pilot Lamp Cable and Socket Assemb.	.30
76-156	24" Tuning Control Cables	1.25
26-157	24" Volume Control Cables	1.25
80-110	Knob Springs	.01
100-27	6-8 V. Pilot Lamp	.15
192-7	Unbreakable Dial Glass	.15

SUPPRESSOR AND MOUNTING PARTS

22-193	.5 Mfd. Ignition Coil Condenser	.45
22-194	.5 Mfd. Generator Coil Condenser	.50
52-44	"A" Battery Cable	.60
57-478	Set Mounting Plate	.25
63-336	15 M Ohm Dist. Suppressor	.35
67-107	10/32 x 3/4 RHM Screws (8 used)	C .35
93-127	No. 10 Lock Washer (8 used)	C .35
93-222	7/16 Lock Washer	.01
93-223	Mounting Bolt Washer	.02
136-6	15 Ampere Fuse	.06
144-14	Mounting Bolt and Nut	.05
196-1	Mounting plate Gasket	.03

*Speakers are numbered 49-100U, 49-100-R, 49-100-M designating three different types. Therefore, when ordering speaker or speaker parts refer to the number on speaker at all times and order by that part number accordingly.

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

Service Bulletin



MODEL 668

Chassis 5626

Model 668 incorporates the same chassis as Model 666 except for the following mechanical parts changes. Use Model 666 service bulletin and diagram.

<u>Model 668 parts added</u>		<u>Model 666 parts omitted</u>	
	Price		
24-87	Chassis box cover.....	MS-350	same
24-88	" " bottom.....	24-88	"
10-42	" " body.....	MS-256	"
10-43	Speaker assem. shell only..	None used	
49-114	8" dynamic speaker less transformer.....	49-100 6" dynamic speaker with transformer.....	
	Cone & voice coil for 49-114	Cone & voice coil for 49-100.....	
95-285	Output transformer for 49-114(mtg.in chassis).....	Output transformer for 49-100.....	
	Field coil for 49-114.....	Field coil for 49-100	
52-69	Speaker cable	None used	
97-92	Speaker mounting stud.....	" "	
S-3665	Complete speaker assembly with case and cable.....	External speaker not used	
	9.00		


Note - All Model 668s use Zenith control head, part #170-16.

ALL PRICES SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.



DIAG. PART NO.	DESCRIPTION	W.
C1	22-747 .0005	600K
C2	22-319 .005	200V
C3	22-190 .1	200K
C4	22-345 .0011	600K
C5	22-162 .0001	600K
C7	22-243 .01	400K
C8	22-229 .005	600K
C9	22-250 .05	200K
C10	22-358 .002	600K
C12	22-407 2 MFD. ELECT. 450V	
C13	22-407 5	
C14	22-407 4	
C15	22-406 .00036 VARIABLE.	
C16	22-205 200-350 MMFD. PARADER.	
R1	63-290 260M OHMS	4W.
R3	63-300 990	4W.
R4	63-353 19M	4W.
R5	63-263 30M	4W.

DIAG. PART NO.	DESCRIPTION	W.
R6	63-280 49M OHMS	4W.
R7	63-376 190M	4W.
R8	63-293 990M	4W.
R9	63-258 490M	4W.
R10	63-455 3M	VOL. CONTROL.
R11	63-265 220	4W.
1	5-3673 ANT. COIL ASSEMBLY.	
2	95-287 1ST I.F. TRANS.	
3	95-284 2ND I.F. TRANS.	
4	85-76 BAND SELECT. TC SWITCH	
5	49-115 SPEAKER-COMPLTE.	
6	5-3674 OSC. COIL ASSEMBLY	
7	20-02 ANT. CHOKE	
8	95-297 115V-60 CYCLE TRANS.	
9	95-288 115V-50 CYCLE VAR. VOLT. TRANS.	
10	95-296 115V-25	

TUBE	POSITION	Rf	Ek	Eg1	Eg2	Eg3	Ep
6A7	1st. Det.	6.1	27	0	111	-	231
	Osc.			12	-	-	150
6F7	I.F.	6.1	25	0	111	-	231
	2nd. Det.			0	-	-	195
42	PWR.	6.1	0	-15	231	-	219
80	RECT.	5	-	-	-	-	231


Line 115 V.

f - heaters; k - cathode; g1 - control grid; g2 - screen grid; g3 - suppressor grid; p - plate.

All measurements taken from point indicated to ground, using a 1,000 ohm per volt D.C. meter (except heater).

Alignment

- (1) Balance I. F. transformer at 456 K.C.
 - (2) Place switch in left or broadcast position. Set dial pointer at 1500 K.C. and align trimmers on gang to resonance. Align broadcast padder at 540 K.C. slowly rocking pointer past 540 on dial to position giving strongest signal.
- There are no adjustments for the short wave band.



PARTS AND PRICES

MODELS 4-P-26

4-T-26

4-P-51

4-T-51

Chassis #5401

Resistors

63-258	490 M	Ohm	$\frac{1}{4}$	Watt Resistor		\$.20
63-263	30M	"	$\frac{1}{2}$	"		.20
63-265	220	"	$\frac{1}{2}$	"		.20
63-280	49M	"	$\frac{1}{2}$	"		.20
63-290	260M	"	$\frac{1}{2}$	"		.20
63-293	990M	"	$\frac{1}{2}$	"		.20
63-300	990	"	$\frac{1}{2}$	"		.20
63-376	190M	"	$\frac{1}{2}$	"		.20
63-455	Volume Control Assembly					1.00

Condensers

22-147	.0005	Mfd.	600	V.		.15
22-162	.0001	"	600	V.		.20
22-205	200-500M	Mfd.	Padder			.35
22-229	.005	Mfd.	600	V.		.15
22-243	.01	"	400	V.		.15
22-250	.05	"	200	V.		.20
22-319	.005	"	200	V.		.20
22-345	.0011	"	600	V.		.15
22-358	.002	"	600	V.		.20
22-406	2-Gang Variable					2.50
22-407	2 x 4 x 8	Mfd.	450	V.		1.75

Coils, Chokes, Etc.

S-3673	Antenna Coil Assembly					1.00
S-3674	Oscillator Coil Assembly					.65
S-3720	1st I.F. Transformer Assembly					1.25
95-284	2nd I.F. Transformer Assembly					1.00
20-82	Antenna Choke					.25

Miscellaneous

S-3717	Dial Pointer and Bushing Assembly					.25
S-3718	Dial Scale and Frame Assembly					.50
46-122	Tuning Knobs					.10
49-115	5" Dynamic Speaker (Model 26)					4.50
	Cone and Voice Coil for 49-115					2.00
	Output Transformer for 49-115					1.75
	Field Coil for 49-115					1.50
49-116	8" Dynamic Speaker for Model 51					6.00
	Cone and Voice Coil for Model 51					2.50
	Output Transformer for Model 51					1.75
	Field Coil for Model 51					1.50
78-82	Type 80 Socket (Wafer Type)					.10
78-102	"	42	"	"		.10

PARTS AND PRICES

PAGE 2

MODELS 4-P-26, 4-P-51

4-T-26, 4-T-51

Chassis #5401

Miscellaneous Cont'd

78-103	Type 6F7 Socket (Wafer Type).....	\$.10
78-106	" 6A7 " " "	.10
78-128	Speaker Plug Socket	.10
78-129	Voltage Indicator Socket (25 Cycle only)	.10
85-76	Band Selector and Tone Control Switch	.35
95-297	115 V., 60 Cycle Power Transformer	2.50
95-296	All Voltage 25 Cycle Power Transformer	4.75
100-23	6.3 V. Pilot Lamp	.15
126-191	Tube Shield	.15

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
Chicago, Illinois, U.S.A.
May 13, 1935

Zenith Radio Corporation

Socket Voltages

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6A8	1st Det. Osc.	0	6 AC	220	90	6	125	6 AC	14	0
6P7	I.F. 2nd Det.	0	6 AC	0	220	100	100	0	13	0
6F6	PWR	0	0	200	220	-1	-	6 AC	0	-
5Y3	Rect.	0	220	-	230 AC	-	230 AC	-	220	-



Line Voltage 110

Antenna and Ground
Disconnected.

All voltages measured from point indicated to ground, using a 1000 ohm per volt D.C. meter (unless marked otherwise.)

Alignment

- (1) Balance I.F. transformer at 456 K.C.
- (2) Place switch in left or broadcast position. Set dial pointer at 1500 K.C., and align trimmers on gang to resonance. Align broadcast padder at 540 K.C. slowly rocking pointer past 540 on dial to position giving strongest signal. There are no adjustments for the short wave band.





PARTS AND PRICES
Chassis #5403
(after serial #54439)

Models 4-T-26
4-T-51

Resistors

63-258	490 M Ohm	$\frac{1}{4}$ Watt		\$.20
63-263	30 M "	"		.20
63-265	220 "	"		.20
63-280	49 M "	"		.20
63-290	260 M "	"		.20
63-293	990 M "	"		.20
63-300	990 "	"		.20
63-353	19 M "	"		.20
63-376	190 M "	"		.20
63-455	3 M "	Volume Control and Switch Assembly		1.00

Condensers

22-147	.0005 Mfd.	600 V.		.15
22-162	.0001 "	600 V.		.20
22-190	.1 "	200 V.		.20
22-205	200-550 Mmfd.	Padder		.35
22-229	.005 Mfd.	600 V.		.15
22-243	.01 "	400 V.		.15
22-250	.05 "	200 V.		.15
22-319	.005 "	200 V.		.20
22-358	.002 "	600 V.		.20
22-406	2-gang	Variable Condenser		2.50
22-407	8 x 4. x 2.	Mfd. 450V.		1.75
22-448	.004 Mfd.	600 V.		.15

Coils, Chokes, Etc.

20-82	Antenna Choke		.25
95-284	2nd I.F. Transformer		1.00
95-287	1st I.F. "		1.25
S-4015	Antenna Coil Assembly		1.00
S-4017	Oscillator Coil Assembly		.75

Miscellaneous

S-3717	Dial Pointer and Bushing Assembly		.25
S-3718	" Scale and Frame Assembly		.50
19-58	New Type Grid Clips		.01
46-122	Tuning Knobs (3 used)		.10
49-115	5" Dynamic Speaker (Model 26)		4.50
	Cone and Voice Coil for 49-115 Speaker		2.00
	Output Transformer for 49-115 Speaker		1.75
	Field Coil for 49-115 Speaker		1.50
49-116	8" Dynamic Speaker (Model 51)		6.00
	Cone and Voice Coil for 49-116 Speaker		2.50
	Output Transformer for 49-116 Speaker		1.75
	Field Coil for 49-116 Speaker		1.50
58-30	4-prong Speaker Plug		.25
78-128	5-prong " " Socket		.10
78-132	Type C&B Socket		.15

PAGE 2


PARTS AND PRICES

Miscellaneous Cont'd

78-136	Type 5Y3 Socket	\$.15
78-137	" 6F6 "	.15
78-138	" 6P7 "	.15
85-76	Band Selector and Tone Control Switch	.35
95-288	Variable Voltage 50 Cycle Power Transformer	4.00
95-296	115 Volt, 25 Cycle Power Transformer	4.75
95-297	115 " 60 " " "	2.50
100-23	6.3 Volt Pilot Lamp	.15
126-191	Tube Shields	.15

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
Chicago, Illinois, U.S.A.
August 22, 1935



6A8-6A8-G
1ST DET-OSC.

6P7-G
I.F. 2nd DET.

6F6-6F6-G
POWER.

DIRG PART
No. No.

DESCRIPTION

DESCRIPTION

DESCRIPTION

- | | | | | | | |
|-----|--------|---------------|--------------|----|--------|-------------------------|
| C1 | 22-147 | .0005 MFD. | 600V. | 1 | 54015 | ANT. COIL ASSEM. |
| C2 | 22-319 | .005 | 200V. | 2 | 95-287 | 1st I.F. TRANS. |
| C3 | 22-198 | .1 | 200V. | 3 | 95-284 | 2nd I.F. TRANS. |
| C4 | 22-448 | .004 | 600V. | 4 | 85-83 | BAND SELECT. & T.C. SW. |
| C5 | 22-162 | .0001 | VAR. VOLTAGE | 5 | 49-115 | 5" SPKR. - MOD. 4T26 |
| C6 | 22-406 | 25 MFD. | 400V. | 6 | 54017 | OSC. COIL ASSEM. |
| C7 | 22-243 | .01 | 200V. | 7 | 20-82 | ANT. CHOKE |
| C8 | 22-229 | .005 | 200V. | 8 | 95-297 | 115V. 60~ TRANS. |
| C9 | 22-250 | .05 | 600V. | 9 | 95-288 | " 50~ " |
| C10 | 22-358 | .002 | 600V. | 10 | 95-296 | " 25~ " |
| C11 | 22-205 | 200 .550 MFD. | 450V. | 11 | 53865 | COUPLING CAPACITY |
| C12 | 22-407 | 8 MFD. | 450V. | 12 | 49-116 | 8" SPKR. MOD. 4T51. |
| C13 | 22-407 | 8 MFD. | 450V. | | | |
| C14 | 22-407 | 4 MFD. | 450V. | | | |

- | | | | |
|-----|--------|------------|-----|
| R1 | 63-290 | 260 M OHMS | 4W. |
| R2 | 63-265 | 220 | 4W. |
| R3 | 63-300 | 990 | 4W. |
| R4 | 63-353 | 19M | 2W. |
| R5 | 63-263 | 30M | 2W. |
| R6 | 63-280 | 49M | 4W. |
| R7 | 63-376 | 190M | 4W. |
| R8 | 63-293 | 990M | 4W. |
| R9 | 63-258 | 490M | 4W. |
| R10 | 63-455 | 3M | 4W. |

I.F. FREQUENCY 456 KC.
4TUBE SUPERHETERODYNE.
CHASSIS No 5403
SERIAL No 54439 & ABOVE.

ZENITH RADIO CORP.
CHICAGO, ILL.

MODELS 4726-4751

(IMPROVED SHORT WAVE)

Zenith Radio Corporation

Socket Voltages

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6A8	1st Det. Osc.	0	6 AC	220	90	6	125	6 AC	14	0
6P7	I.F. 2nd Det.	0	6 AC	0	220	100	100	0	13	0
6F6	PWR	0	0	200	220	-1	-	6 AC	0	-
5Y3	Rect.	0	220	-	230 AC	-	230 AC	-	220	-


Line Voltage 110

Antenna and Ground
Disconnected.


All voltages measured from point indicated to ground, using a 1000 ohm per volt D.C. meter (unless marked otherwise.)

Alignment

- (1) Balance I.F. transformer at 456 K.C.
- (2) Place switch in left or broadcast position. Set dial pointer at 1500 K.C., and align trimmers on gang to resonance. Align broadcast padder at 540 K.C. slowly rocking pointer past 540 on dial to position giving strongest signal. There are no adjustments for the short wave band.



**BOTTOM VIEW
OF SOCKET**





PARTS AND PRICES
Chassis #5403
After Serial No. 54439

Model 4-T-26
Model 4-T-51

Condensers

22-147	.0005 Mfd. 600 Volt	\$.15
22-162	.0001 " 600 Volt	.20
22-190	.1 " 200 Volt	.20
22-205	200-550 Mmfd. Padder	.35
22-229	.005 Mfd. 600 Volt	.15
22-243	.01 " 400 Volt	.15
22-250	.05 " 200 Volt	.15
22-319	.005 " 200 Volt	.20
22-358	.002 " 600 Volt	.20
22-406	Two Gang Variable Condenser	2.50
22-407	8.x4.x2. Mfd. 450 Volt	1.75
22-448	.004 Mfd. 600 Volt	.15

Resistors

63-258	490 M Ohm $\frac{1}{4}$ Watt	.20
63-263	30 M Ohm $\frac{1}{2}$ Watt	.20
63-265	220 Ohm $\frac{1}{4}$ Watt	.20
63-280	49 M Ohm $\frac{1}{4}$ Watt	.20
63-290	260 M Ohm $\frac{1}{4}$ Watt	.20
63-293	990 M Ohm $\frac{1}{4}$ Watt	.20
63-300	990 Ohm $\frac{1}{4}$ Watt	.20
63-353	19 M Ohm $\frac{1}{2}$ Watt	.20
63-376	190 M Ohm $\frac{1}{4}$ Watt	.20
63-455	3 M Volume Control Assembly	1.00

Coils, Chokes, Etc.

20-82	Antenna Choke	.25
95-284	2nd I.F. Transformer	1.00
95-287	1st I.F. Transformer	1.00
S-4015	Antenna Coil Assembly	1.00
S-4017	Oscillator Coil Assembly	.75

Miscellaneous

26-92	Dial Scale only (Less Frame).....	.35
S-3718	" " and Frame Complete	.50
S-3717	" Pointer and Bushing	.25
46-122	Tuning Knobs (3 used).....	.10
49-115	5" Dynamic Speaker	4.50
	Cone and Voice Coil for 49-115	2.00
	Output Transformer for 49-115	1.75
	Field Coil for 49-115	1.50
49-116	8" Dynamic Speaker	6.00
	Cone and Voice Coil for Model 51	2.50
	Output Transformer for Model 51	1.75
	Field Coil for Model 51	1.50
58-30	Four Prong Speaker Plug	.25
78-132	6-A-8 Wafer Type Socket	.15
78-136	5-Y-3 " " "	.15

PARTS AND PRICES
Page 2


Models 4-T-26, 4-T-51
Chassis #5403

Miscellaneous (Cont'd.)

78-137	6-F-6 Wafer Type Socket	\$.15
78-138	6-F-7 " " "	.15
78-128	Four Contact Speaker Plug Socket	.10
85-83	Band Selector and Tone Control Switch	.75
95-288	All Voltage 50 Cycle Power Transformer	4.00
95-296	" " 25 " " "	4.75
95-297	115 Voltage 60 Cycle Power Transformer	2.50
100-23	6.3 Volt Pilot Lamp	.15
126-191	Tube Shield	.15

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR
DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION
Chicago, Illinois, U.S.A.
January 2, 1936.



QING PART	No.	DESCRIPTION	VAR
	1	22-300 0.5 MFD.	200K
	2	22-250 0.5 MFD.	200K
	3	22-127 0.5 MFD.	200K
	4	22-199 0.5 MFD.	200K
	5	22-192 0.0025 MFD.	200K
	6	22-185 0.01 MFD.	200K
	7	22-185 0.02 MFD.	200K
	8	22-170 0.01 MFD.	200K
	9	22-170 0.01 MFD.	200K
	10	22-170 0.01 MFD.	200K
	11	22-305 2-35 MFD.	440K
	12	22-292 500-1000 MFD.	440K
	13	22-125 0.5 MFD.	200K
	14	22-304 0.036 MFD.	200K
	15	22-435 0.02 MFD.	200K
	16	49M 49M OHMS	4W
	17	63-377 170 OHMS	4W
	18	63-250 490M	4W
	19	63-293 990M	4W
	20	63-373 11M	4W
	21	63-366 200M VOL. CONTROL	4W
	22	63-351 17035 CARBON	4W
	23	63-475 50M TONE CONTROL	4W
	24	63-278 99M OHMS	4W

- 53397 SELECTOR DET. COIL
- 53397 SHORT WAVE SW.
- 53397 OSC. COIL ASSEMB.
- 53397 1ST I.F. TRANS.
- 53397 2ND I.F. TRANS.
- 49-01 6-SPHR-1000-FIELD-55-56
- 49-01 6-SPHR-1000-FIELD-55-56
- 49-01 6-SPHR-1000-FIELD-55-56
- 49-01 6-SPHR-1000-FIELD-55-56
- 49-01 6-SPHR-1000-FIELD-55-56

MODELS 5529-5556

THREE BANDS: 535 KC.-1520 KC.
1460 KC.-4350 KC.
5800 KC.-18300 KC.

I.F. FREQUENCY 252.5 KC.
5-TUBE SUPERHETERODYNE
CHASSIS No. 5513-A

ZENITH RADIO CORP.
CHICAGO, ILL.

CIRCUIT CHANGES
FOR MODELS 5513-A


Socket Voltages

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6A8	1st Det. Osc.	0	5.8 _{ac}	260	80	-.1	210	0	4	0
6K7	I. F.	0	5.8 _{ac}	260	80	0	-	0	5.2	0
6B6	2nd Det. A.V.C.	0	5.8 _{ac}	135	0	0	-	0	1.5	0
6F6	PWR	0	5.8 _{ac}	240	260	-.7	-	0	0	-
5Y3	Rect.	0	260	-	270 _{ac}	-	270 _{ac}	-	260	-

Line Voltage 110

Antenna and Ground Disconnected

All voltages measured from point indicated to ground, using a 1000 ohm per volt D.C. meter (unless marked otherwise).




BOTTOM VIEW
OF SOCKET

Alignment

1. Balance I.F. transformers at 252.5 K.C. with test oscillator connected to control grid of 6A8 and ground.
2. Turn band switch to C band. Connect test oscillator to antenna and ground leads. Set test oscillator at 15 Megacycles. Adjust oscillator trimmer on gang condenser for correct dial reading.
3. Adjust detector trimmer (located on top of chassis between front section of gang condenser and coil) for maximum output.
4. Turn band switch to A band. Adjust oscillator trimmer (located on right side underneath chassis)

for correct dial reading at 1400 K.C. also adjust preselector and detector trimmers on gang for maximum output.

5. Adjust oscillator padder (next to oscillator section of gang on top of chassis) while rocking pointer back and forth past 600 K.C. to the combination giving greatest output.
6. Recheck 1400 K.C.
7. Repeat entire procedure.





PARTS AND PRICES
Chassis #5513 - Domestic
#5513A - Export

Models 5-S-29, 5-S-56
5-S-29 A,
5-S-56A

Dial Assembly

S-3867	Complete Split Second Dial Assembly	\$3.75
26-105	Dial Scale	.40
32-6	Drive Belt	.15
59-48	Split Second Pointer	.10
59-49	Special Z Pointer	.15
93-231	Glass Cushion Washer	.05
100-23	6.3 Volt Pilot Lamp	.15
132-14	Dial Glass Retainer Ring	.05
192-6	Dial Glass	.20

Condensers

22-82	.001 Mfd. 600 V.	.25
22-125	8. " 440 V.	1.00
22-127	25 Mmfd. 600 V.	.20
22-170	.1 Mfd. 400 V.	.25
22-182	.00025 Mmfd. 600 V.	.12
22-185	.01 Mfd. 200 V.	.20
22-188	.02 " 400 V.	.15
22-199	.5 " 200 V.	.35
22-250	.05 " 200 V.	.15
22-292	500 - 1000 Mmfd. Padder	.45
22-304	.0036 Mfd. 600 V.	.30
22-305	2-35 Mmfd. Padder	.15
22-380	Gang Variable	3.50
22-417	.1 Mfd. 600 V.	.25
22-435	.02 Mfd. 600 V.	.15

Resistors

63-258	490 M Ohm $\frac{1}{4}$ Watt	.20
63-277	170 " $\frac{1}{4}$ "	.20
63-278	99 M " $\frac{1}{4}$ "	.20
63-280	49 M " $\frac{1}{4}$ "	.20
63-293	990 M " $\frac{1}{4}$ "	.20
63-351	17,035 Candohm.	.65
63-366	Volume Control & Switch Assembly.....	.90
63-373	11 M Ohm $\frac{1}{4}$ Watt	.20
63-409	Volume Control & Switch Assembly.....(Export Only).....	1.00
63-475	Tone Control Assembly.....	.65

Coils and Chokes

95-244	1st I. F. Transformer Assembly.....	1.50
95-245	2nd I. F. Transformer Assembly.....	1.50
S-3129	Oscillator Coil Assembly	1.00
S-3377	16-Meter Detector Coil Assembly.....	.75
S-3397	Selector-Detector Coil Assembly.....	2.00

Miscellaneous

44-7	Phonograph Jack.....(Export Only).....	.15
46-124	Volume and Tone Control Knobs.....	.20

PARTS AND PRICES

-2-

Models 5-S-29, 5-S-56
5-S-29 A,
5-S-56 A


Miscellaneous (Cont'd)

46-127	Tone Control Knob.....	.15
46-130	Band Selector Knob.....	.20
46-131	Tuning Knob.....	.15
49-79	8" Dynamic Speaker (Model 56)	8.00
	Cone and Voice Coil for 49-79	2.50
	Field Coil for 49-79.....	2.00
	Output Transformer for 49-79.....	2.00
49-81	6" Dynamic Speaker (Model 29)	5.50
	Cone and Voice Coil for 49-81.....	2.00
	Field Coil for 49-81	2.00
	Output Transformer for 49-81	1.50
57-483	Dial Escutcheon Plate	.50
78-131	6K7 Wafer Type Tube Socket.....	.15
78-132	6A8 Wafer Type Tube Socket.....	.15
78-136	5Y3 " " " "	.15
78-137	6F6 " " " "	.15
78-143	6B6 " " " "	.15
85-39	Phono Switch - D. P. D. T. ... (Export only).....	1.00
85-62	Band Selector Switch	.80
95-229	All Voltage 25 cycle Power Transformer	6.50
95-234	117 Volt, 50-60 cycle Power Transformer	3.75
126-127	Tube Shield	.10

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS, U. S. A.
July 5, 1935

1/2" DIA. 1/2" DIA.
 1/2" DIA. 1/2" DIA.
 1/2" DIA. 1/2" DIA.



I.F. FREQUENCY 252.5 KG.
 6 TUBE SUPERHETERODYNE.
 CHASSIS NO 5619
 MODELS 6-5-27-6-5-52
 ZENITH RADIO CORP.
 CHICAGO, ILL.

5-15-35-M.A.

PART NO.		DESCRIPTION	
1	5-3397	SELECT DET. COIL	1/4 W.
2	8-5-80	SHORT WAVE SW	1/4 W.
3	5-3-29	OSC. COIL ASSEM.	1/4 W.
4	92-302	1ST. I.F. TRANS.	1/4 W.
5	95-303	2ND. I.F. TRANS.	1/4 W.
6	49-117	8" S.P.H.R. 1000-5-27	1/4 W.
7	49-118	10" S.P.H.R. 1000-5-27	1/4 W.
8	95-289	PHWR. TRANS. 60V	1/4 W.
9	95-290	PHWR. TRANS. 25V	1/4 W.
10	5-3377	1GM DET. COIL ASSEM	1/4 W.
11	85-39	PHONO. SWITCH	1/4 W.
12	44-7	PHONO. JACK	1/4 W.

Zenith Radio Corporation


Socket Voltages

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6A8	1st. Det. Osc.	0	5 _{ac}	225	70	-.1	190	0	0	0
6K7	I.F.	0	5 _{ac}	225	70	0	-	0	0	0
6H6	2nd Det.	0	5 _{ac}	-1	-2.5	-1	-	0	-2.5	-
6K7	1st. Aud.	0	5 _{ac}	60	14	-2.5	-	0	-2.5	0
6F6	PWR	0	5 _{ac}	220	225	-2.5	-	0	-2.5	-
5Y3	Rect.	0	300	-	305 _{ac}	-	305 _{ac}	-	300	-

Line voltage 110.

Antenna and Ground disconnected.


All voltages measured from point indicated to ground, using a 1000 ohm per volt D.C. meter (unless marked otherwise).



**BOTTOM VIEW
OF SOCKET**

Alignment

- (1) Balance I.F. transformers at $252\frac{1}{2}$ K.C. with test oscillator connected to control grid of 6A8 and ground.
- (2) Turn band switch to "C" Band. Connect test oscillator to antenna and ground leads and set for 15 megacycles. Adjust oscillator trimmer on gang condenser to secure correct dial reading.
- (3) Adjust detector trimmer (located on bracket on top of detector coil) for maximum output.
- (4) Turn band switch to "A" Band. Adjust oscillator trimmer (through hole in top of chassis next to oscillator) for correct dial reading at 1400 K.C. Also adjust preselector and detector trimmers on gang for maximum output.
- (5) Adjust oscillator padder (next to oscillator section of gang through hole in top of chassis) while rocking pointer back and forth past 600 K.C. to the combination giving greatest output.
- (6) Recheck at 1400 K.C.
- (7) Repeat entire procedure.





PARTS AND PRICES
Chassis #5619 - Domestic
#5619 A - Export
Dial Assembly

Models 6-S-27, 6-S-27 A,
6-S-52, 6-S-52 A

7-6	Dial Glass Bezel	(part of 57-511).....	-
26-97	Aeroplane Dial Scale		\$1.00
32-7	Dial Drive Belt		.20
34-49	Condenser Shaft Gear		.25
34-50	Pinion Gear		.05
34-51	Lower Pinion and Gear		.15
59-40	Special Z Pointer		.15
59-41	Split Second Pointer and Bushing		.10
61-34	Drive Pulley		.10
61-35	Shaft Pulley and Sleeve		.25
61-36	Tension Pulley		.05
76-178	Drive Shaft		.10
76-180	Tension Pulley Shaft		.05
80-111	Dial Spring		.25
80-112	Tension Pulley Spring		.10
83-407	Dial Light Diffusion Strip		.05
100-23	6.3 V. Pilot Lamp		.15
159-11	Snap Buttons		.02
188-2	Retaining Ring		.10
192-10	Dial Glass	(part of 57-511)....	-
196-4	Dial Glass Gasket.....	" " " "	-
198-1	Dial Reflector		.40
S-3777	Tension Pulley and Spring Assembly		.30

Condensers

22-82	.001	Mfd.	600	Volt		.25
22-127	.000025	"	600	"		.20
22-162	.0001	"	600	"		.20
22-170	.1	"	400	"		.25
22-182	.00025	"	600	"		.12
22-188	.02	"	400	"		.15
22-190	.1	"	200	"		.20
22-250	.05	"	200	"		.15
22-292	500-1000	Mmfd	Padder			.45
22-304	.0036	Mfd.	600	Volt		.30
22-305	2-35	Mmfd.	Padder			.15
22-414	8 x 8	Mfd.	450	Volt		2.00
22-415	3-Gang	Variable	Condenser	Gang		3.50
22-417	.1	Mfd.	600	Volt		.25
22-418	2-35	Mmfd.	Padder			.15
22-420	10.	Mfd.	25	Volt		.65
22-423	8 x 8	"	450	"		2.25
22-435	.02	"	600	"		.15

Resistors

63-258	490 M	Ohm	$\frac{1}{4}$	Watt		.20
63-278	99 M	"	$\frac{1}{4}$	"		.20
63-280	49 M	"	$\frac{1}{4}$	"		.20
63-293	990 M	"	$\frac{1}{4}$	"		.20
63-373	11 M	"	$\frac{1}{4}$	"		.20
63-453	Candohm					.85
63-456	Volume Control and Switch Assembly					1.00

PARTS AND PRICES

-2-

Models 6-S-27, 6-S-27 A,
6-S-52, 6-S-52 A

Resistors (contd.)

63-458	Tone Control Assembly	\$.80
63-473	Volume Control and Switch Assembly	1.00

Coils and Chokes

95-302	1st I.F. Transformer Assembly	1.25
95-303	2nd I.F. " "	1.25
S-3129	Oscillator Coil Assembly	1.00
S-3377	16-meter Detector Coil Assembly	1.00
S-3397	Selector and Detector Coil Assembly	2.00

Miscellaneous

44-7	Phono Jack	(export only).....	.15
46-127	Volume, Tone and Tuning Knobs		.15
46-128	Band Selector Switch Knob		.20
49-117	8" Dynamic Speaker	(Model 27).....	7.00
	Cone and Voice Coil for 49-117		2.50
	Field Coil for 49-117		2.00
	Output Transformer for 49-117		2.00
49-118	10" Dynamic Speaker		9.00
	Cone and Voice Coil for 49-118.....	(Model 52).....	3.25
	Field Coil for 49-118		2.00
	Output Transformer for 49-118		2.00
57-511	Dial Glass and Escutcheon Plate		1.50
58-30	4-Prong Speaker Plug		.25
78-129	Voltage Indicator Socket	(export only).....	.10
78-131	6K7 Wafer Type Tube Socket		.15
78-132	6A8 " " " "		.15
78-133	6H6 " " " "		.15
78-136	5Y3 " " " "		.15
78-137	6F6 " " " "		.15
83-334	Antenna and Ground Terminal Strip		.10
83-398	Voltage Indicator Socket Strip.....	(export only).....	.03
85-39	Phono Switch D.P.D. T.	(" ").....	1.00
85-80	Band Selector Switch		1.00
95-289	117-Volt, 50-60 cycle Power Transformer		3.50
95-290	25 cycle All Voltage Transformer		6.50
126-127	Tube Shields		.10

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
Chicago, Illinois, U.S.A.
June 21, 1935

Socket Voltages

256



PARTS AND PRICES
Chassis #5704 - Domestic
#5704 A - Export

Models 7-S-28, 7-S-30,
and 7-S-53

Dial Assembly

7-6	Dial Glass Bezel (part of 57-511)	-
26-94	Aeroplane Dial Scale	\$1.00
32-8	Drive Belt	.20
34-49	Condenser Shaft Gear	.25
34-50	Pinion Gear	.05
34-51	Lower Pinion and Gear	.15
56-44	Planetary Guide Pin	(furnished with 76-181).... -
59-40	Special Z Pointer	.15
59-41	Split Second Pointer	.10
61-35	Shaft Pulley and Sleeve	.25
61-36	Tension Pulley	.05
61-37	Dial Pulley	.05
76-180	Tension Pulley Shaft	.05
76-181	Planetary Drive Assembly	1.00
80-111	Dial Spring	.25
80-112	Tension Pulley Spring	.10
83-407	Dial Light Diffusion Strip	.05
100-23	6.3 Volt Pilot Lamp	.15
118-10	Band Switch Indicator Link	.05
159-11	Snap Buttons	.02
188-2	Retainer Ring	.10
196-4	Dial Glass Gasket (part of 57-511)	-
S-3777	Tension Pulley and Spring Assembly	.30
S-3782	Band Indicator Lever Arm and Bushing Assembly	.30
S-3783	" " Scale and Arm Assembly	1.00
S-2918	Dial Lamp Socket and Clip Assembly	.15

Condensers

22-82	.001	Mfd.	600	Volts		.25
22-127	.000025	"	600	"		.20
22-162	.0001	"	600	"		.20
22-170	.1	"	400	"		.25
22-188	.02	"	400	"		.15
22-190	.1	"	200	"		.20
22-205	200-550	Mmfd.	Paddder			.35
22-212	.05	Mfd.	400	Volts		.20
22-224	.1	"	300	"		.15
22-243	.01	"	400	"		.15
22-250	.05	"	200	"		.15
22-289	.0005	"	600	"		.12
22-345	.0011	"	600	"		.15
22-408	2-35	Mmfd.	Paddder			.25
22-409	3-Gang	Variable				3.50
22-410	.003	Mfd.	600	Volts		.40
22-411	.0023	"	600	"		.25
22-416	8.x 8.x 2.	Mfd.	450	Volts	(domestic only).....	2.50
22-417	.1	Mfd.	600	Volts		.25
22-420	10.	"	25	"		.65
22-422	8. x 8.x 2.	Mfd.	450	Volts	(export only).....	2.75
22-435	.02	Mfd.	600	Volts		.15

PARTS AND PRICES

-2-

Models 7-S-28, 7-S-30
and 7-S-53

Resistors

63-258	490 M	Ohm	$\frac{1}{4}$ Watt		\$.20
63-278	99 M	"	"		.20
63-280	49 M	"	"		.20
63-293	990 M	"	"		.20
63-353	19 M	"	"		.20
63-373	11 M	"	"		.20
63-453	Candohm				.75
63-457	400 M	Ohm	Volume Control.....(domestic only).....		1.00
63-458	50 M	"	Tone Control		.80
63-466	990	"	$\frac{1}{2}$ Watt		.20
63-474	400 M	"	Volume Control(export only).....		1.00

Coils and Chokes



20-82	Antenna Choke	.25
20-119	R.F. Plate Choke	.50
95-291	1st I.F. Transformer	1.25
95-292	2nd I. F. "	1.25
S-3697	Antenna Coil Assembly	1.00
S-3698	Detector Coil Assembly	.85
S-3699	Oscillator Coil Assembly	.85

Miscellaneous

44-7	Phonograph Jack.....(export only).....	.15
46-123	Band Selector Knob	.20
46-124	Volume and Tone Control Knobs	.20
46-125	Tuning Knob - (small)	.15
46-126	" " (large)	.15
49-117	8" Dynamic Speaker (Models 28 and 30)	8.00
	Cone and Voice Coil for 49-117	2.50
	Field Coil " " "	2.00
	Output Transformer " " "	2.00
49-122	12" Dynamic Speaker (Model 53)	10.00
	Cone and Voice Coils for 49-122	3.25
	Field Coil " " "	2.00
	Output Transformer " " "	2.00
57-511	Dial Glass and Escutcheon Plate	1.50
58-30	4-Prong Speaker Plug.....	.25
78-128	5-Prong Speaker Plug Socket	.10
78-129	Voltage Indicator Socket(export only).....	.10
78-131	6K7 Wafer Type Tube Socket	.15
78-132	6A8 " " " "	.15
78-133	6H6 " " " "	.15
78-136	5Y3 " " " "	.15
78-137	6F6 " " " "	.15
85-39	Phono Switch - D.P.D.T.	1.00
85-78	Band Selector Switch	1.50
95-289	115 Volt, 50-60 cycle Power Transformer	3.50
95-290	All Voltage, 25 " " " ..(export only).....	6.50
126-127	Tube Shields	.10

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS, U.S.A.
June 19, 1935



QMG	PART	DESCRIPTION	QMG	PART	DESCRIPTION
1	22-270	35M OHMS	1	5-3697	ANT COIL ASSEM.
2	63-260	45M	2	5-3698	DET COIL ASSEM.
3	63-373	11M	3	5-3699	1ST I.F. TRANS.
4	63-293	990M	4	5-3699	OSC COIL ASSEM.
5	63-481	400M	5	5-3704	INPUT TRANS.
6	63-268	15M	6	49-120	SPEAKER-MOD 55-54
7	63-450	1MEG	7	5-3703	POWER TRANS-50W
8	63-449	CANDOM	8	5-3704	50W RECT. (PHONO)
9	63-466	990 OHMS	9	5-3704	50W RECT. (PHONO)
10	63-300	990	10	5-3704	50W RECT. (PHONO)
11	63-240	1900	11	5-3704	50W RECT. (PHONO)
12	63-240	1900	12	5-3704	50W RECT. (PHONO)
13	22-409	VARIABLE	13	5-3704	50W RECT. (PHONO)
14	22-170	1	14	5-3704	50W RECT. (PHONO)
15	22-243	01	15	5-3704	50W RECT. (PHONO)
16	22-411	0023	16	5-3704	50W RECT. (PHONO)
17	22-345	001	17	5-3704	50W RECT. (PHONO)
18	22-205	200-550MMFD	18	5-3704	50W RECT. (PHONO)
19	22-127	001	19	5-3704	50W RECT. (PHONO)
20	22-409	2.35 MMFD	20	5-3704	50W RECT. (PHONO)
21	22-433	5	21	5-3704	50W RECT. (PHONO)
22	22-433	5	22	5-3704	50W RECT. (PHONO)
23	22-254	1/6	23	5-3704	50W RECT. (PHONO)
24	22-443	1/6	24	5-3704	50W RECT. (PHONO)
25	22-443	1/6	25	5-3704	50W RECT. (PHONO)
26	22-443	1/6	26	5-3704	50W RECT. (PHONO)
27	22-443	1/6	27	5-3704	50W RECT. (PHONO)
28	22-443	1/6	28	5-3704	50W RECT. (PHONO)
29	22-443	1/6	29	5-3704	50W RECT. (PHONO)
30	22-443	1/6	30	5-3704	50W RECT. (PHONO)

I.F. FREQUENCY 456 KC.
 TUBE SUPERHETERODYNE
 CHASSIS No. 5203
 MODEL 5 9-534-9-535
 ZENITH RADIO CORP.
 CHICAGO, ILL.

Zenith Radio Corporation

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6K7	R.F.	0	3 _{ac}	230	95	0	-	3 _{ac}	0	-.1
6A8	1st. Det. Osc.	0	3 _{ac}	230	95	0	140	3 _{ac}	0	-.1
6K7	I.F.	0	3 _{ac}	230	95	0	-	3 _{ac}	0	-.1
6H6	2nd Det. A.V.C.	0	3 _{ac}	-1	-1	0	-	3 _{ac}	-1	-
6C5	1st. Aud.	0	3 _{ac}	22	-	-2	-	3 _{ac}	-2	-
6C5	2nd Aud.	0	3 _{ac}	210	-	-2	-	3 _{ac}	0	-
6F6	PWR.	0	3 _{ac}	350	350	-3	-	3 _{ac}	27	-
5Y3	Rect.	0	360	-	350 _{AC}	-	350 _{AC}	-	360	-

Line Voltage 115

Antenna and Ground Disconnected

Voltages measured from point indicated to ground, using a 1000 ohm per volt meter, except heaters. (2 - 7)

Alignment


The use of an accurately calibrated service oscillator is imperative in the alignment of modern superheterodynes. The alignment procedure is as follows:

- (1) Connect service oscillator to grid of 6A8 and ground. Balance I. F. trimmers at 456 K.C.
- (2) Connect service oscillator to antenna and ground binding posts and set at 6 megacycles. Adjust oscillator trimmer on gang for correct dial reading, (6 megacycles on Band B).
- (3) Set service oscillator and pointer to 21 megacycles and

BOTTOM VIEW OF SOCKET

- adjust S.W. trimmer (through hole in top of chassis) for correct dial reading.
- (4) Recheck 6 megacycle adjustment.
 - (5) Set service oscillator and pointer to 1700 K.C. (Band A) and adjust broadcast trimmer (through hole in top of chassis) for correct dial reading.
 - (6) Set service oscillator at 600 K.C. Adjust broadcast paddler (through hole in top of chassis next to I.F. transformer), meanwhile rocking pointer to and fro past 600 K.C. on dial to combination giving greatest output.
 - (7) Readjust at 1700 K.C.

Note: These adjustments affect each other slightly and the entire procedure should be repeated to secure maximum results.





PARTS AND PRICES
Chassis #5903 - Domestic
#5903 A - Export
Dial Assembly

Models 9-S-30, 9-S-54
and 9-S-55

7-6	Dial Glass Bezel (part of 57-511).....	-
26-94	Aeroplane Dial Scale	\$1.00
32-8	Drive Belt	.20
34-49	Condenser Shaft Gear	.25
34-50	Pinion Gear	.05
34-51	Lower Pinion and Gear	.15
56-44	Planetary Guide Pin(furnished with 76-181)...	-
59-40	Special Z Pointer	.15
59-41	Split Second Pointer	.10
61-35	Shaft Pulley and Sleeve	.25
61-36	Tension Pulley	.05
61-37	Dial Pulley	.05
76-180	Tension Pulley Shaft	.05
76-181	Planetary Drive Assembly	1.00
80-111	Dial Spring	.25
80-112	Tension Pulley Spring	.10
83-407	Dial Light Diffusion Strip	.05
100-23	6.3 Volt Pilot Lamp	.15
118-10	Band Switch Indicator Link	.05
159-11	Snap Buttons	.02
188-2	Retainer Ring	.10
196-4	Dial Glass Gasket (part of 57-511)	-
S-3777	Tension Pulley and Spring Assembly	.30
S-3782	Band Indicator Lever Arm and Bushing Assembly	.30
S-3783	" " Scale and Arm Assembly	1.00
S-2918	Dial Lamp Socket and Clip Assembly	.15

Condensers

22-82	.001 Mfd.	600 Volt		.25
22-127	.000025 "	600 "		.20
22-162	.001 "	600 "		.20
22-170	.5 "	400 "		.25
22-188	.02 "	400 "		.15
22-205	200-500 Mmfd.	Padder		.35
22-212	.05 Mfd.	400 Volt		.20
22-243	.01 "	400 "		.15
22-250	.05 "	200 "		.15
22-289	.00005 "	600 "		.12
22-345	.0011 "	600 "		.15
22-408	2-35 Mmfd.	Padder		.25
22-409	3-Gang	Variable Condenser		3.50
22-410	.003 Mfd.	600 Volt		.40
22-411	.0023 "	600 "		.25
22-412	16 x 4 x 2 Mfd.	450 Volt	(domestic only)	3.00
22-420	10. Mfd.	25 Volt		.65
22-433	.5 "	400 "		.30
22-435	.02 "	600 "		.15
22-421	16 x 4 x 2 Mfd.	450 Volt	(export only)	3.25

Resistors

63-240	1900 Ohm $\frac{1}{4}$ Watt	.20
--------	-----------------------------------	-----

PARTS AND PRICES

-2-

Models 9-S-30, 9-S-54
and 9-S-55

				Resistors (Cont'd)	and 9-S-55	
63-278	99 M	Ohm	$\frac{1}{4}$ Watt			\$.20
63-280	49 M	"	"			.20
63-288	19 M	"	"			.20
63-293	990 M	"	"			.20
63-300	990	"	"			.20
63-373	11 M	"	$\frac{1}{2}$ "			.20
63-449	Candohm Resistor					1.00
63-450	Volume Control and Switch Assembly.....(domestic only).....					1.00
63-451	Tone Control Assembly					.80
63-452	650 M	Ohm	$\frac{1}{4}$ Watt			.20
63-466	990	"	$\frac{1}{2}$ "			.20
63-472	Volume Control and Switch Assembly(export only).....					1.00
Coils and Chokes						
20-82	Antenna Choke					.25
20-119	R. F. Plate Choke Assembly					.50
95-291	1st I.F. Transformer Assembly					1.25
95-292	2nd " " " "					1.25
S-3697	Antenna Coil Assembly					1.00
S-3698	Detector Coil Assembly					.85
S-3699	Oscillator Coil Assembly					.85
Miscellaneous						
44-7	Phonograph Jack.....(export only).....					.15
46-123	Band Selector Switch Knob.....					.20
46-124	Volume and Tone Control Knobs					.20
46-125	Tuning Knob(small).....					.15
46-126	" "(large).....					.15
49-120	12" Dynamic Speaker (Models 54 and 55)					10.00
	Cone and Voice Coil for 49-120					3.25
	Field Coil for 49-120					2.00
	Output Transformer for 49-120					2.00
49-126	8" Dynamic Speaker (Model 30)					8.00
	Cone and Voice Coil for 49-126					2.50
	Field Coil for 49-126					2.00
	Output Transformer for 49-126					2.00
57-511	Dial Glass Escutcheon Plate					1.50
58-30	4-Prong Speaker Plug					.25
78-128	5-Prong " " Socket					.10
78-120	Voltage Indicator Socket(export only).....					.10
78-131	6K7 Wafer Type Tube Socket					.15
78-132	6A8	"	"	"		.15
78-133	6H6	"	"	"		.15
78-134	6C5	"	"	"		.15
78-136	5Y3	"	"	"		.15
78-137	6F6	"	"	"		.15
85-39	Phono Switch D.P. D.T.					1.00
85-78	Band Selector Switch					1.50
95-293	115 V., 50-60 cycle, Power Transformer					4.50
95-294	Audio Transformer					2.00
95-295	All Voltage, 25 cycle, Power Transformer(export only)...					7.50
126-127	Tube Shields.....					.10

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

ZENITH RADIO CORPORATION
Chicago, Illinois, U.S.A. 6/19/35

Service Bulletin



MODELS

12-L-57
12-L-58

Chassis
No. 1202-1202A

SERVICE NOTES

On actual service hints, check all tubes, aerial and ground installation first.

Lack sensitivity -- Re-Balance.

A.V.C.blocks -- Open A.V.C. resistor or grounded circuit, noticeable by distortion. Usually clears up when aerial is removed.

Weak - S.W. -- Open #22-242 .05 condenser.

Weak - all over -- Open #22-190 .1 in A.V.C. circuit.

Dead -- Open #22-435 .02 coupling condenser. If shorted, set will be weak and distorted.

Dead or very weak -- Open #22-188 .02 condenser. If shorted, set will be distorted with no apparent change in volume control.

Dead -- #22-433 .5 shorted.

Hums -- #22-433 .5 open, also mismatched 6K6 tubes. In rare cases defective choke or filter.

Weak -- Open #22-250 .05 condensers.

Weak -- L.W. band, open .000025 - red - green - black. Condenser in L.W.circuit.

Weak -- I.F. or R.F. coil open or shorted. Flutters all bands - Open .1 #22-170 screen condenser Set dead if shorted with no screen voltage.

Distorted & Weak -- Shorted I.F. grid circuit.

Signals tune sharp -- noise level low off the signal --- check 6H6 tube.

Pointers will not turn -- Belt off pulley. Split second hand will not turn - binds on cabinet or loose planetary lugs - adjust carefully.

Lack sensitivity with oscillation on "D" band around 12 megacycles -- check for open antenna choke or antenna coil.

Carrier Hum -- Open Antenna choke coil.

Oscillates -- Dress all I.F.wires. Check for open condensers, tubes, balance, etc. - check aerial installation and ground.

Off scale -- Large "Z" pointer loose on gang hub.

Alignment

The bands are as follows:

Band	Color	Kilocycles	Megacycles	Meters
A	Green	550 - 1,740	.55 - 1.74	545 - 172
B	Green	2,000 - 7,000	2 - 7	150 - 42.8
C	Red	150 - 370	.15 - .37	2,000 - 800
D	Red	7,000 - 22,500	7 - 22.5	42.8 - 13.3

The diagram on Page 3 shows position of major components and aligning adjustments. It should be studied carefully before any attempt is made to adjust the various circuits. The Clough-Brengle Model OC is a commercial service oscillator highly recommended for this work.


Separate coils are used for each band. Mounted on the coils are individual trimmers that align each band, independent of the other bands.

1. Connect service oscillator to grid of 6A8 detector oscillator tube and peak I.F. trimmers (see diagram Page 3) at 456 K.C.
2. Connect service oscillator to antenna post and set to 1400 K.C. Adjust trimmers A, B and C to resonance with dial indicator to 1400 K.C.
3. Set service oscillator to 600 K.C. and adjust broadcast padder D for maximum gain while rocking dial slowly over 600 K.C.
4. Place band switch on band "B" (2 - 7 megacycles) and set service oscillator and dial indicator to 6 megacycles. Adjust gang condenser, trimmer E for maximum output while slowly rocking dial over 6 megacycles.
5. Align "D" band (7-22.5 megacycles) next by setting service oscillator and dial indicator to 18 megacycles and rocking indicator slowly over that point while adjusting trimmer F to maximum output.
6. Set band switch to "C" band (long wave) and peak at 350 K.C. with trimmers G, I and J. Turn dial indicator and service oscillator to 150 K.C. and adjust long wave padder H while slowly rocking dial indicator.
7. Re-balance again at 6 megacycles and 1400 K.C. as in 2 and 4.



Socket Voltages

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6K7	R.F.	0	2.9 _{ac}	225	97	0	-	2.9 _{ac}	0	- .1
6A8	1st. Det. Osc.	0	2.9 _{ac}	225	97	-5	200	2.9 _{ac}	0	- .1
6K7	I.F.	0	2.9 _{ac}	225	97	0	-	2.9 _{ac}	0	- .1
6H6	2nd Det. A. V. C.	0	2.9 _{ac}	-2.1	-2.5	-2.5	-	2.9 _{ac}	-2.5	-
6C5	Shadow Meter	0	2.9 _{ac}	215	-	0	-	2.9 _{ac}	8.5	-
6C5	1st. Audio	0	2.9 _{ac}	42	-	0	-	2.9 _{ac}	0	-
6C5	Driver	0	2.9 _{ac}	215	-	0	-	2.9 _{ac}	8.5	-
6F6	Power	0	2.9 _{ac}	340	340	-4.5	-	2.9 _{ac}	25	-
5Y3 5Z4	RECT.	0	350	-	300 a.c.	-	300 a.c.	-	350	-




**BOTTOM VIEW
OF SOCKET**


Line Voltage 115

Antenna and Ground Disconnected


Voltages measured from point indicated to ground, using a 1000 ohm per volt meter, except heaters. (2 - 7)



Control Panel




ZENITH
RADIO




QTY	PART	DESCRIPTION	W.
R1	63-278	99M OHMS	1/2 W.
R2	63-280	49M	1/2 W.
R3	63-288	19M	1/2 W.
R4	63-293	990M	1/2 W.
R5	63-303	700	1/2 W.
R6	63-373	11M	1/2 W.
R7	63-450	1MEG. VOL. CONTROL	1/2 W.
R8	63-451	1MEG. TONE CONTROL	1/2 W.
R9	63-481	400M OHMS	1/2 W.
R10	63-466	990	1/2 W.
R11	63-471	CANDOHM	1/2 W.
R12	63-242	2500 OHMS	1/2 W.

C1	22-82	.001	MFD.	600K
C2	22-127	.000025		600K
C3	22-147	.0005		600K
C4	22-162	.0001		600K
C5	22-170	.1		400K
C6	22-188	.02		400K
C7	22-190	.1		200K
C8	22-212	.05		400K
C9	22-229	.005		600K
C10	22-243	.01		400K
C11	22-289	.00005		600K
C12	22-324	2-35 MMFD.-3 SECTION		600K
C13	22-345	.0011	MFD.	600K
C14	22-358	.002		600K
C15	22-205	200-550 MMFD. PADDER		600K
C16	22-368	.003	MFD.	600K
C17	22-409	3 GANG VARIABLE		50V.
C18	22-405	10 MFD.		600K
C19	22-410	.003	MFD.	600K
C20	22-411	.0023		600K
C21	22-418	2-35 MMFD.		600K

QTY	PART	DESCRIPTION	W.
C22	22-294	16 MFD.	450V.
C23	22-445	8 MFD.	
C24	22-445	4 MFD.	
C25	22-433	.5	MFD. 400K
C26	22-435	.02	" 600K
C27	22-424	50-180 MMFD. PADDER	
C28	22-420	10 MFD.	25V.
C29	22-250	.05 MFD.	200V.
1	95-291	1ST I.F. TRANS. - 456 KC.	
2	95-292	2ND I.F.	
3	95-306	117V. 50-60 CYCLE TRANS.	
4	95-307	RADIO TRANS.	
5	95-320	POWER CHOKER	
6	122-10	SHADOW METER	
7	20-120	R.F. PLATE CHOKER	
8	20-124	ANT. CHOKER - 2MH.	
9	5-3747	ANT. COIL ASSEM.	
10	5-3746	DET. COIL ASSEM.	
11	5-3745	OSC. COIL ASSEM.	
12	49-121	12" 5PKR. - MODEL 12 L57	
13	49-124	12" - MODEL 12 L58	
14	49-125	6" - 5800~FIELD	
15	85-82	BAND SELECTOR SW.	
16	95-310	25~ALL VOLT. PWR. TRANS.	
17	85-39	PHONO. SWITCH.	
18	44-7	PHONO. JACK	







Parts and Prices

Models 12-A-57
and 12-A-58

Chassis #1202 - Domestic

#1202 A - Export

Dial and Drive assembly

7-8	Escutcheon Glass Bezel (part of 57-516).....	-
26-99	Glass Dial Scale (Split Second Calibration).....	\$ 1.25
26-100	Glass Dial Scale (Police and Long Wave Band).....	1.25
26-101	Glass Dial Scale (Broadcast and Short Wave Band).....	1.25
27-7	Backing Disc.....	.05
32-9	Drive Belt.....	.25
34-49	Condenser Shaft Gear.....	.25
34-50	Pinion Gear.....	.05
34-51	Lower Pinion and Gear.....	.15
56-44	Planetary Guide Pin. (Part of 76-181).....	-
59-46	Special Z Pointer and Bushing.....	.25
59-47	Split Second Pointer.....	.15
61-35	Shaft Pulley and Sleeve.....	.25
61-36	Tension Pulley.....	.05
61-37	Dial Pulley.....	.05
76-179	Drive Shaft.....	.05
76-180	Tension Pulley Shaft.....	.05
76-181	Planetary Drive Assembly.....	1.00
80-111	Dial Spring.....	.25
80-112	Tension Pulley Spring.....	.10
93-268	Brass U Washer.....	.01
93-269	Spring Washer.....	.01
93-270	Black Bakelite Washer.....	.01
97-91	Lower Gear Stud.....	.01
100-23	6.3 Volt Dial Lamps.....	.15
147-23	Dial Glass Spacer (4 used).....	.01
188-2	Retaining Rings.....	.10
196-6	Escutcheon Glass Gasket (Part of 57-516).....	-
196-7	Dial Glass Gasket.....	.02
3-3777	Tension Pulley and Spring Assembly.....	.30

Condensers

22-82	.001	Mfd.	600 Volts		.25
22-127	.000025	"	600 "		.20
22-147	.0005	"	600 "		.15
22-162	.0001	"	600 "		.20
22-170	.1	"	400 "		.25
22-188	.02	"	400 "		.15
22-190	.1	"	200 "		.20
22-205	200-550	Mafd.	Padder		.35
22-212	.05	Mfd.	400 Volts		.20
22-229	.005	"	600 "		.15
22-243	.01	"	400 "		.15
22-289	.00005	"	600 "		.12
22-294	15.	"	450 "		1.00
22-324	2-35	Mafd.	Padder		.40
22-345	.0011	Mfd.	600 Volts		.15
22-358	.002	"	600 "		.20
22-368	.003	"	600 "		.20
22-405	10.	"	50 "		.75



PARTS AND PRICES

Models 12-A-57
and 12-A-58

Condensers (Cont'd)

22-409	5-Gang Variable Condenser	\$ 3.50
22-410	.003 Mfd. 600 Volt.....	.40
22-411	.0023 " 600 "	.25
22-418	2-35 Mmfd. Padder	.25
22-420	10. Mfd. 25 Volt.....	.65
22-424	50-180 Mmfd. Padder.....	.35
22-433	.5 Mfd. 400 Volt.....	.30
22-435	.02 " 600 "	.15
22-445	8. x 4. Mfd. 450 "(Domestic Only).....	1.75
22-446	8. x 4. " 450 "(Export Only).....	1.75

Resistors

63-242	2500 Ohm $\frac{1}{2}$ Watt	.20
63-278	99 M " $\frac{1}{2}$ "	.20
63-280	49 M " $\frac{1}{2}$ "	.20
63-288	19 M " $\frac{1}{2}$ "	.20
63-293	990 M " $\frac{1}{2}$ "	.20
63-303	700 " $\frac{1}{2}$ "	.20
63-373	11 M " $\frac{1}{2}$ "	.20
63-450	1 Megohm Volume Control Assembly (Domestic Only).....	1.00
63-451	1 " Tone " "	.80
63-452	650 M Ohm $\frac{1}{2}$ Watt	.20
63-466	990 " $\frac{1}{2}$ "	.20
63-471	Candohm Resistor	1.00
63-472	1 Megohm Volume Control Assembly (Export only).....	1.00

Coils and Chokes

20-120	R. F. Plate Choke.....	.75
20-124	Antenna Choke.....	.25
95-291	1st I. F. Transformer Assembly.....	1.25
95-292	2nd I. F. Transformer Assembly.....	1.25
S-3745	Oscillator Coil Assembly.....	1.25
S-3746	Detector Coil Assembly.....	1.50
S-3747	Antenna Coil Assembly.....	1.50

Miscellaneous

44-7	Phonegraph Jack ... (Export only).....	.15
46-123	Band Selector Knob.....	.20
46-124	Volume Control Knob.....	.20
46-125	Tuning Knob (Small).....	.15
46-126	" " (Large).....	.15
46-127	Tone Control Knob.....	.20
49-121	12" Dynamic Speaker (Model 57).....	10.00
	Cone and Voice Coil Assembly for 49-121.....	3.25
	Output Transformer for 49-121.....	2.00
	Field Coil for 49-121.....	2.00
49-124	12" Dynamic Speaker (Model 58).....	10.00
	Cone and Voice Coil Assembly for 49-124.....	3.25
	Output Transformer for 49-124.....	2.00
	Field Coil for 49-124.....	2.00
49-125	6" Dynamic Speaker (Model 58).....	5.00
	Cone and Voice Coil for 49-125.....	2.00
	Field Coil for 49-125.....	2.00
57-516	Dial Glass and Escutcheon Plate.....	3.00
58-31	Seven Prong Speaker Plug.....	.30



PARTS AND PRICES

models 12-A-57
and 12-A-58

Miscellaneous (Cont'd)

78-129	Voltage Indicator Socket (Export only).....	\$.15
78-131	6K7 Wafer Type Socket.....	.15
78-132	6A8 " " "	.15
78-133	6H6 " " "	.15
78-134	6C5 " " "	.15
78-136	5Y3 " " "	.15
78-137	6F6 " " "	.15
78-144	Seven Contact Speaker Plug Socket.....	.15
85-39	Phono Switch D.P.D.T. (Export only).....	1.00
85-82	Band Selector Switch.....	2.00
95-306	117 Volt, 50-60 cycle Power Transformer.....	6.00
95-307	Audio Transformer.....	2.50
95-310	25 Cycle, All Voltage Power Transformer (Export only)..	10.00
95-312	Power Choke.....	.75
122-10	Shadowgraph Meter.....	2.00
126-92	Tube Shields (Black).....	.15
126-109	Tube Shields (Small).....	.15
126-127	Tube Shields (Large).....	.10

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS, U.S.A.
July 16, 1935

WARRANTY

The Zenith Radio Corporation guarantees each new ZENITH receiver and each new ZENITH QUALITY TUBE to be free from defects in workmanship and material.

Our obligation under this warranty is limited to making good at our factory any part or parts of the receiver which within ninety days from date of purchase shall be returned to us with transportation charges prepaid and which on examination shall be found to our satisfaction to have been thus defective. The ZENITH QUALITY TUBES used in this receiver are guaranteed against mechanical and electrical defects under the same warranty as the receiver. This warranty is expressly in lieu of all other warranties expressed or implied, and we neither assume nor authorize any representative or other person to assume for us any other liability in connection with the sale of ZENITH receivers or ZENITH QUALITY TUBES.


This warranty shall not apply to any receiver or tube which shall have been repaired or altered outside of our factory in any way so as, in our judgment, to affect its stability or reliability, nor which has been subject to misuse, negligence or accident, nor which has had the serial number or name altered, defaced or removed. Neither shall this warranty apply to any receiver in which other than ZENITH QUALITY TUBES have been used.

ZENITH RADIO CORPORATION.

ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.



QWKS	PART	NO	NO	DESCRIPTION
C1	22-32	200	350	MFD. 600V.
C2	22-32	200	350	MFD. 600V.
C3	22-182	00025		200V.
C4	22-185	01		200V.
C5	22-199	01		400V.
C6	22-192	05		25V.
C7	22-226	05		MFD.
C8	22-243	01		400V.
C9	22-250	05		200V.
C10	22-287	05		600V.
C11	22-358	002		600V.
C12	22-419	2		250V.
C13	22-419	3		250V.
C14	22-426			VARIABLE
C15	22-427	006		1200V.

R1	63-235	1 M	OHMS	1 W.
R2	63-247	8 M	"	1 W.
R3	63-258	480 M	"	1 W.
R4	63-281	29 M	"	1 W.
R5	63-293	990 M	"	1 W.
R6	63-303	700	"	1 W.
R7	63-378	250	"	1 W.
R8	63-394	200	"	1 W.
R9	63-418	1500	"	1 W.
R10	63-468	200 M	"	1 W.
R11	63-469	50 M	"	1 W.
R12	63-478	50 M	"	1 W.
			V CONTROL	1 W.
			T.	1 W.

ZENITH

4TUBE BATTERY SUPERHETERODYNE
I.F. FREQUENCY 456 KC.
CHASSIS NO 5405.
MODEL'S 4V-31 -4V-59

TUNING RANGE 550-1700 K.C.

ZENITH RADIO CORP.
CHICAGO, ILL.

6-22-95 - W.D.

Socket Voltages

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
15	1st Det. Osc.	2	8	0	115	-	155
15	I. F.	2	3.5	0	115	-	155
75	2nd Det. A.V.C.	6	1.5	0	-	-	30
38	PWR	6	14	0	155	-	148

Battery - 6 volts


Antenna and ground disconnected.

f - filament; k - cathode; g1 - control grid; g2 - screen grid; g3 - suppressor grid; p - plate.

All measurements taken from point indicated to ground using a 1000 ohm per volt D. C. meter.

Alignment

- (1) Balance intermediate transformers at 456 K.C. with service oscillator connected to grid of 15 first detector and ground.
- (2) Connect service oscillator to antenna and ground.
- (3) Adjust oscillator trimmer on gang condenser for correct dial reading at 1400 K.C.
- (4) Adjust detector trimmer on gang condenser to resonance.
- (5) Adjust oscillator padder (located in rear of gang) meanwhile rocking pointer past 600 K.C. to combination giving greatest output.
- (6) Repeat operations 3 and 4.



Tube Layout



PARTS AND PRICES
Chassis #5405

Models 4-V-31
4-V-59

Dial Assembly

7-7	Dial Glass and Scale Bezel and Mounting Bracket.....	\$.40
26-98	Dial Scale.....	.50
59-45	Dial Pointer and Busing Assembly.....	.15
61-38	Dial Pulley.....	.40
76-182	Dial Drive Shaft.....	.10
80-69	Dial Tension Spring.....	.02
94-200	Dial Shaft Bushing.....	.10
100-23	6.3 Volt Dial Lamp.....	.15
132-13	Dial Glass Retaining Ring.....	.05
188-2	Retaining Rings.....	.10
192-11	Dial Glass.....	.15
196-5	Dial Glass Gasket.....	.03

Condensers

22-82	.001 Mfd. 600 Volts	.25
22-182	.00025 " 600 "	.12
22-185	.01 " 200 "	.20
22-199	.5 " 200 "	.35
22-205	200-550 Mmfd. Padder	.35
22-212	.05 Mfd. 400 Volts	.20
22-225	5. " 25 "	.65
22-243	.01 " 400 "	.15
22-250	.05 " 200 "	.15
22-287	.03 " 600 "	.15
22-358	.002 " 600 "	.20
22-419	2 x 8 " 250 "	1.75
22-426	2-Gang Variable Condenser	2.00
22-427	.006 Mfd. 1200 Volts	.15

Resistors

63-238	1 M Ohm $\frac{1}{2}$ Watt	.20
63-247	8 M " "	.20
63-258	490 M " "	.20
63-281	29 M " "	.20
63-293	990 M " "	.20
63-303	700 " "	.20
63-378	250 " "	.20
63-394	200 " "	.20
63-418	1500 " "	.20
63-468	200 M Volume Control and Switch Assembly.....	1.00
63-469	50 M Tone Control Assembly	.60
63-476	9.1 Ohm $\frac{1}{2}$ Watt	.20

Coils and Chokes

95-308	1st I.F. Transformer Assembly.....	1.25
95-309	2nd I.F. Transformer Assembly.....	1.25
S-3755	Antenna Coil Assembly.....	1.25
S-3756	Oscillator Coil Assembly.....	1.50
S-2778	Vibrator R. F. Choke Assembly.....	.15

Miscellaneous

19-59	Battery Lead Clip (positive).....	.15
-------	-----------------------------------	-----

PARTS AND PRICES

Models 4-V-31
4-V-59

Miscellaneous (Cont'd.)

19-60	Battery Lead Clip (Negative).....	\$.15
46-122	Tuning Knobs.....	.10
49-127	6" Magnetic Speaker (Model 31).....	5.00
	Cone Assembly for 49-127	.50
	Paper Ring for " "	.05
	Coil " " "	1.25
	Motor Drive Assembly for 49-127.....	4.75
	Terminal Strip Cord and Plug Assembly for above.....	.50
49-130	8" Dynamic Speaker (Model 59).....	6.00
	Cone Assembly for 49-130.....	.60
	Paper Ring " " "	.10
	Coil " " "	1.25
	Motor Drive Assembly for 49-130.....	4.75
	Terminal Strip Cord and Plug Assembly for 49-130.....	.60
78-101	Type 75 Wafer Tube Socket.....	.10
78-128	Five Contact Speaker Plug Socket.....	.10
78-139	Type 15 Wafer Tube Socket.....	.10
78-140	Type 38 " " "	.10
78-141	Vibrator Socket.....	.10
95-298	Power Choke.....	.75
95-300	Rectifier Transformer.....	2.00
126-127	Tube Shields.....	.10
126-201	Vibrator Shield.....	.15
190-5	Vibrator.....	5.00

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS, U. S. A.
July 15, 1935

4-TUBE 6-VOLT FARM RECEIVER

(5405)

Made by

ZENITH RADIO CORPORATION

3620 IRON ST.

JUNE, 1931

CHICAGO, ILL., U. S. A.

SOCKET VOLTAGES

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
15	R. F.	2	1.5	0	70	-	125
6A7	Det.-Osc.	6	2	0	150	-	150
				-1	-	-	150
15	I. F.	2	2	0	70	-	150
75	2nd Det. A.V.C.	6	1.5	0	-	-	40
75	1st Audio	6	8	0	-	-	140
19	PWR.	2	-	0	-	-	160
				0			160

Battery Voltage 6 Volts

Antenna and Ground Disconnected

All voltages measured from socket contacts to ground with 1000 ohm per volt D. C. meter.

F - Filament; K - Cathode; g1 - Control grid; g2 - Screen grid; g3 - Suppressor grid; p - plate.

Alignment

1. Attach service oscillator to grid cap of 6A7 tube and adjust I.F. trimmers at 456 K.C.
2. Place band switch in "A" (Standard broadcast) position and attach 1400 K.C. service oscillator to antenna and ground posts. Set dial indicator to 1400 K.C. and adjust trimmers "A" (Osc.); "B" (R.F.); "C" (Det.) to maximum output.
3. Set service oscillator to 600 K.C. and rock indicator over 600 K.C. on dial of receiver while adjusting standard broadcast padder "D".
4. Repeat operations 2 and 3.
5. Place band switch in "B" or 1st short wave position (2100 - 6800 K.C.) and set white dial pointer on 6 megacycles. Set service oscillator to 6 megacycles and adjust trimmer "E" for maximum output while rocking dial pointer slowly over 6 megacycle division.
6. Place band switch on "C" position (7000- 23000 K.C.) and set service oscillator and white dial pointer to 18 megacycles. Adjust trimmer "F" to resonance while rocking dial indicator slowly over 18 megacycle division.
7. Set dial and service oscillator at 9 megacycles and twist or untwist tinned bare wire tuning "loop" (on front section of band switch under chassis) for maximum output.
8. Align standard broadcast band again at 1400 K.C. by adjusting trimmer "A" only. Repeat all eight operations for final accuracy.




Figure at left shows tube position and location of balancing adjustments.



PARTS AND PRICES Chassis #5621

Models 6-V-27,
6-V-62

Dial Assembly

7-6	Dial Glass Bezel.....	-
26-104	Aeroplane Dial Scale.....	\$ 1.00
32-7	Dial Drive Belt.....	.20
34-49	Condenser Shaft Gear.....	.25
34-50	Pinion Gear.....	.05
34-51	Lower Pinion and Gear.....	.15
59-40	Special Z Pointer.....	.15
59-41	Split Second Pointer and Bushing.....	.10
61-34	Drive Pulley.....	.10
61-35	Shaft Pulley and Sleeve.....	.25
61-36	Tension Pulley.....	.05
76-178	Drive Shaft.....	.10
76-180	Tension Pulley Shaft.....	.05
80-111	Dial Spring.....	.25
80-112	Tension Pulley Spring.....	.10
83-407	Dial Light Diffusion Strip.....	.05
100-23	6.3 V. Pilot Lamp.....	.15
159-11	Snap Buttons.....	.02
188-2	Retaining Ring.....	.10
192-10	Dial Glass.....(part of 57-511)...	-
196-4	Dial Glass Gasket....." " " "...	-
198-1	Dial Reflector.....	.40
S-3777	Tension Pulley and Spring Assembly.....	.30

Condensers

22-82	.001	Mfd.	600 Volt	.25
22-182	.00025	"	600 "	.12
22-188	.02	"	400 "	.15
22-205	200-350	Mmfd.	Padder	.35
22-212	.05	Mfd.	600 Volt	.20
22-224	.1	"	300 "	.15
22-225	5.	"	25 "	.65
22-228	.5	"	300 "	.35
22-243	.01	"	400 "	.15
22-250	.05	"	200 "	.15
22-251	.5	"	200 "	.40
22-289	50	Mmfd.	600 "	.12
22-345	.0011	Mfd.	600 "	.15
22-408	2-35	Mmfd.	Padder	.25
22-409	3-Gang	Variable	Assembly.....	3.50
22-410	.003	Mfd.	600 Volt	.40
22-411	.0023	"	600 "	.25
22-432	8. x 2.	Mfd.	250 "	1.75
22-437	.01	"	200 "	.15

Resistors

63-238	1 M	Ohm	$\frac{1}{4}$ Watt	.20
63-258	490 M	"	"	.20
63-260	100 M	"	"	.20
63-272	4 M	"	"	.20
63-278	99 M	"	"	.20

PARTS AND PRICES

-2-

Models 6-V-27 and 6-V-62

Resistors (Cont'd)

63-280	49 M	Ohm	$\frac{1}{4}$ Watt		\$.20
63-290	260 M	"	"		.20
63-293	990 M	"	"		.20
63-361	5 M	"	"		.20
63-362	400	"	"		.20
63-353	19 M	"	"		.20
63-394	200	"	"		.20
63-456	200 M	"	Volume Control and Switch Assembly.....		1.00
63-458	50 M	"	Tone Control Assembly.....		.80
63-477	100	"	Flexible $\frac{1}{4}$ Watt		.15

Coils and Chokes

20-82	Antenna Choke.....	.25
20-88	R. F. Choke	.25
20-119	R. F. Plate Choke Assembly.....	.50
95-291	1st I. F. Transformer Assembly.....	1.25
95-292	2nd I. F. " "	1.25
S-3697	Antenna Coil Assembly	1.00
S-3698	Detector " "	.85
S-3699	Oscillator " "	.85

Miscellaneous

19-59	Battery Lead Clip (Positive).....	.15
19-60	" " " (Negative).....	.15
46-124	Volume Control Knob.....	.20
46-127	Tone and Tuning Knobs.....	.20
46-132	Band Selector Switch Knob.....	.20
49-131	12" Magnetic Speaker Assembly (Model 62).....	8.00
	Cone Assembly for 49-131.....	1.00
	Felt Ring " " "	.15
	Coil for 49-131	1.25
	Motor Drive Assembly for 49-131.....	6.50
	Cord and Plug Assembly for 49-131.....	.75
49-132	8" Magnetic Speaker Assembly (Model 27).....	6.00
	Cone Assembly for 49-132.....	.60
	Paper Ring " " "	.10
	Coil for 49-132.....	1.25
	Motor Drive Assembly for 49-132.....	4.75
	Terminal Strip Cord and Plug Assembly for 49-132.....	.60
57-511	Dial Glass and Escutcheon Plate Assembly.....	1.50
58-30	Four Prong Speaker Plug.....	.25
78-101	Type 75 Wafer Tube Socket.....	.10
78-106	" 6A7 " " "	.10
78-109	" 76 " " "	.10
78-124	" 19 " " "	.10
78-128	Five Prong Speaker Plug Socket.....	.10
78-139	Type 15 Wafer Tube Socket	.10
78-141	Vibrator " " "	.10
83-334	Antenna and Ground Terminal Strip.....	.10
85-78	Band Selector Switch.....	1.50
95-298	Power Choke.....	.75
95-305	Rectifier Transformer.....	1.75
95-311	Audio Transformer.....	1.25
126-127	Tube Shield.....	.10
126-201	Vibrator Shield.....	.15
190-5	Special Zenith Vibrator.....	5.00

SERVICE BULLETIN



MODELS

16-A-61

16-A-63

Stratosphere

SERVICE DATA

A.V.C. blocks -- Open A.V.C. resistor or grounded circuit, noticeable by distortion. Usually clears up when aerial is removed.

Distorted & Weak -- Shorted I.F. grid circuit.

Signals tune sharp -- Noise level low off the signal --- check 6H6 tube.

Pointers will not turn -- Belt off pulley. Split second hand will not turn - binds on cabinet or loose planetary lugs - adjust carefully.

Lack sensitivity with oscillation on "D" band around 12 megacycles -- check for open antenna choke or antenna coil.

Distorted -- Tubes - 22-438 - 20 mfd. shorted. A.V.C. grounded or open. Open - 63-478 resistor. One-half of push-pull transformer open.

Distorts at full volume -- (Do not confuse with overloading which is a natural characteristic on a strong input signal) - Check 22-171 .05 condensers for short. Set will be weak if open.

Dead as tone control is turned on bass only - Check 22-196 .01 for short. Set will lack bass response if this condenser is open.

No minimum volume control and also lacks bass response - Check 95-321 for open. If shorted a lack of high response.

Lacks bass - Check 22-287 .03 for open.

Volume control noisy - Check 22-240 for short; also check volume control

Graph will not operate - Defective 6C5 tube or open graph - burned out pilot bulb.


ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

Socket Voltages

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6K7	R.F.	0	3AC	280	100	3.5	-	3AC	3.5	0
6A8	1st Det.& Osc.	0	3AC	280	100	.4	125	3AC	3.5	0
6K7	1st I.F.	0	3AC	280	100	6.5	-	3AC	6.5	0
6K7	2nd I.F.	0	3AC	280	100	6.5	-	3AC	6.5	0
6H6	2nd Det.	0	3AC	-.2	0	-.2	-	3AC	0	-
6F5	1st Audio	0	3AC	-	3	-	-	3AC	1	0
6F6	2nd Audio Driver	0	3AC	280	280	0	-	3AC	25	-
6C5	Shadowgraph Amp.	0	3AC	280	-	0	-	3AC	11	-
6F6	(4 tubes) Power	0		370	370	0	-		35	-
5Y3	Rectifier Top Chassis	0	390	-	320AC	-	320AC	-	390	-
5Y3	Rectifier Lower Chassis	0	360	-	300AC	-	300AC	-	360	-



BOTTOM VIEW
OF SOCKET


Line Voltage 115 Antenna and Ground Disconnected

Voltages measured from point indicated to ground,
using a 1000 ohm per volt meter, except heaters (2 - 7)


Alignment

1. The diagram on page shows position of major components and aligning adjustments. It should be studied carefully before any attempt is made to adjust the various circuits.
2. Set service oscillator to 456 KC, and connect to the grid of the 6A8 tube. The grid cap should not be removed from the tube as this will remove bias. Tune the I.F. transformers for maximum output. Alignment should always be made with the service oscillator set to as low an output as will give a satisfactory indication on the output meter.
3. Connect the service oscillator to the antenna and ground post. With the band switch in the broadcast position, set the dial pointer to 1700 kilocycles, and adjust the oscillator trimmer on the gang condenser for a maximum output. Align the R.F. and detector condenser trimmers, also located on the gang condenser, for a maximum output.
4. Set the dial pointer to 600 kilocycles, and adjust the B.C. padder meanwhile rocking the gang condenser back and forth across 600 kilocycles until the padder setting for maximum output is obtained.. It may be necessary to go back and make a slight correction of the trimmer at 1700 kilocycles after the padder adjustment is completed.


5. Turn the band switch for the "B" band. Rock the gang back and forth across the 6 megacycle readings, meanwhile adjusting the oscillator trimmer on the gang condenser until maximum output is obtained. It will always be found that the dial reading for 6 megacycles is very close to this point. The service oscillator, of course, should be set at 6 megacycles.
6. Align "D" band (7-22.5 megacycles) next by setting service oscillator and dial indicator to 18 megacycles, and rocking indicator slowly over that point while adjusting the S.W. Trimmer to maximum output.
7. Set back to 1700 K.C. Readjust oscillator circuit this time using broadcast trimmer on chassis base.
8. Set band switch to "C" band (long wave) and peak at 350 K.C. with L.W., R.F.-Det. and Oscillator trimmers. Turn dial indicator and service oscillator to 180 K.C., and adjust long wave padder while slowly rocking dial indicator.
9. Repeat operation #2.



Receiver Chassis Drawing




Power Pack Chassis Drawing



QWG PART				
Nº	Nº	DESCRIPTION		
R1	63-278	981M OHMS	1W.	
R2	63-280	49M	1W.	
R3	63-417	99	1W.	
R4	63-293	980M	1W.	
R5	63-357	300	1W.	
R6	63-373	11M.	1W.	
R7	63-450	1 MEG. VOL. CONTROL	1W.	
R8	63-451	1 MEG. TONE CONTROL	1W.	
R9	63-400	250M OHMS	1W.	
R10	63-466	990	1W.	
R11	63-479	CRANDOHM	1W.	
R12	63-416	1400 OHMS	1W.	
R13	63-480	HIGH FIDELITY CONTROL	1W.	
R14	63-325	150M OHMS	1W.	
R15	63-279	3M	1W.	
R16	63-478	1000 CRANDOHM	1W.	
R17	63-404	60 OHMS-GT. CRANDOHM	1W.	
R18	63-369	CRANDOHM	1W.	
C1	22-82	.001 MFD.	600V.	
C2	22-127	.000025 MFD.	600V.	
C3	22-436	25-250 MMFD. DURL I.F.	600V.	
C4	22-447	.0005 MFD.	600V.	
C5	22-368	.003	600V.	
C6	22-156	.01	600V.	
C7	22-207	.03	600V.	
C8	22-212	.05	400V.	
C9	22-361	.16	450V.	
C10	22-243	.01	400V.	
C11	22-289	.00005	600V.	
C12	22-324	2-35 3 SECTION.	600V.	
C13	22-345	.0011 MFD.	600V.	
C14	22-438	20	50K	
C15	22-205	200-550 MMFD. PADD.	25V.	
C16	22-420	10 MFD.	25V.	
C17	22-409	36ANG VARIABLE	25V.	
C18	22-171	.05 MFD.	600V.	
C19	22-410	.003	600V.	

QWG PART				
Nº	Nº	DESCRIPTION		
C20	22-411	.0023 MFD.	600V.	
C21	22-418	2-35 MMFD.	600V.	
C22	22-138	.2 MFD.	200V.	
C23	22-182	.00025	600V.	
C24	22-250	.05	200V.	
C25	22-433	.5	400V.	
C26	22-424	50-180 MMFD. PADD.	450V.	
C27	22-321	8 MFD.	450V.	
1	5-3747	ANT. COIL ASSEN.		
2	5-3746	DET.		
3	5-3745	OSC.		
4	5-4014	VAR. I.F. TRANS. ASSEN.		
5	20-124	ANT. CHOKE		
6	20-120	R.F. PLATE CHOKE		
7	20-125	VAR. I.F. PRIMARY COIL		
8	20-126	VAR. I.F. SECONDARY COIL		
9	85-82	BAND SELECT. SWITCH		
10	122-10	SHADOWGRAPH		
11	95-317	3RD I.F. TRANS.		
12	95-318	DRIVER TRANS.		
13	95-319	FILTER CHOKE		
14	95-321	HIGH FIDELITY CHOKE		
15	95-319	FILTER CHOKE		
16	95-314	117V. 50-60 PWR. TRANS.		
17	95-315	PWR. OUTPUT PLATE VOLT. TRANS. 117V. 50-60		
18	44-7	PHONO. JACK		
19	85-39	SWITCH		
20	49-128	12" 5PKR 9M OHM FIELD		
21	49-129	6" 40 OHM		
22	95-322	25" ALL VOLT PWR. TRANS.		
23	95-323	25" OUTPUT PLV. TRANS.		



I.F. FREQUENCY 456 KC.
16 TUBE SUPERHETERODYNE
CHASSIS N° 1601-C & 1601-P
MODELS 16-A61 - 16-A63

ZENITH RADIO CORP.
CHICAGO, ILL.



Parts and Prices

Models 16-A-61
and 16-A-63

Chassis #1601 C
#1601 P

Dial and Drive Assembly

26-109	Calibrated Dial Scale (Glass).....	\$2.00
26-110	Band Indicator Scale.....	.35
32-9	Dial Drive Belt.....	.25
34-49	Condenser Shaft Gear.....	.25
34-50	Pinion Gear.....	.05
34-51	Lower Pinion and Gear.....	.15
59-46	Large Z Pointer.....	.25
59-47	Split Second Pointer.....	.15
61-35	Shaft Pulley and Sleeve.....	.25
61-36	Tension Pulley.....	.05
61-37	Driver Pulley.....	.05
80-111	Dial Spring.....	.25
80-113	Tension Pulley Spring.....	.10
100-23	6.3 Volt Dial Lamps.....	.15
122-10	Shadowgraph Meter.....	2.00
126-202	Dial Lamp Shield.....	.05
147-23	Dial Glass Spacers.....	.01
159-7	Snap Buttons.....	.05
188-2	Retaining Ring.....	.10
192-12	Escutcheon Plate Glass.....	.20
196-6	Escutcheon Plate Glass Gasket.....	.10
196-7	Dial Glass Gasket.....	.15
S-2918	Dial Light Socket and Clip Assembly (Less Lamp).....	.15
S-3777	Tension Pulley and Spring Assembly.....	.30
S-4089	Planetary Drive Assembly.....	1.00

Condensers

22-82	.001 Mfd. 600 Volts.....	.25
22-127	.000025 " 600 ".....	.20
22-138	.2 " 200 ".....	.25
22-171	.05 " 600 ".....	.20
22-182	.00025 " 600 ".....	.12
22-196	.01 " 600 ".....	.15
22-205	200-550 Mmfd. Padder.....	.35
22-212	.05 Mfd. 400 Volts.....	.20
22-243	.01 " 400 ".....	.15
22-250	.05 " 200 ".....	.15
22-287	.03 " 600 ".....	.15
22-289	.00005 " 600 ".....	.12
22-321	8. " 450 ".....	1.25
22-324	2-35 3 Section Padder.....	.40
22-345	.0011 Mfd. 600 Volts.....	.15
22-361	16. " 450 ".....	1.50
22-368	.003 " 600 ".....	.20
22-409	3-Gang Variable Condenser.....	3.50
22-410	.003 Mfd. 600 Volts.....	.40
22-411	.0023 " 600 ".....	.25

PARTS AND PRICES

Models 16-A-61
and 16-A-63

Condensers (Cont'd)

22-418	2-35 Mmfd. Padder.....	.25
22-420	10. Mfd. 25 Volts.....	.65
22-424	50-180 Mmfd. Padder.....	.35
22-433	.5 Mfd. 400 Volts.....	.30
22-436	25-250 Mmfd. Dual I.F. Padder.....	.40
22-438	20. Mfd. 50 Volts.....	1.00
22-447	.0005 " 600 "	.20

Resistors

63-278	99 M Ohm $\frac{1}{4}$ Watt.....	.20
63-279	3 M " $\frac{1}{4}$ "	.20
63-280	49 M " $\frac{1}{4}$ "	.20
63-293	990 M " $\frac{1}{4}$ "	.20
63-325	150 M " $\frac{1}{4}$ "	.20
63-357	300 " $\frac{1}{4}$ "	.20
63-373	11 M " $\frac{1}{4}$ "	.20
63-389	Candohm 1 M-1857 Ohms.....	.45
63-400	250 M Ohm $\frac{1}{4}$ Watt.....	.20
63-404	Candohm 60 Ohm C.T.....	.25
63-416	1400 Ohm $\frac{1}{4}$ Watt.....	.20
63-417	99 " $\frac{1}{4}$ "	.20
63-450	Volume Control Assembly.....	1.00
63-451	Tone Control Assembly.....	.80
63-466	990 Ohm $\frac{1}{4}$ Watt.....	.20
63-478	Candohm 1 M Ohms.....	.30
63-479	Candohm 4600 Ohms.....	.50
63-480	High Fidelity Control Assembly.....	1.25

R.F. Coils and Chokes

20-120	R.F. Plate Choke.....	.75
20-124	Antenna Choke.....	.25
20-125	Var.I.F. Primary Coil only.....	.30
20-126	" " Secondary " "	.20
95-317	3rd " Transformer Assembly.....	1.25
S-3745	Oscillator Coil Assembly.....	1.25
S-3746	Detector " "	1.50
S-3747	Antenna " "	1.50
S-4014	Variable I.F. Transformer Assembly (2 used).....	3.00

Miscellaneous

44-7	Phonograph Jack.....	.15
46-123	Band Selector and Variable Selectivity Knobs.....	.20
46-125	Tuning Control Knob (Small).....	.15
46-127	Tone and Volume Control Knobs.....	.20
46-134	Tuning Control Knob (Large).....	.15
49-128	12" Dynamic Speaker (Concert Type).....	17.50
	Cone and Voice Coil Assembly for 49-128.....	3.25
	Output Transformer for 49-128.....	3.00
	Field Coil for 49-128.....	3.00
49-129	6" Dynamic Speaker (Tweeter Type).....	7.00
	Cone and Voice Coil Assembly for 49-129.....	2.00
	Output Transformer for 49-129.....	2.00
	Field Coil for 49-129.....	1.50
52-74	Power Cable.....	2.00

PARTS AND PRICES

Models 16-A-61
and 16-A-63

Miscellaneous (Cont'd)

52-75	Speaker Cable.....	.50
57-516	Escutcheon Plate and Glass Assembly.....	3.00
58-32	5 Prong Power Cable Plug.....	.35
58-33	6 " " and Speaker Cable Plug.....	.35
62-7	A.C. Plug Receptacle.....	.75
78-129	Voltage Indicator Socket.....	.15
78-131	6-K-7 Wafer Type Socket.....	.15
78-132	6-A-8 " " "	.15
78-133	6-H-6 " " "	.15
78-134	6-C-5 " " "	.15
78-136	5-Y-3 " " "	.15
78-137	6-F-6 " " "	.15
78-145	6-F-5 " " "	.15
78-146	Six Contact Power Cable Socket.....	.15
78-147	Seven " " " " "	.15
85-39	Phono Switch D.P.D.T.....	1.00
85-82	Band Selector Switch.....	2.00
95-313	Power Cable.....	2.50
95-314	117 Volt, 50-60 Cycle Power Transformer.....	8.00
95-315	117 Volt 50-60 Cycle Power Output Plate Transformer....	6.50
95-318	Driver Transformer.....	3.00
95-319	Power Choke.....	2.50
95-321	High Fidelity Choke.....	1.00
95-322	All Voltage 25 Cycle Power Transformer.....	12.00
95-323	All Voltage 25 Cycle Power Output Plate Transformer....	10.00
126-171	Tube Shields (Large).....	.20
126-182	Tube Shields (Small).....	.20

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS, U.S.A.
November 5, 1935

WARRANTY


The Zenith Radio Corporation guarantees each new ZENITH receiver and each new ZENITH QUALITY TUBE to be free from defects in workmanship and material.

Our obligation under this warranty is limited to making good at our factory any part or parts of the receiver which within ninety days from date of purchase shall be returned to us with transportation charges prepaid and which on examination shall be found to our satisfaction to have been thus defective. The ZENITH QUALITY TUBES used in this receiver are guaranteed against mechanical and electrical defects under the same warranty as the receiver. This warranty is expressly in lieu of all other warranties expressed or implied, and we neither assume nor authorize any representative or other person to assume for us any other liability in connection with the sale of ZENITH receivers or ZENITH QUALITY TUBES.

This warranty shall not apply to any receiver or tube which shall have been repaired or altered outside of our factory in any way so as, in our judgment, to affect its stability or reliability, nor which has been subject to misuse, negligence or accident, nor which has had the serial number or name altered, defaced or removed. Neither shall this warranty apply to any receiver in which other than ZENITH QUALITY TUBES have been used.

ZENITH RADIO CORPORATION.


SERVICE BULLETIN



25 Tube

Stratosphere

(SERIAL NOS. 174001 TO 174100)



ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

GENERAL INFORMATION

Tubes used are as follows:

	6D6	First Radio Frequency Amplifier
	6D6	Second Radio Frequency Amplifier
	6A7	First Detector and Oscillator
	6D6	First Intermediate Amplifier
	6D6	Second Intermediate Amplifier
	76	Second Detector
2 -	76	First Audio Amplifier
2 -	42	Push-Pull Second Audio Amplifier
8 -	45	Parallel Push-Pull Power Amplifier
	79	Electron Relay for Q Circuit
	6D6	Shadowgraph Amplifier
	85	Automatic Volume Control
	6D6	A.V. C. Amplifier
2 -	5Z3	Rectifier for Power Amplifier
	5Z3	Rectifier for remainder for receiver.

CIRCUIT

Radio Frequency Amplifier. This receiver employs two stages of radio frequency amplification using pentode tubes in conjunction with tuned plate circuits resulting in high R. F. gain at all frequencies. The bias voltage on both stages is varied through the band switch to secure stability and preserve maximum gain on all bands. Both stages are used on all bands except the fifth or ultra-high frequency band. Double shielding is employed on the entire R. F. section to prevent signal pick-up by the wiring.

First Detector and Oscillator. A 6A7 tube is used as first detector and oscillator. The input circuit of the first detector is an R.F. choke and a 50,000 ohm resistor in parallel. The input grid of a 6A7 type of tube has a tendency to become positive whenever a strong signal is impressed on it, if there is any appreciable resistance in the grid circuit. The grid return connection of the choke is connected to one diode plate of the 85 A.V.C. tube so that if at any time the input grid of the 6A7 should become positive, due to overload, the diode plate will provide a low D.C. path to ground preventing detector overload distortion.

Intermediate Amplifier. The circuit employed in the two stages of intermediate amplification is conventional. The unusual feature of this portion of the receiver is in the transformers which are so designed that the mechanical coupling, and, in turn, the band width or selectivity may be varied continuously without changing the natural period of either primary or secondary coils. This variation of selectivity has no effect on the sensitivity of the receiver.

Delayed Automatic Volume Control. A pick-up winding is incorporated in the third I.F. transformer which feeds I.F. to the control grid of a 6D6 A.V.C. amplifier. The output of this stage is coupled through an untuned transformer to the diode plate of an 85 tube. The plate of the 85 is connected directly to B plus and the control grid to a tap in the diode load resistor. This tube is biased at approximately 10 volts which places a negative bias on the diode plate and no A.V.C. voltage is developed until a signal is tuned in of a strong enough value to swing the diode plate positive. At this point A.V.C. voltage is developed, which in turn makes the grid of the 85 negative and reduces the plate current which reduces the bias and allows still more A.V.C. voltage to be developed. This accumulative action allows excellent automatic control of the stronger signals and eliminates the detrimental effects of A.V.C. on weak signals.

Q.A.V.C. A portion of the resistance load of the 85 diode is incorporated in a potentiometer on the rear of the upper chassis. The arm of this potentiometer is connected to the grids of a 79 tube. The two plates of the 79 are connected in parallel and operate a magnetic relay which short-circuits the grids of the push-pull 42 audio driver stage. When a signal is tuned in the grids of the 79 tube become negative stopping the plate current and the relay opens, allowing the audio system of the receiver to operate. The signal level at which this occurs is determined by the setting of the potentiometer arm. A switch, operated by a lever under the band switch knob on the front panel is in series with the 79 plate circuit and when opened makes the Q.A.V.C. circuit inoperative. The shadowmeter is connected in the plate circuit of a separate 6D6 whose control grid is controlled by the A.V.C. voltage. The amplifying action of this tube allows the shadowmeter to operate on very weak stations.

First Audio and Driver. In order to eliminate any possibility of overloading, two 76 tubes are used in parallel in the first audio stage. Two audio transformers of special design couple the first audio stage to a push-pull driver stage using two 42 tubes. The smaller transformer only handles frequencies above 400 cycles and has a rising high characteristic. The large transformer handles frequencies below 400 cycles and is resonated at 30 cycles. The voltage output of each of these transformers is controlled by the tone control.

The Power Output Stage. This consists of eight 45 tubes connected in parallel push-pull. A much better balance is preserved in this stage by using several medium size power tubes rather than a pair of high-power tubes. Also, the voltage requirements are greatly reduced. A 99 ohm resistor is incorporated in the grid circuit of each tube to prevent parasitic oscillation.

Power Supply. There are two rectifying and filtering systems incorporated in the lower power amplifier chassis. One uses a single 5Z3 full wave rectifier and supplies plate current for the upper chassis and bias voltage for the output stage. The second uses two 5Z3 tubes and supplies plate current for the output stage only. Special electrolytic condensers are used in both power supplies. These condensers will make a slight frying sound while the tubes are heating, unlike the more common type of electrolytic condensers. This is not an indication of deterioration.

Reproducers. There are three dynamic reproducers used. The small one in the center reproduces the higher register above 4000 cycles. A filtering system is used in conjunction with this speaker which prevents the lower frequencies from being reproduced. The two large concert dynamics handle all frequencies lower than 4000 cycles. Two are necessary to handle the 500 watts output of the power stage without distortion. The leads and connections on all three speakers are color coded so as to insure correct connections and proper phasing. These connections must not be reversed.

Tuning Ranges.

Color	Kilocycles	Macacycles	Meters
Green	535 - 1,550	.53 - 1.55	560 - 190
Orange	1,530 - 4,575	1.53 - 4.57	196 - 65.7
Yellow	3,725 - 11,150	3.72 - 11.15	80.5 - 27
Red	9,500 - 31,600	9.5 - 31.6	31.5 - 9.4
Blue	19,500 - 63,600	19.5 - 63.6	15.3 - 4.7

The high efficiency and unexcelled performance of this receiver has been achieved by the careful selection and high quality of all components. It is therefore most important that when service is required only genuine Zenith parts and tubes be used.

Socket Voltages

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	1st R. F.	6.3	10	0	100	10	270
6D6	2nd R. F.	6.3	3	0	100	3	270
6A7	1st Det.	6.3	3	0	100	-	270
	Osc.			0	-	-	165
6D6	1st I.F.	6.3	3	0	100	3	255
6D6	2nd I.F.	6.3	3	0	100	3	255
76	2nd Det.	6.3	0	0	-	-	0
76	Parallel 1st. Audio	6.3	12	0	-	-	192
42	P.P.Driver	6.3	19	0	-	-	258
45	Power Aud.	2.5	63	0	-	-	330
79	Q.A.V.C.	6.3	0	.5	-	-	240
6D6	Shadowmeter Amplifier	6.3	1.3	0	100	1.3	255
6D6	A.V.C. Amplifier	6.3	3	0	100	3	255
85	A.V.C.	6.3	7	0	-	-	100
5Z3	Rect.Power Amplifier	5	-	-	-	-	-
5Z3	Rect. for Upper Chassis.	5	-	-	-	-	-

Line voltage 112.

Antenna and Ground shorted.

f - filament; k - cathode; g1 - control grid; g2 - screen grid; g3 - suppressor grid; p - plate.

Balance Procedure: Caution - Test set thoroughly for defective tubes, antenna and ground, check line voltage and chassis voltages before any attempt is made to re-balance.

Set volume control in full position, fidelity control in selective position, tone control at high position. Output meter usually connected across plates of 45 tubes.

Connect 485 K.C. service oscillator to grid of 6A7 and chassis ground, adjust I.F. transformers to maximum output with minimum signal input. Rotate selectivity control to broad position, I.F. output should remain constant six K.C. plus and minus of 485 K.C.

Set band switch on 550 to 1500 scale, rotate gang to 1400 K.C. Set test oscillator at 1400 and connect to aerial and ground.

Adjust oscillator trimmer screw, top padder screw on oscillator coil, to scale.

Rotate gang to 600 K.C., set test oscillator at 600. Adjust padder inside left front corner of shield can, near oscillator coil, for maximum output.

Rotate gang and padder together near 600 K.C. while making this adjustment. Set pointer to exactly 600 K.C. Re-adjust service oscillator to 1400, rotate gang

back to 1400 and re-check for maximum output and scale. The two R. F. and detector gang condenser trimmers should be adjusted to maximum output at 1400 K.C.

The short wave bands are adjusted at 3.5 and 9 and 28 Meg. Adjust for maximum signal or noise level. Under no circumstances should wires in oscillator and 5-meter circuits be disturbed. Adjust screws following in sequence below 1400 oscillator screw on oscillator coil.

Resistance Checks: The following D. C. resistances are given as help for continuity test, taken with the average type of ohmmeter.

Chassis - Power pack disconnected.

Driver transformer, Part #95-250 - #2853 -- Center tap of secondary to each side, numbers, 5 to 4, and 5 to 6 - 675 and 700 Ohms.

Primary - Center tap to each side 450 and 525 Ohm, numbers 2 to 1 and 2 to 3.

High Boost, #95-252, with low boost disconnected.

Primary (White wire
(White and black tracer - 200 Ohms

Secondary - (Blue - 200 Ohm
(Yellow

Secondary- (Red
(White and Red tracer - 200 Ohms.

Low Boost, #95-251, with high boost and tone control disconnected.

Primary - 650 Ohms.

Secondary center tap to each side 5000 Ohms.

Antenna choke - #20-71 - 15 Ohms.

Wave Trap - #20-101 - 5 Ohms.

Relay - #195-1 - 3000 Ohms.

Detector filter choke - #20-99 - 150 Ohms.

3rd I.F. - #20-100 - (Brown - 7 Ohms
(Green

(Red -

(Blue - 6.5 Ohms

(Black

(Green grid cap wire - 3 Ohms.

High fidelity I.F. - #S-3356 - 2 used.

(Green - Brown - 3.2 Ohms.

(Blue - Red - 3.2 Ohms.

R.F. Coil - Check from Grid cap, green wire to brown wire coming out of bottom of coil 490,000 Ohms. This high resistance is due to series resistor mounted on coil form of 490,000 value. Black to White - Yellow to Blue - $\frac{1}{2}$ ohms approximately.

Oscillator Coil -

Brown to Slate - $\frac{1}{2}$ Ohm.

Brown to Black - 3.9 Ohm.

Brown to White - 1.5 Ohm.

Red Green tracer to Blue - 4.8 Ohms.


Red Green tracer to Yellow - .8 Ohms.


Red Green tracer to Red - 1.5 Ohms.

Red to Blue - 3.2 Ohms.

Red to Yellow - 6.8 Ohms.

(Continued on Page 8)





SWITCHES SHOWN IN BROADCAST POSITION.

- | | | |
|---|---|--------|
| A | • | SEC. 1 |
| B | • | 2 |
| C | • | 3 |
| D | • | 6 |
| E | • | 5 |
| F | • | 4 |
| G | • | 7 |
| H | • | 8 |
| J | • | 9 |
| K | • | 10 |

SECTIONS OF SWITCH IN ALPHABETICAL ORDER FROM FRONT TO REAR OF CHASSIS.

ZENITH RADIO CORP.
CHICAGO, ILL.
U.S.A.

(Continued from Page 5)

Antenna Coil - Check for continuity - Red wire through to Green wire - This will include all coils on this form.

These coil readings are given on coils only, disconnected from associating circuits.

Power pack readings taken with set disconnected and pack cold, tubes in sockets.

Both A. C. primary windings #95-256 and #95-257 less than $\frac{1}{2}$ Ohm. 45 and 6 volt winding practically no D.C. resistance, - check for continuity only and check center tap of 45 winding.

523 filament same as above.

523 plate windings 100 Ohms.

Check center tap, approximately $\frac{1}{2}$ of total winding or 50 Ohms.

Filter chokes - #95-255 - #95-254 - 70 Ohms.

Line filter #S-3367 - Check for continuity.

See voltage readings supplement.

SERVICE NOTES

Hums - Defective tubes and check filters - Voltages, etc.

Hums - Weak and Distorted. Check #95-250 transformer for open winding, weak audio if shorted.

Too Much High, Lacks Low Notes - #95-250 open center tap. #22-225 condenser open 50,000 ohm resistor grounded on tone control to bottom plate. $\frac{1}{2}$ of low boost shorted secondary.

Motorboats On All Bands - #22-228 - .5 condenser to 85 socket open, I. F. shorted, graph won't narrow and set will distort on edge of carrier.

Weak And Distorted All Bands. 1500 Ohm resistor across #22-189 25-volt 2 Mmfd. open.


Blocks Up - Tendency to Slow Motorboat. Check red wire from #63-407 to 10,000 ohm on 5-meter coil for ground. Set seems alive but no signal if this resistor is open.

Set Dead- Check tubes, filters, coils and transformers and I.F. for grounds or open.


Dead - No Radio - Open 'Phono Switch.

Weak Audio And High Notes - Hum level increases slightly if you pull one push-pull #42 tube. Open secondary on low boost #95-251. Disconnect high boost and tone control circuit before testing.

Tone Control No Effect On Highs. Set flutters as tone control is rotated to bass. Check .1-22 -3770 for open or short.



Receiver Chassis Drawing



Power Pack Chassis Drawing



Parts and Prices

Chassis #2501

MODEL
STRATOSPHERE

Dial Assembly

26-76	Calibrated Glass Scales (includes 6 scales & frame).....	\$35.00
32-5	Dial Drive Belt	.50
59-30	Split Second Pointer (white)	.50
59-31	Special "Z" Pointer (gold)	5.00
76-153	Planetary Drive Shaft Assembly	3.50
93-230	Dial Glass Cushion Washer	.50
100-28	Special 110 V. Dial Lamp	1.25
126-170	Dial Lamp Reflector Shields	.25
192-5	Dial Glass	1.50

Resistors

63-136	50 M	Ohm	$\frac{1}{4}$	Watt		.25
63-157	100	"	$\frac{1}{2}$	"		.25
63-180	1 M	"	$\frac{1}{2}$	"		.20
63-241	5 M	"	$\frac{1}{2}$	"		.25
63-246	150	"	$\frac{1}{2}$	"		.20
63-258	490 M	"	$\frac{1}{2}$	"		.20
63-260	100 M	"	$\frac{1}{2}$	"		.20
63-280	19 M	"	$\frac{1}{2}$	"		.20
63-290	260 M	"	$\frac{1}{2}$	"		.20
63-357	300	"	$\frac{1}{2}$	"		.20
63-362	400	"	$\frac{1}{2}$	"		.20
63-387	4 M	"		Candohm		.45
63-389	1 M	- 1857 Ohm		Candohm		.45
63-390	1	Megohm		Dual Volume Control Assembly		5.00
63-391				Dual Tone Control Assembly		4.50
63-396	10 M	Ohm	$\frac{1}{4}$	Watt		.20
63-404	60	Ohm		Candohm		.25
63-405	330	"		"		.25
63-406	5 M	Ohm		Candohm		.40
63-407	10 M	"		"		.45
63-408	500 M	Ohm		Q Control Assembly		.80
63-411	20	Ohm	$\frac{1}{4}$	Watt		.20
63-412	3500	"	$\frac{1}{2}$	"		.20
63-413	4 M	"	$\frac{1}{2}$	"		.20
63-414	99 M	"	$\frac{1}{2}$	"		.20
63-415	10 M	"	$\frac{1}{2}$	"		.20
63-416	1400	"	$\frac{1}{2}$	"		.20
63-417	99	"	$\frac{1}{2}$	"		.20
63-418	1500	"	$\frac{1}{2}$	"		.20
63-432	5	"		Candohm		.25

Condensers

22-170	.1	Mfd.	400 V.		.25
22-189	20.	"	25 V.		1.25
22-199	.5	"	200 V.		.35
22-205	200-500	Mnfd.			.35



Condensers Cont'd

22-225	5. Mfd. 25 V.	\$.65
22-305	2 - 35 Mmfd. Padder	.15
22-338	Special	1.00
22-340	Four-Gang Variable	7.00
22-360	4. Mfd. 600 V.	4.00
22-361	16. " 450 V.	1.50
22-362	6. " 300 V.	1.00
22-364	.0013 Mfd. 600 V.	.20
22-365	.0001 " 600 V.	.15
22-366	.00035 " 600 V.	.15
22-367	.00003 " 600 V.	.15
22-368	.003 " 600 V.	.20
22-369	.005 " 600 V.	.35
22-370	.00325 " 600 V.	.25
22-371	.01 " 600 V.	.25
22-372	.01 " 300 V.	.25
22-373	.05 " 300 V.	.25
22-374	.01 " 300 V.	.25
22-375	.1 " 300 V.	.25
22-377	.1 " 600 V.	.35
22-378	.04 " 600 V.	.35
22-379	.002 " 600 V.	.25
22-381	2 - 35 Mmfd. Special Padder	.50
22-383	Special	1.00

Coils and Chokes

20-71	Antenna Choke	.20
20-76	R.F. Plate Choke	.25
20-99	Detector Filter Choke	.45
20-100	Untuned I. F. Coil	.65
20-104	5 Meter Detector Coil	.20
95-264	3rd I. F. Transformer Assembly	2.50
S-3340	Antenna Coil Assembly	3.50
S-3341	R.F. " "	4.00
S-3358	Variable Selector I.F. Assembly	7.00
S-3366	Oscillator Coil Assembly	4.00
S-3367	Line Filter Coil	3.50
S-3368	H.F. Oscillator Coil Assembly	3.00
S-3498	Detector Coil Assembly	4.25

Miscellaneous

8-33	Antenna Binding Post	1.00
3-34	Ground Binding Post	1.00
44-4	Phonograph Jack	.15
46-103	"Q" Control Knob	.15
46-104	Volume and Tone Control Knobs	1.50
46-105	Tuning Knob (front half)	1.50
46-106	" " (rear half)	1.50
46-107	Band Selector Switch Knob	1.50



Miscellaneous Cont'd

49-99	Tweeter Dynamic Speaker	\$35.00
49-102	#2 - 12" Concert Dynamic Speaker	30.00
49-103	#1 - 12" " " " "	30.00
	Cone and Voice Coil for either 49-102 or 49-103	7.00
52-60	Power Cable	3.00
52-61	Speaker Cable	.75
57-463	Shadowgraph Escutcheon Plate	.35
57-471	Dial Escutcheon Plate	6.00
78-64	85 Tube Socket (for .0625 chassis stock)	.10
78-69	6D6 " " (" " " ")	.10
78-92	42 " " (" " " ")	.10
78-96	6D6 " " (" .0805 " ")	.10
78-105	6A7 " " (" " " ")	.10
78-117	76 " " (" .0625 " ")	.10
78-118	79 " " (" " " ")	.10
78-119	45 " " (" " " ")	.10
78-120	5Z3 " " (" " " ")	.10
80-104	I.F. Unit Plunger Spring	.10
80-105	Control Arm Spring	.10
85-64	Toggle Switch	1.00
85-67	Band Selector Switch	8.00
85-69	S.P. D.T. Phono Switch	.75
95-250	Driver Transformer	4.00
95-251	Low Boost Audio Transformer	4.00
95-252	High Frequency Transformer	2.00
95-253	Main Speaker Transformer	4.00
95-254	Power Choke	6.50
95-255	" "	3.50
95-256	Power Transformer for Output Tubes - 117 V. - 60 Cycle	14.00
95-257	" " " Receiver and Filaments - 117 V. - 60 C.	15.00
95-265	Special Choke for Tweeter Speaker	2.25
95-266	" " " " " "	2.25
95-267	Output Transformer for Tweeter Speaker	2.25
95-271	Power Transformer for Receiver and Filaments, 117 V. - 25 C.	25.00
95-272	" " " Output Tubes - 117 V. - 25 C.	24.00
122-9	Shadowgraph Meter	2.00
126-127	Tube Shields	.15
126-155	Line Filter Shield	.15
126-171	Tube Shield	.25
195-1	"Q" Control Relay	2.00

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

February 8, 1935

ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

SERVICE BULLETIN



25 Tube

Stratosphere

(SERIAL NOS. AFTER 754106)



ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

GENERAL INFORMATION

Tubes used are as follows:

6D6	First Radio Frequency Amplifier
6D6	Second Radio Frequency Amplifier
6A7	First Detector and Oscillator
6D6	First Intermediate Amplifier
6D6	Second Intermediate Amplifier
76	Second Detector
2 - 76	Audio Amplifier
2 - 42	Push-Pull Driver Amplifier
8 - 45	Parallel Push-Pull Power Amplifier
79	Electron Relay for Q Circuit
6D6	Shadowgraph Amplifier
85	Automatic Volume Control
6D6	A.V.C. Amplifier
2 - 5Z3	Rectifier for Power Amplifier
5Z3	Rectifier for remainder for receiver

CIRCUIT

Radio Frequency Amplifier. This receiver uses a preselector and a tuned R.F. stage on the green band, and a single tuned R.F. stage on the orange and yellow bands. Two tuned R.F. stages are employed on the red band. Due to the extreme difficulty of obtaining usable R.F. gain on frequencies below 18 megacycles, the antenna is coupled directly to the grid circuit of the first detector on the blue band. Double shielding is employed on the entire R.F. section to prevent signal or noise pick-up by the wiring.

First Detector and Oscillator. A 6A7 tube is used as first detector and oscillator. The input grid of a 6A7 tube has a tendency to become positive whenever a strong signal is impressed on it, if there is any appreciable resistance in the grid circuit. The grid return side of the input circuit is connected to one diode plate of the 85 A.V.C. tube so that if at any time the input grid of the 6A7 should become positive, the diode plate will allow a low D.C. path to ground, preventing overload distortion.

Intermediate Amplifier. The circuit employed in the two stages of intermediate amplification is conventional. The unusual feature of this portion of the receiver is in the transformers which are so designed that the mechanical coupling, and, in turn, the band width or selectivity may be varied continuously without changing the natural period of either primary or secondary coils. This variation of selectivity has no effect on the sensitivity of the receiver.

Delayed Automatic Volume Control. A pick-up winding is incorporated in the third I.F. transformer which feeds I.F. to the control grid of a 6D6 A.V.C. amplifier. The output of this stage is coupled through an untuned transformer to the diode plate of an 85 tube. The plate of the 85 is connected directly to B plus and the control grid to a tap in the diode load resistor. This tube is biased at approximately 10 volts which places a negative bias on the diode plate and no A.V.C. voltage is developed until a signal is tuned in of a strong enough value to swing the diode plate positive. At this point A.V.C. voltage is developed, which in turn makes the grid of the 85 negative and reduces the plate current which reduces the bias and allows still more A.V.C. voltage to be developed. This accumulative action allows excellent automatic control of the stronger signals and eliminates the detrimental effects of A.V.C. on weak signals.

Q.A.V.C. A portion of the resistance load of the 85 diode is incorporated in a potentiometer on the rear of the upper chassis. The arm of this potentiometer

is connected to the grids of a 79 tube. The two plates of the 79 are connected in parallel and operate a magnetic relay which short-circuits the grids of the push-pull 42 audio driver stage. When a signal is tuned in the grids of the 79 tube become negative stopping the plate current and the relay opens, allowing the audio system of the receiver to operate. The signal level at which this occurs is determined by the setting of the potentiometer arm. A switch, operated by a lever under the band switch knob on the front panel is in series with the 79 plate circuit and when opened makes the Q.A.V.C. circuit inoperative. The shadowmeter is connected in the plate circuit of a separate 6D6 whose control grid is controlled by the A.V.C. voltage. The amplifying action of this tube allows the shadowmeter to operate on very weak stations.

Preamplifier and Audio Driver. The preamplifier consists of two cascade resistance-coupled stages using 76 tubes. The value of the grid resistance on the second stage may be varied by the switch in the upper right-hand corner of the control panel so as to achieve a 400% increase of power sensitivity for use on short wave reception. It is possible to overload the power amplifier when using this high gain. Two audio transformers of special design couple the second audio stage to a push-pull driver stage, using two 42 tubes. The smaller transformer only handles frequencies above 400 cycles and has a rising high characteristic. The large transformer handles frequencies below 400 cycles and is resonated at 30 cycles. The voltage output of each of these transformers is controlled by the tone control.

The Power Output Stage. This consists of eight 45 tubes connected in parallel push-pull. A much better balance is preserved in this stage by using several medium size power tubes rather than a pair of high-power tubes. Also, the voltage requirements are greatly reduced. A 99 ohm resistor is incorporated in the grid circuit of each tube to prevent parasitic oscillation.

Power Supply. There are two rectifying and filtering systems incorporated in the lower power amplifier chassis. One uses a single 5Z3 full wave rectifier and supplies plate current for the upper chassis and bias voltage for the output stage. The second uses two 5Z3 tubes and supplies plate current for the output stage only. Special electrolytic condensers are used in both power supplies. These condensers will make a slight frying sound while the tubes are heating, unlike the more common type of electrolytic condensers. This is not an indication of deterioration.

Reproducers. There are three dynamic reproducers used. The small one in the center reproduces the higher register above 4000 cycles. A filtering system is used in conjunction with this speaker which prevents the lower frequencies from being reproduced. This speaker may be made inoperative whenever desired by means of the switch in the upper left-hand corner of the control panel. The two large concert type dynamics handle all frequencies below 4000 cycles. Two are necessary to handle the 50 watt output of the power stage without distortion. The leads and connections of all three speakers are color coded so as to insure correct connections and proper phasing. These connections must not be reversed.

Tuning Ranges.

Color	Kilocycles	Megacycles	Meters
Green	520 - 1,500	.52 - 1.5	576 - 200
Orange	1,450 - 4,200	1.45 - 4.2	207 - 71
Yellow	3,700 - 10,000	3.7 - 10	81 - 30
Red	8,500 - 23,000	8.5 - 23	35 - 13
Blue	18,000 - 45,000	18 - 45	16.6- 6.5

The high efficiency and unexcelled performance of this receiver has been achieved by the careful selection and high quality of all components. It is therefore most important that when service is required only genuine Zenith parts and tubes be used.

Socket Voltages

TUBE	POSITION	Ef	Ek	Eg1	Eg2	Eg3	Ep
6D6	1st R. F.	6.3	3	0	100	3	300
6D6	2nd R. F.	6.3	3	0	100	3	300
6A7	1st Det.	6.3	3	0	100	-	300
	Osc.			3	-	-	130
6D6	1st I. F.	6.3	7	0	100	7	300
6D6	2nd I. F.	6.3	3	0	100	3	300
76	2nd Det.	6.3	0	0	-	-	0
76	1st A.F.	6.3	8	0	-	-	140
76	2nd A. F.	6.3	14	0	-	-	270
42	Driver	6.3	22	0	300	-	300
45	Power A.F.	2.5	63	0	-	-	330
79	Q.A.V.C.	6.3	0	0	-	-	250 Q on 0 Q off
6D6	Shadowmeter Amplifier	6.3	3	0	100	3	300
6D6	A.V.C. Amplf.	6.3	3	0	100	3	300
85	A.V.C.	6.3	0	0	-	-	100
523	Rect. Power Amplifier	5	-	-	-	-	-
523	Rect. for Upper Chassis	5	-	-	-	-	-

Line Voltage 112.

Antenna and Ground shorted.

f - filament; k - cathode; g1 - control grid; g2 - screen grid; g3 - suppressor grid; p - plate.

Balance Procedure: Caution - Test set thoroughly for defective tubes, antenna and ground, check line voltage and chassis voltages before any attempt is made to rebalance. All balancing should be done with a calibrated oscillator capable of a steady signal and minimum attenuation of signal input strength. The screw driver used should be of non metallic type and output meter usually connected across plates of 45 tubes at point where the two green speaker wires come out of power pack.

Warning. Do not rebalance this chassis unless absolutely necessary as all chassis are balanced on an accurate signal generator before shipment. Set volume control in full on position, tone control on treble, high fidelity control in selective position. Band switch set on broadcast position, gang 580 K.C., approximately. Connect 485 K.C. service oscillator to grid of 6A7 and chassis ground, adjust I.F. transformers, to maximum output with minimum input signal. Rotate selectivity control to broad position, I.F. output should remain constant 6 K.C. plus and minus 485 K. C. Next, connect the same 485 K.C. signal directly across aerial and ground binding post. Balance wave trap to minimum signal. Gang set at 550.

Note: Refer to drawing of trimmer assembly to identify trimmers.

Set service oscillator at 600 K.C. Adjust broadcast padder "A" meanwhile rocking pointer past 600 K.C. on dial to combination giving greatest output.


Set chassis dial to exactly 1400 K.C., and service oscillator to 1400 K.C. Balance "L" oscillator trimmer to scale. Reset oscillator to 600 K.C., rotate gang to 600 and re-check 600 padder for maximum output. Next, retune oscillator trimmer at 1400 K.C. Adjust detector trimmer "H" and R.F. trimmer "B" to maximum output.


Police or Orange band. Rotate chassis band switch to police band, gang should be rotated to 3 megacycles, oscillator to 3 megacycles also. Adjust oscillator trimmer "K" to scale, peak "G" detector and "C" R.F. trimmers to maximum peak.

Yellow band. Set dial and oscillator to 9 megacycles, Peak oscillator trimmer "J" for scale, "N" detector and "D" R. F. trimmers for maximum peak.

Red band. Set dial and oscillator at 21 megacycles, peak "I" oscillator for scale, "M" detector and "E" R.F., and trimmer "F" located at back of band switch for maximum peak. There are no adjustments on the Blue band.

On all short wave adjustments be careful not to balance the oscillator circuit to the image frequency of the signal. This is equal to signal frequency minus twice the I.F. frequency.





DIAG. PART DESCRIPTION


N ^o	N ^o	
G1-22-371	.01 MFD.	
G2-22-374	.01	
G3-22-373	.05	
G4-22-377	.1	
G5-22-361	.16	
G6-22-372	.01	
G7-22-365	.0001	
G8-22-127	.000025 MFD.	
G9-22-375	.1 MFD.	
G10-22-367	.00005 MFD.	
G11-22-189	20 MFD.	
G12-22-378	.04	
G13-22-362	8 MFD.	
G14-22-225	5	
G15-22-360	4	
G16-22-379	.002 MFD.	
G17-22-289	.0005	
G18-22-395	450 MMFD.	
G19-22-287	.03 MFD.	
G20-22-342	.0029 MFD.	
G21-22-341	.00092	
G22-22-147	.0005	
G23-22-305	2-35 MFD.	
G24-22-383	ORDER BY PART N ^o ONLY	
G25-22-338	SPECIAL TOLERANCES	
G26-22-289	.00005 MFD.	
G27-22-199	5 MFD.	
G28-22-397	2-35 MMFD.	
G29-22-398	2-35	
G30-22-205	200-500 MMFD. BRIDGE	
G31-22-321	8 MFD.	
G32-22-396	2-35 MMFD.	
G33-22-229	.005	

DIAG. PART DESCRIPTION

N ^o	N ^o	
R1-63-362	400 OHMS	1/4 W.
R2-63-416	1400	1/4 W.
R3-63-258	490 M	1/4 W.
R4-63-136	50 M	1/4 W.
R5-63-357	300	1/4 W.
R6-63-291	29 M	1/4 W.
R7-63-260	100 M	1/4 W.
R8-63-412	3500	1/4 W.
R9-63-390	1 MEG. DUAL VOL.	
R10-63-391	T.G.	
R11-63-387	4 M OHMS CANDOHM	1/4 W.
R12-63-389	1M-18.57 CANDOHMS	1/4 W.
R13-63-406	5 M OHMS CANDOHM	1/4 W.
R14-63-413	4 M	1/4 W.
R15-63-405	330 CANDOHM	1/4 W.
R16-63-408	500M. 0 CONTROL	1/4 W.
R17-63-404	60 OHMS CANDOHM	1/4 W.
R18-63-279	3 M	1/4 W.
R19-63-414	99M OHMS	1/4 W.
R20-63-417	99 OHMS	1/4 W.
R21-63-326	4 M	1/4 W.
R22-63-407	10 MOHMS CANDOHM	1/4 W.
R23-63-396	10 M	1/4 W.
R24-63-442	50 M	1/4 W.
R25-63-440	200 M	1/4 W.
R26-63-441	1 MEG	1/4 W.
R27-63-290	260 M	1/4 W.
R28-63-241	5 M	1/4 W.
R29-63-432	5 OHMS CANDOHM	1/4 W.
R30-63-435	20 M OHMS	1/4 W.
R31-63-439	2700 OHMS	1/4 W.
R32-63-378	250	1/4 W.

DIAG. PART DESCRIPTION


N ^o	N ^o	
1	85-71	BAND SELECTOR SWITCH
2	95-250	DRIVER TRANS.
3	95-251	LOW BOOST AUDIO TRANS.
4	95-252	HIGH FREQUENCY TRANS.
5	95-253	SPEAKER OUTPUT TRANS.
6	95-254	POWER CHoke
7	95-255	
8	95-256	OUTPUT B. SUPPLY TRANS.
9	95-257	POWER TRANS.
10	95-264	3RD I.F. TRANS.
11	122-9	SHADOWGRAPH
12	195-1	SINGLE CONTACT RELAY
13	5-3587	OSC. COIL ASSEM.
14	5-3593	ANT. COIL
15	5-3589	R.F. COIL ASSEM.
16	5-3588	VAR. SELECT. I.F. ASSEM.
17	20-109	WAVE TRAP COIL ASSEM.
18	5-3115	H.F. OSC. COIL ASSEM.
19	20-99	DET. FILTER CHoke
20	20-100	UNTUNED I.F. COIL
21	5-3367	LINE FILTER COIL ASSEM.
22	20-83	ANT. CHoke
23	20-114	7 METER DET. COIL
24	85-69	PHONO SWITCH
25	SPKR. FIELD 49-102-49-103	
26	49-99	
27	49-99	SPEAKER
28	49-102	2 JENSEN SPEAKER
29	49-103	#1
30	85-64	TOGGLE SWITCH
31	95-266	ORDER BY PART N ^o ONLY
32	95-265	SPECIAL TOLERANCES
33	95-267	
34	20-81	R.F. PLATE CHoke ASSEM.
35	5-3586	DET. COIL ASSEM.
36	20-79	DET. BROADCAST BAND COIL
37	20-71	R.F. CHoke
38	5-3538	R.F. PLATE CHoke ASSEM.
39	5-3591	10-23 MEGACYCLE COIL
40	85-75	TWEETER SWITCH ASSEM.
41	85-75	SWITCH
42	20-118	SCRATCH FILTER COIL



115 V.
50-60 CYCLE

110V OUTLET
FOR PHONO.

5Z3
RECTIFIERS



SWITCHES SHOWN IN BROADCAST POSITION

REVISED MODEL N° 1000Z

SECTIONS OF SWITCH ARE IN ALPHABETICAL ORDER FROM FRONT TO REAR OF CHASSIS

A - SECTION N° 1
 B - " " 2
 C - " " 3
 D - " " 4
 E - " " 5
 F - " " 6
 G - " " 7

RESISTANCE MEASUREMENTS - UPPER CHASSIS

TUBE	POSITION	HEATER	CATHODE	GRID	SCREEN	SUPPRESSOR	PLATE
6D6	1st. R. F.	20	350	600 M.	5 Meg.	350	1 Meg.
6D6	2nd. R. F.	20	350	600 M.	5 Meg.	350	1 Meg.
6A7	1st. Det.	20	275	600 M.	5 Meg.	-	1 Meg.
	Osc.			50 M.	-	-	1 Meg.
6D6	1st. I. F.	20	350	2	5 Meg.	350	1 Meg.
6D6	2nd. I. F.	20	3000	500 M.	5 Meg.	3000	1 Meg.
76	2nd Det.	20	0	100 M.	-	-	100 M.
76	1st. Aud.	20	4000	3000	-	-	1 Meg.
76	2nd. Aud.	20	3000	1 Meg.	-	-	1 Meg.
42	Driver	20	325	3000	-	-	1 Meg.
79	Q.A.V.C.	20	0	1 Meg.	-	-	1 Meg. Q on
6D6	Shadowmeter Amplifier	20	250	500 M.	5 Meg.	250	1 Meg.
6D6	A.V.C. Amplf.	20	250	2	5 Meg.	250	1 Meg.
85	A.V.C.	20	10M	250 M.	400 M.	500 M.	5 Meg.

All Measurements Made With Lower Chassis Disconnected.

SERVICE NOTES

Hums - Defective tubes and check filters - Voltages, etc.

Hums - Weak and Distorted. Check #95-250 transformer for open winding, weak audio if shorted.

Too Much High, Lacks Low Notes - #95-250 open center tap. #22-225 condenser open, 50,000 ohm resistor grounded on tone control to bottom plate. $\frac{1}{2}$ of low boost shorted secondary.

Motorboats on All Bands - #22-228 - .5 condenser to 85 socket open, I.F. shorted, graph won't narrow and set will distort on edge of carrier.


Weak and Distorted - All Bands. Audio bias resistor across #22-189 25-volt 20 Mmfd. open.

Set Dead - Check tubes, filters, coils and transformers and I. F. for grounds or open.


Dead - No Radio - Open 'Phono Switch.

Weak Audio and High Notes - Hum level increases slightly if you pull one push-pull #42 tube. Open secondary on low boost #95-251. Disconnect high boost and tone control circuit before testing.

Tone Control No Effect On Highs. Set flutters as tone control is rotated to bass. Check .1-22 -3770 for open or short.



Receiver Chassis Drawing



Power Pack Chassis Drawing



Parts and Prices

Chassis #2501-C
#2501-P

MODEL 1000Z
STRATOSPHERE

Dial Assembly

26-74	Planetary drive and Dial drive mechanism assemblies.....	\$20.00
26-88	Calibrated Glass Scales (includes 6 scales & frames).....	30.00
32-5	Dial Drive Belt	.50
59-30	Split Second Pointer (white).....	.50
59-31	Special Z Pointer (gold).....	5.00
93-230	Dial Glass Cushion Washer	.50
100-28	Special 110 V. Dial Lamp	1.25
126-170	Dial Lamp Reflector Shields	.25
192-5	Dial Glass	1.50

Resistors

63-136	50 M	ohm	$\frac{1}{2}$	watt		.25
63-241	5 M	"	$\frac{1}{2}$	"		.25
63-258	490 M	"	$\frac{1}{2}$	"		.20
63-260	100 M	"	$\frac{1}{2}$	"		.20
63-279	3 M	"	$\frac{1}{2}$	"		.20
63-290	260 M	"	$\frac{1}{2}$	"		.20
63-291	29 M	"	$\frac{1}{2}$	"		.25
63-326	4 M	"	$\frac{1}{2}$	"		.20
63-357	300	"	$\frac{1}{2}$	"		.20
63-362	400	"	$\frac{1}{2}$	"		.20
63-378	250	"	$\frac{1}{2}$	"		.20
63-387	4 M	"	Candohm			.45
63-389	1 M - 1857	Ohm	Candohm			.45
63-390	1 Megohm	Dual	Volume Control Assembly			5.00
63-391	Dual	Tone Control Assembly				4.50
63-396	10 M	ohm	$\frac{1}{2}$	watt		.20
63-404	60	"	Candohm			.25
63-405	330	"	"			.25
63-406	5 M	"	"			.40
63-407	10 M	"	"			.45
63-408	500 M	"	"Q"	Control Assembly		.80
63-412	3500	"	$\frac{1}{2}$	watt		.20
63-413	4 M	"	$\frac{1}{2}$	"		.20
63-414	99 M	"	$\frac{1}{2}$	"		.20
63-416	1400	"	$\frac{1}{2}$	"		.20
63-417	99	"	$\frac{1}{2}$	"		.20
63-432	5	"	Candohm			.25
63-438	20 M	"	$\frac{1}{2}$	watt		.20
63-439	2700	"	$\frac{1}{2}$	"		.20
63-440	200 M	"	$\frac{1}{2}$	"		.20
63-441	1 Megohm	"	$\frac{1}{2}$	"		.20
63-442	50 M	ohm	$\frac{1}{2}$	"		.20

Condensers

22-127	25.	Mufd.	600 V.		.20
--------	-----	-------	--------	-------	-----

Condensers Cont'd

22-147	.0005	Mfd.	600 V.		\$.15
22-189	20.	"	25 V.		1.25
22-199	.5	"	200 V.		.35
22-205	200-500	Mmfd.	Padder		.35
22-225	5.	Mfd.	25 V.		.65
22-229	.005	"	600 V.		.15
22-287	.03	"	600 V.		.15
22-289	.00005	"	600 V.		.12
22-305	2 - 35	Mmfd.	Padder		.15
22-321	8.	Mfd.	450 V.		1.25
22-341	920	Mmfd.	600 V.		.15
22-342	2900	"	600 V.		.25
22-360	4.	Mfd.	600 V.		4.00
22-361	16.	"	450 V.		1.50
22-362	8.	"	300 V.		1.00
22-365	.0001	"	600 V.		.15
22-367	.00005	Mfd.	600 V.		.15
22-371	.01	"	600 V.		.25
22-372	.01	"	300 V.		.25
22-373	.05	"	300 V.		.25
22-374	.01	"	300 V.		.25
22-375	.1	"	300 V.		.25
22-377	.1	"	600 V.		.35
22-378	.04	"	600 V.		.35
22-379	.002	"	600 V.		.25
22-395	4-Gang	Variable	Condenser		7.00
22-396	" "	Trimmer	Condenser		.60
22-397	" "	"	"		.60
22-398	2-Gang	"	"		.35
22-383	Special	(order by part number only)			1.00
22-338	"	"	"		1.00

Coils and Chokes

20-71	R.F. Choke		.20
20-79	Detector Broadcast Band Coil		.40
20-81	R.F. Plate Choke		.65
20-88	Antenna Choke		.25
20-99	Detector Filter Choke		.45
20-100	Untuned I.F. Coil		.65
20-109	Wave Trap Coil Assembly		1.00
20-114	7-Meter Detector Coil Assembly		.60
20-118	Phono Scratch Filter Choke		2.00
95-264	3rd I.F. Transformer Assembly		2.50
S-3115	H.F. Oscillator Coil Assembly		.75
S-3367	Line Filter Coil Assembly		3.50
S-3538	R.F. Plate Choke Assembly		.40
S-3587	Oscillator Coil Assembly		4.50
S-3588	Detector Coil Assembly		4.00
S-3589	R.F. " "		3.50
S-3591	10-23 Megacycle R.F. Coil Assembly		.75
S-3593	Antenna Coil Assembly		3.00

Miscellaneous

8-33	Antenna Binding Post		1.00
8-34	Ground " "		1.00
44-10	Phonograph Jack		.15

Miscellaneous Cont'd

46-103	"Q" Control Knob	\$.15
46-104	Volume and Tone Control Knobs	1.50
46-105	Tuning Knob (front half)	1.50
46-106	" " (rear half)	1.50
46-107	Band Selector Switch Knob	1.50
46-120	Tweeter and L.D. Knob	1.50
49-99	Tweeter Dynamic Speaker	35.00
49-102	#2 - 12" Dynamic Speaker	30.00
49-103	#1 - 12" " "	30.00
	Cone and Voice Coil Assembly for 49-102 or 49-103	7.00
52-60	Power Cable	3.00
52-61	Speaker "	.75
57-463	Shadowgraph Escutcheon Plate	.35
57-471	Dial Escutcheon Plate	6.00
78-64	85 Tube Socket (for .0625 chassis stock)	.10
78-69	6D6 " " " " " "	.10
78-92	42 " " " " " "	.10
78-96	6D6 " " " .0805 " "	.10
78-105	6A7 " " " " " "	.10
78-116	Dial Lamp Sockets	.50
78-117	76 Tube " (for .0625 chassis stock)	.10
78-118	79 " " " " " "	.10
78-119	45 " " " " " "	.10
78-120	5Z3 " " " " " "	.10
85-64	Toggle Switch	1.00
85-69	S.P.D.T. Phono Switch	.75
85-71	Band Selector "	8.00
85-75	S.P.S.T. Tweeter Switch	.60
95-250	Driver Transformer	4.00
95-251	Low Boost Audio Transformer	4.00
95-252	High Frequency Transformer	2.00
95-253	Main Speaker Transformer	4.00
95-254	Power Choke	6.50
95-255	" "	3.50
95-256	Power Transformer for Output Tubes, 117 V., 60 Cycle	14.00
95-257	" " " Receiver & Filaments, 117 V., 60 C....	15.00
95-265	Special Choke for Tweeter Speaker	2.25
95-266	" " " " " "	2.25
95-267	Output Transformer for Tweeter Speaker	2.25
95-271	Power Transformer for Receiver & Filaments, 117 V., 25 C....	25.00
95-272	" " Output Tubes, 117 V., 25 Cycle	24.00
122-9	Shadowgraph Meter	2.00
126-127	Tube Shields	.15
126-155	Line Filter Shield	.15
126-171	Tube Shield	.25
126-182	" "	.25
191-1	"Q" Control Relay	2.00

THESE PRICES SUPERSEDE ALL OTHER PREVIOUS QUOTATIONS AND ARE SUBJECT TO
REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

May 21, 1935

ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

SERVICE MANUAL



1936 AUTOMOBILE RECEIVERS

MODELS

5M90
6M90-S
6M90-D
6M91-S
6M91-D
6M92
7M91-S
7M91-D

ZENITH RADIO CORPORATION
CHICAGO, U. S. A.




Fig. 1.—Circuit Diagram. Model 5-M-90. (Chassis No. 5510)

SOCKET VOLTAGES 5-M-90

Tube	Position	Ef	Ek	Eg ¹	Eg ²	Eg ³	Ep
6A7	1st Det.	5.8	4	0	97	—	205
	Osc.			0	—	—	175
6D6	I. F.	5.8	4	0	97	4	217
75	2nd Det. A. V. C. 1st Audio	5.8	1.1	0	—	—	160
41	PWR.	5.8	0	—15	225	—	215
6Z4	RECT.	5.8	—	225	—	—	—

Line Voltage —6V.

Ef—heaters; Ek—cathode; Eg¹—control grid; Eg²—screen grid; Eg³—suppressor grid; Ep—plate.

All measurements taken from point indicated to ground, using a 1000 ohm per volt. D. C. meter.






Fig. 2.—Tube Position. 5-M-90



314

SOCKET VOLTAGES 6-M-92

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R.F. Amp.	0	5.8	175	84	4.6	—	0	4.6	0
6A8	1st Det. Osc.	0	0	175	84	—16	110	5.8	4.6	0
6K7	I. F. Amp.	0	5.8	180	84	3.6	—	0	3.6	0
6Q7	2nd Det. A. V. C. 1st Audio	0	5.8	130	.3	.3	—	0	1.3	0
6F6	Power	0	0	170	180	—3.4	—	5.8	0	—
6X5	RECT.	0	5.8	AC	—	AC	—	0	180	—



Voltage at Battery 6V.

Voltage at Switch 5.8 V.

Antenna disconnected.

All voltages measured with 1000 ohms per volt D. C. meter.

Total current consumption 6 Amperes.

Sensitivity at one watt output 4 Mv.

Maximum undistorted power output 4 Watts.




Fig. 5.—Tube Position. 6-M-92




Fig. 6.—Circuit Diagram. Models 6-M-90S and 6-M-90D (Chassis No. 5630)

SOCKET VOLTAGES 6-M-90S, 6-M-90D

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R.F. Amp.	0	5.8	215	100	5.7	—	0	5.7	0
6A8	1st Det. Osc.	0	0	215	100	—26	150	5.8	5.9	0
6K7	I. F. Amp.	0	5.8	225	100	5.4	—	0	5.4	0
6Q7	2nd Det. A. V. C. 1st Audio	0	5.8	150	—2	—2	—	0	2	0
6F6	Power	0	0	210	220	—3	—	5.8	0	—
6X5	RECT.	0	5.8	AC	—	AC	—	0	220	—




Fig. 7

Voltage at Battery 6V.

Voltage at Switch 5.8V.

All voltages measured with 1000 ohms per volt D. C. meter.

Total current consumption 6.5 Amperes.

Sensitivity at one watt output 1.5 Mv.

Maximum undistorted power output 4.5 Watts.




Fig. 8.—Tube Position. 6-M-90S, 6-M-90D




Fig. 9.—Circuit Diagram. Models 6-M-91S and 6-M-91D (Chassis No. 5631)

SOCKET VOLTAGES 6-M-91S, 6-M-91D

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R.F. Amp.	0	5.8	215	100	5.7	—	0	5.7	0
6A8	1st Det. Osc.	0	0	215	100	—26	.150	5.8	5.9	0
6K7	I. F. Amp.	0	5.8	225	100	5.4	—	0	5.4	0
6Q7	2nd Det. A. V. C. 1st Audio	0	5.8	150	—2	—2	—	0	2	0
6F6	Power	0	0	210	220	—3	—	5.8	0	—
6X5	RECT.	0	5.8	AC	—	AC	—	0	220	—




Fig. 10

Voltage at Battery 6V.

Voltage at Switch 5.8V.

All voltages measured with 1000 ohms per volt D. C. meter.

Total current consumption 6.5 Amperes.

Sensitivity at one watt output 1.5 Mv.

Maximum undistorted power output 4.5 Watts.




Fig. 11.—Tube Position. 6-M-91S, 6-M-91D




Fig. 12.—Circuit Diagram, Models 7-M-91S and 7-M-91D. (Chassis No. 5706)

ZENITH
AUTO RADIO
MODEL 7M91 CHASSIS 5706
ZENITH RADIO CORPORATION
CHICAGO, ILL.

I.F. FREQUENCY 252K.C.

Headset, Ceiling & Firemill
Speaker Assemblies

Part No. 5-1242
5-1243
5-1244
5-1245
5-1246

EXTERNAL FIREMILL
SPEAKER PLUG

SWITCH ON
VOLUME CONTROL

SOCKET VOLTAGES 7-M-91S, 7-M-91D

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R.F. Amp.	0	5.8	250	100	5.2	—	0	5.2	0
6A8	1st Det. Osc.	0	0	250	100	—23	165	5.8	5.2	0
6K7	I. F. Amp.	0	5.8	240	100	6.7	—	0	6.7	0
6Q7	2nd Det. A. V. C. 1st Audio	0	0	145	—2	—2	—	5.8	1.6	0
6C5	Driver	0	0	240	0	0	—	5.8	8.2	—
6N7	Class B Power	0	0	250	0	0	250	5.8	0	—
6X5	RECT.	0	0	AC	—	AC	—	5.8	250	—




Fig. 13

Voltage at Battery 6V.

Voltage at Switch 5.8V.


Antenna disconnected.

All voltages measured with 1000 ohms per volt D. C. meter.

Total current consumption 8.2 Amperes.

Sensitivity at one watt output 1Mv.

Maximum power output 9 watts at 6 volts.



ALIGNMENT

Every Zenith receiver is balanced, and the sensitivity measured on accurate crystal controlled signal generators before leaving the factory, and unless a part is changed, or the receiver otherwise altered, the adjustment should not be tampered with.

When alignment is thus required, an accurately calibrated service oscillator and output meter are essential.

The proper procedure is as follows:

MODEL 5M90

"A" Connect the service oscillator output leads to the control grid of the 6A7 tube, and to the chassis. If the oscillator output is a single shielded lead the shield should connect to the chassis.

Connect the output meter across the primary of the speaker transformer.

Set the service oscillator at 456 K.C., and adjust the trimmers on the I F transformers to the point giving the greatest reading on the output meter. These, as well as the following adjustments should be made using as small an output from the signal generator as possible so that the A.V.C. action will be least effective.

"B" Change the service oscillator connection from the grid of the 6A7 to the antenna wire, leaving the other lead attached to the chassis.

Set the service oscillator at 1600 K.C. and rotate the gang condenser until the plates are entirely out of mesh. Adjust the oscillator section trimmer until the 1600 K.C. signal is tuned in.

Change the service oscillator to 1400 K.C. Rotate the gang condenser until this signal is tuned in, and then adjust the ANTENNA trimmer on the gang condenser to the point given the greatest output reading.

"C" Set the service oscillator to 600 K.C., and rock the gang condenser slowly to and fro past the point where this signal is received, meanwhile adjusting the padder condenser for a setting which gives the greatest output reading.

"D" Repeat operation "B".

"E" Reset the service oscillator to 456 K.C., leaving it connected to antenna, and adjust the wave trap trimmer to the point giving the MINIMUM output reading.

MODELS 6-M-90, 6-M-91, 6-M-92

"A" Connect the service oscillator to the control grid of the 6A8 tube and the chassis.

Connect the output meter across the primary of the speaker transformer.

Set the service oscillator to 252.5 K.C., and adjust the trimmers on the I. F. transformers for the greatest output reading. These adjustments should be repeated several times using as weak an input signal as possible so as to obtain greater accuracy.

"B" Change the service oscillator lead from the grid of the 6A8 to the antenna connection. A male Delco Remy connector may be used in making a connection to the antenna lead.

Set the service oscillator at 1400 K.C.

Rotate the gang condenser one and one fourth turns from the minimum setting. At the proper position eight teeth on the tuning gear will be visible past the gear bracket.

Adjust the oscillator, R.F. and antenna trimmers in that order to the point giving the greatest output.

"C" Set the service oscillator at 600 K.C. and rotate the gang condenser to tune in this signal. Move the gang condenser to and fro past the signal meanwhile adjusting the oscillator padder condenser until the combination of adjustments giving the greatest reading of the output meter is obtained.

"D" Repeat operation "B."

MODEL 7-M-91

The alignment of this receiver is identical with Model 6M90.

The sensitivity switch should be in the clockwise or sensitive position during adjustment. The output meter may be connected across the voice coil connections at the speaker socket.

IGNITION INTERFERENCE SUPPRESSION

All automobiles develop high frequency disturbance through radiation from the coil, distributor and plugs and it is necessary to minimize this interference by means of suppression. A suppressor is placed in the center distributor lead and, if necessary, on each spark plug. By-pass condensers must be used on the generator, coil and at all electrical gauges and the leads kept as short as possible. Each car, however, presents an individual problem where the technician must use some ingenuity, carefully following instructions.

Apply the standard suppression parts furnished with the receiver. This consists of a resistor for the distributor in addition to a coil condenser and a generator condenser. Lay all high tension leads close to the motor to lessen the possibility of radiation. Be sure the coil condenser is connected from the BATTERY side to ground. The points will become burned and pitted if placed on the coil side. Apply additional condensers to oil, water, gas or other electrical gauges. Carefully shield the aerial lead-in to the receiver, from the running board or the wind-shield post, with large loom and copper shielding. The capacity here **MUST** be as low as possible. The lead-in shield is grounded at the outer edge of the running board or at a point on the frame as close as possible to the lead-in post if a top antenna is used. Bond the instrument panel thoroughly to the car frame and body on each side.

After the hood is clamped in place to prevent radiation, the receiver should be turned on and dial tuned off a station with the volume control at maximum.

If motor noise is prevalent determine whether it is being conducted through the chassis or from the antenna. This test is made by disconnecting the antenna and grounding it to the shield. If ignition noise is heard upon again starting the motor it indicates chassis pickup which may be removed as follows:

Check distributor points and clean. Set to between .013" minimum and .015" maximum clearance. Next build-up the distributor rotor arm to a clearance of between .002" to .004" clearance to the distributor cap contacts. Solder may be used for this purpose, but it will eventually burn off and the noise will return. In the event low tension leads are bunched or in the same pipe housing with high tension leads, they should be separated as far as possible or removed from the same pipe. Removal and segregation is very effective. In some cases it might be necessary to shield and bond the low tension coil or distributor leads.

Motors mounted on rubber must be bonded with heavy braid to produce a short path to ground in order to break any radiating oscillatory circuit. Such bonds should be placed between the front motor support and frame and between the radiator top hose pipe and to the cylinder head where the water jacket is bolted. Move control cables slightly so that inner shaft contacts outer armour and tape in position under instrument panel.

When chassis pickup has been reduced to a minimum the antenna is then re-connected. Be sure the lead-in shield is grounded as previously mentioned.

Where a running board antenna is used it must be installed under the board farthest from the distributor and high tension system. If a top antenna is used it is usually necessary to by-pass the dome light lead. This should be done as close as possible to the windshield post through which it is wired. It will **NOT** help remove noise from this source if connected at any distance from the post. Another method is to break the dome lead and install an auxiliary switch at this point. In that case the condenser is not necessary. In many cases a condenser from one side of the ammeter to ground is very effective. Be sure to keep the radio battery cable out of the motor compartment. Running this cable through the motor side may cause severe interference.

The suggestions given need not all be necessary for a satisfactory installation. Therefore, they should be followed in order until the most effective remedy has been found. In any event, these rules should prove helpful in all cases. Spark plug suppressors are not required or furnished due to the added filtering incorporated in the 1936 Receiver. They should be applied only in extremely stubborn cases as a last resort after all bonding and filtering instructions have been followed.

PARTS LIST

R.F. Coils, Chokes & I.F. Transformers

PART NO.		5M 90	6M 90	6M 91	6M 92	7M 91	PRICE
20-103	Filament Choke	*	*	*	*	*	.15
20-106	Oscillator Coil	*					.50
20-107	Antenna Choke	*					.25
20-110	Motor Noise Filter Coil Only	*					.25
20-128	R.F. Coil		*	*	*	*	1.00
20-129	Antenna Coil		*	*	*	*	1.25
20-130	Oscillator Coil		*	*	*	*	.65
20-132	Antenna Coil Assembly				*	*	.75
95-275	2nd I.F. Transformer	*					1.25
95-337	1st I.F. Transformer				*	*	1.25
95-338	2nd I.F. Transformer				*	*	1.25
95-342	1st I.F. Transformer (95-331)		*	*	*	*	1.25
95-343	2nd I.F. Transformer (95-332)		*	*	*	*	1.25
S-2778	R.F. Choke	*	*	*	*	*	.15
S-3609	1st I.F. Transformer Assembly	*					1.35
S-3622	Antenna Coil Assembly (20-105)	*					2.00
S-4248	Filament Choke		*	*	*	*	.35
S-4283	Oscillator Coil and Wire Assembly				*	*	.60

Condensers—By Pass, Fixed, Variable & Electrolytic

22-82	.001 mfd. 600 Volt	*	*	*	*	*	.25
22-147	.0005 mfd. 600 Volt	*					.15
22-162	.0001 mfd. 600 Volt	*	*	*	*	*	.20
22-170	.1 mfd. 400 Volt	*	*	*	*	*	.15
22-182	.00025 mfd. 600 Volt	*	*	*	*	*	.12
22-185	.01 mfd. 200 Volt	*	*	*	*	*	.20
22-190	.1 mfd. 200 Volt	*	*	*	*	*	.20
22-193	.5 mfd. Ignition Coil Condenser	*	*	*	*	*	.45
22-194	.5 mfd. Generator Coil Condenser	*	*	*	*	*	.50
22-196	.01 mfd. 600 Volt	*	*	*	*	*	.15
22-212	.05 mfd. 400 Volt	*	*	*	*	*	.20
22-219	.03 mfd. 200 Volt	*	*	*	*	*	.15
22-224	.1 mfd. 300 Volt	*	*	*	*	*	.15
22-250	.05 mfd. 200 Volt	*	*	*	*	*	.15
22-251	.5 mfd. 200 Volt	*					.40
22-280	.5 mfd. 200 Volt	*					.25
22-327	.02 mfd. 200 Volt	*	*	*	*	*	.15
22-350	.25 mfd. 200 Volt	*	*	*	*	*	.20
22-354	.007 mfd. 800 Volt	*					.20
22-355	.01 mfd. 1400 Volt	*					.20
22-358	.002 mfd. 600 Volt	*					.20
22-388	4-8 mfd. 350 Volt Electrolytic	*					1.50
22-389	365 mmfd. 2 gang Variable	*					4.00
22-390	200-400 mmfd. Oscillator Padder	*					.40
22-391	1000-1950 mmfd. Padder	*					.75
22-393	.00025 mfd. 600 Volt	*					.12
22-413	.006 mfd. 600 Volt	*					.15
22-456	365 mmfd. 3 gang Variable	*	*	*	*	*	4.00
22-461	.05 mfd. 800 Volt	*	*	*	*	*	.25
22-462	.004 mfd. 750 Volt	*	*	*	*	*	.15
22-463	200-750 mmfd. Padder	*	*	*	*	*	.35
22-464	8-8 mfd. 350 Volt Electrolytic	*	*	*	*	*	2.00
22-465	.25 mfd. 400 Volt	*	*	*	*	*	.30
22-466	.5 mfd. 200 Volt	*	*	*	*	*	.30
22-467	.2 mfd. 200 Volt	*	*	*	*	*	.20
22-468	.5 mfd. 200 Volt	*	*	*	*	*	.30
22-469	8-8 mfd. 350 Volt 20 mfd. 20 Volt	*	*	*	*	*	2.75
22-470	.00015 mfd. 600 Volt	*	*	*	*	*	.20
22-471	.008 mfd. 1400 Volt	*	*	*	*	*	.20
22-472	.0013 mfd. 600 Volt	*	*	*	*	*	.20
22-473	.5 mfd. 200 Volt	*	*	*	*	*	.25
22-474	4-8 mfd. 300 Volt	*	*	*	*	*	1.50
22-476	.0035 mfd. 750 Volt	*	*	*	*	*	.15
22-477	Dual 250 mmfd. 600 Volt	*	*	*	*	*	.15

Resistors, Voltage Dividers and Variable Controls

PART NO.		5M 90	6M 90	6M 91	6M 92	7M 91	PRICE
63-260	100 M ohm 1/4 watt	*					.20
63-263	30 M ohm 1/2 watt	*					.20
63-271	1 megohm 1/4 watt	*					.20
63-288	19 M ohm 1/4 watt	*					.20
63-336	Distributor Suppressor	*	*	*	*	*	.35
63-357	300 ohm 1/4 watt	*					.20
63-394	200 ohm 1/2 watt	*					.20
63-400	250 M ohm 1/4 watt	*					.20
63-401	500 M ohm 1/4 watt	*					.20
63-410	1200 ohm 1/4 watt	*					.20
63-422	200 ohm 1/2 watt	*	*	*	*	*	.20
63-423	600 ohm 1/4 watt	*	*	*	*	*	.20
63-425	75 M ohm 1/4 watt	*					.20
63-426	250 M ohm 1/4 watt	*	*	*	*	*	.20
63-428	1200 ohm 1/4 watt	*	*	*	*	*	.20
63-429	Spark Plug Suppressor (Optional)	*					.30
63-433	250 ohm 1/4 watt, 24 M ohm 1/2 watt, 15 M ohm 1 1/2 watt	*					.65
63-434	500 M ohm Volume Control	*					1.00
63-436	750 M ohm 1/4 watt	*					.20
63-443	300 ohm 1/4 watt	*	*	*	*	*	.20
63-446	750 M ohm 1/4 watt	*	*	*	*	*	.20
63-464	1 megohm 1/4 watt	*	*	*	*	*	.20
63-485	500 M ohm Volume Control	*	*	*	*	*	1.00
63-487	100 M ohm Tone Cont. (In Cont. Head)	*	*	*	*	*	.75
63-490	49 M ohm 1/4 watt	*	*	*	*	*	.20
63-491	490 M ohm 1/4 watt	*	*	*	*	*	.20
63-493	50 M ohm 1/4 watt	*	*	*	*	*	.20
63-494	13 M ohm 2 watt	*	*	*	*	*	.25
63-495	850 ohm 1/4 watt	*	*	*	*	*	.20
63-497	25 M ohm 1/4 watt	*	*	*	*	*	.20
63-502	300 M ohm 1/4 watt	*					.20
63-503	15 M ohm 1/4 watt	*					.20
63-504	550 ohm 1/4 watt	*					.20
63-506	1500 ohm 1/4 watt	*					.20
63-507	500 M ohm Volume Control	*					1.25
63-508	2900 ohm 1/4 watt	*					.20
63-509	90 M ohm 1/4 watt	*					.20
63-510	18 M ohm 2 watt	*					.25
63-512	19 M ohm 1 watt	*	*	*	*	*	.20
63-514	200 M ohm Volume Control and Switch	*					1.25

Speakers and Speaker Parts

49-111	6" Dynamic Speaker with Output Transf.	*					5.00
	Cone & Voice Coil for 49-111	*					2.30
	Output Transformer for 49-111	*					2.00
	Field Coil for 49-111	*					2.00
49-136	6" Dynamic Speaker with Output Transf.	*					5.00
	Cone and Voice Coil for 49-136	*					2.30
	Output Transformer for 49-136	*					2.00
	Field Coil for 49-136	*					2.00
49-137	8" Dynamic Speaker	*	*	*	*	*	6.00
	Cone & Voice Coil for 49-137	*	*	*	*	*	2.50
	Field Coil for 49-137	*	*	*	*	*	2.00
	(Output Transformer in set)						
49-138	5 3/8" Dynamic Speaker with Output Transf.	*					4.00
	Cone & Voice Coil for 49-138	*					1.75
	Field Coil for 49-138	*					2.00
	Output Transformer for 49-138	*					1.50
49-139	5 1/4" Dynamic Speaker	*	*	*	*	*	4.00
	Cone & Voice Coil for 49-139	*	*	*	*	*	1.75
	Field Coil for 49-139	*	*	*	*	*	2.00
	(Output Transformer in Set)						

PARTS LIST (Cont'd)

PART NO.		5M 90	6M 90	6M 91	6M 92	7M 91	PRICE
49-140	5 1/4" Dynamic Speaker (Uses same replacement parts as 49-139)	*	*	*	*	*	4.00
52-83	Speaker Cable for S-4169 (49-137)	*	*	*	*	*	1.00
52-84	Speaker Cable for S-4242 (49-140) S-4244, S-4245, S-4243 (49-139)	*	*	*	*	*	1.00
S-4169	Firewall Speaker Assembly (Uses Speaker 49-137)	*	*	*	*	*	
S-4242	1936 Ford Header Assembly (Uses Speaker 49-140)	*	*	*	*	*	
S-4243	General Motors Ceiling Assembly (Uses Speaker 49-139)	*	*	*	*	*	
S-4244	Dodge, Plymouth & 1935 Ford Header Assembly (Uses Speaker 49-139)	*	*	*	*	*	
S-4245	Nash & Studebaker Header Assembly (Uses Speaker 49-139)	*	*	*	*	*	
IMPORTANT! When ordering speaker parts always give the entire part and code number i.e., 49-138AB or 49-138U							

Sockets—Tube & Speaker—Plugs

58-36	Speaker Socket Plug	*	*	*	*	*	.15
58-37	Speaker Socket Plug					*	.15
78-100	Wafer Socket for 6D6 Tube	*					.10
78-101	Wafer Socket for No. 75 Tube	*					.10
78-106	Wafer Socket for 6A7 Tube	*					.10
78-114	Wafer Socket for 6Z4 Tube	*					.10
78-115	Wafer Socket for Vibrator	*	*	*	*	*	.10
78-126	Wafer Socket for 41 Tube	*					.10
78-148	Wafer Socket for 6Q7 Tube	*	*	*	*	*	.10
78-149	Wafer Socket for 6X5 Tube	*	*	*	*	*	.10
78-150	Wafer Socket for 6K7 Tube	*	*	*	*	*	.10
78-151	Wafer Socket for 6A8 Tube	*	*	*	*	*	.10
78-152	Wafer Socket for 6F6 Tube	*	*	*	*	*	.10
78-153	Speaker Plug Socket	*	*	*	*	*	.10
78-154	Speaker Plug Socket					*	.10
78-156	Wafer Socket for 6C5 Tube					*	.10
78-157	Wafer Socket for 6N7 Tube					*	.10

Transformers—Audio & Power

95-273	Power Transformer	*					2.00
95-276	Hum Filter Choke	*					.60
95-328	Power Transformer	*	*				2.25
95-330	Hum Filter Choke	*	*				.75
95-333	Speaker Transformer	*	*				1.50
95-334	Power Transformer					*	2.75
95-335	Hum Filter Choke	*	*				.75
95-336	Audio & Speaker Output Transformer	*	*				3.50
95-341	Power Choke	*					.75
95-344	Power Transformer	*					2.25

CONTROL HEADS

Zenith Safety Control Head

MS-295	Complete Safety Steering Column Control with Cables	*	*	*			12.50
7-9	Dial Glass Gezel (Chromium Plate)	*	*	*			.35
15-19	Steering Column Mtg. Cap	*	*	*			.25
24-107	Steering Col. Mtg. Cover (Upper Half)	*	*	*			1.50
24-108	Steering Col. Mtg. Cover (Lower Half)	*	*	*			1.50
26-112	Celluloid Dial Scale	*	*	*			.50
27-11	Celluloid Pointer Disc	*	*	*			.50
34-55	Celluloid Pointer Gear	*	*	*			.15
34-58	Tuning Control Pinion Gear (15 Teeth)	*	*	*			.15
34-59	Tone Control Gear	*	*	*			.10
46-145	Tuning & Volume Control Knobs	*	*	*			.20

PART NO.		5M 90	6M 90	6M 91	6M 92	7M 91	PRICE
46-146	Pilot Light & Tone Control Knobs	*	*	*			.20
52-78	Pilot Light & Tone Control Cable	*	*	*			.65
54-90	Shaft Sheath Clamping Nut	*	*	*			.05
54-95	Panel Clamping Nut	*	*	*			.08
63-487	100 M ohm Tone Control	*	*	*			.75
69-47	6/32 x 5/8" R.H.M.S. Case Holding Screws per C.	*	*	*			.20
69-123	Contact Screw for Pilot Light	*	*	*			.01
73-2	Control Knob Set Screw	*	*	*			.01
73-25	10/32 x 5/16" Clamp Cap Set Screw	*	*	*			.03
76-192	Tone Control Pinion Shaft and Gear	*	*	*			.40
76-194	Volume Control Knob Shaft	*	*	*			.10
80-122	Tuning Control Head Shaft Spring	*	*	*			.03
80-123	Pilot Light Switch Contact Spring	*	*	*			.10
94-216	Black Fibre Clamp Bushing (Halves)	*	*	*			.15
100-32	Pilot Light Bulb	*	*	*			.15
115-12	10/32 x 1/2" Clamp Fastening Bolts per C.	*	*	*			.40
192-13	Unbreakable Dial Glass	*	*	*			.15
S-4194	Idler Gears & Washer Assembly	*	*	*			.35

Skeleton Control Head for Panel Mtg. Only For Models 6M90, 6M91 and 7M91

(S-4220)

S-4220	Skeleton Head Only for 6M90, 6M91 & 7M91 (Dash) (Inc. Cables)	*	*	*			8.50
S-4219	Tone Control & Shaft Assembly	*	*	*			1.25
26-114	Calibrated Dial Scale	*	*	*			.20
27-12	Dial Pointer Disc	*	*	*			.10
46-150	Tone Control Knob	*	*	*			.15
52-82	Pilot Light & Tone Control Cable	*	*	*			.75
54-101	Cable Sheath Clamping Nuts	*	*	*			.05
54-102	3/8 - 32 x 1/2" Hex Nut per C.	*	*	*			.50
93-143	3/8" Shakeproof Washer per C.	*	*	*			.35
100-32	Pilot Light Bulb	*	*	*			.15
147-28	Tuning Control Knob Spacer	*	*	*			.15
170-18	Remote Control Drive Mechanism	*	*	*			2.75

Skeleton Control Head for Panel and Steering Column Mtg., Model 6M92 Only (S-4224)

S-4224	Skeleton Head for 6M92 Steering & Dash Mtg. (Inc. Cables)	*					7.00
S-4249	Volume Control Shaft & Bushing Assem.	*					.30
26-114	Calibrated Dial Scale	*					.20
27-12	Dial Pointer Disc	*					.10
52-81	Pilot Light Cable	*					.50
54-101	Cable Sheath Clamping Nuts	*					.05
100-32	Pilot Light Bulb	*					.15
170-18	Control Drive Mechanism	*					2.75

Steering Column Mounting Accessory Kit

(To be used with S-4224 Only)

(S-4250)

S-4250	Steering Column Mtg. Accessory Kit (Use with S-4224)	*					1.50
12-459	Mounting Bracket	*					.05
12-469	Mounting Bracket (Steering Column)	*					.05
17-38	Retaining Clamp (Steering Column)	*					.05
43-11	Control Mechanism Housing	*					.50
46-160	Tuning & Volume Control Knob - Black	*					.25
54-106	No. 10/32 x 3/8" Hex Nuts Parkerized	*					.01
69-4	No. 6/32 x 3/16" R.H.M.S. N.P.	*					.01
69-124	No. 8/32 x 7/8" R.H.M.S. Parkerized	*					.01
69-125	No. 10/32 x 5/16" R.H.M.S. Parkerized	*					.01
93-126	No. 8 Shakeproof Lockwashers	*					.01
93-127	No. 10 Shakeproof Lockwashers	*					.01

PARTS LIST (Cont'd)

PART NO.		5M	6M	6M	6M	7M	PRICE
		90	90	91	92	91	
93-312	.010" Shim Washers	*					.01
112-108	No. 3/48 x 7/32" B.H.M.S. Black Nickel Finish	*					.01
192-14	Unbreakable Dial Glass	*					.20

5M90 Remote Control Steering Column Head

170-15	Zenith Remote Control Unit with Knobs, Mtg. Bracket and Pilot Lamp Cable less Shafts	*					4.50
12-423	Comp. Steer. Mounting Bracket Assem.	*					.60
17-29	Mounting Clamp only	*					.35
83-395	Mounting Strip only	*					.20
93-183	1/4" Shakeproof Washer only	*					.01
112-85	Mtg. Clamp Screws (small)	*					.03
112-86	Mtg. Clamp Screws (large)	*					.05
26-90	Dial Scale and Cup Assembly	*					.30
46-121	Volume and Tuning Knobs	*					.20
73-21	Headless Set Screw for 46-121	*					.02
80-110	Tension Springs for 46-121	*					.01
52-72	Dial Lamp Cable Assembly	*					.30
59-37	Dial Pointer	*					.10
100-29	6-8 V. Dial Lamp	*					.15
112-83	Set Screw for Volume Control Coupling Housing	*					.01
112-84	Set Screw for Tuning Control Coupling Housing	*					.01
192-9	Dial Glass	*					.12
196-3	Dial Glass Gasket	*					.03

Control Cables

(5 TUBE SET)

76-171	18" Tuning Control Cable	1.00
76-174	18" Volume Control Cable	1.00
76-172	24" Tuning Control Cable	1.25
76-175	24" Volume Control Cable	1.25
76-173	30" Tuning Control Cable	1.50
76-176	30" Volume Control Cable	1.50

(6 & 7 TUBE SET)

76-200	18" Volume Control Cable (Safety Steering Head) (Black Large Type)	1.00
76-203	18" Tuning Control Cable (Safety Steering Head) (Black Large Type)	1.00
76-201	24" Volume Control Cable (Safety Steering Head) (Black Large Type)	1.25
76-202	30" Volume Control Cable (Safety Steering Head) (Black Large Type)	1.50
76-204	24" Tuning Control Cable (Safety Steering Head) (Black Large Type)	1.25
76-205	30" Tuning Control Cable (Safety Steering Head) (Black Large Type)	1.50
76-206	18" Volume Control Cable (Dash Head) (Grey Small Type)	1.00
76-207	24" Volume Control Cable (Dash Head) (Grey Small Type)	1.25
76-208	18" Tuning Control Cable (Dash Head) (Grey Small Type)	1.00
76-209	24" Tuning Control Cable (Dash Head) (Grey Small Type)	1.25
76-213	30" Volume Control Cable (Dash Head) (Grey Small Type)	1.50
76-214	30" Tuning Control Cable (Dash Head) (Grey Small Type)	1.50
76-217	36" Volume Control Cable (Dash Head) (Grey Small Type)	1.75
76-218	36" Tuning Cable (Dash Head) (Grey Small Type)	1.75

Auto Set Mounting Parts

PART NO.		5M	6M	6M	6M	7M	PRICE
		90	90	91	92	91	
52-44	A Battery Cable	*	*	*	*	*	.60
57-478	Set Mounting Plate	*	*	*	*	*	.25
58-21	D.R. Cap	*	*	*	*	*	.01
58-26	D.R. Fuse Bushing	*	*	*	*	*	.01
69-84	10/32 x 1/4" R.H.M. Screws per C.	*	*	*	*	*	.30
93-127	No. 10 Shakeproof Lockwashers per C.	*	*	*	*	*	.35
93-222	7/16 Internal Shakeproof Washer	*	*	*	*	*	.01
93-233	Set Mounting Bolt Washer	*	*	*	*	*	.02
93-300	White Felt Washer	*	*	*	*	*	.02
136-6	15 Amp Fuse	*	*	*	*	*	.06
136-9	20 Amp Fuse	*	*	*	*	*	.06
144-14	7/16 x 3" Carriage Bolt & Nut	*	*	*	*	*	.05
196-1	Mounting Plate Gasket	*	*	*	*	*	.03

Miscellaneous Chassis Parts

19-51	Goat Tube Shield Clips	*	*	*	*	*	.03
19-53	Chassis Box Top Cover Spring Clips	*	*	*	*	*	.02
44-12	Pilot Light & Tone Control Cable Jack	*	*	*	*	*	.10
44-13	Pilot Light Cable Jack	*	*	*	*	*	.10
46-147	Sensitivity Control Knob	*	*	*	*	*	.25
80-107	Spring for 46-147 Knob	*	*	*	*	*	.01
52-44	A Battery Cable with Fuse Receptacle	*	*	*	*	*	.60
52-59	Antenna Shielded Loom	*	*	*	*	*	.50
52-66	A Battery Cable Lead on Chassis	*	*	*	*	*	.25
52-79	Antenna Cable	*	*	*	*	*	.45
52-80	Battery Cable	*	*	*	*	*	.25
54-76	1/4 - 20 Knurled Coupling Shaft Nuts	*	*	*	*	*	.08
54-97	Flexible Shaft Coupling Nuts	*	*	*	*	*	.08
85-87	Sensitivity Switch	*	*	*	*	*	.40
80-120	Vibrator Retainer Spring	*	*	*	*	*	.06
93-220	Bakelite Washer for Chassis Mtg. Screws	*	*	*	*	*	.02
93-278	Rubber Shoulder Washers for Variable Cond. Mtg.	*	*	*	*	*	.02
93-279	11/32" x 1/4" x 3/4" Rubber Washers for Variable Cond. Mtg.	*	*	*	*	*	.02
94-185	Rubber Bushings for Chassis Mtg. Screws	*	*	*	*	*	.02
97-75	10/32 x 1/4" Wing Screw for Top Cover	*	*	*	*	*	.02
97-76	Wing Screw for Ground Connections	*	*	*	*	*	.02
112-69	Chassis Mtg. Screws	*	*	*	*	*	.02
112-100	Chassis Mtg. Screws	*	*	*	*	*	.01
112-102	10/32 x 1/4" Thumb Screws	*	*	*	*	*	.02
114-27	No. 8 x 1/4" Black Screws for Bottom Cover	*	*	*	*	*	.01
114-36	No. 8 x 1/4" H.H. Slotted Self Tapping Screws for Bottom Cover	*	*	*	*	*	.005
126-131	Tube Shields Complete with ring (Large)	*	*	*	*	*	.10
126-168	Tube Shields Complete with ring (Small)	*	*	*	*	*	.10
183-2	Rubber Bands for Tube Shields	*	*	*	*	*	.02
190-4	Vibrator	*	*	*	*	*	5.00
190-7	Vibrator	*	*	*	*	*	3.75
S-3603	Motor Noise Filter Assem. Comp. with Case & A Batt. Lead	*	*	*	*	*	1.50
S-4185	Motor Noise Rejection Coil Assem. Comp. with Case & Ant. Cable	*	*	*	*	*	1.50

These Prices Supersede All Previous Quotations and Are Subject to Regular Discounts and Change Without Notice.

Zenith Radio Corporation
CHICAGO, ILL.

4-6-36

SERVICE MANUAL




1937 RECEIVERS

MODELS

4-B-106	6-D-117	7-D-162
4-B-131	6-D-118	7-D-168
4-B-132	6-S-128	8-S-129
5-S-119	6-S-137	8-S-154
5-S-126	6-S-147	10-S-130
5-S-127	6-S-152	10-S-147
5-S-150	6-S-157	10-S-153
5-S-151	7-D-119	10-S-155
5-S-161	7-D-126	10-S-156
6-B-107	7-D-127	10-S-157
6-B-129	7-D-138	10-S-160
6-B-164	7-D-148	12-U-158
6-D-116	7-D-151	12-U-159

ZENITH RADIO CORPORATION

CHICAGO, U. S. A.



DIAG. PART NO.	DESCRIPTION	DIAG. PART NO.	DESCRIPTION
C1	22-82 .001 MFD 600V	R13	63-260 100M OHMS 1/4W
C2	22-205 200-550MMFD PAPER		
C3	22-182 .00025 MFD 600V		
C4	22-185 .01 MFD 200V		
C5	22-199 .5 " 200V		
C6	22-212 .05 " 400V		
C7	22-225 .5 MFD ELTLYTIC 25V		
C8	22-243 .01 " 400V		
C9	22-250 .05 " 200V		
C10	22-455 .01 " 1200V		
C11	22-358 .002 " 600V		
C12	22-419 (2 MFD 250V		
C13	22-426 (2 MFD 250V		
C14	22-426 (2 MFD 250V		

DIAG. PART NO.	DESCRIPTION	DIAG. PART NO.	DESCRIPTION
R1	63-238 1M OHMS 1/4W	SPEAKER	MODELS
R2	63-499 9M " 1/4W	49-153	6" P.M. (4-B-131
R3	63-258 490M " 1/4W	49-159	6" P.M. (4-B-132
R4	63-281 29M " 1/4W		
R5	63-293 990M " 1/4W		
R6	63-303 700 " 1/4W		
R7	63-357 300 " 1/4W		
R8	63-394 200 " 1/2W		
R9	63-418 1500 " 1/2W		
R10	63-534 400M " VOL. CONTROL		
R11	63-469 100M " TONE "		
R12	63-536 30 " WIRE WOUND		

4TUBE BATTERY SUPERHETERODYNE
I.F. FREQUENCY 456 K.C.
CHASSIS No 5406

TUNING RANGE 550-1700 K.C.

ZENITH RADIO CORP.
CHICAGO, ILL.

MODELS

4-B-106, 4-B-131, 4-B-132

CHASSIS No. 5406

SOCKET VOLTAGES

Tube	Position	Ef	Ek	Eg ¹	Eg ²	Eg ³	Ep
15	1st Def. Osc.	2	8	0	115	—	155
15	I. F.	2	3.5	0	115	—	155
75	2nd Def. A.V.C.	6	1.5	0	—	—	30
38	PWR	6	14	0	155	—	148

f—filament; k—cathode; g¹—control grid; g²—screen grid; g³—suppressor grid; p—plate.


All measurements taken from point indicated to ground using a 1000 ohm per volt D. C. meter with antenna and ground disconnected.

Battery Voltage 6V.

Battery Drain 1.7 amperes.

Power Output 1 watt.

Alignment procedure on page 24.



TUBE POSITION

CAUTION: Reversal of the battery polarity will damage the filter condensers. The storage battery must be connected as shown above.

I.F. FREQUENCY 456 K.C.
6 TUBE BATTERY SUPERHETERODYNE
CHASSIS No 5635

**ZENITH RADIO CORPORATION
CHICAGO, ILL.**

CIRCUIT DIAGRAM — Models 6-B-107, 6-B-129, 6-B-164. (Chassis No. 5635)

MODELS

6-B-107, 6-B-129, 6-B-164

CHASSIS No. 5635

SOCKET VOLTAGES

Tube	Position	Ef	Eg	Eg ¹	Eg ²	Eg ³	Ep
15	R. F.	2	1.5	0	65	—	115
6A7	Det. Osc.	6	2.5	0	75	—	115
15	I. F.	2	3.5	0	75	—	130
75	2nd Det. A.V.C.	6	1.2	0	—	—	35
76	1st Audio	6	6		—	—	125

f—filament; k—cathode; g¹—control grid; g²—screen grid; g³—suppressor grid; p—plate.


All voltages measured from socket contacts to ground with 1000 ohm per volt D. C. meter. Antenna and ground disconnected.

Battery Voltage 6V.

Battery Drain 2.2 amperes.

Power Output 2 watts.

Alignment procedure on page 27.



TUBE POSITION

CAUTION: Reversal of the battery polarity will damage the filter condensers. The storage battery must be connected as shown above.

NOTE: See bottom page 18 for details of antenna connector strip.


MODELS

5-S-119, 5-S-126, 5-S-127, 5-S-150, 5-S-151, 5-S-161

CHASSIS No. 5516

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	1st Det. Osc.	0	0	240	85	-1	166	6ac	4	0
6K7	I. F.	0	0	240	85	3	—	6ac	3	0
6Q7	2nd Det. A.V.C.	0	0	75	.1	.1	—	6ac	1.5	0
6F6	Power	0	0	230	240	-5	—	6ac	0	—
5Y3 5W4	Rectifier	0	240	—	AC	—	AC	—	240	—



**BOTTOM VIEW
OF SOCKET**


All voltages measured from point indicated to ground, using a 1000 ohm per volt meter with antenna and ground disconnected.

Line Voltage 112V.

Current Consumption 55 watts.

Power Output 3 watts.

Alignment Procedure on page 26.



TUBE POSITION

NOTE: See bottom page 18 for details of antenna connector strip.

I.F. FREQUENCY 456 K.C.
6 TUBE SUPERHETRODYNE
CHASSIS No. 5633 AC-DC
MODELS 6D-116, 6D-117, 6D-118
ZENITH RADIO CORPORATION
CHICAGO, ILL.

DWG. PART No. No.	DESCRIPTION	DIAG. PART No. No.	DESCRIPTION
C1	22-182 .001MFD.	R6	63-452 650M OHMS 1/4W
C2	22-327 .02 "	R7	63-517 400M " VOL. CONTROL
C3	22-145 .01 "	R8	63-562 400M OHMS 1/4W
C4	22-478 2 GANG VARIABLE	R9	63-135 25 M " 1/4W
C5	22-500 .05 MFD.	R10	63-376 150M " 1/4W
C6	22-376 .0021 "	R11	63-290 260M " 1/4W
C7	22-205 200-.550MMFD. PROBE	R12	63-293 950M " 1/4W
C8	22-162 .0001 MFD.	R13	63-278 99 M " 1/4W
C9	22-182 .00025 MFD.		
C10	22-183 .02 "		
C11	22-193 .05 "		
C12	22-212 .05 "		
C13	22-229 .005 "		
C14	22-229 .005 "		
C15	22-455 .01 "		
C16	22-517 1/4 MFD. @		
C17	22-517 1/6 "		
C18	22-516 8 - @		
		1	5-4302 ANT. COIL ASSEMBLY
		2	5-4304 OSC. COIL ASSEMBLY
		3	95-346 1ST I.F. TRANS.
		4	95-347 2ND I.F. TRANS.
		5	85-88 BAND SELECT. SWITCH
		6	100-37 BALLAST TUBE 115V
		7	95-345 POWER CHOKES
		8	49-141 SPEAKER
R1	63-377 170 OHMS 1/4W		
R2	63-261 900M 1/4W		
R3	63-261 400M 1/4W		
R4	63-288 15M 1/4W		
R5	63-300 990 "		

CIRCUIT DIAGRAM—Models 6-D-116, 6-D-117, 6-D-118. (Chassis No. 5633)


MODELS

6-D-116, 6-D-117, 6-D-118

CHASSIS No. 5633

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	1st Det. Osc.	0	AC	100	50	-5	100	AC	1	-1
6K7	I. F.	0	AC	100	100	.5	—	AC	5	0
6Q7	2nd Det. A.V.C.	0	AC	50	0	0	—	AC	1	0
25A6	Power	0	AC	90	100	1	—	AC	0	—
25Z6	Rectifier	0	AC	AC	AC	100	—	AC	125	—
100-37	115 Volt Ballast	—	—	—	—	—	—	—	—	—



BOTTOM VIEW
OF SOCKET


All voltages measured from point indicated to ground, using a 1000 ohm per volt meter. Antenna and ground disconnected.

Line Voltage 112V. (A.C.)

Current Consumption 44 watts.


Power Output 1.5 watts.

Alignment procedure on page 25.



TUBE POSITION

CAUTION: Do not ground chassis while testing or during operation, otherwise filter choke will be short circuited.



CIRCUIT DIAGRAM—Models 7-D-119, 7-D-126, 7-D-127, 7-D-138, 7-D-151, 7-D-148, 7-D-162, 7-D-168. (Chassis No. 5707)


MODELS

**7-D-119, 7-D-126, 7-D-127, 7-D-138,
7-D-151, 7-D-148, 7-D-162, 7-D-168**

CHASSIS No. 5707

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	1st Det. Osc.	0	AC	125	80	20	100	AC	25	15
6K7	I. F.	0	AC	125	125	25	—	AC	.25	10
6H6	2nd Det. A.V.C.	0	AC	10	25	10	—	AC	25	—
6F5	1st Audio	0	AC	—	60	—	—	AC	25	5
25A6	Power	0	AC	110	125	1	—	AC	25	—
25Z6	Rectifier	0	0	AC	AC	105	—	AC	125	—
	Ballast	—	—	—	—	—	—	—	—	—



**BOTTOM VIEW
OF SOCKET**


Measured from point indicated to junction of filter choke and speaker field using a 1000 ohm per volt meter.

Line Voltage 112 (A.C.)

Current Consumption 44 watts.


Power Output 1.5 watts.

Alignment procedure on page 26.



TUBE POSITION

NOTE: See bottom page 18 for details of antenna connector strip.




MODELS

6-S-128, 6-S-137, 6-S-147, 6-S-152, 6-S-157

CHASSIS No. 5634

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	1st Det Osc.	0	6AC	280	80	-4	175	0	0	0
6K7	I F	0	6AC	280	80	0	—	0	Local 7	0
6H6	2nd Det A.V.C.	0	6AC	—2	—2	-2	—	0	—2	—
6F5	1st Audio	0	6AC	—	75	—	—	0	—2	—2
6F6	Power	0	6AC	260	280	-2	—	0	—2	—
5Y3 5W4	Rectifier	0	320	—	AC	—	AC	—	320	—



**BOTTOM VIEW
OF SOCKET**


All voltages measured from point indicated to ground, using a 1000 ohm per volt meter. Antenna and ground disconnected.

Line Voltage 112V.

Current Consumption 75 watts.


Power Output 4 watts.

Alignment procedure on page 26.



TUBE POSITION


NOTE: See bottom page 18 for details of antenna connector strip.



CIRCUIT DIAGRAM—Models 8-S-129, 8-S-154. (Chassis No. 5801)

MODELS **8-S-129, 8-S-154** CHASSIS No. 5801 **SOCKET VOLTAGES**

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	6AC	250	68	0	—	0	0	0
6A8	1st Det. Osc.	0	6AC	250	68	-4	150	0	0	0
6K7	I. F.	0	6AC	250	68	0	—	0	Local 5	0
6H6	2nd Det. A.V.C.	0	6AC	-3	-3	-3	—	0	-3	—
6F5	1st Audio	0	6AC	—	70	0	0	0	-3	-3
6F6	Power	0	6AC	235	250	-4	—	0	-4	—
6C5	Target Tuning Amp.	0	6AC	250	—	-5	—	0	4	—
5Y3 5W4	Rectifier	0	310	—	AC	—	AC	—	310	—




BOTTOM VIEW
OF SOCKET

All voltages measured from point indicated to ground, using a 1000 ohm per volt meter. Antenna and ground disconnected, Line Voltage 112V.

Current Consumption 85 watts.


Power Output 5 watts.

Alignment procedure on page 27.



TUBE POSITION

NOTE: See bottom page 18 for details of antenna connector strip.



SPEAKER	MODEL
49-146 8"	105130
	105155
49-147 12"	105156
	105160
	105147
49-156 12"	105153
	105157

I.F. FREQUENCY 456 KC.
10 TUBE SUPERHETERODYNE ~ 3 BAND
CHASSIS NO 1004

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS

SERVICE NOTES 1004 CHASSIS

FF SCALE AT LOW FREQUENCY END OF DIAL, UNABLE TO ADJUST BY REGULAR ALIGNMENT—Check 600 padder, broken lug, wire, etc. Also check .0012 condenser in oscillator plate circuit C-6 22-486.

ACK OF SENSITIVITY ON ALL BANDS—Check tubes, antenna and ground—all coils. Poor contact on sensitivity switch—rebalance.

ACK OF SENSITIVITY ON BROADCAST BAND—Open radio frequency plate choke.

LOISY—Tubes, check condenser bond wires to clear chassis; dirty gang condenser or wipers; loose lugs on candohm resistor; shorted bus bar wires in coil circuits; aerial and ground. Also loose connecting wire between G and Z on aerial strip.

LOISY ON "C" BAND ONLY IN SPOTS—Check dial pulley—move pulley away from dial pan; condenser bonds do not clear chassis hold. Poor contacts on any of the band, tone or sensitivity switches; defective volume control; defective 16 mmfd. condenser—22-506.

HUM—Tubes, oscillator tube shorted or output tubes not matched; open filter, electrostatic shield open in power transformer. This will give carrier hum and can be corrected by by-passing the A.C. line with .001 mica-condenser. Reverse A.C. plug.

TATIONS RIDE IN—Check balance; check .0012 condenser in oscillator plate circuit.

WEAK OR LACK VOLUME—Open 2nd detector cathode resistor or candohm; will also affect tone quality if open; .00025 condenser grounded in tone circuit, noticeable on high fidelity position of switch, with distortion. Repeak I.F.'s to 456 K.C. Defective tubes, in particular 1st and 2nd detector. Switch on normal and with lack volume—check tone switch for short circuit to foreign lug.

FLUTTERING AT LOW FREQUENCY—Tubes, particularly oscillator tube, rebalance I.F.'s to 456.

INTERMITTENT RECEPTION—Tubes, I.F. trimmers short; dirty variable condenser, poor ground at candohm; loose link wire across Z and G on aerial strip. Poor contact on band switch; defective aerial; defective by-pass condenser.

POOR ACTION OF TARGET TUNER—Note: Do not expect target to center exactly in the center of bull's eye except on very strong input signal. Check 6C5 tube or replace target unit.

DIAL SLIPS—Loose dial clutch.

IMPORTANT!



Connect ordinary single wire antenna to A with jumper wire placed between Z and G (shipped from factory in this manner.)

When using a ZENITH DOUBLET ANTENNA, remove jumper wire between Z and G and attach doublet lead-in to A and Z.


Although it is not usually necessary to ground the receiver, there may be occasional instances where a ground connection removes noise or may aid reception of signals. It should be tried and left connected if any improvement is noted. Where it does not help, or if it introduces hum, try reversing the wall plug or leave the ground lead off entirely.

MODELS **10-S-130, 10-S-155, 10-S-156, 10-S-160,** **10-S-147, 10-S-153, 10-S-157**

CHASSIS No. 1004

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	3AC	250	100	0	—	3AC	0	0
6A8	1st Det. Osc.	0	3AC	250	100	-6.5	175	3AC	0	0
6K7	I. F.	0	3AC	250	100	0	—	3AC	Local 9	0
6H6	2nd Det. A.V.C.	0	3AC	-2.5	.25	-2.5	—	3AC	-2.5	—
6C5	1st Audio	0	3AC	45	—	-2	—	3AC	-2.5	—
6C5	Driver	0	3AC	235	—	-2	—	3AC	2	—
6L6	Power	0	3AC	320	120	-4	—	3AC	13	—
6C5	Target Tuning Amp.	0	3AC	250	—	-5	—	3AC	4	—
5Y3 5W4	Rectifier	0	340	—	AC	—	AC	—	340	—




BOTTOM VIEW
OF SOCKET

All voltages measured from point indicated to ground, using a 1000 ohm per volt meter. Antenna and ground disconnected. Line Voltage 112V.

Current Consumption 110 watts.


Power Output 12 watts.

Alignment procedure on page 27.




TUBE POSITION

NOTE: See bottom page 18 for details of antenna connector strip.




Part No.	Description	Value
C1	22-323	5 MMFD 600V
C2	487	.05 MFD 400V
C3	170	.1 " 400V
C4	289	50 MMFD 600V
C5	187	25 MFD 600V
C6	212	.05 MFD 400V
C7	486	.0013 " 600V
C8	243	.01 " 400V
C9	250	.05 " 200V
C10	508	TRIMMER COND 600V
C11	285	10 MMFD 600V
C12	205	200-550 MFD PADDER 600V
C13	384	.0015 MFD 600V
C14	489	3 GANG VARIABLE 600V
C15	182	.00025 MFD 600V
C16	147	.0005 " 600V
C17	188	.02 " 400V
C18	162	.0001 " 600V
C19	495	.02 " 600V
C20	509	10 MFD DRY ELEC COND 50V
C21	506	16 " WET 250V
C22	229	.005 MFD (TUBULAR) 600V
C23	485	.005 " 600V
C24	125	8 MFD WET ELEC COND 450V
C25	294	16 " " 450V
C26	304	8 " " (CHROM) 450V
C27	405	10 " DRY " COND. 50V
R1	65278	99 M OHM 1/4W
R2	987	900 " 1/4W
R3	299	990 M " 1/4W
R4	208	12 M " 1/4W
R5	466	990 " 1/4W
R6	392	5100 " 1/4W
R7	550	5 " 1/4W
R8	280	40 M " 1/4W
R9	303	700 " 1/4W

Part No.	Description	Value
Q1	6K7G	R.F. TUBE
Q2	6L7G	1ST DETECTOR
Q3	6C5	SHADOWGRAPH TUBE
Q4	6C5G	OSCILLATOR
Q5	6H6G	2ND DET. AVG.
Q6	6K7	R.F. TUBE
Q7	6L7	1ST DETECTOR
Q8	6C5	SHADOWGRAPH TUBE
Q9	6C5G	OSCILLATOR
Q10	6H6G	2ND DET. AVG.
Q11	6K7	R.F. TUBE
Q12	6L7	1ST DETECTOR
Q13	6C5	SHADOWGRAPH TUBE
Q14	6C5G	OSCILLATOR
Q15	6H6G	2ND DET. AVG.
Q16	6K7	R.F. TUBE
Q17	6L7	1ST DETECTOR
Q18	6C5	SHADOWGRAPH TUBE
Q19	6C5G	OSCILLATOR
Q20	6H6G	2ND DET. AVG.
Q21	6K7	R.F. TUBE
Q22	6L7	1ST DETECTOR
Q23	6C5	SHADOWGRAPH TUBE
Q24	6C5G	OSCILLATOR
Q25	6H6G	2ND DET. AVG.
Q26	6K7	R.F. TUBE
Q27	6L7	1ST DETECTOR
Q28	6C5	SHADOWGRAPH TUBE
Q29	6C5G	OSCILLATOR
Q30	6H6G	2ND DET. AVG.
Q31	6K7	R.F. TUBE
Q32	6L7	1ST DETECTOR
Q33	6C5	SHADOWGRAPH TUBE
Q34	6C5G	OSCILLATOR
Q35	6H6G	2ND DET. AVG.
Q36	6K7	R.F. TUBE
Q37	6L7	1ST DETECTOR
Q38	6C5	SHADOWGRAPH TUBE
Q39	6C5G	OSCILLATOR
Q40	6H6G	2ND DET. AVG.
Q41	6K7	R.F. TUBE
Q42	6L7	1ST DETECTOR
Q43	6C5	SHADOWGRAPH TUBE
Q44	6C5G	OSCILLATOR
Q45	6H6G	2ND DET. AVG.
Q46	6K7	R.F. TUBE
Q47	6L7	1ST DETECTOR
Q48	6C5	SHADOWGRAPH TUBE
Q49	6C5G	OSCILLATOR
Q50	6H6G	2ND DET. AVG.
Q51	6K7	R.F. TUBE
Q52	6L7	1ST DETECTOR
Q53	6C5	SHADOWGRAPH TUBE
Q54	6C5G	OSCILLATOR
Q55	6H6G	2ND DET. AVG.
Q56	6K7	R.F. TUBE
Q57	6L7	1ST DETECTOR
Q58	6C5	SHADOWGRAPH TUBE
Q59	6C5G	OSCILLATOR
Q60	6H6G	2ND DET. AVG.
Q61	6K7	R.F. TUBE
Q62	6L7	1ST DETECTOR
Q63	6C5	SHADOWGRAPH TUBE
Q64	6C5G	OSCILLATOR
Q65	6H6G	2ND DET. AVG.
Q66	6K7	R.F. TUBE
Q67	6L7	1ST DETECTOR
Q68	6C5	SHADOWGRAPH TUBE
Q69	6C5G	OSCILLATOR
Q70	6H6G	2ND DET. AVG.
Q71	6K7	R.F. TUBE
Q72	6L7	1ST DETECTOR
Q73	6C5	SHADOWGRAPH TUBE
Q74	6C5G	OSCILLATOR
Q75	6H6G	2ND DET. AVG.
Q76	6K7	R.F. TUBE
Q77	6L7	1ST DETECTOR
Q78	6C5	SHADOWGRAPH TUBE
Q79	6C5G	OSCILLATOR
Q80	6H6G	2ND DET. AVG.
Q81	6K7	R.F. TUBE
Q82	6L7	1ST DETECTOR
Q83	6C5	SHADOWGRAPH TUBE
Q84	6C5G	OSCILLATOR
Q85	6H6G	2ND DET. AVG.
Q86	6K7	R.F. TUBE
Q87	6L7	1ST DETECTOR
Q88	6C5	SHADOWGRAPH TUBE
Q89	6C5G	OSCILLATOR
Q90	6H6G	2ND DET. AVG.
Q91	6K7	R.F. TUBE
Q92	6L7	1ST DETECTOR
Q93	6C5	SHADOWGRAPH TUBE
Q94	6C5G	OSCILLATOR
Q95	6H6G	2ND DET. AVG.
Q96	6K7	R.F. TUBE
Q97	6L7	1ST DETECTOR
Q98	6C5	SHADOWGRAPH TUBE
Q99	6C5G	OSCILLATOR
Q100	6H6G	2ND DET. AVG.



CIRCUIT DIAGRAM—Models 12-U-158.



12-U-159. (Chassis No. 1203)

SERVICE NOTES ON 1203 CHASSIS

OFF SCALE—Unable to line up and gain drops off—check 20 ohm. resistor in screen of 1st detector for open R-16 63-411.—check 50 mmfd condenser in oscillator circuit C4—22-289.

NOISY—Tubes, antenna and ground. Poor contact on band switch; volume control; coil wires short to band switch; poor contact on sensitivity switch. Noisy air trimmers, 16 mfd. screen condenser noisy, C-21—22-506.

NOISY ON "D" BAND—Clear gang bonds away from chassis, center in chassis holes, wire of "D" band tuned circuit shorting, loose solder lugs or terminals.

POOR SENSITIVITY ON "D" BAND—Open coil winding, defective 6H6, 6L7 tubes, poor contact of tube prongs, poor contact on band switch, check antenna, check I.F. peak, 456 K.C. Shorted 50 mmfd condenser in oscillator circuit; if shorted sensitivity will fall off on all bands, but more noticeable on "D" band. Check coupling of wires in "D" band circuit.

NOISY AND OFF SCALE ON "D" BAND—Replace 50 mmfd. in oscillator circuit, will vary scale reading considerably if defective.

OSCILLATIONS RIDE IN—Check balance. Check .0012 in oscillator plate circuit.

POOR SENSITIVITY ON ULTRA SHORT WAVE—Note: Do not expect extreme pick-up on this band. However, the following will affect operation of the band—open oscillator coil, open or shorted .0012 condenser, shorted 50 mmfd across H.F. coil, grounded trimmer on detector section of gang. Do not alter or change length of wires or position of coils, etc., as this will affect entire short wave band operation—leave or replace all units in position shipped from factory. Open 5 ohm resistor at H.F. coil, will give spotty sensitivity; tubes, in particular 1st detector has a great effect on ultra short wave reception; also aerial installation.

DISTORTION—Tubes, open 16 mfd. condenser, output tubes mismatched, 10 mfd. dry electrolytic in cathode circuit shorted; open cathode circuits, defective by-pass condenser; grounded or shorted tone circuit, defective speaker. Distortion only on normal, tone switch lugs are shorted. Also shorted .005 on one of the output tubes, open P.P. transformer.

CARRIER HUM—Open electrostatic shield in power transformer, by-pass A.C. line with approx. 100K micamold. Reverse A.C. plug. Open candohm ground—shorted .005 plate of output tube, grounded tap on volume control, tubes 6C5, 6H6 and output.

LACKS HIGHS—Poor contact on tone switch .00025 open; if tap on volume control is open, tone control will have no effect.

DEAD—Audio but no R.F. signals. 5 meter coil broken loose from gang terminal. Shorted air trimmer, gang trimmer shorted, open resistor in plate 1st audio. Tubes, filters shorted or by-pass condenser. Open coils.

I. C. OFF SCALE—Check pointer—line up across dial scale parallel to line with gang closed. Note: Air trimmer for "B" band as shown in earlier receivers and listed in technical book not used on later models. B.C. and D trimmers in same position as shown—follow usual line up procedure.

LACKS SENSITIVITY—Open coils, tubes, 2nd detector in particular; open R.F. choke in plate circuit, rebalance I.F.'s; broken grid wires; defective antenna and ground.

SPECIAL ACCESSORIES

For the convenience of those wishing to use headphones, and those hard of hearing, Zenith has made available an adapter, and several headphone combinations such as single, double and Bone Conductor head sets. They may be used with or without operation of the set speaker, and with external independent volume control.

There is also available an adapter and special cased permanent magnet dynamic speaker for extension use, and a Volume Limiting Knob for controlling maximum speaker level in hospitals or other installations where subdued response is desirable.

Write the factory for literature and prices on this special equipment.

CHASSIS No. 1203

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	3AC	235	100	0	—	3AC	0	0
6L7	1st Det.	0	3AC	230	120	-.5	—	3AC	0	0
6C5	Osc.	0	3AC	185	—	-8	—	3AC	0	—
6K7	I. F.	0	3AC	235	100	0	—	3AC	Local 9	0
6H6	2nd Det. A.V.C.	0	3AC	-2.5	-2.5	-2.5	—	3AC	-2.5	—
6F5	1st Audio	0	3AC	—	90	—	—	3AC	-2.5	—
6F6	Driver	0	3AC	215	215	-.5	—	3AC	11	—
6L6	Power	0	3AC	330	210	-3	—	3AC	14	—
6C5	Target Tuning Amp.	0	3AC	230	—	0	—	3AC	0	—
5Y3 5W4	Rectifier	0	340	—	AC	—	AC	—	340	—



ALIGNMENT PROCEDURE


CHASSIS No. 5406

- (1) Connect the output leads of the signal generator to the grid of the first detector and receiver ground lead. Also connect an output meter across the speaker leads.
- (2) Set the signal generator at 456 K.C. and carefully adjust the four I.F. trimmers to the point giving the greatest output reading. These I.F. transformers are of a very high gain, selective type, and the adjustments should be repeated several times for greatest accuracy.
- (3) Change the signal generator leads to the antenna and ground leads of the receiver.

- (4) Set the signal generator at 1400 K.C. Set the pointer on the receiver dial at the same frequency.

First adjust the oscillator and then the detector trimmers on the gang condenser to the point giving the maximum reading on the output meter, using as small a signal from the generator as possible so as to prevent the A.V.C. action from affecting the output readings.

- (5) Reset the signal generator to 600 K.C.
- (6) Slowly rock the pointer past 600 K.C. on dial meanwhile adjusting the osc. padder (located in rear of gang condenser) to the combination giving the greatest output reading.
- (7) Repeat operation No. 4.



LOCATION OF TRIMMERS


ALIGNMENT PROCEDURE

CHASSIS No. 5633

- (1) Connect the output leads of the signal generator to the grid of the first detector and receiver chassis through an .01 mfd. condenser. Also connect an output meter across the speaker transformer leads.
- (2) Set the signal generator at 456 K.C. and carefully adjust the four I.F. trimmers to the point giving the greatest output reading. These I.F. transformers are of a very high gain selective type, and the adjustments should be repeated several times for greatest accuracy.
- (3) Change the signal generator leads to the antenna and ground leads of the receiver.
- (4) Set the signal generator at 1400 K.C. Set the pointer on the receiver dial at the same frequency.

First adjust the oscillator and then the detector trimmers on the gang condenser to the point giving the maximum reading on the output meter, using as weak a signal from the generator as possible so as to prevent the A.V.C. action from affecting the output readings.

- (5) Reset the signal generator to 600 K.C.
- (6) Slowly rock the pointer past 600 K.C. on dial meanwhile adjusting the osc. padder (located on front of chassis) to the combination giving the greatest output reading.
- (7) Repeat operation No. 4.
- (8) There are no adjustments on the short wave band.



LOCATION OF TRIMMERS


ALIGNMENT PROCEDURE

CHASSIS Nos. 5516-5634-5707

- 1) Connect the output leads of the signal generator to the grid of the first detector and receiver chassis. Also connect an output meter across the speaker transformer leads.
- 2) Set the signal generator at 456 K.C. and carefully adjust the four I.F. trimmers to the point giving the highest reading on the output meter. The output transformers are of a very high grain, selective type and these adjustments should be repeated several times in order to secure maximum accuracy.

All adjustments should be made using as weak an output from the signal generator as possible in order to prevent the A.V.C. action from affecting the output readings.

- (3) Change the signal generator leads to the antenna and ground terminals of the receiver.
- (4) Adjust the wave trap (located on rear of chassis) for **minimum** output reading.
- (5) Set signal generator at 6 M.C. Switch receiver to band B, and adjust osc. trimmer on gang for correct dial reading.
- (6) Set signal generator at 1400 K.C. Switch receiver to band A and adjust broadcast trimmer (located in front of 6A8 tube—see diagram below) for correct dial reading. Also adjust antenna trimmer on gang to resonance.
- (7) Set signal generator at 18 M.C.—Switch receiver to band C, and adjust the short wave trimmer while rocking the pointer past 18 M.C. on the dial to the combination giving the greatest output.
- (8) Set signal generator at 600 K.C.—Switch receiver to band A, and rock pointer past 600 on dial while adjusting the broadcast padder (located adjacent to gang condenser) to combination giving the greatest output reading.
- (9) Readjust broadcast and ant. trimmers at 1400 K.C. (as in operation 6).




LOCATION OF TRIMMERS

(Trimmer positions are the same on all chassis)

ALIGNMENT PROCEDURE

CHASSIS Nos. 5635-5801-1004

- (1) Connect the output leads of the signal generator to the grid of the first detector and receiver chassis. Also connect an output meter across the speaker transformer leads.
- (2) Set the signal generator at 456 K.C. and carefully adjust the four I.F. trimmers to the point giving the highest reading on the output meter. The output transformers are of a very high gain, selective type and these adjustments should be repeated several times in order to secure maximum accuracy. All adjustments should be made using as weak an output from the signal generator as possible in order to prevent the A.V.C. action from affecting the output readings.
- (3) Change the signal generator leads to the antenna and ground terminals of the receiver.
- (4) Set signal generator at 6 M.C.—Switch receiver to band B, and adjust osc. trimmer on gang for correct dial reading.
- (5) Set signal generator at 1400 K.C.—Switch receiver to band A and adjust broadcast trimmer (located in front of 6A8 tube—see diagram below) for correct dial reading. Also adjust ant. and det. trimmers on gang to resonance, adjust only the det. trimmer on two gang sets.
- (6) Set signal generator at 18 M.C.—Switch receiver to band C and adjust the short wave trimmer while rocking the pointer past 18 M.C. on the dial to the combination giving the greatest output.
- (7) Set signal generator at 600 K.C.—Switch receiver to band A, and rock pointer past 600 on dial while adjusting the broadcast padder (located adjacent to gang condenser) to combination giving the greatest output reading.
- (8) Re-align broadcast trimmers at 1400 K.C. as outlined in operation 5.



(Trimmer positions are the same on all chassis)

CHASSIS No. 1203

CHASSIS No. 1203

-
- 6L6
POWER
6L6G
- AUDIO
TRANS.
- 6L6
POWER
6L6G
- SPKR.
SOCKET
- 6C5
SHADOW
METER
6C5G
- 5Y3
RECTIFIER
5W4
- 5Y3
RECTIFIER
5W4
- POWER
- TRANS.
- 8MFD.
450V.
- 16MFD.
450V.
- 6F6
DRIVER
6F6G
- 8MFD.
450V.
- 6K7
I.F.
6K7G
- 1ST I.F.
TRANS.
- 6K7
D.F.
6K7G
- 6F5G
6F5C
6F5B
- 6G6
2ND DET.
A.V.C.
6HE5
- 2ND I.F.
TRANS.
- BROADCAST PADER
- R.F.
- DET.
- ANT.
COIL
- 6K7
D.F.
6K7G
- 6L7G
6L7
1ST DET.
- OSC.
COIL
- 6C5
OSC.
6C5G
- FILTER
CHOK
- OSC. TRIMMERS
A-BAND
B-BAND
D-BAND
- TONE CONTROL
- SWITCH & VOLUME
- TUNING CONTROL
- SENSITIVITY CONTROL
- BAND INDICATOR

LOCATION OF TRIMMERS

PARTS LIST

Dial & Drive Assembly Parts

PART NO.	DESCRIPTION	CHASSIS NO.								PRICE
		1203	1004	5801	5707	5634	5635	5633	5516	
11-3	Dial cord (per foot)							*	*	\$.10
26-98	Dial scale							*	*	.50
26-116	Dial Scale							*	*	.50
26-117	Dial Scale					*	*	*	*	1.25
26-122	Dial Scale				*			*	*	.75
26-123	Dial Scale		*	*						1.50
26-130	Dial Scale	*								2.00
27-16	Flywheel Disc	*	*	*	*	*				1.00
32-10	Drive belt				*			*	*	.20
32-11	Drive belt		*	*	*	*	*	*	*	.25
32-12	Drive belt	*						*	*	.25
34-49	Condenser shaft gear	*	*	*	*	*	*	*	*	.25
34-51	Lower pinion and gear	*	*	*	*	*	*	*	*	.15
59-32	Split second pointer			*				*	*	.15
59-40	Z pointer			*				*	*	.15
59-41	Split second pointer			*				*	*	.10
59-45	Dial pointer and bushing							*	*	.15
59-52	Split second pointer		*			*	*	*	*	.15
59-53	Z pointer		*	*	*	*	*	*	*	.20
59-54	Pointer	*						*	*	.25
59-55	Split second pointer	*						*	*	.15
61-34	Drive pulley	*						*	*	.10
61-40	Drive pulley		*	*	*	*	*	*	*	.10
76-215	Drive shaft		*	*	*	*	*	*	*	.10
76-216	Dial shaft	*						*	*	.35
76-219	Band selector shaft	*						*	*	.20
80-53	Tension pulley spring	*	*	*	*	*	*	*	*	.05
80-60	Tension pulley spring				*			*	*	.05
80-69	Tension pulley spring							*	*	.01
80-118	Dial drive spring	*	*	*	*	*	*	*	*	.15
80-127	Dial glass retainer spring	*	*	*	*	*	*	*	*	.03
80-128	Shaft pulley spring	*	*	*	*	*	*	*	*	.01
83-407	Dial light diffusion strip		*	*	*	*	*	*	*	.05
93-273A	.031 x 9/32 x 3/4 bake. wash.	*	*	*	*	*	*	*	*	.01
97-91	Lower gear stud		*	*	*	*	*	*	*	.01
100-36	Dial lights 6.3V bayonet	*	*	*	*	*	*	*	*	.15
100-39	Dial lights 2.9V bayonet						*	*	*	.15
118-11	Band switch link	*						*	*	.05
122-13	Target tuning meter		*	*						2.00
122-14	Target tuning meter	*								2.00
126-221	Dial light shield	*								.01
132-15	Dial glass retainer ring							*	*	.05
148-13	Switch lever arm	*						*	*	.05
159-12	Snap buttons	*						*	*	.02
188-2	Retainer rings	*	*	*	*	*	*	*	*	.01
192-11	Dial glass							*	*	.15
192-15	Dial glass							*	*	.15
192-16	Dial glass				*			*	*	.25
192-17	Dial glass		*	*	*	*	*	*	*	.50
192-19	Dial glass	*						*	*	1.50
196-5	Dial glass gasket							*	*	.03
196-9	Dial glass gasket							*	*	.05
196-10	Dial glass gasket				*			*	*	.10
196-11	Dial glass gasket		*	*	*	*	*	*	*	.10
196-12	Dial glass gasket	*						*	*	.10
MS-308	Dial drive pulley assm.							*	*	.25
MS-310	Dial refl. & strip assm.							*	*	.75
MS-312	Dial drive pulley assm.	*	*	*	*	*	*	*	*	.25
MS-313	Dial refl. & strip assm.				*			*	*	1.00
MS-321	Dial drive pulley assm.							*	*	.20

PART NO.	DESCRIPTION	CHASSIS NO.								PRICE
		1203	1004	5801	5707	5634	5635	5633	5516	
S-3780	Shft. pul., slv. & pin. assm.				*			*	*	.35
S-3888	Drive shaft assembly							*	*	.10
S-4301	Dial light sock. & clip assm.	*	*	*	*	*	*	*	*	.10
S-4323	Dial drive shft. & wash. assm.						*	*	*	.10
S-4340	Tension pulley & arm assm.	*	*	*	*	*	*	*	*	.15
S-4342	Drive shaft & pulley assm.							*	*	.35
S-4380	Lever arm and shaft assm.	*	*					*	*	.25
S-4412	Vol. con. indic. scale & bush.		*	*	*	*	*	*	*	.35
S-4413	Band Ind. scale & bush.		*	*	*	*	*	*	*	.35
S-4414	Tone Cont. Ind. scale & bush.		*	*	*	*	*	*	*	.35
S-4415	Sensitiv. Con. Ind. scale & bush		*	*	*	*	*	*	*	.35
S-4416	Pin. gear & pntr. shft. bush. as.	*	*	*	*	*	*	*	*	.25
S-4541	Vol. Con. ind. scale & bush. as.	*						*	*	.35
S-4542	Band Ind. scale & bush. as.	*						*	*	.35
S-4543	Tone cont. ind. scale & bush. as.	*						*	*	.35
S-4544	Sensitivity control indicator scale and bushing assembly	*						*	*	.35

R. F. Coils, Chokes & I. F. Transformers

20-71	Antenna Choke	*	*	*	*					.20
20-88	R. F. Choke					*				.25
20-133	Wave Trap Assembly				*	*				.60
20-134	Antenna Choke				*	*		*	*	.25
20-135	R. F. Plate Choke	*	*	*	*	*	*	*	*	.50
95-346	1st I.F. Transformer							*	*	1.25
95-347	2nd I.F. Transformer							*	*	1.25
95-349	1st I.F. Transformer							*	*	1.25
95-350	2nd I.F. Transformer							*	*	1.25
95-352	1st I.F. Transformer							*	*	1.25
95-353	1st I.F. Transformer	*	*	*	*	*	*	*	*	1.25
95-354	2nd I.F. Transformer	*	*	*	*	*	*	*	*	1.25
95-358	1st I.F. Transformer				*			*	*	1.25
95-359	2nd I.F. Transformer				*			*	*	1.25
95-368	1st I.F. Transformer	*						*	*	1.25
95-369	2nd I.F. Transformer	*						*	*	1.25
95-371	1st I.F. Transformer							*	*	1.25
95-372	2nd I.F. Transformer							*	*	1.25
S-2778	R.F. Choke							*	*	.15
S-3756	Osc. Coil Assembly							*	*	1.50
S-4302	Antenna Coil Assembly							*	*	1.00
S-4304	Oscillator Coil Assembly							*	*	.50
S-4343	Antenna Coil Assembly				*			*	*	1.25
S-4344	Oscillator Coil Assembly				*			*	*	1.25
S-4362	Antenna Coil Assembly							*	*	1.00
S-4363	Oscillator Coil Assembly							*	*	1.00
S-4387	H.F. Det. Coil Assembly	*						*	*	.35
S-4388	H.F. Osc. Coil Assembly	*						*	*	.35
S-4394	Antenna Coil Assembly				*			*	*	1.00
S-4395	Oscillator Coil Assembly				*			*	*	1.00
S-4419	Detector Coil Assembly		*	*				*	*	1.25
S-4420	Oscillator Coil Assembly		*	*				*	*	1.25
S-4421	Detector Coil Assembly		*	*				*	*	1.25
S-4452	Wave Trap Assembly							*	*	.75
S-4456	Antenna Coil Assembly							*	*	1.25
S-4480	Antenna Coil Assembly							*	*	1.25
S-4481	Detector Coil Assembly							*	*	1.25
S-4482	Oscillator Coil Assembly							*	*	1.25
S-4545	Antenna Coil Assembly	*						*	*	1.00
S-4546	Detector Coil Assembly	*						*	*	1.00
S-4547	Oscillator Coil Assembly	*						*	*	1.50

PRICE LIST (Continued)

Condensers—By-Pass, Fixed, Variable & Electrolytic

PART NO.	DESCRIPTION	CHASSIS NO.							PRICE
		1203	1004	5801	5707	5634	5635	5633	
22-82	.001 mfd. 600 Volt							*	.25
22-125	8 mfd. 450 Volt Wet Elec.	*						*	1.00
22-127	25 mmfd. 600 Volt	*	*	*	*	*	*	*	.15
22-138	.2 mfd. 200 Volt							*	.25
22-147	.005 mfd. 600 Volt	*	*	*	*	*	*	*	.15
22-162	.0001 mfd. 600 Volt	*	*	*	*	*	*	*	.20
22-170	.1 mfd. 400 Volt	*	*	*	*	*	*	*	.25
22-182	.00025 600 Volt	*	*	*	*	*	*	*	.12
22-185	.01 200 Volt							*	.20
22-188	.002 400 Volt	*	*	*	*	*	*	*	.15
22-190	.1 200 Volt							*	.20
22-199	.5 200 Volt							*	.35
22-205	200-550 mmfd. Padder	*	*	*	*	*	*	*	.35
22-212	.05 mfd. 400 Volt	*	*	*	*	*	*	*	.20
22-219	.03 mfd. 200 Volt			*	*	*	*	*	.15
22-224	.1 mfd. 300 Volt	*	*					*	.15
22-225	5 mfd. Elect. 25 Volt							*	.65
22-229	.0005 600 Volt	*	*	*	*	*	*	*	.15
22-243	.01 400 Volt	*	*	*	*	*	*	*	.15
22-250	.5 mfd. 200 Volt	*	*	*	*	*	*	*	.15
22-280	.5 mfd. 200 Volt						*	*	.25
22-285	10 mmfd. 600 Volt	*						*	.15
22-289	50 mmfd. 600 Volt	*	*	*	*	*	*	*	.12
22-294	16 mfd. 450 Volt	*	*	*	*	*	*	*	1.00
22-303	5 mmfd. 600 Volt	*	*	*	*	*	*	*	.15
22-305	2-35 mmfd. Padder							*	.15
22-326	.003 mfd. 400 Volt			*	*	*	*	*	.15
22-327	.02 mfd. 200 Volt							*	.20
22-350	.25 mfd. 200 Volt					*	*	*	.20
22-358	.002 600 Volt							*	.20
22-376	.0021 600 Volt							*	.20
22-384	.0015 mfd. 600 Volt	*	*	*	*	*	*	*	.20
22-405	10 mfd. Dry Elect. 50 Volts	*						*	.75
22-408	2-35 mfd. Trimmer Cond.		*	*	*	*	*	*	.25
22-419	2-8 mfd. 250 Volt							*	1.75
22-435	.02 mfd. 600 Volt	*	*	*	*	*	*	*	.15
22-455	.01 mfd. 1200 Volt					*	*	*	.15
22-459	2-8 mfd. 250 Volt Dry Elect.					*	*	*	1.25
22-467	.2 mfd. 200 Volt				*	*	*	*	.20
22-478	2 gang Variable							*	2.50
22-481	4-16-8 mfd. 150V							*	2.50
22-482	2 gang Variable				*	*	*	*	2.50
22-484	4-8-16-4 mfd. 250 Volt				*	*	*	*	3.00
22-485	.005 mfd. 600 Volt	*	*	*	*	*	*	*	.35
22-486	.0012 mfd. 600 Volt	*	*	*	*	*	*	*	.15
22-487	.05 mfd. 400 Volt	*	*	*	*	*	*	*	.15
22-488	3 gang Variable		*	*	*	*	*	*	3.50
22-489	3 gang Variable	*						*	3.50
22-491	8-2 mfd. Dry Elect. 450 V. (Rep. 22-496)			*	*	*	*	*	1.50
22-492	.002 mfd. 600 Volt			*	*	*	*	*	.20
22-493	8-8 mfd. Dry Elect. 450 Volt		*					*	2.00
22-494	.1 mfd. 600 Volt							*	.25
22-495	.2 mfd. 400 Volt			*	*	*	*	*	.20
22-502	8-16 mfd. Dry Elect. 450 V. 25 Cy.		*					*	1.00
22-504	8 mfd. Wet Elect. Cond. 450 V.	*	*	*	*	*	*	*	1.00
22-505	12 mfd. Wet Elect. Cond. 325 V							*	1.00
22-506	16 mfd. Wet Elect. Cond. 250 V.	*	*	*	*	*	*	*	1.00

PART NO.	DESCRIPTION	CHASSIS NO.							PRICE
		1203	1004	5801	5707	5634	5635	5633	
22-507	10 mfd. Dry Elect. 25 Volts		*						.65
22-508	Trimmer Cond.		*						.20
22-509	10 mfd. Dry Elect. Cond. 50 V.		*						.75
22-510	8-8-8 mfd. Dry Elect. Cond. 450 V.		*						2.75
22-512	8 mfd. Dry Elect. 450 Volt		*						1.00
22-513	16 mfd. Dry Elect. 450 V.					*			1.50
22-514	4-16 mfd. Dry Elect. 250 V.				*				1.50
22-515	4-8 mfd. Dry Elect. 250 V.				*				1.25
22-516	8 mfd. Elect. 150 Volt							*	.75
22-517	4-16 mfd. Elect. 150 V.							*	1.15

Resistors, Voltage Dividers and Variable Controls

63-135	25M ohm 1/2 watt							*	.20
63-208	12 M ohm 1 watt		*						.25
63-238	1 M ohm 1/4 watt							*	.20
63-258	490 M ohm 1/4 watt			*	*	*	*	*	.20
63-260	100 M ohm 1/4 watt	*	*	*	*	*	*	*	.20
63-261	9900 M ohm 1/4 watt	*	*	*	*	*	*	*	.20
63-263	30 M ohm 1/2 watt							*	.20
63-278	99 M ohm 1/4 watt	*	*	*	*	*	*	*	.20
63-280	49 M ohm 1/4 watt		*	*	*	*	*	*	.20
63-281	29 M ohm 1/4 watt							*	.20
63-288	19 M ohm 1/4 watt			*	*	*	*	*	.20
63-290	260 M ohm 1/4 watt			*	*	*	*	*	.20
63-293	990 M ohm 1/4 watt	*	*	*	*	*	*	*	.20
63-300	990 ohm 1/4 watt		*					*	.20
63-303	700 ohm 1/4 watt	*	*	*	*	*	*	*	.20
63-353	19 M ohm 1/2 watt		*	*	*	*	*	*	.20
63-357	300 ohm 1/4 watt	*	*	*	*	*	*	*	.20
63-360	2 M ohm 1/4 watt						*	*	.20
63-361	5 M ohm 1/4 watt				*	*	*	*	.20
63-362	400 ohm 1/4 watt				*	*	*	*	.20
63-373	11 M ohm 1/2 watt		*	*	*	*	*	*	.20
63-376	190 M ohm 1/4 watt		*	*	*	*	*	*	.20
63-377	170 ohm 1/4 watt				*	*	*	*	.20
63-385	300 M ohm 1/4 watt	*	*					*	.20
63-394	200 ohm 1/4 watt					*	*	*	.20
63-411	20 ohm 1/4 watt	*						*	.20
63-418	1500 ohm 1/2 watt							*	.20
63-442	50 M ohm 1/4 watt			*				*	.20
63-452	650 M ohm 1/4 watt			*				*	.20
63-466	990 ohm 1/2 watt	*						*	.20
63-469	100 M ohm Tone Control							*	.60
63-477	100 ohm Flex Wire Wound						*	*	.20
63-481	400 M ohm 1/4 watt		*	*	*	*	*	*	.20
63-486	80 M ohm 1 watt							*	.20
63-498	800 ohm 1/4 watt				*	*	*	*	.20
63-499	9 M ohm 1/4 watt							*	.20
63-515	Candohm Resistor		*	*	*	*	*	*	.65
63-516	Candohm Resistor		*	*	*	*	*	*	.65
63-517	400 M ohm Volume Control							*	1.00
63-518	590 ohm 1/4 watt			*	*	*	*	*	.20
63-520	400 M ohm Vol. Con. & Switch			*	*	*	*	*	1.00
63-521	50 M ohm Tone Control			*	*	*	*	*	.70
63-522	2 megohm Vol. Con. & Switch	*	*	*	*	*	*	*	1.00
63-523	2 megohm 1/4 watt	*	*	*	*	*	*	*	.20
63-528	Candohm Resistor	*	*	*	*	*	*	*	.65
63-530	5 ohm 1/4 watt	*	*	*	*	*	*	*	.20
63-531	650 ohm 1 watt	*	*	*	*	*	*	*	.20
63-532	5100 ohm 1 watt	*	*	*	*	*	*	*	.20

PRICE LIST (Continued)

PART NO.	DESCRIPTION	CHASSIS NO.							PRICE	PART NO.	DESCRIPTION	CHASSIS NO.							PRICE
		1203	1004	5801	5707	5634	5635	5633				1203	1004	5801	5707	5634	5635	5633	
63-534	400 M vol. Con. & Switch								1.00	49-147	12" Dynamic Speaker								10.00
63-536	30 ohm Flex Wire Wound								.15		Cone and Voice Coil for 49-147								3.25
Transformers—Audio and Power											Output Transformer for 49-147								2.50
95-289	Power Trans. 115 V. 50-60 Cy.								3.50		Field Coil for 49-147								3.00
95-290	Power Trans. All Voltage 25 Cy.								6.50	49-148	12" Dynamic Speaker								10.00
95-298	Power Choke								.75		Cone and Voice Coil for 49-148								3.25
95-300	Rectifier Trans.								2.00		Output Transformer for 49-148								2.50
95-305	Rectifier Trans.								1.75		Field Coil for 49-148								3.00
95-311	Audio Trans.								1.25	49-149	12" Dynamic Speaker 12U158								10.00
95-312	Power Choke								1.00		Cone and Voice Coil for 49-149								3.25
95-345	Power Choke								.75		Output Transformer for 49-149								2.00
95-348	Power Choke								.75		Field Coil for 49-149								2.00
95-351	Power Trans. 115 V. 50-60 Cy.								3.00	49-150	12" Dynamic Speaker 12U159								12.00
95-355	Power Trans. 115 V. 50-60 Cy.								5.00		Cone and Voice Coil for 49-150								3.25
95-356	Power Choke								1.25		Output Transformer for 49-150								2.00
95-360	Audio Trans.								2.00		Field Coil for 49-150								2.00
95-361	Power Trans. All Voltage 25 Cy.								5.00	49-151	8" Dynamic Speaker								6.50
95-365	Power Trans. All Voltage 25 Cy.								9.00		Cone and Voice Coil for 49-151								2.00
95-366	Power Choke								1.50		Output Transformer for 49-151								2.00
95-367	Audio Trans.								2.50		Field Coil for 49-151								2.00
95-370	Power Trans. 115 V. 50-60 Cy.								6.00	49-152	8" Dynamic Speaker								6.50
95-373	Power Trans. All Voltage 25 Cy.								10.00		Cone and Voice Coil for 49-152								2.00
Speakers and Speaker Parts											Output Transformer for 49-152								2.00
49-117	8" Dynamic Speaker								8.00		Field Coil for 49-152								2.00
	Cone and Voice Coil for 49-117								2.50	49-153	6" P. M. Dynamic Speaker								6.00
	Output Transformer for 49-117								2.00		Cone and Voice Coil for 49-153								2.00
	Field Coil for 49-117								2.00		Output Transformer for 49-153								2.00
49-118	10" Dynamic Speaker								9.00	49-155	8" P. M. Dynamic Speaker								8.00
	Cone and Voice Coil for 49-118								3.25		Cone and Voice Coil for 49-155								2.50
	Output Transformer for 49-118								2.00		Output Transformer for 49-155								2.50
	Field Coil for 49-118								2.00	49-156	12" Dynamic Speaker								10.00
49-141	5" Dynamic Speaker								4.00		Cone and Voice Coil for 49-156								3.25
	Cone and Voice Coil for 49-141								1.50		Output Transformer for 49-156								2.50
	Output Transformer for 49-141								1.50		Field Coil for 49-156								3.00
	Field Coil for 49-141								1.50	49-157	12" P. M. Dynamic Speaker								10.00
49-142	6" Dynamic Speaker								5.00		Cone and Voice Coil								3.25
	Cone and Voice Coil for 49-142								2.00		Output Transformer								2.50
	Output Transformer for 49-142								1.50	49-158	6" Dynamic Speaker								5.00
	Field Coil for 49-142								2.00		Cone and Voice Coil for 49-158								2.00
49-143	6" Dynamic Speaker								5.00		Output transformer for 49-158								2.00
	Cone and Voice Coil for 49-143								2.00		Field Coil for 49-158								2.00
	Output Transformer for 49-143								1.50	49-159	6" P. M. Dyn. Speaker for S4465								6.50
	Field Coil for 49-143								2.00		Cone and Voice Coil for 49-159								2.00
49-144	10" Dynamic Speaker								8.00	S-4465	Comp. Speaker and Case Assm.								10.00
	Cone and Voice Coil for 49-144								2.50	49-160	8" P. M. Dynamic Speaker								8.00
	Output Transformer for 49-144								2.00		Cone and Voice Coil for 49-160								2.50
	Field Coil for 49-144								2.00		Output Transformer for 49-160								2.50
49-145	10" Dynamic Speaker								8.00	S-4466	Comp. Speaker and Case Assm.								10.00
	Cone and Voice Coil for 49-145								2.50	Miscellaneous									
	Output Transformer for 49-145								2.00	78-101	Wafer Socket for 75 Tube								.10
	Field Coil for 49-145								2.00	78-106	Wafer Socket for 6A7 Tube								.10
49-146	8" Dynamic Speaker								7.00	78-109	Wafer Socket for 76 Tube								.10
	Cone and Voice Coil for 49-146								2.00	78-124	Wafer Socket for 19 Tube								.10
	Output Transformer for 49-146								2.00	78-128	Wafer Sock. for Speak. (5 con.)								.10
	Field Coil for 49-146								2.00	78-129	Voltage Indicator Socket								.10
										78-133	Wafer Socket for 6H6 Tube								.15
										78-136	Wafer Socket for 5Y3-5W4 Tube								.15
										78-137	Wafer Socket for 6F6-6L6 Tube								.15

PRICE LIST (Continued)

PART NO.	DESCRIPTION	CHASSIS NO.								PRICE
		1203	1004	5801	5707	5634	5635	5633	5516	
78-139	Wafer Socket for 15 Tube						*		*	.10
78-140	Wafer Socket for 38 Tube								*	.10
78-141	Vibrator Socket						*		*	.10
78-144	Wafer Socket for Speaker	*								.15
78-145	Wafer Socket for 6F5 Tube	*		*	*	*				.15
78-148	Wafer Socket for 6Q7 Tube							*	*	.15
78-150	Wafer Socket for 6K7 Tube	*	*	*	*	*		*	*	.15
78-151	Wafer Socket for 6A8 Tube			*	*	*		*	*	.15
78-156	Wafer Socket for 6C5 Tube	*	*	*						.15
78-158	Wafer Socket for 25A6 Tube				*			*		.15
78-159	Wafer Socket for 25Z6 Tube				*			*		.15
78-160	Wafer Socket for Speaker							*		.15
78-161	Wafer Socket for Ballast Tube				*			*		.15
78-162	Wafer Socket for 6L7 Tube	*								.15
19-59	Battery clip (positive)						*		*	.15
19-60	Battery clip (negative)						*		*	.15
44-7	Phono jack	*	*	*	*	*			*	.15
46-122	Tuning knob								*	.10
*46-123	Band selector and vol. con. knob	*	*	*	*	*	*		*	.20
46-127	Tuning and vol. con. knob				*				*	.20
*46-166	Tuning knob	*	*	*		*	*			.35
*46-167	Tone and sensitiv. con. knob	*	*	*		*	*			.20
46-168	Control knob							*		.20
46-169	Band switch knob				*			*		.20
51-21	Fuse mounting						*		*	.25
57-551	Escutcheon plate						*	*		1.00
57-556	Escutcheon plate		*	*						1.00
PART NO.	DESCRIPTION	CHASSIS NO.								PRICE
		1203	1004	5801	5707	5634	5635	5633	5516	
57-562	Escutcheon plate	*								2.00
83-433	Antenna and gr. terminal strip	*	*	*	*	*	*	*	*	.15
85-39	Phono switch	*	*	*	*	*	*	*	*	1.00
85-88	Band selector switch							*		.60
85-89	Band selector switch				*			*		1.00
85-90	Band selector switch					*				1.00
85-91	Sensitivity switch	*	*	*		*	*			.35
85-92	Tone control switch	*	*	*		*	*			.50
85-93	Band selector switch		*	*	*	*				1.50
85-94	Band selector switch	*								2.75
91-190	Battery cable (black) per ft						*		*	.05
91-191	Battery cable (red) per ft						*		*	.05
97-91	Lower gear stud			*						.01
100-37	115 V ballast tube								*	.75
100-38	117 V ballast tube					*				.75
100-45	125 V ballast tube					*				.75
100-46	150 V ballast tube					*				.75
100-47	200 V ballast tube					*				.75
100-48	220 V ballast tube					*				.75
100-49	250 V ballast tube					*				.75
126-109	Tube shields (small)	*	*	*	*	*				.15
126-127	Tube shields (large)	*	*	*	*	*	*	*	*	.10
136-10	5 ampere fuse						*		*	.06
190-6	Vibrator						*		*	5.00
S-4567	Acoustic adapter assembly	*	*	*						3.50

*When ordering colored knobs place the code letter H—Honey maple, Y—Ebony, W—Bone White, after the part number and add \$.10 to list price.

Zenith Radio Corporation
CHICAGO, ILL.


A 63-548 MGS 63-540 81% P.D.
B WAS C.I.
81% P.D.

POWER
1F5

2ND DETECTOR AVC
1F7

I.F. TUBE
1D5

DETECTOR-OSCILLATOR
1CZ



SPEAKER MODEL
49-163 G.P.M. 4F-199


BATTERY CABLE
SOCKET

JUMPER FOR 2V.
OPERATION

VIBRATOR
UNIT SOCKET

RESISTOR PLUG FOR 2V. CELL OPERATION
BALAST TUBE FOR 3V. DRY CELL OPERATION

VIBRATOR SUPPLY UNIT



BOTTOM VIEW
OF
SOCKET 2

ALL FILAMENTS
ON PILOT LIGHT

CONNECTS TO
CHASSIS

ALL FILAMENTS
ON PILOT LIGHT


CONNECTS TO
CHASSIS

Comp. No.	Part No.	Description	Comp. No.	Part No.	Description
C1	2220	.05 MFD	1	54712	ANTENNA COIL ASSEM.
C2	486	.0012 MFD	2	95379	1ST. I.F. TRANSFORMER
C3	350	.25 MFD	3	95380	2ND. I.F. TRANSFORMER
C4	289	50 MFD	4	54662	OSCILLATOR COIL ASSEM.
C5	527	.02 MFD	5	950-8	VIBRATOR
C6	182	.00025	6	20-148	R.F. CHOKER
C7	188	.02 MFD	7	95381	POWER TRANSFORMER
C8	229	.005 MFD	8	52718	R.F. CHOKER ASSEMBLY
C9	205	200-550 MFD ADJ. 25V.	9	95345	FILTER CHOKER
C10	406	25 GANG VARIABLE			
C11	199	.5 MFD			
C12	455	.01 MFD (TUBULAR)			
C13	522	250 MFD DRY ELEC.			
C14	243	.01 MFD (TUBULAR)			
R1	65280	49 M OHM			
R2	961	5 M OHM			
R3	599	40 M OHM			
R4	481	400 M OHM			
R5	293	550 M OHM			
R6	548	1 MEG OHM VOL. CONT. 5 W.			
R7	441	1 MEG OHM			
R8	594	200 M OHM			
R9	400	250 M OHM			
R10	278	99 M OHM			

I.F. FREQUENCY 456 K.C.
4 TUBE BATTERY SUPERHETERODYNE
CHASSIS N9 5407

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS.

MODEL 4F-133



SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9	
1C7	1st Det. Osc.	0	2	128	48	-2	112	0	0	0	-
1D5	I.F.	0	2	126	48	-	-	0	0	0	
1F7	2nd Det. A.V.C.	0	2	27	0	0	9	0	0	0	
1F5	Power	0	2	122	126	0	-	0	0	-	



All voltages measured with a 1000 ohm per volt D.C. meter and using the Zenith 6 V. Economy Pack - Antenna and ground disconnected.

Battery Voltage - 6.3 V.

Battery Drain - .98 amp.

ALIGNMENT

- (1) Connect the output leads of the signal generator to the grid of the first detector and receiver ground lead. Also connect an output meter across the speaker leads.
- (2) Set the signal generator at 456 K.C. and carefully adjust the four I.F. trimmers to the point giving the greatest output reading. These I.F. transformers are of a very high gain, selective type, and the adjustments should be repeated several times for greatest accuracy.
- (3) Change the signal generator leads to the antenna and ground leads of the receiver.
- (4) Set the signal generator at 1400 K.C. Set the pointer on the receiver dial at the same frequency. First adjust the oscillator and then the detector trimmers on the gang condenser to the point giving the maximum reading on the output meter, using as small a signal from the generator as possible so as to prevent the A.V.C. action from affecting the output readings.
- (5) Reset the signal generator to 600 K.C.
- (6) Slowly rock the pointer past 600 K.C. on dial meanwhile adjusting the osc. padder (located in rear of gang condenser) to the combination giving the greatest output reading.
- (7) Repeat operation No. 4.





PARTS LIST

Model 4F-133

Condensers

22-182	.00025 mfd. 600 Volt	.12
22-188	.02 mfd. 400 Volt	.15
22-199	.5 mfd. 200 Volt	.35
22-205	200-550 mmfd. Padder Condenser	.35
22-229	.005 mmfd. 600 Volt	.15
22-243	.01 mmfd. 400 Volt	.15
22-250	.05 mmfd. 200 Volt	.15
22-289	50 mmfd. 600 Volt	.12
22-327	.02 mfd. 200 Volt	.15
22-350	.25 mfd. 200 Volt	.20
22-406	Two Gang Variable Condenser	2.50
22-455	.01 mfd. 1200 Volt	.15
22-486	.0012 mfd. 600 Volt	.15
22-522	2 x 8 mfd. Dry Electrolytic (S-4680)	1.00

Resistors

63-278	99 M Ohm 1/4 Watt	.20
63-280	49 M Ohm 1/4 Watt	.20
63-293	990 M Ohm 1/4 Watt	.20
63-361	5 M Ohm 1/4 Watt	.20
63-394	200 Ohm 1/2 Watt	.20
63-400	250 M Ohm 1/4 Watt	.20
63-441	1 Megohm 1/4 Watt	.20
63-481	400 M Ohm 1/4 Watt	.20
63-539	40 M Ohm 1/4 Watt	.20
63-548	1 Megohm Volume Control and Switch	1.00

Coils, Chokes, Etc.

20-146	R. F. Choke	.20
95-379	1st I. F. Transformer	1.25
95-380	End I. F. Transformer	1.25
S-2778	R. F. Choke Assembly	.15
S-4662	Oscillator Coil Assembly	.30
S-4712	Antenna Coil Assembly	1.25

Parts For S-4680

Economy Pack (Used with 6 V. Storage Battery)

S-4680	Economy Pack Complete	10.00
20-146	R. F. Choke	.20
22-199	.5 mfd. 200 Volt Condenser	.35
22-243	.01 mfd. 400 Volt Condenser	.15
22-455	.01 mfd. 1200 Volt Condenser	.15
22-522	2-8 mfd. 250 Volt Elect. Condenser	1.25
63-394	200 Ohm 1/2 Watt Resistor	.20
78-141	Vibrator Wafer Type Socket	.15
95-345	Filter Choke	.75
95-381	Power Transformer	2.00
100-51	Dial Lights 2.5 Volt .65 Amp.	.15
166-4	Channeled Rubber Bumpers 2 7/8" Long	.05
166-5	Channeled Rubber Bumpers 3/8" Long	.02
190-8	Vibrator	5.00

Parts and Prices

Model 4F-133

Parts for S-4680 Economy Pack (Cont'd)

S-4659	Battery Cable-Plug and Clip Assembly	1.25
S-4663	Power Unit Cable and Plug Assembly	.50
Special Parts		
23-12	Tube Socket Contact Jumper	.02
63-544	Resistor Plug (Used With Air Cell Battery)	.50
100-52	Ballast Tube (Used with 3 Volt Dry Cell)	1.25
Miscellaneous		
46-122	Tuning Knobs	.10
49-163	6" P. M. Speaker	6.00
	Cone and Voice Coil for 49-163	2.00
	Output Transformer for 49-163	2.00
52-85	Battery Cable and Plug	.90
78-163	Battery Cable Plug Socket	.15
78-164	Power Supply Cable Plug Socket	.15
78-165	1C7 Wafer Type Socket	.15
78-166	1D5 Wafer Type Socket	.15
78-167	1F5 Wafer Type Socket	.15
78-168	1F7 Wafer Type Socket	.15
100-50	Dial Light 2 Volt .06 Amp.	.30
171-4	Dial Scale Lens	.25
S-3717	Dial Pointer and Bushing Assembly	.25
S-4301	Dial Light Socket and Clip Assembly	.10
S-4709	Dial Scale and Frame Assembly	.75

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS, U. S.A.
September 25, 1936

SOCKET VOLTAGES



Tube	Position	1	2	3	4	5	6	7	8	9
1C7	1st Det. Osc.	0	2	130	53	0	115	0	0	0
1D5	I.F.	0	2	130	53	-	-	0	0	0
1F7	2nd Det. A.V.C.	0	2	24	0	0	15	0	0	0
1H4	Driver	0	2	120	-	0	-	0	0	-
1J6	Power	0	2	143	-1	-1	143	0	0	-

All voltages measured with a 1000 ohm per volt D.C. meter and using the Zenith 6 V. Economy Pack. Antenna and ground disconnected.

Battery Voltage 6.3 V. - Battery Drain 1.1 ampere

ALIGNMENT PROCEDURE

- (1) Connect the output leads of the signal generator to the grid of the first detector and receiver chassis. Also connect an output meter across the speaker transformer leads.
- (2) Set the signal generator at 456 K.C. and carefully adjust the four I.F. trimmers to the point giving the highest reading on the output meter. The output transformers are of a very high gain, selective type, and these adjustments should be repeated several times in order to secure maximum accuracy. All adjustments should be made using as weak an output from the signal generator as possible in order to prevent the A.V.C. action from affecting the output readings.
- (3) Change the signal generator leads to the antenna and ground terminals of the receiver.
- (4) Set signal generator at 5 M.C. Switch receiver to band B and adjust osc. trimmer on gang for correct dial reading.
- (5) Set signal generator at 1400 K.C. Switch receiver to band A and adjust broadcast trimmer (located at front of chassis - see diagram below) for correct dial reading. Also adjust antenna trimmer on gang to resonance.
- (6) Set signal generator at 18 M.C. - Switch receiver to band C and adjust the short wave trimmer while rocking the pointer past 18 M.C. on the dial to the combination giving the greatest output.
- (7) Set signal generator at 600 K.C. - Switch receiver to band A and rock pointer past 600 on dial while adjusting the broadcast padder (located adjacent to gang condenser) to combination giving the greatest output reading.
- (8) Readjust broadcast and ant. trimmers at 1400 K.C. (Same as No.5)



Tube Position

Dial and Drive Assembly

26-122	Airplane Dial Scale	\$.75
32-10	Drive Belt	.20
34-49	Condenser Shaft Gear	.25
34-51	Lower Pinion and Gear	.15
59-40	Special Z Pointer	.15
59-41	Split Second Pointer	.10
80-60	Tension Pulley Spring	.05
80-118	Dial Spring	.15
80-127	Dial Glass Retainer Spring	.05
83-407	Dial Light Diffusion Strip	.05
93-273	Black Bakelite Pointer Washer	.01
97-91	Lower Gear Stud	.01
100-50	2 Volt .06 Amp. Dial Light Lamp (Bayonet)	.30
192-16	Dial Glass	.25
192-10	Dial Glass Gasket.....	.10
S-3780	Shaft Pulley and Sleeve and Pinion Assembly	.35
S-4301	Dial Light Socket and Clip Assem. (Bayonet)	.10
S-4340	Tension Pulley and Arm Assem.	.15
S-4342	Drive Shaft and Pulley Assembly	.35

Coils and Chokes

95-358	1st I.F. Transformer	1.25
95-359	2nd I.F. Transformer	1.25
S-2778	R.F. Choke	.15
S-4669	Oscillator Coil Assembly	1.25
S4735	Antenna Coil Assembly	1.25

Condensers

22-171	.05 Mfd. 600 Volt	.20
22-182	.00025 Mfd. 600 Volt	.12
22-188	.02 Mfd. 400 Volt	.15
22-199	.5 Mfd. 200 Volt	.35
22-205	200-550 Mmfd. Osc. Padder	.35
22-250	.05 Mfd. 200 Volt	.15
22-289	50 Mmfd. Volt	.12
22-305	2-35 Mmfd. Trimmer	.15
22-327	.02 Mfd. 200 Volt	.15
22-384	.0015 Mfd. 600 Volt	.20
22-408	2-35 Mmfd. Trimmer	.25
22-482	Two Gang Variable	2.50
22-485	.005 Mfd. 600 Volt	.35
22-486	.0012 Mfd. 600 Volt	.15
22-487	.05 Mfd. 400 Volt	.15
22-492	.002 Mfd. 600 Volt	.20

Resistors

63-278	99 M Ohm 1/4 Watt	.20
63-293	990 M Ohm 1/4 Watt	.20
63-361	5 M Ohm 1/4 Watt	.20
63-399	75 M Ohm 1/4 Watt	.20
63-400	250 M Ohm 1/4 Watt	.20
63-441	1 Megohm 1/4 Watt	.20
63-481	400 M Ohm 1/4 Watt	.20

Resistors (Cont'd)

63-521	50 M Ohm Tone Control	\$.70
63-539	40 M Ohm 1/4 Watt	.20
63-541	1 Megohm Volume Control and Switch	1.00

Parts for S -4680 Economy Pack

(Used with 6 Volt Storage Battery)

S -4680	Economy Pack Complete.....	10.00
20-146	R.F.Choke	.20
22-199	.5 Mfd. 200 V. Condenser	.35
22-243	.01 Mfd. 400 V. Condenser	.15
22-455	.01 Mfd. 1200 V. Condenser	.15
22-522	2-8 Mfd. Electrolytic Cond. 250 V.	1.25
63-394	200 Ohm Resistor 1/2 Watt	.20
78-141	Vibrator Wafer Type Socket	.15
95-345	Filter Choke	.75
95-381	Power Transformer	2.00
100-39	Dial Lights 2.9 V. .17 Amp. (Bayonet Type)	.15
190-8	Vibrator	5.00
S-4659	Battery Cable Plug and Clip Assem.	1.25
S-4663	Power Unit Cable and Plug Assem.	.50

Special Parts

23-12	Tube Socket Contact Jumper (Large)	.02
23-13	Tube Socket Contact Jumper (Small)	.02
63-543	Resistor Plug (For Air Cell Operation)	.50
100-53	Ballast Tube (For Dry Cell Operation)	1.25

Miscellaneous

46-123	Tone Control Knob	.20
46-127	Tuning and Volume Control Knob	.20
46-169	Band Selector Switch Knob	.20
49-162	6" P.M. Speaker (5F134)	6.50
	Cone and Voice Coil for 49-162	2.00
	Output Transformer for 49-162	2.00
49-164	8" P.M. Speaker (5F166)	8.00
	Cone and Voice Coil for 49-164	2.50
	Output Transformer for 49-164	2.50
52-85	Battery Cable and Plug	.90
78-128	Speaker Plug Socket	.10
78-163	Battery Cable Plug Socket	.15
78-164	Power Supply Cable Plug Socket	.15
78-165	#1C7 Wafer Type Socket	.15
78-166	#1D5 Wafer Type Socket	.15
78-168	#1F7 Wafer Type Socket	.15
78-169	#1H6 Wafer Type Socket	.15
78-170	#1J6 Wafer Type Socket	.15
83-433	Ant. & Grnd. Term Strip	.15
85-89	Band Selector Switch	1.00
95-382	Audio Transformer	1.50
126-127	Tube Shields	.10
159-13	Plug Button	.05
188-2	Shaft Retaining Ring	.01

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION,
CHICAGO, ILLINOIS, U.S.A.
September 25, 1936



RADIO TUBES

TYPE	CLASS	OPERATION	ELECTRODE POTENTIALS (VOLTS)				ELECTRODE CURRENTS				AVERAGE COEFFICIENTS			INTERELECTRODE CAPACITANCE	
			HEATER	PLATE	G ₁	G ₂	G ₃	G ₄	PLATE M.A.	WATTS ON M.A.	PLATE RESIS- TANCE OHMS	TRANS- MUTATION FACTOR	RATED POWER PLATE LOAD WATTS	GRID M.M.F.D.	PLATE M.M.F.D.
5Y3 (54)	RECTIFIER	FULL-WAVE HIGH VACUUM	5.0	400 ¹					2.0	110					
6X4-Q (544)	RECTIFIER	FULL-WAVE HIGH VACUUM	5.0	300 ¹					1.5	110					
6AR-0 (646)	RECTIFIER	OSCILLATOR MODULATOR	6.3	200	-h	250 ¹	100 ¹	-3	0.3	3.3	4.0	3.2		0.03	12.5
636 (64)	DIODE TRIODE	DETECTOR AMPLIFIER	6.3	250	-2				0.3	0.8		100		1.70	3.00
654-0 (650)	TRIODE	AMPLIFIER	6.3	250	-8				0.3	8.0		20		1.80	4.00
6F5-0 (675)	TRIODE	AMPLIFIER	6.3	250	-2				0.3	0.9		100		2.00	6.00
6F6-0 (676)	PENTODE	POWER AMPLIFIER	6.3	250	-16.5	250			0.7	34.0	6.3	200	1000		
6H6-0 (686)	TWIN DIODE	DETECTOR	6.3	100 ¹					0.3	8.0				0.02	
6J7-0 (677)	PENTODE	AMPLIFIER	6.3	250	-3	100	6		0.3	2.0	0.5	3400		.005	7.00
6J7-G (677)	PENTODE	VARIABLE-MU AMPLIFIER	6.3	250	-3 ¹	100	6		0.3	7.0	1.7	1160		.005	7.00
6L4-0 (614)	TETRODE POWER AMPLIFIER		6.3	875	-17.5	250			0.9	57.0	2.5	500	4000		
6L7-0 (677)	PENTAPART MILE		6.3	250	-6	150 ¹	18 ¹		0.3	3.3	0.5 ¹	35 ¹		.000	6.5
6L7-0 (617)	PENTAPART VARIABLE MU AMPLIFIER		6.3	250	-3 ¹	100 ¹	-3 ¹		0.3	0.3	0.5	880		.000	6.5
6N4-0 (684)	DIODE TRIODE	POWER AMPLIFIER	6.3	400 ¹	0				0.8 ¹	48 ¹		20	1000		
6P7-0 (687)	DIODE TRIODE	AMPLIFIER CLASS B	6.3	300	0				0.8	128 ¹			10000 ¹		
6P7-0 (617)	DIODE TRIODE	AMPLIFIER CLASS A	6.3	294	-8				0.8	7.0		7	40000		
6P7	TRIODE PENTODE	TRIODE AMPLIFIER	6.3	100	-3				0.3	3.5		8			
6P7	TRIODE PENTODE	TRIODE AMPLIFIER	6.3	250	-3	100			0.3	6.5	1.5	900		2.00	3.00
6P7-0 (677)	DIODE TRIODE	DETECTOR AMPLIFIER	6.3	250	-3				0.3	1.1		70		.008	5.20
6P7-0 (677)	DIODE TRIODE	DETECTOR AMPLIFIER	6.3	250	-9				0.3	9.5		16			
6S5-0 (655)	RECTIFIER	FULL-WAVE HIGH VACUUM	6.3	350 ¹					0.6	75					
25A-0 (25-6)	PENTODE	AMPLIFIER CLASS A	25.0	96	-15	95	135		0.3	20.0	4.0	20	4500		
25Z4-0 (25-4)	RECTIFIER	HIGH VACUUM DOUBLER	25.0	125 ¹					0.3	85					

A - Also contains two diodes
B - Class B
C - Class A - Driver, both grids connected
D - Mixer Operation
E - Amplifier Operation

(a) R.M.S. per plate
(b) Grid Nos. 345
(c) Grid Nos. 224
(d) With 20,000 ohm dropping
resistor
(e) R.M.S. volts with 50,000 ohm
dropping resistor

(f) Peak volts applied to Grid #3
from Separate Oscillator
(g) Tied to cathode at socket
(h) 50,000 Automatic Biasing Resistor
(i) At -42.5 volts Gm 2 umhos

(j) Plate to Plate
(k) Minimum
(l) Peak. Zero signal plate current
per plate 17.5 m.a.
(m) Conversion Conductance
(n) Plate to Plate
(o) Min. applied peak oscillator volts.
(p) Developed D.C. bias on 50,000
grid resistor
(r) Signal applied to No.1 grid only
(s) Both Input and Output sections
(t) Output section
(u) Input section Plate Current

TYPE	CLASS	OPERATION	EMITTER	ELECTRODE POTENTIALS (VOLTS)				ELECTRODE CURRENTS				AVERAGE COEFFICIENTS				INTERELECTRODE CAPACITANCE					
				FILAMENT OR HEATER	PLATE	G ₁ (NEGATIVE)	G ₂	G ₃	G ₄	FILAMENT OR HEATER AMPS.	PLATE M.A.	G ₂ M.A.	G ₃ M.A.	PLATE RESISTANCE OHMS	TRANS-CONDUCTANCE MICRO-MHOS	AMPLIFICATION FACTOR	RATED PLATE LOAD OHMS	RATED POWER OUTPUT MILLI-WATTS	GRID-PLATE	MMFD.	INPUT
01-A	TRIODE	DETECTOR AMPLIFIER	F	5.0	22.5 45.0 90.0 135.0	4.5 9.0				0.25	2.5 3.0			11,000 10,000	725 800	8.0 8.0			8.1	3.1	2.2
10	TRIODE	AMPLIFIER CLASS A	F	7.5	250.0 350.0 425.0	22.0 31.0 39.0				1.25	10.0 18.0			6,000 5,150 5,000	1230 1550 1600	8.0 8.0 8.0	13,000 11,000 10,500	400 900 1500	7.0	4.0	3.0
12-A	TRIODE	DETECTOR OR AMPLIFIER	F	5.0	90.0 135.0 180.0	4.5 6.8 9.0 13.5				0.25	5.2 6.2 7.6			6,400 6,100 4,700	1575 1650 1800	8.5 8.5 8.5	5,300 9,000 10,550	35 130 285	8.1	4.0	2.0
		AMPLIFIER																			
15	PENTODE	AMPLIFIER	H	2.0	67.5 135	1.5 1.5	67.5 67.5			0.220	1.85 1.85	0.5 0.4		630,000 800,000	710 750	480 600			0.01	2.35	7.8
19	DUPLEX TRIODE	AMPLIFIER CLASS B	F	2.0	135.0 135.0	0.0 3.0				0.26	10.0 1.0						10,000 ⁽²⁾ 15,000 15,000	2100 1900 1600			
22	TETRODE	AMPLIFIER	F	3.3	135.0 135.0	1.5 1.5	45.0 67.5			0.13	1.7 3.7	0.6 1.3		755,000 325,000	375 800	270.0 160.0			.01	3.0	10.0
24	TETRODE	DETECTOR BIASED (1)	H	2.5	250.0 180.0 180.0 250.0	5.0 ⁽¹⁾ 1.6 3.0 3.0	20.0 ⁽²⁾ 75.0 90.0 90.0			1.75	0.1 4.0 4.0 4.0	1.0 1.5 1.5		400,000 400,000 600,000	1050 1000 1050	420.0 400.0 530.0			.007	5.3	10.5
		AMPLIFIER																			
26	TRIODE	AMPLIFIER	F	1.5	90.0 135.0 180.0	7.0 10.0 14.5				1.05	2.9 5.5 6.2			8,900 7,600 7,300	935 1100 1150	8.3 8.3 8.3			8.1	3.5	2.2
27	TRIODE	DETECTOR BIASED (2)	H	2.5	250.0 275.0 90.0 135.0 180.0 250.0	30.0 ⁽¹⁾ 33.0 ⁽¹⁾ 6.0 9.0 13.5 21.0				1.75	0.2 2.7 4.5 5.0 6.2						14,000 13,000 18,700 24,000	30 80 165 300	3.3	3.5	3.0
		AMPLIFIER																			
30	TRIODE	DETECTOR OR AMPLIFIER	F	2.0	90.0 135.0 180.0	4.5 9.0 13.5				0.06	2.5 3.0 3.1			11,000 9,000 9,000	850 1000 1000	9.3 9.3 9.3	15,000	15	6.0	3.7	2.1
		AMPLIFIER																			
31	TRIODE	POWER AMPLIFIER	F	2.0	135.0 180.0	22.5 30.0				0.13	8.0 12.3			4,100 3,500	925 1050	3.8 3.8	7,000 5,700	185 375	5.7	3.5	2.2
32	TETRODE	DETECTOR BIASED (5)	F	2.0	135.0 180.0 135.0 180.0	4.5 ⁽⁴⁾ 5.0 ⁽⁴⁾ 3.0 3.0	45.0 67.5 67.5 67.5			0.06	0.2 0.2 1.7 1.7	0.4 0.4		950,000 950,000 1,200,000	640 650	510.0 780.0	100,000 100,000		.015	6.0	11.7
		AMPLIFIER																			
33	PENTODE	AMPLIFIER CLASS A	F	2.0	135.0	13.5	135.0			0.26	14.5	3.0		50,000	1450	70.0	7,000	700	.9	8.9	11.1
		SUPER-CONTROL R.F. AMPLIFIER																			
34	PENTODE		F	2.0	67.5 135.0 180.0	3.0 3.0 3.0	67.5 67.5 67.5			0.06	2.7 2.8 2.8	1.1 1.0 1.0		400,000 600,000 1,000,000	560 ⁽⁴⁾ 600 ⁽⁴⁾ 620 ⁽⁴⁾	224.0 360.0 620.0			.02	5.8	11.6
35	USE TYPE 51																				
36	TETRODE	DETECTOR BIASED	H	6.3	100.0 180.0 250.0 100.0 135.0 180.0 250.0	5.0 ⁽²⁾ 6.0 ⁽²⁾ 8.0 ⁽²⁾ 1.5 1.5 3.0 3.0	55.0 67.5 90.0 55.0 67.5 90.0 90.0			0.30	0.2 0.2 0.2 2.8 3.1 3.2			550,000 475,000 500,000 550,000	850 1000 1050 1080	470.0 475.0 525.0 595.0					
		AMPLIFIER																			
37	TRIODE	DETECTOR BIASED	H	6.3	90.0 135.0 180.0 250.0 100.0 135.0 180.0 250.0	10.0 ⁽²⁾ 15.0 ⁽²⁾ 20.0 ⁽²⁾ 28.0 ⁽²⁾ 6.0 9.0 13.5 18.0				0.30	0.2 0.2 0.2 2.5 4.1 4.3 7.5								2.0	3.5	2.2
		AMPLIFIER																			
38	PENTODE	AMPLIFIER CLASS A	H	6.3	100.0 135.0 180.0 250.0	9.0 13.5 18.0 25.0	100.0 135.0 180.0 250.0			0.30	7.0 9.0 14.0 22.0	1.2 1.5 2.4 3.8		140,000 130,000 110,000 100,000	875 925 1050 1200	120.0 120.0 120.0 120.0	15,000 13,500 11,600 10,000	270 550 1000 2500	0.3	3.5	7.5

39-44	PENTODE	SUPER-CONTROL R.F. AMPLIFIER	H	6.3	90.0	3.0	90.0	0.30	5.6	1.6	375,000	960 ⁽⁷⁾	350.0	.007	3.5	10.0
		MODULATOR			90.0	3.0	90.0		5.8	1.4	750,000	1000 ⁽⁷⁾	750.0			
					90.0	3.0	90.0		5.8	1.4	1,000,000	1050 ⁽⁷⁾	1050.0			
41	PENTODE	AMPLIFIER CLASS A	H	6.3	100.0	7.0	100.0	0.40	9.0	1.6	103,500	1450	150.0			
					135.0	10.0	135.0		12.5	2.2	94,000	1600	150.0			
					180.0	13.5	180.0		18.5	3.0	81,000	1850	150.0			
					250.0	18.0	250.0		32.0	5.5	68,000	2200	150.0			
42	PENTODE	AMPLIFIER CLASS A	H	6.3	250.0	16.5	250.0	0.70	34.0	6.5	100,000	2200	222.0			
					96.0	15.0	96.0	0.30	20.0	4.0	45,000	2000	90.0			
43	PENTODE	AMPLIFIER CLASS A	H	25.0 ⁽¹⁾	135.0	20.0	135.0	0.30	34.0	7.0	35,000	2300	80.0			
44	USE TYPE 39-44															
45	TRIODE	AMPLIFIER CLASS A	F	2.5	180.0	31.5	180.0	1.50	31.0		1,900	1850	3.5		7.2	3.0
					250.0	50.0	250.0		36.0		1,750	2000	3.5			
					275.0	56.0	275.0				1,670	2100	3.5			
46	TETRODE	AMPLIFIER CLASS A AMPLIFIER CLASS B	F	2.5	250.0 ⁽¹⁾	33.0	250.0 ⁽²⁾	1.75	22.0		2,380	2250	5.5			
					300.0	± .0 ⁽¹⁾	± .0 ⁽²⁾		4.0 ⁽³⁾				6.400			
					400.0	± .0 ⁽¹⁾	± .0 ⁽²⁾		6.0 ⁽³⁾				1,300			
47	USE TYPE PZ												1,450			
50	TRIODE	AMPLIFIER CLASS A	F	7.5	350.0	63.0	350.0	1.85	45.0		1,900	2000	3.8		9.0	5.0
					400.0	70.0	400.0		55.0		1,800	2100	3.8			
					450.0	84.0	450.0		55.0		1,800	2100	3.8			
51	TETRODE	VARIABLE-MU AMPLIFIER MODULATOR	H	2.5	180.0	3.0	180.0	1.75	6.3	2.5	300,000	1160 ⁽⁴⁾	350.0		.007	5.0
					250.0	3.0	250.0		6.5	2.5	400,000	1110 ⁽⁴⁾	445.0			10.0
53	DUPLEX TRIODE	AMPLIFIER CLASS B AMPLIFIER CLASS A DRIVER ⁽²⁾	H	2.5	250.0	± 0	250.0	2.0	14.0 ⁽³⁾				8,000			
					300.0	± 0	300.0		17.5				10,000			
					250.0	-5.0	250.0		6.0		11,300	3100	35.0			
					300.0	-6.0	300.0		7.0		11,000	3200	35.0			
55	DUPLEX DIODE TRIODE	AMPLIFIER CLASS A ⁽²⁾	H	2.5	135.0	10.5	135.0	1.00	3.7		11,000	750	8.3		1.5	4.3
					180.0	13.5	180.0		6.0		8,500	975	8.3			
					250.0	20.0	250.0		8.0		7,500	1100	8.3			
56	TRIODE	DETECTOR BIASED ⁽²⁾ AMPLIFIER	H	2.5	250.0	20.0 ⁽⁴⁾	250.0	1.00	0.2		9,500	1450	13.8		3.2	2.2
					250.0	13.5	250.0		5.0							
57	PENTODE	DETECTOR BIASED ⁽¹⁾	H	2.5	250.0	1.95 ⁽¹⁾	250.0	1.00	0.2				250,000		.007	5.2
					250.0	33.0	250.0		0.2				500,000			6.6
					250.0	3.86 ⁽²⁾	250.0		0.2				250,000			
					250.0	4.30 ⁽²⁾	250.0		0.2				500,000			
					250.0	3.0	250.0		2.0	0.5	1,500,000	1225 ⁽³⁾	1500.0			
58	PENTODE	VARIABLE-MU AMPLIFIER MODULATOR	H	2.5	250.0	3.0	250.0	1.00	8.2	3.0	800,000	1800 ⁽⁴⁾	1280.0		.007	5.2
					250.0	10.0 ⁽²⁾	250.0									6.8
59	PENTODE	AMPL. CLASS A TRIODE AMPL. CLASS B TRIODE PER TUBE TWO TUBES	H	2.5	250.0	28.0	250.0	2.00	25.0		2,400	2500	6.0			
					250.0	18.0	250.0		35.0	9.0	40,000	2800	100.0			
					400.0	± .0 ⁽²⁾	400.0		13.0 ⁽⁴⁾				6,000 ⁽²⁾			

- For use as a grid leak detector 250-volts plate; screen up to 70-volts; capacity .00025-mfd; resistance 1-5 megohms; grid return to cathode.
- For use as a grid leak detector 90-volts plate; capacity .00025-mfd; resistance 1-5 megohms; grid return to cathode.
- Screen G₂, +20 to +45-volts; adjust G₁ to give 0.1 ma. with no a.c. input signal.
- Adjust G₁ bias for plate current of 0.6 ma. with no a.c. input signal.
- For use as a grid leak detector 135-volts plate; .00025-mfd; resistance 1-5 megohms; screen up to 45-volts; plate load 100,000 ohms; grid return to cathode.
- Mutual conductance at G₁ -22.5 volts is approximately 15 μ-mhos.
- Mutual conductance at G₁ -42.5 volts is approximately 2 μ-mhos.
- This grid bias is minimum for oscillator peak potential of 6.0 volts.
- Total harmonic distortion 1%.
- Heater to cathode potential should not exceed 90 volts d.c. as measured between negative heater terminal and cathode.
- Grid G₂ adjacent to plate is connected to plate.
- G₁ and G₂ are connected together to serve as control grid.
- Peak plate current (per tube) 150 ma. and maximum plate dissipation (per tube) 10 watts.
- Peak plate current (per tube) 200 ma. and maximum plate dissipation (per tube) 10 watts.
- Maximum continuous power output for two tubes 40-watts.
- Maximum signal potential (rms per tube) 40 volts.
- Maximum signal potential (rms per tube) 40 volts.
- Mutual conductance at G₁ -40 volts is approximately 15.0 μ-mhos, and at -50 is 0.
- Diode units used for half-wave and full-wave detection, and are arranged.
- Screen G₂, +20 to 60-volts; adjust G₁ to give 0.2 ma. with input signal.
- Out-of-of cathode current occurs at -7 volts G₁.
- Suppressor G₃ connected to cathode at screen.
- Mutual conductance at G₁ -40 volts is approximately 10 μ-mhos and at -50 is 2.
- This grid bias is minimum for oscillator peak voltage of 9.0-volts.
- Grids G₂ and G₃ are connected to plate when operated as class "A" amplifier.
- Grid G₂ tied to cathode.
- Grid G₂ is screen only.
- Grids G₁ and G₂ tied to plate.
- Grid G₃ tied to plate.
- Dynamic peak plate current 200 ma. and average plate dissipation 10-watt (max.).
- Plate to plate.

TYPE	CLASS	OPERATION	EMITTER	ELECTRODE POTENTIALS (VOLTS)				ELECTRODE CURRENTS (MA)				PLATE RESIS- TANCE OHMS	TRANS- CONDUCTANCE MICRO- MHO'S	AMPLIFI- CATION FACTOR	RATED PLATE LOAD OHMS	RATED POWER OUTPUT MILLI- WATTS	CAPACITANCE MMFD.	
				FILAMENT OR HEATER	PLATE	G ₁ (NEGATIVE)	G ₂	G ₃	G ₄	FILAMENT OR HEATER AMPS	PLATE MA.	G ₂ MA	G ₃ MA				GRID PLATE	INPUT OUTPUT
71-A	TRIODE	AMPLIFIER CLASS A	F	6.0	90.0 135.0 180.0	16.5 27.0 40.5				0.25	10.0 17.3 20.0			3.0 3.0 3.0	3,000 3,000 4,800	125 400 790	7.6	3.7 2.1
75	DUPLEX DIODE TRIODE	AMPLIFIER CLASS A (3)	H	6.3	250.0	2.0				0.30	0.8			100.0			1.7	1.7 3.8
76	TRIODE	DETECTOR BIASED(2) AMPLIFIER	H	6.3	250.0 250.0	20.0 (4) 13.5				0.30	0.2 5.0			15.8			3.2	3.2 8.2
77	PENTODE	DETECTOR BIASED (2) AMPLIFIER CLASS A	H	6.3	100.0 250.0 100.0 250.0	1.95 (4) 1.95 (4) 4.30 (4) 1.50 3.0	36.0 50.0 100.0 60.0 100.0	(4)		0.30	0.2 0.2 1.7 2.3				250,000 250,000 600,000 650,000 1,500,000	1400 1650 1700 1100 1250	.007	4.4 10.6
78	PENTODE	AMPLIFIER CLASS A	H	6.3	90.0 180.0 250.0	3.0 (4) 3.0 (4) 3.0 (4)	90.0 75.0 100.0 125.0	(4)		0.30	5.4 4.0 7.0 10.5	1.5 2.0 2.0 3.0			400.0 1100 1150.0 990.0		.007	4.4 10.6
79	DUPLEX TRIODE	AMPLIFIER CLASS B	H	6.3	180.0 (4)	± 1.0				0.60	7.5 (4)					5500 (4)		
80	DUPLEX DIODE	RECTIFIER FULL-WAVE HALF-WAVE	F	5.0	350.0 (4) 400.0 (4) 650.0 (4) 350.0 (5) 400.0 (5) 550.0 (5)					2.00	125.0 110.0 135.0 250.0 220.0 270.0							
81	DIODE	RECTIFIER HALF-WAVE	F	7.5	700.0					1.25	85.0 (4)							
82 (AF)	DUPLEX DIODE	RECTIFIER FULL WAVE	F	2.5	500.0 (47)					3.00	125.0 (4)				(4)			
83 (AG)	DUPLEX DIODE	RECTIFIER FULL-WAVE	F	5.0	500.0 (47)					3.00	250.0 (4)				(4)			
84	DUPLEX DIODE	RECTIFIER FULL-WAVE	H	6.3	350.0 (51)					0.60	50.0							
85	DUPLEX TRIODE	AMPLIFIER CLASS A (46)	H	6.3	135.0 180.0 250.0	10.5 13.5 20.0				0.30	3.7 6.0 8.0				25,000 20,000 20,000	75 160 350	1.6	1.6 4.3
89	PENTODE	AMPLIFIER CLASS A TRIODE AMPLIFIER CLASS A PENTODE AMPLIFIER CLASS B TRIODE-PER TUBE TWO TUBES	H	6.3	160.0 180.0 250.0 100.0 135.0 180.0 250.0 250.0	20.0 22.5 31.0 10.0 13.5 18.0 25.0 ± 0.0 (4)	150.0 (4) 180.0 (4) 250.0 (4) 100.0 (4) 135.0 (4) 180.0 (4) 250.0 (4) ± 0.0 (4)	(4) (4) (4) (4) (4) (4) (4) (4)		0.40	17.0 20.0 32.0 9.5 14.0 20.0 32.0 3.0 (4)	1.5 1.6 2.2 3.0 5.5		1425 1550 1600 1250 1250 1550 1600 1800	7,000 6,500 5,500 10,700 9,200 8,000 6,750 13,600	300 400 500 580 760 1600 3400 2500		
99 UV	TRIODE	DETECTOR OR AMPLIFIER	F	3.3	90.0	4.5				.06	2.5			6.6			3.3	2.5 2.5
99 UX	TRIODE	DETECTOR OR AMPLIFIER	F	3.3	90.0	4.5				.06	2.5			6.6			3.3	2.5 2.5
GA	PENTODE	AMPLIFIER CLASS A	F	5.0	180.0	10.0	180.0 (55)			.85	25.0	7.5		60.0	7,000	800		
PZ	PENTODE	AMPLIFIER CLASS A	F	2.5	250.0	16.5	250.0 (55)			1.75	31.0	6.0		150.0	7,000	2700	1.5	3.7 13.2
PZH	PENTODE	AMPLIFIER CLASS A	H	2.5	250.0	16.5	250.0 (54)			2.00	36.0	8.2		98.0	6,600	3300		
WANDERLICH WANDERLICH AUTO	DUAL-GRID (DETECTOR, AMPLIFIER)		H H H	2.5 6.3	250.0 250.0	16.5 16.5				1.00 0.30	7.5 7.5			9.5 9.5			4.7 4.7	3.0 3.0
1A 6	HEPTODE	OSCILLATOR MODULATOR	F	2.0	135.0	(4)	135.0 (57) -3.0 (58)			.06	1.2	2.3 2.6						
1C 6	HEPTODE	OSCILLATOR MODULATOR	F	2.0	135.0 180.0	(4)	135.0 (57) 180.0 (58)			.120	1.3 1.5	2.6 2.0 3.3 2.0						

2A3	TRIODE	AMPLIFIER CLASS A PUSH PULL SELF BIAS PUSH PULL FIXED BIAS	F	2.5	250.0	45.0				2.5	60.0		800	5250	4.2	2,500	3500	13.	9.	4.
2A5	PENTODE	AMPLIFIER CLASS A	H	2.5	250.0	16.5	250.0	(34)		1.75	34.0	5.5	100,000	2200	220.0	5,000	10000			
2A6	DUPLEX DIODE TRIODE	AMPLIFIER CLASS A	H	2.5	250.0	2.0				0.8	0.8		91,000	1100	100.0	7,000	3000	1.7	1.7	3.8
2A7	HEPTODE	OSCILLATOR MODULATOR	H	2.5	250.0	6.0	250.0	1000 ⁽³⁴⁾		0.80	4.0	3.5	300,000	475 ⁽³⁴⁾						
2B7	DUPLEX DIODE PENTODE	AMPLIFIER CLASS A	H	2.5	250.0	3.0	100.0	(34)		0.80	5.8	1.7	300,000	950 ⁽³⁴⁾	285.0					
		AMPLIFIER R.F. OR IF	H	2.5	250.0	3.0	75.0	(34)		0.80	3.4	0.9	1,000,000	840 ⁽³⁴⁾	840.0					
		AMPLIFIER A.F.	H	2.5	250.0	3.0	100.0	(34)		0.80	6.0	1.5	800,000	1000 ⁽³⁴⁾	800.0					
		RECTIFIER FULL-WAVE	F	5.0	500.0	4.5	50.0	(34)		0.80	9.0	2.3	650,000	1125 ⁽³⁴⁾	730.0	200,000				
5Z3	DUPLEX DIODE	AMPLIFIER CLASS B	H	6.3	250.0	1.0				3.00	250.0					8,000	8000			
6A6	DUPLEX TRIODE	AMPLIFIER CLASS A	H	6.3	250.0	1.0				1.8	14.0 ⁽³⁴⁾					10,000	10000			
6A7	HEPTODE	IDENTICAL TO 2A7 EXCEPT HEATER	H	6.3	250.0	1.0				0.30	6.0		11,300	3100	35.0					
6B7	DUPLEX DIODE PENTODE	IDENTICAL TO 2B7 EXCEPT HEATER	H	6.3	250.0	1.0				0.30	7.0		11,000	3200	35.0					
6C6	PENTODE	DETECTOR BIASED	H	6.3	250.0	1.95	50.0	(23)		0.30	0.2					250,000	500,000	.007	5.2	6.8
		AMPLIFIER CLASS A	H	6.3	250.0	3.0	100.0	(23)		0.30	0.2					250,000	500,000			
6D6	PENTODE	VARIABLE MU AMPLIFIER MODULATOR	H	6.3	250.0	10.0 ⁽²³⁾	100.0	(23)		0.30	8.2	3.0	800,000	1600 ⁽³⁴⁾	1280.0			.007	5.2	6.8
6F7	TRIODE PENTODE	OSCILLATOR MODULATOR	H	6.3	250.0	3.0	100.0	(23)		0.3	3.5	1.0	17,800	450	8.0			.008	3.2	12.5
12A5	PENTODE	AMPLIFIER CLASS A	H	12.6	180.0	27.0	180.0	(23)		0.30	36.0	9.0	32,000	2500	80.0	3800	3.5			
12A7	PENTODE	OUTPUT PENTODE	H	12.6	180.0	27.0	180.0	(23)		0.30	36.0	9.0	35,000	2500	80.0	3800	3.5			
12Z3	DIODE	RECTIFIER HALF WAVE	H	12.6	180.0	9.0	100.0			0.30	7.0	1.2	140,000	875	120.0	15,000	270	0.3	3.5	7.5
12Z5	DUPLEX DIODE	RECTIFIER FULL-WAVE	H	12.6	180.0	13.5	135.0			0.30	9.0	1.5	130,000	925	120.0	13,500	580			
25Z5	DUPLEX DIODE	VOLTAGE DOUBLER	H	25.0	250.0	18.0	180.0			0.30	14.0	2.4	110,000	1050	120.0	11,600	1000			
		RECTIFIER FULL-WAVE	H	25.0	250.0	25.0	250.0			0.30	30.0	3.8	100,000	1200	120.0	10,000	2500			

1. For use as a grid leak detector 250-volts plate; screen up to 70-volts; capacity .00025-μf; resistances 1-5 megohms; grid return to cathode.
20. Diode units in grid leak detector and full-wave detector, and are arranged as follows:
21. Screen grid, 20 to 60 volts, adjust G₁ to give 0.2 ma. with input signal.
22. Cut-off of cathode current occurs at -7 volts G₁.
23. Suppressor G₂ connected to cathode at socket.
24. Mutual conductance at G₁ 40 volts is approximately 10 mhos and at -60 is 2.
25. This grid class is minimum for oscillator peak voltage of 9.0-volts.
26. Grids G₂ and G₃ are connected to plate when operated as class "A" amplifier.
27. Grid G₃ tied to cathode.
28. Grid G₃ is screen only.
29. Grids G₁ and G₂ tied together and average dissipation is 1.5-watts (max.).
30. Grid G₃ tied to plate.
31. Dynamic peak plate current 200 ma. and average plate dissipation 10-watt (max.).
32. Plate to plate.
33. The triode unit is bi-mu and the diode units are used in various detector arrangements.
34. Grid G₃ connected to cathode at socket as suppressor.
35. Both the internal shield surrounding plate and grid G₁ tied internally to pin 3.
36. Mutual conductance approximately 0 (cathode current cut-off) at G₁ -7.5 volts.
37. Mutual conductance at G₁ -55 volts is approximately 10, and at -52.5 is 2.
38. Mutual conductance at G₁ -55 volts is approximately 10, and at -52.5 is 2.
39. Mutual conductance at G₁ -45 volts is approximately 10, and at -52.5 is 2.
40. Both internal shield surrounding plate and cathode connected internally to pin 5.
41. Average plate dissipation 7-watts (max.).
42. Static plate current 7.5 ma. and dynamic peak plate current (per plate) 90 ma. (max.).
43. With average power in-put of 360 milli-watts applied between grids G₁ and G₂.
44. Operating with condenser in-put filter.
45. Operating with choke in-put filter of 20-henry (min.).
46. Two tubes operated as full-wave rectifier delivers 170 ma. (max.) at 700 plate volts r.m.s. (max.).
47. Maximum peak inverse potential 1400-volts.
48. Maximum peak plate current 400 ma.
49. Approximate internal drop 15 volts.
50. Maximum peak plate current should not exceed 800 ma.
51. Operating with either condenser or choke in-put to filter.
52. Grids G₁ and G₂ tied together and average dissipation 0.35 watts (max.).
53. Dynamic peak plate current 75 ma. (max.).
54. With a plate load of 9400-ohms nominal power output is 3600 milli-watts.
55. Grid G₂ tied to center of filament.
56. Grid G₂ operating in oscillator circuit feeding 50,000 ohms.
57. Grids G₁ and G₂ connected together.
58. Grid G₂ operating as control grid for modulator.
59. Conversion conductance 475 at -3 volts grid G₂, and 2 at -50 volts.
60. Cathode current cut-off at -17 volts G₁.
61. Cathode current cut-off at -21 volts G₁.
62. Cathode current cut-off at -21 volts G₁.
63. Heater-cathode potential should not exceed 100-volts.
64. G₁ tap on heater to permit dual operation.
65. Conversion conductance 275 at -3 volts grid G₂, and 4 at -22.5 volts.
66. With average power of 360 milli-watts applied between grids.
67. Static plate current, dynamic peak plate current 125 ma.
68. Connect the two grids together at socket; likewise the two plates.
69. Depends on design factors of class B amplifier. In general between 20,000 and 40,000 ohms.
70. Applied through 20,000 ohm dropping resistor.
71. Conversion Conductance at -14 volts on G = 4.0

— PHYSICAL CHARACTERISTICS —													
TYPE	TYPE BULB	TYPE BASE	TERMINAL			ARRANGEMENT			PIN NO.			OVERALL HEIGHT (MAX.) INCHES	DIAMETER (MAX.) INCHES
			1	2	3	4	5	6	7	TOP CAP			
Q1-A	ST-14	M-4	F	P	01	F						4.666	1.015
10	ST-17	M-4	F	P	01	F						5.885	2.186
12 A	ST-14	M-4	F	P	01	F						4.666	1.015
15	ST-12C	S-6	H	P	02	K	H				01	4.531	1.063
19	ST-18	S-6	H	P ₂	0 ₂	0 ₂	P ₂	H				4.850	1.063
22	ST-14C	M-4	F	P	02	F					01	5.081	1.015
24	ST-14C	M-6	H	P	02	K	H				01	5.081	1.015
26	ST-14	M-4	F	P	01	F						4.666	1.015
27	ST-12	S-6	H	P	01	K	H					4.850	1.063
30	ST-12	S-6	F	P	01	F						4.850	1.543
31	ST-12	S-4	F	P	01	F						4.850	1.543
33	ST-14C	M-4	F	P	02	F					01	5.031	1.015
35	ST-14	M-6	F	P	01	02	F					4.666	1.015
38	ST-14C	M-4	F	P	02						01	5.081	1.015
39	ST-12C	S-6	H	P	02	K	H					4.851	1.063
41	ST-12	S-6	H	P	02	01	K	H				4.850	1.543
42	ST-14	M-6	H	P	02	01	K	H				4.666	1.015
43	ST-14	M-6	H	P	02	01	K	H				4.666	1.015
45	ST-14	M-4	F	P	01	F						4.666	1.015
46	ST-17	M-6	F	P	01	02	F					5.425	2.186
50	ST-21	M-4	F	P	01	F						6.250	2.643
61	ST-14C	M-6	H	P	02	K	H				01	5.081	1.031
53	ST-14	M-7	H	P ₂	01 ^a	K	01 ^b	P ₂	H			4.666	1.015
55	ST-12C	S-6	H	P	P ₂	P ₂	K	H			01	4.851	1.063
56	ST-12	S-6	H	P	01	K	H					4.850	1.063
57	ST-12C	S-6	H	P	02	03	K	H			01	4.857	1.063
58	ST-12C	S-6	H	P	02	03	K	H			01	4.857	1.568
59	ST-16	M-7	H	P	02	01	03	K	H			5.376	2.045
71-A	ST-14	M-4	F	P	01	F						4.666	1.015
76	ST-12C	S-6	H	P	P ₂	P ₂	K	H			01	4.851	1.063
76	ST-12	S-5	H	P	31	K	H					4.850	1.663
77	ST-12C	S-6	H	P	02 ¹⁰⁰	03	K	H			01	4.851	1.063

— PHYSICAL CHARACTERISTICS —													
TYPE	BULB	TYPE BASE	TERMINAL			ARRANGEMENT			PIN NO.			OVERALL HEIGHT (MAX.) INCHES	DIAMETER (MAX.) INCHES
			1	2	3	4	5	6	7	TOP CAP			
78	ST-12C	S-6	H	P	02	03	K	H				4.851	1.063
79	ST-12C	S-6	H	P ₂	01 ^a	K	P ₂	H				4.851	1.063
80	ST-14	M-4	F	P	P ₂	F						4.666	1.015
81	ST-19	M-4	F	P	—	F						6.250	2.645
83	ST-14	M-4	F	P	P ₂	F						4.666	1.015
85	ST-15	M-4	F	P	P ₂	F						5.376	2.045
86	ST-12	S-6	H	P	P ₂	K	H					4.850	1.063
88	ST-12C	S-6	H	P	P ₂	P ₂	K	H				4.851	1.063
89	ST-12C	S-6	H	P	02	03	K	H				4.851	1.063
99-07	ST-8	S-AM	F	P	F	01						5.000	1.045
99-08	ST-8	S-4	F	P	01	F						4.855	1.060
99-09	ST-14	M-5	F	P	01	02	F					4.666	1.015
99-10	ST-14	M-5	F	P	01	02	F					4.666	1.015
99-11	ST-14	M-7	H	P	02	01	03	K	H			4.666	1.015
99-12	ST-12C	S-6	H	0	P	0	H					4.438	1.063
99-13	ST-12C	S-12	M-6	0	P	0	K					4.438	1.063
99-14	ST-16	M-4	F	P	01	F						5.375	2.063
99-15	ST-14	M-6	H	P	02	01	K	H				4.666	1.015
99-16	ST-12C	S-6	F	P	02	01	03 ⁵	F				4.531	1.563
99-17	ST-12C	S-6	F	P	02	01	03 ⁵	F				4.531	1.563
99-18	ST-12C	S-6	H	P	P ₂	P ₂	K	H				4.631	1.563
99-19	ST-12C	S-7	H	P	03 ⁵	02	01	K	H			4.531	1.563
99-20	ST-12C	S-7	H	P	02	P ₂	P ₂	K	H			4.531	1.563
99-21	ST-15	M-4	F	P	P ₂	F						5.376	2.045
99-22	ST-14	M-7	H	P ₂	01 ^a	K	01 ^b	P ₂	H			4.666	1.015
99-23	ST-14	M-7											
99-24	ST-14	M-7											
99-25	ST-12C	S-6	H	P	02	03	K	H				4.631	1.563
99-26	ST-12C	S-6	H	P	02	03	K	H				4.631	1.563
99-27	ST-12C	S-7	H	P ₂	02 ^b	P ₂	01 ^a	K	H			4.531	1.563
99-28	ST-12	S-7	H	P	02	01	K	H ⁵	H			4.220	1.563
99-29	ST-12C	S-7	H	P ₂	02 ^b	K _P	P ₂	K _P	H			4.531	1.563
99-30	ST-12	S-4	H	P	K	H						4.850	1.563
99-31	ST-12	S-7	H	P ₂	K ₁	H ⁵	P ₂	P ₂	H			4.850	1.563
99-32	ST-12	S-6	H	P ₂	K ₁	K ₂	P ₂	P ₂	H			4.250	1.563

EXPLANATION OF SYMBOLS

CLASS OF TUBE

Tubes are assigned names according to the number of active elements, progressing outward from the cathode; a tube with a cathode, a control grid and a plate is classified as a triode.

NUMBER ELEMENTS	CLASSIFI- CATION	NUMBER ELEMENTS	CLASSIFI- CATION
2	Diode	6	Hexode
3	Triode	7	Heptode
4	Tetrode	8	Octode
5	Pentode		

Where two separate units are contained in a single bulb, a compound name is assigned -- i.e., double diode, diode triode, etc.

TUBE TYPE NUMBERS (New Tubes)

The first digit or digits indicates the filament voltage in steps of one volt. The figure 1 is used for voltages below 2.0; the figure 2, for voltages between 2.0 and 2.9; 3, voltages between 3.0 and 3.9; etc.

Next is a letter for serial designation. Rectifiers start at "Z" and work backwards; all other types start at "A".

The next number indicates the number of useful elements brought out to terminals.

ELECTRODE SYMBOLS

In a tube embodying a single set of elements, the electrodes are designated:

H - Heater	G - Grid
K - Cathode	P - Plate

PLATE NOMENCLATURE

In tubes with one plate the letter "P" is employed; tubes possessing two sets of elements, as the type 75 (duplex diode triode), the plate of the triode unit is identified by the letter "P"; the two diode plates as P₁ and P₂.

NOTE: P₁ and P₂ always designate the plates of a diode or rectifier.

Where duplex elements are contained in a bulb each set are uniformly correlated and designated by small letters, a, b, etc. For instance, the type 79 class "B" twin amplifier; the plate and grid of one unit should be designated as P_a and G_{1a}; the other unit P_b and G_{2b}.

GRID NOMENCLATURE

In tubes possessing more than one grid the notations G₁, G₂, etc. are used. G₁ is the grid nearest the cathode and the numbering runs consecutively toward the plate.

Where grids are not coaxially arranged but interlaced as in the co-planar or twin-grid construction, the grids are designated as No. A-1 grid and No. A-2 grid, etc.

PIN IDENTIFICATION

Point the pins toward observer so that the two heater pins (the heater pins are larger than the others) are at the top. With 5-prong tubes, rotate the base until the isolated pin is at the bottom; the two pins opposite at the top are the heater pins. Separate these two by a vertical line and the heater pin to the right is No. 1. The numbers assigned to the remaining pins progress consecutively in a clock-wise direction.

TUBE DIMENSIONS

When capital letters designate the various dimensions of a radio tube, generally the letter "A" represents the over-all height of the tube as measured from the extreme bottom of the pins to the extreme top of the tube. When a top cap is employed "A" represents the over-all height of the tube including the top cap.

- B, the largest diameter of the tube,
- C, the diameter of the dome,
- D, the height of the top-cap,
- E, the height from the bottom of the base to the top of the dome,
- F, the height of the base,
- G, the length of the pins,
- H, the diameter of the base.

When a single dimension is listed it represents the average dimension; when two are entered they are maximum and minimum.

BULB SHAPE AND DIMENSIONS

A letter indicates the shape of the bulb and a figure represents the number of eighths of inches as the maximum diameter of the bulb.

When the bulb is referred to as a S-16, it describes a "straight-sloped sided" bulb similar to that of the 01-A, the maximum diameter being 16/8" or 2".


An ST-12 bulb has a tee section at the top, commonly called a dome bulb, similar to the glass of the 25-Z-5 rectifier. "C" appended to the bulb designation indicates a top cap.

BASING CONNECTIONS FOR TUBES WITH OCTAL BASES

TYPE	NO. OF PRONGS	P O S I T I O N S								TOP CAP	OVERALL HEIGHT	MAXIMUM DIAMETER
		1	2	3	4	5	6	7	8			
5Y3	5	Xa	H	X	P1	X	P2	X	H	X	4-3/32"	1-13/16"
5W4	5		S	F	X	P1	X	P2	X	F	X	
5W4-G	5	Xa	F	X	P1	X	P2	X	F	X	4-3/32"	1-13/16"
6A8	8	S	H	P	G3-G5	G1	G2	H	K	G4		
6A8-G	8	Xa	H	P	G3-G5	G1	G2	H	K	G4	3-15/16"	1-9/16"
6B6	7	Xa	H	P	D	D	X	H	K	G1	3-15/16"	1-9/16"
6C5	6	S	H	P	X	G1	X	H	K	X		
6C5-G	6	S	H	P	X	G1	X	H	K	X	3-17/32"	1-9/16"
6F5	5	S	H	X	P	X	X	H	K	G1		
6F5-G	5	Xa	H	X	P	X	X	H	K	G1	3-15/16"	1-9/16"
6F6	7	S	H	P	G2	G1	X	H	K	X		
6F6-G	7	Xa	H	P	G2	G1	X	H	K	X	4-3/32"	1-13/16"
6H6	7	S	H	P1	K1	P2	X	H	K2	X		
6H6-G	7	Xa	H	P1	K1	P2	X	H	K2	X	3-17/32"	1-9/16"
6J7	7	S	H	P	G2	G3	X	H	K	G1		
6J7-G	7	S	H	P	G2	G3	X	H	K	G1	3-15/16"	1-9/16"
6K7	7	S	H	P	G2	G3	X	H	K	G1		
6K7-G	7	S	H	P	G2	G3	X	H	K	G1	3-15/16"	1-9/16"
6L6	7		S	H	P	G2	G1	X	H	K	X	
6L6-G	7	Xa	H	P	G2	G1	X	H	K	X	4-3/4"	2-1/16"
6L7	7	S	H	P	G2-G4	G3	X	H	K-G5	G1		
6L7-G	7	Xa	H	P	G2-G4	G3	X	H	K-G5	G1	3-15/16"	1-9/16"
6N6	7		S	H	P _{out} P _{in}	G _{out}	X	H	K	X		
6N6-G	7	Xa	H	P _{out} P _{in}	G _{out}	X	H	K	X	X	4-3/4"	2-1/16"
6N7-G	8	Xa	H	P1	G1	G2	P2	H	K	X	4-3/32"	1-13/16"
6P7	8	Xa	H	H	Pp	G2	Pt	Gt	K	G1p	3-15/16"	1-9/16"
6Q7-G	7	Xa	H	P	D	D	X	H	K	G1	3-15/16"	1-9/16"
6R7	7	S	H	P	D	D	X	H	K	G1		
6R7-G	7	Xa	H	P	D	D	X	H	K	G1	3-15/16"	1-9/16"
6X5-G	6	Xa	H	P	X	5	X	H	K	X	3-17/32"	1-9/16"
25A6	7	S	H	P	G2	G1	X	H	K-G3	X		
25A6-G	7	Xa	H	P	G2	G1	X	H	K-G3	X	4-3/32"	1-13/16"
25Z6	7	S	H	P2	K2	P1	X	H	K1	X		
25Z6-G	7	Xa	H	P2	K2	P1	X	F	K1	X	3-17/32"	1-9/16"


- X - Indicates omission of terminal.
 Xa - Pin provided but no internal connection. Corresponding contact in socket should be grounded to accommodate metal tube replacements.
 S - Shield(external in metal tubes; internal in G tubes). Should be grounded.
 NOTE - Base is viewed from bottom, with key pointing upward - 1st pin in clockwise direction is #1; 2nd is #2; etc.

CHASSIS No. 5519



SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8G	1st Det. Osc.	0	0	220	102	—5	97	6.1AC	0	0
6K7G	I. F.	0	0	220	102	0	—	6.1AC	0	0
6Q7G	2nd Det. A. V. C.	0	0	54	—3	—3	—	6.1AC	—3	0
6F6G	Power	0	0	210	225	—4	—	6.1AC	—5	—
5Y3	Rect.	0	225	—	305AC	—	305AC	—	225	—




**BOTTOM VIEW
OF SOCKET**

Line voltage 115 V. Antenna and ground disconnected. All voltages measured from point indicated to ground, using a 1000 ohm per volt meter.

ALIGNMENT PROCEDURE

- (1) Connect the output leads of the signal generator to the grid of the first detector and receiver ground lead. Also connect an output meter across the speaker leads.
- (2) Set the signal generator at 456 K.C. and carefully adjust the four I.F. trimmers to the point giving the greatest output reading. These I.F. transformers are of a very high gain, selectivity type, and the adjustments should be repeated several times for greatest accuracy.
- (3) Change the signal generator leads to the antenna and ground leads of the receiver.
- (4) Set the signal generator at 1400 K.C. Set the pointer on the receiver dial at the same frequency. First adjust the oscillator and then the detector trimmers on the gang condenser to the point giving the maximum reading on the output meter, using as small a signal from the generator as possible so as to prevent the A.V.C. action from affecting the output readings.
- (5) Reset the signal generator to 600 K.C.
- (6) Slowly rock the pointer past 600 K.C. on dial meanwhile adjusting the osc. padder (located beneath dial on front of chassis) to the combination giving the greatest output reading.
- (7) Repeat operation No. 4.



TUBE POSITION

PARTS PRICE LIST

	Models
	5R135
	5R123
	5R165
CONDENSERS	
22-82	.001 Mfd. 600 Volts.....\$.25
22-147	.0005 Mfd. 600 Volts..... .15
22-162	.0001 Mfd. 600 Volts..... .20
22-170	.1 Mfd. 400 Volts..... .25
22-224	.1 Mfd. 400 Volts..... .15
22-250	.05 Mfd. 200 Volts..... .15
22-327	.02 Mfd. 200 Volts..... .15
22-406	Two Gang Variable..... 2.50
22-435	.02 Mfd. 600 Volts..... .15
22-505	12 Mfd. Wet Elect. 325 Volts.... 1.00
22-506	16 Mfd. Wet Elect. 250 Volts.... 1.00
22-519	200-550 Mmfd. Padder..... .35
RESISTORS	
63-246	150 Ohm 1/4 Watt..... .20
63-258	490 M Ohm 1/4 Watt..... .20
63-280	49 M Ohm 1/4 Watt..... .20
63-293	990 M Ohm 1/4 Watt..... .20
63-376	190 M Ohm 1/4 Watt..... .20
63-545	12.5 M Ohm 1 Watt..... .20
63-546	80 Ohm 1/42 Watt..... .20
63-547	400 M Ohm Vol. Cont. and Switch .90
COILS AND CHOKES	
95-383	1st I.F. Transformer..... 1.25
95-384	2nd I.F. Transformer..... 1.25
S-4737	Ant. Coil Assem..... .60
S-4738	Osc. Coil Assem..... .60

	MISCELLANEOUS
46-122	Tuning Control Knobs..... .10
49-115	5" Dynamic Speaker (Model 123).. 4.50
	Cone & Voice Coil for 49-115 Spkr. 2.00
	Output Trans. for 49-115 Spkr.... 1.75
	Field Coil for 49-115 Speaker.... 1.50
49-144	10" Dynamic Speaker (Model 165) 8.00
	Cone & Voice Coil for 49-144 Spkr. 2.50
	Output Transformer for 49-144... 2.00
	Field Coil for 49-144..... 2.00
49-152	8" Dynamic Speaker (Model 135).. 6.50
	Cone & Voice Coil for 49-152 Spkr. 2.00
	Output Trans. for 49-152 Spkr.... 2.00
	Field Coil for 49-152 Speaker.... 2.00
78-128	Speaker Plug Socket..... .10
78-136	No. 5Y3 Wafer Socket..... .15
78-137	No. 6F6 Wafer Socket..... .15
78-148	No. 6Q7 Wafer Socket..... .10
78-150	No. 6K7 Wafer Socket..... .15
78-151	No. 6A8 Wafer Socket..... .15
85-84	Tone Control Switch..... .45
95-351	Power Trans. 115 V. 50-60 Cy.... 3.00
95-387	Power Trans. 25 Cy. All Voltage... 5.50
100-36	Dial Light Lamp 6.3 V. .25 Amp. .15
126-127	Tube Shields10
S-3717	Dial Pointer & Bushing Assem.... .25
S-4301	Dial Light Socket & Clip Assem... .10
S-4722	Dial Scale & Frame Assem..... .75

THESE PRICES SUPERSEDE ALL PREVIOUS QUOTATIONS AND ARE SUBJECT TO REGULAR DISCOUNT AND CHANGE WITHOUT NOTICE.

**ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS, U.S.A.
OCTOBER 26, 1936**

Made by

ZENITH RADIO CORPORATION

3620 IRON ST.

CHICAGO, ILL., U. S. A.

SERVICE MANUAL




1937

AUTOMOBILE RECEIVERS

MODELS
5-M-191
6-M-192
6-M-193
6-M-194
8-M-195

ZENITH RADIO CORPORATION

CHICAGO, U. S. A.



I.F. FREQUENCY 456 K.C.

ZENITH
AUTO RADIO
 MODEL 5M191 CHASSIS 5520
 ZENITH RADIO CORPORATION
 CHICAGO, ILL.

DIAG. PART NO.	DESCRIPTION	DIAG. PART NO.	DESCRIPTION
R1 63-550	240 M OHMS 1/4 W	T1 98-400	12T I.F. TRANSFORMER
R2 63-430	4.9 M OHMS 1/4 W	T2 98-401	700 M I.F. TRANSFORMER
R3 63-506	1500 OHMS 1/4 W	T3 98-386	POWER TRANSFORMER
R4 63-555	3500 OHMS 1/4 W	T4 98-386	POWER TRANSFORMER
R5 63-491	450 M OHMS 1/4 W	T5 98-386	POWER TRANSFORMER
R6 63-491	450 M OHMS 1/4 W	T6 98-386	POWER TRANSFORMER
R7 63-491	450 M OHMS 1/4 W	T7 98-386	POWER TRANSFORMER
R8 63-556	40 OHMS 1/4 W	T8 98-386	POWER TRANSFORMER
R9 63-477	500 M OHMS 1/4 W	T9 98-386	POWER TRANSFORMER
R10 63-569	50 OHMS 1/4 W	T10 98-386	POWER TRANSFORMER
R11 63-551	100 K OHMS 1/4 W	T11 98-386	POWER TRANSFORMER
C1 22-227	.02 MFD 250V	C12 22-528	.0005 MFD 250V
C2 22-250	.05 MFD 250V	C13 22-528	.0005 MFD 250V
C3 22-423	.001 MFD 250V	C14 22-528	.0005 MFD 250V
C4 22-423	.001 MFD 250V	C15 22-528	.0005 MFD 250V
C5 22-518	.001 MFD 250V	C16 22-528	.0005 MFD 250V
C6 22-170	.001 MFD 250V	C17 22-528	.0005 MFD 250V
C7 22-229	.0005 MFD 250V	C18 22-528	.0005 MFD 250V
C8 22-182	.0005 MFD 250V	C19 22-528	.0005 MFD 250V
C9 22-182	.0005 MFD 250V	C20 22-528	.0005 MFD 250V
C10 22-560	.005 MFD 250V	C21 22-528	.0005 MFD 250V
C11 22-229	.005 MFD 250V	C22 22-528	.0005 MFD 250V
C12 22-528	.005 MFD 250V	C23 22-528	.0005 MFD 250V
C13 22-528	.005 MFD 250V	C24 22-528	.0005 MFD 250V
C14 22-528	.005 MFD 250V	C25 22-528	.0005 MFD 250V
C15 22-528	.005 MFD 250V	C26 22-528	.0005 MFD 250V
C16 22-528	.005 MFD 250V	C27 22-528	.0005 MFD 250V
C17 22-528	.005 MFD 250V	C28 22-528	.0005 MFD 250V
C18 22-182	.0005 MFD 250V	C29 22-528	.0005 MFD 250V

FIG. 1. CIRCUIT DIAGRAM, MODEL 5-M-191 (CHASSIS No. 5520)




Fig. 2

IMPORTANT: BALANCING SET TO ANTENNA. There is such an extremely wide variation in antenna capacities that it is difficult to match this condition without some means of variable antenna alignment. To accomplish this, an antenna compensating adjustment is provided through the small hole directly above the antenna cable connector on the receiver case. In addition to this, a tapped antenna transformer is also incorporated (see Figure No. 2). The proper method of alignment is as follows: After completely connecting receiver, tune in a signal between 1400 and 1450 K.C. and adjust the antenna compensator shown in Figure 3, for either the roof antenna, or single or double under-car antenna. The receiver is shipped from the factory with the antenna tap shown in Figure 2 set to the No. 2 position, and, therefore, need not be changed for either of the two types of antennas mentioned.

For Zenith Fleet Wing, and Over the Top Antennas, unsolder the antenna lead from the No. 2 lug, and resolder it to the No. 3 lug. After this is done, tune in a station between 1450 and 1400 K.C., and adjust the antenna compensator shown in Figure 3 to resonance.

For high capacity antennas such as the 1936 Dodge solid steel roof, or the Lincoln Zephyr luggage compartment, drawer antenna, etc., remove the antenna lead from the No. 2 lug, as it comes from the factory, and resolder it to the No. 1 connector. After this is done, the same procedure of tuning in a signal from 1450 to 1400 K.C., and balancing to resonance with the antenna compensator, as described above, should be followed.

This system of tapped transformer, and variable compensating adjustment gives an extremely flexible means of resonating the receiver to any type of antenna, and it should be noted that the tap need only be changed in two cases. Of course, it is necessary to remove the bottom cover in order to shift the antenna tap where necessary.




Fig. 3.—Tube Position 5-M-191





FIG. 4. WIRING DIAGRAM 6-M-192 (CHASSIS No. 5637)

SOCKET VOLTAGES 6-M-192

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	0	225	95	0	—	5.9	0	0
6A8	Mixer Osc.	0	0	225	95	—32	140	5.9	0	0
6K7	L F.	0	0	235	95	4	—	5.9	4	0
6Q7	Det. A. V. C. Audio	0	0	140	0	—5	—	5.9	—2	0
6F6	Power	0	0	215	233	—14	—	5.9	0	—
OZ4	Rectifier			Inaccessible						



Voltage at Battery 6V.

Voltage at Receiver 5.9 V.

Antenna disconnected

All voltages measured with 1000 ohms per volt D. C. meter

Total current consumption 6-M-192—7.5 amperes

Sensitivity at 1 watt output — .9 M. V.

Maximum power output 4.5 watts.




Fig. 5.—Tube Position 6-M-192




Fig. 6.—Bottom View—6-M-192, 6-M-193, 6-M-194






Fig. 7.—Steering Control Assembly



Page 384

SOCKET VOLTAGES 6-M-193, 6-M-194

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	0	225	95	0	—	5.9	0	0
6A8	Mixer Osc.	0	0	225	95	—32	140	5.9	0	0
6K7	I. F.	0	0	235	95	4	—	5.9	4	0
6Q7	Det. A. V. C. Audio	0	0	140	0	—5	—	5.9	—2	0
6F6	Power	0	0	215	233	—14	—	5.9	0	—
OZ4	Rectifier			Inaccessible						



Voltage at Battery 6V.

Voltage at Receiver 5.9 V.

Antenna disconnected

All voltages measured with 1000 ohms per volt D. C. meter

Total current consumption 6-M-193—6-M-194 5.9 amperes

Sensitivity at 1 watt output — .9 M. V.

Maximum power output 4.5 watts.




Fig. 9.—Tube Position 6-M-193, 6-M-194





FIG. 10. WIRING DIAGRAM MODEL 8-M-195 (CHASSIS No. 5803)

DWG. PART NUMBER	DESCRIPTION	DWG. PART NUMBER	DESCRIPTION
R1	83-550 240M OHMS 1/4W	C14	20 MFD 250 V
R2	63-443 300 OHMS 1/4W	C15	22-527 8 MFD 350 V
R3	63-510 18M OHMS 2W	C16	8 MFD 350 V
R4	63-510 18M OHMS 2W	C17	22-475 8 MFD 350 V
R5	63-510 18M OHMS 2W	C18	22-468 5 MFD 120V
R6	63-560 SENSITIVITY CONTROL	C19	22-531 5 MFD 120V
R7	63-559 100 OHMS 1/4W	C20	22-535 500 MFD 400V
R8	63-491 430M OHMS 1/4W	C21	22-82 10M MFD 600V
R9	63-549 2 MEG VOL. CONTROL	C22	22-580 1.25 MFD 200V
R10	63-552 93M OHMS 1/4W	C23	22-580 1.25 MFD 200V
R11	63-482 200 OHMS 1/2W	L1	20 149 ANTENNA COIL
R12	63-482 200 OHMS 1/2W	L2	20 150 P.F. COIL
R13	63-446 750M OHMS 1/4W	L3	20 150 OSCILLATOR COIL
R14	63-446 750M OHMS 1/4W	L4	20 150 OSCILLATOR COIL
R15	63-446 750M OHMS 1/4W	L5	20 150 OSCILLATOR COIL
R16	63-446 750M OHMS 1/4W	L5	20 150 OSCILLATOR COIL
R17	63-446 750M OHMS 1/4W	L5	20 150 OSCILLATOR COIL
R18	63-561 4300 OHMS 1/4W	L5	20 150 OSCILLATOR COIL
C1	22-327 .02 MFD 200V	L5	20 150 OSCILLATOR COIL
C2	22-250 .05 MFD 200V	L5	20 150 OSCILLATOR COIL
C3	22-532 165MVA MAC COND.	L5	20 150 OSCILLATOR COIL
C4	22-170 .1 MFD 400V	L5	20 150 OSCILLATOR COIL
C5	22-538 1/2 MFD AC TUNER	L5	20 150 OSCILLATOR COIL
C6	22-443 200M OHMS 1/4W	L5	20 150 OSCILLATOR COIL
C7	22-162 1000 MFD 600V	L5	20 150 OSCILLATOR COIL
C8	22-162 1000 MFD 600V	L5	20 150 OSCILLATOR COIL
C9	22-470 1000 MFD 600V	L5	20 150 OSCILLATOR COIL
C10	22-537 .0025 MFD 120V	L5	20 150 OSCILLATOR COIL
C11	22-386 .005 MFD 120V	L5	20 150 OSCILLATOR COIL
C12	22-812 .05 MFD 400V	L5	20 150 OSCILLATOR COIL
C13	22-554 .125 MFD 400V	L5	20 150 OSCILLATOR COIL

SOCKET VOLTAGES 8-M-195

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	0	220	75	0	—	5.9	0	0
6A8	Mixer Osc.	0	0	220	75	—11	115	5.9	0	0
6K7	I. F.	0	0	230	75	0	—	5.9	0	0
6H6	Det. A. V. C.			Inaccessible						
6C5	Audio	0	5.9	44	—	0	—	0	1.1	—
6C5	Driver	0	5.9	200	—	0	—	0	6.8	—
6N7	Power	0	0	235	—3.5	—3.5	235	5.9	—3.5	—
6X5	Rectifier			Inaccessible						



Voltage at Battery 6V.

Voltage at Receiver 5.9 V.

Antenna disconnected

All voltages measured with 1000 ohms per volt D. C. meter

Total current consumption 9.2 amperes

Maximum sensitivity at 1 watt output .9 M. V.

Maximum power output 9 watts





Fig. 11.—Tube Position 8-M.195



The proper procedure is as follows:

5-M-91

"A" Connect the service oscillator output leads to the control grid of the 6A8 tube, and to the chassis. If the oscillator output is a single shielded lead the shield should connect to the chassis.

Connect an output meter across the primary of the speaker transformer.

Set the service oscillator at 456 K.C. and adjust the trimmers on the I.F. transformers to the point giving the greatest reading on the output meter. These, as well as the following adjustments should be made using as small an output from the signal generator as possible so that the A.V.C. action will be least effective.

"B" Change the service oscillator lead from the grid of the 6A8 to the antenna connection. A male Delco Remy connector may be used in making a connection to the antenna lead.

Set the service oscillator at 1600 K.C. and rotate the gang condenser until the plates are entirely out of mesh. Adjust the oscillator section trimmer until the 1600 K.C. signal is tuned in.

"C" Set the service oscillator to 600 K.C. and rock the gang condenser slowly to and fro past the point where this signal is received, meanwhile adjusting the padder condenser for a setting which gives the greatest output reading.

"D" Repeat operation "B". See antenna instruction page 379 for correct alignment of antenna stage.

6-M-192 — 6-M-193 — 6-M-194 — 8-M-195

"A" Connect the service oscillator to the control grid of the 6A8 tube and the chassis.

Connect the output meter across the primary of the speaker transformer.

Set the service oscillator to 252.5 K.C. and adjust the trimmers on the I.F. transformers for the greatest output reading. These adjustments should be repeated several times using as weak an input signal as possible so as to obtain greater accuracy.

"B" Change the service oscillator lead from the grid of the 6A8 to the antenna connection. A male Delco Remy connector may be used in making a connection to the antenna lead.

Set the service oscillator at 1600 K.C. and rotate the gang condenser until the plates are entirely out of mesh. Adjust the oscillator section trimmer until the 1600 K.C. signal is tuned in.

Change the service oscillator to 1400 K.C. Rotate the gang condenser until this signal is tuned in, and then adjust the R.F. trimmer on the gang condenser to the point giving the greatest output reading.

"C" Set the service oscillator to 600 K.C. and rock the gang condenser slowly to and fro past the point where this signal is received, meanwhile adjusting the padder condenser for a setting which gives the greatest output reading.

"D" Repeat operation "B".

The sensitivity control should be in the extreme clockwise position when making all adjustments.

NOTE — Due to the high gain type of I.F. transformers used in these receivers it is essential that a non metallic screw driver be used in making all adjustments. See antenna instructions page 379 for correct alignment of antenna stage.

SERVICE NOTE

The 0Z4 rectifier tube used in the 5 and 6 tube models may be replaced with a 6X5 rectifier, providing the 6X5 tube is inclosed in a grounded tube shield.

The Goat shield with a ground clip which connects to the shield contact pin of the tube is the most convenient type to use.

PARTS LIST

ST. ST. ST. PRICE

Coils and Chokes

0-149	Antenna Coil	8	6	\$ 1.25
0-150	R.F. Coil	8	6	.60
0-152	Antenna Coil		5	1.25
5-392	1st I.F. Transformer		6	1.25
3-393	2nd I.F. Transformer		6	1.25
5-394	1st I.F. Transformer	8		1.25
5-395	2nd I.F. Transformer	8		1.25
5-400	1st I.F. Transformer		5	1.25
5-401	2nd I.F. Transformer		5	1.25
2778	Hash Choke	8	6	.15
4771	Oscillator Coil	8	6	.45
4778	Oscillator Coil		5	.45
4791	Motor Noise Filter Choke	8	6	.20

Condensers

2-82	.001 mfd. 600 Volt	8	6	.25
2-162	.0001 mfd. 600 Volt	8	6	.20
2-170	.1 mfd. 400 Volt	8	6	.25
2-182	.00025 mfd. 600 Volt	8	6	.12
2-190	.1 mfd. 200 Volt		6	.20
2-212	.05 mfd. 400 Volt	8	6	.20
2-229	.005 mfd. 600 Volt		6	.15
2-250	.05 mfd. 200 Volt	8	6	.15
2-289	.00005 mfd. 600 Volt		6	.12
2-327	.02 mfd. 200 Volt	8	6	.15
2-336	.005 mfd. 120 Volt			
	(Models 193-194 only)	8	6	.15
2-350	.25 mfd. 200 Volt	8	6	.20
2-463	200-750 mmfd. Osc. Padder	8	6	.35
2-468	.5 mfd. 200 Volt	8	6	.30
2-470	.00015 mfd. 600 Volt	8	6	.20
2-476	.0035 mfd. 750 Volt	8		.15
2-526	8-8 mfd. Dry Elect. 350 Volt		6	1.25
2-527	8-8 mfd. 350 Volt-20 mfd. 20 Volt	8		2.25
2-528	4-8 mfd. 350 Volt		5	1.25
2-531	.5 mfd. 120 Volt	8		.30
2-532	3 Gang Variable Cond. 365 mmfd.	8	6	4.50
2-533	2 Gang Variable Cond.			
	362.5 mmfd.		5	3.00
2-534	.25 mfd. 400 Volt	8	6	.25
2-535	.008 mfd. 1400 Volt	8	6	.20
2-537	.0005 mfd. 120 Volt	8	6	.15
2-538	1-12 mmfd. Air Trimmer	8	6	.20
2-539	.5 mfd. 200 Volt		6	.30
2-540	.25 mfd. 200 Volt		5	.25

Resistors

1-422	200 Ohm 1/2 Watt	8	6	.20
1-423	600 Ohm 1/4 Watt		6	.20
1-426	250 M ohm 1/4 Watt		6	.20
1-427	500 M ohm 1/4 Watt		5	.20
1-443	300 Ohm 1/4 Watt	8		.20
1-446	750 M ohm 1/4 Watt	8		.20
1-464	1 megohm 1/4 Watt		6	.20
1-490	49 M ohm 1/4 Watt	8	6	.20
1-491	490 M ohm 1/4 Watt	8	6	.20
1-493	50 M ohm 1/4 Watt		6	.20
1-494	13 M ohm 2 Watt		6	.25
1-506	1500 ohm 1/4 Watt	8	6	.20
1-510	18 M ohm 2 Watt	8		.25
1-512	19 M ohm 1 Watt	8	6	.20
1-549	2 megohm vol. and tone control (dual)	8	6	2.00
1-550	240 M ohm 1/4 Watt	8	6	.20
1-551	1 megohm vol. control (6M192 only)		6	1.00
1-552	99 M ohm 1/4 Watt	8		.20
1-554	40 ohm 1/4 Watt		5	.20
1-555	9.500 ohm 2 Watt		5	.25
1-557	60 ohm 1/4 Watt		6	.20
1-559	120 ohm wire wound 1/4 Watt	8		.20
1-560	Sensitivity Control		8	.70
1-561	4900 ohm 1/4 Watt	8		.20

PRICE

Control Head Assem. Part for Model 5M191

S-4789	Volume Control and Cable Assembly	\$ 3.50
	Above Assembly consists of	
	1 22-182 .00025 mfd. condenser 600 v.	.12
	1 52-93 Control Head Cable and Plug	1.00
	1 52-95 On-Off Switch Cable	.20
	1 52-96 Battery Cable	.20
	1 52-99 Pilot Light Cable and Socket	.20
	1 63-551 Volume Control and Switch	1.00
	1 94-239 Extension Bushing	.15
	1 183-6 Rubber Band	.01
26-140	Calibrated Dial Scale	.10
27-17	Dial Pointer Disc	.10
54-101	Cable Sheath Clamping Nut	.05
76-208	Tuning Control	
	Flexible Shaft 18"	1.00
100-32	Pilot Light Bulb	.15
170-18	Remote Control Drive Mechanism	2.75

Control Head Assem. Part for Model 6M192

S-4844	Volume Control and Cable Assembly	\$ 4.00
	Above Assembly consists of	
	1 22-182 .00025 mfd. Condenser 600 v.	.12
	1 52-95 On-Off Switch Cable	.20
	1 52-96 Battery Cable	.20
	1 52-98 Control Head Cable and Plug Assem.	1.00
	1 52-99 Pilot Light Cable & Socket	.20
	1 63-551 Volume Control and Switch	1.00
	1 94-239 Extension Bushing	.15
	1 183-6 Rubber Band	.01
26-141	Calibrated Dial Scale	.10
27-17	Dial Pointer Disc	.10
54-101	Cable Sheath Clamping Nut	.05
76-209	Tuning Control	
	Flexible Shaft 24"	1.25
100-32	Pilot Light Bulb	.15
170-19	Remote Control Drive Mechanism	2.75

Control Head Assembly Parts for Models 6M193 - 6M194 - 6M195

S-4846	Volume Control and Cable Assembly	\$ 5.00
	Above Assembly consists of	
	1 22-182 .00025 mfd. Condenser 600 v.	.12
	1 22-336 .005 mfd. Condenser 120 v.	.15
	1 22-537 .005 mfd. Condenser 120 v.	.15
	1 52-95 On-Off Switch Cable	.20
	1 52-96 Battery Cable	.20
	1 52-98 Control Head Cable and Plug	1.00
	1 52-100 Pilot Light Cable and Socket	.30
	1 63-549 Volume & Tone Control & Switch Assem.	2.00
	1 183-7 Rubber Band	.01
26-141	Calibrated Dial Scale	.10
27-17	Dial Pointer Disc	.10
46-150	Tone Control Knob	.15
54-101	Cable Sheath Clamping Nut	.05
76-223	Tuning Control	
	Flexible Shaft 24" long	1.25
100-32	Pilot Light Bulb Mazda	.15
147-28	Tuning Control Knob Spacer	.15
170-20	Remote Control Drive Mechanism	4.00

PARTS LIST (Cont'd.)

PRICE

ST. ST. ST. PRICE

Additional Optional Control Cables

Models 6M192—5M191 Only

76-209	Tuning Control Flexible Shaft 24"	1.25
76-214	Tuning Control Flexible Shaft 30"	1.50
76-218	Tuning Control Flexible Shaft 36"	1.75

Models 6M193—6M194—8M195 Only

76-223	Tuning Control Flexible Shaft 24"	1.25
76-224	Tuning Control Flexible Shaft 30"	1.50
76-225	Tuning Control Flexible Shaft 36"	1.75

S-4700

Z-188

Steering Column Control Head Accessory Kit (Used on Models 6M193—6M194—8M195 Only)

12-503	Mechanism Retaining Bracket	.05
15-21	Steering Column Mtg. Cap	.30
24-133	Steering Column Mtg. Cover	
	Upper Half	1.50
24-134	Steering Column Mtg.	
	Cover Lower Half	2.00
46-206	Tuning Control Knob	.20
46-207	Volume & Tone Control Knobs	.15
57-591	Bezel Plate	.45
57-592	Mounting Plate	.30
69-4	No. 6/32 x 3/16" R.H.M.S. N.P.	.01
73-25	No. 10/32 x 5/16"	
	Headless Set Screw	.01
94-238	Paper Bushings	.01
112-108	Dial Pointer Mtg.	
	Screw 3/48" x 7/32	.01
115-12	No. 10/32 x 1/2 F.H.M.S. N.P.	.01
115-14	No. 4/36 x 3/8" F.H.M.S.	.01
147-37	Pointer Screw Spacer	.01
192-14	Unbreakable Dial Glass	.20

S-4810

R-188

Steering Column Mounting Shell (Used with Models 5M191 — 6M192 Only)

12-459	Control Mechanism	
	Retaining Bracket	.05
12-469	Control Housing Mtg. Bracket	.05
17-38	Control Housing Retaining Clamp	.05
43-11	Control Mechanism Housing	.50
46-160	Tuning & Volume Control Knobs	.25
54-106	No. 10/32 x 3/8" Hex Nuts	.01
57-594	Spacer Plate	.05
69-4	No. 6/32 x 3/16 R.H.M.S. N.P.	.01
69-124	No. 8/32 x 7/8" R.H.M.S.	
	Parkerized	.01
69-125	No. 10/32 x 5/16" R.H.M.S.	.01
93-126	No. 8 Internal Shakeproof	
	Lockwashers	.01
93-127	No. 10 Internal Shakeproof	
	Lockwashers	.01
93-312	Shim Washers	.01
93-322	1/16" x 13/32" x 13/16	
	Steel Washer	.01
112-108	No. 3/48 x 7/32" B.J.M.S.	
	Black Nickel Finish	.01
192-14	Unbreakable Dial Glass	.20

Special Cables to Adapt 1936

External Speakers to 1937 Auto Radios

52-102	Firewall Cable (Used for BH-177 BH-177S Also)	1.50
52-103	Header Cable	2.25
	I.E. Additional of either of the above transforms	
	1936 speaker to X type (GM77+52-103=GM77X)	

Set Mounting Parts

22-193	.5 mfd. Ignition Coil	
	Condenser 200 volts	.45
22-194	.5 mfd. Generator Condenser	.50

52-90	Antenna Cable	.50
52-97	Battery Cable - Ammeter End	.25
54-102	3/8-32 x 1/2" Hex Nuts Cadmium	.01
57-478	Set Mounting Plate	.25
58-26	Delco Remy Fuse Bushing	.01
63-336	15 M ohm Distributor Suppressor	.35
69-84	No. 10/32 x 1/4" R.H.M.S.	
	for Mounting Plate	.30
93-127	No. 10 Internal Shakeproof	
	Lockwasher	.35
93-143	3/8" Internal Shakeproof	
	Lockwasher	.01
93-222	7/16" Internal Shakeproof	
	Lockwasher	.01
93-233	Set Mounting Bolt Washer	
	2 1/4" Dia.	.02
136-6	15 Amp. Fuse	.06
144-14	7/16" x 3" Carriage Bolt & Nut	.05
193-2	Installation Template	.01
196-1	Mounting Plate Gasket	.03

Miscellaneous

12-502	Spkr. Mtg. Brackets (5M191 - 6M192 Only)	6	5	.03
19-65	Chassis Box Top Cover Grd.			
	Clip Terminal	8	6	5
44-14	Speaker Plug Jack		6	5
46-205	Sensitivity Control Knob	8		.20
49-170	5" Dynamic Speaker (5M191 - 6M192 Only)*			3.50
	Cone & Voice Coil for 49-170			1.50
	Field Coil for 49-170			1.50
49-171	6" P.M. Dynamic Speaker (6M193 Only)			5.00
	Cone & Voice Coil for 49-171			2.00
49-172	8" P.M. Dynamic Speaker (BH-177 Only)			6.00
	Cone & Voice Coil for 49-172			2.00
49-173	6" P. M. Dynamic Speaker (BH-177S Only)			5.00
	Cone & Voice Coil for 49-173			2.00

*IMPORTANT! When ordering speaker parts always give the entire part and code number i.e., 49-138AB or 49-138U.

52-91	Chassis & Speaker Supply Cable	6		1.75
52-94	Chassis Control Cable & Plug Assem.		5	1.50
52-101	Chassis Control Cable & Plug Assem.	8		1.70
69-129	10/32 x 1" R.H.M.S. Statuary			
	Bronze for Mounting Top Cover	8	6	5
69-130	10/32 x 3/8" R.H.M.S. Statuary			
	Bronze for Mtg. Top Cover	6		.01
73-17	No. 8/32 x 1/4" Headless Set Screw Cuppoint			.01
78-115	Vibrator Wafer Type Socket	8	6	5
78-133	No. 6H6 Wafer Type Socket	8		.15
78-148	No. 6Q7 Wafer Type Socket		6	5
78-149	No. 6 x 5-No. OZ4 Wafer Type Socket	8	6	5
78-150	No. 6K7 Wafer Type Socket	8	6	5
78-151	No. 6A8 Wafer Type Socket	8	6	5
78-152	No. 6F6 Wafer Type Socket		6	5
78-156	No. 6C5 Wafer Type Socket	8		.10
78-157	No. 6N7 Wafer Type Socket	8		.10
95-388	Audio Transformer Assembly	8		4.00
95-389	Power Transformer		5	2.75
95-390	Power Transformer		6	2.75
95-391	Power Transformer	8		3.25
95-396	Power Choke			.75
95-397	Output Transformer		6	1.25
95-398	Power Choke	8		.90
95-399	Audio Transformer		5	1.00
112-130	No. 8 x 1/4" H.H. Slotted Self Tapping Screw Acorn Head	8	6	5
126-131	Tube Shield Complete With Rings	8	6	5
143-31	Insulated Coupling	8		.10
190-9	Vibrator	8	6	5

PARTS LIST (Cont'd.)

Instrument Panel Plate Kits 1936 and Previous

NUMBER	CAR AND YEARS
A88	Auburn 34-35-36
B88	Buick 36
CA87	Cadillac-LaSalle 35
CA88	Cadillac-LaSalle 36
C88	Chevrolet 35-36
CH87	Chrysler 6 - DeLuxe 8 34-35
	All Hupmobile; DeSoto 34
CH88	Chrysler 36
CH88A	Chrysler Del. 8 - 36
CH88B	Chrysler Airflow and Imp. 36
DE88F	DeSoto Airstr. Cust. & Airfl. 36
DE87D	All DeSoto 35
DE88S	DeSoto DeLuxe 36
DO88	Dodge 36
DO87	Dodge 35
DO-86	Dodge-Plymouth DeLuxe 34
FS88 Gray	Ford Standard 36
FS88L Mah.	Ford Standard 36
F88L Wal.	Ford DeLuxe 36
F87	Ford Standard 35
F87D	Ford DeLuxe 35
F86	Ford DeLuxe 34
F88	Lincoln Zephyr 36
	Ford DeLuxe 36
G87	Graham 35
H86	Hudson Terraplane 34
H87	Hudson-Terraplane 35
H88	Hudson 36
LA88	LaFayette 35-36
N88	Nash 400-Ambass. 35-36
OL87	Oldsmobile 35
OL88	Oldsmobile 36
PC188S	Packard 6 37
PC188	Packard 120 37
PC88	Packard 120B 36
PC87	Packard 120 35
PC88S	Packard 8 Sup. 8-12 35-36
PL87	Plymouth DeLuxe 35
PL87W	Plymouth DeLuxe 35
PL88S	Chrysler Airfl. and Imp. 34-35;
	Plym. Std. 35-36; All Studebaker 35
PL88	Gray Plymouth DeLuxe 36
PO88	Pontiac Standard 35-36
	Pontiac DeLuxe 35
PO88D	Pontiac DeLuxe 36
PO88DL	Pontiac DeLuxe After June 36
RE88	Reo Flying Cloud 36
SD-188	Studebaker Dict. "37"
SD188C	Stu. Dict. Bus. C. "37"
SP188	Stude. Pres. "37"
SD88	Studebaker Dictator 36
SP88	Studebaker President 36
T88	Terraplane 36

Instrument Panel Plate Kits 1937 Models

NUMBER	MAKE OF CAR
R-188	Steering post and under panel (Polished Chrome)
A-188	Steering post and under panel (Dull Black)
A-188	Auburn
B-188	Buick — 40-60 Series
B-188-A	Buick — 80-90 Series
CA-188	Cadillac and LaSalle
C-188	Chevrolet
CH-188R	Chrysler Royal
CH-188B	Chrysler Imperial
CH-188A	Chrysler Airflow
DE-188	DeSoto
DO-188	Dodge
FS-188	Ford Standard
F-188	Ford De Luxe
G-188	Graham
H-188	Hudson
L-188	Lincoln Zephyr
N-188	Nash Lafayette 400
NA-188	Nash Ambassador
OL-188	Oldsmobile
PC-188	Packard 120-C
PC-188S	Packard 6
PC-188D	Packard Super 8 and 12
PL-188S	Plymouth Standard
PL-188	Plymouth DeLuxe
PO-188	Pontiac
SD-188C	Studebaker Dictator Business Coupe
SD-188	Studebaker Dictator
SP-188	Studebaker President
T-188	Terraplane

All panel and steering assemblies available @ .65 each net.



Housing Kits For Steering Column Installation — Description

TYPE	
R188	Standard Steering Column Housing for Models 5M191 and 6M192 only
Z188	Safety Steering Column Housing for Models 6M193, 6M194 and 8M195 only.

These Prices Supersede All Previous Quotations and Are Subject to Regular Discounts and Change Without Notice.

ZENITH RADIO CORPORATION
CHICAGO, ILL.
1-1-37

© Zenith Radio Corp. 1935
 CHICAGO, ILL.




I.F. FREQUENCY 456 K.C.

ZENITH
 AUTO RADIO

MODEL 5M191 CHASSIS 5520
 ZENITH RADIO CORPORATION
 CHICAGO, ILL.

DIAG. NO.	PART NUMBER	DESCRIPTION	DIAG. NO.	PART NUMBER	DESCRIPTION
R1	63-350	240H OHMS 1/4W.	T1	95-400	1/2 L.T. TRANSFORMER
R2	63-480	45H OHMS 1/4W.	T2	95-401	2 1/2 L.T. TRANSFORMER
R3	63-308	500 OHMS 1/4W.	T3	95-385	POWER TRANSFORMER
R4	63-353	300 OHMS 1/4W.	T4	95-386	POWER CHOKE
R5	63-421	600 OHMS 1/4W.	T5	95-389	AUDIO TRANSFORMER
R6	63-421	600 OHMS 1/4W.			
R7	63-454	1MEG. 1/4W.			
R8	63-554	40 OHMS 1/4W.			
R9	63-477	500 OHMS 1/4W.			
R10	63-553	50 OHMS 1/4W.			
R11	63-551	1MEG. VOL. CONTROL			
R12	63-552	95H OHMS 1/4W.			
C1	22-127	.02 MFD. 200V.			
C2	22-127	.02 MFD. 200V.			
C3	22-533	2.5MFD. 50V. (M.C. CONDENSER)			
C4	22-519	100-250 MFD. AUDIO			
C5	22-170	.1 MFD. 400V.			
C6	22-170	.1 MFD. 400V.			
C7	22-170	.1 MFD. 400V.			
C8	22-170	.1 MFD. 400V.			
C9	22-170	.1 MFD. 400V.			
C10	22-170	.1 MFD. 400V.			
C11	22-170	.1 MFD. 400V.			
C12	22-170	.1 MFD. 400V.			
C13	22-170	.1 MFD. 400V.			
C14	22-170	.1 MFD. 400V.			
C15	22-170	.1 MFD. 400V.			
C16	22-170	.1 MFD. 400V.			
C17	22-170	.1 MFD. 400V.			
C18	22-170	.1 MFD. 400V.			

DATE	REVISION	DESCRIPTION
1-4-37	1	REVISION
1-4-37	2	REVISION
1-4-37	3	REVISION




I.F. FREQUENCY 252½ K.C.

ZENITH
AUTO RADIO
 MODEL-6M192 CHASSIS 5637
 ZENITH RADIO CORPORATION
 CHICAGO, ILL.

CHANGES ON 6M-192


ITEM	DESCRIPTION	DATE
A	VAR DIAPHRAGM 60V (22-47)	12-29-36
B	TRAP FUSED	1-4-37
C	RESISTOR R100 (R1)	1-4-37
D	RESISTOR R100 (R2)	1-4-37
E	CONNECTION SHOWN	1-4-37
F	600P22-47 VAR 200-70 HPPD	1-5-37

DIAG. NO.	PART NUMBER	DESCRIPTION	DIAG. NO.	PART NUMBER	DESCRIPTION
C1	22-327	0.2 MFD	R1	65-552	50M OHMS 1/4W
C2	22-327	0.2 MFD	R2	65-552	50M OHMS 1/4W
C3	22-327	0.2 MFD	R3	65-552	50M OHMS 1/4W
C4	22-327	0.2 MFD	R4	65-552	50M OHMS 1/4W
C5	22-327	0.2 MFD	R5	65-552	50M OHMS 1/4W
C6	22-327	0.2 MFD	R6	65-552	50M OHMS 1/4W
C7	22-327	0.2 MFD	R7	65-552	50M OHMS 1/4W
C8	22-327	0.2 MFD	R8	65-552	50M OHMS 1/4W
C9	22-327	0.2 MFD	R9	65-552	50M OHMS 1/4W
C10	22-327	0.2 MFD	R10	65-552	50M OHMS 1/4W
C11	22-327	0.2 MFD	R11	65-552	50M OHMS 1/4W
C12	22-327	0.2 MFD	R12	65-552	50M OHMS 1/4W
C13	22-327	0.2 MFD	R13	65-552	50M OHMS 1/4W
C14	22-327	0.2 MFD	R14	65-552	50M OHMS 1/4W
C15	22-327	0.2 MFD	R15	65-552	50M OHMS 1/4W
C16	22-327	0.2 MFD	R16	65-552	50M OHMS 1/4W
C17	22-327	0.2 MFD	R17	65-552	50M OHMS 1/4W
C18	22-327	0.2 MFD	R18	65-552	50M OHMS 1/4W
C19	22-327	0.2 MFD	R19	65-552	50M OHMS 1/4W
C20	22-327	0.2 MFD	R20	65-552	50M OHMS 1/4W
C21	22-327	0.2 MFD	R21	65-552	50M OHMS 1/4W
C22	22-327	0.2 MFD	R22	65-552	50M OHMS 1/4W
C23	22-327	0.2 MFD	R23	65-552	50M OHMS 1/4W
C24	22-327	0.2 MFD	R24	65-552	50M OHMS 1/4W
C25	22-327	0.2 MFD	R25	65-552	50M OHMS 1/4W
C26	22-327	0.2 MFD	R26	65-552	50M OHMS 1/4W
C27	22-327	0.2 MFD	R27	65-552	50M OHMS 1/4W
C28	22-327	0.2 MFD	R28	65-552	50M OHMS 1/4W
C29	22-327	0.2 MFD	R29	65-552	50M OHMS 1/4W
C30	22-327	0.2 MFD	R30	65-552	50M OHMS 1/4W
C31	22-327	0.2 MFD	R31	65-552	50M OHMS 1/4W
C32	22-327	0.2 MFD	R32	65-552	50M OHMS 1/4W
C33	22-327	0.2 MFD	R33	65-552	50M OHMS 1/4W
C34	22-327	0.2 MFD	R34	65-552	50M OHMS 1/4W
C35	22-327	0.2 MFD	R35	65-552	50M OHMS 1/4W
C36	22-327	0.2 MFD	R36	65-552	50M OHMS 1/4W
C37	22-327	0.2 MFD	R37	65-552	50M OHMS 1/4W
C38	22-327	0.2 MFD	R38	65-552	50M OHMS 1/4W
C39	22-327	0.2 MFD	R39	65-552	50M OHMS 1/4W
C40	22-327	0.2 MFD	R40	65-552	50M OHMS 1/4W
C41	22-327	0.2 MFD	R41	65-552	50M OHMS 1/4W
C42	22-327	0.2 MFD	R42	65-552	50M OHMS 1/4W
C43	22-327	0.2 MFD	R43	65-552	50M OHMS 1/4W
C44	22-327	0.2 MFD	R44	65-552	50M OHMS 1/4W
C45	22-327	0.2 MFD	R45	65-552	50M OHMS 1/4W
C46	22-327	0.2 MFD	R46	65-552	50M OHMS 1/4W
C47	22-327	0.2 MFD	R47	65-552	50M OHMS 1/4W
C48	22-327	0.2 MFD	R48	65-552	50M OHMS 1/4W
C49	22-327	0.2 MFD	R49	65-552	50M OHMS 1/4W
C50	22-327	0.2 MFD	R50	65-552	50M OHMS 1/4W
C51	22-327	0.2 MFD	R51	65-552	50M OHMS 1/4W
C52	22-327	0.2 MFD	R52	65-552	50M OHMS 1/4W
C53	22-327	0.2 MFD	R53	65-552	50M OHMS 1/4W
C54	22-327	0.2 MFD	R54	65-552	50M OHMS 1/4W
C55	22-327	0.2 MFD	R55	65-552	50M OHMS 1/4W
C56	22-327	0.2 MFD	R56	65-552	50M OHMS 1/4W
C57	22-327	0.2 MFD	R57	65-552	50M OHMS 1/4W
C58	22-327	0.2 MFD	R58	65-552	50M OHMS 1/4W
C59	22-327	0.2 MFD	R59	65-552	50M OHMS 1/4W
C60	22-327	0.2 MFD	R60	65-552	50M OHMS 1/4W
C61	22-327	0.2 MFD	R61	65-552	50M OHMS 1/4W
C62	22-327	0.2 MFD	R62	65-552	50M OHMS 1/4W
C63	22-327	0.2 MFD	R63	65-552	50M OHMS 1/4W
C64	22-327	0.2 MFD	R64	65-552	50M OHMS 1/4W
C65	22-327	0.2 MFD	R65	65-552	50M OHMS 1/4W
C66	22-327	0.2 MFD	R66	65-552	50M OHMS 1/4W
C67	22-327	0.2 MFD	R67	65-552	50M OHMS 1/4W
C68	22-327	0.2 MFD	R68	65-552	50M OHMS 1/4W
C69	22-327	0.2 MFD	R69	65-552	50M OHMS 1/4W
C70	22-327	0.2 MFD	R70	65-552	50M OHMS 1/4W
C71	22-327	0.2 MFD	R71	65-552	50M OHMS 1/4W
C72	22-327	0.2 MFD	R72	65-552	50M OHMS 1/4W
C73	22-327	0.2 MFD	R73	65-552	50M OHMS 1/4W
C74	22-327	0.2 MFD	R74	65-552	50M OHMS 1/4W
C75	22-327	0.2 MFD	R75	65-552	50M OHMS 1/4W
C76	22-327	0.2 MFD	R76	65-552	50M OHMS 1/4W
C77	22-327	0.2 MFD	R77	65-552	50M OHMS 1/4W
C78	22-327	0.2 MFD	R78	65-552	50M OHMS 1/4W
C79	22-327	0.2 MFD	R79	65-552	50M OHMS 1/4W
C80	22-327	0.2 MFD	R80	65-552	50M OHMS 1/4W
C81	22-327	0.2 MFD	R81	65-552	50M OHMS 1/4W
C82	22-327	0.2 MFD	R82	65-552	50M OHMS 1/4W
C83	22-327	0.2 MFD	R83	65-552	50M OHMS 1/4W
C84	22-327	0.2 MFD	R84	65-552	50M OHMS 1/4W
C85	22-327	0.2 MFD	R85	65-552	50M OHMS 1/4W
C86	22-327	0.2 MFD	R86	65-552	50M OHMS 1/4W
C87	22-327	0.2 MFD	R87	65-552	50M OHMS 1/4W
C88	22-327	0.2 MFD	R88	65-552	50M OHMS 1/4W
C89	22-327	0.2 MFD	R89	65-552	50M OHMS 1/4W
C90	22-327	0.2 MFD	R90	65-552	50M OHMS 1/4W
C91	22-327	0.2 MFD	R91	65-552	50M OHMS 1/4W
C92	22-327	0.2 MFD	R92	65-552	50M OHMS 1/4W
C93	22-327	0.2 MFD	R93	65-552	50M OHMS 1/4W
C94	22-327	0.2 MFD	R94	65-552	50M OHMS 1/4W
C95	22-327	0.2 MFD	R95	65-552	50M OHMS 1/4W
C96	22-327	0.2 MFD	R96	65-552	50M OHMS 1/4W
C97	22-327	0.2 MFD	R97	65-552	50M OHMS 1/4W
C98	22-327	0.2 MFD	R98	65-552	50M OHMS 1/4W
C99	22-327	0.2 MFD	R99	65-552	50M OHMS 1/4W
C100	22-327	0.2 MFD	R100	65-552	50M OHMS 1/4W



CHANGES ON 6M-193-4		
LINE	DESCRIPTION	DATE
A	Wing Drum .0005440600 (22.47)	12-29-96
B	THPS REVERSED	1-4-97
C	RESISTOR ADDED (R1)	1-4-97
D	RESISTOR ADDED (R6)	1-4-97
E	CONNECTION SHOWN	1-4-97
F	QUANTITY 444 NWS 200-750 NWS	1-8-97

[illegible]



I.F. FREQUENCY 252 1/2 K.C.

ZENITH
AUTO RADIO

MODEL 8M195 CHASSIS 3803

ZENITH RADIO CORPORATION
CHICAGO, ILL.

ITEM	DESCRIPTION	DATE
A	CONDENSER ADDED (C17) 22-30	
B	RESISTOR ADDED (R19) 100-50	
C	TUBE REVISED	1-4-37
D	RESISTOR ADDED (R1) 1-4-37	
E	CONDENSER ADDED (C11) 1-4-37	
F	CONDENSER ADDED (C12) 1-4-37	
G	CONDENSER ADDED (C13) 1-4-37	
H	CONDENSER ADDED (C14) 1-4-37	
I	CONDENSER ADDED (C15) 1-4-37	
J	CONDENSER ADDED (C16) 1-4-37	
K	CONDENSER ADDED (C18) 1-4-37	
L	CONDENSER ADDED (C19) 1-4-37	

DIAG. NO.	PART NUMBER	DESCRIPTION
R1	63-550	40M OHMS 1/4W.
R2	63-747	470 OHMS 1/4W.
R3	63-510	18M OHMS 2W.
R4	63-490	49M OHMS 1/4W.
R5	63-512	19M OHMS 1W.
R6	63-560	SENSITIVITY CONTROL
R7	63-559	120 OHMS 1/4W.
R8	63-491	490M OHMS 1/4W.
R9	63-549	1MEG VOL. CONTROL
R10	63-552	199M OHMS 1/4W.
R11	63-506	650 OHMS 1/4W.
R12	63-700	620 OHMS 1/2W.
R13	63-446	760M OHMS 1/4W.
R14	63-561	4900 OHMS 1/4W.
R15	63-564	450 OHMS 1/4W.
C1	22-317	.02 MFD 200V.
C2	22-250	.05 MFD 500V.
C3	22-312	365 MFD 50V.
C4	22-170	1 MFD 400V.
C5	22-538	1/16 MFD 400V.
C6	22-448	955-825 MFD. POWER
C7	22-162	.00025 MFD. 600V.
C8	22-162	.0001 MFD. 600V.
C9	22-470	.00015 MFD. 120V.
C10	22-537	.0005 MFD. 120V.
C11	22-316	.005 MFD. 120V.
C12	22-212	.05 MFD. 400V.
C13	22-334	.25 MFD. 400V.
L1	20-149	ANTENNA COIL
L2	20-180	P.A. COIL
L3	5-4771	OSCILLATOR COIL
L4	5-2778	DASH CHOICE
L5	5-4751	Phone House Fuse Choice
T1	95-184	1ST I.F. TRANSFORMER
T2	95-193	2ND I.F. TRANSFORMER
T3	95-388	POWER TRANSFORMER
T4	95-388	POWER TRANSFORMER
T5	95-391	POWER TRANSFORMER
T6	95-393	POWER TRANSFORMER
T7	95-395	POWER TRANSFORMER
V1	190-9	VIBRATOR

SERVICE MANUAL



1938 RECEIVERS

Model	Page	Model	Page	Model	Page
4-F-227	400	6-S-229	414	7-S-260	422
4-B-231	402	6-J-230	416	7-S-261	422
5-S-201	404	6-D-238	412	9-S-204	426
5-R-216	406	6-S-239	414	9-S-232	426
5-J-217	408	6-S-241	414	9-S-242	426
5-S-218	404	6-S-254	418	9-S-244	426
5-S-220	404	6-S-256	418	9-S-262	426
5-R-226	406	6-J-257	416	9-S-263	426
5-S-228	404	7-D-203	420	9-S-264	426
5-F-233	410	7-S-204	422	12-S-205	428
5-R-236	406	7-D-222	420	12-S-232	428
5-S-237	404	7-D-223	420	12-S-245	428
5-J-247	408	7-D-229	420	12-S-265	428
5-S-250	404	7-S-232	422	12-S-266	428
5-F-251	410	7-J-232	424	12-S-267	428
5-S-252	404	7-D-239	420	12-S-268	428
5-J-255	408	7-S-240	422	15-U-246	430
6-D-202	412	7-D-241	420	15-U-269	430
6-S-203	414	7-S-242	422	15-U-270	430
6-D-219	412	7-D-243	420	15-U-271	430
6-D-221	412	7-D-253	420	15-U-272	430
6-S-222	414	7-S-258	422	15-U-273	430
6-S-223	414	7-J-259	424	Phono Circ.	432
				Parts List	433

ZENITH RADIO CORPORATION
CHICAGO, U. S. A.

ALIGNMENT INSTRUCTIONS

The proper procedure for the correct alignment of each chassis is outlined on the page opposite each circuit diagram.

The operations are outlined in consecutive order, and the instructions are under the following headings —

OSC. CONNECTED TO — tells where the output of the service oscillator is to be connected.

DUMMY — gives the proper capacity or resistance which should be connected in series with the service oscillator output.

TEST OSC. — Set test oscillator to frequency shown.

BD. SW. — Set the receiver band switch to the position shown.

DIAL — The receiver should be set at the frequency shown.

TRIMMER — This column tells which trimmer (or trimmers) are to be adjusted for each operation. The chassis photo at the bottom of the page has each trimmer indicated by a letter corresponding to the instructions.

REMARKS — This column tells what is being accomplished by each operation.

If these instructions are carefully followed each chassis will be easily and correctly realigned.

PHONO CONNECTIONS

Zenith chassis are not equipped at the factory for phono operation, however, it is possible to make slight wiring changes to accomplish this. On page 432 is a sectional diagram showing the phono circuit adaption for each type chassis. The necessary switch and tip jacks may be mounted on the rear of the chassis base.

ELECTRIC AUTOMATIC TUNING ADJUSTMENTS

1. Make sure that nothing is obstructing the free action of either the belt, the pulley, or the drive shaft, such as wires or component parts.
2. Check the band change shaft for clearance on the 9-12-15 tube models. The die cast bracket through which the brass drive shaft for the motor travels can be centered properly by loosening the two Parker-Kalon screws which hold the bracket to the front of the dial assembly. After centering the above mentioned die cast bracket retighten the two Parker-Kalon screws.
3. Check the 9/16 nut at rear of chassis in this manner; loosen the nut, permit the motor to run and retighten the 9/16 nut while in operation. This will allow the front and rear bearings to align themselves properly.
4. Check for ample clearance between the dial gang drive pulley and the mounting nut for the bearing through the front of the chassis approximately $1/32''$ clearance. Brass drive shaft should also have ample clearance at the rear of the chassis between the collar mounted on the motor switch.
5. Remove motor drive belt, turn motor armature by hand, if motor action feels tight, oil the felt oil retaining washers on the shaft of the armature with one or two drops of fine oil. Wherever we have use for oil only a few drops should be applied in order to eliminate any danger of seepage into the electrical components of the receiver. We recommend that a zero cold test gear oil be used.

All bearings, dial mechanism and gears of the gang should be lubricated approximately once a year.


6. The large drive pulley mounted on the rear of the brass shaft should be in line with the small pulley which will be found mounted on the motor armature. Alignment can be accomplished by loosening the two set screws and sliding the large pulley either backward or forward on the brass shaft.
7. The tension of the drive belt for the motor can be adjusted by loosening the two hexagon bolts found at the rear of the chassis and holding the motor assembly. The motor assembly should be moved in the elongated holes until the drive belt has a snug tension but not too tight an action. Then retighten the hexagon headed mounting bolts.
8. It is very important that the four bolts that hold the chassis in the cabinet during shipment be removed entirely on installation thus permitting the chassis to float absolutely free on the four cushion rubbers. This will insure freedom of all working parts and permit centering and aligning chassis in the cabinet.
9. If the drive mechanism has a tendency to slip when using the large manual knob check for a loose spring clutch. All adjustments to the clutch should be made very carefully. The mechanism being essentially the same as last year, should be understood by most service men in the field. Adjustments are made by turning the screw mounted through the blue steel clutch spring found at the front of the brass drive shaft mechanism. By running the screw in, the action will be tightened, and by running the screw out, the action will be loosened, but in all cases only one or two complete turns should be necessary.
10. If at any time it is necessary to change the electric eye tube, care should be taken not to place the tube too far forward as this will cause a strain to be placed on the dial pan causing friction at the center hub of the gang shaft and the motor will not operate freely.

MODEL 4F227

CHASSIS No. 5408

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
1C7	Converter Osc.	—	2	136	42	—6	116	0	—	0
1D5	I. F.	—	2	136	42	—	—	0	—	0
1F7	2nd Det. 1st Audio	—	2	15	0	—5	11	0	—	0
1F5	Power	—	2	130	136	—5	—	0	—	—




**BOTTOM VIEW
OF SOCKET**


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. "A" consumption .42 Amp. "B" consumption 19 M.A. Power output .75W.

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Algm't.
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Algm't of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "	200 Mmfd.	1500	"	1500	FG	Rpt. 3 & 4

LOCATION OF TRIMMERS





4 TUBE BATTERY SUPERHETERODYNE
I.F. - FREQUENCY 456 K.C.
CHASSIS NO 5409

SPEAKER
 49-191-5

MODEL 5
 4B 231


ZENITH RADIO CORP.
 CHICAGO, ILLINOIS

DIAG. PART NO.	DESCRIPTION	DIAG. PART NO.	DESCRIPTION
C-1	22-404 TWO GANG VARI COND.	1	5-5215 ANT COIL & SHIELD ASSEMBLY
C-2	22-250 .05 MFD	2	5-4622 OSCIL COIL ASSEMBLY
C-3	22-316 .002 MFD	3	95-443 1ST I.F. TRANSFORMER
C-4	22-245 .01 MFD	4	95-444 2ND I.F. TRANSFORMER
C-5	22-162 .0001 MFD	5	95-445 2ND I.F. TRANSFORMER
C-6	22-147 .0005 MFD	6	95-295 POWER TRANSFORMER
C-7	22-212 .05 MFD	7	190-C VIBRATOR
C-8	22-492 .002 MFD	8	20-82 R.F. CHOKE
C-9	22-199 .5 MFD	9	5-2778 R.F. CHOKE
C-10	22-455 .01 MFD	10	5-2778 SPEAKER TRANSFORMER
C-11	22-582 2 MFD ELECTROLYTIC 250V		
C-12	22-582 2 MFD ELECTROLYTIC 250V		
C-13	22-582 2 MFD ELECTROLYTIC 250V		
C-14	22-582 2 MFD ELECTROLYTIC 250V		
C-15	22-582 2 MFD ELECTROLYTIC 250V		
C-16	22-582 2 MFD ELECTROLYTIC 250V		
C-17	22-582 2 MFD ELECTROLYTIC 250V		
C-18	22-582 2 MFD ELECTROLYTIC 250V		
C-19	22-582 2 MFD ELECTROLYTIC 250V		
C-20	22-582 2 MFD ELECTROLYTIC 250V		
C-21	22-582 2 MFD ELECTROLYTIC 250V		
C-22	22-582 2 MFD ELECTROLYTIC 250V		
C-23	22-582 2 MFD ELECTROLYTIC 250V		
C-24	22-582 2 MFD ELECTROLYTIC 250V		
C-25	22-582 2 MFD ELECTROLYTIC 250V		
C-26	22-582 2 MFD ELECTROLYTIC 250V		
C-27	22-582 2 MFD ELECTROLYTIC 250V		
C-28	22-582 2 MFD ELECTROLYTIC 250V		
C-29	22-582 2 MFD ELECTROLYTIC 250V		
C-30	22-582 2 MFD ELECTROLYTIC 250V		
C-31	22-582 2 MFD ELECTROLYTIC 250V		
C-32	22-582 2 MFD ELECTROLYTIC 250V		
C-33	22-582 2 MFD ELECTROLYTIC 250V		
C-34	22-582 2 MFD ELECTROLYTIC 250V		
C-35	22-582 2 MFD ELECTROLYTIC 250V		
C-36	22-582 2 MFD ELECTROLYTIC 250V		
C-37	22-582 2 MFD ELECTROLYTIC 250V		
C-38	22-582 2 MFD ELECTROLYTIC 250V		
C-39	22-582 2 MFD ELECTROLYTIC 250V		
C-40	22-582 2 MFD ELECTROLYTIC 250V		
C-41	22-582 2 MFD ELECTROLYTIC 250V		
C-42	22-582 2 MFD ELECTROLYTIC 250V		
C-43	22-582 2 MFD ELECTROLYTIC 250V		
C-44	22-582 2 MFD ELECTROLYTIC 250V		
C-45	22-582 2 MFD ELECTROLYTIC 250V		
C-46	22-582 2 MFD ELECTROLYTIC 250V		
C-47	22-582 2 MFD ELECTROLYTIC 250V		
C-48	22-582 2 MFD ELECTROLYTIC 250V		
C-49	22-582 2 MFD ELECTROLYTIC 250V		
C-50	22-582 2 MFD ELECTROLYTIC 250V		
C-51	22-582 2 MFD ELECTROLYTIC 250V		
C-52	22-582 2 MFD ELECTROLYTIC 250V		
C-53	22-582 2 MFD ELECTROLYTIC 250V		
C-54	22-582 2 MFD ELECTROLYTIC 250V		
C-55	22-582 2 MFD ELECTROLYTIC 250V		
C-56	22-582 2 MFD ELECTROLYTIC 250V		
C-57	22-582 2 MFD ELECTROLYTIC 250V		
C-58	22-582 2 MFD ELECTROLYTIC 250V		
C-59	22-582 2 MFD ELECTROLYTIC 250V		
C-60	22-582 2 MFD ELECTROLYTIC 250V		
C-61	22-582 2 MFD ELECTROLYTIC 250V		
C-62	22-582 2 MFD ELECTROLYTIC 250V		
C-63	22-582 2 MFD ELECTROLYTIC 250V		
C-64	22-582 2 MFD ELECTROLYTIC 250V		
C-65	22-582 2 MFD ELECTROLYTIC 250V		
C-66	22-582 2 MFD ELECTROLYTIC 250V		
C-67	22-582 2 MFD ELECTROLYTIC 250V		
C-68	22-582 2 MFD ELECTROLYTIC 250V		
C-69	22-582 2 MFD ELECTROLYTIC 250V		
C-70	22-582 2 MFD ELECTROLYTIC 250V		
C-71	22-582 2 MFD ELECTROLYTIC 250V		
C-72	22-582 2 MFD ELECTROLYTIC 250V		
C-73	22-582 2 MFD ELECTROLYTIC 250V		
C-74	22-582 2 MFD ELECTROLYTIC 250V		
C-75	22-582 2 MFD ELECTROLYTIC 250V		
C-76	22-582 2 MFD ELECTROLYTIC 250V		
C-77	22-582 2 MFD ELECTROLYTIC 250V		
C-78	22-582 2 MFD ELECTROLYTIC 250V		
C-79	22-582 2 MFD ELECTROLYTIC 250V		
C-80	22-582 2 MFD ELECTROLYTIC 250V		
C-81	22-582 2 MFD ELECTROLYTIC 250V		
C-82	22-582 2 MFD ELECTROLYTIC 250V		
C-83	22-582 2 MFD ELECTROLYTIC 250V		
C-84	22-582 2 MFD ELECTROLYTIC 250V		
C-85	22-582 2 MFD ELECTROLYTIC 250V		
C-86	22-582 2 MFD ELECTROLYTIC 250V		
C-87	22-582 2 MFD ELECTROLYTIC 250V		
C-88	22-582 2 MFD ELECTROLYTIC 250V		
C-89	22-582 2 MFD ELECTROLYTIC 250V		
C-90	22-582 2 MFD ELECTROLYTIC 250V		
C-91	22-582 2 MFD ELECTROLYTIC 250V		
C-92	22-582 2 MFD ELECTROLYTIC 250V		
C-93	22-582 2 MFD ELECTROLYTIC 250V		
C-94	22-582 2 MFD ELECTROLYTIC 250V		
C-95	22-582 2 MFD ELECTROLYTIC 250V		
C-96	22-582 2 MFD ELECTROLYTIC 250V		
C-97	22-582 2 MFD ELECTROLYTIC 250V		
C-98	22-582 2 MFD ELECTROLYTIC 250V		
C-99	22-582 2 MFD ELECTROLYTIC 250V		
C-100	22-582 2 MFD ELECTROLYTIC 250V		

Circuit Diagram — Model 4-B-231 (5409 Chassis)

MODEL 4B231
CHASSIS No. 5409
SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6D8	Converter Osc.	0	0	147	98	-9	114	6.3	2	0
6S7	I. F.	0	6.3	146	98	1.5	—	0	1.5	0
6T7	2nd Det. 1st Aud.	0	0	27	-1	-1	—	6.3	.8	0
		H	Ep	Es	Ek	H	Eg			
38	Power	0	143	148	6.5	6.3	0			




BOTTOM VIEW
OF SOCKET


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Battery consumption 2.2 Amp. Power output .84W.

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "	200 Mmfd.	1500	"	1500	FG	Repeat 3 & 4.

LOCATION OF TRIMMERS





I.F.-FREQUENCY 456K.C.
5-TUBE SUPERHETERODYNE
2 BAND

CHASSIS NO. 5521

ZENITH RADIO CORP.
CHICAGO, ILLINOIS

MODEL	SPEAKER
5-S-218	49-178 5"
5-S-220	49-178 5"
5-S-228	49-178 5"
5-S-237	49-178 5"
5-S-250	49-179 8"
5-S-252	49-208 10"

DIAG. NO.	PART NO.	DESCRIPTION
C1	22-546	TWO GANG VARIABLE 400K
C2	22-467	.05 MFD.
C3	22-127	25 MFD.
C4	22-350	.002 MFD.
C5	22-563	FIXED PADDER
C6	22-170	.1 MFD.
C7	22-162	.0001 MFD.
C8	22-185	.01 MFD.
C9	22-327	.02 MFD.
C10	22-147	.0005 MFD.
C11	22-190	.1 MFD.
C12	22-435	.02 MFD.
C13	22-492	.002 MFD.
C14	22-171	.05 MFD.
C15	22-596	8 MFD DRY ELECTROL. 75V 450V
C16		1/4 MFD DRY ELECTROL. 75V 450V
VARIABLE TRIMMERS		
A	1st I.F. TRANS. PRIMARY	
B	1st I.F. TRANS. SECONDARY	
C	2nd I.F. TRANS. PRIMARY	
D	2nd I.F. TRANS. SECONDARY	
E	BROADCAST OSCILLATOR (SEE NOTE)	
F	ANTENNA BROADCAST (OX GANG)	
G	22-519 BROADCAST PADDER	
H	SHORT WAVE OSCILLATOR (SEE NOTE)	
I	SHORT WAVE DETECTOR	
J		
K		
L		
TRIMMERS F & K MOUNTED ON BAKELITE STRIP #22-408		
D1S	PART NO.	DESCRIPTION
R1	63-583	47 M OHM 1/4 W ± 20%
R2	63-583	47 M OHM 1/4 W ± 20%
R3	63-583	47 M OHM 1/4 W ± 20%
R4	63-583	47 M OHM 1/4 W ± 20%
R5	63-583	47 M OHM 1/4 W ± 20%
R6	63-583	47 M OHM 1/4 W ± 20%
R7	63-583	47 M OHM 1/4 W ± 20%
R8	63-583	47 M OHM 1/4 W ± 20%
R9	63-583	47 M OHM 1/4 W ± 20%
R10	63-583	47 M OHM 1/4 W ± 20%
R11	63-583	47 M OHM 1/4 W ± 20%
1		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
2		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
3		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
4		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
5		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
6		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
7		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
8		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY
9		WAVE TRAP COIL MOUNTED ON ANTENNA COIL ASSEMBLY


Circuit Diagram — Models 5-S-201, 5-S-218, 5-S-220, 5-S-228, 5-S-237, 5-S-250, 5-S-252 (5521 Chassis)

MODELS 5S201-5S218-5S220-5S228-5S237-5S250-5S252

CHASSIS No. 5521

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	Converter Osc.	0	6.3	244	97	-9	149	0	0	-.5
6K7	I. F.	0	6.3	246	97	0	—	0	0	-.5
6Q7	2nd Det. AVC 1st Audio	0	0	71	-2.5	-2.5	—	6.3	-2.5	-2.5
6F6	Power	0	0	231	246	-3.5	—	6.3	-2.5	—
5Y4	Rect.	0	—	AC	—	AC	—	316	316	—



**BOTTOM VIEW
OF SOCKET**


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 65W. Power Output 4.5W.


ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	456	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output.
6				"		FG	Repeat 3 & 4.
7	Rec. Ant. Lead	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output.

NOTE: If receiver is used in a location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.

LOCATION OF TRIMMERS





Circuit Diagram—Models 5-R-216, 5-R-226, 5-R-236 (5526 Chassis)


MODELS 5R216-5R226-5R236

CHASSIS No. 5526

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	Converter Osc.	0	6	204	82	11	82	0	0	—.1
6K7	I.F.	0	6	204	82	0	—	0	0	—.1
6Q7	2nd Det. AVC 1st Audio	0	0	38	—2	—2	—	6	—2	—2
6F6	Power	0	0	198	205	—2.5	—	6	—3.5	—
5Y4	Rect.	0	—	AC	—	AC	—	208	208	—

All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 50W. Power output 3.5W.





BOTTOM VIEW
OF SOCKET

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output.
5	" " "	200 Mmfd.	1500	"	1500	FG	Repeat 3 & 4.

LOCATION OF TRIMMERS





MODEL	SPEAKER
5-J-217	49-153 6"
5-J-247	49-153 6"
5-J-255	49-210 8"


NOTE - TRIMMERS F, K, & L MOUNTED ON BAKELITE STRIP #22-324

MODELS 5J217-5J247-5J255

CHASSIS No. 5524

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6D8	Converter Osc.	0	0	129	42.5	—2	110	6.3	1.5	0
6S7	I. F.	0	0	130	42.5	1.5	—	6.3	1.5	0
6T7	2nd Det. A.V.C. 1st Audio	0	0	23	.1	.1	—	6.3	.5	0
6ZY5G	Rect.	0	6.3	—3.5	—	—3.5	—	0	140	—
		H	P	S	K	H	G			
38	Power	0	124	129	12	6.3	0			




All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 16W. Battery voltage 6.3V consumption 2.1 Amp. Power Output .84W.


BOTTOM VIEW OF SOCKET

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output.
5				"		FG	Repeat 2 & 3.
6	Rec. Ant. Lead	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output.

LOCATION OF TRIMMERS





PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
12-440	DETECTOR-OSCILLATOR	12-401	IF TRANSFORMER
12-401	IF TRANSFORMER	12-209	IF TRANSFORMER
12-209	IF TRANSFORMER	12-199	IF TRANSFORMER
12-199	IF TRANSFORMER	12-186	IF TRANSFORMER
12-186	IF TRANSFORMER	12-176	IF TRANSFORMER
12-176	IF TRANSFORMER	12-171	IF TRANSFORMER
12-171	IF TRANSFORMER	12-168	IF TRANSFORMER
12-168	IF TRANSFORMER	12-164	IF TRANSFORMER
12-164	IF TRANSFORMER	12-162	IF TRANSFORMER
12-162	IF TRANSFORMER	12-160	IF TRANSFORMER
12-160	IF TRANSFORMER	12-158	IF TRANSFORMER
12-158	IF TRANSFORMER	12-156	IF TRANSFORMER
12-156	IF TRANSFORMER	12-154	IF TRANSFORMER
12-154	IF TRANSFORMER	12-152	IF TRANSFORMER
12-152	IF TRANSFORMER	12-150	IF TRANSFORMER
12-150	IF TRANSFORMER	12-148	IF TRANSFORMER
12-148	IF TRANSFORMER	12-146	IF TRANSFORMER
12-146	IF TRANSFORMER	12-144	IF TRANSFORMER
12-144	IF TRANSFORMER	12-142	IF TRANSFORMER
12-142	IF TRANSFORMER	12-140	IF TRANSFORMER
12-140	IF TRANSFORMER	12-138	IF TRANSFORMER
12-138	IF TRANSFORMER	12-136	IF TRANSFORMER
12-136	IF TRANSFORMER	12-134	IF TRANSFORMER
12-134	IF TRANSFORMER	12-132	IF TRANSFORMER
12-132	IF TRANSFORMER	12-130	IF TRANSFORMER
12-130	IF TRANSFORMER	12-128	IF TRANSFORMER
12-128	IF TRANSFORMER	12-126	IF TRANSFORMER
12-126	IF TRANSFORMER	12-124	IF TRANSFORMER
12-124	IF TRANSFORMER	12-122	IF TRANSFORMER
12-122	IF TRANSFORMER	12-120	IF TRANSFORMER
12-120	IF TRANSFORMER	12-118	IF TRANSFORMER
12-118	IF TRANSFORMER	12-116	IF TRANSFORMER
12-116	IF TRANSFORMER	12-114	IF TRANSFORMER
12-114	IF TRANSFORMER	12-112	IF TRANSFORMER
12-112	IF TRANSFORMER	12-110	IF TRANSFORMER
12-110	IF TRANSFORMER	12-108	IF TRANSFORMER
12-108	IF TRANSFORMER	12-106	IF TRANSFORMER
12-106	IF TRANSFORMER	12-104	IF TRANSFORMER
12-104	IF TRANSFORMER	12-102	IF TRANSFORMER
12-102	IF TRANSFORMER	12-100	IF TRANSFORMER
12-100	IF TRANSFORMER	12-98	IF TRANSFORMER
12-98	IF TRANSFORMER	12-96	IF TRANSFORMER
12-96	IF TRANSFORMER	12-94	IF TRANSFORMER
12-94	IF TRANSFORMER	12-92	IF TRANSFORMER
12-92	IF TRANSFORMER	12-90	IF TRANSFORMER
12-90	IF TRANSFORMER	12-88	IF TRANSFORMER
12-88	IF TRANSFORMER	12-86	IF TRANSFORMER
12-86	IF TRANSFORMER	12-84	IF TRANSFORMER
12-84	IF TRANSFORMER	12-82	IF TRANSFORMER
12-82	IF TRANSFORMER	12-80	IF TRANSFORMER
12-80	IF TRANSFORMER	12-78	IF TRANSFORMER
12-78	IF TRANSFORMER	12-76	IF TRANSFORMER
12-76	IF TRANSFORMER	12-74	IF TRANSFORMER
12-74	IF TRANSFORMER	12-72	IF TRANSFORMER
12-72	IF TRANSFORMER	12-70	IF TRANSFORMER
12-70	IF TRANSFORMER	12-68	IF TRANSFORMER
12-68	IF TRANSFORMER	12-66	IF TRANSFORMER
12-66	IF TRANSFORMER	12-64	IF TRANSFORMER
12-64	IF TRANSFORMER	12-62	IF TRANSFORMER
12-62	IF TRANSFORMER	12-60	IF TRANSFORMER
12-60	IF TRANSFORMER	12-58	IF TRANSFORMER
12-58	IF TRANSFORMER	12-56	IF TRANSFORMER
12-56	IF TRANSFORMER	12-54	IF TRANSFORMER
12-54	IF TRANSFORMER	12-52	IF TRANSFORMER
12-52	IF TRANSFORMER	12-50	IF TRANSFORMER
12-50	IF TRANSFORMER	12-48	IF TRANSFORMER
12-48	IF TRANSFORMER	12-46	IF TRANSFORMER
12-46	IF TRANSFORMER	12-44	IF TRANSFORMER
12-44	IF TRANSFORMER	12-42	IF TRANSFORMER
12-42	IF TRANSFORMER	12-40	IF TRANSFORMER
12-40	IF TRANSFORMER	12-38	IF TRANSFORMER
12-38	IF TRANSFORMER	12-36	IF TRANSFORMER
12-36	IF TRANSFORMER	12-34	IF TRANSFORMER
12-34	IF TRANSFORMER	12-32	IF TRANSFORMER
12-32	IF TRANSFORMER	12-30	IF TRANSFORMER
12-30	IF TRANSFORMER	12-28	IF TRANSFORMER
12-28	IF TRANSFORMER	12-26	IF TRANSFORMER
12-26	IF TRANSFORMER	12-24	IF TRANSFORMER
12-24	IF TRANSFORMER	12-22	IF TRANSFORMER
12-22	IF TRANSFORMER	12-20	IF TRANSFORMER
12-20	IF TRANSFORMER	12-18	IF TRANSFORMER
12-18	IF TRANSFORMER	12-16	IF TRANSFORMER
12-16	IF TRANSFORMER	12-14	IF TRANSFORMER
12-14	IF TRANSFORMER	12-12	IF TRANSFORMER
12-12	IF TRANSFORMER	12-10	IF TRANSFORMER
12-10	IF TRANSFORMER	12-8	IF TRANSFORMER
12-8	IF TRANSFORMER	12-6	IF TRANSFORMER
12-6	IF TRANSFORMER	12-4	IF TRANSFORMER
12-4	IF TRANSFORMER	12-2	IF TRANSFORMER
12-2	IF TRANSFORMER	12-0	IF TRANSFORMER

I.F. FREQUENCY 456 K.C.
 STUBB BATTERY SUPERHETERODYNE
 CHASSIS NO. 5522
 ZENITH RADIO CORPORATION
 CHICAGO, ILL.

MODEL
 5-F-233
 5-F-231


Circuit Diagram — Models 5-F-233, 5-F-231 (5522 Chassis)

MODELS 5F233-5F251

CHASSIS No. 5522

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
1C7	Converter Osc.	—	2	137	41	—5	116	0	—	0
1D5	I. F.	—	2	137	41	—	—	0	—	0
1F7	2nd Det. A.V.C. 1st Audio	—	2	14	0	0	11	0	—	0
1H4	2nd Audio	—	0	126	—	—5	—	2	—	—
1J6	Power	—	0	136	—1.5	—1.5	136	2	—	—




All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. "A" consumption .66 Amp. "B" consumption 19 M.A. Power output 1.75W.


BOTTOM VIEW OF SOCKET

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output.
5	" " "	"	"	"	"	FG	Repeat 3 & 4.
6	Rec. Ant. Lead	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output.

LOCATION OF TRIMMERS






Circuit Diagram — Models 6-D-202, 6-D-219, 6-D-221, 6-D-238 (5639 Chassis)

MODELS 6D202-6D219-6D221-6D238

CHASSIS No. 5639

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	Converter									
	Osc.	0	AC	102	55	-1	85	AC	0	-.1
6K7	I.F.	0	AC	104	104	0	—	AC	0	-.1
6Q7	2nd Det. AVC									
	1st Audio	0	AC	24	-1	-1	—	AC	-1	-1
25L6	Power	0	AC	94	104	-5	—	AC	-4	—
25Z6	Rect.	0	AC	AC	119	AC	—	AC	119	—
	Ballast									



All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 55W. Power output 1.75W.


BOTTOM VIEW OF SOCKET


ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	456	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
6						FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output

NOTE: If receiver is used in a location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.

LOCATION OF TRIMMERS






MODEL 8 6S203-6S222-6S223-6S229-6S239-6S241

CHASSIS No. 5538

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	Converter Osc.	0	6.1	245	83	-9	200	0	0	-1
6K7	I.F.	0	6.1	247	83	0	—	0	0	-1
6H6	2nd Det. AVC	0	0	-2	-2	-2	—	6.1	-2	—
6F5	1st Audio	0	0	—	114	—	—	6.1	-2	-2
6F6	Power	0	0	231	247	-3.5	—	6.1	-2	—
5Y4	Rect.	0	—	AC	—	AC	—	322	322	—



**BOTTOM VIEW
OF SOCKET**


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 65W. Power Output 4.5W.


ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	456	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
6	" " "	200 Mmfd.				FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output
9	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output

NOTE: If receiver is used in a location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.


LOCATION OF TRIMMERS





MODELS 6J230-6J257 **CHASSIS No. 5642** **SOCKET VOLTAGES**

Tube	Position	1	2	3	4	5	6	7	8	9
6D8	Converter Osc.	0	0	125	35	—1	97	6.3	1.5	0
6S7	I.F.	0	0	124	35	1	—	6.3	1	0
6T7	2nd Def. AVC 1st Audio	0	0	15	.1	.1	—	6.3	.5	0
6L5	2nd Audio	0	0	120	—	0	—	6.3	.2	—
1J6	Power	0	3	137	0	0	137	1	0	—
6ZY5	Rect.	0	6.3	AC	—	AC	—	0	140	—




All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 17W. Battery voltage 6.3V consumption 2.04 Amp. Power output 1.75W.

BOTTOM VIEW
OF SOCKET

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Def. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gmt of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5				"		FG	Repeat 3 & 4
6	Rec. Ant. Lead	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output

LOCATION OF TRIMMERS




MODELS 6S254-6S256

CHASSIS No. 5644

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	Converter Osc.	0	6.2	246	90	—9	190	0	0	—5
6K7	I.F.	0	6.2	237	90	0	—	0	0	—5
6H6	2nd Det. A.V.C.	0	0	—2.5	—2	—2.5	—	6.2	—2	—
6F5	1st Audio	0	0	—	104	—	—	6.2	—2	—2
6F6	Power	0	0	231	243	—3	—	6.2	—2	—
5Y4	Rect.	0	—	AC	—	AC	—	314	314	—



**BOTTOM VIEW
OF SOCKET**


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 65W. Power output 4.5W.

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	456	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gmt of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
6	" " "	200 Mmfd.				FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output
9	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output

NOTE: If receiver is used in a location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.

LOCATION OF TRIMMERS




MODELS 7D203-7D222-7D223-7D229-7D239-7D241-7D243-7D253

CHASSIS No. 5710

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	Converter Osc.	0	AC	104	63	-5.5	74	AC	0	-.1
6K7	I.F.	0	AC	104	104	0	—	AC	0	-.1
6H6	2nd Det. A.V.C.	0	AC	-1.5	-1	-1.5	—	AC	-1	—
6F5	1st Audio	0	AC	—	24	—	—	AC	-1	-1.5
25L6	Power	0	AC	99	100	-.5	—	AC	4.5	—
25Z6	Rect.	0	AC	AC	119	AC	—	AC	119	—
	Ballast									



All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 55W. Power output 1.75W.


BOTTOM VIEW OF SOCKET

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	456	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
6	" " "	200 Mmfd.		"		FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output
9	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output

NOTE: If receiver is used in a location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.

LOCATION OF TRIMMERS




MODELS 7S204-7S232-7S240-7S242-7S258-7S260-7S261

CHASSIS No. 5709

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6A8	Converter Osc.	0	6.4	255	89	-10	182	0	0	-2
6K7	I.F.	0	6.4	243	89	0	—	0	0	-2
6H6	2nd Det. A.V.C.	0	0	-2	-2	-2	—	6.4	-2	—
6F5	1st Audio	0	0	—	117	—	—	6.4	-1.5	-1.5
6F6	Power	0	0	243	255	-2	—	6.4	-2	—
5Y4	Rect.	0	—	AC	—	AC	—	328	328	—
		H	Ep	Eg	Et	Ek	H			
6T5	Target	0	16	-2	255	-2	6.4			




All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 75W. Power output 4.5W.

**BOTTOM VIEW
OF SOCKET**

ALIGNMENT PROCEDURE


Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Algmt. of Ant. & De.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "			"		FGH	Repeat 2 & 3
6	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output
8	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output

LOCATION OF TRIMMERS



MODELS 7J232-7J259 **CHASSIS No. 5711** **SOCKET VOLTAGES**

Tube	Position	1	2	3	4	5	6	7	8	9
6S7	R.F.	0	6.3	126	34	1.5	—	0	1.5	0
6D8	Converter Osc.	0	6.3	126	34	— .1	106	0	1	0
6S7	I.F.	0	6.3	123	34	1	—	0	1	0
6T7	2nd Det. AVC	0	6.3	15	.1	.1	—	0	1	0
6L5	1st Audio	0	6.3	122	—	0	—	0	4.5	—
1J6	2nd Audio	—	1	133	0	0	133	3	—	—
6ZY5G	Power	0	6.3	AC	—	AC	—	0	137	—




All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 19W. Battery voltage 6.3V consumption 2.19 Amp. Power output 1.75W.

BOTTOM VIEW **OF SOCKET**

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Algt. of Ant. & Det
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5				"		FGH	Repeat 2 & 3
6	Rec. Ant. Post	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	LM	Rock gang & adj. for max. output
8	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output

LOCATION OF TRIMMERS




MODELS 9S204-9S232-9S242-9S244-9S262-9S263-9S264

CHASSIS No. 5905

SOCKET VOLTAGES

Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	0	240	80	0	—	6.2	0	—2
6L7	Converter	0	6.2	240	80	—7	—	0	0	—1
6J5	Osc.	0	6.2	130	—	—8	—	0	0	—
6K7	I.F.	0	6.2	237	80	0	—	0	0	—1
6H6	2nd Det. A.V.C.	0	0	—2.5	—2	—2.5	—	6.2	—2	—
6F5	1st Audio	0	0	—	82	—	—	6.2	—2	—2.5
6F6	Power	0	0	225	240	—3.5	—	6.2	—4.5	—
5Y4	Rect.	0	—	AC	—	AC	—	298	298	—
		H	Ep	Eg	Et	Ek	H			
6T5	Target	0	10	—2	240	—2	6.2			




**BOTTOM VIEW
OF SOCKET**


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 75W. Power output 4.5W.

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Algmt. of Ant. & Det
4	" " "	200 Mmfd.	600	"		J	Rock gang & adj. for max. output
5				"		FGH	Repeat 2 & 3
6	Rec. Ant. Post	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	LM	Rock gang & adj. for max. output
8	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output

LOCATION OF TRIMMERS






Circuit Diagram — Models 12-S-205, 12-S-232, 12-S-245, 12-S-265, 12-S-266, 12-S-267, 12-S-268 (1204 Chassis)

MODELS 12S205-12S232-12S245-12S265-12S266-12S267-12S268

CHASSIS No. 1204

SOCKET VOLTAGES




Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	3.2	246	83	0	—	3.2	0	0
6L7	Converter	0	3.2	243	83	—10	—	3.2	0	0
6J5	Osc.	0	3.2	121	—	—10.5	—	3.2	0	—
6K7	I. F.	0	3.2	237	83	0	—	3.2	0	0
6H6	2nd Det. A.V.C.	0	3.2	—2	—1.5	—2	—	3.2	—1.5	—
6J5	1st Audio	0	3.2	70	—	—5	—	3.2	—1.5	—
6J5	2nd Audio	0	3.2	74	—	—2	—	3.2	—5	—
6J5	Inverter	0	3.2	76	—	—2	—	3.2	—5	—
6V6	Power	0	3.2	231	240	—2.5	—	3.2	8	—
6V6	Power	0	3.2	231	240	—2.5	—	3.2	8	—
5Y4	Rect.	0	—	AC	—	AC	—	318	318	—
		H	Ep	Eg	Et	Ek	H			
6T5	Target	3.2	13	—1.5	240	—1.5	3.2			


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 110W. Power output 15W.

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Algnt. of Ant&Det
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5						FGH	Repeat 2 & 3
6	Rec. Ant. Post	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	LM	Rock gang & adj. for max. output
8	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output

LOCATION OF TRIMMERS






ZENITH RADIO CORP.
CHICAGO, ILLINOIS

Circuit Diagram — Models 15-U-246, 15-U-269, 15-U-270, 15-U-271, 15-U-272, 15-U-273 (1501 Chassis)

MODELS 15U246-15U269-15U270-15U271-15U272-15U273

CHASSIS No. 1501

SOCKET VOLTAGES



**BOTTOM VIEW
OF SOCKET**


Tube	Position	1	2	3	4	5	6	7	8	9
6K7	R. F.	0	3	250	93	0	—	3	0	—3
6L7	Converter	0	3	250	153	—8	—	3	3	—2
6J5	Osc.	0	3	225	—	—8	—	3	0	—
6K7	I. F.	0	3	250	93	0	—	3	0	—1
6H6	2nd Det. AVC	0	3	—3	—3	—3	—	3	—3	—
6J5	1st Audio	0	3	53	—	—1	—	3	—1	—
6J5	2nd Audio	0	3	82	—	—5	—	3	1.5	—
6J5	Inverter	0	3	82	—	—2.5	—	3	1.5	—
6V6	Power	0	3	243	250	—1	—	3	8	—
6V6	Power	0	3	243	250	—1	—	3	8	—
6V6	Power	0	3	243	250	—1	—	3	8	—
6V6	Power	0	3	243	250	—1	—	3	8	—
5Y4	Rect.	0	—	AC	—	AC	—	320	320	—
5Y4	Rect.	0	—	AC	—	AC	—	320	320	—
		Eh	Ep	Eg	Et	Ek	Eh			
6T5	Target	3	11	—3	216	—3	3			


All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected. Line voltage 117V. Consumption 160W. Power output 30W.

ALIGNMENT PROCEDURE


Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Algt. of Ant. & Det
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5				"		FGH	Repeat 2 & 3
6	Rec. Ant. Post	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	LM	Rock gang & adj. for max. output
8	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output
9	" " "	400 Ohms	40000	U.H.F.	40000	Q	Set Osc. to Scale
10	" " "	400 Ohms	40000	U.H.F.	40000	P	Rock gang & adj. for max. output

LOCATION OF TRIMMERS







CIRCUIT CHANGES FOR PHONOGRAPH
INSTALLATIONS ON CHASSIS MODELS—
5409-5521-5521A-5521AT-5523-5524
5524T-5526-5526A-5527-5529-5539




CIRCUIT CHANGES FOR PHONOGRAPH
INSTALLATIONS ON CHASSIS MODELS—
5638-5710




CIRCUIT CHANGES FOR PHONOGRAPH
INSTALLATION ON CHASSIS MODELS—
5648-5711-5711T




CIRCUIT CHANGES FOR PHONOGRAPH
INSTALLATIONS ON CHASSIS MODELS—
5644-5644A-5702-5702A
5709AT-5905-5905A-5905AT




CHANGES IN CIRCUIT FOR RADIO-PHONO
INSTALLATIONS ON CHASSIS MODELS—
1204-1501
1204A-1501A



CHANGES IN CIRCUIT FOR RADIO-PHONO
COMBINATIONS ON CHASSIS MODELS—
5638-5638A-5710



CHANGES IN CIRCUIT FOR RADIO-PHONO
COMBINATIONS ON CHASSIS MODELS—
5905-5905A



CHANGES IN CIRCUIT FOR RADIO-PHONO
COMBINATIONS ON CHASSIS MODELS—
1204-1204A

PARTS LIST

DIAL PARTS AND KNOBS

Models 4-F-227, 4-B-231
(Chassis Numbers 5408 and 5409)

Part No.	Description	Price
93-323	Bakelite Washer	.01
171-4	Dial Glass	.25
S-3717	Dial Pointer	.25
S-4906	Dial Light Socket (5408)	.10
S-4913	Dial Light Socket (5409)	.10
S-5098	Dial Scale Assembly	1.00
46-219	Volume Knob	.15
46-220	Tuning Knob	.15

Models 5-R-126, 5-R-226, 5-R-236
(Chassis Number 5526)

19-68	Dial Clips	.02
59-61	Dial Pointer	.15
76-233	Drive Shaft	.10
80-69	Dial Cord Spring	.02
93-273	Bakelite Washer	.01
94-230	Drive Shaft Bushing	.10
192-15	Dial Glass	.20
196-9	Dial Glass Gasket	.05
MS-308	Dial Drive Pulley	.25
S-5322	Dial Cord and Eyelet	.20

Models 5-S-201, 5-S-218, 5-S-220, 5-S-228, 5-S-237, 5-S-250, 5-S-252, 5-F-233, 5-F-251, 5-J-217, 5-J-247, 5-J-255

(Chassis Numbers 5521, 5522, 5524). Same parts as chassis 5526, except the following:

26-143	Dial Scale (5521, 5522)	.50
26-174	Dial Scale (5524)	.50
76-226	Drive Shaft	.05
S-4679	Dial Cord Assembly	.20
46-231	Tone Knob	.15
57-596	Escutcheon Plate	.75

Models 6-S-203, 6-S-222, 6-S-223, 6-S-229, 6-S-239, 6-S-241, 7-D-203, 7-D-222, 7-D-223, 7-D-229, 7-D-239, 7-D-241, 7-D-243, 7-D-253

(Chassis Numbers 5638 and 5710)

19-68	Dial Clips	.02
26-144	Dial Scale	.75
32-13	Dial Drive Belt	.15
34-49	Condenser Shaft Gear	.25
34-51	Lower Pinion and Gear	.15
57-601	Escutcheon Plate	1.50
59-41	Split Second Pointer	.10
59-60	Dial Pointer	.15
61-34	Drive Pulley	.10
73-24	8/32x1/4" H.H. Set Screw	.02
76-227	Drive Shaft	.05
80-60	Tension Pulley Spring	.03
80-118	Dial Spring	.15
80-128	Shaft Pulley Spring	.01
83-407	Dial Diffusion Strip	.03
97-91	Lower Gear Stud	.05
192-16	Dial Glass	.25
196-10	Dial Glass Gasket	.10
S-3780	Pulley Sleeve & Pinion	.35
46-221	Band Switch Knob	.20
46-222	Volume Knob	.15

Models 6-J-230, 6-J-257

(Chassis Number 5642)

Same parts as chassis 5638 and 5710 except following dial scale:

26-188	Dial Scale	.75
--------	------------	-----

Models 6-D-202, 6-D-219, 6-D-221, 6-D-238

(Chassis Number 5639)

Same parts as chassis 5521, 5522 and 5524 except the following:

Part No.	Description	Price
26-157	Dial Scale	.50
MS-321	Dial Drive Pulley	.20
76-231	Drive Shaft	.05

Models 6-S-254 and 6-S-256
(Chassis Number 5644)

19-73	Dial Clips	.02
26-163	Dial Scale	1.25
27-16	Flywheel	1.00
32-17	Condenser Drive Belt	.15
34-49	Condenser Shaft Gear	.25
34-51	Lower Pinion and Gear	.15
59-52	Split Second Pointer	.10
59-53	Dial Pointer	.20
61-43	Condenser Shaft Pulley	.15
76-234	Drive Shaft	.20
80-60	Tension Pulley Spring	.03
80-130	Clutch Spring	.03
94-258	Drive Shaft Bushing	.03
192-17	Dial Glass	.40
196-15	Dial Glass Gasket	.10
S-4906	Dial Light Socket (5408)	.10
S-4984	Volume Control Scale	.35
S-4985	Band Ind. Dial	.35
S-5090	Drive Pulley and Clutch	.35
S-5092	Tone Control Scale	.35
46-191	Tone Knob	.15
46-208	Tuning Knob	.25
46-223	Sensitivity Knob	.15
46-224	Volume Knob	.15
57-601	Escutcheon Plate	1.50

Models 7-J-232 and 7-J-259
(Chassis Number 5711)

26-156	Split Second Scale	.50
27-16	Flywheel	1.00
32-14	Dial Drive Belt	.15
34-68	Condenser Shaft Gear	.20
34-69	Lower Drive Gear	.15
34-72	Frequency Pointer Gear	.30
56-48	Scale Connecting Pins	.01
59-58	Split Second Pointer	.20
59-59	Dial Pointer	.15
61-42	Pointer Shaft Pulley	.20
76-228	Drive Shaft	.25
76-229	Split Second Pointer Shaft	.10
80-136	Scale Return Springs	.05
80-137	Dial Glass Springs	.01
80-138	Hairpin Retainer Springs	.01
80-139	Dial Spring	.05
83-491	Scale Spacer Strip	.05
83-499	Felt Strips	.20
93-339	Black Bakelite Pointer Washer	.01
94-258	Drive Shaft Bushing	.03
159-12	Snap Buttons	.02
192-17	Dial Glass	.40
196-13	Dial Glass Gasket	.10
S-4914	Dial Light Socket	.10
S-4974	Band Switch Lever	1.25
S-4981	Broadcast Scale	.75
S-4982	Short Wave Band Scale	.75
S-4986	Tone Control Dial	.35
S-4989	Complete Dial & Mtg. Plate	4.00
S-4990	Drive Shaft Pulley	.40
S-4991	Drive Pulley & Clutch	.50
S-5007	Control Arm and Pin	.40
S-5041	Vol. Cont. Scale	.35
S-5042	Sensitivity Scale	.35
46-191	Tone Control Knob	.15
46-221	Band Switch Knob	.20
46-223	Sensitivity Knob	.15
46-224	Volume Knob	.15
46-232	Tuning Knob	.20
57-601	Escutcheon Plate	1.50

Models 7-S-204, 7-S-232, 7-S-240, 7-S-242, 7-S-258, 7-S-260, 7-S-261

(Chassis Number 5709)

Same parts as 5711 except the following:

Part No.	Description	Price
12-514	Indicator Brkt. (Female)	.05
12-515	Indicator Brkt. (Male)	.05
26-145	Split Second Scale	.50
80-130	Clutch Spring	.03
97-101	Idler Gear Stud	.05
112-3	Spade Lug	.01
118-13	Lever Link	.05
S-4906	Dial Light Socket (5408)	.10
S-4975	Dial Mtg. Plate	1.25
S-4976	Stationary Dial Scale (5905, 1204)	1.50
S-4983	Control Arm & Pin	.40
S-4984	Volume Control Scale	.35
S-4985	Band Ind. Dial	.35
S-5369	Broadcast Scale Assembly (5905, 1204)	.75

Models 9-S-204, 9-S-222, 9-S-242, 9-S-244, 9-S-262, 9-S-263, 9-S-264, 12-S-205, 12-S-232, 12-S-245, 12-S-265, 12-S-266, 12-S-267, 12-S-268, 15-U-246, 15-U-269, 15-U-270, 15-U-271, 15-U-272, 15-U-273

(Chassis Numbers 5905, 1204 and 1501)

Same parts as 5711 and 5709 except the following:

32-14	Dial Drive Belt	.15
32-15	Condenser Drive Belt	.15
32-18	Automatic Drive Belt	.15
61-43	Condenser Shaft Pulley	.15
61-44	Motor Shaft Pulley	.15
76-237	Motor Switch Shaft	.08
76-238	Condenser Drive Shaft	.30
83-499	Felt Strips	.20
85-116	Motor Switch (9 tube)	1.00
85-120	Motor Switch (12 and 15 tube)	1.00
93-339	Black Bakelite Pointer Washer	.01
94-257	Drive Shaft Bushing	.03
97-103	Moveable Scale Pivot	.02
97-107	Motor Mtg. Studs	.05
118-12	Lever Link	.05
MS-321	Dial Drive Pulley	.20
S-4914	Dial Light Socket	.10
S-4976	Stationary Dial Scale (5905, 1204)	1.50
S-5007	Control Arm & Pin	.40
S-5028	Drive Pulley and Clutch	.25
S-5040	Police Dial Assem.	1.00
S-5041	Vol. Control Scale	.35
S-5042	Sensitivity Scale	.35
S-5235	Short Wave Dial Assem. (1501)	.75
S-5238	Broadcast Dial Assem. (1501)	.75
S-5239	Stationary Dial Scale (1501)	.25
S-5264	Complete Motor Assembly	5.00
46-230	Automatic Knob	.15

Important: For knobs other than walnut, add the following letters to part number: Y—ebony, H—maple, W—white, also add 5c to list.

COILS

20-82	R. F. Choke	.25
20-135	R. F. Choke	.50
20-154	Wave Trap Assembly	.65
95-353	1st I. F. Trans.	1.25
95-407	1st I. F. Trans.	1.25

PARTS LIST (Continued)

Part No.	Description	Price
95-408	2nd I. F. Trans.	1.25
95-411	1st I. F. Trans.	1.25
95-412	2nd I. F. Trans.	1.25
95-413	1st I. F. Trans.	1.25
95-414	2nd I. F. Trans.	1.25
95-416	1st I. F. Trans.	1.25
95-417	2nd I. F. Trans.	1.25
95-419	1st I. F. Trans.	1.25
95-420	2nd I. F. Trans.	1.25
95-439	1st I. F. Trans.	1.25
95-440	2nd I. F. Trans.	1.25
95-443	1st I. F. Trans.	1.25
95-444	2nd I. F. Trans.	1.25
S-2778	R. F. Choke	.25
S-4662	Oscillator Coil	.30
S-4721	Oscillator Coil	.50
S-4780	Antenna Coil	1.00
S-4909	Oscillator Coil	.90
S-4934	Antenna Coil & Shield	2.50
S-4941	Antenna Coil & Shield	1.50
S-4942	Oscillator Coil & Shield	1.50
S-4969	Oscillator Coil	1.50
S-5017	Antenna Coil & Shield	1.50
S-5018	Detector Coil & Shield	1.35
S-5019	Oscillator Coil & Shield	1.75
S-5036	Oscillator Coil	.50
S-5037	Oscillator Coil	.50
S-5038	Oscillator Coil	.50
S-5039	Oscillator Coil	.50
S-5043	R. F. Choke	.50
S-5054	Detector Coil	1.50
S-5055	Antenna Coil	2.25
S-5073	Antenna Coil	1.50
S-5074	Oscillator Coil	1.50
S-5100	Antenna Coil	1.25
S-5153	Antenna Coil	1.50
S-5163	Oscillator Coil	1.50
S-5167	Antenna Coil & Cover	1.25
S-5215	Antenna Coil & Shield	1.25
S-5231	Antenna Coil & Shield	1.50
S-5232	Detector Coil & Shield	1.25
S-5265	Antenna Coil & Shield	1.50
S-5266	Detector Coil & Shield	1.50
S-5272	Antenna Coil & Shield	1.50
S-5303	Antenna Coil & Shield	1.50

CONDENSERS

22-127	25 mmfd. 600 volt	.15
22-147	.0005 mfd. 600 volt	.15
22-162	.0001 mfd. 600 volt	.15
22-170	.1 mfd. 400 volt	.20
22-171	.05 mfd. 600 volt	.18
22-177	.2 mfd. 400 volt	.20
22-182	.00025 mfd. 600 volt	.15
22-185	.01 mfd. 200 volt	.12
22-188	.02 mfd. 400 volt	.15
22-190	.1 mfd. 200 volt	.15
22-196	.01 mfd. 600 volt	.18
22-199	.5 mfd. 200 volt	.30
22-212	.05 mfd. 400 volt	.15
22-229	.005 mfd. 600 volt	.18
22-243	.01 mfd. 400 volt	.15
22-250	.05 mfd. 200 volt	.12
22-289	50 mmfd. 600 volt	.15
22-305	2-35 mmfd. Trimmer	.15
22-324	2-35—3 Section Trimmer	.40
22-326	.003 mfd. 400 volt	.15
22-327	.02 mfd. 200 volt	.12
22-350	.25 mfd. 200 volt	.20
22-358	.002 mfd. 600 volt	.18
22-406	Two Gang Variable	2.25
22-408	2-35 mmfd. 2 Section	.30
22-418	2-35 mmfd. Trimmer	.15
22-425	16-8-4 mfd. 450 volts	2.75
22-435	.02 mfd. 600 volt	.18
22-448	.004 mfd. 600 volt	.15
22-455	.01 mfd. 1200 volt	.18
22-487	.05 mfd. 400 volt	.15
22-492	.002 mfd. 600 volt	.18
22-519	200-500 mmfd. Osc. padder	.35
22-524	2-35 mmfd. Trimmer	.15
22-525	.005 mfd. 1000 volt	.18

Part No.	Description	Price
22-546	Two Gang Variable	2.50
22-547	Two Gang Variable	2.50
22-548	Three Gang Variable	4.00
22-549	2-35 mmfd. 4 Section	.50
22-551	16 mfd. 400 volt	.85
22-552	20 mfd. 300 volt	.75
22-554	20 mfd. 400 volt	.85
22-555	30 mfd. 300 volt	.75
22-558	Double Fixed Padder	.60
22-559	Filter	1.75
22-560	Filter	1.60
22-561	.004 mfd. 400 volt	.15
22-562	2-16 mfd. 450 volt	.45
22-563	Fixed Padder	.50
22-566	20-12 mfd. 450 volt	1.60
22-567	Two Gang Variable	2.00
22-568	10-10 mfd. 450 volt	1.45
22-569	12 mfd. 450 volt	.95
22-570	Wave Trap Trimmer	.15
22-571	Filter	1.25
22-572	10-10-10 mfd. 25 volt	1.00
22-573	Filter	.95
22-574	.02 mfd. 600 volt	.18
22-576	Two gang variable	2.00
22-577	Filter	1.15
22-578	Filter	.95
22-579	3 Gang Variable	4.75
22-580	3-10 mfd. 25 volt	1.00
22-582	Filter	1.25
22-583	Air Trimmer	.25
22-584	.002 mfd. 1600 volt	.18
22-585	5 mmfd. Ceramic	.20
22-586	45 mmfd. Ceramic	.20
22-593	2 Gang Variable	2.00
22-596	8-14 mfd. 450 volt	1.75
22-598	2-35 mmfd. 3 Section Trimmer	.40
22-601	10 mmfd. Ceramic	.15
22-625	2-35 mmfd. 3 Section Trimmer	.40

RESISTORS

63-150	10M ohm 1/2 watt	.08
63-160	100M ohm 1/2 watt	.08
63-208	12M ohm 1 watt	.10
63-260	100M ohm 1/4 watt	.07
63-271	1 megohm 1/4 watt	.07
63-282	2200 ohm 1/4 watt	.07
63-296	220M ohm 1/4 watt	.07
63-325	150M ohm 1/4 watt	.07
63-418	1500 ohm 1/2 watt	.08
63-439	2700 ohm 1/4 watt	.07
63-441	1 megohm 1/4 watt	.07
63-520	400M Volume Control	1.35
63-521	50M Tone Control	.90
63-533	13 ohm Flex. Wirewound	.10
63-541	1 megohm Volume Control	1.35
63-547	400M Volume Control	1.35
63-548	1 megohm Volume Control	1.35
63-563	80 ohm Wirewound	.07
63-565	400M ohm Volume Control	1.35
63-568	2 megohm Volume Control	.90
63-569	Candohm Resistor	.65
63-570	Candohm Resistor	.75
63-577	100 ohm 1/4 watt	.07
63-580	330 ohm 1/4 watt	.07
63-581	470 ohm 1/4 watt	.07
63-583	1000 ohm 1/4 watt	.07
63-586	3300 ohm 1/4 watt	.07
63-587	4700 ohm 1/4 watt	.07
63-589	10M ohm 1/4 watt	.07
63-593	47M ohm 1/4 watt	.07
63-595	100M ohm 1/4 watt	.07
63-596	330M ohm 1/4 watt	.07
63-597	470M ohm 1/4 watt	.07
63-605	1000 ohm 1/2 watt	.08
63-608	15M ohm 1 watt	.10
63-609	22M ohm 1/2 watt	.08
63-610	22M ohm 1 watt	.10

Part No.	Description	Price
63-611	2 megohm Volume Control	1.35
63-612	.24 ohm Wirewound	.10
63-613	Three Section Candohm	.30
63-618	22 ohm 1/4 watt	.07
63-631	470 ohm 1/4 watt	.07
63-632	560 ohm 1/4 watt	.07
63-634	820 ohm 1/4 watt	.07
63-638	5600 ohm 1/4 watt	.07
63-639	6800 ohm 1/4 watt	.07
63-643	18M ohm 1/4 watt	.07
63-645	27M ohm 1/4 watt	.07
63-646	33M ohm 1/4 watt	.07
63-647	39 ohm 1/4 watt	.07
63-648	47M ohm 1/4 watt	.07
63-653	150M ohm 1/4 watt	.07
63-654	180M ohm 1/4 watt	.07
63-656	270M ohm 1/4 watt	.07
63-657	330M ohm 1/4 watt	.07
63-658	390M ohm 1/4 watt	.07
63-675	5600 ohm 1/2 watt	.08
63-677	33M ohm 1 watt	.10
63-678	47M ohm 1/2 watt	.08
63-680	10M ohm 1 watt	.10
63-681	56 ohm 1/2 watt	.08
63-682	22M ohm 2 watts	.17
63-684	.64 ohm Wirewound	.07
63-685	210 ohm 1/2 watt	.17
63-686	150 ohm 1/2 watt	.17
63-687	Volume control	1.35
63-688	Volume control	1.35
63-689	Volume control	1.35
63-796	10M ohm 1/2 watt	.08
63-797	2200 ohm 1/2 watt	.08
63-798	Volume control	1.35
63-799	Volume control	1.35
63-800	26 ohm Wirewound	.20
63-801	21 ohm Wirewound	.10
63-802	Candohm Resistor	.65
63-803	2200 ohm 1/2 watt	.08
63-806	3 Section Candohm	.30
63-807	70 ohm Wirewound	.17
63-808	120 ohm Wirewound	.17
63-809	Candohm Resistor	.65
63-810	Candohm Resistor	.17

SPEAKERS

49-117	8" Dynamic Speaker	7.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
	Field Coil	2.50
49-148	12" Dynamic Speaker	12.00
	Cone & Voice Coil	3.00
	Output Transformer	2.50
	Field Coil	5.00
49-153	6" PM Speaker	6.50
	Cone & Voice Coil	1.75
	Output Transformer	1.50
49-162	6" PM Speaker	6.00
	Cone & Voice Coil	1.75
	Output Transformer	1.50
49-164	8" PM Speaker	6.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
49-178	5" Dynamic Speaker	4.50
	Cone & Voice Coil	1.50
	Output Transformer	1.50
	Field Coil	1.50
49-179	8" Dynamic Speaker	6.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
	Field Coil	2.50
49-180	6" Dynamic Speaker	5.00
	Cone & Voice Coil	1.50
	Output Transformer	1.50
	Field Coil	1.50
49-181	10" Dynamic Speaker	8.00
	Cone & Voice Coil	2.50
	Output Transformer	2.50
	Field Coil	2.75

PARTS LIST (Continued)

Part No.	Description	Price
49-183	8" Dynamic Speaker	7.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
	Field Coil	2.50
49-184	12" Dynamic Speaker	10.00
	Cone & Voice Coil	3.00
	Output Transformer	2.50
	Field Coil	5.00
49-185	12" Dynamic Speaker	13.50
	Cone & Voice Coil	2.50
	Output Transformer	2.50
	Field Coil	5.00
49-186	12" Dynamic Speaker	17.50
	Cone & Voice Coil	3.25
	Output Transformer	3.50
	Field Coil	6.00
49-187	12" Dynamic Speaker	17.50
	Cone & Voice Coil	3.25
	Output Transformer	3.50
	Field Coil	6.00
49-188	6" PM Speaker	6.00
	Cone & Voice Coil	1.75
	Output Transformer	1.50
49-189	5" Dynamic Speaker	4.50
	Cone & Voice Coil	1.50
	Output Transformer	1.50
	Field Coil	1.50
49-190	6" Dynamic Speaker	5.00
	Cone & Voice Coil	1.75
	Output Transformer	1.50
	Field Coil	1.75
49-191	5" Dynamic Speaker	4.50
	Cone & Voice Coil	1.50
	Output Transformer	1.50
	Field Coil	1.50
49-193	8" Dynamic Speaker	6.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
	Field Coil	2.50
49-195	12" Dynamic Speaker	13.50
	Cone & Voice Coil	3.00
	Output Transformer	2.50
	Field Coil	5.00
49-198	10" PM Speaker	8.50
	Cone & Voice Coil	2.50
	Output Transformer	2.50
49-200	12" Dynamic Speaker	13.50
	Cone & Voice Coil	3.00
	Output Transformer	3.50
	Field Coil	5.00
49-202	5" Dynamic Speaker	4.50
	Cone & Voice Coil	1.50
	Output Transformer	1.50
	Field Coil	1.50
49-203	8" Dynamic Speaker	7.00
	Cone & Voice Coil	2.00
	Output Transformer	2.50
	Field Coil	2.50
49-204	8" Dynamic Speaker	6.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
	Field Coil	2.00
49-205	10" Dynamic Speaker	8.50
	Cone & Voice Coil	2.50
	Output Transformer	2.50
	Field Coil	2.50
49-206	8" Dynamic Speaker	7.00
	Cone & Voice Coil	2.00
	Output Transformer	2.50
	Field Coil	2.50
49-207	8" PM Speaker	6.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
49-209	6" PM Speaker	6.00
	Cone & Voice Coil	1.75
	Output Transformer	1.50
49-210	8" PM Speaker	6.50
	Cone & Voice Coil	2.00
	Output Transformer	2.50
MISCELLANEOUS		
19-59	Battery Clip (+)	.15
19-60	Battery Clip (-)	.15
44-7	Phono Jack	.10

Part No.	Description	Price
52-112	Battery Cable & Plug	1.50
52-117	Phono Cable & Male Plug	
52-118	A. C. Cable & Plug	
52-119	Phono Cable & Female Plug	
52-120	Phono Cable & Female Plug	
52-121	Phono Cable & Male Plug	
57-11A	Antenna Lead Marker	.05
57-11G	Ground Lead Marker	.05
57-488	Phono-Radio Escutcheon	.35
57-608	Glass Dial Cover Plate	1.25
57-609	Milk-White Glass Plate	
59-56	Station Indicator Pointer	.05
73-8	8/32 x 5/16" H.H. Set Screws	.02
73-21	8/32 x 3/16" Set Screws	.01
73-24	8/32 x 1/4" H.H. Set Screws	.02
78-115	Vibrator Socket	.10
78-128	Speaker Plug Socket	.10
78-133	6H6 Wafer Socket	.10
78-140	No. 38 Wafer Socket	.10
78-141	Vibrator Wafer Socket	.10
78-145	6F5 Wafer Socket	.10
78-148	6Q7 Wafer Socket	.10
78-150	6K7 Wafer Socket	.10
78-151	6A8 Wafer Socket	.10
78-152	6F6 Wafer Socket	.10
78-159	25Z6 Wafer Socket	.10
78-161	Ballast Tube Socket	.10
78-162	6L7 Wafer Socket	.10
78-165	1C7 Wafer Socket	.10
78-166	1D5 Wafer Socket	.10
78-167	1F5 Wafer Socket	.10
78-168	1F7 Wafer Socket	.10
78-169	1H4 Wafer Socket	.10
78-170	1J6 Wafer Socket	.10
78-173	25L6 Wafer Socket	.10
78-174	Indicator Socket & Cable	.75
78-175	6J5 Wafer Socket	.10
78-176	6V6 Wafer Socket	.10
78-182	5Y4 Wafer Socket	.10
78-183	Indicator Socket & Cable	.75
78-184	6T7 Wafer Socket	.10
78-185	6S7 Wafer Socket	.10
78-186	6D8 Wafer Socket	.10
78-187	6L5 Wafer Socket	.10
78-189	Indicator Socket & Cable	.75
78-190	Speaker Plug Socket	.10
78-191	6ZY5 Wafer Socket	.10
78-192	Indicator Socket & Cable (1501)	.75
80-148	Phono Suspension Spring	.02
83-433	Antenna Terminal Strip	.10
85-39	Phono Switch	.85
85-103	Band Selector Switch	1.25
85-104	Band Selector Switch	.75
85-105	Band Selector Switch	.75
85-107	Band Selector Switch	1.75
85-108	Tone Control Switch	.65
85-109	Sensitivity Switch	.65
85-110	Band Selector Switch	1.00
85-112	Band Selector Switch	.65
85-113	Band Selector Switch	.65
85-116	Automatic Switch	1.00
85-117	Sensitivity Switch	1.00
85-120	Motor Switch	1.00
85-123	Tone Switch	.75
85-124	Toggle Switch	1.00
85-125	Power Switch	.65
91-190	No. 10 Battery Wire (Black)	.05
91-191	No. 10 Battery Wire (Red)	.05
93-168	Rubber Cushion Washers	.01
93-215	Rubber Chassis Mtg. Washers	.05
93-229	1/16" x 1/4" x 1 1/4" Felt Washers	.30C
93-320	1/16" x 1/4" x 1" Felt Washers	.20C

Part No.	Description	Price
93-323	1/32" x 29/64" x 3/4" Bakelite Washer	.01
93-343	3/32" x 33/64" x 7/8" Felt Washers	.40C

TRANSFORMERS, CHOKES

95-298	Power Choke	.75
95-324	Power Choke	.75
95-406	117 Volt 50-60 Cy. Trans.	3.75
95-409	Power Choke	1.25
95-410	Power Choke	1.35
95-415	117 Volt 50-60 Cy. Trans.	3.75
95-418	117 Volt 50-60 Cy. Trans.	4.25
95-421	117 Volt 50-60 Cy. Trans.	5.50
95-425	Power Transformer	3.00
95-438	117 Volt 50-60 Cy. Trans.	3.75
95-441	117 Volt 50-60 Cy. Trans.	3.25
95-442	Power Choke	2.25
95-445	Power Transformer	2.50
95-446	Audio Transformer	1.75
95-447	117 Volt 50-60 Cy. Trans.	7.75
95-450	All Voltage 25 Cy. Trans.	7.00
95-451	All Voltage 25 Cy. Trans.	7.00
95-452	All Voltage 25 Cy. Trans.	6.00
95-454	25 Cy. All Voltage Trans.	7.00
95-455	All Voltage 25 Cy. Trans.	9.00
95-456	All Voltage 25 Cy. Trans.	10.50
100-36	Dial Light 6.3 V. 25 Amp.	.09
100-39	Dial Light 2.9 V. 17 Amp.	.12
100-50	Dial Light 2 V. .06 Amp.	.22
100-37	Ballast tube 115 volt	.75
100-38	Ballast tube 115 volt	.75
100-55	Ballast tube 125 volt	.75
100-56	Ballast tube 150 volt	.75
100-56	Ballast tube 150 volt	.75
100-57	Ballast tube 175 volt	.75
100-58	Ballast tube 200 volt	.75
100-59	Ballast tube 220 volt	.75
100-60	Ballast tube 250 volt	.75
100-61	Ballast tube 125 volt	.75
100-62	Ballast tube 150 volt	.75
100-63	Ballast tube 175 volt	.75
100-64	Ballast tube 200 volt	.75
100-65	Ballast tube 220 volt	.75
100-66	Ballast tube 250 volt	.75
102-23	Station Tab Sheet	.05
114-40	Chassis Bolts (10/32 x 7/8")	.40C
114-41	Chassis Bolts (1/4-20 x 1 1/4")	.02
114-42	Chassis Bolts (10/32 x 1/4")	.60C
114-61	Chassis Bolts (10/32 x 1 1/2")	.02
117-38	Band Selector Lever	.10
117-39	Band Selector Lever	.10
118-12	Lever Connecting Link	.05
126-201	Vibrator Shield	.15
126-239	Tube Shield	.10
126-243	Grid Lead Shield	.05
126-244	Spiral Shields	.05
126-248	Electrolytic Shield	.08
126-251	Spiral Shield	.04
126-254	Grid Lead Shield	.03
142-5	Crystal Pickup (Head only)	
159-12	Snap Buttons	.02
159-14	Snap Buttons	.50C
159-17	Snap Buttons	.05
169-27	Automatic Record Changer	80.00
180-2	Shaft Retaining Ring	.01
190-6	Vibrator	3.50
190-11	Vibrator	3.00
S-4567	Acoustic Adapter	3.50
S-5399	Complete Phono Motor	35.00
S-5404	Complete Phono Motor	50.00
S-5408	Phono Motor Assembly	35.00
S-5409	Acoustic Adapter (1501 only)	3.50



USE ONLY GENUINE



REPLACEMENT PARTS and TUBES



ZENITH RADIO CORPORATION


6001 Dickens Avenue

CHICAGO, ILL.

U. S. A.

SOCKET VOLTAGES

TUBE	POSITION	1	2	3	4	5	6	7	8	9
6A8	1st Det. Osc.	0	10	146	50	0	132	5.5	2.5	0
6K7	I.F.	0	16.5	154	50	2	-	10.5	2.	0
6Q7	2nd Det. A.V.C.	0	0	25	0	0	-	5.	1.	0
6V6	Power	0	22	134	154	0	-	16	6	-
6X5	Rect.	0	28	A.C.	-	AC	-	22	166	-




BOTTOM VIEW
OF SOCKET

All voltages measured from point indicated to ground using a 1000 Ohm per Volt meter, antenna and ground disconnected.
Line voltage 31.5 volts.
Consumption 3.9 amp.

ALIGNMENT PROCEDURE

Operation	Conn. Test Osc. to	Dummy Ant.	Set Test Osc. to	Band	Set Dial At	Adj. Tr.	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Brdc't	600	ABCD	I.F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5						FG	Repeat 3 & 4
6	Rec. Ant. Lead	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	L	Rock gang & adj. for max. output



LOCATION OF TRIMMERS

PARTS AND PRICES

MODELS 5X230 5X248 5X274

CHASSIS NO. 5523

Dial Assembly

5 TUBE 32 VOLT

19-68	Dial glass retaining clip	\$.02
26-188	Dial Scale	.75
32-13	Drive belt	.15
34-49	Condenser shaft gear	.25
34-51	Lower pinion and gear	.15
59-41	Split second pointer	.10
59-60	Frequency indicator pointer	.15
61-34	Drive pulley	.10
76-227	Drive shaft	.05
80-60	Tension pulley spring	.03
80-118	Dial spring	.15
80-128	Shaft pulley spring	.01
83-407	Dial light diffusion strips	.03
93-348	Black bakelite pointer washer	.01
94-230	Drive shaft bushing	.10
97-91	Lower gear stud	.05
100-36	Dial lamp 6.3 volt .25 amp.	.09
192-16	Dial glass	.20
196-10	Dial glass gasket	.10
MS-310	Dial reflector & strip assembly	.40
S-3780	Shaft pulley sleeve & pinion assembly	.35
S-4340	Tension pulley & arm assembly	.15
S-4913	Dial light socket & clip assembly	.10

Coils & Chokes

20-82	R. F. choke	.25
95-414	2nd I. F. transformer	1.25
95-443	1st I. F. transformer	1.25
S-4909	Oscillator coil assembly	.90
S-5043	R. F. choke assembly	.50
S-5478	Antenna coil & shield assembly	2.00

Condensers

22-127	25 mmfd.600 volt	.15
22-147	.005 mfd.600 volt	.15
22-162	.0001 mfd.600 volt	.15
22-170	.1 mfd.400 volt	.20
22-171	.05 mfd.600 volt	.18
22-185	.01 mfd.200 volt	.12
22-199	.5 mfd.200 volt	.30
22-212	.05 mfd.400 volt	.15
22-229	.005 mfd.600 volt	.18
22-250	.05 mfd.200 volt	.12
22-327	.02 mfd.200 volt	.12
22-350	.25 mfd.200 volt	.20
22-358	.002 mfd.600 volt	.18
22-435	.02 mfd.600 volt	.18
22-487	.05 mfd.400 volt	.15
22-519	200-550 mmfd. Oscillator padder	.35
22-563	5000 mmfd. padder	.50
22-598	2-35 mmfd. 3 Section trimmer	.40
22-632	Two gang variable condenser	3.00
22-646	.1 mfd.1000 volt	.25
22-647	8-8 mfd. dry electrolytic 450 volt	1.35
22-648	16 mfd. 450 volt 10 mfd. 25 volt	1.35

PARTS AND PRICES

MODELS 5X230, 5X248, 5X274

Resistors

63-160	100,000 ohm $\frac{1}{2}$ watt	\$.08
63-271	1 megohm $\frac{1}{4}$ watt	.07
63-296	220,000 ohm $\frac{1}{4}$ watt	.07
63-520	400,000 ohm Volume Control & Switch	1.35
63-521	50,000 ohm Tone control	.90
63-589	10,000 ohm $\frac{1}{4}$ watt	.07
63-593	47,000 ohm $\frac{1}{4}$ watt	.07
63-597	470,000 ohm $\frac{1}{4}$ watt	.07
63-632	560 ohm $\frac{1}{4}$ watt	.07
63-633	680 ohm $\frac{1}{4}$ watt	.07
63-675	5600 ohm $\frac{1}{2}$ watt	.08
63-678	47,000 ohm $\frac{1}{2}$ watt	.08
63-804	Candohm resistor	.25
63-805	300 ohm wirewound $\frac{1}{2}$ watt	.15
63-928	Candohm resistor	.50

Miscellaneous

46-220	Tuning control knob	.15
46-222	Volume control knob	.15
46-231	Band Selector & tone control knob	.15
49-192	6" Dynamic Speaker (5X230, 5X248)	5.00
208-192	Cone and voice coil for 49-192	2.00
206-192	Output transformer for 49-192	2.00
207-192	Field coil for 49-192	2.00
49-194	8" Dynamic speaker (5X274)	6.00
208-194	Cone & voice coil for 49-194	2.50
206-194	Output transformer for 49-194	2.50
207-194	Field coil for 49-194	2.00
57-597	Escutcheon Plate	1.00
59-56	Station Indicator pointers	.05
62-9	Lamp Plug Receptacle	.10
78-115	Socket for vibrator	.10
78-128	Socket for Speaker Plug	.10
78-148	Socket for 6Q7 tube	.10
78-149	Socket for 6X5 tube	.10
78-150	Socket for 6K7 tube	.10
78-151	Socket for 6A8 tube	.10
78-176	Socket for 6V6 tube	.10
85-113	Band selector switch	.65
93-320	1/16" x 1/4" x 1" Brown felt knob washers	.20C
95-449	Power transformer	1.75
95-467	Power Choke	1.25
102-23	Station indicator tab sheet	.05
114-40	Chassis mounting bolts	.40C
126-239	Tube Shield	.10
126-243	Spiral Grid Lead Shield	.05
136-3	3 Amp. auto type fuse	.08
166-6	Rubber bumper	.03
188-2	Shaft Retaining ring	.01
190-10	Vibrator	3.50

SERVICE MANUAL

ZENITH



GENERAL




Fig. 1. GUARDIAN EAR

The Zenith Radio Nurse is a super-sensitive sound amplifying system made in two units. The Guardian Ear contains a condenser type microphone, speech amplifier, and modulator-oscillator circuit. The generated signal is conducted by means of the lighting circuit and intercepted by the Radio Nurse. The Radio Nurse unit is composed of a detector, audio amplifier and reproducer. Total amplification from microphone to speaker is on the order of 500,000 times. This gain provides a measure of sensitivity capable of amplifying the slightest sounds. Being purely a sound amplifier no attempt is made to attain high fidelity or high power output. The Zenith Radio Nurse is NOT an inter-communicating system nor intended to be used as such. Its use is primarily for the nursery or sick room. Any attempt to obtain great volume by speaking loudly direct into the Guardian Ear will result in serious distortion and speaker rattle.

To test or demonstrate the Radio Nurse elsewhere than in a home the Guardian Ear must be placed in a soundproof box or separate room. This will prevent howling or feedback which normally results from an amplifier where the speaker and microphone units are in close proximity.

CIRCUIT

The output of the condenser microphone in the Guardian Ear is coupled to one triode of a 79 tube. The plate circuit is capacity coupled to the second triode of the same tube. The plate of this second triode is fed to the grid of a 41 tube which acts as modulator to the screen and plate circuit in the same tube. The R.F. carrier is generated by the oscillating screen and plate circuits and coupled to the light circuit by means of a low impedance coupling coil. A harmonic filter is built into the Guardian Ear to prevent radio receiver interference at 600, 900 and 1200 K.C. The harmonic filter consists of part numbers 4, 5 and C6. (See circuit on page 2.)

Bias on both grids of the 79 tube is obtained by the use of Bias Cells. These units have an extremely long life and should not be replaced unless the plate voltages of the 79 tube measure abnormally low. Never test the bias cell with a voltmeter of any kind. The current drawn by the meter will discharge the cell immediately, and no reading will be obtained although the cell may be in good condition. Only a vacuum tube voltmeter will show the true condition of the bias cells.

The receiver is coupled from the line to a 6F5G detector by another low impedance link. The detector is capacity coupled to a 41 output tube.

TUBES

The tubes employed are of standard type, and are used as follows:

Guardian Ear: 1 type 79, 1st and 2nd audio amplifier;
1 type 41 modulator-oscillator; 1 type 84 rectifier.

Radio Nurse: 1 type 6F5G detector; 1 type 41 power output, 1 type 84 rectifier.

Use only Zenith High Quality tubes for replacement.

FREQUENCY ADJUSTMENT

When shipped from the factory, both units are adjusted accurately to 300 K.C. by means of a variable trimmer in each unit. If either trimmer adjustment is moved separately, the circuits will be detuned and loss of sensitivity will result. If for any reason it is suspected that either of the units is not tuned to resonance it is only necessary to readjust the trimmer on the side of the Guardian Ear, until maximum sensitivity is reached. (See Fig. 1.)





Fig. 2. RADIO NURSE

300K.C
TRANSMITTER



300 K.C.
RECEIVER

NOTE - ALL VOLTAGE'S MEASURED FROM
A POINT COMMON TO BOTH THE
CIRCUITS, IN THIS CASE, THE
GROUND PLANE OF THE CIRCUITS
(PAGE 2).

[illegible]

QWS	PART	DESCRIPTION	QWS	PART	DESCRIPTION
C-1	22-668	0.1MFD.	60W	22-669	0.1MFD.
C-2	22-180	.1MFD.	60W	22-181	.1MFD.
C-3	22-182	.0001MFD.	60W	22-435	.001MFD.
C-4	22-435	.001MFD.	60W	22-463	PHOSOR CONGR. VARS
C-5	22-463	PHOSOR CONGR. VARS	60W	22-464	4MFD ELECTROLYTIC
C-6	22-464	4MFD ELECTROLYTIC	60W	22-676	1MFD ELECTROLYTIC
C-7	22-676	1MFD ELECTROLYTIC	60W	22-677	1MFD ELECTROLYTIC
C-8	22-677	1MFD ELECTROLYTIC	60W	22-678	1MFD ELECTROLYTIC
C-9	22-678	1MFD ELECTROLYTIC	60W	22-679	1MFD ELECTROLYTIC
C-10	22-679	1MFD ELECTROLYTIC	60W	22-680	1MFD ELECTROLYTIC
C-11	22-680	1MFD ELECTROLYTIC	60W	22-681	1MFD ELECTROLYTIC
R-1	65-719	470 M OHMS	1/4 W	65-719	470 M OHMS
R-2	65-718	350 M OHMS	1/4 W	65-718	350 M OHMS
R-3	65-944	880 OHMS	1/4 W	65-944	880 OHMS
R-4	65-510	18 M OHMS	1/4 W	65-510	18 M OHMS
R-5	65-921	400 M OHMS VOLUME CONT.	1/4 W	65-921	400 M OHMS VOLUME CONT.
1	20-174	R.R. COIL	1	20-174	R.R. COIL
2	40-231	5" CYLINDRICAL SPEAKER	1	40-231	5" CYLINDRICAL SPEAKER
3	95-400	POWER TRANS. 50-400	1/17 V	95-400	POWER TRANS. 50-400
4	95-512	POWER TRANS. 25-	1/17 V	95-512	POWER TRANS. 25-

ZENITH RADIO NURSE

Maximum sensitivity may be found by placing a watch on the Guardian Ear, and after raising the volume on the Radio Nurse to a point just below feedback, (howl) adjust the Guardian Ear trimmer for maximum volume of the watch tick.

The trimmers have a tuning range of from 250 to 450 K.C. If interference from another Radio Nurse is encountered, it may be eliminated by readjusting either pair of units in the following manner. Shift the frequency of one Radio Nurse (Bakelite unit) slightly or until the interference drops out. The bakelite shell of the Nurse must be removed in order to reach the trimmer. The Guardian Ear of the pair is then tuned to resonance as previously outlined.

THREE WIRE SYSTEMS

In cases where the electric service to the home or apartment is of the 3 wire, 220 volt type, and the transmitter is used on one 110 volt circuit and the receiver on the other, it is sometimes necessary to install a bridging condenser across the outside 220 volt leads to form a path for the signals. To accomplish this, a special bridging condenser was developed.

This condenser is a special oil impregnated unit made for continuous operation on 250 volts A.C. and has a 2.5 ampere fuse sealed inside the condenser case, Zenith part number S-5766.

The condenser is connected to the line by first removing a fuse on one side of the 220 volt circuit and inserting the metal tab into the shell of the fuse socket so that when the fuse is screwed back into place the metal strip makes contact with the shell of the fuse. The remaining condenser wire is fastened under a fuse on the opposite side of the 220 volt circuit in the same manner.

In some installations, fuses are used on both the live side of the line as well as the neutral or ground circuit. In such cases it is imperative that the two fuses to which the condenser is connected be in the live leads and not in the ground side.

The diagram shows a typical installation. If it is found difficult to trace the wiring of the fuse box, simply try the condenser under various pairs of fuses until you find a combination that properly couples the 220 V. circuit, or until a combination is obtained which produces satisfactory operation of the Radio Nurse. This condenser is fully protected by its internal fuse, and even if improperly installed will cause no difficulty whatsoever from short circuits, etc.




Fig. 4. FUSE BOX

IMPORTANT INFORMATION

If The Radio Nurse Lacks Sensitivity: The Radio Nurse is designed to operate under normal home conditions. When it is operated in a commercial establishment, lack of sensitivity may result due to heavy light loads, heavy power loads, high line capacities, split wiring circuits and heavily by-passed or filtered wiring commonly used to reduce line disturbances in radio receivers. The Radio Nurse being a radio frequency operated device depends on freedom of loads or capacity on the line which factors partially or completely bypass the signal. To overcome this condition and obtain proper efficiency from the Radio Nurse in commercial installations, the various factors must be eliminated. If, however, this is not possible, then an isolated power line must be used. Isolation can be accomplished by placing an R.F. choke in each 110 volt lead on the wall outlet, and running the 110 volt leads from the chokes to both the Guardian Ear and the Radio Nurse direct. Such an isolation unit is manufactured under the Zenith part number S-6114. Do not determine that the Radio Nurse lacks sensitivity unless such isolation has been made, and the units separated far enough, and well isolated by separate closed rooms to avoid howl with the volume control set at maximum.

Interference from ACDC receivers. Due to the type of circuit, and rectification system employed in AC-DC receivers, they may cause loud interference in the form of a hum to be heard in the Radio Nurse. This can be overcome by connecting a Zenith filter part No. 22-677 at the socket to which the AC-DC receiver is attached. A soldering iron or curling iron may also cause this interference in which case the same filter units may be applied to the interfering device.

PARTS LIST

Model TA Guardian Ear - 60 Cycle

Condensers

2-138	.2 mfd. 200 volt	\$.15
2-162	.0001 mfd. 600 volt	.15
2-190	.1 mfd. 200 volt	.15
2-435	.02 mfd. 600 volt	.18
2-463	Padder condenser	.30
2-667	4.x 6.x 6.x 5. Electrolytic	1.25
2-669	.01 mfd. 600 volt	.18
2-670	.1 mfd. 400 volt	.20

Resistors

3-464	1. megohm $\frac{1}{4}$ watt	.15
3-715	100 M ohm $\frac{1}{4}$ watt	.15
3-718	330 M ohm $\frac{1}{4}$ watt	.15
3-719	470 M ohm $\frac{1}{4}$ watt	.15
3-722	2.2 megohm $\frac{1}{4}$ watt	.15
3-726	10. megohm $\frac{1}{4}$ watt	.15
3-749	680 ohm $\frac{1}{4}$ watt	.15
3-949	2200 ohm 1 watt	.17

Chassis Parts

5-15	Bias cells	.10
0-172	Oscillator coil assembly	.50
0-173	Line filter choke	.40
8-217	#84 tube socket	.12
8-218	#41 tube socket	.12
8-220	#79 tube socket	.12
8-221	Microphone socket	.07
5-136	On and off switch	.25
5-510	117 volt 50-60 cycle power transformer	2.50
5-17	Rubber grommets for transformer mounting	.01
6-168	Goat tube shield	.10
5762	Complete microphone and housing assembly	2.00
5767	Choke coil assembly	.25

Model TAZ Guardian Ear (25 Cycle)

Same as Model TA 60 cycle with the exception of the following

2-675	8.x 12.x 12.x 5. electrolytic condenser (replaces 22-667)	1.25
6-266	Electrolytic condenser shield (replaces 126-248)	.10
5-511	117 volt 25 cycle power transformer (replaces 95-510)	3.00

Model RA Radio Nurse — 60 cycle

Condensers

22-162	.0001 mfd. 600 volt	\$.15
22-190	.1 mfd. 200 volt	.15
22-435	.02 mfd. 600 volt	.18
22-463	Padder Condenser	.30
22-666	4. x 4. x 5 Electrolytic condenser	.85
22-669	.01 mfd. 600 volt	.18

Resistors

63-510	18 M ohm 2 watt	.25
63-718	330 M ohm $\frac{1}{4}$ watt	.15
63-719	470 M ohm $\frac{1}{4}$ watt	.15
63-944	680 ohm $\frac{1}{2}$ watt	.15
63-951	400 M ohm Volume control	1.35

Miscellaneous Chassis Parts

12-545	Volume control bracket	.05
19-81	Knob tension spring	.01
20-174	R.F. coil assembly	.50
49-231	Dynamic speaker	3.50
208-231	Cone and voice coil	1.00
206-231	Output transformer	1.50
207-231	Field coil assembly	1.00
78-145	6F5 tube socket	.12
78-217	#84 tube socket	.12
78-218	#41 tube socket	.12
95-509	117 volt 50-60 cycle transformer	2.50
110-63	Speaker dust cloth	.10
126-264	Electrolytic shield	.05

Receiver Cabinet Assembly

36-4	Bakelite handle	.50
43-22	Housing Front	1.50
43-23	Housing Rear	2.00
46-241	Knob	.10
112-160	8/32x7/8 Cabinet holding screws	.01
112-162	10/32x27/16 Cabinet holding screws	.02

Model RAZ Radio Nurse (25 Cycle)

Same as Model RA 60 cycle excepting the following

22-674	8.x 8.x 5. Electrolytic condenser (replaces 22-666)	1.10
95-612	117 volt 25 cycle power transformer (replaces 95-509)	3.25
12-547	Volume control mounting bracket (replaces 12-547)	.05

1 Prices Subject to Regular Parts Discount and Change Without Notice

ZENITH RADIO CORPORATION

CHICAGO, U. S. A.

SERVICE MANUAL



1938 AUTOMOBILE RECEIVERS

MODELS
5-M-291
5-M-294
6-M-292
6-M-293
6-M-295

ZENITH RADIO CORPORATION

CHICAGO, U. S. A.





Fig. 2

Tube	Position	1	2	3	4	5	6	7	8	9
6A8G	Mixer Osc.	0	0	240	93.0	*	147	6.0	**	—
6K7G	I. F.	0	0	240	93.0	***	—	6.0	***	—
6Q7G	Det. A. V. C. Audio	0	0	112	—	—	—	6.0	—	1.8
6F6G	Power	0	0	235	250	—	—	6.0	—	16.0
6X5G	Rectifier	—	0	—	—	—	—	6.0	250	—



Voltage at Battery 6.2V

Voltage at Receiver 6V

Antenna disconnected

All voltages measured with 1000 ohms per volt D. C. meter

Total current consumption 7.1 amperes


Sensitivity at 1 watt out put 5-10M

Maximum power output 3.2 watts.

* { —5.8 manual
+4.2 automatic

** { +4.4 manual
+5.0 automatic

*** { +5.2 manual
+4.9 automatic



ANTENNA ALIGNMENT (Models 5-M-291 and 5-M-294)

There is such a great variation in the capacity of different antennas that it is impossible to meet every condition without some means of variable antenna alignment. To accomplish this, 2 screw adjustments are provided on the receiver case as shown in Figure 3. After the set has been completely installed, the proper method of antenna alignment is as follows: Tune in a weak signal at or near 1400 K.C., and carefully adjust the lower screw as indicated in Figure 3 to loudest signal strength. Turn the tuning dial to a station at or near 600 K.C., and carefully adjust the upper left screw, also shown in Figure 3. Do not use a loud local signal for either of the adjustments. The adjustments at both 600 and 1400 K.C. should be repeated not only as a recheck but for more perfect alignment.

MODEL 5-M-294

NOTE: All Socket Voltages identical with 5-M-291 given on page 447. Also tube layout and electrical specifications.

IMPORTANT — ANTENNA ALIGNMENT

Due to the large variation in electrical capacity of different automobile antennas it is necessary to adjust the receiver to the particular antenna used after installation has been made for maximum performance. Model 5-M-294 is equipped with two adjusting screws to accomplish this alignment. The green tag on the side of the receiver case shows the location of the two adjusting screws.

To align, first turn the receiver on with the center knob shown in Fig. 3. Press the tuning knob IN. This places the tuning mechanism in the **manual** operating position. Tune to a weak station near 1400 K.C. and adjust the trimmer directly below the antenna connector to maximum volume. Next tune the receiver to a weak station near 600 K.C. and adjust the trimmer nearest the power pack case for maximum volume. Repeat the adjustments for greatest accuracy.




Fig. 5


AUTOMATIC

To set the automatic buttons, first pull the tuning knob OUT. This shifts the tuning mechanism to the **Automatic** position. Press Automatic button A and turn the volume up and with a small screw driver carefully adjust screw A at bottom of the Automatic unit shown in Fig. 3 to a local station between 1500 to 1050 K.C. Set to exact position of maximum volume and clearest tone. Next adjust trimmer A1 for maximum volume

and clearest tone **on the same station**. It should be noted that there are two trimmer adjustments to each station button. To set the second button press B and tune trimmer B to a local station between 1250 to 850 K.C. Trim with adjustment B1 to best volume and tone on the same station. To set the third button press C and tune trimmer screw C to a station between 1000 to 700 K.C. and corresponding adjustment C1 again for maximum volume of the selected station. Follow the same procedure for the fourth button by pressing button D and using trimmers D and D1 on a local station between 885 to 540 K.C. After all four buttons have been set, cut the call letters of stations selected from the gummed call letter sheet supplied with the receiver. Remove the escutcheon over the automatic buttons by taking out the three screws which hold it in position. Remove the celluloid strip and paste the station call letters in their proper positions by wetting the back of the call letter sticker. The four outlines on the celluloid strip provide the exact points at which the gummed labels are placed. After the call letter stickers are attached replace the celluloid and the escutcheon plate.

SOCKET VOLTAGES 6-M-292, 6-M-293

Tube	Position	1	2	3	4	5	6	7	8	9
6K7G	R. F.	0	6.0	250	78	*	—	0	*	
6A8G	Mixer Osc.	0	6.0	250	78	**	132	0	*	
6K7G	I. F.	0	0	250	78	-3.8	—	6.0	3.5	
6Q7G	Det. A. V. C. Audio	0	0	95	0	—	—	6.0	1.6	
6V6G	Power	0	6.0	240	250	—	—	0	11.5	
6X5G	Rectifier	—	0	—	—	—	—	6.0	255	



Voltage at Battery 6.3
Voltage at Receiver 6.0
Antenna disconnected
All Voltages measured with 1000 ohm per volt meter
Total current consumption 7.4 amperes
Sensitivity at 1 watt output - 1 microvolt
Maximum power output 6 watts.

*Sensitivity position $\left\{ \begin{array}{l} -4.96 \text{ country} \\ -8.0 \text{ city} \\ -9.5 \text{ noise} \end{array} \right.$

**Sensitivity position { —18.5 country
—17.5 city
—15.0 noise




Fig. 7
Tube Position




Fig. 8

ANTENNA ALIGNMENT

"L" position, depending on the capacity of the antenna being used. The "H" position must be used for antennas with a capacity in the range of from 100 to 500 mmfd. The "L" connection must be used for low capacity antennas of from 0 to 125 mmfd. Compare this listing with that given under the various antennas, and the proper position will easily be recognized. After selecting the position desired, place the capping plug back over the hole to prevent motor noise from entering into the antenna circuit of the receiver. Connect the antenna proper by means of the Delco-Remy connector shown in Fig. 8.




SOCKET VOLTAGES MODEL 6-M-295

Tube	Position	1	2	3	4	5	6	7	8	9
6K7G	R. F.	0	6.1	245	100	0	—	0	*	
6A8G	Mixer Osc.	0	6.1	245	100	**	128	0	*	
6K7G	I. F.	0	0	250	100	4.2	—	6.1	4.2	
6Q7G	Det. A. V. C. Audio	0	0	155	0	0	—	6.1	1.9	
6V6G	Power	0	6.1	240	250	0	—	0	12.5	
6X5G	Rectifier	—	0	—	—	—	—	6.1	255	

Sensitivity * { 5.2 Country ** { 11.2 Country ** { 18.5 Country
 { 9.2 City { 8.3 City { 17.5 City
 { 11.2 Noise { 6.5 Noise { 15.0 Noise

Automatic Manual



**BOTTOM VIEW
OF SOCKET**

All other electrical characteristics identical to models 6-M-292 and 6-M-293 shown on page 451.

ANTENNA ALIGNMENT

Manual Tuning: Press the MANUAL button on the automatic key board. This disconnects the automatic system and allows operation of the receiver from the standard tuning mechanism. After adjusting the dial calibration accurately, turn the volume control up full and tune to a weak station near 1400 K.C. Adjust the antenna trimmer A (Fig. 8) to the point of greatest volume. This completes antenna alignment for manual operation. The trimmer does not have to be adjusted at any other point on the dial.

Automatic Tuning: Press automatic button 2 (Fig. 8) This will disconnect the manual tuning mechanism and place the automatic buttons into service. After button 2 has been pressed, turn adjusting screw 2 in either direction until a weak station between 1100 to 1000 K.C. is heard. Now adjust trimmers B and C on the automatic assembly for maximum signal strength of the weak station tuned

in by the number 2 adjusting screw. The automatic is in complete resonance with the antenna over the entire automatic button range and need not be resonated at any other button setting. Adjusting screw 2 may now be tuned to a local station as outlined under "AUTOMATIC" with no further attention to adjustments B or C.




Fig. 10

AUTOMATIC


Study Fig. 8 carefully. Although simple in adjustment, best results will only be obtained if made accurately and by the following procedure.

1. Press button 1. (This button will be on the left if automatic unit is mounted on edge of instrument panel.)

2. Adjust automatic trimmer screw (until a desired local station between 1600 and 1000 K.C. is heard. Turn the screw slowly back and forth over the station as if tuning the dial of a receiver, for clearest reception and best tone quality and allow the screw setting to remain at that point.

3. Press button 2 and tune for a station between 1450 and 900 K.C. on automatic adjusting screw 2.

4. Follow above procedure for buttons 3, 4 and 5 using the ranges shown on Fig. 8.



5. Remove the chrome bezel over the parts adjacent to the automatic buttons and insert the station call letters cut from the sheet supplied. After placing the proper station calls in correct order over the port holes, fasten the escutcheon back in place.

6. Repeat careful adjustment of each automatic trimmer pressing the corresponding button in order from 1 to 5 to obtain best tone, loudest signal and greatest freedom from noise.

IGNITION INTERFERENCE

Remove the center high tension lead of the distributor and insert the suppressor into the distributor at that point. The wire is then placed in the open end of the suppressor. The generator condenser is fastened under the cut-out housing and the wire connected to the generator connection on the cut-out. The coil condenser is attached to the battery connection of the coil and the other end to the coil case. Make absolutely certain that this condenser is not accidentally connected to the distributor side of the coil since this will increase motor noise terrifically and make operation of the receiver highly unsatisfactory when the motor is running. Where two distributors or two coils are employed a corresponding number of condensers and suppressors must be applied. In some instances it might be of benefit to attach a by-pass condenser from one side of the ammeter to a grounded part of the instrument panel. If the dome light is feeding interference to the antenna the lead should be cut where it comes from the post and a switch inserted on the instrument panel at that point, to turn it off and on. In some cases, a by-pass condenser connected to the dome-light lead and grounded at the post is as effective as a separate switch. Try this first.

If additional attention is necessary to reduce motor interference, the motor block must be securely bonded, both at the rear and front supports with $\frac{1}{2}$ inch copper braid. Also bond or ground all metal control cables or pipes feeding from the motor side into the car. These bonds should be made to the control wire or pipe and soldered to the fire wall immediately adjacent on the motor side. As a further precaution the rotor should be lengthened to reduce the gap between it and the distributor head contacts by either peening the end or applying a small quantity of solder at this point.

CIRCUIT ALIGNMENT

MODELS 5-M-291, 5-M-294

Operation	Connect Test Oscillator To	Dummy Antenna	Set Test Osc. To	Manual or Automatic Position	Set Gang Cond.	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Manual	Max. Cap.	A.B.C.D.	I. F. Alignment
2	Rec. Ant. Lead	50 Mmfd.	1530	Manual	Min. Cap.	E	Trim Oscillator
3	Rec. Ant. Lead	50 Mmfd.	1400	Manual	1400	F	Trim Ant. Stage
4	Rec. Ant. Lead	50 Mmfd.	600	Manual	600	G	Adjust Ant. Padder For Max. Output
5	Connect Car Antenna to Set — Tune to Weak Station Around 1400 K. C. — Trim Antenna Trimmer "F" for Maximum Peak Output.						
6	With Set Connected to Car Antenna—Tune To Weak Station Around 600 K. C. —Trim Antenna Padder "G" for Maximum Peak Output.						

See tube layout page 447 for location of aligning trimmers

MODELS 6-M-292, 6-M-293, 6-M-295

Operation	Connect Test Oscillator To	Dummy Antenna	Set Test Osc. To	Manual or Automatic Position	Set Gang Cond.	Adjust Trimmers	Purpose
1	1st Det. Grid	½ Mfd.	252.5	Manual	Max. Cap.	DEFG	I. F. Alignment
2	Rec. Ant. Lead	50 Mmfd.	1600	Manual	Min. Cap.	I	Trim Oscillator
3	Rec. Ant. Lead	50 Mmfd.	1400	Manual	1400	AH	Trim Ant. & R. F. Stage
4	Rec. Ant. Lead	50 Mmfd.	600	Manual	600	J	Rock Gang & Adjust Osc. Padder for Max. Output
5	Rec. Ant. Lead	50 Mmfd.	—	Manual	Tune To A Station Around 900 K. C. and Set Dial for Calibration		
6	Rec. Ant. Lead	50 Mmfd.	1000	Automatic	Range #2	Trim Ant. & R.F. of Automatic Unit — Trimmers "B" - "C"	
7	Connect Car Antenna to Set — Tune to Weak Station Around 1400 K. C. — Trim Antenna Trimmer "A" for Maximum Peak Output.						
8	Trim Automatic Antenna Trimmer "B" to Car Antenna on a Weak Station around 1000 K. C. on Range #2.						

See tube layouts pages 451 and 453 for location of aligning trimmers

PARTS PRICE LIST

1939 AUTOMOBILE SETS AND ACCESSORIES

Model 5M291 Chassis 5527 (Code A)

Model 5M294 Chassis 5530 (Code B)

Model 6M292 Chassis 5645 (Code C)

Model 6M293 Chassis 5645 (Code D)

Model 6M295 Chassis 5650 (Code E)

PART NUMBER	DESCRIPTION	USED IN MODEL	LIST PRICE
Coils and Chokes			
20-166	Filament choke	C-D-E	\$.15
20-169	Oscillator coil	A	.65
20-170	Antenna coil	C-D	.75
20-171	Detector coil	C-D-E	.50
20-175	Hash choke coil	A-B-C-D-E	.20
20-176	Motor noise choke (R.F. Amp.)	A-B	.10
20-178	Motor noise choke	E	.10
20-184	Antenna coil	E	.75
20-185	Oscillator	B	.65
20-186	Compensating coil	E	.50
*20-188	Oscillator coil assy. (Serial Nos. Above 656501)	C-D	.35
20-188	Oscillator coil assy.	E	.35
*95-500	1st I. F. Transformer & Oscillator Coil	C-D	1.50
	(Serial No. Above 656501)		
95-501	2nd I.F. Transformer assy.	C-D-E	1.25
95-504	1st I.F. Transformer assy.	A-B	1.25
95-505	2nd I.F. Transformer assy.	A-B	1.25
95-517	1st I.F. Transformer assy.	E	1.25
*95-524	1st I.F. Transformer assy.	C-D	1.25
	(Serial Nos. Above 656501)		
S5844	Motor noise choke coil	C-D-E	.15
S5952	Antenna coil assy.	A	1.25
S6028	Antenna coil assy.	B	1.25

Condensers

22-82	.001 mfd. 600 volt	C-D-E	.15
22-127	.25 mmfd.	E	.15
22-147	.0005 mfd. 600 volt	A-B	.15
22-162	.0001 mfd. 600 volt	B-C-D-E	.15
22-170	.1 mfd. 400 volt	A-B-C-D-E	.20
22-182	.00025 mfd. 600 volt	A-B-C-D-E	.15
22-185	.01 mfd. 200 volt	C-D	.15
22-190	.1 mfd. 200 volt	C-D-E	.15
22-212	.05 mfd. 400 volt	A-B-C-D	.15
22-219	.03 mfd. 200 volt	A-B	.12
22-229	.005 mfd. 600 volt	A-B-C-D-E	.18
22-250	.05 mfd. 200 volt	A-B-C-D-E	.15
22-287	.03 mfd. 600 volt	A-B	.18
22-319	.005 mfd. 200 volt	A-B-C-D-E	.15
22-327	.02 mfd. 200 volt	A-B-C-D-E	.12
22-435	.02 mfd. 600 volt	E	.18
22-463	Oscillator Padder	C-D	.45
22-47	.00015 mfd. 600 volt	C-D-E	.15
22-654	.5 mfd. 120 volt (Power Pack)	A-B	.20
22-656	7. x 8. x 10. Electrolytic	C-D-E	1.25
22-659	7. x 8. x 10. mfd. Electrolytic	A-B	1.25
22-660	.006 mfd. 1400 volt	A	.20
22-661	Two Gang Variable	A-B	1.75
22-662	600 K.C. Antenna trimmer	A-B	.35
22-663	Oscillator padder	A	.25
22-665	Three Gang Variable	C-D-E	3.50
22-671	.07 mfd. 600 volt	C-D-E	.23
22-672	.006 mfd. 1400 volt	C-D-E	.20
22-678	.25 mfd. 300 volt	A-B-C-D-E	.20
22-682	Oscillator padder	B	.25
22-687	Compensator	B	.25
22-688	Oscillator padder	E	.25
22-690	130-450 mmfd. padder (In selector unit)	E	.25

PART NUMBER	DESCRIPTION	USED IN MODEL	LIST PRICE
22-693	.5 mfd. 120 volt	C-D-E	.25
22-694	75-325 mmfd. padder (In selector unit)	E	.25
22-702	Compensator	E	.20
S-5828	22-657 antenna trimmer & bracket	C-D-E	.30

Resistors

63-464	1 megohm 1/4 watt	A-B-C-D-E	.10
63-697	100 ohms 1/4 watt	C-D-E	.10
63-704	1500 ohms 1/4 watt	A-B-C-D-E	.10
63-705	2200 ohms 1/4 watt (In TS288 Acoustrol)		.10
63-707	4700 ohms 1/4 watt (In X288 Acoustmatic)		.10
63-713	47000 ohms 1/4 watt	A-B-C-D-E	.10
63-715	100,000 ohms 1/4 watt	A-B	.10
63-717	220,000 ohms 1/4 watt	A-B-C-D-E	.10
63-719	470,000 ohms 1/4 watt	A-B-C-D-E	.10
63-746	390,000 ohms 1/4 watt	C-D-E	.10
63-748	560,000 ohms 1/4 watt	A-B	.10
63-749	680,000 ohms 1/4 watt	A-B-C-D-E	.10
63-750	820,000 ohms 1/4 watt	A-B-C-D-E	.10
63-766	39,000 ohms 1/4 watt	A-B-C-D-E	.10
63-775	270,000 ohms 1/4 watt	A-B	.10
63-939	400,000 ohms Volume control with switch	A	1.35
63-940	220 ohms 1/2 w. (In Power Pack)	A-B-C-D-E	.10
63-941	390 ohms 1 watt	A-B	.15
63-942	15,000 ohms 2 watt	A	.25
63-946	33,000 ohms 1 watt	B-C-D-E	.15
63-947	27,000 ohms 2 watt	B-C-D-E	.25
63-948	330 ohms 1 watt	C-D-E	.15
63-950	1 megohm volume control	C-D-E	1.35
63-952	400,000 ohms volume control	B	1.35

Miscellaneous

12-540	Connecting bracket (P. P. to R. F. Amp.)	A-B	.05
46-242	Tuning knob	A-B	.10
46-247	Volume knob	A-B	.10
49-230	8" Dynamic speaker (less O.P. Trans.)	C	4.00
	207-230 Field coil		1.50
	208-230 Cone & voice coil		2.50
49-232	8" Dynamic used in BH277	A-B-D	4.00
	207-232 Field coil		1.50
	208-232 Cone & voice coil		2.50
49-236	8" Dynamic speaker (less O. P. Trans.)	E	4.00
	207-232 Field coil		1.50
	208-236 Cone & voice coil		2.50
52-126	Power supply cable & plug assy.	A-B	.45
58-21	D. R. Male connector		.01
58-22	D. R. Spring		.005
58-23	D. R. Female connector		.01
58-24	D. R. Contact		.01
58-25	D. R. Washer		.01
58-26	D. R. Insulator		.01
58-28	D. R. Fuse holder		.01
78-148	Socket 6Q7G	C-D-E	.10

PARTS PRICE LIST (Cont'd.)

PART NUMBER	DESCRIPTION	USED IN MODEL	LIST PRICE
78-149	Socket 6X5G	A-B-C-D-E	.10
78-207	Socket Vibrator	A-B-C-D-E	.12
78-208	Socket 3 contact speaker plug	C-D-E	.12
78-209	Socket power supply cable plug (R. F. chassis)	A-B	.12
78-210	Socket 6Q7G	A-B	.12
78-211	Socket 6K7G	A-B-C-D-E	.12
78-212	Socket 6A8G	A-B-C-D-E	.12
78-213	Socket 6F6G	A-B	.12
78-215	Socket 6V6G	C-D-E	.12
78-219	Socket 5 contact for Acoustimatic Acoustrol	C-D-E	.12
78-222	Socket 2 contact antenna adjuster	C-D-E	.12
83-531	Connecting strip (R.F. Amp. Amp. & P. P.) rear	A-B	.05
93-309	#10 Shakeproof washer	A-B	.20C
95-497	Power choke	C-D-E	.85
95-498	Power Transformer	C-D-E	3.00
95-499	Audio output transformer	C-D-E	1.25
95-506	Power choke (Power Pack)	A-B	.85
95-507	Audio transformer (Power Pack)	A-B	.85
95-508	Power Transformer (Power Pack)	A-B	2.75
112-43	#6-32x1/4" B.H. Machine screw Pkzd.	A-B	.25C
112-56	#6x1/4" Slotted H.H. Parker-Kalon screw	A-B-C-D-E	.25C
112-147	#10-32x1/4" B.H. Machine screws - Pkzd.	A-B	.35C
112-148	#2x3/16" R.H. Parker-Kalon screw - Cadmium	A-B	.65C
112-149	#8-32x3/16" B.H. Machine screw - Pkzd.	A-B	.25C
112-169	#2x3/16" B. H. Parker-Kalon Screw - Statuary Bronze	A-B	.65C
114-48	#6-32x1/4" Slotted H.H. Machine screw	A-B	.35C
114-64	#6x1/4" Parker-Kalon Acorn Hd. screw - Pkzd.	A-B	.25C
114-66	#6x3/8" Parker-Kalon Acorn Hd. screw - Pkzd.	A-B	.25C
114-68	#8x1/4" Slotted H.H. self-tapping case screw	C-D-E	.30C
114-69	#4x1 1/4" P-K acorn head screws Pkzd.	A-B	.25C
126-131	Goat tube shield (large)	A-B-C-D-E	.10
126-168	Goat tube shield (small)	C-D-E	.10
159-21	Cinch snap buttons	A-B	.02
159-24	Plug button (antenna trimmer)	C-D-E	.05
183-10	Rubber band	C-D-E	.02
190-13	Vibrator	A-B-C-D-E	2.75
S5737	Low reactance condenser & brkt.	A-B	.25
S5739	Battery Cable assy. (R.F. chassis)	A-B	.20
S5749	Tone control switch assy.	A-B	.35
S5838	Shield for electrolytic condenser	C-D-E	.15
S5857	Rubber coupling-pin assy.	C-D-E	.10
S5860	Battery cable - chassis end	C-D-E	.10
S6066	Manual & automatic switch assy.	E	2.25

Dial Parts For 5M291 - 5M294

19-82	Tuning shaft tension clip	A-B	.07
*26-191	Dial scale	A	.15
*26-195	Dial scale	A-B	.15
*27-22	Dial pointer disc	A-B	.10
34-74	Drive pinion	A	.35
54-112	Tuning Shaft lock nut	B	.04
57-626	Dial escutcheon plate	B	.20
73-32	#8-32x3/16" self-locking slotted set screw	A-B	.02
93-2	Spacer washer (used with 26-195)	A-B	.05C
100-36	Dial lamp 6.3 volt bayonet type	A-B	.09
114-69	#4-40x1/4" screws (used with 27-22)	A-B	.04
192-26	Dial crystal	A-B	.05
*MS407	Dial pointer	A	.35
S4906	Dial lamp socket & clip assy.	A-B	.10

PART NUMBER	DESCRIPTION	USED IN MODEL	LIST PRICE
S5735	Condenser Gear and bushing assem.	A-B	.20
S5738	Dial cover & escutcheon	A-B	.65
*Early 5M291 models used 26-191 scale and MS407 dial pointer. Later models used 26-195 scale & 27-22 pointer disc.			

Control Head Components 6M292 - 6M293 - 6M295

S5741	Tuning shaft gears & housing (mtd. on chassis box)	C-D-E	2.00
S5742	Volume control coupling shaft - switch and battery cable assembly consisting of	C-D-E	3.00
1	#52-127 battery cable (fuse to ammeter)	C-D-E	.30
1	#52-136 battery cable (fuse to switch)	C-D-E	.30
1	#52-137 battery cable (switch to set)	C-D-E	.50
1	#52-138 dial light cable & socket	C-D-E	.30
1	#58-26 D.R. Fuse bushing	C-D-E	.01
1	#76-256 volume control coupling shaft & bracket	C-D-E	1.50
1	- #85-138 S.P.S.T. switch	C-D-E	.40
1	- #100-36 dial lamp	C-D-E	.09
1	- #136-6 15 ampere fuse	C-D-E	.05
S5743	Dial drive gears - housing & scale assy.	C-D-E	2.25
76-247	26-192 dial scale & hub assy.	C-D-E	.65
76-250	Volume control flexible shaft 24"	C-D-E	1.00
76-253	Scale drive flexible shaft 23 1/8"	C-D-E	1.00
	Tuning control flexible shaft 25 1/2"	C-D-E	1.00

Optional Control Shafts

76-248	Volume control flexible shaft 30"	C-D-E	1.00
76-249	Volume control flexible shaft 36"	C-D-E	1.00
76-251	Scale drive flexible shaft 29 1/8"	C-D-E	1.00
76-252	Scale drive flexible shaft 35 1/8"	C-D-E	1.00
76-254	Tuning control flexible shaft 31 1/2"	C-D-E	1.00
76-255	Tuning control flexible shaft 37 1/2"	C-D-E	1.00

6M295 Selector Unit Assembly (On Chassis)

22-690	130-450 mmfd. padder condenser	E	.25
22-694	75-325 mmfd. padder condenser	E	.25
52-140	Cable & plug assembly	E	1.00
57-650	Terminal plate	E	1.00
80-164	Switch bar tension spring	E	.03
80-165	Latch bar tension spring	E	.03
83-555	Latch bar	E	.10
112-167	Inductance coil adjusting screw	E	.03
158-2	Magnet armature	E	.01
S5943	Electro-magnet coils		.75
S5970	Inductance coil & core assembly (red)	E	1.00
S5971	Inductance coil & core assembly (green)	E	1.00
S5972	Inductance coil & core assembly (yellow)	E	1.00
S5973	Inductance coil & core assembly (blue)	E	1.00
S5974	Inductance coil & core assembly (white)	E	1.00
S6130	Switch contact bar & pin		.10

PARTS PRICE LIST (Cont'd.)

6M295 Automatic Control Switch Assembly

46-248	Station selector knob	E	.05
46-249	Station selector knob (Manual)	E	.05
52-139	Cable & plug assembly	E	1.00
80-168	Knob thrust spring	E	.25C
83-553	Celluloid strip (printed)	E	.05
83-579	Celluloid strip (plain)	E	.02
100-36	6.3 volt pilot lamp	E	.09
102-40	Station indicator call letter sheet	E	.25

Parts For Automatic Tuner - 5M294

46-239	Selector Switch knob	B	.03
57-641	Selector switch escutcheon plate	B	.15
83-552	Celluloid dial strip	B	.05
85-142	Selector switch assembly	B	2.00
102-40	Station indicator call letter sheet	B	.25
112-174	Inductance adjusting screw	B	.10
112-177	Trimmer adjusting screw	B	.10
184-3	Steel ball	B	.01
S5954	Inductance coil (red) 915-1550	B	.15
	K.C.	B	.15
S5955	Inductance coil (green) 820-1400	B	.15
	K.C.	B	.15
S5956	Inductance coil (yellow) 630-1050	B	.15
	K.C.	B	.15
S5957	Inductance coil (blue) 535-860	B	.15
	K.C.	B	.15
S6031	Manual-automatic switch frame	B	.60
	(With contact strip)		
S6033	Manual-automatic switch arm	B	.25

TS288 — Zenith Acoustrol

S5923	Housing & switch assembly		.75
52-134	Cable & plug assembly		.75
57-632	Mounting plate (back)		.25
63-705	2200 ohm 1/4 watt resistor		.10
112-115	6/32 x 1/4 B.H. machine screws		.30C

X288 — Zenith Acoustimatic

S5931	Dial light socket - bulb & wire assembly		.15
100-36	Dial light bulb		.09
52-129	Cable & plug assembly		.75
57-632	Mounting plate (back)		.25
63-707	4700 ohm 1/4 watt resistor		.10
63-751	1000 ohm 1/4 watt resistor		.10
83-545	Celluloid strip		.10
83-575	Celluloid diffusion strip (green)		.05
85-135	Switch		2.25
114-45	#8 x 3/8" H.H. slotted self tapping screws		.30C

Z288 — Zenith Steering Column Shell

15-24	Mounting cap		.75
-------	--------------------	--	-----

33-71	Housing frame & holding clamp		.75
46-240	Control knob		.15
54-102	3/8 x 32 x 1/2 hex nuts		.25C
57-631	Control mounting plate		.05
73-25	10/32 x 5/16 headless set screws		.02
94-238	Paper bushings		.01
112-131	8/32 x 1/4" B. H. machine screws (N.P.)		.50C
112-155	6/32x1/4" B.H. machine screws (chromized)		.20C
115-16	10/32 x 3/4 fillister head machine screws		.75C

BH277 — 8" Firewall Speaker (S-5721)

43-25	Composition housing assembly		2.00
49-232	8" dynamic speaker assembly		4.00
208-232	Cone & voice coil assembly		2.00
207-232	Field coil assembly		1.50
52-128	Cable & plug assembly		.75
54-30	8/32 x 5/16 hex nuts		.25C
54-77	5/16-18 x 1/2 hex nuts		.01
74-18	Grill screens		.10
97-110	Mounting stud		.08
147-60	Wood spacer block		.10

Set Mounting Parts 6M292 - 6M293 - 6M294

22-194	Generator condenser		.50
22-565	Ignition coil condenser		.30
58-21	D. R. male connector		.01
58-24	D. R. bushing & ferrule		.01
63-336	Distributor suppressor		.30
93-222	7/16" Internal shakeproof washer		.60C
93-233	Set mounting bolt washer		.05
144-14	7/16" x 3" carriage bolt & nut		.05

Installation Accessories - 5M291 - 5M294

22-194	.5 mfd. 200 volt generator condenser		.50
52-97	Battery cable (ammeter end)		.25
58-21	D.R. male connector		.01
58-24	D.R. bushing & ferrule		.01
58-26	D.R. fuse bushing		.01
63-336	Distributor suppressor		.30
73-18	10/32 x 3/16" cuppoint headless set screw		.01
94-261	Black paper bushing (small)		.05
94-262	Black paper bushing (large)		.05
115-15	10/32 x 1/2" fillister head machine screw		.40C
136-6	15 Ampere fuse		.05
S5750	Mounting U clamp with set screw		.25

All prices are subject to regular discount
and change without notice.

ZENITH RADIO CORPORATION

CHICAGO, U. S. A.

SERVICE MANUAL




1939 RECEIVERS

Model	Chassis	Page	Model	Chassis	Page
4-B-313	5410	462	6-S-330	5648	476
4-B-314	5411	464	6-S-361	5648	476
4-B-317	5411	464	6-S-341	5649	478
5-R-303	5528	466	6-S-362	5649	478
5-R-312	5528	466	6-B-321	5653	480
5-R-316	5528	466	6-J-322	5654	482
5-R-317	5528	466	6-J-357	5654	482
5-R-337	5528	466	7-J-323	5715	484
5-S-319	5529	468	7-J-368	5715	484
5-S-327	5529	468	7-S-323	5714	486
5-S-330	5529	468	7-S-342	5714	486
5-S-338	5529	468	7-S-343	5714	486
5-S-339	5529	468	7-S-363	5714	486
6-D-302	5646	470	7-S-364	5714	486
6-D-311	5646	470	7-S-366	5714	486
6-D-326	5646	470	9-S-365	5906	488
6-D-336	5646	470	9-S-307	5907	490
6-D-360	5646	470	9-S-324	5907	490
6-D-312	5647	472	9-S-344	5907	490
6-D-316	5647	472	9-S-367	5907	490
6-D-317	5647	472	9-S-369	5907	490
6-D-337	5647	472	12-S-345	1206	492
6-S-301	5651	474	12-S-370	1206	492
6-S-304	5651	474	12-S-371	1206	492
6-S-305	5651	474	15-S-308	1502	494
6-S-306	5651	474	15-S-346	1502	494
6-S-321	5651	474	15-S-372	1502	494
6-S-322	5651	474	15-S-373	1502	494
6-S-340	5651	474	Phono Connections		496
			Part Price List		497

All prices contained herein were effective at time of receiver production. Check your Zenith distributor for latest prices.

ZENITH RADIO CORPORATION
CHICAGO, U. S. A.

AUTOMATIC RANGES



NOTE—Buttons numbered from left to right, or top to bottom as they appear on receivers, except on model 6B321 (Chassis 5653) and Models 6S322 and 6S357 (Chassis 5654) which are reversed.

ALIGNMENT INSTRUCTIONS

The proper procedure for the correct alignment of each chassis is outlined on the page opposite each circuit diagram.

The operations are outlined in consecutive order, and the instructions are under the following headings —

OSC. CONNECTED TO — tells where the output of the service oscillator is to be connected.

DUMMY — gives the proper capacity or resistance which should be connected in series with the service oscillator output.

TEST OSC. — Set test oscillator to frequency shown.

BAND — Set the receiver band switch to the position shown.

DIAL — The receiver should be set at the frequency shown.

TRIMMER — This column tells which trimmer (or trimmers) are to be adjusted for each operation.

The chassis drawing has each trimmer indicated by a letter corresponding to the instructions.


PURPOSE—This column tells what is being accomplished by each operation.

If these instructions are carefully followed each chassis will be easily and correctly realigned.

SERVICE HINTS

Chassis	Complaint	Cause and Remedy
5907 & 1206 only	Distortion	Very much like blocking AVC action. Can usually be traced to open filter section.
1502 only	Won't log	Can be traced to loose PK screw in gang hub gear.
5714 only	Noisy automatic or automatic dead	Dirt on contacts or warped strip. Shorted at switch to ground or shorted compensating condenser.
	Automatic dead 1 or more positions	Open coils — usually broken leads or poor contact at switch. Open leads to R. F. section of automatic or leaky or open compensating condenser. Padder loose — out of adjustment or all plates not soldered.
	Automatic weak	
	Eye flutters	Open filter.
	Eye overlaps on strong signal	Open AVC resistors
	No eye action	Shorted condenser (C7.)
	Chirps on medium to loud signal	Leaky condenser across speaker
Radiogram	No effect	Insulation on 33m resistor cut through and shorts to cathode lug. Open leads, poor contact at switch, open condenser. 5714 only — plate lead of I.F. too far away from chassis. Push down close to metal base.
	Too much change on some, none on others.	Condenser shorted or leads shorting to switch.
	Tone changes with different settings of volume control.	Defective volume control or shorted terminal either of tone switch or volume control. Poor contacts and defective or shorted volume control taps.
	Noisy when tuning	Dirty wipers or gang plates. Flywheel touching band switch lug. Volume control or drive shaft not making good contact to ground. 5714 — Volume control shaft and drive shaft out of line.
	Volume control has two peaks and distorts at low volume.	Isolate 6F5 grid circuit from I.F. plate leads. (Later sets have I.F. plate lead shielded.)
5714 only	Set whistles at medium volume.	Open filter condenser.
	Noisy between signals	—Loose connection or open condenser across RF choke.
Battery Sets	Hash	Loose cover of power pack.
	Hash on automatic position.	Automatic assembly touching power pack. Insulate at point of contact.

CONVERTER 6A8G



ZENITH

AUTOMATIC TUNING SYSTEM

The Zenith automatic tuning system is designed so as to be very simple in adjustment, and to remain in adjustment regardless of changes in humidity, temperature or vibration. This system makes use of the fact that the inductance of a winding varies directly with any change in the permeability of the core material of the coil. A switch is incorporated in each receiver which allows the normal tuned circuits, consisting of a coil and variable condenser in the oscillator, first detector, and, in some cases, the R.F. section of the receiver to be disconnected and replaced by very small fixed windings which may be tuned over a considerable range of frequency by means of a change in the core material.

Specially prepared iron slugs which have very low losses at radio frequency are so arranged that they may be mechanically moved in and out of the field of the afore mentioned coils. The permeability of these iron slugs is naturally much higher than that of air, and as they are moved in or out of the field of the coil, the inductance and natural period of the coil varies accordingly. It is quite

easy to arrange such coils and iron slugs so that they may be tuned in tandem, that is, two or more iron slugs moved simultaneously into corresponding coils. This allows the receiver to be designed having only one tuning adjustment for each bank of coils and corresponding button.


As you will see on the circuit above, one button can be pressed to disconnect all automatic coils, and allows the normal tuning system of a coil and variable condenser to operate. On those receivers having short wave band, this switch is a part of the band switch. When the band switch is turned to the automatic position, or, in the smaller receivers, when one of the automatic buttons is pushed, this tuned circuit is disconnected, and the automatic coils are in circuit. The range of each set of coils will vary from 300 k.c. to 600 k.c., depending over which portion of the broadcast band they are designed to operate, and after being adjusted for a certain station within their range will come into operation whenever the corresponding button is pushed in.

The antenna is coupled to the input of the 1st detector by means of a 50 mmfd. condenser (C2) and an antenna compensating condenser (C5) is used to compensate for variations in antenna capacity. This condenser is preset at the factory, and under most conditions it will not be necessary to change it. However, where there is a seeming lack of sensitivity when tuning automatically, the condenser may very easily be reset by setting one of the automatic buttons at approximately the center of the broadcast band, tuning the button to a point where no station is heard, and readjusting the antenna compensating condenser to a point where the background noise is loudest. The button may then be re-set for whatever station is desired. This setting of the antenna condenser will be effective over the entire broadcast band and for all buttons.

In the oscillator circuit, it is necessary to alter the tuning curve so as to provide for tracking between the oscillator and first detector circuits. In the normal tuned circuit, this may be easily accomplished by means of a trimmer and padding condenser working in conjunction with the oscillator section of the variable condenser. However, as no variable condenser is used with the iron core coils, a different method must be resorted to. A small winding connected in series with the grid end of the automatic windings, and so placed as not to be affected by the iron core will, if properly designed, alter the shape of the tuning curve at the high frequency portion of the coil's range. Also, when two inductances are connected in parallel, the maximum inductance is limited by the size of the smaller of the two inductances. The upper portion of coil No. 3 in the above drawing is the padder winding, and also serves as a means of coupling to the oscillator plate circuit, and when used in conjunction with the smaller winding mentioned above alters the shape of the tuning curve so as to allow excellent tracking.

Variations in humidity and temperature are compensated for by means of condenser C6 which consists of a small fixed condenser composed of silver surfaces sprayed on a special ceramic tube which changes its capacity in the opposite way from any changes in the coil, and will compensate for the same.

This automatic system is remarkably simple and trouble free, and once set up for a customer should not require any further attention until it is desired to reset for other stations which can be easily accomplished by the customer himself.



DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION
C-1	32-495	750 OHM VARIABLE	P-9	63-571	1M500M
C-2	32-165	.01 MFD.	P-10	63-160	100 M OHM
C-4	32-390	.25 MFD.	P-11	63-584	100 OHM
C-5	32-192	.0001 MFD.	P-12	63-595	100 OHM
C-6	32-167	.0005 MFD.	P-13	63-296	250 M OHM
C-7	32-188	.02 MFD.	P-14	63-297	475 M OHM
C-8	32-449	.004 MFD.	P-15	63-405	100 OHM
C-9	32-212	.05 MFD.	P-16	63-377	100 OHM
C-10	32-199	.5 MFD.	P-17	63-577	100 OHM
C-11	32-250	.05 MFD.	P-18	63-577	100 OHM
C-12	32-182	.0005 MFD.	P-19	63-577	100 OHM
C-13	32-649	.01 MFD.	P-20	63-577	100 OHM
C-14	32-739	10MFD. ELECTROLYTIC	P-21	63-577	100 OHM
C-15	32-739	15 MFD.	P-22	63-577	100 OHM
C-16	32-739	15 MFD.	P-23	63-577	100 OHM
P-1	63-507	4700 OHM	P-24	63-577	100 OHM
P-2	63-629	500 OHM	P-25	63-577	100 OHM
P-3	63-599	47 K OHM	P-26	63-577	100 OHM
P-4	63-590	60 K OHM	P-27	63-577	100 OHM

Chassis No. 5410

Model 4B313

CHASSIS No. 5410

SOCKET
VOLTAGES

NOTE

Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.


Battery Voltage at chassis 6.2 v.

Battery Consumption 2.3 am-pere.

(A) Bias for 6G6 measured from point "B" to chassis.

6A8G or 6D8G
1ST. DET.-OSC.

6K7G or 6S7G
I.F. AMP




LEGEND

- SH — Shield
- H — Heater
- P — Plate
- S — Screen
- G — Grid
- SU — Suppressor
- D — Diode
- K — Cathode
- NC — No Connection

FRONT OF CHASSIS


6G6G
OUTPUT



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.



NOTE—MANUAL AUTOMATIC SWITCH
SHOWN IN AUTOMATIC POSITION—

MODEL 4-B-314
SPEAKER 49-262-5*

I.F. FREQUENCY 455 K.C.
4-TUBE SUPERHETERODYNE
CHASSIS No. 5411—6V-SINGLE BAND
ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
C-1	500K VARIABLE	4	95-513	137 I.F. TRANS.	
C-2	50 MFD 50 V	5	95-513	2ND I.F. TRANS.	
C-3	TRIMMER CONDENSER	6	1-5043	CHOKE 400 OHM	
C-4	COMPENSATING CONDENSER	7	1-5043	1/2 100 OHM	
C-5	500 MFD 50 V	8	95-513	2ND I.F. TRANS.	
C-6	500 MFD 50 V	9	95-513	2ND I.F. TRANS.	
C-7	500 MFD 50 V	10	95-513	2ND I.F. TRANS.	
C-8	500 MFD 50 V	11	95-513	2ND I.F. TRANS.	
C-9	500 MFD 50 V	12	95-513	2ND I.F. TRANS.	
C-10	500 MFD 50 V	13	95-513	2ND I.F. TRANS.	
C-11	500 MFD 50 V	14	95-513	2ND I.F. TRANS.	
C-12	500 MFD 50 V	15	95-513	2ND I.F. TRANS.	
C-13	500 MFD 50 V	16	95-513	2ND I.F. TRANS.	
C-14	500 MFD 50 V	17	95-513	2ND I.F. TRANS.	
C-15	500 MFD 50 V	18	95-513	2ND I.F. TRANS.	
C-16	500 MFD 50 V	19	95-513	2ND I.F. TRANS.	
C-17	500 MFD 50 V	20	95-513	2ND I.F. TRANS.	
C-18	500 MFD 50 V	21	95-513	2ND I.F. TRANS.	
C-19	500 MFD 50 V	22	95-513	2ND I.F. TRANS.	

Chassis No. 5411

Models 4B314, 4B317

CHASSIS No. 5411

SOCKET
VOLTAGES

NOTE

Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.


Battery Voltage at chassis 6.2 v.

Battery Consumption 2.3 am-pere.

(A) Bias for 6G6 measured from point "B" to chassis.


6A8G or 6D8G
1ST. DET.-OSC.

6K7G or 6S7G
I.F. AMP.



LEGEND


- SH — Shield
- H — Heater
- P — Plate
- S — Screen
- G — Grid
- SU — Suppressor
- D — Diode
- K — Cathode
- NC — No Connection



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.



I.F. FREQUENCY 455 K.C.
5 TUBE SUPERHETERODYNE
CHASSIS NO. 5528 A.C.
ZENITH RADIO CORPORATION
CHICAGO, ILL.

DIAG. NO.	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION
C-1	22-691	750 OHM 60W VAR COND.	R-1	63-597	4	95-513	1ST I.F. TRANS.
C-2	22-289	50 OHM MFD.	R-2	63-593	5	95-520	2ND I.F. TRANS.
C-3	22-162	.0001 MFD.	R-3	63-208	6	95-521	POWER TRANS. (100V, 50-60~)
C-4	22-250	.005 MFD.	R-4	63-271	7	95-521	POWER TRANS. 25~
C-5	22-519	TRIMMER COND.	R-5	63-296	8	100-36	PILOT LIGHT .25 A 6.3V
C-6	22-729	COMPENSATING COND.	R-6	63-658	9		5 TUBE TRANS.
C-7	22-182	.00025 MFD.	R-7	63-260	10		
C-8	22-212	.01 MFD.	R-8	63-373			
C-9	22-196	.01 MFD.	R-9	63-606			
C-10	22-147	.0005 MFD.	R-10	63-955			
C-12	22-691	8 MFD. ELECTROLYTIC					
C-13	22-692	8 MFD. ELECTROLYTIC					

Chassis No. 5528

Models 5R303, 5R312, 5R316, 5R317, 5R337

CHASSIS No. 5528

SOCKET VOLTAGES

NOTE


Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.

Line voltage 115 v. Consumption 45 watts.


Power output 3.5 watts.

(A) Bias for 6A8 — 6K7 and diodes of 6Q7 measured across resistor R9.

(B) Bias for triode section of 6Q7 and 6K6 measured across R8 and R9.




- LEGEND**
- NC — No-Connection
 - VC — Volume Control
 - SH — Shield
 - H — Heater
 - P — Plate
 - S — Screen
 - G — Grid
 - SU — Suppressor
 - D — Diode
 - K — Cathode
 - F — Filament



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.



SPEAKER	MODEL
49-242-5"	5-S-319
49-240-6"	5-S-320
49-244-6"	5-S-327
49-240-6"	5-S-338
49-240-6"	5-S-339

I.F. FREQUENCY 455 K.C.
5 TUBE SUPERHETERODYNE
CHASSIS NO. 5529 A.C. 2 BAND
ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS

NOTE-
 TRIMMERS "F" & "A"
 MOUNTED ON BASE PLATE
 STRIP # 22-645-

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
C-1 22-288	VAR. COND.	P-1 63-593	270M OHM	95-513	1ST. I.F. TRANS.	95-513	1ST. I.F. TRANS.	95-513	1ST. I.F. TRANS.
C-2 22-289	50 MMFD	P-2 63-593	47 M OHM	95-514	2ND. I.F. TRANS.	95-514	2ND. I.F. TRANS.	95-514	2ND. I.F. TRANS.
C-3 22-162	0001 MFD	P-3 63-593	15M OHM	95-521	POWER TRANS. 50-60-117VAT	95-521	POWER TRANS. 50-60-117VAT	95-521	POWER TRANS. 50-60-117VAT
C-4 22-212	05 MFD	P-4 63-593	22 M OHM	95-522	PILOT LIGHT 25A - 6.3V	95-522	PILOT LIGHT 25A - 6.3V	95-522	PILOT LIGHT 25A - 6.3V
C-5 22-280	05 MFD	P-5 63-593	1M OHM	95-523	SPEAKER TRANS.	95-523	SPEAKER TRANS.	95-523	SPEAKER TRANS.
C-6 22-167	2.5 MMFD	P-6 63-593	220 M OHM	100-36	1ST. I.F. TRANS. SEC.	100-36	1ST. I.F. TRANS. SEC.	100-36	1ST. I.F. TRANS. SEC.
C-7 22-705	COMPENSATING COND.	P-7 63-593	330 M OHM	100-36	2ND. I.F. TRANS. SEC.	100-36	2ND. I.F. TRANS. SEC.	100-36	2ND. I.F. TRANS. SEC.
C-8 22-563	FIXED PHOSPHOR	P-8 63-593	100 M OHM	100-36	3RD. I.F. TRANS. SEC.	100-36	3RD. I.F. TRANS. SEC.	100-36	3RD. I.F. TRANS. SEC.
C-9 22-338	TRIMMER COND.	P-9 63-593	150 OHM WIREWOUND	100-36	4TH. I.F. TRANS. SEC.	100-36	4TH. I.F. TRANS. SEC.	100-36	4TH. I.F. TRANS. SEC.
C-10 22-519	01 MFD	P-10 63-593	150 OHM WIREWOUND	100-36	5TH. I.F. TRANS. SEC.	100-36	5TH. I.F. TRANS. SEC.	100-36	5TH. I.F. TRANS. SEC.
C-11 22-196	004 MFD	P-11 63-593	220 OHM WIREWOUND	100-36	6TH. I.F. TRANS. SEC.	100-36	6TH. I.F. TRANS. SEC.	100-36	6TH. I.F. TRANS. SEC.
C-12 22-443	004 MFD	P-12 63-593	220 OHM WIREWOUND	100-36	7TH. I.F. TRANS. SEC.	100-36	7TH. I.F. TRANS. SEC.	100-36	7TH. I.F. TRANS. SEC.
C-13 22-117	0005 MFD	P-13 63-593	220 OHM WIREWOUND	100-36	8TH. I.F. TRANS. SEC.	100-36	8TH. I.F. TRANS. SEC.	100-36	8TH. I.F. TRANS. SEC.
C-14 22-180	1 MFD	P-14 63-593	220 OHM WIREWOUND	100-36	9TH. I.F. TRANS. SEC.	100-36	9TH. I.F. TRANS. SEC.	100-36	9TH. I.F. TRANS. SEC.
C-15 22-455	02 MFD	P-15 63-593	220 OHM WIREWOUND	100-36	10TH. I.F. TRANS. SEC.	100-36	10TH. I.F. TRANS. SEC.	100-36	10TH. I.F. TRANS. SEC.
C-16 22-700	8 MFD ELECTROLYTIC	P-16 63-593	220 OHM WIREWOUND	100-36	11TH. I.F. TRANS. SEC.	100-36	11TH. I.F. TRANS. SEC.	100-36	11TH. I.F. TRANS. SEC.
C-17 22-701	8 MFD ELECTROLYTIC	P-17 63-593	220 OHM WIREWOUND	100-36	12TH. I.F. TRANS. SEC.	100-36	12TH. I.F. TRANS. SEC.	100-36	12TH. I.F. TRANS. SEC.

Chassis No. 5529

CHASSIS No. 5529


NOTE

Line voltage 115 v. Consumption 45 watts.

(A) Bias for 6A8—6K7 and diodes measured across R11.

(B) Low side of volume control.

(C) Bias for triode section of 6Q7 and 6K6 measured across R10 and R11.



NC — No Connection

SH — Shield

H—Heater

P — Plate

S—Screen

G—Grid


SU — Suppre

D—Diode

K—Catholic

F — Filament

1. Introduction




Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	455	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
6	" " "	200 Mmfd.		"		FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Rock gang & adj. for max. output

469



SPEAKER **MODEL**

49-237-5 INCH. 6D-311

49-237-5 * 6D-326

49-237-5 * 6D-336

49-241-6 * 6D-360

I.F. FREQUENCY-455 K.C.

6-TUBE SUPERHETERODYNE

CHASSIS NO. 5646-A.C.D.C.

ZENITH RADIO CORPORATION


CHICAGO, ILL.

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
C-1	22-879 TWO GANG VARIABLE COND.	R-3	63-443	10M OHM	2	3-3038	OSCILLATOR COIL ASSEM.
C-2	22-906 .01 MFD.	R-4	63-271	1MEG OHM	3	95-513	1ST I.F. TRANSFORMER
C-3	22-280 .05 MFD.	R-5	63-681	56M OHM	4	95-514	2ND I.F. TRANSFORMER
C-4	22-182 .00025 MFD.	R-6	63-653	880 OHM	5	100-70	SPEAKER TRANSFORMER
C-5	22-182 .0001 MFD.	R-7	63-296	220M OHM	6	100-70	BALLAST TUBE -115V
C-6	22-147 .0005 MFD.	R-8	63-593	100M OHM	7	100-36	PILOT LIGHT 25W-0.3V
C-7	22-327 .02 MFD.	R-9	63-557	60 OHM WIREWOUND	8	A	1ST I.F. TRANS. PRI.
C-8	22-435 .02 MFD.	R-10	63-954	50 OHM WIREWOUND	9	A	2ND I.F. TRANS. PRI.
C-9	22-640 40 MFD. ELECTROLYTIC	R-11	63-953	220M OHM VOL. CONTROL	C	D	2ND I.F. TRANS. SEC.
C-10	22-460 10 MFD. ELECTROLYTIC	1	5-5807	ANTENNA COIL ASSEM.	F	G	BROADCAST OSC. (ON GANG)
C-11	22-120 400V						1ANT. BROADCAST (ON GANG)
C-12	22-120 400V						
R-2	63-593						


Chassis No. 5646

CHASSIS No. 5646

(B) Bias for 26L6 measured between "C" at 6Q7 socket and chassis.



NC—No Connection
SH—Shield
H—Heater
P—Plate
S—Screen
G—Grid
SU—Suppressor
D—Diode
K—Cathode
F—Filament



Location of Tubes and Trimmers


Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.

CONVERTER

1.F.
6K 7G

DET. AMPLIFIER
6Q 7G

POWERAMPLIFIER
25L6G



SPEAKER
49-237-5"
49-237-5"
49-237-5"
49-237-5"

MODEL
6D-312
6D-316
6D-317
6D-337

I F FREQUENCY 455 KC.
6-TUBE SUPERHETERODYNE
CHASSIS N2 5647-AC. DC.
ZENITH RADIO CORPORATION
CHICAGO, ILL.

DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION
C-1	22-425	TWO GANG VAR. COND.	C-1	23-587	470 M OHM	14M	20-47	COMPENSATING COIL
C-2	22-186	101 MFD.	C-2	63-593	47 M OHM	14M	3	
C-3	22-289	50 MFD.	C-3	63-643	18 M OHM	14M	5	1ST I.F. TRANS.
C-4	22-162	500 MFD.	C-4	63-77	1M50 OHM	14M	6	2ND I.F. TRANS.
C-5	22-182	1000 MFD.	C-5	63-681	56M OHM	12M	7	BALLAST TUBE-115V
C-6	22-250	05 MFD.	C-6	63-63	680 OHM	14M	8	PILOT LIGHT 250-63V
C-7	22-347	00035 MFD.	C-7	63-286	220 M OHM	14M	9	SPARKER TRANS.
C-8	22-327	02 MFD.	C-8	63-585	100 M OHM	14M		
C-9	22-435	02 MFD.	C-9	63-557	60 OHM METERING	12M	A	1ST I.F. TRANS. PRI
C-10	22-519	VARIABLE TRIMMER	C-10	63-954	50 OHM METERING	12M	B	1ST I.F. TRANS. SEC.
C-11	22-729	COMPENSATING COND.	C-11	63-955	220 M OHM VOL CONT.		C	2ND I.F. TRANS. PRI
C-12	22-681	40 MFD. ELECT. PLYC.	C-12				D	2ND I.F. TRANS. SEC.
C-13	22-660	18 MFD.	C-13	5-2808	4N TRANS. COIL 600M		E	ARMORCAST OSCILLATOR (ON GANG)
C-14	22-730	04 MFD.	C-14	5-6039	OSC. COIL 600M		G	ARMORCAST BROADCAST (ON GANG)

Chassis No. 5647

Models 6D312, 6D316, 6D317, 6D337

CHASSIS No. 5647

NOTE

Voltages measured from socket contacts to chassis using a 1000 ohm per volt meter. Antenna disconnected — volume control on full.

Line voltage 115 v. Consumption 55 watts.

Power output 1.6 watts.


(A) Bias for 6A8 — 6K7 and 6Q7 measured at 6Q7 cathode.

(B) Bias for 25L6 measured at point C on 6Q7 socket.


Filament voltages measured across heaters of 25L6 and 25Z6 is 22 volts A.C. Other tubes 6 v A.C.

LEGEND

NC — No Connection
SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
K — Cathode
F — Filament




SOCKET VOLTAGES



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.



SPEAKER	MODEL
49-179-8"	6 S 301
49-248-6"	6 S 304
49-266-12"	6 S 305
49-248-6"	6 S 321
49-248-6"	6 S 322
49-248-6"	6 S 340
49-255-12"	6 S 306

I.F. FREQUENCY 455KC.
6 TUBE SUPERHETERODYNE
CHASSIS NO. 5651-A.C. 3-BAND
ZENITH RADIO CORPORATION
CHICAGO, ILL.

Part No.	Part No.	Description	Part No.	Part No.	Description	Part No.	Part No.	Description
C-1 22-717	20-144	WAVE TRAP	1	20-144	WAVE TRAP	1	20-144	WAVE TRAP
C-2 22-229	5-4254	ANT. COIL & SHIELD ASSEMB.	2	5-4254	ANT. COIL & SHIELD ASSEMB.	2	5-4254	ANT. COIL & SHIELD ASSEMB.
C-3 22-162	5-4254	CONVERTING COIL	3	5-4254	CONVERTING COIL	3	5-4254	CONVERTING COIL
C-4 22-167	5-4254	CONVERTING COIL	4	5-4254	CONVERTING COIL	4	5-4254	CONVERTING COIL
C-5 22-170	5-4254	CONVERTING COIL	5	5-4254	CONVERTING COIL	5	5-4254	CONVERTING COIL
C-6 22-170	5-4254	CONVERTING COIL	6	5-4254	CONVERTING COIL	6	5-4254	CONVERTING COIL
C-7 22-170	5-4254	CONVERTING COIL	7	5-4254	CONVERTING COIL	7	5-4254	CONVERTING COIL
C-8 22-170	5-4254	CONVERTING COIL	8	5-4254	CONVERTING COIL	8	5-4254	CONVERTING COIL
C-9 22-170	5-4254	CONVERTING COIL	9	5-4254	CONVERTING COIL	9	5-4254	CONVERTING COIL
C-10 22-170	5-4254	CONVERTING COIL	10	5-4254	CONVERTING COIL	10	5-4254	CONVERTING COIL
C-11 22-170	5-4254	CONVERTING COIL	11	5-4254	CONVERTING COIL	11	5-4254	CONVERTING COIL
C-12 22-170	5-4254	CONVERTING COIL	12	5-4254	CONVERTING COIL	12	5-4254	CONVERTING COIL
C-13 22-170	5-4254	CONVERTING COIL	13	5-4254	CONVERTING COIL	13	5-4254	CONVERTING COIL
C-14 22-170	5-4254	CONVERTING COIL	14	5-4254	CONVERTING COIL	14	5-4254	CONVERTING COIL
C-15 22-170	5-4254	CONVERTING COIL	15	5-4254	CONVERTING COIL	15	5-4254	CONVERTING COIL
C-16 22-170	5-4254	CONVERTING COIL	16	5-4254	CONVERTING COIL	16	5-4254	CONVERTING COIL
C-17 22-170	5-4254	CONVERTING COIL	17	5-4254	CONVERTING COIL	17	5-4254	CONVERTING COIL
C-18 22-170	5-4254	CONVERTING COIL	18	5-4254	CONVERTING COIL	18	5-4254	CONVERTING COIL
C-19 22-170	5-4254	CONVERTING COIL	19	5-4254	CONVERTING COIL	19	5-4254	CONVERTING COIL
C-20 22-170	5-4254	CONVERTING COIL	20	5-4254	CONVERTING COIL	20	5-4254	CONVERTING COIL

Chassis No. 5651

Models 6S301, 6S304, 6S305, 6S306, 6S321, 6S322, 6S340
CHASSIS No. 5651

SOCKET
VOLTAGES

NOTE

Voltages measured for socket contacts to chassis using a 1000 ohm per volt meter. Antenna disconnected — volume control on full.


Line voltage 115 v. Consumption 60 watts.

Power Output 4.5 watts.

(A) Bias for 6A8 — 6K7 and 6J5 measured across X which is neg. 2.3 volts.


(B) Bias for 6F5 measured across X and Y which is neg. 3.8 volts.

(C) Bias for 6F6 measured across XY and Z which is neg. 16 volts.



LEGEND

NC — No Connection
SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
K — Cathode
F — Filament




Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	455	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output.
6	" " "	200 Mmfd.		"		FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	18000	S.W.	18000	L	Rock Gang & adj. for max. output.
9	" " "	400 Ohms	6000	Police	6000	N	Rock Gang & adj. for max. output.

NOTE: If receiver is used in location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.



SPEAKER MODEL
49-180-6* 6 S-330
49-181-10* 6 S-361

IF FREQUENCY 456 Kc
6-TUBE SUPERHETERODYNE
CHASSIS No. 5648-AC
ZENITH RADIO CORPORATION
CHICAGO, ILL.

PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
C-1	22-547 100V	1	10-154	10-154	10-154	10-154	10-154
C-2	22-548 100V	2	5-4941	5-4941	5-4941	5-4941	5-4941
C-3	22-549 100V	3	U-4942	U-4942	U-4942	U-4942	U-4942
C-4	22-550 100V	4	95-413	95-413	95-413	95-413	95-413
C-5	22-551 100V	5	95-414	95-414	95-414	95-414	95-414
C-6	22-552 100V	6	95-415	95-415	95-415	95-415	95-415
C-7	22-553 100V	7	95-416	95-416	95-416	95-416	95-416
C-8	22-554 100V	8	95-417	95-417	95-417	95-417	95-417
C-9	22-555 100V	9	95-418	95-418	95-418	95-418	95-418
C-10	22-556 100V	10	95-419	95-419	95-419	95-419	95-419
C-11	22-557 100V	11	95-420	95-420	95-420	95-420	95-420
C-12	22-558 100V	12	95-421	95-421	95-421	95-421	95-421
C-13	22-559 100V	13	95-422	95-422	95-422	95-422	95-422
C-14	22-560 100V	14	95-423	95-423	95-423	95-423	95-423
C-15	22-561 100V	15	95-424	95-424	95-424	95-424	95-424
C-16	22-562 100V	16	95-425	95-425	95-425	95-425	95-425
C-17	22-563 100V	17	95-426	95-426	95-426	95-426	95-426
C-18	22-564 100V	18	95-427	95-427	95-427	95-427	95-427
C-19	22-565 100V	19	95-428	95-428	95-428	95-428	95-428
C-20	22-566 100V	20	95-429	95-429	95-429	95-429	95-429

Chassis No. 5648

Models 6S330, 6S361

CHASSIS No. 5648

SOCKET
VOLTAGES

NOTE

Voltages measured for socket contacts to chassis using a 1000 ohm per volt meter. Antenna disconnected — volume control on full.

Line voltage 115 v. Consumption 65 watts.

Power Output 4.5 watts.

(A) Bias for 6A8 — 6K7 and 6H6 tubes measured across X which is neg. 2.6 volts.


(B) Bias for 6F5 tube measured across X and Y which is neg. 4 volts.

(C) Bias for 6F6 tube measured across X-Y and Z which is neg. 16 volts.

6K7G
1F.A.M.P.

6H6G
2ND DET. AVC.


6F5G
1ST. AUDIO



LEGEND

NC — No Connection
SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
K — Cathode
F — Filament

FRONT OF CHASSIS




Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Def. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	456	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
6	" " "	200 Mmfd.		"		FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	16500	S.W.	16500	L	Rock Gang & adj. for max. output
9	" " "	400 Ohms	5500	Police	5500	N	Rock Gang & adj. for max. output

NOTE: If receiver is used in location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.



SPEAKER MODEL
49-206-8" 6 S-341
49-208-10" 6 S-362

IF FREQUENCY 456 KC.
6-TUBE SUPERHETERODYNE
CHASSIS NO. 5649-A.C. 3-BAND
ZENITH RADIO CORPORATION
CHICAGO, ILL.

CHAS. NO.	PART NO.	DESCRIPTION	CHAS. NO.	PART NO.	DESCRIPTION	CHAS. NO.	PART NO.	DESCRIPTION	CHAS. NO.	PART NO.	DESCRIPTION
C-1	22-547	TWO GANG VARIABLE	C-20	22-552	0.02 MFD	400V	1	80-154	WHITE TRAMP ASSEMBLY	A	1/16 I/F TRAMP ASP
C-2	22-548	500K MFD	400V	2	80-155	0.001	2	1-5070	ANTENNA COIL & SHIELD FORMER	B	2 MHO I/F TRAMP JAC
C-3	22-549	500K MFD	400V	3	80-156	0.001	3	85-416	COIL C.F. & SHIELD ASSEMBLY	C	2 MHO I/F TRAMP JAC
C-4	22-550	500K MFD	400V	4	80-157	0.001	4	85-417	1/16 I/F TRAMP ASSEMBLY	D	WHITE TRAMP
C-5	22-551	CONVENTIONAL COND	R-1	63-593	47 M OHM	1/4 W	5	85-418	2 MHO I/F TRAMP ASSEMBLY	E	BRASS CONTACT COIL (SEE NOTE)
C-6	22-552	CONVENTIONAL COND	R-2	63-587	430 OHM	1/4 W	6	85-419	2 MHO I/F TRAMP ASSEMBLY	F	WHITE TRAMP COIL (SEE NOTE)
C-7	22-553	CONVENTIONAL COND	R-3	63-588	33 M OHM	1/4 W	7	85-420	2 MHO I/F TRAMP ASSEMBLY	G	WHITE TRAMP COIL (SEE NOTE)
C-8	22-554	CONVENTIONAL COND	R-4	63-589	33 M OHM	1/4 W	8	85-421	2 MHO I/F TRAMP ASSEMBLY	H	WHITE TRAMP COIL (SEE NOTE)
C-9	22-555	CONVENTIONAL COND	R-5	63-590	33 M OHM	1/4 W	9	85-422	2 MHO I/F TRAMP ASSEMBLY	I	WHITE TRAMP COIL (SEE NOTE)
C-10	22-556	CONVENTIONAL COND	R-6	63-591	33 M OHM	1/4 W	10	85-423	2 MHO I/F TRAMP ASSEMBLY	J	WHITE TRAMP COIL (SEE NOTE)
C-11	22-557	CONVENTIONAL COND	R-7	63-592	33 M OHM	1/4 W	11	85-424	2 MHO I/F TRAMP ASSEMBLY	K	WHITE TRAMP COIL (SEE NOTE)
C-12	22-558	CONVENTIONAL COND	R-8	63-593	33 M OHM	1/4 W	12	85-425	2 MHO I/F TRAMP ASSEMBLY	L	WHITE TRAMP COIL (SEE NOTE)
C-13	22-559	CONVENTIONAL COND	R-9	63-594	33 M OHM	1/4 W	13	85-426	2 MHO I/F TRAMP ASSEMBLY	M	WHITE TRAMP COIL (SEE NOTE)
C-14	22-560	CONVENTIONAL COND	R-10	63-595	33 M OHM	1/4 W	14	85-427	2 MHO I/F TRAMP ASSEMBLY	N	WHITE TRAMP COIL (SEE NOTE)
C-15	22-561	CONVENTIONAL COND	R-11	63-596	33 M OHM	1/4 W	15	85-428	2 MHO I/F TRAMP ASSEMBLY		
C-16	22-562	CONVENTIONAL COND	R-12	63-597	33 M OHM	1/4 W	16	85-429	2 MHO I/F TRAMP ASSEMBLY		
C-17	22-563	CONVENTIONAL COND	R-13	63-598	33 M OHM	1/4 W	17	85-430	2 MHO I/F TRAMP ASSEMBLY		
C-18	22-564	CONVENTIONAL COND	R-14	63-599	33 M OHM	1/4 W	18	85-431	2 MHO I/F TRAMP ASSEMBLY		
C-19	22-565	CONVENTIONAL COND	R-15	63-600	33 M OHM	1/4 W	19	85-432	2 MHO I/F TRAMP ASSEMBLY		
C-20	22-566	CONVENTIONAL COND	R-16	63-601	33 M OHM	1/4 W	20	85-433	2 MHO I/F TRAMP ASSEMBLY		
C-21	22-567	CONVENTIONAL COND	R-17	63-602	33 M OHM	1/4 W	21	85-434	2 MHO I/F TRAMP ASSEMBLY		
C-22	22-568	CONVENTIONAL COND	R-18	63-603	33 M OHM	1/4 W	22	85-435	2 MHO I/F TRAMP ASSEMBLY		
C-23	22-569	CONVENTIONAL COND	R-19	63-604	33 M OHM	1/4 W	23	85-436	2 MHO I/F TRAMP ASSEMBLY		
C-24	22-570	CONVENTIONAL COND	R-20	63-605	33 M OHM	1/4 W	24	85-437	2 MHO I/F TRAMP ASSEMBLY		
C-25	22-571	CONVENTIONAL COND	R-21	63-606	33 M OHM	1/4 W	25	85-438	2 MHO I/F TRAMP ASSEMBLY		
C-26	22-572	CONVENTIONAL COND	R-22	63-607	33 M OHM	1/4 W	26	85-439	2 MHO I/F TRAMP ASSEMBLY		
C-27	22-573	CONVENTIONAL COND	R-23	63-608	33 M OHM	1/4 W	27	85-440	2 MHO I/F TRAMP ASSEMBLY		
C-28	22-574	CONVENTIONAL COND	R-24	63-609	33 M OHM	1/4 W	28	85-441	2 MHO I/F TRAMP ASSEMBLY		
C-29	22-575	CONVENTIONAL COND	R-25	63-610	33 M OHM	1/4 W	29	85-442	2 MHO I/F TRAMP ASSEMBLY		
C-30	22-576	CONVENTIONAL COND	R-26	63-611	33 M OHM	1/4 W	30	85-443	2 MHO I/F TRAMP ASSEMBLY		
C-31	22-577	CONVENTIONAL COND	R-27	63-612	33 M OHM	1/4 W	31	85-444	2 MHO I/F TRAMP ASSEMBLY		
C-32	22-578	CONVENTIONAL COND	R-28	63-613	33 M OHM	1/4 W	32	85-445	2 MHO I/F TRAMP ASSEMBLY		
C-33	22-579	CONVENTIONAL COND	R-29	63-614	33 M OHM	1/4 W	33	85-446	2 MHO I/F TRAMP ASSEMBLY		
C-34	22-580	CONVENTIONAL COND	R-30	63-615	33 M OHM	1/4 W	34	85-447	2 MHO I/F TRAMP ASSEMBLY		
C-35	22-581	CONVENTIONAL COND	R-31	63-616	33 M OHM	1/4 W	35	85-448	2 MHO I/F TRAMP ASSEMBLY		
C-36	22-582	CONVENTIONAL COND	R-32	63-617	33 M OHM	1/4 W	36	85-449	2 MHO I/F TRAMP ASSEMBLY		
C-37	22-583	CONVENTIONAL COND	R-33	63-618	33 M OHM	1/4 W	37	85-450	2 MHO I/F TRAMP ASSEMBLY		
C-38	22-584	CONVENTIONAL COND	R-34	63-619	33 M OHM	1/4 W	38	85-451	2 MHO I/F TRAMP ASSEMBLY		
C-39	22-585	CONVENTIONAL COND	R-35	63-620	33 M OHM	1/4 W	39	85-452	2 MHO I/F TRAMP ASSEMBLY		
C-40	22-586	CONVENTIONAL COND	R-36	63-621	33 M OHM	1/4 W	40	85-453	2 MHO I/F TRAMP ASSEMBLY		
C-41	22-587	CONVENTIONAL COND	R-37	63-622	33 M OHM	1/4 W	41	85-454	2 MHO I/F TRAMP ASSEMBLY		
C-42	22-588	CONVENTIONAL COND	R-38	63-623	33 M OHM	1/4 W	42	85-455	2 MHO I/F TRAMP ASSEMBLY		
C-43	22-589	CONVENTIONAL COND	R-39	63-624	33 M OHM	1/4 W	43	85-456	2 MHO I/F TRAMP ASSEMBLY		
C-44	22-590	CONVENTIONAL COND	R-40	63-625	33 M OHM	1/4 W	44	85-457	2 MHO I/F TRAMP ASSEMBLY		
C-45	22-591	CONVENTIONAL COND	R-41	63-626	33 M OHM	1/4 W	45	85-458	2 MHO I/F TRAMP ASSEMBLY		
C-46	22-592	CONVENTIONAL COND	R-42	63-627	33 M OHM	1/4 W	46	85-459	2 MHO I/F TRAMP ASSEMBLY		
C-47	22-593	CONVENTIONAL COND	R-43	63-628	33 M OHM	1/4 W	47	85-460	2 MHO I/F TRAMP ASSEMBLY		
C-48	22-594	CONVENTIONAL COND	R-44	63-629	33 M OHM	1/4 W	48	85-461	2 MHO I/F TRAMP ASSEMBLY		
C-49	22-595	CONVENTIONAL COND	R-45	63-630	33 M OHM	1/4 W	49	85-462	2 MHO I/F TRAMP ASSEMBLY		
C-50	22-596	CONVENTIONAL COND	R-46	63-631	33 M OHM	1/4 W	50	85-463	2 MHO I/F TRAMP ASSEMBLY		
C-51	22-597	CONVENTIONAL COND	R-47	63-632	33 M OHM	1/4 W	51	85-464	2 MHO I/F TRAMP ASSEMBLY		
C-52	22-598	CONVENTIONAL COND	R-48	63-633	33 M OHM	1/4 W	52	85-465	2 MHO I/F TRAMP ASSEMBLY		
C-53	22-599	CONVENTIONAL COND	R-49	63-634	33 M OHM	1/4 W	53	85-466	2 MHO I/F TRAMP ASSEMBLY		
C-54	22-600	CONVENTIONAL COND	R-50	63-635	33 M OHM	1/4 W	54	85-467	2 MHO I/F TRAMP ASSEMBLY		
C-55	22-601	CONVENTIONAL COND	R-51	63-636	33 M OHM	1/4 W	55	85-468	2 MHO I/F TRAMP ASSEMBLY		
C-56	22-602	CONVENTIONAL COND	R-52	63-637	33 M OHM	1/4 W	56	85-469	2 MHO I/F TRAMP ASSEMBLY		
C-57	22-603	CONVENTIONAL COND	R-53	63-638	33 M OHM	1/4 W	57	85-470	2 MHO I/F TRAMP ASSEMBLY		
C-58	22-604	CONVENTIONAL COND	R-54	63-639	33 M OHM	1/4 W	58	85-471	2 MHO I/F TRAMP ASSEMBLY		
C-59	22-605	CONVENTIONAL COND	R-55	63-640	33 M OHM	1/4 W	59	85-472	2 MHO I/F TRAMP ASSEMBLY		
C-60	22-606	CONVENTIONAL COND	R-56	63-641	33 M OHM	1/4 W	60	85-473	2 MHO I/F TRAMP ASSEMBLY		
C-61	22-607	CONVENTIONAL COND	R-57	63-642	33 M OHM	1/4 W	61	85-474	2 MHO I/F TRAMP ASSEMBLY		
C-62	22-608	CONVENTIONAL COND	R-58	63-643	33 M OHM	1/4 W	62	85-475	2 MHO I/F TRAMP ASSEMBLY		
C-63	22-609	CONVENTIONAL COND	R-59	63-644	33 M OHM	1/4 W	63	85-476	2 MHO I/F TRAMP ASSEMBLY		
C-64	22-610	CONVENTIONAL COND	R-60	63-645	33 M OHM	1/4 W	64	85-477	2 MHO I/F TRAMP ASSEMBLY		
C-65	22-611	CONVENTIONAL COND	R-61	63-646	33 M OHM	1/4 W	65	85-478	2 MHO I/F TRAMP ASSEMBLY		
C-66	22-612	CONVENTIONAL COND	R-62	63-647	33 M OHM	1/4 W	66	85-479	2 MHO I/F TRAMP ASSEMBLY		
C-67	22-613	CONVENTIONAL COND	R-63	63-648	33 M OHM	1/4 W	67	85-480	2 MHO I/F TRAMP ASSEMBLY		
C-68	22-614	CONVENTIONAL COND	R-64	63-649	33 M OHM	1/4 W	68	85-481	2 MHO I/F TRAMP ASSEMBLY		
C-69	22-615	CONVENTIONAL COND	R-65	63-650	33 M OHM	1/4 W	69	85-482	2 MHO I/F TRAMP ASSEMBLY		
C-70	22-616	CONVENTIONAL COND	R-66	63-651	33 M OHM	1/4 W	70	85-483	2 MHO I/F TRAMP ASSEMBLY		
C-71	22-617	CONVENTIONAL COND	R-67	63-652	33 M OHM	1/4 W	71	85-484	2 MHO I/F TRAMP ASSEMBLY		
C-72	22-618	CONVENTIONAL COND	R-68	63-653	33 M OHM	1/4 W	72	85-485	2 MHO I/F TRAMP ASSEMBLY		
C-73	22-619	CONVENTIONAL COND	R-69	63-654	33 M OHM	1/4 W	73	85-486	2 MHO I/F TRAMP ASSEMBLY		
C-74	22-620	CONVENTIONAL COND	R-70	63-655	33 M OHM	1/4 W	74	85-487	2 MHO I/F TRAMP ASSEMBLY		
C-75	22-621	CONVENTIONAL COND	R-71	63-656	33 M OHM	1/4 W	75	85-488	2 MHO I/F TRAMP ASSEMBLY		
C-76	22-622	CONVENTIONAL COND	R-72	63-657	33 M OHM	1/4 W	76	85-489	2 MHO I/F TRAMP ASSEMBLY		
C-77	22-623	CONVENTIONAL COND	R-73	63-658	33 M OHM	1/4 W	77	85-490	2 MHO I/F TRAMP ASSEMBLY		
C-78	22-624	CONVENTIONAL COND	R-74	63-659	33 M OHM	1/4 W	78	85-491	2 MHO I/F TRAMP ASSEMBLY		
C-79	22-625	CONVENTIONAL COND	R-75	63-660	33 M OHM	1/4 W	79	85-492	2 MHO I/F TRAMP ASSEMBLY		
C-80	22-626	CONVENTIONAL COND	R-76	63-661	33 M OHM	1/4 W	80	85-493	2 MHO I/F TRAMP ASSEMBLY		
C-81	22-627	CONVENTIONAL COND	R-77	63-662	33 M OHM	1/4 W	81	85-494	2 MHO I/F TRAMP ASSEMBLY		
C-82	22-628	CONVENTIONAL COND	R-78	63-663	33 M OHM	1/4 W	82	85-495	2 MHO I/F TRAMP ASSEMBLY		
C-83	22-629	CONVENTIONAL COND	R-79	63-664	33 M OHM	1/4 W	83	85-496	2 MHO I/F TRAMP ASSEMBLY		
C-84	22-630	CONVENTIONAL COND	R-80	63-665	33 M OHM	1/4 W	84	85-497	2 MHO I/F TRAMP ASSEMBLY		
C-85	22-631	CONVENTIONAL COND	R-81	63-666	33 M OHM	1/4 W	85	85-498	2 MHO I/F TRAMP ASSEMBLY		
C-86	22-632	CONVENTIONAL COND	R-82	63-667	33 M OHM	1/4 W	86	85-499	2 MHO I/F TRAMP ASSEMBLY		
C-87	22-633	CONVENTIONAL COND	R-83	63-668	33 M OHM	1/4 W	87	85-500	2 MHO I/F TRAMP ASSEMBLY		
C-88	22-634	CONVENTIONAL COND	R-84	63-669	33 M OHM	1/4 W	88	85-501	2 MHO I/F TRAMP ASSEMBLY		
C-89	22-635	CONVENTIONAL COND	R-85	63-670	33 M OHM	1/4 W	89	85-502	2 MHO I/F TRAMP ASSEMBLY		
C-90	22-636	CONVENTIONAL COND	R-86	63-671	33 M OHM	1/4 W	90	85-503	2 MHO I/F TRAMP ASSEMBLY		
C-91	22-637	CONVENTIONAL COND	R-87	63-672	33 M OHM	1/4 W	91	85-504	2 MHO I/F TRAMP ASSEMBLY		
C-92	22-638	CONVENTIONAL COND	R-88	63-673	33 M OHM	1/4 W	92	85-505	2 MHO I/F TRAMP ASSEMBLY		
C-93	22-639	CONVENTIONAL COND	R-89	63-674	33 M OHM	1/4 W	93	85-506	2 MHO I/F TRAMP ASSEMBLY		
C-94	22-640	CONVENTIONAL COND	R-90	63-675	33 M OHM	1/4 W	94	85-507	2 MHO I/F TRAMP ASSEMBLY		
C-95	22-641	CONVENTIONAL COND	R-91	63-676	33 M OHM	1/4 W	95	85-508	2 MHO I/F TRAMP ASSEMBLY		
C-96	22-642	CONVENTIONAL COND	R-92	63-677	33 M OHM	1/4 W	96	85-509	2 MHO I/F TRAMP ASSEMBLY		
C-97	22-643	CONVENTIONAL COND	R-93	63-678	33 M OHM	1/4 W	97	85-510	2 MHO I/F TRAMP ASSEMBLY		
C-98	22-644	CONVENTIONAL COND	R-94	63-679	33 M OHM	1/4 W	98	85-511	2 MHO I/F TRAMP ASSEMBLY		
C-99	22-645	CONVENTIONAL COND	R-95	63-680	33 M OHM	1/4 W	99	85-512	2 MHO I/F TRAMP ASSEMBLY		
C-100	22-646	CONVENTIONAL COND	R-96	63-681	33 M OHM	1/4 W	100	85-513	2 MHO I/F TRAMP ASSEMBLY		
C-101	22-647	CONVENTIONAL COND	R-97	63-682	33 M OHM	1/4 W	101	85-514	2 MHO I/F TRAMP ASSEMBLY		
C-102	22-648	CONVENTIONAL COND	R-98	63-683	33 M OHM	1/4 W	102	85-515	2 MHO I/F TRAMP ASSEMBLY		
C-103	22-649	CONVENTIONAL COND	R-99	63-684	33 M OHM	1/4 W	103	85-516	2 MHO I/F TRAMP ASSEMBLY		
C-104	22-650	CONVENTIONAL COND	R-100	63-685	33 M OHM	1/4 W	104	85-517	2 MHO I/F TRAMP ASSEMBLY		
C-105	22-651	CONVENTIONAL COND	R-101	63-686	33 M OHM	1/4 W	105	85-518	2 MHO I/F TRAMP ASSEMBLY		
C-106	22-652	CONVENTIONAL COND	R-102	63-687	33 M OHM	1/4 W	106	85-519	2 MHO I/F TRAMP ASSEMBLY		
C-107	22-653	CONVENTIONAL COND	R-103	63-688	33 M OHM	1/4 W	107	85-520	2 MHO I/F TRAMP ASSEMBLY		
C-108	22-654	CONVENTIONAL COND									

Models 6S341, 6S362

CHASSIS No. 5649

SOCKET
VOLTAGES

NOTE

Voltages measured from socket contacts to chassis using a 1000 ohm per volt meter with tenna disconnected — volume control on full.

Line voltage 115 v. Consumption 65 watts.

Power output 4.5 watts.

(A) Bias for 6A8 — 6K7 and 6H6 measured across X which is — 2.5 volts.

(B) Bias for 6F5 measured across X and Y which is neg. 4 volts.

(C) Bias for 6F6 measured across XY and Z which is neg. 16 volts.

LEGEND

NC — No Connection

SH — Shield

H — Heater

P — Plate

S — Screen



G — Grid

SU — Suppressor

D — Diode

K — Cathode

F — Filament



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	456	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
6	" " "	200 Mmfd.		"		FG	Repeat 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	16500	S.W.	16500	L	Rock Gang & adj. for max. output
9	" " "	400 Ohms	5500	Police	5500	N	Rock Gang & adj. for max. output

NOTE: If receiver is used in location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.

Model No. 6B321

CHASSIS No. 5653

NOTE

Voltages measured from socket contacts to chassis using a 1000 ohm per volt meter. Antenna disconnected — volume control on full.

Battery voltage at chassis 6v.


Consumption — switch on normal—2.3 amperes.

Consumption — switch on conserv. 1.7 amperes.

Power output 1 watt.


(A) Bias voltage measured from cathode to chassis.

(B) Bias for 6G6 measured between point C and chassis and is —6 volts.



SOCKET VOLTAGES


- LEGEND**
- NC—No Connection
 - SH—Shield
 - H—Heater
 - P—Plate
 - S—Screen
 - G—Grid
 - SU—Suppressor
 - D—Diode
 - K—Cathode
 - F—Filament



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "	200 Mmfd.		"		FG	Repeat 2 & 3
6	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to scale
7	" " "	400 Ohms	18000	S.W.	18000	L	Rock gang & adj. for max. output
8	" " "	400 Ohms	6000	Police	6000	N	Rock gang & adj. for max. output



QWG NO.	PART NO.	DESCRIPTION	QWG NO.	PART NO.	DESCRIPTION	QWG NO.	PART NO.	DESCRIPTION	QWG NO.	PART NO.	DESCRIPTION	QWG NO.	PART NO.	DESCRIPTION	QWG NO.	PART NO.	DESCRIPTION
C-1	22-744	100 MFD	C-19	63-333	10 MFD ELECT	1	5-6835	ANT. COIL & SHIELD ASSEM	1A	5-270	CHOKES ASSEM.	1	5-270	CHOKES ASSEM.	1A	5-270	CHOKES ASSEM.
C-2	22-196	50 MFD	C-20	63-333	10 MFD ELECT	2	5-6835	OSCILLATOR COIL ASSEM	1B	5-270	PILOT LIGHT 25V 17A	2	5-270	PILOT LIGHT 25V 17A	1B	5-270	PILOT LIGHT 25V 17A
C-3	22-209	50 MFD	C-21	63-333	10 MFD ELECT	3	5-6835	COMPENSATING COIL	1C	5-270	SPEAKER TRANS.	3	5-270	SPEAKER TRANS.	1C	5-270	SPEAKER TRANS.
C-4	22-162	1000 MFD	C-22	63-333	10 MFD ELECT	4	5-6835	ANT. COIL & SHIELD ASSEM	1D	5-270	CHOKES ASSEM.	4	5-270	CHOKES ASSEM.	1D	5-270	CHOKES ASSEM.
C-5	22-215	1000 MFD	C-23	63-333	10 MFD ELECT	5	5-6835	OSCILLATOR COIL ASSEM	1E	5-270	PILOT LIGHT 25V 17A	5	5-270	PILOT LIGHT 25V 17A	1E	5-270	PILOT LIGHT 25V 17A
C-6	22-740	100 MFD	C-24	63-333	10 MFD ELECT	6	5-6835	COMPENSATING COIL	1F	5-270	SPEAKER TRANS.	6	5-270	SPEAKER TRANS.	1F	5-270	SPEAKER TRANS.
C-7	22-245	100 MFD	C-25	63-333	10 MFD ELECT	7	5-6835	ANT. COIL & SHIELD ASSEM	1G	5-270	CHOKES ASSEM.	7	5-270	CHOKES ASSEM.	1G	5-270	CHOKES ASSEM.
C-8	22-245	100 MFD	C-26	63-333	10 MFD ELECT	8	5-6835	OSCILLATOR COIL ASSEM	1H	5-270	PILOT LIGHT 25V 17A	8	5-270	PILOT LIGHT 25V 17A	1H	5-270	PILOT LIGHT 25V 17A
C-9	22-245	100 MFD	C-27	63-333	10 MFD ELECT	9	5-6835	COMPENSATING COIL	1I	5-270	SPEAKER TRANS.	9	5-270	SPEAKER TRANS.	1I	5-270	SPEAKER TRANS.
C-10	22-245	100 MFD	C-28	63-333	10 MFD ELECT	10	5-6835	ANT. COIL & SHIELD ASSEM	1J	5-270	CHOKES ASSEM.	10	5-270	CHOKES ASSEM.	1J	5-270	CHOKES ASSEM.
C-11	22-245	100 MFD	C-29	63-333	10 MFD ELECT	11	5-6835	OSCILLATOR COIL ASSEM	1K	5-270	PILOT LIGHT 25V 17A	11	5-270	PILOT LIGHT 25V 17A	1K	5-270	PILOT LIGHT 25V 17A
C-12	22-245	100 MFD	C-30	63-333	10 MFD ELECT	12	5-6835	COMPENSATING COIL	1L	5-270	SPEAKER TRANS.	12	5-270	SPEAKER TRANS.	1L	5-270	SPEAKER TRANS.
C-13	22-245	100 MFD	C-31	63-333	10 MFD ELECT	13	5-6835	ANT. COIL & SHIELD ASSEM	1M	5-270	CHOKES ASSEM.	13	5-270	CHOKES ASSEM.	1M	5-270	CHOKES ASSEM.
C-14	22-245	100 MFD	C-32	63-333	10 MFD ELECT	14	5-6835	OSCILLATOR COIL ASSEM	1N	5-270	PILOT LIGHT 25V 17A	14	5-270	PILOT LIGHT 25V 17A	1N	5-270	PILOT LIGHT 25V 17A
C-15	22-245	100 MFD	C-33	63-333	10 MFD ELECT	15	5-6835	COMPENSATING COIL	1O	5-270	SPEAKER TRANS.	15	5-270	SPEAKER TRANS.	1O	5-270	SPEAKER TRANS.
C-16	22-245	100 MFD	C-34	63-333	10 MFD ELECT	16	5-6835	ANT. COIL & SHIELD ASSEM	1P	5-270	CHOKES ASSEM.	16	5-270	CHOKES ASSEM.	1P	5-270	CHOKES ASSEM.
C-17	22-245	100 MFD	C-35	63-333	10 MFD ELECT	17	5-6835	OSCILLATOR COIL ASSEM	1Q	5-270	PILOT LIGHT 25V 17A	17	5-270	PILOT LIGHT 25V 17A	1Q	5-270	PILOT LIGHT 25V 17A
C-18	22-245	100 MFD	C-36	63-333	10 MFD ELECT	18	5-6835	COMPENSATING COIL	1R	5-270	SPEAKER TRANS.	18	5-270	SPEAKER TRANS.	1R	5-270	SPEAKER TRANS.
C-19	22-245	100 MFD	C-37	63-333	10 MFD ELECT	19	5-6835	ANT. COIL & SHIELD ASSEM	1S	5-270	CHOKES ASSEM.	19	5-270	CHOKES ASSEM.	1S	5-270	CHOKES ASSEM.
C-20	22-245	100 MFD	C-38	63-333	10 MFD ELECT	20	5-6835	OSCILLATOR COIL ASSEM	1T	5-270	PILOT LIGHT 25V 17A	20	5-270	PILOT LIGHT 25V 17A	1T	5-270	PILOT LIGHT 25V 17A
C-21	22-245	100 MFD	C-39	63-333	10 MFD ELECT	21	5-6835	COMPENSATING COIL	1U	5-270	SPEAKER TRANS.	21	5-270	SPEAKER TRANS.	1U	5-270	SPEAKER TRANS.
C-22	22-245	100 MFD	C-40	63-333	10 MFD ELECT	22	5-6835	ANT. COIL & SHIELD ASSEM	1V	5-270	CHOKES ASSEM.	22	5-270	CHOKES ASSEM.	1V	5-270	CHOKES ASSEM.
C-23	22-245	1000 MFD	C-41	63-333	10 MFD ELECT	23	5-6835	OSCILLATOR COIL ASSEM	1W	5-270	PILOT LIGHT 25V 17A	23	5-270	PILOT LIGHT 25V 17A	1W	5-270	PILOT LIGHT 25V 17A
C-24	22-245	100 MFD	C-42	63-333	10 MFD ELECT	24	5-6835	COMPENSATING COIL	1X	5-270	SPEAKER TRANS.	24	5-270	SPEAKER TRANS.	1X	5-270	SPEAKER TRANS.
C-25	22-245	100 MFD	C-43	63-333	10 MFD ELECT	25	5-6835	ANT. COIL & SHIELD ASSEM	1Y	5-270	CHOKES ASSEM.	25	5-270	CHOKES ASSEM.	1Y	5-270	CHOKES ASSEM.
C-26	22-245	100 MFD	C-44	63-333	10 MFD ELECT	26	5-6835	OSCILLATOR COIL ASSEM	1Z	5-270	PILOT LIGHT 25V 17A	26	5-270	PILOT LIGHT 25V 17A	1Z	5-270	PILOT LIGHT 25V 17A
C-27	22-245	100 MFD	C-45	63-333	10 MFD ELECT	27	5-6835	COMPENSATING COIL	1A	5-270	SPEAKER TRANS.	27	5-270	SPEAKER TRANS.	1A	5-270	SPEAKER TRANS.
C-28	22-245	100 MFD	C-46	63-333	10 MFD ELECT	28	5-6835	ANT. COIL & SHIELD ASSEM	1B	5-270	CHOKES ASSEM.	28	5-270	CHOKES ASSEM.	1B	5-270	CHOKES ASSEM.
C-29	22-245	100 MFD	C-47	63-333	10 MFD ELECT	29	5-6835	OSCILLATOR COIL ASSEM	1C	5-270	PILOT LIGHT 25V 17A	29	5-270	PILOT LIGHT 25V 17A	1C	5-270	PILOT LIGHT 25V 17A
C-30	22-245	100 MFD	C-48	63-333	10 MFD ELECT	30	5-6835	COMPENSATING COIL	1D	5-270	SPEAKER TRANS.	30	5-270	SPEAKER TRANS.	1D	5-270	SPEAKER TRANS.
C-31	22-245	100 MFD	C-49	63-333	10 MFD ELECT	31	5-6835	ANT. COIL & SHIELD ASSEM	1E	5-270	CHOKES ASSEM.	31	5-270	CHOKES ASSEM.	1E	5-270	CHOKES ASSEM.
C-32	22-245	100 MFD	C-50	63-333	10 MFD ELECT	32	5-6835	OSCILLATOR COIL ASSEM	1F	5-270	PILOT LIGHT 25V 17A	32	5-270	PILOT LIGHT 25V 17A	1F	5-270	PILOT LIGHT 25V 17A
C-33	22-245	100 MFD	C-51	63-333	10 MFD ELECT	33	5-6835	COMPENSATING COIL	1G	5-270	SPEAKER TRANS.	33	5-270	SPEAKER TRANS.	1G	5-270	SPEAKER TRANS.
C-34	22-245	100 MFD	C-52	63-333	10 MFD ELECT	34	5-6835	ANT. COIL & SHIELD ASSEM	1H	5-270	CHOKES ASSEM.	34	5-270	CHOKES ASSEM.	1H	5-270	CHOKES ASSEM.
C-35	22-245	100 MFD	C-53	63-333	10 MFD ELECT	35	5-6835	OSCILLATOR COIL ASSEM	1I	5-270	PILOT LIGHT 25V 17A	35	5-270	PILOT LIGHT 25V 17A	1I	5-270	PILOT LIGHT 25V 17A
C-36	22-245	100 MFD	C-54	63-333	10 MFD ELECT	36	5-6835	COMPENSATING COIL	1J	5-270	SPEAKER TRANS.	36	5-270	SPEAKER TRANS.	1J	5-270	SPEAKER TRANS.
C-37	22-245	100 MFD	C-55	63-333	10 MFD ELECT	37	5-6835	ANT. COIL & SHIELD ASSEM	1K	5-270	CHOKES ASSEM.	37	5-270	CHOKES ASSEM.	1K	5-270	CHOKES ASSEM.
C-38	22-245	100 MFD	C-56	63-333	10 MFD ELECT	38	5-6835	OSCILLATOR COIL ASSEM	1L	5-270	PILOT LIGHT 25V 17A	38	5-270	PILOT LIGHT 25V 17A	1L	5-270	PILOT LIGHT 25V 17A
C-39	22-245	100 MFD	C-57	63-333	10 MFD ELECT	39	5-6835	COMPENSATING COIL	1M	5-270	SPEAKER TRANS.	39	5-270	SPEAKER TRANS.	1M	5-270	SPEAKER TRANS.
C-40	22-245	100 MFD	C-58	63-333	10 MFD ELECT	40	5-6835	ANT. COIL & SHIELD ASSEM	1N	5-270	CHOKES ASSEM.	40	5-270	CHOKES ASSEM.	1N	5-270	CHOKES ASSEM.
C-41	22-245	100 MFD	C-59	63-333	10 MFD ELECT	41	5-6835	OSCILLATOR COIL ASSEM	1O	5-270	PILOT LIGHT 25V 17A	41	5-270	PILOT LIGHT 25V 17A	1O	5-270	PILOT LIGHT 25V 17A
C-42	22-245	100 MFD	C-60	63-333	10 MFD ELECT	42	5-6835	COMPENSATING COIL	1P	5-270	SPEAKER TRANS.	42	5-270	SPEAKER TRANS.	1P	5-270	SPEAKER TRANS.
C-43	22-245	100 MFD	C-61	63-333	10 MFD ELECT	43	5-6835	ANT. COIL & SHIELD ASSEM	1Q	5-270	CHOKES ASSEM.	43	5-270	CHOKES ASSEM.	1Q	5-270	CHOKES ASSEM.
C-44	22-245	100 MFD	C-62	63-333	10 MFD ELECT	44	5-6835	OSCILLATOR COIL ASSEM	1R	5-270	PILOT LIGHT 25V 17A	44	5-270	PILOT LIGHT 25V 17A	1R	5-270	PILOT LIGHT 25V 17A
C-45	22-245	100 MFD	C-63	63-333	10 MFD ELECT	45	5-6835	COMPENSATING COIL	1S	5-270	SPEAKER TRANS.	45	5-270	SPEAKER TRANS.	1S	5-270	SPEAKER TRANS.
C-46	22-245	100 MFD	C-64	63-333	10 MFD ELECT	46	5-6835	ANT. COIL & SHIELD ASSEM	1T	5-270	CHOKES ASSEM.	46	5-270	CHOKES ASSEM.	1T	5-270	CHOKES ASSEM.
C-47	22-245	100 MFD	C-65	63-333	10 MFD ELECT	47	5-6835	OSCILLATOR COIL ASSEM	1U	5-270	PILOT LIGHT 25V 17A	47	5-270	PILOT LIGHT 25V 17A	1U	5-270	PILOT LIGHT 25V 17A
C-48	22-245	100 MFD	C-66	63-333	10 MFD ELECT	48	5-6835	COMPENSATING COIL	1V	5-270	SPEAKER TRANS.	48	5-270	SPEAKER TRANS.	1V	5-270	SPEAKER TRANS.
C-49	22-245	100 MFD	C-67	63-333	10 MFD ELECT	49	5-6835	ANT. COIL & SHIELD ASSEM	1W	5-270	CHOKES ASSEM.	49	5-270	CHOKES ASSEM.	1W	5-270	CHOKES ASSEM.
C-50	22-245	100 MFD	C-68	63-333	10 MFD ELECT	50	5-6835	OSCILLATOR COIL ASSEM	1X	5-270	PILOT LIGHT 25V 17A	50	5-270	PILOT LIGHT 25V 17A	1X	5-270	PILOT LIGHT 25V 17A
C-51	22-245	100 MFD	C-69	63-333	10 MFD ELECT	51	5-6835	COMPENSATING COIL	1Y	5-270	SPEAKER TRANS.	51	5-270	SPEAKER TRANS.	1Y	5-270	SPEAKER TRANS.
C-52	22-245	100 MFD	C-70	63-333	10 MFD ELECT	52	5-6835	ANT. COIL & SHIELD ASSEM	1Z	5-270	CHOKES ASSEM.	52	5-270	CHOKES ASSEM.	1Z	5-270	CHOKES ASSEM.

1ST 1A TRANS PRIMARY
2ND 1A TRANS SECONDARY
END 1F TRANS PRIMARY
END 1F TRANS SECONDARY
OROAD COST DEC. (SEE NOTES)
ANT BRACKET (AN BARS)
OROAD COST AUGUST
SHORT WAVE DEC. (SEE NOTES)

NOTE: TRIMMERS P.O.R. ARE
MOUNTED ON ORONALITE
STRIP PART 22-440

Models 6J322, 6J357

CHASSIS No. 5654

SOCKET VOLTAGES

NOTE

Voltages measured from socket contacts to chassis using a 1000 ohm per volt meter with chassis operating on 110 volt A.C.

Antenna disconnected — volume control on full.

Line voltage 115 v. Consumption 18 watts.

Battery voltage at chassis 6v.

Consumption — switch on normal 2.3 amperes.

Consumption — switch on conserv. 1.95 amperes.

Power Output 1 watt.



(A) Bias for 6D8 and 6S7 measured at K contacts of respective sockets which is +1.8 volts.

(B) Bias for 6G6 tubes measured at K contact of sockets which is +7 volts.

(C) Bias for 6T7 triode measured at K contact of same socket which is +1 volt.

LEGEND

NC — No Connection
SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
K — Cathode
F — Filament



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock Gang & adj. for max. output
5	" " "	200 Mmfd.		"		FG	Repeat 3 & 4
6	" " "	400 Ohms	18000	S.W.	18000	K	Rock gang & adj. for max. output

Models 7J323, 7J368
CHASSIS No. 5715

NOTE

Voltages measured from socket contacts to chassis using a 1000 ohm per volt meter with chassis operating on 110 volt A.C.

Line voltage 115 V. A.C. consumption 18 watts.

Battery voltage at chassis 6 volts.

Consumption with switch in normal position 2.6 amperes. **6S7G**
R.F.AMP

Consumption with switch in conserv. position 2.2 amperes.

Power output 1 watt.

(A) Bias for 6D8 and 6S7 R.F. and I.F. tubes measured at K of respective sockets which is +1.6 volts.

(B) Bias for 6T7 triode section measured at K of 6T7 socket which is +1 volt.

(C) Bias for 6G6 tubes measured at K of respective sockets which is +7 volts


LEGEND

NC—No Connection
SH—Shield
H—Heater
P—Plate
S—Screen
G—Grid
SU—Suppressor
D—Diode
K—Cathode
F—Filament

6S7G
I.F.AMP


6T7G
2ND DET. AVC.
1ST AUDIO

6ZY5G
RECTIFIER



FRONT OF CHASSIS


SOCKET VOLTAGES



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Al'gment of Ant. and Det.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "	200 Mmfd.		"		FGH	Repeat 2 & 3
6	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to scale
7	" " "	400 Ohms	18000	S.W.	18000	M	Rock gang & adj. for max. output
8	" " "	400 Ohms	6000	Police	6000	NO	Rock gang & adj. for max. output



I.F. FREQUENCY 455 K.C.
7 TUBE SUPERHETERODYNE
CHASSIS NO 5714-A.C. 3-BAND
ZENITH RADIO CORPORATION
CHICAGO, ILL.

CHASSIS NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	CHASSIS NO.	DESCRIPTION	PART NO.	DESCRIPTION
C-1	22-717	6001	100K 500V	1	100K 500V	C-19	22-717	6001	100K 500V
C-2	22-718	6002	100K 500V	2	100K 500V	C-20	22-718	6002	100K 500V
C-3	22-719	6003	100K 500V	3	100K 500V				
C-4	22-720	6004	100K 500V	4	100K 500V				
C-5	22-721	6005	100K 500V	5	100K 500V				
C-6	22-722	6006	100K 500V	6	100K 500V				
C-7	22-723	6007	100K 500V	7	100K 500V				
C-8	22-724	6008	100K 500V	8	100K 500V				
C-9	22-725	6009	100K 500V	9	100K 500V				
C-10	22-726	6010	100K 500V	10	100K 500V				
C-11	22-727	6011	100K 500V	11	100K 500V				
C-12	22-728	6012	100K 500V	12	100K 500V				
C-13	22-729	6013	100K 500V	13	100K 500V				
C-14	22-730	6014	100K 500V	14	100K 500V				
C-15	22-731	6015	100K 500V	15	100K 500V				
C-16	22-732	6016	100K 500V	16	100K 500V				
C-17	22-733	6017	100K 500V	17	100K 500V				
C-18	22-734	6018	100K 500V	18	100K 500V				
C-19	22-735	6019	100K 500V	19	100K 500V				
C-20	22-736	6020	100K 500V	20	100K 500V				


CHASSIS No. 5714

Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.

Power Output 4.5 watts.

(B) Bias for 6F5 measured across X and Y sections of voltage divider is—3.2 volts.

(C) Bias for 6F6 measured across XY and Z sections of voltage divider is—16 volts.



SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
K — Cathode
NC — No Connection
F — Filament

VOLTAGES

6F6G

6K7G

GND

6X5G

6F5G

AUTOMATIC TRIMMERS

PUSH BUTTONS

6A8G

6U5

6J5G

PILOT LIGHTS


The diagram shows the rear panel of the Model 1000 receiver. It features several vacuum tube sockets labeled 6F6G, 6K7G, 6F5G, 6X5G, 6A8G, and 6U5. There are also two sets of automatic trimmers, two push buttons, and two pilot lights. A ground connection (GND) is indicated. The diagram is labeled with various components and their connections, including labels like G, L, F, J, N, and K.

Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	455	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output.
6	" " "	200 Mmfd.		"		FG	Repea 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	18000	S.W.	18000	L	Rock Gang & adj. for max. output.
9	" " "	400 Ohms	6000	Police	6000	N	Rock Gang & adj. for max. output.

NOTE: If receiver is used in location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.



SPEAKER
49-148-12"

MODEL
95-365

I.F. FREQUENCY 455 KC.
9TUBE SUPERHETERODYNE
CHASSIS NO. 5906 AC. 3 BAND
ZENITH RADIO CORPORATION
CHICAGO, ILLINOIS

**NOTE:- TUNING EYE, 2" x 1 1/2"
100V. 100V. 100V. 100V. 100V.
WIRE # 22-36**

COMPONENT	VALUE	DESCRIPTION	COMPONENT	VALUE	DESCRIPTION	COMPONENT	VALUE	DESCRIPTION	COMPONENT	VALUE	DESCRIPTION
C-1	22-348	100V. 100V. 100V. 100V. 100V.	C-11	22-348	100V. 100V. 100V. 100V. 100V.	C-21	22-348	100V. 100V. 100V. 100V. 100V.	C-31	22-348	100V. 100V. 100V. 100V. 100V.
C-2	22-348	100V. 100V. 100V. 100V. 100V.	C-12	22-348	100V. 100V. 100V. 100V. 100V.	C-22	22-348	100V. 100V. 100V. 100V. 100V.	C-32	22-348	100V. 100V. 100V. 100V. 100V.
C-3	22-348	100V. 100V. 100V. 100V. 100V.	C-13	22-348	100V. 100V. 100V. 100V. 100V.	C-23	22-348	100V. 100V. 100V. 100V. 100V.	C-33	22-348	100V. 100V. 100V. 100V. 100V.
C-4	22-348	100V. 100V. 100V. 100V. 100V.	C-14	22-348	100V. 100V. 100V. 100V. 100V.	C-24	22-348	100V. 100V. 100V. 100V. 100V.	C-34	22-348	100V. 100V. 100V. 100V. 100V.
C-5	22-348	100V. 100V. 100V. 100V. 100V.	C-15	22-348	100V. 100V. 100V. 100V. 100V.	C-25	22-348	100V. 100V. 100V. 100V. 100V.	C-35	22-348	100V. 100V. 100V. 100V. 100V.
C-6	22-348	100V. 100V. 100V. 100V. 100V.	C-16	22-348	100V. 100V. 100V. 100V. 100V.	C-26	22-348	100V. 100V. 100V. 100V. 100V.	C-36	22-348	100V. 100V. 100V. 100V. 100V.
C-7	22-348	100V. 100V. 100V. 100V. 100V.	C-17	22-348	100V. 100V. 100V. 100V. 100V.	C-27	22-348	100V. 100V. 100V. 100V. 100V.	C-37	22-348	100V. 100V. 100V. 100V. 100V.
C-8	22-348	100V. 100V. 100V. 100V. 100V.	C-18	22-348	100V. 100V. 100V. 100V. 100V.	C-28	22-348	100V. 100V. 100V. 100V. 100V.	C-38	22-348	100V. 100V. 100V. 100V. 100V.
C-9	22-348	100V. 100V. 100V. 100V. 100V.	C-19	22-348	100V. 100V. 100V. 100V. 100V.	C-29	22-348	100V. 100V. 100V. 100V. 100V.	C-39	22-348	100V. 100V. 100V. 100V. 100V.
C-10	22-348	100V. 100V. 100V. 100V. 100V.	C-20	22-348	100V. 100V. 100V. 100V. 100V.	C-30	22-348	100V. 100V. 100V. 100V. 100V.	C-40	22-348	100V. 100V. 100V. 100V. 100V.
C-11	22-348	100V. 100V. 100V. 100V. 100V.	C-21	22-348	100V. 100V. 100V. 100V. 100V.	C-31	22-348	100V. 100V. 100V. 100V. 100V.	C-41	22-348	100V. 100V. 100V. 100V. 100V.
C-12	22-348	100V. 100V. 100V. 100V. 100V.	C-22	22-348	100V. 100V. 100V. 100V. 100V.	C-32	22-348	100V. 100V. 100V. 100V. 100V.	C-42	22-348	100V. 100V. 100V. 100V. 100V.
C-13	22-348	100V. 100V. 100V. 100V. 100V.	C-23	22-348	100V. 100V. 100V. 100V. 100V.	C-33	22-348	100V. 100V. 100V. 100V. 100V.	C-43	22-348	100V. 100V. 100V. 100V. 100V.
C-14	22-348	100V. 100V. 100V. 100V. 100V.	C-24	22-348	100V. 100V. 100V. 100V. 100V.	C-34	22-348	100V. 100V. 100V. 100V. 100V.	C-44	22-348	100V. 100V. 100V. 100V. 100V.
C-15	22-348	100V. 100V. 100V. 100V. 100V.	C-25	22-348	100V. 100V. 100V. 100V. 100V.	C-35	22-348	100V. 100V. 100V. 100V. 100V.	C-45	22-348	100V. 100V. 100V. 100V. 100V.
C-16	22-348	100V. 100V. 100V. 100V. 100V.	C-26	22-348	100V. 100V. 100V. 100V. 100V.	C-36	22-348	100V. 100V. 100V. 100V. 100V.	C-46	22-348	100V. 100V. 100V. 100V. 100V.
C-17	22-348	100V. 100V. 100V. 100V. 100V.	C-27	22-348	100V. 100V. 100V. 100V. 100V.	C-37	22-348	100V. 100V. 100V. 100V. 100V.	C-47	22-348	100V. 100V. 100V. 100V. 100V.
C-18	22-348	100V. 100V. 100V. 100V. 100V.	C-28	22-348	100V. 100V. 100V. 100V. 100V.	C-38	22-348	100V. 100V. 100V. 100V. 100V.	C-48	22-348	100V. 100V. 100V. 100V. 100V.
C-19	22-348	100V. 100V. 100V. 100V. 100V.	C-29	22-348	100V. 100V. 100V. 100V. 100V.	C-39	22-348	100V. 100V. 100V. 100V. 100V.	C-49	22-348	100V. 100V. 100V. 100V. 100V.
C-20	22-348	100V. 100V. 100V. 100V. 100V.	C-30	22-348	100V. 100V. 100V. 100V. 100V.	C-40	22-348	100V. 100V. 100V. 100V. 100V.	C-50	22-348	100V. 100V. 100V. 100V. 100V.

Model 9S365
CHASSIS No. 5906

SOCKET
VOLTAGES

NOTE

Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.

Line voltage 115 v. Consumption 75 watts.

Power Output 4.5 watts.

(A) Bias for 6A8 — 6K7 R.F. and I.F. and 6H6 measured at X is—2.6 volts.

(B) Bias for 6F5 measured at X and Y is—4 volts.


(C) Bias for 6F6 measured across XY and Z is—16 volts.

LEGEND

- SH—Shield
- H—Heater
- P—Plate
- S—Screen
- G—Grid
- SU—Suppressor
- D—Diode
- K—Cathode
- NC—No Connection
- F—Filament

5Y4G
RECT.


6F6G
OUTPUT



6J5G
OSC.

FRONT OF CHASSIS


6H6G
2ND DET. AVC.



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	456	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Al'gment of Ant. and Det.
4	" " "	200 Mmfd.	600	"		J	Rock gang & adj. for max. output
5				"		FGH	Repeat 2 & 3
6	Rec. Ant. Post	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	16500	S.W.	16500	LM	Rock gang & adj. for max. output
8	" " "	400 Ohms	5500	Police	5500	N	Rock gang & adj. for max. output



MODEL	SPEAKER
9 S 307	49-249-12"
9 S 324	49-179-8"
9 S 344	49-251-10"
9 S 367	49-249-12"
9 S 369	49-249-12"

I.F. FREQUENCY 455 KC.
9-TUBE SUPERHETERODYNE
CHASSIS NO. 5907 AC 3-BAND
ZENITH RADIO CORPORATION
CHICAGO, ILL.

DISC NO.	PART NO.	DESCRIPTION	DATE	PART NO.	DESCRIPTION	DATE	PART NO.	DESCRIPTION
C-1	12-744	THREE BANDS CONG.	1947	14	SECTION CANNON	1947	14	SECTION CANNON
C-2	12-745	40 MFD	1947	15	SECTION CANNON	1947	15	SECTION CANNON
C-3	12-746	10 MFD	1947	16	SECTION CANNON	1947	16	SECTION CANNON
C-4	12-747	1000 MFD	1947	17	SECTION CANNON	1947	17	SECTION CANNON
C-5	12-748	25 MFD	1947	18	SECTION CANNON	1947	18	SECTION CANNON
C-6	12-749	10 MFD	1947	19	SECTION CANNON	1947	19	SECTION CANNON
C-7	12-750	10 MFD	1947	20	SECTION CANNON	1947	20	SECTION CANNON
C-8	12-751	10 MFD	1947	21	SECTION CANNON	1947	21	SECTION CANNON
C-9	12-752	10 MFD	1947	22	SECTION CANNON	1947	22	SECTION CANNON
C-10	12-753	10 MFD	1947	23	SECTION CANNON	1947	23	SECTION CANNON
C-11	12-754	10 MFD	1947	24	SECTION CANNON	1947	24	SECTION CANNON
C-12	12-755	10 MFD	1947	25	SECTION CANNON	1947	25	SECTION CANNON
C-13	12-756	10 MFD	1947	26	SECTION CANNON	1947	26	SECTION CANNON
C-14	12-757	10 MFD	1947	27	SECTION CANNON	1947	27	SECTION CANNON
C-15	12-758	10 MFD	1947	28	SECTION CANNON	1947	28	SECTION CANNON
C-16	12-759	10 MFD	1947	29	SECTION CANNON	1947	29	SECTION CANNON
C-17	12-760	10 MFD	1947	30	SECTION CANNON	1947	30	SECTION CANNON
C-18	12-761	10 MFD	1947	31	SECTION CANNON	1947	31	SECTION CANNON
C-19	12-762	10 MFD	1947	32	SECTION CANNON	1947	32	SECTION CANNON
C-20	12-763	10 MFD	1947	33	SECTION CANNON	1947	33	SECTION CANNON
C-21	12-764	10 MFD	1947	34	SECTION CANNON	1947	34	SECTION CANNON
C-22	12-765	10 MFD	1947	35	SECTION CANNON	1947	35	SECTION CANNON
C-23	12-766	10 MFD	1947	36	SECTION CANNON	1947	36	SECTION CANNON
C-24	12-767	10 MFD	1947	37	SECTION CANNON	1947	37	SECTION CANNON
C-25	12-768	10 MFD	1947	38	SECTION CANNON	1947	38	SECTION CANNON
C-26	12-769	10 MFD	1947	39	SECTION CANNON	1947	39	SECTION CANNON
C-27	12-770	10 MFD	1947	40	SECTION CANNON	1947	40	SECTION CANNON
C-28	12-771	10 MFD	1947	41	SECTION CANNON	1947	41	SECTION CANNON
C-29	12-772	10 MFD	1947	42	SECTION CANNON	1947	42	SECTION CANNON
C-30	12-773	10 MFD	1947	43	SECTION CANNON	1947	43	SECTION CANNON
C-31	12-774	10 MFD	1947	44	SECTION CANNON	1947	44	SECTION CANNON
C-32	12-775	10 MFD	1947	45	SECTION CANNON	1947	45	SECTION CANNON
C-33	12-776	10 MFD	1947	46	SECTION CANNON	1947	46	SECTION CANNON
C-34	12-777	10 MFD	1947	47	SECTION CANNON	1947	47	SECTION CANNON
C-35	12-778	10 MFD	1947	48	SECTION CANNON	1947	48	SECTION CANNON
C-36	12-779	10 MFD	1947	49	SECTION CANNON	1947	49	SECTION CANNON
C-37	12-780	10 MFD	1947	50	SECTION CANNON	1947	50	SECTION CANNON
C-38	12-781	10 MFD	1947	51	SECTION CANNON	1947	51	SECTION CANNON
C-39	12-782	10 MFD	1947	52	SECTION CANNON	1947	52	SECTION CANNON
C-40	12-783	10 MFD	1947	53	SECTION CANNON	1947	53	SECTION CANNON
C-41	12-784	10 MFD	1947	54	SECTION CANNON	1947	54	SECTION CANNON
C-42	12-785	10 MFD	1947	55	SECTION CANNON	1947	55	SECTION CANNON
C-43	12-786	10 MFD	1947	56	SECTION CANNON	1947	56	SECTION CANNON
C-44	12-787	10 MFD	1947	57	SECTION CANNON	1947	57	SECTION CANNON
C-45	12-788	10 MFD	1947	58	SECTION CANNON	1947	58	SECTION CANNON
C-46	12-789	10 MFD	1947	59	SECTION CANNON	1947	59	SECTION CANNON
C-47	12-790	10 MFD	1947	60	SECTION CANNON	1947	60	SECTION CANNON
C-48	12-791	10 MFD	1947	61	SECTION CANNON	1947	61	SECTION CANNON
C-49	12-792	10 MFD	1947	62	SECTION CANNON	1947	62	SECTION CANNON
C-50	12-793	10 MFD	1947	63	SECTION CANNON	1947	63	SECTION CANNON
C-51	12-794	10 MFD	1947	64	SECTION CANNON	1947	64	SECTION CANNON
C-52	12-795	10 MFD	1947	65	SECTION CANNON	1947	65	SECTION CANNON
C-53	12-796	10 MFD	1947	66	SECTION CANNON	1947	66	SECTION CANNON
C-54	12-797	10 MFD	1947	67	SECTION CANNON	1947	67	SECTION CANNON
C-55	12-798	10 MFD	1947	68	SECTION CANNON	1947	68	SECTION CANNON
C-56	12-799	10 MFD	1947	69	SECTION CANNON	1947	69	SECTION CANNON
C-57	12-800	10 MFD	1947	70	SECTION CANNON	1947	70	SECTION CANNON
C-58	12-801	10 MFD	1947	71	SECTION CANNON	1947	71	SECTION CANNON
C-59	12-802	10 MFD	1947	72	SECTION CANNON	1947	72	SECTION CANNON
C-60	12-803	10 MFD	1947	73	SECTION CANNON	1947	73	SECTION CANNON
C-61	12-804	10 MFD	1947	74	SECTION CANNON	1947	74	SECTION CANNON
C-62	12-805	10 MFD	1947	75	SECTION CANNON	1947	75	SECTION CANNON
C-63	12-806	10 MFD	1947	76	SECTION CANNON	1947	76	SECTION CANNON
C-64	12-807	10 MFD	1947	77	SECTION CANNON	1947	77	SECTION CANNON
C-65	12-808	10 MFD	1947	78	SECTION CANNON	1947	78	SECTION CANNON
C-66	12-809	10 MFD	1947	79	SECTION CANNON	1947	79	SECTION CANNON
C-67	12-810	10 MFD	1947	80	SECTION CANNON	1947	80	SECTION CANNON
C-68	12-811	10 MFD	1947	81	SECTION CANNON	1947	81	SECTION CANNON
C-69	12-812	10 MFD	1947	82	SECTION CANNON	1947	82	SECTION CANNON
C-70	12-813	10 MFD	1947	83	SECTION CANNON	1947	83	SECTION CANNON
C-71	12-814	10 MFD	1947	84	SECTION CANNON	1947	84	SECTION CANNON
C-72	12-815	10 MFD	1947	85	SECTION CANNON	1947	85	SECTION CANNON
C-73	12-816	10 MFD	1947	86	SECTION CANNON	1947	86	SECTION CANNON
C-74	12-817	10 MFD	1947	87	SECTION CANNON	1947	87	SECTION CANNON
C-75	12-818	10 MFD	1947	88	SECTION CANNON	1947	88	SECTION CANNON
C-76	12-819	10 MFD	1947	89	SECTION CANNON	1947	89	SECTION CANNON
C-77	12-820	10 MFD	1947	90	SECTION CANNON	1947	90	SECTION CANNON
C-78	12-821	10 MFD	1947	91	SECTION CANNON	1947	91	SECTION CANNON
C-79	12-822	10 MFD	1947	92	SECTION CANNON	1947	92	SECTION CANNON
C-80	12-823	10 MFD	1947	93	SECTION CANNON	1947	93	SECTION CANNON
C-81	12-824	10 MFD	1947	94	SECTION CANNON	1947	94	SECTION CANNON
C-82	12-825	10 MFD	1947	95	SECTION CANNON	1947	95	SECTION CANNON
C-83	12-826	10 MFD	1947	96	SECTION CANNON	1947	96	SECTION CANNON
C-84	12-827	10 MFD	1947	97	SECTION CANNON	1947	97	SECTION CANNON
C-85	12-828	10 MFD	1947	98	SECTION CANNON	1947	98	SECTION CANNON
C-86	12-829	10 MFD	1947	99	SECTION CANNON	1947	99	SECTION CANNON
C-87	12-830	10 MFD	1947	100	SECTION CANNON	1947	100	SECTION CANNON
C-88	12-831	10 MFD	1947	101	SECTION CANNON	1947	101	SECTION CANNON
C-89	12-832	10 MFD	1947	102	SECTION CANNON	1947	102	SECTION CANNON
C-90	12-833	10 MFD	1947	103	SECTION CANNON	1947	103	SECTION CANNON
C-91	12-834	10 MFD	1947	104	SECTION CANNON	1947	104	SECTION CANNON
C-92	12-835	10 MFD	1947	105	SECTION CANNON	1947	105	SECTION CANNON
C-93	12-836	10 MFD	1947	106	SECTION CANNON	1947	106	SECTION CANNON
C-94	12-837	10 MFD	1947	107	SECTION CANNON	1947	107	SECTION CANNON
C-95	12-838	10 MFD	1947	108	SECTION CANNON	1947	108	SECTION CANNON
C-96	12-839	10 MFD	1947	109	SECTION CANNON	1947	109	SECTION CANNON
C-97	12-840	10 MFD	1947	110	SECTION CANNON	1947	110	SECTION CANNON
C-98	12-841	10 MFD	1947	111	SECTION CANNON	1947	111	SECTION CANNON
C-99	12-842	10 MFD	1947	112	SECTION CANNON	1947	112	SECTION CANNON
C-100	12-843	10 MFD	1947	113	SECTION CANNON	1947	113	SECTION CANNON
C-101	12-844	10 MFD	1947	114	SECTION CANNON	1947	114	SECTION CANNON
C-102	12-845	10 MFD	1947	115	SECTION CANNON	1947	115	SECTION CANNON
C-103	12-846	10 MFD	1947	116	SECTION CANNON	1947	116	SECTION CANNON
C-104	12-847	10 MFD	1947	117	SECTION CANNON	1947	117	SECTION CANNON
C-105	12-848	10 MFD	1947	118	SECTION CANNON	1947	118	SECTION CANNON
C-106	12-849	10 MFD	1947	119	SECTION CANNON	1947	119	SECTION CANNON
C-107	12-850	10 MFD	1947	120	SECTION CANNON	1947	120	SECTION CANNON
C-108	12-851	10 MFD	1947	121	SECTION CANNON	1947	121	SECTION CANNON
C-109	12-852	10 MFD	1947	122	SECTION CANNON	1947	122	SECTION CANNON
C-110	12-853	10 MFD	1947	123	SECTION CANNON	1947	123	SECTION CANNON
C-111	12-854	10 MFD	1947	124	SECTION CANNON	1947	124	SECTION CANNON
C-112	12-855	10 MFD	1947	125	SECTION CANNON	1947	125	SECTION CANNON
C-113	12-856	10 MFD	1947	126	SECTION CANNON	1947	126	SECTION CANNON
C-114	12-857	10 MFD	1947	127	SECTION CANNON	1947	127	SECTION CANNON
C-115	12-858	10 MFD	1947	128	SECTION CANNON	1947	128	SECTION CANNON
C-116	12-859	10 MFD	1947	129	SECTION CANNON	1947	129	SECTION CANNON
C-117	12-860	10 MFD	1947	130	SECTION CANNON	1947	130	SECTION CANNON
C-118	12-861	10 MFD	1947	131	SECTION CANNON	1947	131	SECTION CANNON
C-119	12-862	10 MFD	1947	132	SECTION CANNON	1947	132	SECTION CANNON
C-120	12-863	10 MFD	1947	133	SECTION CANNON	1947	133	SECTION CANNON
C-121	12-864	10 MFD	1947	134	SECTION CANNON	1947	134	SECTION CANNON
C-122	12-865	10 MFD	1947	135	SECTION CANNON	1947	135	SECTION CANNON
C-123	12-866	10 MFD	1947	136	SECTION CANNON	1947	136	SECTION CANNON
C-124	12-867	10 MFD	1947	137	SECTION CANNON	1947	137	SECTION CANNON
C-125	12-868	10 MFD	1947	138	SECTION CANNON	1947	138	SECTION CANNON
C-126	12-869	10 MFD	1947	139	SECTION CANNON	1947	139	SECTION CANNON
C-127	12-870	10 MFD	1947	140	SECTION CANNON	1947	140	SECTION CANNON
C-128	12-871	10 MFD	1947	141	SECTION CANNON	1947	141	SECTION CANNON
C-129	12-872	10 MFD	1947	142	SECTION CANNON	1947	142	SECTION CANNON
C-130	12-873	10 MFD	1947	143	SECTION CANNON	1947	143	SECTION CANNON
C-131	12-874	10 MFD	1947	144	SECTION CANNON	1947	144	SECTION CANNON
C-132	12-875	10 MFD	1947	145	SECTION CANNON	1947	145	SECTION CANNON
C-133	12-876	10 MFD	1947	146	SECTION CANNON	1947	146	SECTION CANNON
C-134	12-877	10 MFD	1947	147	SECTION CANNON	1947	147	SECTION CANNON
C-135	12-878	10 MFD	1947	148	SECTION CANNON	1947	148	SECTION CANNON
C-136	12-879	10 MFD	1947	149	SECTION CANNON	1947	149	SECTION CANNON
C-137	12-880	10 MFD	1947	150	SECTION CANNON	1947	150	SECTION CANNON
C-138	12-881	10 MFD	1947	151	SECTION CANNON	1947	151	SECTION CANNON
C-139	12-882	10 MFD	1947	152	SECTION CANNON	1947	152	SECTION CANNON
C-140	12-883	10 MFD	1947	153	SECTION CANNON	1947	153	SECTION CANNON
C-141	12-884	10 MFD	1947	154	SECTION CANNON	1947	154	SECTION CANNON
C-142	12-885	10 MFD	1947	155	SECTION CANNON	1947	155	SECTION CANNON
C-143	12-886	10 MFD	1947	156	SECTION CANNON	1947	156	SECTION CANNON
C-144	12-887	10 MFD	1947	157	SECTION CANNON	1947	157	SECTION CANNON
C-145	12-888	10 MFD	1947	158	SECTION CANNON	1947	158	SECTION CANNON
C-146	12-889	10 MFD	1947	159	SECTION CANNON	1947	159	SECTION CANNON
C-147	12-890	10 MFD	1947	160	SECTION CANNON	1947	160	SECTION CANNON
C-148	12-891	10 MFD	1947	161	SECTION CANN			

NOTE

Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.

Line voltage 115 v. Consumption 75 watts

Power Output 4.5 watts.

(A) Bias for 6K7 R. F. and I.F. — 6L7—6U5 and 6J5 second det. measured across X and is—1.6 volt.


(B) Bias for 6F5 measured across X and Y and is—3 volts.

(C) Bias for 6F6 measured across XY and Z and is—16 volts.

LEGEND

SH—Shield
H—Heater
P—Plate
S—Screen
G—Grid
SU—Suppressor
D—Diode
K—Cathode
NC—No Connection
F—Filament

Location of
Tubes and Trimmers




6J5G
OSC.

FRONT OF CHASSIS

6J5G
2ND DET.

SOCKET
VOLTAGES



ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Al'gment of Ant. and Det.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "	200 Mmfd.		"		FGH	Repeat 2 & 3
6	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to scale
7	" " "	400 Ohms	18000	S.W.	18000	M	Rock gang & adj. for max. output
8	" " "	400 Ohms	6000	Police	6000	N	Rock gang & adj. for max. output

CHASSIS No. 1206

Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.

Line voltage 115 volts. Consumption 110 watts.


Power Output 15 watts.

(A) Bias for 6J5 first audio is measured across R14 and is +2.3 volts.

(B) Bias for 6V6 tubes measured across Y is $+10$ volts.


(C) Bias for 6K7 R.F. and I.F. and 6L7 measured across X is -2.6 volts.

(D) Bias for 6F8 grids shown at cathodes of 6F8 sockets.



LEGEND



SH—Shield
H—Heater
P—Plate
S—Screen
G—Grid
SU—Suppressor
D—Diode
K—Cathode
NC—No Connection
F—Filament



ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABABAB 1 1 2 2 3 3	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Al'gment of Ant. and Det.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "			"		FGH	Repeat 2 & 3
6	" " "	400 Ohms	18000	S.W.	18000	K	Set. Osc. to Scale
7	" " "	400 Ohms	18000	S.W.	18000	M	Rock Gang & adj. for max. output
8	" " "	400 Ohms	6000	Police	6000	N	Rock gang & adj. for max. output

CHASSIS No. 1502



Voltages measured with a 1000 ohm per volt meter from chassis to socket contacts. Antenna disconnected — volume control on full.

Line voltage 115 volts. Consumption 160 watts.


Power Output 30 watts.

(A) Bias for 6K7 R.F. and I.F. — 6L7 — 6V5 triode and 6J5 second detector is measured across X and is—2.6 volts.

(B) Bias for 6J5 first audio is measured between points K of 6J5 socket and Z and is 2.4 volts.

(C) Bias for 6F8 measured at K^1 and K^2 and is 2 volts.

(D) Bias for the four 6V6 measured across X and Y and is 10 volts.




Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABABAB 1 1 2 2 3 3	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	GH	Al'gment of Ant. and Det.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "			"		FGH	Repeat 2 & 3
6	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
7	" " "	400 Ohms	18000	S.W.	18000	M	Rock Gang & adj. for max. output
8	" " "	400 Ohms	6000	Police	6000	N	Rock gang & adj. for max. output


CIRCUIT CHANGES FOR PHONO PICKUP CONNECTIONS

CIRCUIT #1-A




CIRCUIT CHANGES FOR PHONOGRAPH
INSTALLATIONS ON CHASSIS MODELS
5410-5411-5520-5528AT-5529-5529AT
5646-5647-5653-5653T AND 5654.


MODEL #5R-303-CHASSIS-5528




CIRCUIT # 5A
MODEL-65-306 CHASSIS # 5651




CIRCUIT #3A
MODEL #6D-302-CHASSIS #5646
WIRING OF PHONO CKT. COMPONENTS




CIRCUIT #30
MODEL #65-301 & MODEL #65-305
CHASSIS #9651



CIRCUIT #6A
MODEL #195-300 CHASSIS #1902 ALPHABETICALLY




CIRCUIT #2A




CIRCUIT CHANGES NECESSARY FOR
INSTALLATION OF PHONO IN AND JACK
CHASSIS 5714-5901-5715 657157 3AM
EXCEPT 67TG DETAMP TUBE.


CIRCUIT 4B



CIRCUIT #98
MODEL 95-307 CHASSIS #5907



DET
6H6G



CIRCUIT CHANGES FOR PHONOGRAPH
INSTALLATIONS ON CHASSIS MODELS
3649-5906

PARTS PRICE LIST

1939 MODELS

FOR CHASSIS MODEL CHART SEE FRONT COVER

Chassis No.	Code	Chassis No.	Code	Chassis No.	Code
1206	A	5646	G	5654	M
1502	B	5647	H	5714	N
5410	C	5648	I	5715	O
5411	D	5649	J	5906	P
5528	E	5651	K	5907	R
5529	F	5653	L		

Note—25 cycle sets are designated by the number '2' following the code letter. Example — A2—1206A.

DIAL ASSEMBLIES

12-514	Resonance ind. mtg. brkt. (lower)	P	\$.05	80-130	Clutch spring	A-B-B2-J-P	.03
12-515	Resonance ind. mtg. brkt. (upper)	P	.05	80-136	Movable scale return spring	P	.05
19-68	Dial glass retaining clip	I	.02	80-137	Dial glass retaining spring	P	.01
19-73	Dial glass retaining clip	J	.02	80-138	Retainer spring (hairpin type)	A-B-B2-O-P-R	.01
26-144	Dial scale	I	.75	80-139	Dial spring	A-B-B2-O-P	.05
26-145	Dial scale	P	.50	80-151	Movable scale return spring	A-B-B2-O-R	.06
26-163	Dial scale	J	1.25	83-407	Dial light diffusion strip	I-J	.03
26-196	Dial scale	G	.15	83-490	Movable scale spacer strip	A-B-B2-O-R	.75C
26-199	Dial scale	C-D-E-H	.15	83-491	Movable scale spacer strip	P	.05
26-200	Dial scale	F	.30	83-499	Felt strip	P	.20
26-201	Dial scale	N	.35	83-516	Brass spacer strip (bent)	A-B-B2-O-R	.02
26-209	Dial scale	K-L	.35	83-522	Brass spacer strip (straight)	A-B-B2-O-R	.01
26-215	Dial scale	M	.35	83-523	Movable scale spacer strip	A-B-B2-O-R	.03
27-16	Flywheel disc	A-B2-J-N-O	1.00	83-538	Dial support strip	F	.005
27-28	Flywheel disc	K-L	.30	85-116	Motor control switch	P	1.00
32-13	Drive belt	I	.15	85-156	Motor switch	B	1.00
32-15	Dial belt	A-B-B2-O-P	.15	93-273	Black bakelite pointer washer	I-J	.01
32-17	Dial belt	J	.15	93-339	1/32 x .234 x 3/4" bake. wshr.	P	.01
32-18	Motor drive belt	B-P	.15	93-360	1/32 x .243 x .355 brass wshr.	G	.50C
34-49	Condenser shaft gear	I-J	.25	93-371	Dial pointer bakelite wshr.	C-D-E-F-K-L-M	.25C
34-51	Lower pinion & gear	I-J	.15	94-230	Drive shaft bushing	I	.10
34-68	Condenser shaft gear & bush.	A-B-B2-O-P	.20	94-257	Shaft bushing	P	.03
34-69	Lower drive gear & pinion	P	.15	94-258	Drive shaft bushing	J-P	\$.03
34-72	Frequency pointer gear & sht.	P	.30	94-267	Brass spacer bushing	A-B2	.01
34-79	Frequency pointer gear & sht.	A-B-B2	.30	94-271	Volume control shaft coupling	A-B-B2-N-O	.04
34-80	Lower drive gear & pinion	A-B-B2-O	.15	94-557	Brass bushing	B	.01
54-108	Palnut	B	.50C	97-91	Lower gear stud	I-J	.05
56-54	Fiber clutch pin	A-B-B2	.02	97-101	Idler gear stud	P	.05
56-56	Fiber clutch pin	A	.02	97-103	Movable scale pivot stud	P	.02
59-41	Split second pointer	I	.10	97-107	Motor mounting stud	P	.05
59-52	Split second pointer	J	.10	100-36	6.3 volt pilot lamp	A-B-B2-E-F-G-H-I-J-K-N-P-R	.09
59-53	Frequency indicator pointer	J	.20	100-39	2.9 volt pilot lamp	L-M	.12
59-58	Split second pointer	P	.20	100-67	6.3 volt pilot lamp	O	.12
59-59	Frequency indicator pointer	P	.15	114-47	#6 x 3/16" slotted P.K. screws	A-B-B2-O-R	.30C
59-60	Frequency indicator pointer	I	.15	114-52	8/32 x 3/16" slotted mach. scr.	A-B2-O	.25C
59-65	Dial pointer	G	.10	114-60	6/32 x 3/16" slotted P.K. scr.	A-B-B2-O-R	.25C
59-66	Dial pointer	C-D-E-H	\$.15	114-62	#8 x 1/4" slotted self tap. screw	A-B2-O	.40C
59-67	Dial pointer	F	.15	117-38	Band selector lever	A-B-B2-N-R	.10
59-69	Station indicator pointer	A-B-B2-O-R	.08	117-48	Band switch lever arm	A-B-B2-O-R	.20
59-70	Pointer & spring assy.	N	.10	118-16	Band switch lvr. conn. link	A-B-B2-N-O-R	.01
59-71	Dial pointer	K-L-M	.15	148-25	Band switch control arm	N	.10
61-34	Drive pulley	I	.10	159-12	Band switch lvr. arm link but.	A-B-B2-N-O-P-R	.02
61-42	Pointer shaft pulley	A-B-B2-O-P	.20	188-2	Retaining ring	B	.01
61-43	Drive pulley (part of S-5090)	J-P	.15	188-27	Retaining ring	D-E-G-K	.05C
61-44	Motor shaft pulley	B-P	.15	192-16	Dial glass	I	.20
61-51	Drive shaft pulley	A-B	.10	192-17	Dial glass	J-P	.40
61-61	Drive shaft pulley	B2	.15	192-28	Dial crystal	G	.20
73-8	Dial pulley set screw	C-L-M	.02	192-29	Dial crystal	C-D-E-H	.15
73-16	8/32 x 1/8" headless set screw	A-O	.01	192-30	Dial glass	F	.25
73-24	8/32 x 1/4" H.H. set screw	I	.02	192-32	Dial glass	K-L-M	.35
73-28	Pointer pulley set screw	A-B2-O	.01	192-33	Dial glass	A-B-B2-N-O-R	.35
73-30	6/32 x 1/4" H.H. set screw	N	.02	196-10	Dial glass	I	.10
76-227	Drive shaft	I	.05	196-13	Dial glass gasket	P	.10
76-229	Split second pointer sht. & pin.	A-B-O-P	.10	196-15	Dial glass gasket	J	.10
76-234	Drive shaft	J	.20	196-16	Dial glass gasket	F	.25
76-237	Motor switch control shaft	P	.08	196-17	Dial glass gasket	A-B-B2-N-O-R	.15
76-238	Condenser drive shaft	P	.30	196-18	Dial glass gasket	K	.15
76-257	Tuning control shaft	G	.03	199-11	Rubber sleeve for 61-51	B	.01
76-258	Tuning control shaft	D-E-H	.08	199-13	Movable scl.e.retrn.rubbr.bump	A-B-B2-O-R	.02
76-259	Tuning control shaft	F	.10	S-3780	Shaft pulley sleeve assembly	I-J	.35
76-262	Volume control shaft	A-B-O	.10	S-4340	Tension pulley assembly	I-J	.15
76-263	Drive shaft	K	.10	S-4906	Dial light socket & clip assem.	J	.10
76-265	Volume control shaft	N	.10	S-4913	Dial light socket & clip assem.	O-P	.10
76-266	Condenser drive shaft	B	.10	S-4914	Dial light socket & clip assem.	P	.10
78-226	Dial lamp socket	L-M	.10	S-4974	Band switch lever & bushing	P	.40
80-60	Tension pulley spring	I-J	.03	S-4975	Dial mtg. plate & stud assem.	P	1.25
80-69	Dial cord tension spring	C-D-E-F-G-H-K-L-M-N	.02	S-4976	Stationary dial scl.e. & liht. brkt.	P	1.50
80-116	Dial spring	J	.03				
80-118	Dial spring	I	.15				
80-128	Shaft pulley spring	I	.01				

PARTS LIST (Continued)

4981	Brdest. band scale assy. (26-147+148)	P	.75
4982	Short wave bnd. scale assy. (26-154)	P	.75
4984	Volume cntrl. scale & bshng. (26-254)	J	.35
4986	Tone cntrl. scale & bshng. (26-152)	P	.35
4989	Complete dial scale & mtg. plate assembly	P	4.00
-5007	Movable scale cntrl. arm & pin assembly	P	.40
-5009	Motor & cover assembly (141-51)	P	5.00
-5041	Volume cntrl. scale & bushng. (26-151)	P	.35
-5090	Drive pulley & clutch assem.	J	.35
-5092	Tone control scale & bushing (26-165)	J	.35
-5998	Manual automatic scl. & bushing (26-198)	P	\$.35
-5999	Dial light socket & clip assem.	K-N	.10
-6002	Dial cord & eyelet assem.	G	.10
-6011	Band indicator & autoc. switch (26-197)	J	.35
-6109	Dial cord & eyelet assem.	C-D-E-H	.15
-6122	Condenser drive shaft & bush. assembly	A-O	.35
-6175	Dial cord & eyelet assem.	F	.15
-6181	Oscillator Coil Assem.	C	.50
-6182	Antenna Coil Assem.	C	.50
-6210	Dial mtg. plate & stud assem.	A-B-B2-O-R	.75
-6211	Dial scale assembly (26-208)	A-B-B2-O-R	2.00
-6216	Dial scale assem. (26-204 & 5)	A-B-B2-O-R	.75
-6217	Dial scale assem. (26-206 & 7)	A-B-O-R	.75
-6218	Dial scale control arm & pin	O	.40
-6220	Condenser drive shaft pulley & clutch	A-O	.20
-6221	Station pointer gear & pin ass.	A-O	.30
-6223	Tuning shaft & bush. assem.	N	.20
-6284	Dial cord & eyelet assem.	K-L-N	.25
-6379	Large split second pointer	A-B-B2-R	.10
-6394	Dial scale assem. (26-211 & 12)	A2-B2-R2	.75
-6398	Motor switch lever arm & bracket	B	.20
-6399	Motor Switch & Bracket	B	1.25
-6402	Motor & cover assembly	B	5.00
-6556	Dial cord & eyelet assembly	N	.15
4S-321	Pulley assembly (motor drive)	P	.20
4S-418	Dial pulley & bracket assem.	C-D-E-F-H	.10
4S-449	Dial pulley & bracket assem.	K-L-M-N	.35
4S-452	Drive shaft pulley assembly	B	.75

COILS & CHOKES

20-135	R. F. Choke	P	\$.50
20-154	Wave trap assembly	I-J-K-N	.65
20-183	Compensating coil	F-I-J-P	.50
20-187	Compensating coil	D-E-H	.45
20-189	R. F. Choke coil	A-B-O-R	.35
20-196	Compensating coil assembly	A-B-K-L-M-N-O-R	.50
95-413	1st I. F. transformer	I	1.50
95-414	2nd I. F. transformer	I	1.50
95-416	1st I. F. transformer	J-P	1.25
95-417	2nd I. F. transformer	J-P	1.25
95-513	1st I. F. transformer	C-D-E-F-G-H	.75
95-514	2nd I. F. transformer	F-G	.75
95-520	2nd I. F. transformer	C-D-E-H	.75
95-529	1st I. F. transformer	K-L	1.25
95-530	2nd I. F. transformer	K-L	1.25
95-536	1st I. F. transformer	N	1.00
95-537	2nd I. F. transformer	N	1.00
95-538	1st I. F. transformer	R	1.00
95-539	2nd I. F. transformer	R	1.00
95-553	1st I. F. transformer	R2	1.00
95-554	2nd I. F. transformer	R2	1.00
95-558	1st I. F. transformer	K-M	1.25
95-559	2nd I. F. transformer	M	1.25
95-560	1st I. F. transformer	N	1.00
95-561	2nd I. F. transformer	K-N-O	1.25
95-562	1st I. F. transformer	O	1.25
S-4941	Antenna coil & shield assem.	I	1.50
S-4942	Oscillator coil assem.	I	1.50
S-5017	Antenna coil & shield assem.	P	1.50
S-5018	Detector coil & shield assem.	P	1.35

S-5019	Oscillator coil & shield assem.	P	1.75
S-5073	Antenna coil & shield assem.	J	1.50
S-5074	Oscillator coil & shield assem.	J	1.50
S-5808	Antenna coil assembly	E-H	.50
S-5958	Antenna coil assembly	G	.50
S-5959	Oscillator coil assembly	G	.65
S-6039	Oscillator coil assembly	E-H	.35
S-6118	Oscillator coil assembly	F	.75
S-6161	Antenna coil assembly	F	2.00
S-6207	Antenna coil & shield assem.	R	1.50
S-6208	Detector coil & shield assem.	O-R	1.25
S-6209	Oscillator coil & shield assem.	R	1.25
S-6266	Antenna coil & shield assem.	K	1.50
S-6267	Oscillator coil & shield assem.	K	1.25
S-6294	Antenna coil & shield assem.	N	1.50
S-6295	Oscillator coil & shield assem.	N	1.25
S-6327	Antenna coil & shield assem.	A-B	1.50
S-6328	Detector coil & shield assem.	A-B	1.25
S-6329	Oscillator coil & shield assem.	A-B	1.25
S-6374	I. F. transformer	A-B	2.00
S-6375	I. F. transformer	A-B	2.00
S-6376	I. F. transformer	A-B	2.00
S-6381	Oscillator coil assembly	C	.50
S-6382	Antenna coil assembly	C	.50
S-6442	Oscillator coil assembly	D	.60
S-6508	Antenna coil & shield assem.	L	1.50
S-6541	Antenna coil & shield assem.	O	1.50
S-6553	Antenna coil & shield assem.	M	1.50
S-6554	Oscillator coil & wire assem.	M	.75
S-6560	Antenna coil assembly	D	.60
S-6607	Oscillator coil & shield assem.	L	1.25
S-6608	Oscillator coil & shield assem.	O	1.25

CONDENSERS

22-127	25 mmfd.	600 volt	\$.15
22-147	.0005 mfd.	600 volt	.15
22-162	.0001 mfd.	600 volt	.15
22-170	.1 mfd.	400 volt	.20
22-171	.05 mfd.	600 volt	.18
22-177	.2 mfd.	400 volt	.20
22-182	.00025 mfd.	600 volt	.15
22-185	.01 mfd.	200 volt	.15
22-188	.02 mfd.	400 volt	.15
22-190	.1 mfd.	200 volt	.15
22-196	.01 mfd.	600 volt	.15
22-199	.5 mfd.	200 volt	.25
22-212	.05 mfd.	400 volt	.15
22-219	.03 mfd.	200 volt	.12
22-229	.005 mfd.	600 volt	.18
22-243	.01 mfd.	400 volt	.15
22-250	.05 mfd.	200 volt	.15
22-285	10 mmfd.	600 volt	.15
22-289	50 mmfd.	600 volt	.15
22-305	2-35 mmfd. trimmer	F-I-J-K-L-N-O	.15
22-324	Three sec. trimr. 2-35 mmfd.	J-L	.30
22-326	.003 mfd.	400 volt	.15
22-327	.02 mfd.	200 volt	.12
22-350	.25 mfd.	200 volt	.15
22-358	.002 mfd.	600 volt	.25
22-405	10 mfd. 50 volt electrolytic	M-O	.75
22-408	2-35 mmfd. two sec. trimmer	M	.30
22-418	2-35 mmfd. trimmer	P-R	.10
22-435	.02 mfd.	600 volt	.18
22-448	.004 mfd.	600 volt	.18
22-455	.01 mfd.	1200 volt	.20
22-458	.006 mfd.	600 volt	.18
22-463	335-825 mmfd. padder	A-K-L-N-O	.30
22-470	.00015 mfd.	600 volt	.15
22-487	.05 mfd.	400 volt	.15
22-492	.002 mfd.	600 volt	.15
22-519	200-550 mmfd. trimmer	A-B-D-E-F-H-I-J-K-L-M-N-O-P-R	.35
22-524	2-35 mmfd. trimmer	A	.15
22-525	.005 mfd.	600 volt	.20
22-547	Two gang variable	I-J	2.50
22-548	Three gang variable	P	4.00
22-549	Four section 2-35 mmfd. trim.	P	.40
22-551	16 mfd.	400 volt	.75
22-552	20 mfd.	300 volt	.75
22-558	Dual fixed padder	I-J-R	.60
22-563	5000 mmfd. fixed padder	F-M	.50
22-569	12 mfd. 450 volt electrolytic	B-P	.95
22-570	15-70 mmfd. trimmer	F	.15

PARTS LIST—(Continued)

22-571	2x8 mfd. 450 volt—6 mfd.			
	250 volt	P	1.25	
22-596	8. x 14. mfd. 450 volt	I	1.75	
22-598	2-35 mmfd. Three sec. trim.	I-O-R	.30	
22-599	14 x 8 mfd. 450 volt electrolytic	J	1.75	
22-627	.002 mfd. 1000 volt		.15	
22-669	.01 mfd. 600 volt		.18	
22-679	Two gang variable	G	1.85	
22-680	16 mfd. 150 volt electrolytic	G-H	\$.35	
*22-681	40 mfd. 150 volt electrolytic (G)	B-G-H	.50	
22-685	2-35 mmfd. 2 sec. trimmer	F	.30	
22-691	8 mfd. 450 volt electrolytic	E	.50	
22-692	8 mfd. 350 volt electrolytic	E	.45	
22-695	Two gang variable	C-D-E-H	2.00	
22-696	Two gang variable	F	2.00	
22-698	Compensating condenser	F	.30	
22-699	Compensating condenser	P	.50	
22-700	8 mfd. 450 volt electrolytic (B)	B-F	.50	
22-701	8 mfd. 350 volt electrolytic	F	.50	
22-703	Compensating condenser	E-H	.50	
22-704	Three gang variable	A-B	5.00	
22-705	Compensating condenser	I-J	.50	
22-708	Dual fixed padder	A-B-K-L-N-O-		
		R	.65	
22-710	15 mfd. 450 volt x 10 mfd. 250 v.	R	1.00	
22-711	10 mfd. 450 volt x 5 mfd. 450 v.	R	1.00	
*22-712	10 x 10 x 10 mfd. 25 volt (A)	A-B	.75	
22-714	12 x 20 mfd. 450 volt electrolytic	A	1.75	
22-717	Two gang variable	K-L-N	3.00	
22-718	12 mfd. 450 volt electrolytic	K-N	.55	
22-719	16 mfd. 350 volt electrolytic	K-N	.50	
22-727	10 x 10 mfd. 450 volt electrolytic	B	1.25	
*22-728	4 mfd. 350 volt x 40 mfd. 450 v.			
	electrolytic (A-B)	A-B	.75	
22-729	Compensating condenser	D	.50	
22-731	2-35 mfd. Three sec. trimmer.	A-K-N	.40	
22-738	Compensating condenser	R	.55	
22-739	10 x 15 x 15 mfd. 250 v. electrol.	C-D	1.00	
22-740	Compensating condenser	K-L-M-N	.55	
22-741	8 mfd. 250 volt electrolytic	L-O	.45	
22-742	10x15x15 mfd. 250 v. electrol.	L-M-O	1.00	
22-743	Compensating condenser	A-B	.50	
22-744	Two gang variable	M	2.50	
22-746	Three gang variable	O-R	3.00	
*22-747	16 mfd. 450 v. x 40 mfd. 200 v.			
	electrolytic (C)	B	1.00	
*22-748	20x20x40 mfd. 25 volt (B-F)	A-B	.85	
22-749	Two gang variable (export)	K	3.00	
22-750	Three gang variable	R-R2	3.00	
22-751	Two gang variable (export)	F	2.00	
22-753	2-35 mmfd. Three section trim.	R2	.40	
22-754	2-35 mmfd. Two section trim.	F	.30	
22-755	Compensating condenser		.50	
RESISTORS & VOLUME CONTROLS				
63-150	10 M ohm	1/2 watt	L	\$.08
63-151	5 M ohm	1 watt	F-M	.10
63-160	100 M ohm	1/2 watt	C-D-L-M-O	.08
63-208	12 M ohm	1 watt	E	.10
63-260	100M ohm	1/4 watt	E-F	.07
63-270	7 megohm	1/4 watt	L	.07
63-271	1 megohm	1/4 watt	A-B-C-D-G-H-	
			I-J-K-M-N-O-	
			P-R	.07
63-282	2200 ohm	1/4 watt	A-B	.07
63-296	220 M ohm	1/4 watt	C-D-E-F-G-H-	
			I-J-K-L-M-	
			N-O-P-R	.07
63-325	150 M ohm	1/4 watt	J	.07
63-439	2700 ohm	1/4 watt	A-B	.07
63-461	47 M ohm	1 watt	N	.10
63-520	400M ohm volume control & switch		I	1.35
63-521	50 M ohm tone cntrl. assem.		I	.90
63-533	13 ohm (wire wound)		L-M	.08
63-557	60 ohm	1/2 watt	G-H	.08
63-563	80 ohm	1/4 watt	E-F	.07
63-568	2 megohm volume control		P	.90
63-570	Candohm resistor		P	.75
63-577	100 M ohm	1/4 watt	B-C-D-L	.07
63-581	470 ohm	1/4 watt	A-B-P-R	.07
63-582	680 ohm	1/4 watt	O	.07
63-585	2200 ohm	1/4 watt	A-B-O-R	.07
63-586	3300 ohm	1/4 watt	P	.07
63-587	4700 ohm	1/4 watt	C-I-J-L-M	.07
63-589	10 M ohm	1/4 watt	L	.07

A—Used in First Run Sets
A-B—Used in Second Run Sets
C—Used in Third Run Sets

63-591	22 M ohm	1/4 watt	A-B-N-O-R	.07
63-592	30 M ohm	1/4 watt	K-L-N-O-R	.07
63-593	47 M ohm	1/4 watt	A-B-C-D-E-	
			F-G-H-I-J-	
			K-L-M-P-R	.07
63-595	100 M ohm	1/4 watt	B-G-H-K-L-	
			N-P	.07
63-597	470 M ohm	1/4 watt	A-B-C-D-E-	
			F-H-I	.07
63-605	1000 ohm	1/2 watt	A-B-C-D-I-J-	
			K-L-M-N-O-	
			P-R	.08
63-608	15 M ohm	1 watt	A-B-P-R	.10
63-609	22 M ohm	1/2 watt	P	.08
63-610	22 M ohm	1 watt	K	.10
63-613	Three section candohm resistor		I-J	.30
63-618	22 ohm	1/4 watt	B	.07
63-621	39 ohm	1/4 watt	K-L-N	.07
63-627	180 ohm	1/4 watt	O	.07
63-628	270 ohm	1/4 watt	M	.07
63-629	330 ohm	1/4 watt	C-D-L	.07
63-632	560 ohm	1/4 watt	L	.07
63-633	680 ohm	1/4 watt	G-H-M	.07
63-634	820 ohm	1/4 watt	C-D-L-M-O	.07
63-643	18 M ohm	1/4 watt	G-H-L-N	.07
63-645	27 M ohm	1/4 watt	A-B-P-R	.07
63-649	56 M ohm	1/4 watt	A-B-O	.07
63-653	150 M ohm	1/4 watt	A	.07
63-654	180 M ohm	1/4 watt	P	.07
63-655	220 M ohm	1/4 watt	B-N-O-R	.07
63-657	330 M ohm	1/4 watt	A-B	\$.07
63-658	390 M ohm	1/4 watt	E-F-J-L-P	.07
63-660	560,000 ohm	1/4 watt	B	.07
63-671	1 megohm	1/4 watt	F	.07
63-675	5600 ohm	1/2 watt	L-O	.08
63-676	27 M ohm	1 watt	R	.10
63-677	33 M ohm	1 watt	I-J-K	.10
63-680	10 M ohm	1 watt	A-B-I-J-K-N-	
			P-R	.10
63-681	56 M ohm	1/2 watt	G-H-M	.08
63-686	150 ohm	1/2 watt	E-F	.08
63-796	10 M ohm	1/2 watt	L-O	.07
63-799	2 megohm volume contrl. & switch		J	1.35
63-885	82 M ohm	1/2 watt	L-O	.08
63-953	400 M ohm volume contrl. & switch		G	.85
63-954	50 ohm	1/2 watt	G-H	.08
63-955	400 M ohm v. contrl. & switch		C-D-E-H	.85
63-956	400 M ohm v. contrl. & switch		F	.85
63-958	22 M ohm	1 watt	F	.10
63-960	68 M ohm	1/2 watt	C-D	.08
63-962	4700 ohm	1 watt	L-M-O	.10
63-978	Volume control		R	.65
63-979	Candohm resistor		R	.35
63-980	Volume control assembly		A-B	1.25
63-981	Candohm resistor		A	.75
63-982	Tone control		K-L	.90
63-983	Volume control & switch			
	220 M ohm		K-L	1.35
63-984	Three section candohm resistor		K-N	.35
63-985	Volume contrl. & switch assem.		N	1.35
63-986	Four section candohm resistor		B	.75
63-988	15 M ohm	3 watt	R	.35
63-990	Volume contrl. & switch assem.		O	.85
63-991	Volume contrl. & switch assem.		M	1.00
63-992	Candohm resistor		R	.30
AUTOMATIC PARTS				
12-570	Latch bar retaining bracket		D-E-F-H-I-	
			J-K-L-M	\$.02
12-603	Mounting bracket		K	.20
22-519	Padder condenser		A-B-I-J-K-	
			M-N-O-P-R	.35
24-158	Metal cover for automatic coil		I	.25
24-159	Coil cover		J-P	.30
24-161	Automatic adjusting cover		J-P	.03
24-164	Adjustment screw cover		A-B-O-R	.03
24-167	Inductance coil cover		K	.20
46-246	Push button knob		I-J-K-L-M-P	.03
46-250	Automatic knob		D-E-F-H	.03
46-255	Automatic AC switch button		A-B-N-O-R	.03
46-262	Automatic push button		D	.03
80-161	Latch bar spring		D-E-F-H-I-J-	
			K-L-M-P	.25C

E—Used in First Run Sets
E-G—Used in Second Run Sets
F—Used in Third Run Sets

PARTS LIST—(Continued)

-176	Push lever spring	D-E-F-H-I-J-		46-220	Tuning control knob	I	.15
-557	Latch bar strip	K-L-M-P	.40C	46-221	Band selector switch knob	I-M-O	.20
-561	Latch bar strip	J-P	.04	46-222	Volume control knob	I	.15
-584	Latch bar strip	D-E-F-H	.01	46-223	Band sel. & auto. switch knob	J-P	.15
-596	Latch bar	K-L-M	.04	46-224	Volume control knob	J-P	.15
-600	Pin-jack terminal strip	A-B-O-R	.15	46-229	Tuning control knob	P	.20
-603	Pin-jack terminal strip	K-N	.10	46-230	Motor switch control knob	P	.15
-149	Automatic selec. switch assem.	A-B-R	2.00	46-231	Tone control knob	I	.15
-152	Station selector switch	N	1.50	46-233	Tone control knob	J-P	.20
-159	Automatic selec. switch assem.	O	2.00	46-239	Motor control switch knob	B	.05
-216	Latch bar spring steel washer	D-E-F-H-		46-244	Tuning control knob	G	.15
		L-M	.15C	46-245	Tuning knob	C-D-E-F-G-	
-364	Felt washer for push button	P	.20C			H-K-L-M	.10
-370	Felt washer for push button	D-H	.20C	46-251	Manual tun. & vol. control knob	E-H	.15
-385	Felt washer for push button	A-B-N-O-R	.15C	46-252	Tuning control knob	N	.15
2-41	Call letter sheet	D-E-F-H-I-		46-253	Volume control knob	N	.10
		K-L-M	.25	46-254	Radiorgan knob	A-B-N-O-R	.02
2-42	Call letter sheet	J-P	.25	46-255	AC switch knob	B-O	.03
2-45	Call letter sheet	A-B-N-O-R	.25	46-257	Band switch knob	K-L-M	.10
2-56	#6 1/4" H.H. slotted P.K. scr.	J-P	.25C	46-260	Phono switch knob	A-B-N-R2	.10
2-173	Inductance adjusting screw	I	.02	46-261	Tuning knob	C-D	.10
2-179	Inductance adjusting screw	J-P	.03	46-263	Manual tuning knob	A-B-O-R	.15
2-183	Inductance adjusting screw	D-E-F-H-K-		46-264	Vol. Control Knob	B-R	.10
		L-M	.01	49-148	12" Dynamic speaker (9S365)		12.00
2-188	Inductance adjusting screw	A-B-O-R	.03		206-148 output transformer		2.50
2-190	Inductance adjusting screw	N	.03		207-148 field coil		5.00
7-41	Push button lever	I-K-L-M	.03		208-148 cone & voice coil		3.00
7-42	Push button lever	I-P	.02	49-179	8" Dynamic speaker (6S301-7S323-9S324)		\$6.50
7-44	Push lever	D-E-F-H	.25C		206-179 output transformer		2.50
9-25	Adjusting screw cap (plain)	D-E-F-H-			207-179 field coil		2.50
		K-L-M	.03		208-179 cone & voice coil		2.00
9-26	Adjusting screw cap (dial)	D-E-H	.03	49-180	10" Dynamic speaker (9S361)		8.00
5975	Bakelite strip & termal. assem.	I	.15		206-180 output transformer		2.50
5976	Switch contact spring & brkt.	I	.50		207-180 field coil		2.50
6010	Brkt. & contact spring assem.	J-P	1.00		208-180 cone & voice coil		2.50
6012	Bakelite termal strip & contact	J-P	.15	49-185	12" Dynamic speaker (12S370-12S371)		13.50
6093	Fiber & terminal strip assem.	D-E-H	.15		206-185 output transformer		2.50
6094	Metal switch brkt. & contact	D-E-H	.50		207-185 field coil		5.00
6095	Manual automatic switch blade	D-E-H	.07		208-185 cone & voice coil		2.50
6095	Manual automatic switch			49-186	12" Dynamic speaker (15S308-15S372-15S373)		17.50
	contact & terminal strip	D-E-H	.25		206-186 output transformer		3.50
6103	Automatic coil & core (Red)	D-E-F-H-I-J			207-186 field coil		6.00
		K-L-M-N-P	.50		208-186 cone & voice coil		3.25
6104	Automatic coil & core (Green)	D-E-F-H-I-J		49-206	8" Dynamic speaker (6S341)		7.00
		K-L-M-N-P	.50		206-206 output transformer		2.50
6105	Automatic coil & core (Yellow)	D-E-F-H-I-J			207-206 field coil		2.50
		K-L-M-N-P	.50		208-206 cone & voice coil		2.00
6106	Automatic coil & core (Blue)	F-I-J-K-L-		49-208	10" Dynamic speaker (6S362-7S363)		8.00
		M-N-P	.50		206-208 output transformer		2.50
6107	Automatic coil & core (White)	D-E-F-H-I-J			207-208 field coil		2.75
		K-L-M-N-P	.50		208-208 cone & voice coil		2.50
6146	Automatic coil & core (Red)	A-B-O-R	.75	49-216	10" Dynamic speaker (7S363AT)		10.00
6147	Automatic coil & core (Green)	A-B-O-R	.75		206-216 output transformer		2.50
6148	Automatic coil & core (Yellow)	A-B-O-R	.75		207-216 field coil		4.50
6149	Automatic coil & core (Blue)	A-B-O-R	.75		208-216 cone & voice coil		3.00
6150	Automatic coil & core (White)	A-B-O-R	.75	49-219	8" Dynmc. spkr. (9S324AT-6S301AT-7S323AT)		8.00
6163	Switch bracket & contact sprg.	F	.50		206-219 output transformer		2.50
6164	Fiber strip & terminal assem.	F	.15		207-219 field coil		3.00
6173	Switch bracket & contact sprg.	L	.50		208-219 cone & voice coil		2.50
6196	Automatic coil & core (Orange)	A-B-O-R	.75	49-220	12" Dynamic speaker (6S306AT-9S307AT)		13.50
6273	Bakelite strip & lug assem.	K-M	.20		206-220 output transformer		3.50
6274	Fiber strip & terminal assem.	L-M	.15		207-220 field coil		2.50
6287	Frequency coil & core assem.	J-N-P	.50		208-220 cone & voice coil		5.00
MISCELLANEOUS				49-237	5" Dynamic speaker (6D311)		2.75
19	Bakelite cabinet back (312)	E	\$.15		206-237 output transformer		1.00
-371	Walnut cabinet (312)	E-H	2.75		207-237 field coil		1.00
-372	Walnut cabinet (311)	G	2.50		208-237 cone & voice coil		1.00
-383	Cabinet (313)	C	3.50	49-238	5" Dynamic speaker (5R312-5R316-5R317-5R337)		3.00
-384	Cabinet (314)	D	3.50		206-238 output transformer		1.00
	Note: White or Ebony—bakelite Cabinets—2.25 List. Add.				207-238 field coil		1.00
-59	Battery clip (positive)	C-D-L-M-O	.15		208-238 cone & voice coil		1.00
-60	Battery clip (negative)	C-D-L-M-O	.15	49-240	6" Dynamic speaker (5S320-5S338-5S339)		3.50
-15	Antenna strip connector	O-R	.02		206-240 output transformer		1.00
-120	Electrolytic condenser cover	I	.10		207-240 field coil		1.00
-164	Auto. adjust. screw cover	N-O	.03		208-240 cone & voice coil		1.00
-174	AC switch indicator (on)	A-B-R	.05	49-241	6" Dynamic speaker (6D360)		3.50
-175	AC switch indicator (off)	A-B-R	.05		206-241 output transformer		1.00
-176	Tone switch ind. (voice)	A-B-N-O-R	.05		207-241 field coil		1.00
-177	Tone switch ind. (normal)	A-B-N-O-R	.05		208-241 cone & voice coil		1.50
-178	Tone switch ind. (treble)	A-B-N-O-R	.05	49-242	5" Dynamic speaker (5S319)		3.50
-179	Tone switch ind. (lo-bass)	A-B-N-O-R	.05		206-242 output transformer		1.25
-180	Tone switch ind. (bass)	A-B-N-O-R	.05		207-242 field coil		1.25
-181	Tone switch ind. (alto)	A-B-N-O-R	.05				
-7	Phono jack	A-N-R2	.10				
-208	Tuning control knob	J	.25				

PARTS LIST—(Continued)

208-242 cone & voice coil	\$ 1.50	207-273 field coil	\$6.00
49-244 6" Dynamic speaker (5S327)	4.00	208-273 cone & voice coil	4.00
206-244 output transformer	1.25	49-274 12" Dnmc. spkr. (15S308AT-15S372AT-15S373AT)	17.50
207-244 field coil	1.25	206-274 output transformer	3.50
208-244 cone & voice coil	1.50	207-274 field coil	6.00
49-248 6" Dynamic speaker (6S321-6S322-6S340-6S304)	5.50	208-274 cone & voice coil	4.50
206-248 output transformer	1.50	49-275 12" Dynamic spkr. (6S305AT-7S364AT)	10.00
207-248 field coil	1.50	206-275 output transformer	2.50
208-248 cone & voice coil	2.50	207-275 field coil	4.00
49-249 12" Dynamic speaker (7S366-9S367-9S369)	13.25	208-275 cone & voice coil	3.50
206-249 output transformer	2.50	49-280 6" P.M. speaker (6B321AT)	5.00
207-249 field coil	2.50	206-280 output transformer	1.50
208-249 cone & voice coil	3.25	208-280 cone & voice coil	2.00
49-251 10" Dynamic speaker (7S342-7S343-9S344)	8.00	49-281 6" P.M. speaker (6B321)	4.00
206-251 output transformer	2.50	206-281 output transformer	1.25
207-251 field coil	2.50	208-281 cone & voice coil	1.50
208-251 cone & voice coil	3.00	49-282 6" Dynamic speaker (4B355)	4.00
49-253 12" Dynamic Speaker (12S345)	10.00	206-282 output transformer	1.25
206-253 output transformer	2.50	207-282 field coil	1.25
207-253 field coil	4.00	208-282 cone & voice coil	1.50
208-253 cone & voice coil assem.	3.50		
49-254 12" Dynamic speaker (15S346)	15.00	Note: Speakers used in Models with A.T. affixed — for export only.	
206-254 output transformer	3.50	52-144 Speaker cable & plug	G .30
207-254 field coil	6.00	52-146 Shielded lead	A .15
208-254 cone & voice coil	3.25	52-147 Shielded lead	A .15
49-255 12" Dynamic speaker (6S306-9S307)	10.00	52-149 Speaker cable & plug	C .40
206-255 output transformer	2.50	54-117 Mtg. nut for dial crystal	G-H .50
207-255 field coil	2.50	56-654 Escutcheon plate (316-317-337)	H .75
208-255 cone & voice coil	3.25	57-645 Escutcheon plate	I 1.50
49-257 6" Dynamic speaker (6S340AT-6S304AT-6S322AT-6S321AT)	5.50	57-647 Escutcheon plte. (less glss & gasket)	J-P 1.75
206-257 output transformer	1.50	57-651 Escutcheon plate (311-336)	G .35
207-257 field coil	2.00	57-652 Escutcheon plte (less glss & gasket)	K-L 1.75
208-257 cone & voice coil	1.50	57-653 Escutcheon plte. (less glss. & gasket)	F .75
49-258 10" Dynamic speaker (9S344AT-7S343AT-7S342AT)	8.50	57-654 Escutcheon plate (317)	D-E .75
206-258 output transformer	2.50	57-655 Escutcheon plate (326-360)	G .35
207-258 field coil	3.00	57-657 Escutcheon plate (less glass & gasket)	A-B-R 2.00
208-258 cone & voice coil	2.50	57-660 Escutcheon plate (less glass & gasket)	N-O 2.00
49-259 12" Dynamic speaker (7S366AT-9S367AT-9S369AT)	10.00	57-661 Escutcheon plate (motor switch)	B .30
206-259 output transformer	2.50	57-666 Escutcheon plate	M 1.75
207-259 field coil	4.00	62-9 Lamp plug receptacle	L-M-O .10
208-259 cone & voice coil	3.50	73-8 3/32x5/16 H.H. set screw	J .02
49-262 5" Dynamic speaker (4B313)	3.00	73-21 8/32x3/16 H.H. set screw	J .01
206-262 output transformer	1.00	73-24 8/32x1/4" H.H. set screw	J .02
207-262 field coil	1.00	78-115 Vibrator socket	M-O .10
208-262 cone & voice coil	1.00	78-128 Speaker plug socket	A-B-F-J-I-K-L-N-P-R .10
49-263 6" Dynamic speaker (5S320AT-5S338AT-5S339AT)	4.00	78-133 6H6 tube socket	I-J-P .10
206-263 output transformer	1.50	78-141 Vibrator socket	C-D-L .10
207-263 field coil	1.00	78-145 6F5 tube socket	I-J-K-N-P-R .10
208-263 cone & voice coil	1.50	78-148 6Q7 tube socket	E-F-G-H .10
49-264 5" Dynamic speaker (5S319AT)	4.00	78-149 6X5 tube socket	E-F-K-N .10
206-264 output transformer	1.50	78-150 6K7 tube socket	A-B-E-F-G-H-I-J-K-N-P-R .10
207-264 field coil	1.00		
208-264 cone & voice coil	1.50	78-151 6A8 tube socket	E-F-G-H-I-J-K-N .10
49-265 6" Dynamic speaker (5S327AT)	4.00	78-152 6F6 tube socket	K-N .10
206-265 output transformer	1.50	78-159 25Z6 tube socket	I-J-K-N-P-R .10
207-265 field coil	1.00	78-161 Ballast tube socket	G-H .10
208-265 cone & voice coil	1.50	78-162 6L7 tube socket	G-H .10
49-266 12" Dynamic speaker (6S305-7S364)	8.50	78-171 Voltage indicator socket	A-B-P-R .10
206-266 output transformer	3.00	78-173 25L6 tube socket	A2-B2-J-N-R2 .10
207-266 field coil	3.25	78-175 6J5 tube socket	G-H .10
208-266 cone & voice coil	2.00	78-176 6V6 tube socket	A-B-K-N-P-R .10
49-267 8" P.M. speaker (7J328)	6.00	78-182 5Y4 tube socket	A-B .10
206-267 output transformer	2.00	78-183 Resonance ind. sock. & cable	A-B-I-J-P-R .10
208-267 cone & voice coil	2.00	78-184 6T7 tube socket	P .75
49-269 10" P.M. speaker (7J368-6J357)	8.50	78-185 6S7 tube socket	L-M-O .10
206-269 output transformer	2.50	78	F-K-L-M-N-O-R2 .10
208-269 cone & voice coil	3.50	78-186 6D8 tube socket	L-M-O .10
49-270 6" P.M. speaker (6J322)	5.00	78-190 Speaker plug socket	M-O .10
206-270 output transformer	1.50	78-191 6ZY5 tube socket	M-O .10
208-270 cone & voice coil	2.00	78-224 6K6 tube socket	E-F .10
49-271 12" Dynamic speaker (12S345AT)	12.00	78-227 Resonance ind. sock. & cable	A-B .75
206-271 output transformer	2.50	78-228 6F8 tube socket	A-B .10
207-271 field coil	4.00	78-229 Electrolytic condenser socket	L-M-O .02
208-271 cone & voice coil	3.25	78-230 Resonance ind. sock. & cable	N .50
49-272 12" Dynamic spkr. (12S370AT-12S371AT)	15.00	78-232 6A8-6D8 tube socket	C-D .10
206-272 output transformer	3.00		
207-272 field coil	6.00		
208-272 cone & voice coil	4.00		
49-273 12" Dynamic speaker (15S346AT)	15.00		
206-273 output transformer	3.00		

PARTS LIST—(Continued)

1-233	6K7-6S7 tube socket	C-D	\$.10
1-234	6Q7-6T7 tube socket	C-D	.10
1-235	6G6 tube socket	C-D-L-M	.10
1-178	Knob spring		.01
1-433	Antenna ground term. strip	A-B-I-J-K-N-P-R	.10
1-585	Line cord tension strip	K	.05
1-613	Power pack shipping strip	L	.02
1-614	Power pack shipping strip	C	.02
1-35	Phono switch (5649A only)	J	.85
1-103	Band selector switch	P	1.25
1-108	Tone control switch	J-P	.65
1-111	Phono switch	R2	.65
1-116	Motor switch	P	1.00
1-139	Band sel. & manual auto. switch	I	.85
1-140	Band sel. & manual auto. switch	J	.85
1-141	Manual auto. on & off switch	P	.85
1-145	Tone control switch	F-M	.30
1-146	Band selector switch	F	1.00
1-147	Band selector switch	A-B-O-R	1.50
1-148	AC switch (S-6387)	A-B-R	.60
1-150	Band selector switch	K	1.00
1-151	Band selector switch	N	1.00
1-152	Phono switch	B	2.00
1-153	Band switch	L	1.00
1-155	110 volt to 6 volt switch	M-O	.65
1-157	Battery conservator switch	L-M-O	.25
1-158	Phono switch	A-N	.15
1-160	Band change switch	M	1.00
1-267	#14 battery wire (red)	C-D-L-M	.05 ft.
1-268	#14 battery wire (black)	C-D-L-M	.05 ft.
1-168	Chassis mtg. washer (rubber)	A-B	.01
1-215	Chassis floating washer (rubber)	A-B-R	.05
1-229	1/16 x 1/4 brown felt washer	J-P	.30C
1-320	1/16 x 1/4 "x1" brown felt washer	I-J-P	.20C
1-343	3/32 x 33/64 x 7/8 brown felt washer	P	.40C
1-344	Rubber washer (chassis mtg.)	I-J-P	.01
1-364	Small b. felt wash. for auto. but.	I-J	.20C
1-392	Felt washer	B-N	.75C
1-415	117 volt 50-60 cycle pwr. transf.	I	3.75
1-418	117 volt 50-60 cycle pwr. transf.	P	4.25
1-438	117 volt 50-60 cycle pwr. transf.	J	3.75
1-442	Power choke	B	2.25
1-450	Power transf. (25 cycle all v.)	I	7.00
1-451	Power transf. (25 cycle all v.)	P	7.00
1-454	Power transf. (25 cycle all v.)	J	7.00
1-521	Pwr. transf. (50-60 cycle 117 v.)	E-F	2.25
1-523	Pwr. transf. (25 cycle 120-240 v.)	E-F	4.50
1-525	Pwr. transf. (50-60 cycle 117 v.)	R	3.75
1-526	Pwr. transf. (50-60 cycle 117 v.)	K-N	3.00
1-528	Pwr. transf. (50-60 cycle 117 v.)	A	5.50
1-533	Pwr. transf. (50-60 cycle 117 v.)	B	7.00
1-535	Pwr. transf. (25 cycle all v.)	K-N	6.00
1-545	Pwr. transf. (25 cycle all v.)	R2	7.00
1-549	Pwr. transf. (25 cycle all v.)	A2	11.75
1-550	Pwr. transf. (25 cycle all v.)	B2	3.25
1-552	Power transformer	C-D-L	1.50
1-555	Power transformer	M-O	2.50
10-70	Ballast tube (115 volt)	G-H	.75
	11-29-150 v. ext. resistor cord		1.25
	11-30-175 v. ext. resistor cord		1.25
	11-31-220 v. ext. resistor cord		1.25
	11-32-250 v. ext. resistor cord		1.25
2-25	Chassis mtg. screw (346)	B	.03
2-187	#10-32 x 1 1/4" mtg. screw (337)	H	.01
2-189	10/32 x 1-3/8" mtg. scr. (326-336)	G	.01
4-40	Chassis mtg. bolt (355)	C-G-K-L	.40C
4-41	Chassis mtg. bolt	J-P	.02
4-42	Chassis mtg. bolt	M	.25C
4-43	10/32 x 3/8" mtg. screw (311)	G-H	.40C
4-75	#10-32 x 5/8 mach. screw	D-H	.45C
4-80	Chassis mtg. bolt	A-B-O	.03
4-85	Chassis mtg. bolt (313)	C-D	.005
7-38	Band selector lever	O-P	.10
7-46	AC switch lever arm	A	.01
7-48	Band switch lever	A	.20
8-16	Lever connecting link	A	.01
5-19	Rubber grommet for 311	G-H	.75C
6-239	Tube shield	A-B-E-F-H-J-K-L-M-N-O-P-R	.10
6-243	Grid lead shield	I	.05
6-245	Electrolytic cond. shield	B	.10

126-254	Grid lead shield	P	\$.03
126-256	Tube shield	C-D-F-K-L-M-N-O-R2	.10
139-48	Speaker baffle	C-E	.02
159-17	Snap button	I	.05
188-2	Shaft retaining ring	I-J-P	.01
190-6	Vibrator	C-D-L	3.50
190-11	Vibrator	M	2.75
202-79	Instruction book	G	.10
202-84	Instruction book	H	.10
202-87	Instruction book	P	.10
202-89	Instruction book	R	.10
202-92	Instruction book	B	.10
202-93	Instruction book	N	.10
202-94	Instruction book	K	.10
202-98	Instruction book	C	.10
202-99	Instruction book	D	.10
202-100	Instruction book	L	.10
202-101	Instruction book	M	.10
202-102	Instruction book	O	.10
9268-360	#14 battery cable (black)	C-D	.05 ft.
9268-376	#14 battery cable (black)	L	.05 ft.
S-2778	Choke (A battery)	M-O	.25
S-5043	Choke (A battery)	C-D-L-M-O	.25
S-5129	Antenna ground & connector	L	.12
S-5346	Voltage ind. lead & eyelet	A2-B2	.06
S-5356	Voltage ind. lead & eyelet	R2	.06
S-6224	Radiorgan switch & knob		
	assem.	A-B-N-O-R	1.00

PHONO MODELS CABINET ASSEMBLY PARTS

Model	Code	Model	Code
5R303	A	6S305	E
6D302	B	6S306	F
6S301	C	9S307	G
6S304	D	15S308	H
22-82	.001 mfd. 600 volt condenser	C-D	\$.15
22-190	.1 mfd. 200 volt condenser	B	.15
22-492	.002 mfd. 600 volt condenser	H	.18
24-142	Needle cup cover	C-D-E	.25
29-1	Turntable (8 inch)	A-B	1.00
29-2	Turntable (8 inch)	D	1.00
29-4	Turntable (10 inch)	C-D-E	1.50
41-1	Needle cup	C-D-E	.10
44-15	Phono jack	F-G-H	.10
46-265	Knob (phono radio)	A-B-D-F-G-	.10
		H	.35
57-488	Escutcheon plate (phono)	A-B-D	.10
57-668	Escutcheon plate (phono)	F-G-H	.10
57-669	Escutcheon plate (phono)	H	.10
58-39	Five prong cinch plug	B	.07
63-271	1 megohm 1/4 watt resistor	F-G	.07
63-296	220 M ohm 1/4 watt resistor	F-G	.07
63-595	100 M ohm 1/4 watt resistor	C-D-H	.07
63-597	470 M ohm 1/4 watt resistor	H	.07
63-649	56 M ohm 1/4 watt resistor	F-G-H	.10
78-236	Two contact socket		
80-148	Spring-suspension for phono motor	C-D-E	.02
83-619	Pin-jack terminal strip	A-B-C-D-F-	.10
		G	1.00
85-124	Switch (D.P.D.T. toggle)	C	2.00
85-161	Switch (automatic stop)	C-D	.55
85-162	Switch (phono radio)	F-G	1.00
85-164	Switch (phono radio)	A	1.00
85-165	Switch (phono radio)	H	.65
*141-68	Motor—110 volt 60 cycle (less turntable & pick-up assem.)	D	10.00
141-69	Motor — 110 volt 60 cycle (less turntable & pick-up assem.)	A-B-C-D-	10.00
142-6	Pick-up & arm assem. (compl.)	E	6.50
142-7	Pick-up & arm assem. (compl.)	C-D-E	6.50
142-9	Pick-up & arm assem. (cartridge only)	A-B	4.50
142-11	Pick-up & arm assem. (cartridge only)	F-G-H	4.50
152-117	Wood shipping block	C-D-E	.05
152-124	Wood shipping block	F-G-H	.03
169-31	Automatic record changer (complete)	E-F-G-H	85.00
202-103	Instruction book	C-E-F	.10
202-104	Instruction book (record changer)	F-G-H	.10

*MODEL 6D301 ONLY.



INSTRUCTIONS FOR INSTALLATION, OPERATION AND SERVICE AUTOMATIC RECORD CHANGER 169-31

used in
Models 6-S-306; 9-S-307; 15-S-308

This Record Changer will automatically play a series of eight 10- or seven 12-inch records of the 78 revolutions-per-minute type or, if you so desire, you may change records, of any size up to 12 inches, manually. Records of the last few years with the standard eccentric or spiral stopping groove

will operate the automatic mechanism and change your records for you.

INSTALLATION

The Automatic Record Changer as supplied consists of two units.

1. The **Motorboard Unit** which includes the automatic record changer mechanism, the turntable, and the pickup.

2. The **Motor Unit** which includes the support plate assembly.

The units are supplied ready for mounting on a cabinet rail. This rail must be drilled in accordance with the information and dimensions shown on page 4. Wooden support blocks as shown, must be provided by the customer. All other necessary parts are included in your purchase. It is essential for proper operation that the rail and support blocks provide for the mounting of the motor support plate exactly $2\frac{3}{4}$ inches below the top surface of the motorboard. The support blocks should be attached to the rail with heavy wood screws. Details of this mounting, with all necessary dimensions, are given on page 4.

1. Install the Motor Unit with support plate loosely in position as shown on page 4. Do not tighten the mounting screws.
2. Loosen the two set screws in the collar of the flexible coupling on the Motorboard Unit, a detail of which is shown on page 3.
3. Place the Motorboard Unit in position on the cabinet rail with the upper mounting springs in place as shown on page 4. Make sure that the guide pins extending from the motor support plate enter the rubber grommets in the Motorboard Unit without binding.
4. Secure Motorboard in position using the screws and lower mounting springs as shown on page 4. Tighten up the four motorboard mounting screws to compress all eight mounting springs to the dimensions shown. *Make sure that the Motorboard Assembly is level in the cabinet.*
5. Tighten up the mounting screws on the Motor Unit support plate assembly so that they are firmly down against the spacers.
6. Check the installation to be sure that there is no binding between the collar of the flexible coupling and the collar of the motor spindle. See page 3.

7. Tighten the two set screws of the flexible coupling down on the spindle of the Motor Unit.

Needle Box

The needle box is in a separate package. Place the box in the hole in the motorboard with the needle ejector tab toward the front. To do this tilt the box upwards at front and lower into hole with the lug on back of box in the slot in the motorboard. Slide the lug under the motorboard and the box drops in place.

Speed Regulation and Lubrication

There are three holes in the top of the turntable which give access to oil holes and a speed regulating screw in the motor mechanism beneath. Revolve the turntable slowly until you can see the holes and screw through the turntable. A few drops of good quality light machine oil should be applied in the oil holes at regular intervals, about once every six months.

Speed Regulation.—After the phonograph is in operation the speed should be checked while playing a record.

1. Place a piece of white paper under edge of record so that it is plainly visible.

2. Count the number of revolutions per minute with the aid of a watch.

3. If not 78, stop the turntable, lift off the record and set the turntable to give access to the speed regulator screw through one of the holes.

4. Insert a screwdriver through the hole in the turntable into the groove in the speed regulator screw and turn to right (clockwise) to decrease speed, or to the left (counterclockwise) to increase speed.

5. Replace and replay record, recount and adjust until speed is checked at 78 r. p. m.

Shipping

Shipping blocks as shown on page 4 should be used in all cases of reshipment.

OPERATION

Before operating the phonograph, either automatically or manually, be sure that the pickup is down and can be moved by hand. If not, a "cycle" must be completed to bring it down. To do this, throw Turntable Switch "on." The turntable will start to revolve and the cycle of motion on the pickup arm will be resumed. When the pickup arm comes down, turn off the Turntable Switch.

Cautions

1. Never use force to start or stop the motor or any part of the record-changing mechanism or pickup arm.

2. The use of records which have become warped or damaged through improper care may cause the mechanism to jam and damage the instrument. In addition, records which have become warped will slide on one another when playing, resulting in unsatisfactory reproduction.

3. This instrument is not recommended for playing 10-inch and 12-inch records in mixed sequence. If the user desires this service he must be positive that all records are perfectly flat and free from warp. The Index and Record Reject Lever must be set at "10" and after playing the last selection the pickup will come down in position for a 10-inch record and repeat the playing of the record on a 10-inch diameter unless the Turntable Switch is turned off. Any jamming of the mechanism under these conditions indicates that the records used are not perfectly flat or that their edges are not sufficiently smooth to permit normal operation of the separators in dropping each record in sequence onto the turntable.

4. Do not leave records on the record holder posts, as they are liable to warp, particularly so in warmer climates. Keep your records in a record file (album or cabinet) when not in use. If any records should become warped, place them on a flat surface with a flat heavy article, such as a large book, on top and leave them in this position for a few days.

Controls and Moving Mechanism

Index and Record Reject Lever.—This lever is located near the right front corner of the motorboard with its index plate marked for four positions—"MANUAL," "12," "10," and "REJECT." When you desire to change record selections manually, this lever should be set in the "MANUAL" position. With the lever in the "12" position, the mechanism is set to play a series of 12-inch records automatically. To play either a series of 10-inch records, or 10- and 12-inch records mixed, the lever should be set at the "10" position.

To reject a record being played, or to start the record-changing cycle in case the record just played does not have the standard eccentric or spiral stopping groove, simply push the lever to the "REJECT" position and let go. The pickup will raise up and swing outwards and the next record will drop down. Upon releasing the lever, it will automatically return to the "10" position. If you are playing a series of 12-inch records, the lever should be returned to the "12" position after rejecting a record. Keep the lever in its "MANUAL" position when not actually playing records automatically.

(Continued on page 4)

Automatic Record Changer

GENERAL INFORMATION

Before servicing the automatic record changer, inspect the assembly to see that all levers, parts, gears, springs, etc., are in good order and are correctly assembled.

A bind or jam in the mechanism can usually be relieved by rotating the turntable in the reverse direction.

The changer can be conveniently rotated through its change cycle by pushing the index lever to "Reject" and revolving the turntable by hand. Six turntable revolutions are required for one change cycle.

The turntable, spindle, and pinion gear are assembled by means of a 3/32 inch straight pin. This pin may be removed by gently driving with a standard pin punch.

If the record changer or cabinet is not perfectly level, normal operation is likely to be affected.

The 10 and 12 inch records must be absolutely flat for smooth operation when using a mixture of the two sizes.

A shorting switch, located in the pickup head, operates due to pressure when the pickup is placed on the pickup rest.

ADJUSTMENTS

A. Main Lever.—This lever is basically important in that it interlinks the various individual mechanisms which control needle landing, tripping, record separation, etc. One adjustment is provided for the main lever. Rotate the turntable until the changer is out-of-cycle; and adjust rubber bumper bracket (A) so that the roller clears the nose of the cam plate by 1/16 inch.

B. Friction Clutch.—The motion of the tone arm toward the center of the record is transmitted to the trip pawl "22" by the trip lever "7" through a friction clutch "5." If the motion of the pickup is abruptly accelerated or becomes irregular due to swinging in the eccentric groove, the trip finger "7" moves the trip pawl "22" into engagement with the pawl on the main gear, and the change cycle is started. Proper adjustment of the friction clutch "5" occurs when movement of the tone arm causes positive movement of the trip pawl "22" without tendency of the clutch to slip. The friction should be just enough to prevent slippage, and is adjustable by means of screw "B." If adjustment is too tight, the needle will repeat grooves; if too loose, tripping will not occur at the end of the record.

C. Pickup Lift Cable Screw.—During the record change cycle, lever "16" is actuated by the main lever "15" so as to raise the tone arm clear of the record by means of the pickup lift cable. To adjust pickup for proper elevation, stop the changer "in-cycle" at the point where pickup is raised to the maximum height above turntable plate, and has not moved outward; at this point adjust locknuts "C" to obtain 1 inch spacing between needle point and turntable top surface.

D. & E. Needle Landing on Record.—The relation of coupling between the tone arm vertical shaft and lever "20" determines the landing position of the needle on a 10 inch record. Position of eccentric stud "E" governs the landing of the needle on a 12 inch record; this, however, is dependent on the proper 10 inch adjustment.

To adjust for needle landing, place 10 inch record on turntable; push index lever to reject position and return to the 10 inch position; see that pickup locating lever "17" is tilted fully toward turntable; rotate mechanism through cycle until needle is just ready to land on the record; then see that pin "V" on lever "14" is in contact with "Step T" on lever "17." The correct point of landing is 4-11/16 inches from the nearest side of the turntable spindle; loosen the two screws "D" and adjust horizontal position of tone arm to proper dimension, being careful not to disturb levers "14" and "17". Leave approximately 1/32 inch end play between hub of lever "20" and pickup base bearing, and tighten the blunt nose screw "D"; run mechanism through several cycles as a check, then tighten cone pointed screw "D".

After adjusting for needle landing on a 10 inch record, place 12 inch record on turntable; push index lever to reject and return to 12 inch position; rotate mechanism through cycle until needle is just ready to land on the record; the correct point of landing is 5-11/16 inches from nearest side of spindle. If the landing is incorrect, turn stud "E" until the eccentric end adjusts lever "14" to give correct needle landing. The eccentric end of the stud must always be toward the rear of the motor board, otherwise incorrect landing may occur with 10 inch records.

F. & G. Record Separating Knife.—The upper plate (knife) "25" on each of the record posts serves to separate the lower record from the stack and to support the remaining records during the change cycle. It is essential that the spacing between the knife and the rotating record shelf "27" be accurately maintained. The spacing for the 10 inch record is nominally .053 inch, and for the 12 inch record is .075 inch.

To adjust, rotate the knife to the point of minimum

vertical separation from the record shelf and turn screw and locknut "F" to give .052—.058 inch separation. Screw "G" must not be depressed during this adjustment. After setting screw "F" adjust screw "G" so that when its tip is depressed flush with top of record shelf, the vertical spacing between the knife, in its lowest rotational position, and the shelf, is .072—.078 inch.

H. Record Support Shelf.—The record shelf revolves during the change cycle to allow the lower record to drop onto the turntable. Both posts are rotated simultaneously by a gear and rack coupled to the main lever "15," and it is necessary that adjustments be such that the record is released from both shelves at the same instant. To adjust, place a 12 inch record on the turntable, rotate mechanism into cycle to the point where tone arm is at maximum distance outward from turntable; lift record upward until it is in contact with both separating knives, then loosen screws "H" and shift record shelves so that the curved inner edges of the shelves are uniformly spaced at least 1/16 inch from record edge. Tighten the blunt nose screw "H," run mechanism through cycle several times to check action, then tighten cone pointed screw "H".

If record shelves or knives are bent, or not perfectly horizontal, improper operation and jamming of mechanism will occur.

J. Tone Arm Rest Support (not shown).—When the changer is out-of-cycle, the front lower edge of the pickup head should be 5/16 inch above surface of motor board. This may be adjusted by bending the tone arm support bracket, which is associated with the tone arm mounting base, in the required direction.

K. Trip Pawl Stop Pin.—The position of the trip pawl stop pin "K" in relation to the main lever "15" governs the point at which the roller enters the cam. By bending the pin support either toward or away from trip pawl bearing stud, the roller can be made to enter the cam later or earlier, respectively. This adjustment should be made so that the roller definitely clears the cam outer guide as well as the nose of the cam plate.

Lubrication.—Petrolatum or petroleum jelly should be applied to cam, main gear, spindle pinion gear, and gears of record posts.

Light machine oil should be used in the tone arm vertical bearing, record post bearings, and all other bearings of various levers on underside of motor board.


The felt washer between the turntable and spindle bearing should be soaked in light engine oil whenever the turntable is removed, or as required for proper operation.

Do not allow oil or grease to come in contact with, rubber mounting of tone arm base, rubber bumper, or flexible coupling of drive motor.


MISCELLANEOUS SERVICE HINTS

Incorrect adjustment of a particular mechanism of the changer is generally exhibited in a specific mode of improper operation. The following relations between effects on operation and the usual mis-adjustments will enable ready adjustment in most cases.


1. For any irregularity of operation, the adjustment of the main lever "15" should be checked first as in "A".
2. Needle does not land properly on both 10 and 12 inch records—Make complete adjustments "D" and "E".
3. Needle does not land properly on 12 inch record but correct on 10 inch—Effect adjustment "E".
4. Failure to trip at end of record—Increase clutch "5" friction by means of screw "B". Also, see that levers "7" and "12" are free to move without touching each other.
5. Pickup strikes lower record of stack or drags across top record on turntable—Adjust lift cable per adjustment "C".
6. Needle does not track after landing—Friction clutch "5" adjustment "B" may be too tight; bind in tone arm vertical bearing; levers "7" and "12" fouled; or pickup output cable twisted.
7. Cycle commences before record is complete—Record is defective, or adjustment "B" of friction clutch "5" is too tight.
8. Wow in record reproduction—Record is defective; flexible coupling between motor and changer mechanism not correctly assembled; or instrument is not being operated at normal room temperature (65° F).
9. Record knives strike edge of records—Records warped; record edges are rough; or knife adjustments "F" and "G" are incorrect.
10. Record not released properly—Adjust record shelf assemblies in respect to shaft by means of adjustment "H".
11. Needle lands in 10 inch position on 12 inch record or misses record when playing both types mixed—Increase tension of pickup locating lever spring "30".




Bottom View of Automatic Record Changer



Details of Record Shelf Posts, and Locating Lever Assemblies



Motor Data and Coupling



Top View of Automatic Record Changer

NOTE: Numbers refer to parts—letters refer to adjustments.

Turntable Switch.—The toggle switch located just in front of the Index and Record Reject Lever controls the current to the turntable motor. To start the turntable, throw the switch to the "ON" position. To stop the turntable throw the switch to the "OFF" position.

Pickup and Top-Loading Needle Socket.—The pickup is the new crystal type, with a hole in the top for insertion of needles. When not playing records, the pickup arm should be moved out to the right beyond the turntable and placed at rest on the support with the edge of the pickup arm in the groove and the pickup over the needle gauge plate. The pickup must be in this position to change needles.

To insert a needle initially, loosen the needle screw on the front of the pickup, place needle in hole at top so that it drops down against the needle gauge plate and then tighten up the needle screw.

Needle Ejector.—The extending tab on the needle gauge plate of the needle box operates the needle ejector. To change a needle, place pickup in rest position, loosen needle screw and press the extending tab on the needle gauge plate to drop the used needle into the box below. Release tab, allowing the needle gauge plate to swing back, and then insert a new needle in the pickup as described above.

Record Holder Shelves.—To place a record on the turntable or to remove records, raise the record holder shelves, by lifting with the fingers under the shelf, and swing clear of outer edge of record. Also push back vertical lever adjacent to the rear record holder post. You now have clear access to the turntable. Before loading the magazine for Automatic Operation swing the record holder shelves back into position.

Automatic Operation

1. See that pickup is over needle gauge plate with needle properly in place. If not, complete a "cycle," as explained in the first paragraph under "OPERATION."

2. With Index and Record Reject Lever at "MANUAL," place the first of the series of records on the turntable and the remainder of the series (up to seven 10-inch or six 12-

inch records) on the record holder posts (as shown in Figure 1). The records should be arranged in the desired order with the desired selection face up and the last selection on top.

3. Set the Index and Record Reject Lever to the proper position. (See CONTROLS:—INDEX AND RECORD REJECT LEVER.)

4. Throw Turntable Switch to the left—"ON"—turntable should commence to revolve.

5. When turntable has attained speed, lift pickup and lower gently on to the record so that the needle point enters the outside groove.

6. Close the lid of the cabinet to eliminate mechanical reproduction of sound by the needle.

The whole series of records will now play without further attention, and the last record will repeat until the Turntable Switch is turned off. Allow the record-changing mechanism to complete its cycle before the turntable is stopped. Then lift the pickup, swing the arm to the right beyond the edge of the record and lower it onto the pickup rest with pickup over needle gauge plate. The record player is then ready for reloading, or for manual operation.

Manual Operation

To play records manually:

1. Proceed as in step 1, under "AUTOMATIC OPERATION."


2. Place record on turntable with desired selection upwards.

3. Set Index and Record Reject Lever to "MANUAL" position.

4. Proceed as in steps 4, 5 and 6 under "AUTOMATIC OPERATION."

When you have finished playing, be sure that the turntable has stopped and the pickup is in the rest position over needle gauge plate. Never leave pickup with needle resting on a record or on the turntable.

Good reproduction can only be obtained with the turntable revolving at 78 revolutions per minute. For speed check and regulation see INSTALLATION, page 1.



MOUNTING DETAILS FOR

SERVICE MANUAL



AUTOMATIC RECORD CHANGER



ZENITH RADIO CORPORATION

CHICAGO, U. S. A.



AUTOMATIC RECORD CHANGER




FIGURE NO. 1

OPERATING INSTRUCTIONS

The Zenith Record Changer plays seven 12" or eight 10" Records automatically. The last record remains on the turntable and repeats as long as the Record Changer is in operation.

Records may be repeated as often as desired by raising the record removing arm at A Fig. 1 to the upright position.

To reject a record and play the next record below it, pull the latch lever at L Fig. 1 forward.

To adjust the record removing arm to handle 10" records set the record removing arm change lever at D Fig. 1 opposite the number 10 stamped on the base plate. For 12" records set the lever opposite the number 12.

To adjust the pickup to play 10" records, push the pickup stop at K Fig. 1 back. (Away from the pickup needle) . For 12" records pull the stop forward (toward the needle) as far as it will go.

Some units are equipped with two speed motors, and others with 78 RPM motors. When the two speed motor is used change from one speed to the other by simply moving lever at F Fig. 1 to position desired.

To start motor, throw switch (supplied on some models) at N Fig. 1 on the "on" position.

MOTOR LUBRICATION

The motor installed in the Record Changer is governor controlled, with all gearing enclosed, and leaves the factory lubricated for proper operation. For maximum satisfaction, lubricate the motor at regular intervals with SAE No. 10 oil. Please do not use any other grade of oil.

The governor disc engages with a ring of hard felt. This felt is impregnated with a lubricating solution sufficient for proper operation for approximately a year under normal conditions. It may be necessary, however, if the motor shows a tendency to chatter or waiver, to apply a drop or two of oil to this felt ring.

MOTOR SPEED

The motor speed is adjusted by means of a lever at C Fig. 1 which is mounted under the turntable. The direction of swing to fast or slow is indicated by the legends F and S on the base plate.

33-1/3 RPM — 78 RPM SHIFT

(Two-speed motors only)

Move the speed change lever at F Fig. 1 as far as it will go in the direction of swing indicated by the legends 33-1/3 and 78 on the base plate.

If adjustment of the speed change lever is required for any reason, proceed as follows: First loosen the screw which clamps the lever to the motor shaft. This shaft is provided with a screw-driver slot in the end. Next, using a screw driver, turn this shaft in a clockwise direction until you feel it strike the stop. The motor is now in the 33-1/3 RPM position. Now set the lever against the lug provided in the base plate and opposite the legend 33-1/3 and tighten the clamp screw. This places the lever in the correct position on the motor shaft. The final step is the adjustment of the eccentric bushing at G Fig. 1 which limits the throw of the lever. First loosen the screw which holds the eccentric bushing. Next, throw the speed change lever to its farthest 78 RPM position, (using care that the lever does not slip on the motor shaft). Then turn the eccentric bushing around until it touches the side of the lever, and tighten it in place with the screw provided.

TRIP MECHANISM

The trip mechanism is the trigger that sets the Record Changer in motion. This is done by allowing the latch bar at O Fig. 1 to drop in front of, and be actuated by the cam at P Fig. 1. This cam is driven by the motor and is in motion as long as the motor is running. If this mechanism does not operate smoothly, the precautions outlined in succeeding paragraphs should be observed.

First of all, make sure that the square pin in the latch lever at U Fig. 1 latches properly in the notch in the lift lever at I Fig. 1. When latched, the notch should be engaged approximately one-half of its depth. The depth of engagement is adjusted by means of the eccentric washer and locking screw at J Fig. 1. Now run the Record Changer through its cycle. If the square pin fails to engage the notch in the lift lever, first check the tension of the latch spring at H Fig. 1 to insure that the notch can engage the pin. Next check the tension of the reset spring at E Fig. 1. This reset spring should not be under tension when the latch bar is latched but should have enough tension when the latch bar drops back off of the cam to cause the square pin to over travel the notch in the lift lever.

IMPORTANT — Before attempting to change the tension of any spring, be sure that the parts involved work freely without any tendency to bind, as of course any binding condition would preclude proper operation.

The Record Changer is adjusted at the factory to trip on a spiral trip groove record when the phonograph needle is 1 3/4" from the edge of the hole in the center of the record.

When eccentric or oscillating trip groove records are used, tripping is effected by means of the hardened steel pin in the end of tone arm lift crank at S Fig. 2 engaging the serrated block on the trip lever at T Fig. 2. There must be a minimum of $1/32$ " play between the end of the pin and the block, when, with a short needle, ($5/8$ " Minimum Length) the pickup is resting on one record on the turntable. If the pressure of the pin on the block is not sufficient to insure operation, then check the pressure spring which is located up under the pickup.




FIG. NO. 2

ing out of a worn record trip groove. Next make certain that all parts of the mechanism work freely and smoothly. If it is found that the latch bar at O Fig. 1 is not dropping in far enough to engage the cam at P Fig. 1, then check the tension of the trip spring at B Fig. 1.

The oval head pivot screw at R Fig. 1 serves as a pivot for the lift lever at I Fig. 1. This screw should allow the lift lever to be raised by the latch bar to its maximum height without binding but also without any additional play.

If the Record Changer fails to trip, see if the phonograph needle is jump-

RECORD REMOVING MECHANISM

The Record Changer is adjusted so that it will always leave one record on the turntable. This is done to prevent the phonograph needle from damaging the covering on the turntable.

In case the Record Removing Mechanism fails to operate smoothly, proceed as follows: First make certain that all parts work freely with no binding in pivots or bearings, and that the record removing arm assembly rests on the stop screw at Q Fig. 3. Next stop the motor in such a position that the latch bar at O Fig. 1 can swing by and clear the cam at P Fig. 1. Place just one record on the turntable and measure from the top of this record down to the base plate. This distance should be one inch. Now by pulling the reject lever at L Fig. 1 first, it will be found possible to swing the record removing finger at Y Fig. 3 over to where it just touches the edge of the record. If the adjustment is correct, the record removing finger should just barely rise over the edge of the first record. If adjustment is required it can be made by means of the stop screw at Q Fig. 3. In the event the record removing arm raises the record from the turntable and drops it back in place without removing it, check the lift adjustment at V Fig. 1. This adjustment consists of an eccentric stud which is provided with a lock nut, and is made by loosening the lock nut and turning




FIG. NO. 3

the eccentric stud. The lift adjustment should be set so that the hole in the center of the record just clears turntable spindle when the Record Changer is in operation.

PICKUP LOWERING MECHANISM

The pickup lowering mechanism has two functions. First, it lowers the phonograph needle gently to the surface of the record. Second, it feeds the needle toward the center of the record so that it will enter the playing groove.




FIG. NO. 4

If the pickup descends too fast or too slow, adjust the speed of descent by turning the knurled thumb nut on the dashpot sleeve at W Fig. 2.

The unit is adjusted at the factory so that the needle will be set down approximately $3/32$ " in from the edge of the record. An adjusting screw is provided on the side of the pickup at M Fig. 2. If the needle is being lowered onto the playing surface of the record, and the adjusting screw at M Fig. 2 fails to correct the condition proceed as follows: First stop the record changer, with the pickup in the maximum raised position and check the clearance between the underside of the pickup shelf at Z Fig. 2 and the tip of

the dashpot. This clearance should be very small as otherwise the pickup will tend to bounce as it is lowered. There must be sufficient clearance however to prevent the pickup shelf from rubbing on the tip of the dash pot, or the pickup will not swing out far enough to allow the adjustable stop at K Fig. 2 to come to rest against the dashpot. Check this clearance in both 10" and 12" record positions. If adjustment is required, the height of the dashpot may be regulated by loosening the nuts on the bottom of the lift lever stud at X Fig. 4 and changing their position on the stud. To raise the dashpot turn the nuts clockwise, to lower the dashpot turn the nuts counter-clockwise. Be sure to lock the nuts tightly together after the adjustment is made.



SERVICE MANUAL

MODEL
6-M-390



Built for
FORD MOTOR CO.
Dearborn, Mich.

Made by ZENITH RADIO CORPORATION, Chicago, Ill., U.S.A.

ELECTRICAL SPECS: Rotomatic Tuning—Provides a means of selecting either manual or any one of five pre-selected stations using a single push-button. The automatically controlled circuits consist essentially of permeability tuned inductances in the oscillator circuit and mica type trimmers in the detector stage. Switching is accomplished electrically by coincidental solenoid operation of band-switch type segments.

Sensitivity—10 microvolts at 1 watt output. **Tuning range** 540—1580 K.C. **Power output**—3 watts measured at voice coil. **Speaker**—8" dynamic. **I.F.**—455 K.C. **Automatic**—Five positions and "Dial."

Tube complement—78 R.F., 6A7 mixer, 78 I.F., 75 2nd det. and audio, 42 output, 84 rectifier. **Current Consumption**—7 amp. at 6 volts.

NOTE: This receiver is equipped with a fixed-variable sensitivity control located on the chassis base below the tuning control shaft of the variable condenser. (See Fig. 5.) The control can be adjusted with a screw driver either from above or below the chassis, and is set at the factory to a position which gives a sensitivity of 10 microvolts at 1 watt output. In practice it is found advisable to hold the receiver to this level as any higher sensitivity might result in increased motor noise or excessive background noise. Unless laboratory equipment capable of accurately measuring the input and output of the receiver is available, it is not advisable to alter this setting.

MANUAL DIAL ADJUSTMENT: The manual control dial must be aligned with the receiver for correct calibration. To do this, turn the manual tuning knob in one direction as far as it will go. Now do the same in the opposite direction. Then tune in a station of known frequency, and note if the dial reading corresponds. If the frequency reading is not correct, hold the tuning knob firmly and move the dial drum with your fingers through the bezel to the correct frequency reading of the station being received.

automatic dial to the receiver which is done as follows: Turn on the receiver, and try to tune in a station with the manual tuning control. If no station





FIG. 2

can be picked up, push the automatic station selector button until a position is found where stations can be tuned in manually. Remove the automatic dial assembly by pulling out from the rear and turn the station indicator drum downward until the word "Dial" appears in the opening. The adjusting screws in the receiver can now be resonated for the stations shown around the automatic dial as the automatic button is operated. It is very important that these adjusting screws be set on a weak signal from the station so that the circuit may be sharply tuned. A very short piece of wire used as an antenna will hold down the signal strength. Always be sure the antenna characteristics are similar to actual car conditions. A 38 mmfd. condenser from antenna to ground will provide the necessary input capacity.


AUTOMATIC TUNING ADJUSTMENTS: 1. Turn the receiver on and allow it to operate until thoroughly heated. Loosen the screws holding the cover plate over the automatic adjustments, and slide it upward exposing the adjusting screws and recording strip. This plate is on the front of the receiver. (See Fig. 4.) 2. Push the automatic station selector button until the word "Dial" is at the automatic dial window. Tune in manually the station whose call letters are in the No. 1 position on the dial (the lowest frequency station—see Fig. 3) and note the program so that it can be identified. Push the automatic station selector button once, and this station's call letters will appear at the automatic window.

3. With a small screw driver, turn the station setting screw A (see Fig. 4) in the upper row to the right or left until that station is tuned in accurately.



AUTOMATIC DIAL SYNCHRONIZATION: Before setting the station adjusting screws for automatic tuning, it may be necessary to synchronize the

Now adjust the corresponding screw A1 in the lower row until maximum volume is obtained. Make these adjustments very carefully as it is quite easy to pass the resonant point due to the unusual selectivity of the receiver.



4. Press the automatic station selector button until "Dial" again is at the automatic window and tune in manually the station whose call letters are in the No. 2 position (the next higher frequency) on the automatic dial. Press the automatic station selector button twice to bring the No. 2 station's call letters in view, and adjust B and B1 screws to this station. Repeat this procedure until each of the five pairs of adjusting screws have been carefully set to their respective stations. It is necessary that the setting of the adjusting screws be repeated in the order given to be sure that they are properly set for maximum performance.




FIG. 4

If the station setup on the automatic tuning dial should appear in the wrong position, the dial can easily be re-synchronized to the receiver as ex-

plained under "Dial Synchronization." If it is necessary to examine the automatic dial mechanism or change call letters it may easily be removed from the speaker housing by pressing the spring catch directly beneath the assembly and pulling out from the rear.

If difficulty is experienced in setting the adjusting screws for the desired station, first turn the antenna trimmer screw down tight, and then adjust the station setting screw (oscillator) to the station, and follow with a readjustment of the antenna trimmer screw for resonance.

ALIGNMENT: I. F. Connect signal generator set at 455 K. C. through .1 mfd. condenser direct to 6A7 grid cap. Adjust I. F. trimmers A, B, C, D, (Fig. 5) to resonance. This should be done with the volume control of the receiver on full, and the generator signal reduced to a weak level.




FIG. 5 TUBE AND TRIMMER LAYOUT

Wave Trap: Remove signal generator lead from 6A7 grid, and attach to 78 R. F. tube grid. Using the same signal frequency of 455 K. C. carefully adjust the wave trap trimmer E for minimum response with a strong generator signal.

R. F. Press the automatic button to where the "Dial" position shows, or until the set can be tuned manually. Now rotate the manual tuning control until the condenser plates are completely out of mesh. Remove the generator lead from the 78 R. F. tube and connect it direct through a Zenith dummy antenna unit (Zenith part No. S6740) to the antenna socket on the receiver. Set the signal generator to 1580 K. C., and adjust the oscillator trimmer F on the gang condenser to resonance. Reset the signal generator to 1400 K. C. turn the dial until the signal is heard and adjust the gang condenser trimmer G to maximum response. Reset the signal generator to 600 K. C., and again turn the manual dial until the signal is heard. Rock the condenser gang slightly while adjusting padder H to maximum response at this point.




FIG. 6 DUMMY ANTENNA REQUIREMENTS.

Figure 6 shows the dummy antenna requirements necessary where the special Zenith dummy connector S6740 is not available.




FIG. 7 MODEL 6-M-390 WIRING DIAGRAM

MADE ESPECIALLY FOR
Sund Motor Company
 DEARBORN, MICH.

MODEL 6-M-390
 MFD. BY
ZENITH RADIO CORPORATION
 CHICAGO, ILLINOIS - U.S.A.

IMPORTANT: Unless certain dummy antenna capacities are employed with either the signal generator or in making adjustments on stations, the receiver will not respond properly. The values provided in the Zenith dummy antenna unit shown in Fig. 6 are identical with the conditions in the Ford car, and if adjusted accordingly the instrument will operate properly when reinstalled in the automobile. The Zenith dummy antenna S6740 is especially priced at 25c net to service stations, and should be purchased for use in servicing Zenith built Ford receivers.

PARTS LIST

Tuning Control Head & Speaker Assembly

S6623	Dial clutch gear assy. (for manual tuning)	\$.25
S6628	Magnet assy. (for automatic dial drum)	1.00
S6653	Magnet plunger & ratchet pawl assy.	.25
22-162	Condenser .0001 mfd. 600 volt	.15
22-185	Condenser .01 mfd. 200 volt	.15
26-216	Dial scale for manual tuning dial drum	.20
34-83	Volume control shaft gear	.02
35-1	Drum—manual tuning indicator	.10
35-2	Drum—automatic station indicator	.10
46-268	Knob—volume control	.15
46-269	Knob—tuning control (manual)	.15
46-270	Knob—automatic push button	.02
49-285	Speaker—8" dynamic	4.00
	208-285—cone & voice coil for 49-285	2.25
52-151	Cable & six prong plug assembly	.80
52-152	Cable—battery (control unit to set)	.15
52-153	Cable—battery (control unit to fuse)	.15
52-154	Cable—battery (fuse to battery)	.15
63-591	Resistor—22M ohm ¼ watt	.07
63-995	Volume control & switch assembly	.90
76-273	Flexible drive shaft assembly	.90
80-188	Spring—retainer for S6623	.005
80-189	Spring—manual dial drum take up	.03
80-191	Spring—return for S6628	.04
83-632	Speaker cloth cover retaining strip	.03
85-169	Switch—automatic station selector	2.25
100-31	Bulb—dial light Mazda #55	.12
100-32	Bulb—dial light Mazda #51	.12
110-67	Speaker grill cloth	.03
110-68	Speaker dust cloth	.15
112-207	Screw—volume control shaft	.005
102-58	Tab—marked dial	.005
136-11	Fuse—14 ampere	.06
188-13	Retaining washer (automatic dial drum)	.01
188-30	Retaining washer (volume control knob)	.01
196-20	Speaker gasket (rubber)	.20

Automatic Coils & Switch Assembly

22-756	Six section trimmer condenser assembly	1.10
22-777	Condenser—1000 mmfd.	.45
85-168	Complete switch & relay assembly	2.15
	80-199—magnet coil plunger spring	.05
	85-174—automatic coil switch segment	.50
	85-175—trimmer condenser switch segment	.50
	93-412—magnet coil plunger spring retainer washer	.05
	149-10—magnet coil plunger	.10
	S6681—magnet coil & bracket	1.00
	S6682—ratchet arm & spring assembly	.75
	S6683—ratchet gear & shaft assembly	.75
S6226	Adjustment screw & bushing assembly	.45
S6635	Manual tuning oscillator coil assembly	.25
S6636	Auto. tuning oscillator coil assy.—red	.15
S6637	Auto. tuning oscillator coil assy.—green	.15
S6638	Auto. tuning oscillator coil assy.—yellow	.15
S6639	Auto. tuning oscillator coil assy.—blue	.15
S6640	Auto. tuning oscillator coil assy.—White	.15
S6663	Fibre terminal strip assembly	.25

Coils & Chokes

20-166	Heater line hash choke (on R. F. base)	.03
20-175	Main hash choke (large on P. P. base)	.15
20-202	Antenna motor noise choke (on R. F. base)	.03
95-563	1st I. F. coil assembly	1.10
95-564	2nd I. F. coil assembly	1.10
S5844	Motor noise choke (small on P. P. base)	.15
S6648	Antenna coil assembly (less shield)	.85
S6650	Untuned R. F. & wave trap assembly	1.75

Condensers

22-82	.001 mfd. 600 volt	.15
22-127	.25 mfd. 600 volt	.15
22-162	.0001 mfd. 600 volt	.15
22-170	.1 mfd. 400 volt	.20
22-182	.00025 mfd. 600 volt	.15
22-185	.01 mfd. 200 volt	.15
22-190	.1 mfd. 200 volt	.15
22-212	.05 mfd. 400 volt	.15
22-229	.005 mfd. 600 volt	.18

22-250	.05 mfd. 200 volt	.15
22-280	.5 mfd. 200 volt	.30
22-289	50 mmfd. 600 volt	.15
22-435	.02 mfd. 600 volt	.18
22-721	10 mfd. 450 volt x 10 mfd. 350 volt x 10 mfd. 25 V. (dry electrolytic)	1.00
22-756	Adjustable trimmer condenser	1.00
22-757	Two gang variable condenser (less gear & worm gear)	2.25
22-777	1000 mfd. 600 volt	.45
22-781	R. F. coil trimmer	.25
22-782	.012 mfd. 800 volt	.25

Variable Condenser & Gear Assembly

22-757	Two gang variable condenser only	2.25
34-86	Gear—condenser shaft	.25
34-87	Gear—worm	.25
54-125	Worm gear lock nut	.02
73-34	Worm gear adjusting screw	.02
83-499	Felt strip	.001
94-286	Brass bushing (used with 22-757 only)	.03
94-293	Brass bushing (used with 22-757 only)	.03
184-3	Ball—steel	.02

Resistors

63-271	1 megohm ¼ watt	.07
63-296	220 M ohm ¼ watt	.07
63-461	1200 ohm ¼ watt	.07
63-510	18 M ohm 2 watt	.25
63-584	1500 ohm ¼ watt	.07
63-591	22 M ohm ¼ watt	.07
63-593	47 M ohm ¼ watt	.07
63-595	100 M ohm ¼ watt	.07
63-629	330 ohm ¼ watt	.07
63-641	10 M ohm ¼ watt	.07
63-655	220 M ohm ¼ watt	.07
63-709	10 M ohm ¼ watt	.07
63-719	470 M ohm ¼ watt	.07
63-941	390 ohm 1 watt	.08
63-968	1800 ohm 2 watt	.18
63-969	18 M ohm ½ watt	.08
63-970	47 ohm 1 watt	.08
63-971	220 ohm ½ watt	.08
63-972	15 M ohm 1 watt	.08
63-994	Sensitivity control	.35
63-995	Volume control & switch assembly	.90


Miscellaneous

56-56	Pins—for rubber coupling	.01
58-21	Delco Remy—cap	.01
58-24	Delco Remy—bushing & ferrule	.01
78-238	Socket—78 tube	.10
78-239	Socket—6A7 tube	.10
78-240	Socket—75 tube	.10
78-241	Socket—42 tube	.10
78-242	Socket—84 tube	.10
78-243	Socket—vibrator	.10
78-251	Socket—antenna connector	.10
85-134	Switch—tone control	.15
95-565	Transformer—speaker output	1.10
95-566	Transformer—power	2.25
126-179	Shield—goat tube	.10
136-11	Fuse—14 ampere	.04
143-36	Rubber coupling	.02
190-14	Vibrator	2.60

Accessory parts

22-271	Condenser—voltage regulator	.45
22-497	Condenser—oil gauge	.40
54-122	Nuts—hex cadmium plated ¾" x 16 x 11/16"	.04
54-123	Nuts—wing	.02
93-399	Washer—steel	.04
93-409	Lockwasher—# ¾ cadmium plated	.02
93-410	Washer—rubber	.02
112-205	Hooks—screw	.03
144-15	Set mounting bolts	.03
102-53	Station call letter tab sheet	.40
202-110	Instruction book	.05
S-6740	Dummy antenna	net .25

All Prices Subject to Regular Discount and Change Without Notice.



Models 4K310, 4K331, 4K355. Chassis No. 5412

Models 4K310, 4K331, 4K355

CHASSIS No. 5412

NOTE



All voltages measured from point indicated to chassis using a 1000 ohm per volt meter.

Antenna disconnected — volume control at minimum and condenser plates in full mesh.

All voltages measured using Zenith No. Z28 battery pack.

LEGEND

NC — No Connection
SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
K — Cathode
F — Filament




9/23-18/

Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Def. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.



Model 4K329. Chassis No. 5413

DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION
C-1	22-650	TWO GANG VARIABLE	1	3-5028	ANTENNA COIL ASSEMBLY
C-2	22-280	.05 MFD	2	35100	ANT. COIL & SHIELD ASSEM
C-3	22-199	.5 MFD	3	3-4682	OSCILLATOR COIL ASSEM
C-4	22-588	.002 MFD	4	35-449	1ST. I.F. TRANSFORMER
C-5	22-212	.05 MFD	5	35-410	2ND I.F. TRANSFORMER
C-6	22-482	.0001 MFD			SPEAKER TRANS. (IN SPEAKER.)
C-7	22-317	.02 MFD			
C-8	22-108	.02 MFD			
C-9	22-604	8 MFD ELECTROLYTIC			
C-10	22-492	.002 MFD			
R-1	63-328	150 M OHM			
R-2	63-594	68 M OHM			
R-3	63-628	5600 OHM			
R-4	63-271	1 MEG OHM			
R-5	63-658	390 M OHM			
R-6	63-545	1 MEG OHM VOL CONTROL			
R-7	63-600	2.2 MEG OHM			
R-8	63-238	1000 OHM			

Model 4K329

CHASSIS No. 5413



NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to point indicated using a Z28 battery pack.

Antenna disconnected — vol. control at minimum and condenser plates in full mesh.

LEGEND

NC — No Connection
SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
K — Cathode
F — Filament



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to—	Dummy Antenna	Set Test Osc. μ	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	$\frac{1}{2}$ Mfd.	456	Br'dc't	600	ABCD	I. F. Algm't.
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Algm't of Ant.
4	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output
5	" " "	200 Mmfd.	1500	"	1500	FG	Rpt. 3 & 4

Model 6D315

CHASSIS No. 5657


5413
123-200

NOTE

Voltages measured from No. 7 pin on ballast tube to point indicated using a 1000 ohm per volt meter. Vol. control at minimum. Antenna disconnected.


All filament voltages measured across each respective tube, using a 0-30 A.C. volt-meter.

(A) Plate voltage of 25Z6 shows 110 v. A.C. measured from plate of 25Z6 to No. 7 pin of 6Q7 socket.



LEGEND

NC — No Connection
SH — Shield
H — Heater
P — Plate
S — Screen
G — Grid
SU — Suppressor
D — Diode
F — Filament
K — Cathode



ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Lead	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
3	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.

Model 8S359—Chassis 5807


CHASSIS No. 5807

NOTE

All voltages measured from chassis to point indicated using a 1000 ohm per volt meter. Antenna disconnected. Volume control at minimum. Band switch on manual B.C. position.

Line voltage 114 v.


(A) Grid bias for 6A8 and 6K7 tubes measured from chassis to K of 6J5 tube is neg. 1.3 volts.



FRONT OF CHASSIS

LEGEND

- NC — No Connection
- SH — Shield
- H — Heater
- P — Plate
- S — Screen
- G — Grid
- SU — Suppressor
- D — Diode
- F — Filament
- K — Cathode



Location of tubes and trimmers


ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Rec. Ant. Post	200 Mmfd.	455	"	600	E	See Note
3	" " "	200 Mmfd.	1500	"	1500	F	Set Osc. to Scale
4	" " "	200 Mmfd.	1500	"	1500	G	Al'gment of Ant.
5	" " "	200 Mmfd.	600	"	600	J	Rock gang & adj. for max. output.
6	" " "	200 Mmfd.		"		FG	Repea 3 & 4
7	" " "	400 Ohms	18000	S.W.	18000	K	Set Osc. to Scale
8	" " "	400 Ohms	18000	S.W.	18000	L	Rock Gang & adj. for max. output.
9	" " "	400 Ohms	6000	Police	6000	N	Rock Gang & adj. for max. output.

NOTE: If receiver is used in location subject to code interference adjust wave trap (E) for minimum interference with antenna connected and receiver operating in broadcast band.

PHONOGRAPH OSCILLATOR

MODEL-S 6622



DWG. NO.	PART NO.	DESCRIPTION	
C-1	22-768	16 MFD. ELECTROLYTIC	200V
C-2	22-250	40 MFD.	150V
C-3	22-250	.05 MFD.	200V
C-4	22-196	.01 MFD.	600V
C-5	22-182	.00025 MFD.	600V
C-6	22-147	.0005 MFD.	600V
C-7	22-463	TRIMMER	1000V
C-8	22-525	.005 MFD.	1000V
R-1	63-658	390M OHM	1/4W
R-2	63-654	180M OHM	1/4W
R-3	63-593	47M OHM	1/4W
R-4	63-583	1000 OHM	1/4W
R-5	63-587	4700 OHM	1/4W
R-6	63-964	4700 OHM	1/2W
1	100-36	PILOT LIGHT-6V. 25A.	
2	142-14	PICKUP ARM-COMPLETE	
3	142-16	CRYSTAL UNIT ONLY	
4	S-6625	OSC. COIL ASSEM.	
5	95-567	POWER TRANS.	
	85-170	SWITCH	

Wireless Record Player
Model S-6622

PARTS PRICE LIST

Models 4K310, 4K355,—Chassis 5412

DIAL ASSEMBLY

26-199	Dial scale	\$.15
59-66	Dial pointer	.15
76-258	Dial control shaft	.08
80-69	Dial cord tension spring	.02
93-371	Dial spacer bakelite washer	.25C
188-27	Dial retainer	.05C
192-29	Dial crystal	.15
MS-418	Dial pulley & bracket assembly	.10
S6109	Dial cord & eyelet assembly	.15

COILS

95-513	1st I. F. Transformer assembly	.75
95-520	2nd I. F. Transformer assembly	.75
S-6381	Oscillator coil assembly	.65
S-6704	Antenna coil assembly	.65

CONDENSERS

22-162	.0001 mfd.	600 volt.	.15
22-182	.00025 mfd.	600 volt.	.15
22-185	.01 mfd.	200 volt.	.15
22-212	.05 mfd.	400 volt.	.15
22-243	.01 mfd.	400 volt.	.15
22-250	.05 mfd.	200 volt.	.15
22-305	2-35 mmfd. trimmer condenser		.15
22-448	.004 mfd.	600 volt.	.18
22-684	8. mfd.	150 volt electrolytic	.45
22-778	Two gang variable condenser		1.75

RESISTORS

63-238	1000 ohm	1/4 watt.	.07
63-271	1 megohm	1/4 watt.	.07
63-587	4700 ohm	1/4 watt.	.07
63-594	68 M ohm	1/4 watt.	.07
63-600	2.2 megohm	1/4 watt.	.07
63-654	180 ohm	1/4 watt.	.07
63-997	Volume control & switch assembly		.75

MISCELLANEOUS

2-19	Back for 310 cabinet	.15
14-458	Cabinet for model 310	3.50
46-245	Knob—tuning (Model 355)	.10
46-251	Knob—tuning (Model 310)	.15
46-257	Knob—volume (Model 355)	.10
46-271	Knob—volume (Model 310)	.10
49-286	Speaker—5" PM (Model 310)	4.00
	206-286 output transformer	1.00
	208-286 cone & voice coil assembly	1.25
49-287	Speaker—6" PM (Model 355)	5.00
	206-287 output transformer	1.00
	208-287 cone & voice coil assembly	1.50
52-156	Battery cable & Plug assembly	.35
52-157	Speaker cable & Plug assembly (Model 355)	.25
57-654	Escutcheon plate (Model 355)	.75
78-246	Socket—1A7G tube	.10
78-247	Socket—1N5G tube	.10
78-248	Socket—1H5G tube	.10
78-249	Socket—1C5G tube	.10
126-239	Tube shield	.10
139-48	Speaker baffle (cardboard)	.02
202-116	Instruction book	.10

Model 4K329—Chassis 5413

4 TUBE BATTERY SET

171-4	Dial scale lens	\$.25
S3717	Dial pointer & bushing assembly	.25
S5098	Dial scale & bracket assembly (26-168)	1.00

COILS & CHOKES

95-419	1st I. F. Transformer assembly	1.25
95-420	2nd I. F. Transformer assembly	1.25
S4662	Oscillator coil assembly	.30
S5100	Antenna coil & shield assembly	1.25

CONDENSERS

22-162	.0001 mfd.	600 volt.	.15
22-188	.02 mfd.	400 volt.	.15
22-199	.5 mfd.	200 volt.	.25
22-212	.05 mfd.	400 volt.	.15
22-305	2-35 mmfd. trimmer condenser		.15
22-327	.02 mfd.	200 volt.	.15
22-358	.002 mfd.	600 volt.	.20
22-406	Two gang variable condenser		2.25
22-492	.002 mfd.	600 volt.	.15
22-519	Oscillator padder condenser		.30

RESISTORS

63-238	1000 ohm	1/4 watt.	.07
63-271	1 megohm	1/4 watt.	.07
63-325	150 M ohm	1/4 watt.	.07
63-441	1 megohm	1/4 watt.	.07
63-548	1 megohm volume control assembly		1.35
63-594	68 M ohm	1/4 watt.	.07

63-600	2.2 megohm	1/4 watt.	.07
63-638	5600 ohm	1/4 watt.	.07
63-647	39 ohm	1/4 watt.	.07
63-658	390 M ohm	1/4 watt.	.07

MISCELLANEOUS

46-219	Volume control knob	.15
46-220	Tuning control knob	.15
49-209	6" PM speaker	6.00
	206-209 Cone & voice coil	1.75
	208-209 Output transformer	1.50
78-190	Speaker plug socket	.10
78-246	1A7G tube socket	.10
78-247	1N5G tube socket	.10
78-248	1H5G tube socket	.10
78-249	1C5G tube socket	.10
93-323	1/32" x 29/64" x 3/4" bakelite washer	.01
126-239	Tube shield	.10
159-14	Snap button	.50C
202-115	Instruction book	.10
S6170	Cable & Male Plug Assembly	.25

Model 6D315—Chassis 5657

DIAL ASSEMBLY

26-218	Dial Scale	.15
59-73	Dial pointer	.15
76-257	Dial tuning control shaft	.03
80-69	Dial cord tension spring	.02
93-360	1/32 x .273 x .355 brass washer	.50C
94-279	Pointer bushing	
100-36	6.3 volt pilot lamp	.09
188-2	Retaining ring	.01
192-28	Dial crystal	.20
MS-418	Pulley & bracket	.10
S-6002	Dial cord & eyelet assembly (11-3)	.10

COILS

S-6847	1st I. F. Transformer	1.00
95-514	2nd I. F. Transformer	.75
S-6750	Oscillator coil assembly	.65

CONDENSERS

22-127	25 mmfd.	600 volt.	.15
22-147	.0005 mfd.	600 volt.	.15
22-162	.0001 mfd.	600 volt.	.15
22-182	.00025 mfd.	600 volt.	.15
22-185	.01 mfd.	200 volt.	.15
22-196	.01 mfd.	600 volt.	.15
22-250	.05 mfd.	200 volt.	.15
22-327	.02 mfd.	200 volt.	.12
22-435	.02 mfd.	600 volt.	.18
22-524	2-35 mmfd. trimmer condenser		.15
22-680	16 mfd.	150 volt electrolytic	.35
22-681	40 mfd.	150 volt electrolytic	.50
22-730	.04 mfd.	600 volt.	.18
22-794	Two gang variable condenser		1.75

RESISTORS

63-271	1 megohm	¼ watt.....	.07
63-296	220 M ohm	¼ watt.....	.07
63-557	60 ohm	½ watt (wire wound)	.08
63-593	47 M ohm	¼ watt.....	.07
63-595	100 M ohm	¼ watt.....	.07
63-605	1 M ohm	¼ watt.....	.07
63-633	680 ohm	¼ watt.....	.07
63-643	18 M ohm	¼ watt.....	.07
63-681	56 M ohm	¼ watt.....	.08
63-954	50 ohm	½ watt (wire wound)	.08
63-1004	500 M ohm volume control & switch assembly.....		.75
46-244	Tuning control knob		\$.15
46-245	Volume control knob		.10
49-237	Dynamic speaker—5"		2.75
	206-237 Output transformer for 49-237.....		1.00
	207-237 Field coil for 49-237.....		1.00
	208-237 Cone & voice coil for 49-237.....		1.00
57-651	Escutcheon plate		.35
78-148	Socket—6Q7 tube		.10
78-151	Socket—6A8 tube		.10
78-159	Socket—25Z6 tube		.10
78-161	Socket—ballast tube		.10
78-173	Socket—25L6 tube		.10
78-253	Socket—6U7G tube		.10
100-70	115 volt ballast tube		.75
	11-29—150 volt external resistor cord.....		1.25
	11-30—175 volt external resistor cord.....		1.25
	11-31—220 volt external resistor cord.....		1.25
	11-32—250 volt external resistor cord.....		1.25
126-191	Tube shield		.10
202-117	Instruction book		.10

CABINET & WAVE MAGNET ASSEMBLY

14-385	Model 315 bakelite cabinet (less back & handle)	2.50
36-6	Cabinet handle	.35
43-38	Housing for wave magnet assembly	1.50
S6780	Wave magnet coil assembly	1.50
125-295	Shields (2 used)	.50

PARTS PRICE LIST (Cont.)

Model 8S359

DIAL & DRIVE ASSEMBLY

26-201	Dial scale	\$.35
26-265	Volume control shaft	.10
27-16	Flywheel disc	1.00
59-70	Pointer & spring assembly	.10
73-30	6/32 x 1/4 H.H. set screws (cuppoint)	.02
80-69	Dial core tension spring	.02
94-271	Volume control shaft coupling	.05
100-36	6.3 volt pilot lamp	.09
117-38	Band selector lever arm	.05
118-16	Lever connecting link	.05
148-25	Band switch & control arm	.10
159-12	Cinch snap button	.02
192-33	Dial glass	.35
196-17	Dial glass gasket	.15
S5999	Dial light socket & clip assembly	.10
S6223	Tuning shaft & bushing assembly	.20
S6284	Dial cord & eyelet assembly (11-3)	.20
MS449	Pulley & bracket assembly	.35

COILS & CHOKES

20-154	Wave trap	.65
20-196	Compensating coil	.50
95-536	1st I. F. transformer	1.00
95-537	2nd I. F. transformer	1.00
S6294	Antenna coil & shield assembly	1.50
S6295	Oscillator coil & shield assembly	1.25

CONDENSERS

22-127	25 mmfd.	600 volt.	.15
22-147	.0005 mfd.	600 volt.	.15
22-162	.0001 mfd.	600 volt.	.15
22-170	.1 mfd.	400 volt.	.20
22-182	.00025 mfd.	600 volt.	.15
22-185	.01 mfd.	200 volt.	.15
22-212	.05 mfd.	400 volt.	.15
22-250	.05 mfd.	200 volt.	.15
22-289	50 mmfd.	600 volt.	.15
22-305	2-35 mmfd. trimmer condenser		.15
22-326	.003 mfd.	400 volt.	.15
22-327	.02 mfd.	200 volt.	.12
22-358	.002 mfd.	600 volt.	.25
22-435	.02 mfd.	600 volt.	.18
22-448	.004 mfd.	600 volt.	.18
22-458	.006 mfd.	600 volt.	.18
22-463	335-825 mmfd. oscillator padder		.30
22-470	.00015 mfd.	600 volt.	.15
22-492	.002 mfd.	600 volt.	.18
22-519	200-550 mmfd. padder (on auto. assy.)		.35
22-708	Dual fixed padder		\$.65
22-717	Two gang variable condenser		3.00
22-718	12 mfd.	450 volt electrolytic	.55
22-719	16 mfd.	350 volt electrolytic	.50
22-731	2-35 mmfd. trimmer condenser (3 section)		.40
22-740	Compensating condenser		.55

MISCELLANEOUS

63-296	220 M ohm	1/4 watt.	.07
63-461	47 M ohm	1 watt.	.10
63-591	22 M ohm	1/4 watt.	.07
63-592	33 M ohm	1/4 watt.	.07
63-605	1000 ohm	1/2 watt.	.08
63-621	39 M ohm	1/4 watt.	.07
63-643	18 M ohm	1/4 watt.	.07
63-655	220 M ohm	1/4 watt.	.07
63-680	10 M ohm	1 watt.	.10
63-975	8 M ohm	1/2 watt (wire wound)	.08
63-976	15 M ohm	1/4 watt.	.07
63-985	Volume control & switch assembly		1.35
24-199	Adjustment screw cover		.03
24-202	Tone control switch indicator (voice)		.05
24-203	Tone control switch indicator (normal)		.05
24-204	Tone control switch indicator (treble)		.05
24-205	Tone control switch indicator (lo bass)		.05
24-206	Tone control switch indicator (bass)		.05
24-207	Tone control switch indicator (alto)		.05
46-252	Knob—tuning control		.15
46-253	Knob—volume control		.10
46-254	Knob—radiorgan switch		.03
46-255	Knob—automatic selector switch		.03
49-249	12" dynamic speaker		13.25
	206-249—output transformer for 49-249		2.50
	207-249—field coil for 49-249		2.50
	208-249—cone & voice coil for 49-249		3.25
208-57-660	Escutcheon plate (for glass & gasket see dial parts)		2.00
78-128	Socket—speaker plug		.10
78-145	Socket—6F5 tube		.10
78-149	Socket—6X5 tube		.10
78-150	Socket—6K7 tube		.10
78-151	Socket—6A8 tube		.10
78-175	Socket—6J5 tube		.10
78-230	Socket—resonance indicator & cable assy.		.50
78-257	Socket—6P5 tube		.10
78-258	Socket—6AC5 tube		.10

80-198	Chassis mounting springs	\$.005
80-199	Chassis mounting springs	.005
83-433	Antenna & ground terminal strip assembly	.10
85-151	Switch—band selector	1.00
95-526	117 volt 50-60 cycle power transformer	3.00
126-239	Tube shield	.10
202-120	Instruction book	.10
S6224	Radiorgan switch & knob assembly	1.00

AUTOMATIC PARTS

22-519	Padder condenser	.35
46-255	Automatic push button knob	.03
83-605	Pin Jack terminal strip assembly	.10
85-152	Station selector switch	1.50
93-385	Felt washer for auto. push lever	15C
102-45	Station call letter sheet	.25
112-190	Inductance adjustment screw	.03
S6103	Automatic coil & core assy. (red)	.50
S6104	Automatic coil & core assy. (green)	.50
S6105	Automatic coil & core assy. (yellow)	.50
S6106	Automatic coil & core assy. (blue)	.50
S6107	Automatic coil & core assy. (white)	.50
S6287	Automatic coil & core assy. (orange)	.50

PHONO RECORD PLAYER

Model S-6222

CONDENSERS

22-147	.0005 mfd.	600 volt.	\$.15
22-182	.00025 mfd.	600 volt.	.15
22-196	.01 mfd.	600 volt.	.15
22-250	.05 mfd.	200 volt.	.15
22-463	Trimmer condenser		.30
22-525	.005 mfd.	1000 volt.	.20
22-768	16 mfd.-200 volt x 40 mfd.-150 volt.		.95

RESISTORS

63-583	1 M ohm	1/4 watt.	.07
63-587	4700 ohm	1/4 watt.	.07
63-593	47 M ohm	1/4 watt.	.07
63-654	180 M ohm	1/4 watt.	.07
63-658	390 M ohm	1/4 watt.	.07
63-964	4700 ohm	1/2 watt.	.08

MISCELLANEOUS

S-6625	Oscillator coil assembly	.30
12-634	Pickup support arm	.05
14-457	Cabinet	7.00
24-142	Needle cup cover	.05
29-5	8" Turntable	1.00
41-1	Needle cup	.10
46-265	Switch knob	.10
57-684	Escutcheon plate	.10
78-149	Socket—6X5G tube	.10
78-162	Socket—6L7G tube	.10
85-170	On & Off switch	.70
95-567	110 volt 60 cycle power transformer	1.75
100-36	Pickup light bulb	.09
141-63	110 volt 60 cycle phono motor	8.50
142-14	Phono pickup & arm assembly	7.50
142-16	Pickup cartridge only	4.50
202-112	Instruction book	.05


OSCILLATOR ASSEMBLY

22-182	.00025 mfd.	600 volt condenser	\$.15
22-196	.01 mfd.	600 volt condenser	.15
22-250	.05 mfd.	200 volt condenser	.15
22-285	10 mmfd.	600 volt condenser	.15
22-463	Trimmer condenser		.30
22-525	.005 mfd.	1000 volt condenser	.20
22-768	16 mfd. 200 volt x 40 mfd. 150 volt condenser		.95
63-583	1 M ohm	1/4 watt resistor	.07
63-587	4700 ohm	1/4 watt resistor	.07
63-593	47 M ohm	1/4 watt resistor	.07
63-654	180 M ohm	1/4 watt resistor	.07
63-658	390 M ohm	1/4 watt resistor	.07
63-964	4700 ohm	1/2 watt resistor	.08
95-567	110 volt 60 cycle power transformer		1.75
12-634	Pickup support arm		.05
24-142	Needle cup cover		.05
29-5	8" turntable		1.00
41-1	Needle holder		.10
46-265	Switch knob		.10
57-684	Escutcheon plate		.10
78-149	Socket—6X5G tube		.10
78-162	Socket—6L7G tube		.10
85-170	On & Off switch		.70
100-36	Pickup light bulb		.09
141-63	110 volt 60 cycle phono motor		8.50
142-14	Phono pickup & arm assembly		7.50
142-16	Pickup cartridge only		4.50
202-112	Instruction book		.05

All Prices Subject to Regular Parts Discount and Change Without Notice.



MODELS 4K400D, 4K400S, 4K400L, 4K400M
Chassis 5416



NOTE:

All measurements with 1000 ohms per voltmeter — loop antenna not connected — volume at minimum — All readings made with fresh Zenith (part No. Z-59) battery pack with speaker in circuit.


NOTE: "A"


Bias for 1C5 measured across 1000 ohm resistor at points marked X—X.

Bias is neg. 10 volts.

LEGEND

F — FILAMENT
P — PLATE
S — SCREEN
G — GRID
D — DIODE
NC — NO CONNECTION





ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Osc. to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 Mfd.	455	Br'dc't	600	ABCD	I. F. Alignment
2	Separate 3 foot antenna		1500	"	1500	F	Set Osc. to Scale
3	Separate 3 foot antenna		1500	"	1500	G	Al'gment of Ant.

PARTS LIST

Chassis 5416

MODELS 4K400D, 4K400S, 4K400L, 4K400M

Dial Assembly

25-220	Dial scale	\$.20
59-75	Dial pointer	.10
76-278	Dial drive shaft	.10
80-69	Dial cord tension spring	.02
93-371	Dial spacer bakelite washer	.25
192-38	Dial crystal	.15
MS-418	Pulley and bracket assembly	.10
S-6870	Indicator disc and bushing	.15
S-6893	Dial cord and eyelet assembly	.15

Coils

95-593	1st I. F. Transformer	1.00
95-594	2nd I. F. Transformer	1.00
S-6869	Oscillator coil assembly	.60
S-6888	Loop antenna assembly	1.35

Condensers

22-162	.0001 mfd. ... 600 volt	.15
22-182	.00025 mfd. ... 600 volt	.15
22-243	.01 mfd. 400 volt	.15
22-448	.004 mfd. 600 volt	.18
22-684	8. mfd. 150 volt Dry Electrolytic	.45
22-800	Two gang variable	2.00
22-802	30 mmfd. 600 volt	1.00
22-826	.01 mfd. 200 volt	.12

22-828	.05 mfd. 400 volt	.15
22-829	.05 mfd. 200 volt	.12

Resistors

63-238	1000 ohm 1/4 watt	.07
63-271	1 megohm 1/4 watt	.07
63-593	47 M ohm 1/4 watt	.07
63-600	2.2 megohm .. 1/4 watt	.07
63-604	10 megohm ... 1/4 watt	.07
63-654	180 M ohm ... 1/4 watt	.07
63-669	3.9 megohm .. 1/4 watt	.07
63-1026	Volume control and switch	1.50

Miscellaneous

46-273	Tuning control knob	.10
49-294	Speaker—5 1/2" PM—all models	6.25
	208-294 cone and voice coil	1.50
	206-294 output transformer	1.25
78-208	Speaker plug socket	.10
78-246	Socket 1A7G tube	.10
78-247	Socket 1N5G tube	.10
78-248	Socket 1H5G tube	.10
78-249	Socket 1C5G tube	.10
83-658	Pin jack terminal strip	.06
126-297	Tube shield	.10
S-6872	Battery cable and plugs	.45

ALL PRICES LIST SUBJECT TO REGULAR PARTS DISCOUNT
AND CHANGE WITHOUT NOTICE

ZENITH RADIO CORPORATION

Chicago, Ill.

ALIGNMENT INSTRUCTIONS

The proper procedure for the correct alignment of each chassis is outlined on the page opposite each circuit diagram.

In order to obtain proper alignment of the chassis when using a wavemagnet the signal generator should be coupled to the wavemagnet by means of a single turn loop approximately one foot in diameter. The leads of the signal generator may be connected together forming a satisfactory loop which should be placed about two feet from the receiver.

The operations are outlined in consecutive order, and the instructions are under the following headings —

OSC. CONNECTED TO — tells where the output of the service oscillator is to be connected.

DUMMY — gives the proper capacity or resistance which should be connected in series with the service oscillator output.

TEST OSC. — Set test oscillator to frequency shown.

BAND — Set the receiver band switch to the position shown.

DIAL — The receiver should be set at the frequency shown.

TRIMMER — This column tells which trimmer (or trimmers) are to be adjusted for each operation. The chassis drawing has each trimmer indicated by a letter corresponding to the instructions.


PURPOSE—This column tells what is being accomplished by each operation.

If these instructions are carefully followed each chassis will be easily and correctly realigned.

AUTOMATIC RANGES

Button No. 1	tunes from	550 K.C.	to	950 K.C.
" 2	" "	600 K.C.	"	1100 "
" 3	" "	650 K.C.	"	1200 "
" 4	" "	730 K.C.	"	1390 "
" 5	" "	900 K.C.	"	1550 "

The use of a wavemagnet requires two adjustments for each automatic button. These adjustments are made with a special wrench (part No. 68-1) supplied with each receiver. The center or screw adjustment controls the oscillator circuit and the nut tunes the wavemagnet or antenna input — see illustration at right.



The minimum tuning range covered by each pair of adjustments is shown above and will usually exceed the frequencies shown.

The adjustments covering the highest frequency range is in all cases either at the bottom when the buttons are vertical or closest to the band switch when the buttons are arranged horizontally.

SERVICE NOTES

In many cases a ground lead may be eliminated by connecting the ground terminal on the wavemagnet to the chassis base.

The operation of the bass radiorgan button in chassis 5719-5721 can often be improved by connecting a 1 megohm resistor from the high side of the volume control to the tap on same.

Noisy operation of the automatic tuning may be caused by the leads to the automatic assembly or coil leads laying against the metal frame of the assembly.

Excessive oscillation in Model 4K401 will be caused by the 1A7 tube which should be replaced.

Motorboating in Model 4K401 will be due to a poor ground connection on the electrolytic condenser at the rivet which fastens it to the chassis.

Care should be taken that the leads from the tone control condenser and switch in all six tube bakelite models be kept away from the 6Q7 tube, otherwise the tone will be affected.

Excessive hum in AC-DC or voltage doubler chassis can be corrected by reversing the power plug in the light socket.

Cutting out in the portable receivers will usually be due to poor connections at the battery pack plug. Slight bending of the prongs will correct this condition.

Excessive regeneration in 5659 chassis may be corrected in most cases by moving the 12A8G grid lead away from the oscillator section of the gang condenser.


The Theory Of The Voltage Doubler

The voltage doubler circuit is a means of simultaneously rectifying and doubling the voltage of an alternating current without the use of a transformer.


Referring to the circuit below, on one alternation of the A.C. input voltage, tube A will pass current charging condenser C1 to 110 volts. On the next alternation the polarity is reversed and tube A is inoperative due to the negative voltage on its plate. The input voltage (110 V.) being in series with condenser C1 places a 220 volt positive charge on the plate of tube B which then passes current to the filter system comprising a choke or speaker field and condensers C2 and C3.

The current handling ability of this circuit is limited only by the size of the rectifier tubes and condenser C1. In smaller chassis requiring but a few milliamperes plate current, a single 25Z6 is satisfactory, and in larger chassis 2 - 25Z6's are used with the plates and cathodes of each tube in parallel as in chassis #5721.

This circuit obviously will not operate on direct current (D.C.) inasmuch as the plate of tube B never becomes positive when so connected, and, therefore, does not pass current.



WAVEMAGNET



WAVEMAGNET CIRCUIT

The circuit diagram on the right shows the switching arrangement used on the Wavemagnet in chassis employing more than one waveband.

With the Wavemagnet-Antenna switch in the Wavemagnet position, the two shields surrounding the loop winding are connected together and grounded to the chassis through the short wave primary winding and an isolation condenser of .05 mfd. The reactance of the short wave primary is negligible at broadcast frequencies and the shield is effectively grounded although this primary winding is in the circuit.

When the receiver is switched to short wave the entire Wavemagnet assembly acts as a small antenna coupled to the short wave input winding by means of the aforementioned primary winding.

The trimmer condenser connected between the shield and the grid end of the loop winding is used to compensate for unavoidable variation of distributed capacity between the shield and the loop winding and preserves tracking over the high frequency portion of the broadcast band.

With the Wavemagnet-Antenna switch in the Antenna position, the connection between the two shields is broken and the outer shield acts as an antenna connected to the loop by means of the trimmer condenser which in this case also acts as a coupling condenser. In many cases an increase of signal strength will be apparent with this connection but at the expense of increased pickup of interference inasmuch as the shielding action of the shield is no longer effective. The antenna primary winding which is associated with the loop winding is not effective unless an outside antenna is connected to the antenna terminal on the Wavemagnet.


Model 4K402

CHASSIS No. 5419

NOTE


All measurements with 1000 ohms per volt meter — loop antenna not connected—volume at minimum — All readings made with fresh Zenith (part No. Z-59) battery pack with speaker in circuit.

All voltages measured from contact X on 1C56 tube socket to point indicated.



LEGEND

SH—Shield
H—Heater
P—Plate
S—Screen
G—Grid
SU—Suppressor
D—Diode
K—Cathode
NC—No Connection



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 mfd.	455	—	600	A B C D	I. F. Alignment
2	Single Turn Loop Loosely Coupled to Wave Magnet	—	1400	—	1400	F	Set Osc. to Scale
3		—	1400	—	1400	G	Alignment of Ant.

Model 5G401


CHASSIS No. 5537

NOTE

All voltages measured from point indicated to chassis using a 1000 ohm per volt meter.

Antenna disconnected — volume control at minimum and condenser plates in full mesh.

Line voltage — 110v.



LEGEND

NC—No Connection

SH—Shield

H—Heater

P—Plate

S—Screen


G—Grid

SU—Suppressor

D—Diode

K—Cathode


F—Filament



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 mmfd.	455	—	600	A B C D	I. F. Alignment
2	Single Turn Loop Coupled Loosely to Wave Magnet	—	1400	—	1400	F	Set Osc. to Scale
3		—	1400	—	1400	G	Alignment of Antenna



DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION	DIAG. NO.	PART NO.	DESCRIPTION
C1	22-279	TWO-GANG VARIABLE	R14	63-506	3500 OHM	A	1E	1E TRANS. PRI	117	Z6G	RECT.
C2	22-280	50 MMFD.	R15	63-605	1000 OHM	B	1E	1E TRANS. SEC	49-316	8"	SPEAKER
C3	22-281	0.5 MFD.	R16	63-1036	3-SECTION CANDOHM	C	2E	2E TRANS. PRI	49-317	10"	SPEAKER
C4	22-350	25 MFD.	R17	63-1012	90 OHM WIREWOUND	D	2E	2E TRANS. SEC	49-318	10"	SPEAKER
C5	22-196	0.1 MFD.	1	57257	ANTENNA COIL ASSEMBLY	E	BO	BO TRANS. PRI			
C6	22-162	100 MMFD.	2	57252	OSC. COIL ASSEMBLY	F	BO	BO TRANS. SEC			
C7	22-325	0.1 MFD.	3	56992	OSC. COUPLING COIL ASSEM.	G	BO	BO TRANS. SEC			
C8	22-325	0.1 MFD.	4	56992	OSC. COUPLING COIL ASSEM.	H	BO	BO TRANS. SEC			
C9	22-325	0.1 MFD.	5	56992	OSC. COUPLING COIL ASSEM.	I	BO	BO TRANS. SEC			
C10	22-325	0.1 MFD.	6	56992	OSC. COUPLING COIL ASSEM.	J	BO	BO TRANS. SEC			
C11	22-448	0.04	7	95-607	13T I.F. TRANSFORMER	K	BO	BO TRANS. SEC			
C12	22-830	20 MFD. ELECTROLYTIC	8	95-607	13T I.F. TRANSFORMER	L	BO	BO TRANS. SEC			
C13	22-830	20 "	9	95-607	13T I.F. TRANSFORMER	N	BO	BO TRANS. SEC			
C14	22-830	20 "	10	95-607	13T I.F. TRANSFORMER						
C15	22-830	20 "	11	95-607	13T I.F. TRANSFORMER						
C16	22-830	20 "	12	95-607	13T I.F. TRANSFORMER						
C17	22-830	20 "	13	95-607	13T I.F. TRANSFORMER						
C18	22-350	0.02 MFD.	14	95-607	13T I.F. TRANSFORMER						

MODEL 5G441 5G442 5G461
 I.F. FREQUENCY 455 KC
 5 TUBE SUPERHETERODYNE
 110V. AC - BATT. PACK - UNIVERSAL
 CHASSIS N° 5539 - 3 BAND
 ZENITH RADIO CORPORATION
 CHICAGO, ILL.

MODELS 5G441, 5G442, 5G461

(Chassis No. 5539)

Models 5G441, 5G442, 5G461

CHASSIS No. 5539

NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to point indicated.

Antenna disconnected — volume control at minimum and condenser plates in full mesh.

Line voltage — 110v.

LEGEND

NC—No Connection

SH—Shield

H—Heater

P—Plate

S—Screen



G—Grid

SU—Suppressor

D—Diode

K—Cathode

F—Filament



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	1/2 mfd.	455	Br'dc't	600	A B C D	I. F. Alignment
2	Rec. Ant. Wire	400 ohms	18000	S. W.	18000	K	Set. Osc. to Scale
3	" " "	400 ohms	16000	S. W.	16000	L	Rock gang & adj. for max. output Alignment of Ant.
4	" " "	400 ohms	6000	Police	6000	N	Rock gang & adj. for max. output
5	" " "	200 mmf.	1400	Br'dc't	1400	F	Rock gang & adj. for max. output
6	" " "	200 mmf.	600	"	600	J	Rock gang & adj. for max. output
7	" " "	200 mmf.		"		Repeat F & J	

Models 6D410, 6D411, 6D425


CHASSIS No. 5659

NOTE


Voltages measured from line switch to point indicated using a 1000 ohm per volt meter. Vol. control at minimum. Antenna disconnected.

All filament voltages measured across each respective tube, using an A.C. volt-meter.

Line voltage — 110v.



- LEGEND**
- NC—No Connection
 - SH—Shield
 - H—Heater
 - P—Plate
 - S—Screen
 - G—Grid
 - SU—Suppressor
 - D—Diode
 - F—Filament
 - K—Cathode



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 Mfd.	455	B'dcast	600	A B C	I. F. Alignm't
2	Single Turn Loop Loosely Coupled to Wave Magnet	—	1500	"	1500	F	Set Osc. to Scale
3		—	1500	"	"	G	Alignment of Ant.

DESCRIPTION			PART NO	DESCRIPTION			DWG NO	PART NO	DESCRIPTION		
C1	22-888	TWO GANG VARIABLE	R1	63-593	47 M OHM	1/4 W	5	5603	2ND I/F TRANS ASSEMBLY		
C2	22-935	1 MFD	R2	63-591	25 M OHM	1/4 W	6	5497	AUTOMATIC TUNING UNIT		
C3	22-935	1 MFD	R3	63-572	15 M OHM	1/4 W	7	MS57	TONE CONTROL SWITCH		
C4	22-250	.05 MFD	R4	63-600	22 MEG OHM	1/4 W	8	100-77	BALLAST TUBE		
C5	22-841	100 MFD	R5	63-602	22 MEG OHM	1/4 W	9	100-67	PILOT LIGHT BULB		
C6	22-868	COMPENSATING CONDENSEL	R6	63-296	47 MEG OHM	1/4 W			6.3 V -15 AMP		
C7	22-868	DUAL 100 MMFD	R7	63-597	470 M OHM	1/4 W					
C8	22-837	.01 MFD	R8	63-597	470 M OHM	1/4 W			1ST I/F TRANS PRI		
C9	22-833	.0005 MFD	R9	63-696	150 OHM WIREWOUND	1/4 W	4		1ST I/F TRANS SEC		
C10	22-836	.03 MFD	R10	63-1017	27 OHM WIREWOUND	1/4 W	5		2ND I/F TRANS SEC		
C11	22-839	.05 MFD	R11	63-713	47 M OHM	1/4 W	6		BROADCAST OSC (ON GANG)		
C12	22-835	.40 MFD ELECTROLYTIC	R12	63-717	220M OHM	1/4 W	7		ANTENNA BROADCAST (ON GANG)		
C13	22-835	.16 "									
C14	22-841	TONE CONTROL CONDENSEL	1	56927	OSCILLATOR COIL ASSEMBLY		G				
C15	22-841	TONE CONTROL CONDENSEL	2	56927	OSC COUPLER COIL ASSEMBLY						
			3	56903	1ST I/F TRANS ASSEMBLY						
			4	56903	2ND I/F TRANS ASSEMBLY						

1. I.F. FREQUENCY 455 KC.
6 TUBE SUPERHETERODYNE
CHASSIS *5660*5664 AC-DC.
ZENITH RADIO CORPORATION
CHICAGO, ILL.

MODELS 6D413, 6D414, 6D426, 6D427, 6D446, 6D455 (Chassis No. 5660)

Models 6D413, 6D414, 6D426, 6D427, 6D446, 6D455

CHASSIS No. 5660


NOTE

Voltages measured from No. 7 pin on ballast tube to point indicated using a 1000 ohm per volt meter. Vol. control at minimum. Antenna disconnected.


All filament voltages measured across each respective tube, using an A.C. volt-meter.

Line voltage — 110v.


35L6G-OUTPUT



35Z5G-RECT.



12A8G-DET. OSC.



12Q7G-2ND. DET.

12K7G-I.F.
FRONT OF CHASSIS

100-77-BALLAST

LEGEND

NC—No Connection

SH—Shield

H—Heater

P—Plate

S—Screen


G—Grid

SU—Suppressor

D—Diode

F—Filament


K—Cathode



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 Mfd.	455	B'dcast	600	A B C	I. F. Alignm't.
2	Single Turn Loop Loosely Coupled to Wave Magnet	—	1500	"	1500	F	Set Osc. to Scale
3		—	1500	"	"	G	Alignment of Ant.





MODELS 6P416, 6P417, 6P418, 6P419 (Chassis No. 5661)

DIAG. N°	PART N°	DESCRIPTION	DIAG. N°	PART N°	DESCRIPTION	DIAG. N°	PART N°	DESCRIPTION
C1	22-845	TWO GANG VARIABLE	C13	63-593	47 M OHM	5	95-594	2 NO. I.F. TRANS.
C2	22-190	100 MFD	R5	63-722	2.2 MEG OHM	6	MS515	BAND SWITCH
C3	22-250	0.5 MFD	R6	63-976	15 MEG OHM	7	100-79	GALLAST TUBE
C4	22-845	0.5 MFD	R7	63-976	15 MEG OHM	8	100-39	PILOT LIGHT 29V-17A
C5	22-845	0.5 MFD	R8	63-296	220 M OHM	9	MS517	TO NE CONTROL SWITCH
C6	22-212	0.5 MFD	R9	63-597	470 M OHM	A	121	I.F. TRANS. PRI.
C7	22-212	DUAL 100 MMFD	R10	63-486	150 OHM WIREWOUND	B	121	I.F. TRANS. SEC.
C8	22-839	0.005 MFD	R11	63-1023	22 OHM	C	221	I.F. TRANS. SEC.
C9	22-833	0.005 MFD	R12	63-717	22 OHM	D	221	I.F. TRANS. SEC.
C10	22-833	0.01 MFD	R13	63-717	22 OHM	E	221	I.F. TRANS. SEC.
C11	22-836	0.01 MFD	1	56913	WAVEMAGNET ASSEMBLY	F	221	I.F. TRANS. SEC.
C12	22-875	0.01 MFD	2	56914	SHUNT ANT.	G	221	I.F. TRANS. SEC.
			3	56915	121 I.F. TRANS.			

CHASSIS No. 5661

- B. This lug (No. 8) has a 50 v. A. C. potential with respect to lug No. 2 and also a 117 v. A.C. potential with respect to line switch.

NC—No Connection
SH—Shield
H—Heater
P—Plate
S—Screen
G—Grid
SU—Suppressor
D—Diode
F—Filament
K—Cathode



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 mfd.	455	B'dcast	600	ABCD	I. F. Alignment
2	Single Turn Loop Coupled Loosely to Wave Magnet		1500	"	1500	F	Set Osc. to Scale
3			"	"	"	G	Alignm't of Ant.
4			2700	Police	2700	N	Algn't of S. W.

Models 6P418, 6P419, 6P428, 6P429, 6P430, 6P447, 6P448, 6P457

CHASSIS No. 5662

NOTE

Voltages measured from No. 7 pin on ballast tube to point indicated using a 1000 ohm per volt meter. Vol. control at minimum. Antenna disconnected.

All filament voltages measured across each respective tube, using an A.C. voltmeter.

- A. This lug is C.T. of fil. and is one side of pilot light supply line.

Lug No. 7 is return for pilot light.

- B. This lug (No. 8) has a 50 v. A. C. potential with respect to lug No. 2 and also a 117 v. A.C. potential with respect to line switch.**

LEGEND

NC—No Connection

SH—Shield

H—Heater

P—Plate

S—Screen



G—Grid

SU—Suppressor

D—Diode

F—Filament

K—Cathode



Location of tubes and trimmers

ALIGNMENT PROCEDURE


Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 mfd.	455	B'dcast	600	A B C D	I. F. Alignment
2	Single Turn		1500	"	1500	F	Set Osc. to Scale
3	Loop Coupled		"	"	"	G	Alignm't of Ant.
4	Loosely to Wave Magnet		2700	Police	2700	N	Algn't of S. W.

Models 7S432, 7S433, 7S434, 7S449, 7S450, 7S458, 7S459 7S460, 7S461, 7S462 (Chassis No. 5719)

NOTE


Voltages measured from line switch to point indicated using a 1000 ohm per volt meter. Vol. control at minimum. Antenna disconnected.

All filament voltages measured across each respective tube, using an A.C. volt-meter.



LEGEND

- NC—No Connection
- SH—Shield
- H—Heater
- P—Plate
- S—Screen
- G—Grid
- SU—Suppressor
- D—Diode
- F—Filament
- K—Cathode



Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	5 mfd.	455	B'dcast	600	A B C D	I. F.
2	Single *x Turn Coil	—	1500	"	1500	F	Set Osc. to Scale
3	" "	—	1500	"	1500	On Wave Magnet	Alignment of Wave Magnet
4	Rec. Ant. Post **	400 ohms	18000	S.W.#2	18000	K	Set Osc. to Scale
5	"	"	16000	"	16000	L	Rock gang & adj. for max. output
6	"	"	4.500	S.W. #1	4.500	N	"

* Loosely coupled to Wave Magnet

x Switch in Wave Magnet Position

** Switch in Antenna Position


Models 7S487, 7S488, 7S490

CHASSIS No. 5721

NOTE

Voltages measured from line switch to point indicated using a 1000 ohm per volt meter. Vol. control at minimum. Antenna disconnected.

All filament voltages measured across each respective tube, using an A.C. volt-meter.



BOTTOM VIEW OF CHASSIS

LEGEND

NC—No Connection

SH—Shield

H—Heater

P—Plate

S—Screen


G—Grid

SU—Suppressor

D—Diode

F—Filament

K—Cathode




Location of tubes and trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 mfd.	455	B'dcast	600	ABCD	I. F.
2	Single *x Turn Coil	—	1500	"	1500	F	Set Osc. to Scale
3	" "	—	1500	"	1500	On Wave Magnet	Alignment of Wave Magnet
4	Rec. Ant. Post **	400 ohms	18000	S.W. #2	18000	K	Set Osc. to Scale
5	"	"	16000	"	16000	L	Rock gang & adj. for max. output
6	"	"	4,500	S.W. #1	4,500	N	"

* Loosely coupled to Wave Magnet
x Switch in Wave Magnet Position



OPERATING FREQUENCY
APPROXIMATELY 1540 KC.

MODELS
S-7000
S-7001
S-7002
S-7003

**PHONOGRAPH OSCILLATOR
ZENITH RADIO CORPORATION
CHICAGO, ILL.**

DIAG. N ^o	PART N ^o	DESCRIPTION	DIAG. N ^o	PART N ^o	DESCRIPTION
C1	22-690	TUNING CONDENSER	R2	63-658	390 M OHM
C2	22-182	.00025 MFD.	R3	63-260	100 M OHM
C3	22-243	.01 MFD.	R4	63-583	1000 OHM
C4	22-829	.05 MFD.	R5	63-964	4700 OHM
C5	22-827	.1 MFD.	R6	63-803	2200 OHM
C6 } C7 }	22-876	{ 8 MFD. ELECTROLYTIC 40 MFD.	R7	63-575	47 OHM
C8	22-670	.1 MFD.			
			1	56854	OSC. COIL ASSEM
			2	100-76	BALLAST TUBE
			3	85-170	A C SWITCH
R1	63-591	22 M OHM			

WIRELESS RECORD PLAYER Models S7000, S7001, S7002, S7003

PARTS PRICE LIST

1940 ZENITH RECEIVERS

CHASSIS 5419 — A
5537 — B
5538 — C
5539 — D
5659 — E
5663 — F

CHASSIS 5659U — G
5663U — H
5660 — I
5664 — J
5665 — K

CHASSIS 5661 — L
5662 — M
5666 — N
5719 — O
5721 — P
57000 — Q

DIAL PARTS

Part No.	Model	List Price
26-221	Scale — A-G-I-E	.70
26-222	Scale — K-L-M	.10
26-223	Scale — F-H-J	.45
26-224	Scale (See #S6959) — O-P	.30
26-225	Scale — K-N	.45
26-227	Scale — B-C	.25
26-228	Scale (See #S7243) — D	.35
57-709	Scale Add - mounting plate — A-E-F-I-J	.05
57-711	Scale Add - mounting plate — K-L-M-N	.03
59-75	Pointer - dial — B-C	.10
59-77	Pointer - dial — O-P	.10
59-78	Pointer - dial — A-E-F-G-H-I-J	.05
59-81	On indicator — D	.03
S6935	Pointer & pulley assembly — K-L-M-N	.15
61-55	Pulley idler — D-O-P	.03
76-278	Shaft - dial drive — B-C	.10
76-281	Shaft - control (flat end) — K-L	.05
76-282	Shaft - control — B-O-P	.06
76-284	Shaft - control (flat end) — M-N	.05
76-286	Shaft - control (knurled end) — K-L	.05
76-287	Shaft - control (knurled end) — M-N	.06
78-260	Socket - dial light — K-L-M-N	.18
78-267	Socket - dial light — E-F-G-H-I-J	.18
78-286	Socket - dial light — O-P	.45
80-69	Spring - dial cord tension — B-C-D-K-L-M-N-O-P	.01
80-207	Spring - indicator — D	.02
83-666	Strip - dial light diffusion — E-F-G-H	.02
93-371	Washer - bakelite — B-C	.45C
97-119	Stud - idler pulley — D	.03
97-120	Stud - mounting — O	1.40C
100-36	Lamp - dial (6.3 volt) — O-P	.09
100-39	Lamp - dial (2.9 volt) — K-L-M-N	.12
100-67	Lamp - dial (6.3 volt) — E-F-G-H-I-J	.12
188-13	Clip - shaft retaining — D-O-P	.15C
188-27	Clip - shaft retaining — B-C-K-L-M-N	.01
192-38	Dial crystal — B-C	.15
192-39	Dial crystal — A-E-F-G-H-I-J	.15
192-40	Dial crystal — Model 416-417	.15
192-41	Dial crystal — D-O	.50
192-42	Dial crystal — M-N	.15
192-44	Dial crystal — Model 428 only	.25
196-23	Dial glass gasket — O	.15
S6870	Disc - indicator — B-C	.15
S6935	Pulley & pointer — K-L-M-N	.15
S6959	Scale & idler — O-P	.30
S6976	Cord & eyelet assembly — K-L-M-N	.05
S7046	Cord & eyelet assembly — D-O-P	.15
S7071	Cord & eyelet assembly — B-C	.05
S7243	Scale & pulley assembly — D	.35
S7262	Cam - indicator — D	.05
MS418	Pulley & bracket assembly — B-C	.10
MS506	Pulley & bracket assembly — O-P	.15


CONDENSERS

22-138	.2 mfd.	200 volt.	B-C	.25
22-162	.0001 mfd.	600 volt.	A-B-C-D-O-P	.15
22-182	.00025 mfd.	600 volt.	B-C-Q	.20
22-190	.1 mfd.	200 volt.	E-F-I-J-K-L-M-N	.18
22-196	.01 mfd.	600 volt.	D-O-P	.15
22-212	.05 mfd.	400 volt.	K-L-M-N	.15
22-229	.005 mfd.	600 volt.	O-P	.15
22-243	.01 mfd.	400 volt.	A-B-C-D-Q	.15
22-250	.05 mfd.	200 volt.	E-F-G-H-I-J-K-L-M-N	.15
22-289	50 mmfd.	600 volt.	D-O-P	.15
22-326	.003 mfd.	400 volt.	P	.15
22-327	.02 mfd.	200 volt.	O	.15
22-350	.25 mfd.	200 volt.	B-C-D-O-P	.20
22-358	.002 mfd.	600 volt.	D-O-P	.30
22-448	.004 mfd.	600 volt.	A-D-O-P	.15
22-470	.00015 mfd.	600 volt.	P	.15
22-492	.002 mfd.	600 volt.	B-C	.15
22-534	.25 mfd.	400 volt.	O	.25
22-594	.15 mfd.	200 volt.	O-P	.22
22-669	.01 mfd.	600 volt.	O-P	.30
22-670	.1 mfd.	400 volt.	O-P-Q	.20
22-684	8 mfd.	450 volt.	A	.40
22-690	Trimmer condenser		Q	.25
22-708	Dual fixed padder		D	.65
22-788	Trimmer condenser		D-K-L-O-P	.15
22-800	Two gang variable		B-C	2.00
22-802	30 mmfd.	600 volt.	B-C	.15
22-826	.01 mfd.	200 volt.	A-B-C-D	.15
22-827	.1 mfd.	200 volt.	B-C-D-P-Q	.18
22-828	.05 mfd.	400 volt.	O-P	.15
22-829	.05 mfd.	200 volt.	A-B-C-D-O-P-Q	.15
22-833	.0005 mfd.	600 volt.	E-F-G-H-I-J-K-L-M-N	.20

Part No.	Model	List Price
22-834	Two gang variable (flat shaft) — E-F-G-H-I-J	2.00
22-835	40 x 16 mfd. 150 volt. 25 volt. — E-F-G-H-I-J	.85
22-836	.03 mfd. 400 volt. — E-F-G-H-I-J-K-L-M-N	.15
22-837	.01 mfd. 400 volt. — E-F-G-H-I-J-K-L-M-N	.15
22-838	.005 mfd. 600 volt. — K-L-M-N	.15
22-839	.05 mfd. 400 volt. — E-F-G-H-I-J	.15
22-840	20 mfd. 350 volt - 20 mfd. 250 volt. — K-L-M-N	2.00
88-841	.02 mfd. 200 volt. — E-F-G-H-I-J	.15
22-842	.02 mfd. 400 volt. — K-L-M-N	.15
22-844	.05 mfd. 400 volt. — E-F-G-H-I-J	.15
22-845	Two gang variable — K-L-M-N	2.00
22-846	Trimmer condenser (automatic) — O-P	.15
22-847	Trimmer condenser (automatic) — O-P	.20
22-848	Trimmer condenser (automatic) — O-P	.25
22-849	Two gang variable — O-P	2.50
22-850	Three section trimmer — O-P	.50
22-851	30 mfd. 350 volt - 20 mfd. 250 volt. 10 mfd. 250 volt dry electrolytic. — O-P	1.35
22-852	30 mfd. 250 volt. — O-P (electrolytic)	.85
22-853	Dual fixed padder — O-P	.60
22-854	.005 mfd. 600 volt. — O-P	.15
22-859	Trimmer condenser (automatic) — O-P	.20
22-863	Dual fixed padder — O-P	.55
22-866	Broadcast oscillator padder — O-P	.30
22-868	480 mmfd. compensator — O-P	.30
22-869	.05 mfd. 400 volt. — B-C-D	.15
22-871	20-20-20 mfd. 150 volt. — B-C (electrolytic)	1.00
22-873	Trimmer (automatic) — O-P	.25
22-875	.15 mfd. 400 volt. — K-L-M-N	.20
22-876	8-40 mfd. 150 volt. — Q (electrolytic)	.85
22-877	9-180 mmfd. trimmer — M-N	.15
22-878	Two gang variable — D	2.25
22-879	60-60 mfd. 150 volt. — D (electrolytic)	1.25
22-880	20-20 mfd. 150 volt - 20 mfd. 25 volt (electrolytic) — D	1.00
22-881	Four section trimmer — D	.75
22-885	Two gang variable (knurled shaft) — A-E-F-G-H-I-J	2.00
22-887	.001 mfd. 600 volt. — D	.15
22-918	40 mfd. 150 volt - 20 mfd. 25 volt (electrolytic) — B-C	.85
22-939	.1 mfd. 200 volt. — G-H	.18
22-948	.05 mfd. 400 volt. — K-L-M-N	.20

TRIMMER CONDENSER ASSEMBLIES (Bakelite Models)

54-126		.30C
54-127		.30C
57-696		.20C
57-697		.20C
57-698		.15C
57-699		.20C
57-700		.20C



Parts Price List (Con't)

Part No.	Model	List Price
83-663		.80C
86-30		.25C
93-217		.25C
93-417		.50C
83-418		.50C
93-419		1.00C
93-449		1.00C
93-450		1.00C
112-218		.25C
112-220		.20C

RF & IF COILS

95-593	1st IF coil	B-C	\$1.00
95-594	2nd IF coil	B-C	1.00
95-598	2nd IF coil	K-L-M-N	.85
95-600	1st IF coil	O-P	1.00
95-606	2nd IF coil	A	.85
95-607	1st IF coil	D	1.00
95-612	2nd IF coil	O-P	1.00
95-614	2nd IF coil	D	1.00
S6854	Oscillator coil	Q	.55
S6901	Oscillator coil only	E-F-G-H	.55
S6902	1st IF coil only	E-F-G-H-I-J	.60
S6903	2nd IF coil only	E-F-G-H-I-J	.60
S6913	Oscillator coil	K-L	.65
S6914	Shunt antenna coil	K-L-M-N	.40
S6915	1st IF coil	K-L-M-N	.50
S6936	Antenna coil	O-P	1.00
S6937	Oscillator coil	O-P	1.25
S6942	Oscillator coupling coil	M-N	.50
S6992	Oscillator coupler coil	D-G-I-O-P	.45
S7029	Oscillator coil	A	.50
S7030	1st IF coil	A	.65
S7027	Oscillator coil	B-C	.75
S7252	Oscillator coil	D	1.10
S7257	Antenna coil	D	1.35

RESISTORS

63-150	10M ohm	1/2 watt	O-P	\$.08
63-238	1000 ohm	1/4 watt	A	.07
63-263	100M ohm	1/4 watt	Q	.07
63-271	1 megohm	1/4 watt	A-B-C-D-O-P	.07
63-296	220M ohm	1/4 watt	All but A & Q	.07
63-325	150M ohm	1/4 watt	O-P	.07
63-572	15 ohm	1/4 watt	E-F-G-H-I-J-K-L-M-N	.07
63-575	47 ohm	1/4 watt	Q	.07
53-581	470 ohm	1/4 watt	M-N	.07
53-583	1000 ohm	1/4 watt	A-K-L-M-N-Q	.07
63-586	3300 ohm	1/4 watt	D	.07
63-587	4700 ohm	1/4 watt	A-B-C-D	.07
63-591	22M ohm	1/4 watt	All but A-B-C	.07
63-593	47M ohm	1/4 watt	A-B-C-D-I-J-K-L-M-N-O-P	.07
63-596	330M ohm	1/4 watt	P	.07
63-597	470M ohm	1/4 watt	D-E-F-G-H-I-J-K-L-M-N	.07
63-598	680M ohm	1/4 watt	P	.07
63-599	1.5 megohm	1/4 watt	P	.07
63-600	2.2 megohm	1/4 watt	A-B-C-D-E-F-G-H-I-J	.07
63-602	4.7 megohm	1/4 watt	E-F-G-H-I-J	.07
63-604	10 megohm	1/4 watt	A-B-C-D	.07
63-605	1000 ohm	1/2 watt	B-C-D-O-P	.08
63-640	8200 ohm	1/4 watt	D	.07
63-649	56M ohm	1/4 watt	D	.07
63-652	120M ohm	1/4 watt	A-B-C	.07
63-654	180M ohm	1/4 watt	D	.07
63-655	220M ohm	1/4 watt	O-P	.07
63-658	390M ohm	1/4 watt	Q	.07
63-669	3.9 megohm	1/4 watt	A-B-C-D	.07
63-686	150 ohm	1/2 watt	E-F-G-H-I-J-K-L-M-N	.17
63-712	33M ohm	1/4 watt	G-H-K-L-M-N	.15
63-713	47M ohm	1/4 watt	E-F-G-H-I-J	.07
63-717	220M ohm	1/4 watt	G-H	.15
63-722	2.2 megohm	1/4 watt	K-L-M-N	.07
63-803	2200 ohm	1/2 watt	B-C-Q	.08
63-964	4700 ohm	1/2 watt	Q	.08
63-976	15 megohm	1/4 watt	K-L-M-N-O-P	.07
63-1012	90 ohm	1/2 watt (W.W.)	D	.17
63-1015	140 ohm	1/2 watt (W.W.)	K-L	.08
63-1017	27 ohm	1/2 watt (W.W.)	E-F-G-H-I-J	.08
63-1019	68M ohm	1/2 watt	O-P	.08
63-1020	68 ohm	1/2 watt (W.W.)	O-P	.08
63-1021	33 ohm	2 watt (W.W.)	O-P	.12
63-1022	150 ohm	1 watt (W.W.)	R-C	.20
63-1023	22 ohm	1/2 watt (W.W.)	K-L-M-N-O-P	.08
63-1026	Volume control & switch		B-C	1.50
63-1028	Volume control strip & base		E-F-G-H-I-J-K-L-M-N	.35
63-1029	Candohm resistor		O-P	.45
63-1030	Volume control assembly		O	1.00
63-1033	Candohm resistor		B-C	.45
63-1034	Volume control strip & base		A	.35
63-1035	Volume control & switch		P	1.50
63-1036	Candohm resistor		D	.40
63-1047	Volume control & switch		D	1.50
63-1039	Candohm resistor		O-P	.45
63-1080	Volume Control		D	1.50

MISCELLANEOUS

12-692	Chassis retaining bracket	A	\$.03
14-481	Bakelite cabinet - Model 416 (brown)		3.00
14-490	Bakelite cabinet - Model 410 (brown)		2.00
14-491	Bakelite cabinet - Model 411 (mahogany)		2.50

Part No.	Model	List Price
14-491W	Bakelite cabinet - Model 411W (white)	3.00
14-491D	Bakelite cabinet - Model 411D (grey)	3.00
14-491G	Bakelite cabinet - Model 411G (green)	3.00
14-493	Bakelite cabinet - Model 413 (brown)	3.00
14-494	Bakelite cabinet - Model 414 (mahogany)	3.50
14-494W	Bakelite cabinet - Model 414W (white)	4.00
14-494D	Bakelite cabinet - Model 414D (grey)	4.00
14-494G	Bakelite cabinet - Model 414G (green)	4.00
14-497	Bakelite cabinet - Model 417 (mahogany)	3.50
14-497W	Bakelite cabinet - Model 417W (white)	4.00
14-497D	Bakelite cabinet - Model 417D (grey)	4.00
14-497G	Bakelite cabinet - Model 417G (green)	4.00
15-22	Plug cap	P
15-23	Plug cap	P
15-28	Volume control cap	A-E-F-G-H-I-J-K-L-M-N
24-209	Automatic adjustment screw cap	I-J-M-N
24-219	Bottom cover (Model 490)	
44-16	Phono jack	O-P
44-17	Phono jack	B-C
46-265	Knob - power switch	B
46-273	Knob - tuning	B-C
46-275	Knob - volume (spring type)	E-F-G-H-I-J-K-L-M-N
46-276	Knob - tuning (spring type)	E-F-G-H-I-J-K-L-M-N
46-277	Knob - volume (spring type)	K-L (bakelite cabinets)
46-279	Knob - band switch	D
46-280	Knob - volume	D-O-P
46-281	Knob - tuning	D
46-285	Knob - tone	D
46-286	Knob - tuning (knurled type)	A-E-F-G-H-I-J-K-L-M-N
46-287	Knob - volume (knurled type)	A-E-F-G-H-I-J-K-L-M-N
46-288	Knob - volume (knurled type)	K-L (bakelite cabinets)
49-298	Speaker - 5" dynamic (Models 429-30-47-48)	3.50
	206-298 output transformer	1.25
	207-298 field coil	1.25
	208-298 cone & voice coil	1.25
49-301	Speaker - 6 1/4" dynamic (Models 432-33-34-49)	4.00
	206-301 output transformer	1.25
	208-301 cone & voice coil	1.50
49-303	Speaker - 5" dynamic (Models 416-17-18)	3.25
	206-303 output transformer	1.25
	207-303 field coil	1.25
	208-303 cone & voice coil	1.25
49-307	Speaker - 10" dynamic (Model 457)	7.00
	206-307 output transformer	1.25
	207-307 field coil	2.25
	208-307 cone & voice coil	2.50
49-308	Speaker - 10" dynamic (Model 458)	7.50
	206-308 output transformer	1.50
	207-308 field coil	2.25
	208-308 cone & voice coil	2.50
49-309	Speaker - 12" dynamic (Models 461-88)	8.00
	206-309 output transformer	1.50
	207-309 field coil	2.25
	208-309 cone & voice coil	3.50
49-310	Speaker - 4" P. M.	A
	206-310 output transformer	1.25
	208-310 cone & voice coil	1.00
49-311	Speaker - 10" dynamic (Models 460-62)	7.50
	206-311 output transformer	1.50
	207-311 field coil	2.25
	208-311 cone & voice coil	2.50
49-312	Speaker - 10" dynamic (Model 487)	7.50
	206-312 output transformer	1.50
	207-312 field coil	2.25
	208-312 cone & voice coil	2.50
49-314	Speaker - 8" dynamic (Models 450-59-90)	5.50
	206-314 output transformer	1.50
	207-314 field coil	1.75
	208-314 cone & voice coil	2.00
49-316	Speaker - 8" P. M. (Model 5G441)	6.00
	206-316 output transformer	1.25
	208-316 cone & voice coil	2.00
49-317	Speaker - 10" P. M. (Model 5F442)	10.00
	206-317 output transformer	1.65
	208-317 cone & voice coil	2.50
49-318	Speaker - 10" P. M. (Model 5G461)	10.00
	206-318 output transformer	1.65
	208-318 cone & voice coil	2.50
49-323	Speaker - 4" P. M.	E-F
	206-323 output transformer	1.25
	208-323 cone & voice coil	1.00
49-324	Speaker - 4" P. M. (Models 413-14-26-27-55)	4.00
	206-324 output transformer	1.25
	208-324 Cone & voice coil	1.00
49-327	Speaker - 8" P. M. (Model 456)	7.00
	206-327 output transformer	1.25
	208-327 cone & voice coil	2.00
49-336	Speaker - 5" P. M. (Model 446)	5.00
	206-336 output transformer	1.25
	208-336 cone & voice coil	1.25
49-337	Speaker - 5 1/4" P. M. (replaces 49-315) B-C	5.00
	206-337 output transformer	1.25
	208-337 cone & voice coil	1.25
52-164	Cable - speaker (Model 446-56)	.40
52-165	Cable - speaker (Model 457)	.35
54-128	Nut - speed	I-J-M-N
57-11A	Antenna lead marker	D
57-11G	Ground lead marker	D
57-703	Escutcheon plate (Model 416-17)	.30
57-708	Television radio escutcheon	O-P
57-712	Escutcheon plate (less glass)	D-O-P
57-715	Escutcheon plate	E-F-G-H
57-716	Escutcheon plate (Models 426-27-46-56)	1.50
57-717	Escutcheon plate (Model 428)	1.25

Parts Price List (Con't)

Part No.	Model	List Price
57-718	Escutcheon plate M-N	1.95
57-724	Escutcheon plate A	.60
57-749	Power switch plate D	.05
58-73	Plug - battery B-C-D	.10
58-74	Plug - battery A	.10
62-10	Plug - female E-F-G-H-P	.20
68-1	Wrench - auto. adjustment D-I-J-M-N-O-P	.05
76-280	Shaft - volume control (flat) E-F-G-H-I-J-K-L-M-N	.15
76-285	Shaft - vol. control (knurled) A-E-F-G-H-I-J-K-L-M-N	.18
78-128	Socket - speaker O-P	.10
78-148	Socket - 6Q7G tube O-P	.10
78-150	Socket - 6K7G tube O-P	.10
78-151	Socket - 6A8G tube O-P	.10
78-159	Socket - 25Z6G tube O-P	.10
78-190	Socket - speaker D	.10
78-193	Socket - five contact P	.10
78-194	Socket - two contact P	.10
78-229	Socket - electrolytic cond. D-O-P	.02
78-246	Socket - 1A7G tube B-C-D	.10
78-247	Socket - 1N5G tube B-C-D	.10
78-248	Socket - 1H5G tube B-C-D	.10
78-261	Socket - 25Z5G tube O-P	.10
78-263	Socket - 6AF5G tube O-P	.10
78-265	Socket - two contact O-P	.10
78-266	Socket - four contact O-P	.10
78-268	Socket - 1A5G tube B-C	.10
78-269	Socket - 11Z26G tube B-C-D	.10
78-270	Socket - speaker plug B-C	.10
78-273	Socket - 1Q5G tube D	.10
80-206	Spring - knob (46-275 & 46-276)	.55C
83-568	Strip - single lug terminal B-C	.02
83-658	Strip - pin jack terminal A	.06
83-689	Strip - antenna pin jack B-C	.07
85-171	Switch - television O-P	.25
85-185	Switch - band O-P	1.25
85-190	Switch - battery B-C	.45
85-195	Switch - band selector D	1.25
85-196	Switch - power D	.55
93-215	Washer - chassis mounting D-O-P	.06
93-229	Washer - felt O-P	.01
100-77	Ballast tube - 110 volt E-F-G-H-I-J	.75
100-79	Ballast tube - 110 volt K-L-M-N	.75
112-221	Screw - chassis mounting (5G401)	.55C
112-222	Screw - chassis mounting (5G400)	1.25C
114-40	Screw - chassis mounting (5G441-61 & 7 tube sets)	.50C
114-61	Screw - chassis mounting (Model 490)	.03
114-85	Screw - chassis mounting (5G442)	.65C
126-191	Shield - tube O-P	.15
126-256	Shield - tube O-P	.15
126-297	Shield - tube B-C-D	.12
127-15	Contact - tube socket A-E-F-G-H-I-J-K-L-M-N	.30C
127-16	Contact - power switch - (straight) E-F-G-H-I-J-K-L-M-N	.01
127-17	Contact - power switch (bent) E-F-G-H-I-J-K-L-M-N	.01
188-32	Retainer ring (for 76-285) A-E-F-G-H-I-J-K-L-M-N	.85C
188-33	Speaker ring A	.06
196-23	Escutcheon plate gasket (for 57-712)	.15
202-127	Instruction book E-F-G-H	.01
202-128	Instruction book K-L	.02
202-129	Instruction book I-J	.20
202-130	Instruction book M-N	.10
202-131	Instruction book B-C	.05
202-132	Instruction book O-P	.15
202-136	Instruction book (Model 4K402)	.05
202-138	Instruction book D	.20
202-140	Instruction book (Model 4K400)	.05
S6910	Shield - tube A-E-F-G-H-I-J-K-L-M-N	.10
S6911	Shield - condenser E-F-G-H-I-J	.12
S6912	Shield - I F transformer E-F-G-H-I-J	.12
S6945	Escutcheon plate (complete) O-P	1.25
S6975	Escutcheon - electrolytic cond. K-L-M-N	.15
S6994	Switch - tone control D-O-P	.25
MS515	Switch - band selector (85-188) K-L-M-N	.30
MS517	Switch - tone control (85-189) E-F-G-H-I-J-K-L-M-N	.25
MS524	Switch & bracket assy. (85-194) A	.35

WAVEMAGNET PARTS

12-645	Loop retaining bracket (antenna) (410-11-12-16-17)	\$.02
12-651	Loop retaining bracket (antenna) (413-14)	.02
12-686	Loop retaining bracket (ground) (410-11-12-16-17)	.02
12-687	Loop retaining bracket (ground) (413-14)	.02
12-689	AC cord clip B-C	.06
22-182	.00025 mfd. 600 volt condenser O-P	.20
22-865	Trimmer condenser (456-57-87-88-90)	.25
22-882	Trimmer condenser (4K402) A	.15
40-15	Brass hinge B-C	.12
54-79	Brass nuts E-F-G-H-I-J-K-L-M-N	.30C
56-68	Spade pin for cabinet back A	.02
57-719	Switch plate O-P	.03
57-727	Loop mounting plate (429)	.10
57-728	Loop mounting plate (430)	.10
57-731	Loop mounting plate (428)	.10
58-69	Four prong plug O-P	.04
58-72	Two prong plug O-P	.03
69-149	.6-32 x 1 7/8" RH M. screw (bronze) E-F-G-H	.55C
70-34	#6 x 5/8 wood screw	.15C
71-41	.6-32 x 1 11/16" FH screw E-F-G-H-I-J-K-L-M-N	.15C
83-334	A-G terminal strip (446-47-48-55-56-57-87-88-90)	.12
83-686	Loop retaining strip (antenna) (425-26-27-28-29-30-80)	.02
83-687	Loop retaining strip (ground) (425-26-27-28-29-30-80)	.02
83-692	Pin Jack A-G terminal strip B-C	.05
84-61	Suction cup support B-C	.04
85-171	Switch O-P	.25

Part No.	Model	List Price
86-66	Cinch terminals E-F-G-H-M-N	1.50C
93-125	#6 lockwasher E-F-G-H-I-J-K-L-M-N-O	.25C
93-350	#6 finishing washer O	.01
93-414	Fibre washer E-F-G-H	.50C
93-424	Fibre washer I-J-K-L-M-N-O	.30C
112-227	#6-32 x 2 3/4 ornamental screw E-F-G-H-I-J	.02
114-48	6-32 x 1/4 hex acorn head screw E-F-G-H	.25C
114-100	#6 x 1/2" self tapping screw I-J	.90C
114-104	1/4"-20 x 4" machine screw (457-87-88-90)	.05
114-105	1/4"-20 x 3" Hex head machine screw O	.05
114-106	1/4"-20 x 3" machine screw (448)	.05
144-17	1/4"-20 x 3 1/2" carriage bolt and nut O	.02
144-19	1/4"-20 x 4 1/2" carriage bolt and nut P	.05
147-71	Wood spacer - 1/2" E-F-G-H-K-L-M-N	.01
147-72	Wood spacer - 29/32 E-F-G-H-M-N	.01
147-73	Wood spacer - 1 1/8" E-F-G-H-M-N-O-P	.01
147-74	Wood spacer - 1 7/32 E-F-G-H-O-P	.01
147-75	Wood spacer B-C	.75C
147-76	Wood spacer - 3/4 E-F-G-H-K-L	1.25C
147-77	Wood spacer A	.15
159-25	Plug button (401D-M-Y) A-B-C	.35C
159-33	Plug button (401L) B-C	.35C
197-8	Rubber suction cup A	.04
197-9	Rubber suction cup B-C	.06
S6904	Loop winding assembly (410-11-12)	1.25
S6905	Loop shield assembly (410-11-12)	.85
S6916	Loop winding assembly (416-17)	1.25
S6938	Loop shield assembly (413-14)	1.10
S6941	Loop winding assembly (413-14)	1.40
S6951	Loop winding assembly (427-29-30)	1.15
S6952	Loop shield assembly (427-29-30)	1.25
S6983	Rear shield & frame (433-34-60-88)	1.75
S6984	Front shield assembly (433-34-46-49-50-56-57-58-60-61 (62-87-88-90))	1.15
S6985	Loop winding assembly (433-34-49-58-60-61)	1.85
S7031	Loop winding assembly B-C	1.00
S7045	Partition plate B-C	.35
S7048	Loop winding assembly (425-28)	1.50
S7049	Loop shield assembly (425-26-28)	1.25
S7074	Loop winding assembly (426)	1.50
S7079	Rear shield & frame (432)	1.50
S7080	Front shield assembly (455-48-32-59)	.85
S7082	Loop winding assembly (432-59)	1.95
S7092	Rear shield assembly (446)	1.85
S7095	Rear shield assembly (447)	1.25
S7098	Loop winding assembly (448-55)	1.85
S7099	Rear shield assembly (455)	1.65
S7106	Loop winding assembly (4K402D)	1.95
S7113	Loop cover plate B-C	1.15
S7122	Rear shield & frame (450-90)	1.85
S7131	Loop shield assembly (480)	1.00
S7143	Shield & plate assembly (458-61)	2.00
S7146	Loop winding assembly (458-61)	3.75
S7166	Loop winding assembly (446)	1.85
S7167	Loop winding assembly (450-90)	1.75
S7171	Loop winding assembly (447)	1.50
S7174	Loop winding assembly (480)	1.00
S7208	Loop cover & strip (402L-M-Y)	.35
S7241	Rear shield & frame (459)	1.45
S7247	Loop winding assembly (402L-M-Y)	1.50
S7317	Loop winding assembly (487-88)	1.85
S7321	Rear shield & plate (487)	1.75
S7322	Loop winding assembly (462)	1.75
S7326	Wavemagnet assembly (484M)	1.85
S7335	Loop winding assembly (456-57)	1.40
S7345	Loading coil (456-57)	.15
S7348	Plate & condenser assembly (457)	1.50
S7357	Plate & strip assembly (448)	.45
S7364	Antenna cable (402L-M-Y) B-C	.85
S7389	Partition plate A	.35
22-846	Trimmer condenser D-I-J-M-N-O-P	\$.15
22-847	Trimmer condenser D-I-J-M-N-O-P	.20

AUTOMATIC TUNER PARTS

22-848	Trimmer condenser D-I-J-M-N-O-P	.25
22-859	Trimmer condenser D-I-J-M-N-O-P	.20
22-868	480 mmfd compensator D-I-J-M-N-O-P	.30
22-873	Trimmer condenser D-O-P	.25
24-209	Automatic adjustment cover D	.10
46-278	Automatic tuning knob D-I-J-M-N-O-P	.10
57-707	Front plate D-I-J-M-N-O-P	.06
80-161	Latch bar spring D-I-J-M-N-O-P	.25C
80-202	Push lever spring D-I-J-M-N-O-P	.25C
80-203	Push lever spring I-J-M-N	.25C
83-321	Two lug terminal strip D-O-P	.02
83-669	Coil retaining strip D-I-J-M-N-O-P	.03
83-671	Fibre strip D-I-J-M-N-O-P	.02
83-672	Latch bar D-I-J-M-N-O-P	.35C
93-216	Steel washer D-I-J-M-N-O-P	.30C
93-421	Felt washer for 24-209 P	.01
112-223	Adjustment screw & core D-I-J-M-N-O-P	.08
114-37	#6 x 1/4 hex self-tapping screw D-I-J	.40C
114-46	#6 x 3/16 hex self-tapping screw D-I-J-M-N-P	.40C
114-102	#6 x 3/8 hex self-tapping screw M-N-P	.40C
S6926	Contact spring & base assembly I-J	.75
S6927	Manual oscillator coil I-J	.40
S6928	Auto. tuning coil (red) D-I-J-M-N-O-P	.15
S6929	Auto. tuning coil (green) D-I-J-M-N-O-P	.15
S6930	Auto. tuning coil (blue) D-I-J-M-N-O-P	.15
S6931	Auto. tuning coil (white) D-I-J-M-N-O-P	.15
S6932	Push lever assembly D-I-J-M-N-O-P	.12
S6933	Push lever (manual) I-J-M-N	.04
S6934	Switch base assembly & spring D-O-P	.65

Parts Price List (Con't)

Part No.	Model	List Price
S7006	Manual oscillator coil (orange) M-N	.40
S7021	Auto. tuning coil (yellow) D-O-P	.15
S7023	Contact spring & base assy. M-N	.75

PHONOGRAPH PARTS

12-613	Pickup arm support bracket (480-84-90)	\$.20
12-701	Bracket for 62-12	.05
12-730	Switch bracket (phono compartment - 487)	.05
12-731	Switch bracket (phono compartment - 488)	.05
15-22	Plug cap for 58-39 - All models	.05
15-23	Plug cap for 58-50 (480-90)	.10
15-25	Oscillator coil cap (record player)	.01
19-32	Lamp socket retaining clip (487-88)	.01
22-182	.0005 mfd. 600 volt condenser (record player)	.20
22-243	.01 mfd. 400 volt condenser (record player)	.15
22-670	.1 mfd. 400 volt condenser (record player)	.20
22-690	Trimmer condenser (record player)	.25
22-827	.1 mfd. 200 volt condenser (record player)	.18
22-829	.05 mfd. 200 volt condenser (record player)	.15
22-876	8 x 40 mfd. 150 volt condenser (record player)	.85
24-142	Needle cup cover (487-88) (record player)	.05
24-213	Switch cover (490) (record player)	.06
29-9	Turntable - 9" (480-90) (record player)	1.75
29-10	Turntable - 9" (487)	1.75
29-11	Turntable - 11 1/2" (488)	2.25
29-12	Turntable - 9" (484M)	1.75
41-1	Needle holder (all)	.05
41-6	Needle holder (484M)	.05
46-265	Switch knob (record player)	.10
57-684	Escutcheon for switch (record player)	.10
57-721	Escutcheon for switch (480-90)	.10
57-740	Speed regulator plate (484M)	.05
57-743	Escutcheon for switch (484)	.10
57-744	Switch plate (487-88)	.02
57-746	Turntable support bracket (484)	.10
58-39	Plug - five prong (All)	.05
58-50	Plug - two prong (480-90)	.07
58-73	Plug - battery cable (484M)	.05
59-80	Speed regulator pointer (484M)	.10
62-12	Lamp receptacle with switch (487)	.03
		.45

Part No.	Model	List Price
63-260	100M ohm 1/4 watt resistor (record player)	.07
63-575	47 ohm 1/4 watt resistor (record player)	.07
63-583	1000 ohm 1/4 watt resistor (record player)	.07
63-591	22M ohm 1/4 watt resistor (record player)	.07
63-658	390M ohm 1/4 watt resistor (record player)	.07
63-803	2200 ohm 1/2 watt resistor (record player)	.08
63-964	4700 ohm 1/2 watt resistor (record player)	.08
78-161	Socket - ballast tube (record player)	.10
78-271	Socket - 35Z4GT tube (record player)	.10
78-272	Socket - 12SA7GT tube (record player)	.10
78-291	Lamp socket & wire assembly (488)	.12
83-342	Strip - two lug terminal	.05
85-170	Switch (record player)	.70
85-181	Switch - automatic stop (490) (record player)	1.00
85-190	Switch (484M)	.40
85-191	Switch - A C (480-90)	.25
85-192	Switch - phono (All)	.35
85-193	Turntable brake (484M)	.25
85-197	Switch - phono (484M)	.25
85-203	Switch - for phono lamp (488)	.55
85-204	Switch - for phono lamp (487)	.55
100-76	Ballast tube - (record player)	.75
100-78	Lamp - bulb (phono compartment) (487)	.50
100-80	Lamp - bulb (phono compartment) (488)	.25
112-238	Turntable screw (484M)	.04
117-53	Motor - crank (484M)	.65
141-77	Phono motor only 115 volt 60 cycle (480-90)	6.75
141-78	Phono motor only 115 volt 50 cycle (record player)	6.75
141-79	Phono motor only (484M)	6.75
142-17	Pickup arm assembly (record player)	6.25
142-19	Pickup arm assembly (484M)	6.25
142-22	Pickup arm assembly (480-90)	6.25
142-23	Pickup cartridge only for 142-22 142-17	5.00
142-24	Pickup cartridge only for 169-36	6.00
159-25	Plug button (record player)	.35C
169-36	Automatic record changer (115 volt 60 cycle) (487-88)	50.00
169-37	Automatic record changer (115 volt 50 cycle) (487-88)	50.00
199-20	Rubber sleeve	.03
199-134	Instruction book (487-88)	.03
199-135	Instruction book (record player)	.03
S6854	Oscillator coil assembly (record player)	.55

All price Lists Subject to Regular Parts Discount and Change Without Notice.

SEPTEMBER 6, 1939


SERVICE MANUAL SUPPLEMENT



SERVICING CHART

Automatic Record Changer

ZENITH RADIO CORPORATION
CHICAGO, U. S. A.



For the Service Man

This Chart is designed for the use of the Service Mechanic only, and is intended to facilitate as far as possible his work of caring for the Changer mechanism, whether he is called in for the purpose of insuring its continued satisfactory operation, or to remedy some difficulty which has appeared. For his convenience, the "Operating Instructions," supplied to each user by the factory, may be summarized as follows:

The Changer plays twelve 10" or ten 12" records. . . . To reload, revolve the two posts slightly, grasping them underneath the Shelf Plates. Turn them back after the played records are removed; they will fall and lock when in proper position. Then place the new records on the Shelf Plates, and push "R" button to put Changer in operation. . . . To play the other size records, turn the knob at top of each post until proper figure is opposite pointer, and press the "10" or "12" button, to agree with pointer setting. . . . To reject a record (or to start a change cycle as for testing purposes) simply press the "R" (Release or Reject) button, at any time while needle is upon a record. . . . To play manually, turn plates out of the way as for reloading, and press "M" button.

Oiling (reprinted from Operating Instructions)

The changer should be lubricated once a year with about a dozen drops of a good light machine oil at each of the following 6 points. All points can be reached from above, through holes in the mounting plate, as follows:

- No. 1) Three oil holes on motor gear
- No. 2) housing. Reach all three through
- No. 3) two holes marked "A" on drawing.

- No. 4 Through hole marked "B", drop the oil upon flat surface of cam. It will distribute itself to proper points.
- No. 5 Through holes marked "C", see felt wick, and drop the oil directly upon it.
- No. 6 Through hole marked "D", see felt wick, and drop the oil directly upon it.

To Check Oiling

If squeaks are heard compare the squeak with and with a load of records; stacked records themselves sometimes squeak against a center pin. See that all five wicks are in position, including three $\frac{1}{4}$ " wicks in frame of Motor. See that each wick is thoroughly saturated (as it may not be if insufficient oil or too heavy oil has been used). Lift out all three motor wicks, with tweezers; see if old oil has become gummy (commonly due to use of low-grade oil). If necessary, clean gummed-up wicks with kerosene. See that each is saturated with good oil; then, before replacing them, drop a little good oil into the holes.

Adjustments

There are three adjustments that can be made. All are correctly made at the factory, and ordinarily need never be altered. Should it become necessary to remake any of these adjustments, due to accident or tampering, proceed as follows:

A. ADJUSTING LANDING POSITION OF NEEDLE ON THE RECORD. (See Top View. This adjustment is made with a screwdriver from above-- does not require removing Changer from cabinet.) If needle comes down too far from

edge of record, playing of records will not start at their beginning. Turn Needle-Landing Adjusting Screw very slightly counter-clockwise. If needle comes down too close to edge of record, needle may slip off edge of record. Turn the adjusting screw clockwise.

Compare also Paragraph 12 below.

B. ADJUSTING DISTANCE FROM RECORD PIN AT WHICH TRIGGER WILL TRIP AND CHANGE CYCLE WILL BEGIN. Turn Trip Adjusting Screw 18, toward the trigger for earlier tripping, or away from it for later tripping. This Changer does not depend, for automatic tripping, on the records being provided with any special grooves at end; it trips whenever needle comes within a certain distance of Record Pin. The factory adjustment is for 1-7/8" from center of Record Pin. This is the most generally satisfactory distance; no modern record will then be cut off before playing is finished, and none will fail to trip at end. For certain records of early manufacture, it may not be possible to find an adjustment that will always trip and never cut off.

TO OBTAIN REPLACEMENT PARTS

Order by name and number, as given on the photos (names given to parts are "handy" names only, and do not completely distinguish them.)

C. ADJUSTING HEIGHT TO WHICH PICKUP ARM RISES. The arm should rise, during the change cycle, high enough so that it clears by only 1/8" the record above it, next to be played. (Be careful, before deciding that adjustment is necessary, to see that the record at bottom of stack is not a warped one.) To make this adjustment, loosen the lock-nut on Pickup Sleeve 22 (see photographs) and turn the Sleeve to lengthen or shorten Pickup Plunger 21. When correct adjustment is found, tighten lock nut again.

Replacing Motor

The service mechanic may be called upon to adapt the Changer to a different power supply. For this purpose, or in case of any service fault within Motor, remove entire Motor (with Record Pin and connecting gear drive) from the Changer, and replace it with a suitable new Motor. (In ordering a replacement Motor, specify the power supply and make and model number of phono-radio or other type of installation.)

When mounting replacement Motor, it is most important to see that Record Pin is centered between the two Posts of the Changer, that it stands perpendicular to Main Plate 53, and that it has not become bent so as to wobble. Even though the Posts are stout and not easy to bend, it is well to check


them also, with a 12" combination square laid clear across the concave upper surface of Main Plate. When the new Motor has been attached, with three screws through Grommet Sleeves 51 (spacers) into its frame, and Record Pin is seen to revolve without appreciable wobble (a wobble would indicate that it has been bent in transit from factory) the correct position of Pin midway between the Posts can be accurately checked in this way: Place a single 12" record on the Shelf Plates, press "R" button, and turn turntable forward by hand. Immediately after the Shelf Plates open and let it fall, turn Turntable slightly backward, and with other hand support the record between the Shelf Plates; it can then be readily seen whether Record Pin is off center. If it is, remove the record and Turntable, and loosen slightly the screw or screws nearest the Shelf Plate to which record appeared closest. This should improve evenness of operation. However, unless the unevenness was very slight, it will be necessary for a permanent repair to insert a shim or two on one or more of the three screws (or change shims from one screw to another). The shims used are shaped like an ordinary washer, cut out at one side (see cut-away view at 52 on photo, showing a shim in place upon one of the Grommet Sleeves). Shims can readily be cut out with shears and punch from thin metal or cardboard--or an assortment of shims of different

thicknesses can be had from factory (order "Assortment of P-1397 Shims"). They should be inserted, around proper screws (when screws have been sufficiently loosened) between Motor Frame and the metal Grommet Sleeve. Do not insert shims next to rubber grommet. In wiring up, consult wiring diagram for particular installation. Use only Underwriters' approved wire.


Trouble Shooting


Cases of failure to operate satisfactorily will generally be found due either to neglect of proper lubrication, or to tampering with the mechanism after it leaves the factory, or to injuries accidentally sustained as by external vibration or by impact of some heavy object. In addition there is always the possibility that any kind of spring may "go dead" (cease to operate without any visible breakage) even though the utmost factory precautions are taken against it--or that setscrews may work loose due to some external vibration. Damage from tampering is likely to take the form of bent parts; never bend any part during examination. Be careful, especially, never to push upward from below on Cam Connecting Rod Lift 37 while mechanism is operating; bending may result, and even slight bending here might interfere with correct timing of the cycle operations.

Among the principal trouble symptoms to which such causes may give rise, are the following:




Sub-Plate A





ssembly



1. MECHANISM IS SLOW IN STARTING, OR STALLS DURING A CHANGE CYCLE, BUT A SLIGHT FORWARD PUSH WITH THE HAND STARTS IT AGAIN. May be caused by

a. Failure to lubricate properly. Oil thoroughly, per instructions above.

b. Loose setscrews.

c. Weakness of drive: line voltage may be abnormally low, or motor windings damaged. If windings are found damaged, remove motor and return it to factory for repair or replacement. See above: "Replacing Motor."

2. MOTOR FAILS TO RUN, EVEN WHEN IT IS ENTIRELY DISCONNECTED FROM OTHER WIRING AND PROPER VOLTAGE IS APPLIED DIRECTLY TO THE TWO ENDS OF ITS WINDINGS. This indicates trouble in Motor windings. Unless the damage is easily seen and repaired, replace Motor, as above described.

3. MOTOR IS SLOW IN STARTING.

a. Check oiling, as directed above. It may not have been properly done; old oil may have become gummy.

b. Changer may have been in a very cold place, and may not yet have reached room temperature. Give it a fair chance to get warmed up, before concluding that Motor is defective, and proceeding as in Paragraph 2 above.

4. SQUEAKS OR OTHER NOISES, DURING PLAYING OF RECORDS.

a. Check oiling, as directed above. (If squeaks are heard, they will usually be found to come from the records--not from the mechanism).

b. See that all setscrews are tight.

c. Examine Motor windings; especially the shading coils (not visible in photos) which encircle a portion of each laminated pole and make the Motor self-starting. If coils have been jarred loose at any point, they may be tightened accordingly.

5. CHANGER IS NOISY WHEN IN CYCLE. Check oiling.

6. MOTION OF PICKUP TOWARD RECORD PIN WILL NOT TRIP CHANGER MECHANISM.

a. It may be found that, instead of trigger being actuated, there is stretching of Swivel Spring 95 (joining the lugs at ends of Swivel Spreaders 90 and 91), allowing the spreaders to open. Increase tension of Spring 95, by bending slightly the lug on either spreader. If this increased tension causes needle to jump across the record, needle may be a little out of vertical, radially--it may "lean" toward center of record. To remedy this, grasp Pickup arm and twist it, very slightly, in a clockwise direction, so that it stands vertical, or even leans a little in outward direction.

b. If trigger is being properly actuated, probably Cam Lever 39 is binding against Sub-Plate 41. Look for dirt or obstructions; see that rivets are working freely. If the Lever engages Cam Lever Pawl 34, so that Lift 37 forces its roller up into the groove on Cam Gear 82, and if setscrews are tight, the change cycle must operate, as Cam Gear turns.

7. PRESSING "R" BUTTON DOESN'T TRIP CHANGER MECHANISM.

a. Check Key Control Unit 75: see whether there is an obstruction or a bent part which prevents "R" button from going clear down to the end of its travel.

b. Examine Reject Rod 78. If it does not trip, even when properly revolved by complete depressing of "R" button, the rod has probably been bent, and must be re-stored in same way. Grasp the two ends and twist it slightly.

c. If Trigger 16 is being properly actuated but without starting a change cycle, see directions above, Paragraph 6-b.

8. PRESSING "M" BUTTON FAILS TO PUT CHANGER MECHANISM OUT OF ACTION SO AS TO ENABLE MANUAL OPERATION. Check Key Control Unit as in preceding paragraph. First see that button goes clear down; then follow its action through Manual Rod 77.

9. MOTOR STOPS IMMEDIATELY WHEN CHANGER SWITCH IS TURNED OFF DURING A CHANGE CYCLE (instead of continuing to run, as it should, until needle is again upon a record, and then stopping). Or--

10. TURNING CHANGER SWITCH OFF FAILS TO STOP CHANGER AT ALL. Either of these two conditions would indicate failure of Cycling Switch 85. Cycling Switch operates normally to short-circuit the manual Changer Switch (which may be located in position shown at 54, or elsewhere) during change cycle only. Such damage to Cycling Switch (not likely to occur) would necessitate returning the entire Changer to factory.

11. CHANGER FAILS TO REPEAT LAST RECORD. See Paragraph 6, above.

12. NEEDLE LANDS PROPERLY ON RECORD BUT FAILS TO MOVE OVER INTO RECORD GROOVE. Pickup arm is normally impelled toward center of records by Lead Spring 97. Should a slight increase in its tension be found necessary, this can be easily obtained by bending the lug, to which it is attached, down against Main Plate. If tendency then appears for needle to jump across record, check angle of needle (see Paragraph 6-a above).

13. RECORDS FALL UNEVENLY UPON TURNTABLE. Seldom objectionable, this is due to Record Pin not being correctly centered between Posts. If necessary, it can be corrected as described above; see "Replacing Motor."

14. LAST RECORD DROPS ON ONE SIDE ONLY. This suggests a Post bent out of perpendicular to Main Plate. Test with square as directed (see "Replacing Motor"). If Post must be straightened, be careful not to bend other parts.

15. CHANGER CONTINUES CYCLING. Due to failure of Lift 37 to fall back out of engagement with Cam Gear. Check the various rivets at which motion occurs, to find the point where friction or binding is interfering with freedom of motion.

16. RECORD IS DRIVEN, BUT NOT HEARD, OR NOT HEARD WITH PROPER VOLUME. See that Pickup cord is plugged in. Check amplifier and speaker and connections to them, thoroughly. If then trouble is still suspected in pickup, test its output with a vacuum-tube voltmeter. Playing an average record, output should test 1 to 2.5 volts if pickup cartridge is of crystal type, or 0.5 volt if of magnetic type. If pickup cartridge is found not to deliver proper output, remove it and install another.

17. SELECTOR PLATE FAILS TO SEPARATE BOTTOM RECORD FROM STACK. This is due either to a badly warped condition of the record, or to its being of a thickness very considerably different from those now in standard use. The design of both Selector and Shelf Plates is such as to accommodate a maximum variation in thickness and flatness of records, but certain records may be found which are so far out as to be impracticable for use in automatic changers.

If Necessary to Disassemble the Changer


Before attempting to remove Sub-Plate Assembly 83, detach Key Control Unit 75 from Main Plate. To do this, start with Control Unit Truss Bar 80. Then take out the screw which holds left end of Adjusting Rod Lever 94. Next remove Adjusting Rod 92 and Adjusting Rod Extension 79. Take out the screw holding Spring 73; then the screws holding Key Control Unit 75 to Main Plate. Rods 77 and 78 can then, with due care, be extracted without bending. Free the Cam Connecting Rod 58 by loosening setscrew holding Spreader and Hub Assembly 59. Sub-Plate Assembly can then be detached without bending parts. In reassembling, reverse the procedure.

Replacement parts

When spare parts or sub-assemblies are required, order them direct from the factory, by number and name as given on photos. Where no number is given, order by full and exact description, specifying model on which part is to be used.

Questions Not Covered

The service mechanic should not hesitate to inquire of the factory regarding any difficulty encountered which does not seem to be covered by this Servicing Chart.



Typical Wiring Diagram

SERVICE MANUAL

1940 Models

6-MN-496 (DeLuxe AC4289)

6-MN-495 (Special AC4389)



Built for

NASH MOTORS

Division of Nash-Kelvinator Corp.
Kenosha, Wis.

Made by ZENITH RADIO CORPORATION, Chicago, Ill., U.S.A.

IMPORTANT — Be sure the warranty service tag is properly filled out and accompanies each receiver where free warranty service is expected by the customer or dealer.

**Zenith Model 6-MN-496
Nash DeLuxe AC4289**




Fig. 1. Tube and Trimmer Location

Tuning Range: 540 to 1580 K.C.

Sensitivity: 8 microvolts at 1 watt output

Power Output: 9 watts measured at the voice coil

Speaker: 2 full dynamic matched speakers

I.F.: 455 K.C.

Tube Complement: 6K7GT R.F. — 6SA7GT oscillator and modulator — 6K7GT I.F. — 6Q7GT 2nd Det. and A.V.C. — 2 6V6GT beam power push-pull output

Current Consumption: 8 amperes at 6 volts.

**Zenith Model 6-MN-495
Nash Special AC4389**




Fig. 2. Tube and Trimmer Location

Tuning Range: 540 to 1580 K.C.

Sensitivity: 10 microvolts at 1 watt output

Power Output: 3.5 watts measured at the voice coil

Speaker: Full size dynamic

I.F.: 455 K.C.

Tube Complement: 6K7GT R.F. — 6SA7GT oscillator and modulator — 6K7GT I.F. — 6Q7GT 2nd Det. and A.V.C. — 6K6GT Pentode Output — 6X5GT Rectifier.

Current Consumption: 6.8 amperes at 6 volts

We would suggest that the service man procure a $\frac{3}{8}$ " box wrench (small size) for removing the cap screws from the grille of the car. This may be purchased from any automotive supply store and is the only standard wrench which can be used when the receiver is to be removed from the car for service.

ALIGNMENT

The alignment of a receiver is one of the most important functions that a service man performs and the following instructions must be carefully followed for both models.

I.F. — The volume control is placed in the maximum position, and the tone control in the brilliant position for all the following adjustments:

A weak signal at 455 K.C. is fed directly into the grid cap of the 6K7GT R.F. tube through a .1 mfd condenser. The wave trap trimmer, E, (see Fig. 1 and 2) is adjusted for maximum response. The I.F. trimmers are then adjusted in the following order A, B, C and D, for greatest output. The signal level is then increased double or more and the wave trap trimmer, E, see Fig. 1 and 2, is adjusted to minimum response on the output meter.

IMPORTANT — Unless certain dummy antenna capacities are employed with either the signal generator, or in making the adjustments on stations, a receiver will not respond properly. The capacities provided in the Zenith dummy antenna part No. S7694 shown in Fig. 3 are identical with the conditions found in the Nash car, and if adjusted accordingly, the instrument will operate properly when reinstalled in the automobile. The Zenith dummy antenna is especially priced very low, and should be purchased at once for use in servicing the Zenith built Nash receiver.





Fig. 3. Dummy Antenna

R.F. — The tuning condenser is rotated until the plates are completely out of mesh (1580 K.C.) Set the signal generator to 1580 K.C. Remove the generator leads from the R.F. tube, remove the .1 mfd. condenser from the leads, and connect the leads to a Zenith dummy antenna, part No. S-7694 to the antenna socket on the receiver. The high frequency oscillator trimmer F (See Fig. 4) is then peaked for maximum response on the output meter. Reset the signal generator to 1400 K.C., rotate the tuning control until a signal is heard, and adjust the 1400 antenna trimmer G (Fig. 4) for maximum response.



NASH SPECIAL AC 4389
NASH DELUXE AC 4289
ZENITH 6MN495
ZENITH 6MN496

Fig. 4. Antenna Adjustment

Reset the signal generator to 600 K.C. and rotate the tuning control until a signal is heard. The condenser gang is then rocked slightly when adjusting the 600 K.C. oscillator padder H (see Fig. 4) to maximum resonance on the output meter.




Fig. 5.




Fig. 6.

Figures 5 and 6 show the voltage measured at the socket. The resistance measurements are shown on the schematics on the following pages. Figures 7 and 8 show how the dial cable is strung on both receivers.




Fig. 7.




Fig. 8.

AUTOMATIC TUNING — The automatic tuning mechanism, being entirely mechanical and extremely simple in construction, will require no attention except the original adjustments for the desired stations.

It consists of push rods which operate a cam and gear assembly which rotates the tuning condenser to any prearranged position. Each automatic button or push rod may be set for any station in the tuning range of the receiver.

To set the automatic buttons, first select six desired stations. Unscrew the left hand automatic button one-half turn and press all the way in. While holding the button in this position, manually tune in the selected station of lowest frequency. Then release the button and tighten. This button will then automatically tune this station whenever it is pushed in.

The same procedure should be followed on the five remaining buttons and stations. The station which has been tuned automatically will be indicated by the dial pointer.




Fig. 9. CIRCUIT DIAGRAM — MODEL 6-MN-496 (DeLuxe AC4289)




Fig. 10. CIRCUIT DIAGRAM — MODEL 6-MN-495 (Special AC4389)

PARTS PRICE LIST

ZENITH-NASH AUTOMOBILE RECEIVERS

Model	Nash No.	Zenith No.	Chassis No.	Code
Special	AC4389	6MN495	5673	S
DeLuxe	AC4289	6MN496	5676	D

TUNING UNIT ASSEMBLY

22-888	Two gang variable condenser (with pulley & gear)	SD..	\$2.75
26-230	Dial scale	SD..	.10
46-289	Automatic tuning knob & screw	SD..	.10
59-82	Dial pointer	SD..	.10
76-288	Tuning control shaft	SD..	.12
80-209	Dial cord tension spring	SD..	.02
80-210	Condenser gear spring	SD..	.005
93-125	No. 6 Shakeproof lockwasher	SD..	.25C
93-126	No. 8 Shakeproof lockwasher	SD..	.30C
100-36	Pilot lamp	SD..	.09
114-52	No. 8-32 x 3/16" Hex acorn head machine screw	SD..	.25C
114-63	No. 6-32 x 3/16" Hex acorn head machine screw	SD..	.20C
188-34	Retaining ring for 76-288	SD..	.10C
S7258	Automatic tuning unit mechanism	SD..	3.50
S7461	Dial cord & eyelet	SD..	.15
S7518	Dial light socket assembly	SD..	.35

COILS

20-213	Main hash choke	SD..	.20
20-214	Filament "A" choke	S	.10
20-219	Hash choke	D	.10
20-220	Hash choke	D	.10
S5844	Motor noise filter choke	SD..	.15
S6868	Antenna motor noise choke	SD..	.25
S7308	Antenna coil assembly (less shield)	SD..	.75
S7340	Oscillator coil assembly	SD..	.50
S7346	1st I F transformer assembly	SD..	1.35
S7359	2nd I F transformer assembly	SD..	1.35
S7367	R F coil assembly	SD..	1.50
S7388	R F "B" choke	D	.50

CONDENSERS

22-127	25 mmfd. 600 volt.	SD..	.15
22-162	.0001 mfd. 600 volt.	SD..	.15
22-170	.1 mfd. 400 volt.	SD..	.20
22-182	.00025 mfd. 600 volt.	SD..	.20
22-185	.01 mfd. 200 volt.	SD..	.15
22-212	.05 mfd. 400 volt.	SD..	.15
22-250	.05 mfd. 200 volt.	SD..	.15
22-289	50 mmfd. 600 volt.	D	.15
22-435	.02 mfd. 600 volt.	SD..	.15
22-838	.005 mfd. 600 volt.	SD..	.15
22-888	Two gang variable condenser	SD..	2.75
22-899	Trimmer condenser (Part of S7346 1st I F)	SD..	.25
22-900	Trimmer condenser (part of S7359 2nd I F)	SD..	.25
22-901	Trimmer condenser (part of S7367 R F coil)	SD..	.25
22-902	Oscillator padder condenser	SD..	.40
22-903	6.5 mmfd. ceramic condenser	SD..	.30
22-904	10 mfd. 400 volt — 10 mfd. 350 volt 20 mfd. 25 volt — dry electrolytic ..	S	1.15
22-905	.25 mfd. 200 volt.	SD..	.20
22-906	.005 mfd. 200 volt.	SD..	.15
22-907	.007 mfd. 1600 volt.	S	.20
22-908	.5 mfd. 120 volt.	SD..	.25
22-913	.007 mfd. 1600 volt.	D	.35
22-914	.05 mfd. 600 volt.	D	.20
22-917	20 mfd. 450 volt — 10 mfd. 400 volt 20 mfd. 25 volt — dry electrolytic ..	D	1.35

RESISTORS

63-271	1 megohm	1/4 watt.	SD..	\$.07
63-296	220M ohm	1/4 watt.	SD..	.07
63-593	47M ohm	1/4 watt.	D	.07
63-593	100M ohm	1/4 watt.	S	.07
63-596	330M ohm	1/4 watt.	SD..	.07
63-597	470M ohm	1/4 watt.	S	.07
63-604	10 Megohm	1/4 watt.	S	.07
63-632	560 ohm	1/4 watt.	D	.07
63-643	18M ohm	1/4 watt.	SD..	.07
63-646	33M ohm	1/4 watt.	D	.07
63-647	39M ohm	1/4 watt.	D	.07
63-649	56M ohm	1/4 watt.	D	.07
63-713	47M ohm	1/4 watt.	S	.15
63-732	27M ohm	1/4 watt.	S	.15
63-765	33M ohm	1/4 watt.	S	.15
63-941	390 ohm	1 watt.	D	.20
63-947	27M ohm	.2 watt.	SD..	.30
63-949	2200 ohm	.1 watt.	SD..	.20
63-968	1800 ohm	.2 watt.	SD..	.30
63-971	220 ohm	1/2 watt.	S	.08
63-975	82 ohm	1/2 watt.	D	.17
63-1024	350 ohm	1 watt.	S	.20
63-1040	Volume control-tone switch & shaft assembly		SD..	1.50

INTERNAL SPEAKER UNIT ASSEMBLY

24-217	Dial cover	SD..	.02
49-325	6" Dynamic speaker (less output transf.)	S	3.75
	207-325 field coil	S	2.00
	208-325 cone & voice coil	S	1.50
49-334	4" Dynamic speaker (less output transf.)	D	2.50
	207-334 field coil	D	1.00
	208-334 cone & voice coil	D	1.25
54-30	No. 3-32 x 5/16" Hex nuts	SD..	.25C
74-21	Speaker grill screen	S	.13
74-22	Speaker grill screen	D	.15
93-126	No. 8 Shakeproof lockwasher	SD..	.30C
94-307	Tuning shaft bushing	SD..	.08
94-308	Volume control shaft bushing	SD..	.08
112-246	No. 4 x 3/16" R.H. self-tapping screw ..	SD..	.35C
114-114	No. 8-32 x 1/2" Hex acorn head machine screw	SD..	.30C
192-45	Dial crystal	SD..	.05

MISCELLANEOUS

5-15	Bias cell	D	.15
12-702	Set mounting bracket	SD..	.05
46-290	Tuning control knob	SD..	.06
52-153	Battery cable (set to fuse)	SD..	.15
52-168	Battery cable (fuse to battery)	SD..	.25
78-208	Socket — external speaker plug	D	.10
78-275	Socket — electrolytic condenser	S	.02
78-276	Socket — tube 6K7GT	SD..	.10
78-277	Socket — tube 6SA7GT	SD..	.10
78-278	Socket — tube 6Q7GT	SD..	.10
78-281	Socket — vibrator	S	.10
78-283	Socket — antenna connector	SD..	.10
78-284	Socket — synchronous vibrator	D	.10
78-298	Socket — electrolytic condenser	D	.20C
95-613	Power transformer	S	2.50
95-615	Output transformer	S	1.00
95-617	Power transformer	D	2.50
95-618	Input transformer	D	1.65
95-619	Output transformer	D	1.00

PARTS LIST — cont'd

14-46	No. 6 x 3/16" Hex acorn head self-tapping screw	SD..	.30C
14-58	No. 6-32 x 3/8" Hex acorn head machine screw	SD..	.20C
14-109	No. 6 x 1/4" Hex acorn head self-tapping screw	SD..	.35C
32-18	Bias cell retainer.....	D..	.10
36-11	Fuse — 14 ampere.....	SD..	.03
59-37	Plug button (small).....	SD..	.03
59-38	Plug button (large).....	SD..	.03
90-15	Vibrator	S	2.25
90-16	Vibrator — synchronous.....	D..	3.25
902-139	Instruction book	SD..	.15
37472	Shield assembly (antenna coil).....	SD..	.12
37473	Volume control knob & set screw (46-291 73-26)	SD..	.15

FIREWALL SPEAKER ASSEMBLY (AC4289-6MN496)

13-40	Housing	D..	1.25
49-335	8" Dynamic speaker.....	D..	4.00
	207-335 Field coil.....	D..	2.00
	208-335 cone & voice coil.....	D..	2.00
52-170	Speaker cable	D..	.75
54-30	No. 8-32 x 5/16" Hex nuts.....	D..	.25C
74-23	Screen	D..	.50

93-126	No. 8 Shakeproof lockwasher.....	D..	.30C
112-130	Speaker mounting screws.....	D..	.75C
147-83	Brass spacers	D..	.02

SPEAKER INSTALLATION KIT

54-77	5/16"-18 x 1/2" Hex nuts.....	D..	.01
93-443	3/16" Internal-External shakeproof lockwasher	D..	1.50C
93-444	Steel washer		2.00C
97-110	Mounting stud		.10
147-80	Wood spacer		.10

INSTALLATION ACCESSORIES

22-919	Ammeter condenser	SD..	.35
22-920	Generator condenser	SD..	.40
54-132	7/16"-32 round nuts.....	SD..	.04
63-1046	Distributor suppressor	SD..	.25
68-2	Installation tool	SD..	.02
80-145	Motor Hood band spring.....	SD..	.02
112-243	Thumb screws	SD..	.03

All Prices List Subject to Regular Discount and Change Without Notice.

SERVICE NOTES



SERVICE MANUAL

Built for
FORD MOTOR CO.
Detroit, Mich.



Model
6MF490

Made by ZENITH RADIO CORPORATION, Chicago, Ill., U. S. A.

ELECTRICAL SPECIFICATIONS

Sensitivity—7 Micro-volts at one watt output. **Power Output**—4.5 watts measured at the voice coil. **Tuning Range**—540-1520 K.C. **Speaker**—full size electro-dynamic. **I.F.**—455 K.C. **Roto-matic tuning**—single button tuning for five stations. **Tube Complement**—7A7 R.F.; 7B8 Oscillator and Modulator; 7A7 I.F.; 7B6 second detector; and AVC; 7C5 Beam Power output; 7Y4 rectifier. **Current Consumption**—7 Amp.

Mr. Warranty Service Man:

The following information is furnished you so you may restore original performance to the Ford receiver.

The alignment procedure is new so study it carefully before trying to make any adjustments.

IMPORTANT:

Be sure the Warranty service tag is properly filled out and accompanying each receiver where free warranty service is expected by the customer or dealer.

NOTE:

This receiver is equipped with a fixed-variable sensitivity control located on the side of the chassis as shown in Fig. 3B. The control is set at the factory to a position which gives sensitivity of 7 micro-volts at one watt output. It is found advisable to hold the receiver at this level as any higher sensitivity may result in motor noise or excessive background noise and unless laboratory equipment is available for measuring sensitivity, it is not advisable to change this setting.

MANUAL DIAL CALIBRATION:

If the frequency of a station does not correspond with the dial reading, it may be corrected by holding the tuning control securely and turning the dial drum with the forefinger until it reads correctly.

SOCKET VOLTAGES:

Fig. 1 shows approximate voltages at the socket terminals. The resistance measurements are shown on the schematic on page 574.

ALL MEASUREMENTS
WITH 1000 OHM PER.
VOLT METER FROM
CHASSIS GROUND TO
POINT INDICATED

ANTENNA
DISCONNECTED
VOL. AT MIN.
BATTERY VOLTS-6




FIG. 1

ALIGNMENT:

The signal for the entire alignment procedure, both I.F. and R.F., is fed through a special Zenith dummy. Part number S7832. The capacities in the Zenith dummy antenna as shown in Fig. 2 are identical




FIG. 2

with the standard Ford antenna. If the Zenith dummy is not available at your Zenith distributor, you can substitute the values shown.

CAUTION:

Care should be taken while making all adjustments on the receiver to have the volume control turned full on. The intensity of the signal should be reduced only at the signal generator.

I.F.:

The tuning condenser is fully meshed (540 K.C.). The word "dial" must appear in the Roto-matic window. The signal generator is set at 455 K.C. and fed through the special Zenith antenna dummy to the receiver. The wave trap adjustment screw




FIG. 3A

A, see Fig. 3A-3B, is adjusted for maximum response. The adjusting screws B, C, D and E are then adjusted in order for maximum response on the output meter. (See Fig. 3A-3B.)

The wave trap A is then adjusted for minimum response.




FIG. 3B

R.F.:

The tuning control is rotated until the condenser plates are completely out of mesh (1520 K.C.). Set the signal generator




FIG. 4

to 1520 K.C. Adjust the 1520 K.C. trimmer shown in Fig. 4 for maximum response.

Set the signal generator to 1400 K.C. Ro-

tate the tuning control until the signal is heard and adjust the 1400 antenna trimmer (see Fig. 5), for maximum response.

Reset the signal generator to 600 K.C. and rotate the tuning control until a signal is heard. The condenser gang is then rocked slightly while adjusting the 600 K.C. padder (see Fig. 4) to maximum reading on the output meter.

The opening below the speaker on the front of the receiver is provided so that the output meter may be connected to the voice coil (see Fig. 6).

If you have the type of output meter which is usually connected to the plate of the output tube, it may be adapted for this type of connection by following the instructions shown in Fig. 7.




FIG. 5

ROTO-MATIC TUNING ADJUSTMENT:

The receiver should be turned on and allowed to warm up at least 30 minutes before the automatic tuning controls are adjusted.

It is essential that the adjusting screws be set on a weak signal in order to obtain accuracy and the maximum sensitivity. If




FIG. 6

the received signal is too strong, the antenna should be collapsed to its shortest position. The two screws which hold the escutcheon to the instrument panel are

justed to the desired station. The adjustment screw below 1 is then adjusted for maximum amount of signal.




FIG. 7

Number 1 on the adjustment screw (see Fig. 5) corresponds to Fig. 1 on the Roto-matic tuner. For stations 2, 3, etc., on the Roto-matic tuner, set the adjusting screws 2 and 3, the same as for station 1.

IMPORTANT:

The above procedure should be repeated after the entire five stations are set. This is necessary to make sure that the adjustment screws are peaked for maximum performance.




FIG. 8

now removed (see Fig. 8). The escutcheon plate is removed, making the adjustment screws accessible. They are then adjusted in the following order:

For a station close to 580 K.C. the adjustment screw over 1 (see Fig. 5) is first ad-

If difficulty is experienced in setting up the adjusting screws for a desired station, first turn the bottom adjustment screw down tight and then adjust the top screw to the station and follow with an adjustment of the bottom screw for greatest volume.

MODEL 6MF490

FORD ROTO-MATIC

O1A—18805

MANUAL TUNING ASSEMBLY

12-737	Bracket—condenser mounting	\$0.10
12-738	Bracket—dial drum support	.04
22-949	Condenser—two gang variable	2.25
26-237	Scale—manual tuning	.05
34-91	Gear—idler	.04
34-94	Gear—clutch	.12
35-4	Drum—manual tuning	.12
46-307	Knob—manual tuning control	.20
80-217	Spring—for 34-91 gear	.25 C
80-213	Spring—for 34-94 clutch	.01
93-125	No. 6 Shakeproof lockwasher	.25 C
94-313	Bushing—dial drum	.03
94-317	Bushing—condenser mounting	.02
97-130	Stud—dial drum retaining	.06
97-133	Stud—tuning knob retaining	.08
112-38	Screws—No. 6-32 x $\frac{1}{8}$ " for studs	.25 C
114-63	Screws—No. 6-32 x $\frac{1}{8}$ " Hex acorn head	.25 C
114-67	Screws—No. 6-32 x $\frac{1}{8}$ " Hex acorn head	.35 C
125-24	Rubber grommet for mounting condenser	.015
188-34	Retaining ring	.01
S7828	Bracket and stud for idler gear	.10

VOLUME CONTROL ASSEMBLY

22-906	Condenser—.005 mfd. 200 volts	.15
34-92	Gear—volume control shaft	.08
34-93	Gear—idler	.04
46-306	Knob—volume control	.20
54-62	Nut— $\frac{3}{8}$ "-32 x $\frac{1}{8}$ " Hex	1.25 C
63-592	Resistor—33M ohms $\frac{1}{4}$ watt	.07
63-1073	Volume control	1.50
93-125	No. 6 Shakeproof lockwasher	.25 C
93-143	$\frac{3}{8}$ " Shakeproof lockwasher	.40 C
93-455	Insulating washer for volume control	.01
94-314	Bushing—for 46-306 knob	.45 C
97-134	Stud—for 46-306 knob	.07
112-38	Screw—No. 6-32 x $\frac{1}{8}$ " Binding head N. P.	.25 C
112-207	Screw—No. 4-40 x $\frac{1}{8}$ " Binding head brass ...	.03
188-34	Retaining ring	.01
S7839	Bracket and stud for idler gear	.10

AUTOMATIC TUNING COIL ASSEMBLY

S6226	Adjustment screw and bushing	.25
S7745	Automatic coil (red)	.20
S7746	Automatic coil (green)	.20
S7747	Automatic coil (yellow)	.20
S7748	Automatic coil (blue)	.20
S7749	Automatic coil (white)	.20
S7822	Mounting bracket and terminal strip	.15
22-947	Trimmer condenser (6 section)	1.00
54-124	No. 12-32 x $\frac{3}{8}$ " Hex nut	.30 C
80-214	Spring	.02
83-734	Armit strip	.005
93-125	No. 6 Shakeproof lockwasher	.25 C
93-372	No. 12 Shakeproof lockwasher	.50 C
112-82	No. 6-32 x $\frac{1}{8}$ " Binding head machine screw N. P.	.40 C

AUTOMATIC TUNING

SWITCH AND DRUM ASSEMBLY

12-742	Bracket—condenser locking	.03
22-162	Condenser—.0001 mfd. 600 volt	.15

22-983	Condenser—oscillator padder	.35
26-236	Scale—automatic tuning	.04
35-3	Drum—automatic dial	.12
46-309	Switch knob	.03
85-207	Switch—automatic	1.65
93-125	No. 6 Shakeproof lockwasher	.25 C
93-149	Washer—fibre	.65 M
94-315	Bushing—dial drum	.04
97-131	Stud—dial drum retaining	.08
112-38	Screw—No. 6-32 x $\frac{1}{8}$ " Binding head	.25 C
114-113	Screw—No. 6-32 x $\frac{3}{4}$ " Hex acorn head S. B.	.40 C

COILS

20-213	Main hash choke	.20
20-217	Heater line hash choke	.15
S6868	Motor noise choke coil	.25
S7544	Manual oscillator coil assembly	
S7572	R.F. coil and shield assembly	1.75
S7573	1st I.F. transformer	1.35
S7574	2nd I.F. transformer	1.35
S7588	Antenna coil—less shield	.75
S7760	Motor noise choke	.25

SPEAKER COVER ASSEMBLY

49-341	7" Dynamic speaker	4.00
	*207-341 field coil	2.00
	*208-341 cone and voice coil	2.00
	*Note—when ordering field coil or cone assy. give complete number and letters shown on part.	
54-30	No. 8-32 x $\frac{1}{8}$ " Hex nut	.25 C
78-300	Socket and bracket—dial lamp	.10
78-302	Socket and bracket—dial lamp	.10
80-141	Spring for socket	.30 C
83-724	Pin jack terminal strip	.15
85-208	Switch—tone control	.20
93-337	Washer for socket	.35 C
94-252	Bushing for socket	.02
100-36	Pilot lamp	.09
114-111	No. 8-32 x $\frac{1}{2}$ " Hex acorn head machine screw S.B.	.45 C
126-349	Shield for pilot lamp	.015
196-27	Rubber gasket for speaker grille	.45

CONDENSERS

22-82	.001 mfd. moulded condenser—600 volt	.20
22-127	.25 mfd. moulded condenser—600 volt	.15
22-162	.0001 mfd. moulded condenser—600 volt	.15
22-170	.1 mfd. tubular condenser—400 volt	.20
22-182	.00025 mfd. moulded condenser—600 volt	.20
22-185	.01 mfd. tubular condenser—200 volt	.15
22-190	.1 mfd. tubular condenser—200 volt	.18
22-212	.05 mfd. tubular condenser—400 volt	.15
22-250	.05 mfd. tubular condenser—200 volt	.15
22-271	Voltage regulator condenser	.50
22-435	.02 mfd. tubular condenser—600 volt	.15
22-497	Oil gauge condenser	.50
22-782	.012 mfd. tubular condenser—800 volt	.15
22-899	1st I.F. transformer trimmer condenser	.25
22-900	2nd I.F. transformer trimmer condenser	.20
22-901	R.F. coil trimmer condenser	.25

1-906	.005 mfd. tubular condenser—200 volt.....	.15
1-908	.5 mfd. tubular condenser—120 volt.....	.25
1-947	Multiple section trimmer condenser.....	1.00
1-949	Two gang variable condenser.....	2.25
1-955	10 mfd. dry electrolytic—400 volt.....	
	10 mfd. dry electrolytic—350 volt.....	
	20 mfd. dry electrolytic—25 volt.....	1.25
2-956	500 mmfd. Silvercap condenser.....	.35
2-957	.02 mfd. tubular condenser—600 volt.....	.25
2-963	.005 mfd. tubular condenser—600 volt.....	.15
2-971	Distributor condenser	.35
2-983	Oscillator padder condenser.....	.35

RESISTORS

3-271	1 megohm— $\frac{1}{4}$ watt.....	.07
3-296	220M ohm— $\frac{1}{4}$ watt.....	.07
3-410	1200 ohm— $\frac{1}{4}$ watt.....	.07
3-584	1500 ohm— $\frac{1}{4}$ watt.....	.07
3-590	15M ohm— $\frac{1}{4}$ watt.....	.07
3-592	33M ohm— $\frac{1}{4}$ watt.....	.07
3-593	47M ohm— $\frac{1}{4}$ watt.....	.07
3-595	100M ohm— $\frac{1}{4}$ watt.....	.07
3-695	47 ohm— $\frac{1}{4}$ watt.....	.15
3-717	220M ohm— $\frac{1}{4}$ watt.....	.15
3-719	470M ohm— $\frac{1}{4}$ watt.....	.15
3-738	560 ohm— $\frac{1}{4}$ watt.....	.15
3-947	27M ohm—2 watt.....	.30
3-948	330 ohm—1 watt.....	.20
3-968	1800 ohm—2 watt.....	.30
3-971	220 ohm— $\frac{1}{2}$ watt.....	.08
3-972	15M ohm—1 watt.....	.20
3-994	Sensitivity control	1.00
3-1059	39M ohm— $\frac{1}{2}$ watt.....	.17
3-1073	Volume control and switch.....	1.50

MISCELLANEOUS

52-153	Battery cable—set to fuse.....	.15
52-154	Battery cable—fuse to ammeter.....	.15
54-134	Antenna connector retaining nut.....	.015
57-785	Escutcheon plate	.35
78-281	Socket—vibrator	.10
78-294	Socket—locktal tubes	.15
93-456	Cushion washer—vibrator	.015
95-640	Output transformer	1.10
95-641 $\frac{1}{2}$	Power transformer	2.50
112-239	No. 4-36 x $\frac{1}{4}$ " oval binding head screw S.B....	.20 C
112-256	Set mounting screw.....	.01
114-46	No. 6 x $\frac{1}{8}$ " Hex acorn head self tapping screw	.30 C
114-109	No. 6 x $\frac{1}{4}$ " Hex acorn head self tapping screw	.35 C
114-110	No. 4-40 x $\frac{7}{32}$ " Hex head slotted screw.....	.40 C
114-112	No. 6-32 x $\frac{1}{2}$ " Hex acorn head machine screw	.50 C
125-17	Rubber grommet	.015
125-24	Rubber grommet	.015
136-11	Fuse—14 ampere	.06
159-37	Plug button	.03
190-15	Vibrator	2.95
196-28	Gasket for escutcheon.....	.02
202-159	Owners manual	.10
S7701	Antenna connector assembly.....	.25
S7823	Power pack shield.....	.40
S7832	Dummy antenna	
S7837	Sensitivity control and bracket (63-994).....	1.00
S7787	Condenser kit	
	22-271 voltage regulator condenser.....	.45
	22-497 oil gauge condenser.....	.40
	22-971 distributor condenser	.35
S7846	Installation kit	
	54-123 No. 10-24 wing nuts.....	.02
	94-312 Antenna connector insulating bushing..	.04
	97-127 Antenna connector stud.....	.30
	112-256 Hook mounting screw.....	1.20 C

*All Price Lists Subject to Regular Discount and
Change Without Notice*

SERVICE MANUAL



1940 RECEIVERS

Model	Chassis	Page	Model	Chassis	Page
4B422	5417	580	7S461	5724	594
4B437	5417	580	7S432	5724	594
4B466	5417	580	7S487	5725	596
4B468	5417	580	7S488	5725	596
4K422	5420	582	7S490	5725	596
4K435	5420	582	8S443	5808	598
4K465	5420	582	8S451	5808	598
4K466	5420	582	8S463	5808	598
5G438	5536	584	10S443	1005	600
5G467	5536	584	10S452	1005	600
6J436	5679	592	10S464	1005	600
6J463	5679	592	10S470	1005	600
6R481	5675	588	10S491	1005	600
6R485	5672P	586	10S492	1005	600
6S439	5678	590	11S474	1103	602
6S469	5678	590	12S445	1207	604
7S432	5724	594	12S453	1207	604
7S433	5724	594	12S471	1207	604
7S434	5724	594	12S475	1207	604
7S449	5724	594	12S494	1207	604
7S450	5724	594	15S479	1503	606
7S458	5724	594	15S495	1503	606
7S459	5724	594	Phono Circuits		608
7S460	5724	594	Service Notes		578
			Parts List		609

SEE FORM H5R FOR 1940 ADVANCE LINE DATA

ZENITH RADIO CORPORATION

CHICAGO, U.S.A.

ALIGNMENT INSTRUCTIONS

The proper procedure for the correct alignment of each chassis is outlined on the page opposite each circuit diagram.

In order to obtain proper alignment of the chassis when using a wavemagnet the signal generator should be coupled to the wavemagnet by means of a single turn loop approximately one foot in diameter. The leads of the signal generator may be connected together forming a satisfactory loop which should be placed about two feet from the receiver.

The chassis drawing shows all trimmers to correspond to the alignment chart. Corresponding letters are also shown adjacent to each trimmer on the circuit diagrams.

The operations are outlined in consecutive order, and the instructions are under the following headings —

OSC. CONNECTED TO — tells where the output of the service oscillator is to be connected.

DUMMY — gives the proper capacity or resistance which should be connected in series with the service oscillator output.

INPUT SIGNAL FREQUENCY — Set test oscillator to frequency shown.

BAND — Set the receiver band switch to the position shown.


DIAL — The receiver should be set at the frequency shown.

TRIMMER — This column tells which trimmer (or trimmers) are to be adjusted for each operation. The chassis drawing has each trimmer indicated by a letter corresponding to the instructions.

PURPOSE — This column tells what is being accomplished by each operation.

If these instructions are carefully followed each chassis will be easily and correctly realigned.

The use of a wavemagnet requires two adjustments for each automatic button. These adjustments are made with a special wrench (part No. 68-1) supplied with each receiver. The center or screw adjustment controls the oscillator circuit and the nut tunes the wavemagnet or antenna input — see illustration at right.



VOLTAGE CHARTS

The voltages appearing on each socket contact are shown on the chassis drawings. Voltages are measured with a 1000 ohm per volt meter and allowance should be made for variations in line voltage or if a voltmeter of different rating is used in making tests.

SERVICE NOTES

GENERAL:

Noisy when jarred — orange resistor on loop loading coil grounding against chassis.

Broken or loose leads in 6U5 socket.

Black wire on S.W. antenna coil not grounded properly to aeroplane terminal.

Noisy wavemagnet—rubber insulation of loop lead touching trimmer lug, antenna terminal, or other end of loop winding. Noise will be most noticeable at higher frequencies.

Poor connection to loop shields.

CHASSIS 5808 — 1005 — 1103

Oscillates at 550 K.C.—improper adjustment of wave trap—too high resistance in plate circuit of 1232 tube.

Automatic dead or antenna trimmer won't peak—usually due to open winding on compensating coil.

SERVICE NOTES — (Continued)

Noisy tuning—Ground braid of gang rubbing against flywheel—Burrs on drive shaft shorting to volume control shaft.

Dial pulley rubbing against dial or chassis.

Tuning Indicator inoperative—resistor inside socket shorting to socket prong—loose lead in socket—cathode lug on voltage divider grounded by solder.

Set blocks—usually due to broken resistor in A.V.C. circuit of first detector.

CHASSIS 5724 — 5725

Noisy tuning on automatic.

Poor contact in speaker socket.

Washer on latch bar grounding lug.

Poor contact on band switch.

Aeroplane lug on automatic grounding to No. 5 push rod.

Automatic trimmer shorting.

Signal cuts out above 1400 K.C.

5 megacycle trimmer screwed in too tight.

Signal cuts out on local—distance switch.

Defective 6A8 tube.

No change on treble button.

Insulation of blue tone control lead cut by fastening lug.

Weak audio.

Poor contact in television switch.

Open coupling condenser.

Oscillates.

Open screen bypass.

Grid lead of 6K7 near A.V.C. lug or near plate lead of 6A8.

Wave trap open or not properly adjusted.

PHONO MODELS


Insensitivity—check phono switch and plug contacts.

Weak phono—check shield on lead from crystal for poor ground.

1205 — 1503 CHASSIS

Improper action of volume control is usually caused by 6J5G in audio stage.

Poor radiorgan action is often caused by defective 6F8G in audio.



MODEL SPEAKER
 4B422 49-345 5"
 4B437 49-328 6½"
 4B466 49-342 10"
 4B468 49-359 8"

I.F. FREQUENCY 455 KC.
 4 TUBE SUPERHETERODYNE
 CHASSIS N° 5417-6V.-SINGLE BAND
 ZENITH RADIO CORPORATION
 CHICAGO, ILL.

DIAG. N°	PART N°	DESCRIPTION	DIAG. N°	PART N°	DESCRIPTION	DIAG. N°	PART N°	DESCRIPTION
C 1	22-695	TWO GANG VARIABLE	R 2	63-595	100M OHM	1	20-208	ANTENNA COIL ASSEMBLY
C 2	22-826	0.1 MFD.	R 3	63-594	68M OHM	2	5-6381	OSCILLATOR COIL ASSEM
C 3	22-829	0.5 MFD.	R 4	63-583	1000 OHM	3	95-589	1ST I.F. TRANS.
C 4	22-162	0.001 MFD.	R 5	63-296	220M OHM	4	95-590	2ND I.F. TRANS.
C 5	22-828	0.5 MFD.	R 6	63-669	39 MEGOHM	5	180-17	VIBRATOR
C 6	22-199	5 MFD.	R 7	63-593	47M OHM	6	95-635	POWER TRANSFORMER
C 7	22-243	0.1 MFD.	R 8	63-1079	VOLUME CONTROL	7	5-5043	CHOKE ASSEMBLY
C 8	22-448	0.04 MFD.	R 9	63-604	10 MEGOHM			
C 9	22-966	0.04 MFD.	R 10	63-271	1 MEGOHM			
C 10	22-966	500 MFD. ELECTROLYTIC	R 11	63-600	2.2 MEGOHM	A	1E1	I.F. TRANS. PRI.
C 11	22-742	15 MFD.	R 12	63-1060	90 OHM WIREWOUND	B	1E1	I.F. TRANS. SEC.
C 12	22-742	15 MFD.	R 13	63-577	100 OHM	C	2ND	I.F. TRANS. PRI.
C 13	22-742	15 MFD.	R 14	63-697	100 OHM	D	2ND	I.F. TRANS. SEC.
			R 15	63-605	1000 OHM	F	BDCAST	OSC. (ON GANG)
			R 16	63-1061	7 OHM	G	ANT. BDCAST	(ON GANG)
R 1	63-597	470M OHM						

Models 4B422—4B437—4B466—4B468

Chassis No. 5417

Models 4B422—4B437—4B466—4B468

CHASSIS No. 5417

NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contacts.

Voltage readings are all positive D.C. unless otherwise indicated.

Antenna disconnected volume control full on.

Battery voltage 6 volt.

Battery consumption — .4 ampere.

LEGEND

D—Diode

F—Filament

G1—Control Grid

G2—Screen Grid


P—Plate

CONVERTER

1A7G

I. F.


1N5G



BOTTOM VIEW OF CHASSIS

FRONT OF CHASSIS


Socket Voltages



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	1A7 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	Antenna	200 Mmf.	1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
3	Antenna	200 Mmf.	1400 Kc.	Broadcast	1400 Kc.	G	Alignment of Antenna



Models 4K422—4K435—4K465—4K466

Chassis No. 5420


NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contacts using a fresh Z28 battery pack.

Antenna disconnected — volume control full on.


LEGEND

F—Filament
D—Diode
G1—Control Grid
G2—Screen Grid
P—Plate



FRONT OF CHASSIS


Socket Voltages



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	1A7 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	Antenna	200 Mmf.	1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
3	Antenna	200 Mmf.	1400 Kc.	Broadcast	1400 Kc.	G	Alignment of Scale



PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
C1	22-500	R1	63-537	1	20-808	ANTENNA COIL	
C2	22-196	R2	63-652	2	5-6381	OSC. COIL ASSEMBLY	
C3	22-929	R3	63-713	3	95-593	1ST I.F. TRANS.	
C4	22-182	R4	63-296	4	95-594	2ND I.F. TRANS.	
C5	22-350	R5	63-669	5	85-187	1ST I.F. TRANS.	
C6	22-162	R6	63-591	6	85-198	POWER SWITCH	
C7	22-926	R7	63-583	A	1ST I.F. TRANS.	PRI.	
C8	22-887	R8	63-604	B	1ST I.F. TRANS.	SEC.	
C9	22-243	R9	63-271	C	2ND I.F. TRANS.	PRI.	
C10	22-448	R10	63-600	D	2ND I.F. TRANS.	SEC.	
C11	22-928	R11	63-600	E	3RD I.F. TRANS.	PRI.	
C12	22-879	R12	63-600	F	3RD I.F. TRANS.	SEC.	
C13	22-879	R13	63-600	G	ANTENNA 20-CAST (ON GANG)		
C14	22-869	R14	63-602				
C15	22-869						
C16	22-138						

Models 5G488—5G467

Chassis No. 5536

CHASSIS No. 5536


NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.

All voltages are positive D.C.
unless marked otherwise.

Volume control on full.


Line voltage 112 v. A.C.



Socket Voltages

LEGEND

- F—Filament
H—Heater
D—Diode
G1—Control Grid
G2—Screen Grid
G3—Suppressor Grid
P—Plate
K—Cathode



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	1A7 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	Antenna	200 Mmf.	1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
3	Antenna		1400 Kc.	Broadcast	1400 Kc.	G	Alignment of Antenna

CHASSIS No. 5672P

NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.


All voltages are positive D.C.
unless marked otherwise.

Volume control on full.


Line voltage 112 v. A.C.

LEGEND

F—Filament
H—Heater
D—Diode
G1—Control Grid
G2—Screen Grid
G3—Suppressor Grid
P—Plate
K—Cathode



Socket Voltages



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	.5 Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, D	I. F. Alignment
2	Single Turn Loop Loosely Coupled to Wave Magnet	—	1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
3		—	1500 Kc.	Broadcast	1500 Kc.	G	Alignment of Antenna

Model 6R481
CHASSIS No. 5675

NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.


All voltages are positive D.C. unless marked otherwise.

Volume control on full.


Line voltage 120 A.C.

LEGEND

F—Filament
H—Heater
D—Diode
G1—Control Grid
G2—Screen Grid
G3—Suppressor Grid
P—Plate
K—Cathode




Socket Voltages



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	12A8 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, D	I. F. Alignment
2	Single Turn Loosely		1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
3	Coupled to Loop		1500 Kc.	Broadcast	1500 Kc.	G	Alignment of Antenna



PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
C1 22-849	2 GANG VARIABLE	R16 63-1026	250 OHM WIREWOUND	D46 100-36	PILOT LIGHT 6.3V 25A		
C2 22-162	0001 MFD	R17 63-151	15 M OHM				
C3 22-829	05 MFD	R18 63-339	15 MEG OHM	A	1E I.F. TRANS PRI		
C4 22-826	0005 MFD	R19 63-339	15 MEG OHM	B	1E I.F. " SEC		
C5 22-826	0005 MFD	R20 63-339	100 OHM	C	250 I.F. " SEC		
C6 22-289	50 M MFD	R21 63-585	2500 OHM	D	250 I.F. T.O. P		
C7 22-182	00025 MFD			E	ANTENNA BROADCAST		
C8 22-830	02 MFD			F	SHORT WAVE DET		
C9 22-219	03 MFD			G	POLICE BAND OSC (-)		
C10 22-229	0005 MFD			H	ADZE		
C11 22-975	10 MFD ELECTROLYTIC			I	TRIMMERS 500 M		
C12 22-975	10 MFD ELECTROLYTIC			J	ARE MOUNTED ON		
C13 22-975	10 MFD ELECTROLYTIC			K	STRAP #22-850		
C14 22-448	004 MFD			L			
C15 22-448	004 MFD			N			
C16 22-150	002 MFD						
C17 22-150	002 MFD						
C18 22-868	COMPENSATING COND						
C19 22-853	DUAL OSC PADDER						

Models 6S439—6S469

Chassis No. 5678

MODEL
6S439
6S469


SPEAKER
49-364 6"
49-344 10"

I.F. FREQUENCY 455 KC.
6 TUBE SUPERHETERODYNE
CHASSIS NO. 5678 3BAND
ZENITH RADIO CORPORATION
CHICAGO, ILL.

PWR.-AMP.

Line voltage 112 A.C.

FRONT OF CHASSIS



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	6A8 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	R. F. 6K7 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	E	Adjust Wavetrap for Minimum
3	Antenna Post (On Loop)	400 Ohms	18000 Kc.	S. W.	18000 Kc.	K	Set Oscillator to Scale
4	Antenna Post (On Loop)	400 Ohms	16000 Kc.	S. W.	16000 Kc.	L	Rock Gang and Adjust for Max.
5	Antenna Post (On Loop)	400 Ohms	4500 Kc.	Police	4500 Kc.	N	Rock Gang and Adjust for Max.
6	Generator Loosely Coupled to Loop		1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
7	Thru One or Two Turns		1400 Kc.	Broadcast	1400 Kc.	G	Alignment of Antenna

Models 6J436—6J463

CHASSIS No. 5679

NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.

All voltages are positive D.C. unless marked otherwise.


Battery conserver switch in **NORMAL** position.

Volume control full on.


Line voltage 112 v. A.C.

LEGEND

- F—Filament
- H—Heater
- D—Diode
- G1—Control Grid
- G2—Screen Grid
- G3—Suppressor Grid
- P—Plate
- K—Cathode



Socket Voltages



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	6D8 R. F. Grid	0.5 Mfd.	455 Kc.	I. F.	600 Kc.	A, B, C, D	I. F. Alignment
2	Rec. Ant. Post	200 Mfd.	1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
3	Rec. Ant. Post	200 Mfd.	1500 Kc.	Broadcast	1500 Kc.	G	Alignment of Antenna
4	Rec. Ant. Post	200 Mfd.	600 Kc.	Broadcast	600 Kc.	J	Rock Gang and Adjust for Max. Output
5	Rec. Ant. Post	200 Mfd.		Broadcast		F, G	Repeat 2 and 3
6	Rec. Ant. Post	400 Ohms	18000 Kc.	S. W.	18000 Kc.	M	Rock gang & adj. for max. output
7	Rec. Ant. Post	400 Ohms	16000 Kc.	S. W.	16000 Kc.	L	Rock Gang and Adjust for Max. Output
8	Rec. Ant. Post	400 Ohms	6000 Kc.	Police	6000 Kc.	N	Rock Gang and Adjust for Max. Output

CHASSIS No. 5724


NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.

All voltages are positive D.C. unless marked otherwise.

Volume control full on.



Line voltage 112 A.C.



Socket Voltages

LEGEND


- F—Filament
- H—Heater
- D—Diode
- G1—Control Grid
- G2—Screen Grid
- G3—Suppressor Grid
- P—Plate
- K—Cathode



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	6A8 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	R. F. 6K7 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	E	Adjust Wavetrap for Minimum
3	Antenna Post (On Loop)	400 Ohms	18000 Kc.	S. W.	18000 Kc.	K	Set Oscillator to Scale
4	Antenna Post (On Loop)	400 Ohms	16000 Kc.	S. W.	16000 Kc.	L	Rock Gang and Adjust for Max.
5	Antenna Post (On Loop)	400 Ohms	4500 Kc.	Police	4500 Kc.	N	Rock Gang and Adjust for Max.
6	Generator Loosely Coupled to Loop		1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
7	Thru One or Two Turns		1400 Kc.	Broadcast	1400 Kc.	G	Alignment of Antenna




CHASSIS No. 5725

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.



Volume control full on.

Line voltage 112 A.C.




LEGEND

F—Filament
H—Heater
D—Diode
G1—Control Grid
G2—Screen Grid
G3—Suppressor Grid
P—Plate
K—Cathode




Location of Tubes and Trimmers



ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	6A8 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	R. F. 6K7 Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	E	Adjust Wavetrap for Minimum
3	Antenna Post (On Loop)	400 Ohms	18000 Kc.	S. W.	18000 Kc.	K	Set Oscillator to Scale
4	Antenna Post (On Loop)	400 Ohms	16000 Kc.	S. W.	16000 Kc.	L	Rock Gang and Adjust for Max.
5	Antenna Post (On Loop)	400 Ohms	4500 Kc.	Police	4500 Kc.	N	Rock Gang and Adjust for Max.
6	Generator Loosely Coupled to Loop		1500 Kc.	Broadcast	1500 Kc.	F	Set Oscillator to Scale
7	Thru One or Two Turns		1400 Kc.	Broadcast	1400 Kc.	G	Alignment of Antenna




CHASSIS No. 5808
RECTIFIER
6X5G

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.

Sensitivity switch in distance position.


Line voltage 112 A.C.



FRONT OF CHASSIS

Socket Voltages


F—Filament
H—Heater
D—Diode
G1—Control Grid
G2—Screen Grid
G3—Suppressor Grid
P—Plate
K—Cathode



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

599



MODEL 10S443 10S452 10S470 10S464 10S491 10S492

* SPEAKER 49-346 8" 49-351 10" 49-353 12" 49-379 10" 49-356 15" 49-352 12"

I.F. FREQUENCY 455 KC.
10 TUBE SUPERHETERODYNE
CHASSIS N21005 AC 3 BAND
ZENITH RADIO CORPORATION
CHICAGO, ILL.

⊥ DENOTES CHASSIS 'GROUND'

BAND SWITCH SHOWN IN "POLICE" POSITION

DATE	PART NO.	DESCRIPTION	DATE	PART NO.	DESCRIPTION	DATE	PART NO.	DESCRIPTION
C1	22-927	TWO GANG VARIABLE	C22	22-356	.002 MFD.	R16	63-438	22 M OHM
C2	22-879	.05 MFD.	C23	22-810	DUAL OSC. PADDER	R17	63-876	27 M OHM
C3	22-879	.05 MFD.	C24	22-810	DUAL OSC. PADDER	R18	63-876	27 M OHM
C4	22-879	.05 MFD.	C25	22-810	DUAL OSC. PADDER	R19	63-876	27 M OHM
C5	22-441	.005 MFD.	C26	22-745	.0001 MFD.	R20	63-107	10 M OHM
C6	22-127	.83 MFD.	C27	63-554	68 M OHM	R21	63-554	68 M OHM
C7	22-028	.00025 MFD.	C28	63-554	150 M OHM	R22	63-554	150 M OHM
C8	22-171	.01 MFD.	C29	63-554	150 M OHM	R23	63-554	150 M OHM
C9	22-171	.01 MFD.	C30	63-554	150 M OHM	R24	63-554	150 M OHM
C10	22-239	.02 MFD.	C31	63-554	150 M OHM	R25	63-554	150 M OHM
C11	22-446	.005 MFD.	C32	63-554	150 M OHM	R26	63-554	150 M OHM
C12	22-446	.005 MFD.	C33	63-554	150 M OHM	R27	63-554	150 M OHM
C13	22-446	.005 MFD.	C34	63-554	150 M OHM	R28	63-554	150 M OHM
C14	22-446	.005 MFD.	C35	63-554	150 M OHM	R29	63-554	150 M OHM
C15	22-446	.005 MFD.	C36	63-554	150 M OHM	R30	63-554	150 M OHM
C16	22-446	.005 MFD.	C37	63-554	150 M OHM	R31	63-554	150 M OHM
C17	22-446	.005 MFD.	C38	63-554	150 M OHM	R32	63-554	150 M OHM
C18	22-446	.005 MFD.	C39	63-554	150 M OHM	R33	63-554	150 M OHM
C19	22-446	.005 MFD.	C40	63-554	150 M OHM	R34	63-554	150 M OHM
C20	22-446	.005 MFD.	C41	63-554	150 M OHM	R35	63-554	150 M OHM
C21	22-446	.005 MFD.	C42	63-554	150 M OHM	R36	63-554	150 M OHM
C22	22-446	.005 MFD.	C43	63-554	150 M OHM	R37	63-554	150 M OHM
C23	22-446	.005 MFD.	C44	63-554	150 M OHM	R38	63-554	150 M OHM
C24	22-446	.005 MFD.	C45	63-554	150 M OHM	R39	63-554	150 M OHM
C25	22-446	.005 MFD.	C46	63-554	150 M OHM	R40	63-554	150 M OHM
C26	22-446	.005 MFD.	C47	63-554	150 M OHM	R41	63-554	150 M OHM
C27	22-446	.005 MFD.	C48	63-554	150 M OHM	R42	63-554	150 M OHM
C28	22-446	.005 MFD.	C49	63-554	150 M OHM	R43	63-554	150 M OHM
C29	22-446	.005 MFD.	C50	63-554	150 M OHM	R44	63-554	150 M OHM
C30	22-446	.005 MFD.	C51	63-554	150 M OHM	R45	63-554	150 M OHM
C31	22-446	.005 MFD.	C52	63-554	150 M OHM	R46	63-554	150 M OHM
C32	22-446	.005 MFD.	C53	63-554	150 M OHM	R47	63-554	150 M OHM
C33	22-446	.005 MFD.	C54	63-554	150 M OHM	R48	63-554	150 M OHM
C34	22-446	.005 MFD.	C55	63-554	150 M OHM	R49	63-554	150 M OHM
C35	22-446	.005 MFD.	C56	63-554	150 M OHM	R50	63-554	150 M OHM
C36	22-446	.005 MFD.	C57	63-554	150 M OHM	R51	63-554	150 M OHM
C37	22-446	.005 MFD.	C58	63-554	150 M OHM	R52	63-554	150 M OHM
C38	22-446	.005 MFD.	C59	63-554	150 M OHM	R53	63-554	150 M OHM
C39	22-446	.005 MFD.	C60	63-554	150 M OHM	R54	63-554	150 M OHM
C40	22-446	.005 MFD.	C61	63-554	150 M OHM	R55	63-554	150 M OHM
C41	22-446	.005 MFD.	C62	63-554	150 M OHM	R56	63-554	150 M OHM
C42	22-446	.005 MFD.	C63	63-554	150 M OHM	R57	63-554	150 M OHM
C43	22-446	.005 MFD.	C64	63-554	150 M OHM	R58	63-554	150 M OHM
C44	22-446	.005 MFD.	C65	63-554	150 M OHM	R59	63-554	150 M OHM
C45	22-446	.005 MFD.	C66	63-554	150 M OHM	R60	63-554	150 M OHM
C46	22-446	.005 MFD.	C67	63-554	150 M OHM	R61	63-554	150 M OHM
C47	22-446	.005 MFD.	C68	63-554	150 M OHM	R62	63-554	150 M OHM
C48	22-446	.005 MFD.	C69	63-554	150 M OHM	R63	63-554	150 M OHM
C49	22-446	.005 MFD.	C70	63-554	150 M OHM	R64	63-554	150 M OHM
C50	22-446	.005 MFD.	C71	63-554	150 M OHM	R65	63-554	150 M OHM
C51	22-446	.005 MFD.	C72	63-554	150 M OHM	R66	63-554	150 M OHM
C52	22-446	.005 MFD.	C73	63-554	150 M OHM	R67	63-554	150 M OHM
C53	22-446	.005 MFD.	C74	63-554	150 M OHM	R68	63-554	150 M OHM
C54	22-446	.005 MFD.	C75	63-554	150 M OHM	R69	63-554	150 M OHM
C55	22-446	.005 MFD.	C76	63-554	150 M OHM	R70	63-554	150 M OHM
C56	22-446	.005 MFD.	C77	63-554	150 M OHM	R71	63-554	150 M OHM
C57	22-446	.005 MFD.	C78	63-554	150 M OHM	R72	63-554	150 M OHM
C58	22-446	.005 MFD.	C79	63-554	150 M OHM	R73	63-554	150 M OHM
C59	22-446	.005 MFD.	C80	63-554	150 M OHM	R74	63-554	150 M OHM
C60	22-446	.005 MFD.	C81	63-554	150 M OHM	R75	63-554	150 M OHM
C61	22-446	.005 MFD.	C82	63-554	150 M OHM	R76	63-554	150 M OHM
C62	22-446	.005 MFD.	C83	63-554	150 M OHM	R77	63-554	150 M OHM
C63	22-446	.005 MFD.	C84	63-554	150 M OHM	R78	63-554	150 M OHM
C64	22-446	.005 MFD.	C85	63-554	150 M OHM	R79	63-554	150 M OHM
C65	22-446	.005 MFD.	C86	63-554	150 M OHM	R80	63-554	150 M OHM
C66	22-446	.005 MFD.	C87	63-554	150 M OHM	R81	63-554	150 M OHM
C67	22-446	.005 MFD.	C88	63-554	150 M OHM	R82	63-554	150 M OHM
C68	22-446	.005 MFD.	C89	63-554	150 M OHM	R83	63-554	150 M OHM
C69	22-446	.005 MFD.	C90	63-554	150 M OHM	R84	63-554	150 M OHM
C70	22-446	.005 MFD.	C91	63-554	150 M OHM	R85	63-554	150 M OHM
C71	22-446	.005 MFD.	C92	63-554	150 M OHM	R86	63-554	150 M OHM
C72	22-446	.005 MFD.	C93	63-554	150 M OHM	R87	63-554	150 M OHM
C73	22-446	.005 MFD.	C94	63-554	150 M OHM	R88	63-554	150 M OHM
C74	22-446	.005 MFD.	C95	63-554	150 M OHM	R89	63-554	150 M OHM
C75	22-446	.005 MFD.	C96	63-554	150 M OHM	R90	63-554	150 M OHM
C76	22-446	.005 MFD.	C97	63-554	150 M OHM	R91	63-554	150 M OHM
C77	22-446	.005 MFD.	C98	63-554	150 M OHM	R92	63-554	150 M OHM
C78	22-446	.005 MFD.	C99	63-554	150 M OHM	R93	63-554	150 M OHM
C79	22-446	.005 MFD.	C100	63-554	150 M OHM	R94	63-554	150 M OHM
C80	22-446	.005 MFD.	C101	63-554	150 M OHM	R95	63-554	150 M OHM
C81	22-446	.005 MFD.	C102	63-554	150 M OHM	R96	63-554	150 M OHM
C82	22-446	.005 MFD.	C103	63-554	150 M OHM	R97	63-554	150 M OHM
C83	22-446	.005 MFD.	C104	63-554	150 M OHM	R98	63-554	150 M OHM
C84	22-446	.005 MFD.	C105	63-554	150 M OHM	R99	63-554	150 M OHM
C85	22-446	.005 MFD.	C106	63-554	150 M OHM	R100	63-554	150 M OHM
C86	22-446	.005 MFD.	C107	63-554	150 M OHM	R101	63-554	150 M OHM
C87	22-446	.005 MFD.	C108	63-554	150 M OHM	R102	63-554	150 M OHM
C88	22-446	.005 MFD.	C109	63-554	150 M OHM	R103	63-554	150 M OHM
C89	22-446	.005 MFD.	C110	63-554	150 M OHM	R104	63-554	150 M OHM
C90	22-446	.005 MFD.	C111	63-554	150 M OHM	R105	63-554	150 M OHM
C91	22-446	.005 MFD.	C112	63-554	150 M OHM	R106	63-554	150 M OHM
C92	22-446	.005 MFD.	C113	63-554	150 M OHM	R107	63-554	150 M OHM
C93	22-446	.005 MFD.	C114	63-554	150 M OHM	R108	63-554	150 M OHM
C94	22-446	.005 MFD.	C115	63-554	150 M OHM	R109	63-554	150 M OHM
C95	22-446	.005 MFD.	C116	63-554	150 M OHM	R110	63-554	150 M OHM
C96	22-446	.005 MFD.	C117	63-554	150 M OHM	R111	63-554	150 M OHM
C97	22-446	.005 MFD.	C118	63-554	150 M OHM	R112	63-554	150 M OHM
C98	22-446	.005 MFD.	C119	63-554	150 M OHM	R113	63-554	150 M OHM
C99	22-446	.005 MFD.	C120	63-554	150 M OHM	R114	63-554	150 M OHM
C100	22-446	.005 MFD.	C121	63-554	150 M OHM	R115	63-554	150 M OHM
C101	22-446	.005 MFD.	C122	63-554	150 M OHM	R116	63-554	150 M OHM
C102	22-446	.005 MFD.	C123	63-554	150 M OHM	R117	63-554	150 M OHM
C103	22-446	.005 MFD.	C124	63-554	150 M OHM	R118	63-554	150 M OHM
C104	22-446	.005 MFD.	C125	63-554	150 M OHM	R119	63-554	150 M OHM
C105	22-446	.005 MFD.	C126	63-554	150 M OHM	R120	63-554	150 M OHM
C106	22-446	.005 MFD.	C127	63-554	150 M OHM	R121	63-554	150 M OHM
C107	22-446	.005 MFD.	C128	63-554	150 M OHM	R122	63-554	150 M OHM
C108	22-446	.005 MFD.	C129	63-554	150 M OHM	R123	63-554	150 M OHM
C109	22-446	.005 MFD.	C130	63-554	150 M OHM	R124	63-554	150 M OHM
C110	22-446	.005 MFD.	C131	63-554	150 M OHM	R125	63-554	150 M OHM
C111	22-446	.005 MFD.	C132	63-554	150 M OHM	R126	63-554	150 M OHM
C112	22-446	.005 MFD.	C133	63-554	150 M OHM	R127	63-554	150 M OHM
C113	22-446	.005 MFD.	C134	63-554	150 M OHM	R128	63-554	150 M OHM
C114	22-446	.005 MFD.	C135	63-554	150 M OHM	R129	63-554	150 M OHM
C115	22-446	.005 MFD.	C136	63-554	150 M OHM	R130	63-554	150 M OHM
C116	22-446	.005 MFD.	C137	63-554	150 M OHM	R131	63-554	150 M OHM
C117	22-446	.005 MFD.	C138	63-554	150 M OHM	R132	63-554	150 M OHM
C118	22-446	.005 MFD.	C139	63-554	150 M OHM	R133	63-554	150 M OHM
C119	22-446	.005 MFD.	C140	63-554	150 M OHM	R134	63-554	150 M OHM
C120	22-446	.005 MFD.	C141	63-554	150 M OHM	R135	63-554	150 M OHM
C121	22-446	.005 MFD.	C142	63-554	150 M OHM	R136	63-554	150 M OHM
C122	22-446	.005 MFD.	C143	63-554	150 M OHM	R137	63-554	150 M OHM
C123	22-446	.005 MFD.	C144	63-554	150 M OHM	R138	63-554	150 M OHM
C124	22-446	.005 MFD.	C145	63-554	150 M OHM	R139	63-554	150 M OHM
C125	22-446	.005 MFD.	C146	63-554	150 M OHM	R140	63-554	150 M OHM
C126	22-446	.005 MFD.	C147	63-554	150 M OHM	R141	63-554	150 M OHM
C127	22-446	.005 MFD.	C148	63-554	150 M OHM	R142	63-554	150 M OHM
C128	22-446	.005 MFD.	C149	63-554	150 M OHM	R143	63-554	150 M OHM
C129	22-446	.005 MFD.	C150	63-554	150 M OHM	R144	63-554	150 M OHM
C130	22-446	.005 MFD.	C151	63-554	150 M OHM	R145	63-554	150 M OHM
C131	22-446	.005 MFD.	C152	63-554	150 M OHM	R146	63-554	150 M OHM
C132	22-446	.005 MFD.	C153	63-554	150 M OHM	R147	63-554	150 M OHM
C133	22-446	.005 MFD.	C154	63-554	150 M OHM	R148	63-554	150 M OHM
C134	22-446	.005 MFD.	C155	63-554	150 M OHM	R149	63-554	150 M OHM
C135	22-446	.005 MFD.	C156	63-554	150 M OHM	R150	63-554	150 M OHM
C136	22-446	.005 MFD.	C157	63-554	15			

Chassis No. 1005

NOTE


All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.

All voltages are positive D.C. unless marked otherwise.

Sensitivity switch in distance position.

Volume control full on.


Line voltage 112 A.C.



Socket Voltages

FRONT OF CHASSIS

- LEGEND**
- F—Filament
 - H—Heater
 - D—Diode
 - G1—Control Grid
 - G2—Screen Grid
 - G3—Suppressor Grid
 - P—Plate
 - K—Cathode



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	Antenna Post (On Loop)	200 Mmf.	18000 Kc.	S. W.	18000 Kc.	K	Set Oscillator to Scale
3	Antenna Post (On Loop)	200 Mmf.	16000 Kc.	S. W.	16000 Kc.	M	Alignment of Antenna
4	Antenna Post (On Loop)	200 Mmf.	4500 Kc.	Police	4500 Kc.	N	Set Oscillator to Scale
5	Antenna Post (On Loop)	200 Mmf.	4500 Kc.	Police	4500 Kc.	Q	Alignment of Antenna
6	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	1400 Kc.	F	Set Oscillator to Scale
7	Loop Switch in Wave Magnet Position		1400 Kc.	Broadcast	1400 Kc.	G (On Loop)	Alignment of Antenna

Model 11S474
CHASSIS No. 1103

NOTE


All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.

All voltages are positive D.C. unless marked otherwise.

Sensitivity switch in distance position.

Volume control full on.


Line voltage 112 A.C.



LEGEND

- F—Filament
- H—Heater
- D—Diode
- G1—Control Grid
- G2—Screen Grid
- G3—Suppressor Grid
- P—Plate
- K—Cathode

Socket Voltages



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	½ Mfd.	455 Kc.	Broadcast	600 Kc.	A, B, C, D	I. F. Alignment
2	Antenna Post (On Loop)	200 Mmf.	18000 Kc.	S. W.	18000 Kc.	K	Set Oscillator to Scale
3	Antenna Post (On Loop)	200 Mmf.	16000 Kc.	S. W.	16000 Kc.	M	Alignment of Antenna
4	Antenna Post (On Loop)	200 Mmf.	4500 Kc.	Police	4500 Kc.	N	Set Oscillator to Scale
5	Antenna Post (On Loop)	200 Mmf.	4500 Kc.	Police	4500 Kc.	Q	Alignment of Antenna
6	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	1400 Kc.	F	Set Oscillator to Scale
7	Loop Switch in Wave Magnet Position		1400 Kc.	Broadcast	1400 Kc.	G (On Loop)	Alignment of Antenna

CHASSIS No. 1207


NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.

All voltages are positive D.C. unless marked otherwise.


Volume control full on.

Line voltage 112 A.C.



LEGEND

F—Filament
H—Heater
D—Diode
G1—Control Grid
G2—Screen Grid
G3—Suppressor Grid
P—Plate
K—Cathode



Location of Tubes and Trimmers

ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Input Signal Frequency	Band	Loop Switch	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	½ Mfd.	455 Kc.	Broadcast		600 Kc.	A, B, C, D	I. F. Alignment
2	Antenna Post (On Loop)	200 Mmf.	18000 Kc.	S. W.	Ant.	18000 Kc.	K	Set Oscillator to Scale
3	Antenna Post (On Loop)	200 Mmf.	16000 Kc.	S. W.	Ant.	16000 Kc.	L-M	Alignment of Det.—Rock Gang & Adjust for Max.
4	Antenna Post (On Loop)	200 Mmf.	4500 Kc.	Police	Ant.	4500 Kc.	N	Rock Gang & Adjust for Max. Output
5	Antenna Post (On Loop)	200 Mmf.	4500 Kc.	Police	Ant.	4500 Kc.	Q	Alignment of Antenna
6	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	Wave Magnet	1400 Kc.	F	Set Oscillator to Scale
7	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	Wave Magnet	1400 Kc.	H	Alignment of R. F.
8	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	Wave Magnet	1400 Kc.	G (On Loop)	Alignment of Loop
9							J Adjusted at Factory	

Models 15S479—15S495

CHASSIS No. 1503

NOTE

All voltages measured with a 1000 ohm per volt meter from chassis to socket contact indicated.


All voltages are positive D.C. unless marked otherwise.

Volume control full on.

Line voltage 112 A.C.


LEGEND

- F—Filament
- H—Heater
- D—Diode
- G1—Control Grid
- G2—Screen Grid
- G3—Suppressor Grid
- P—Plate
- K—Cathode



FRONT OF CHASSIS


Socket Voltages



Location of Tubes and Trimmers


ALIGNMENT PROCEDURE

Operation	Connect Test Oscillator to	Dummy Antenna	Test Osc. Set at KC	Band	Loop Switch	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	½ Mfd.	455 Kc.	Broadcast		600 Kc.	A, B, C, D, E, F	I. F. Alignment
2	Antenna Post (on Loop)	200 Mmf.	18000 Kc.	S. W.	Antenna	18000 Kc.	K	Set Oscillator to Scale
3	Antenna Post (on Loop)	200 Mmf.	16000 Kc.	S. W.	Antenna	16000 Kc.	L-M	Alignment of Ant. & Det.—Rock Gang & Adjust for Max.
4	Antenna Post (on Loop)	200 Mmf.	4500 Kc.	Police	Antenna	4500 Kc.	N	Rock Gang & Adjust for Max. Output
5	Antenna Post (on Loop)	200 Mmf.	4500 Kc.	Police	Antenna	4500 Kc.	Q	Alignment of Antenna
6	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	Wave-Magnet	1400 Kc.	200 Mmf. F	Set Oscillator to Scale
7	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	Wave-Magnet	1400 Kc.	H	Alignment of R. F.
8	Single Turn Coupled Loosely to Loop		1400 Kc.	Broadcast	Wave-Magnet	1400 Kc.	G (On Loop)	Alignment of Loop
9						J Adjusted at Factory		




QW#	PART	DESCRIPTION	
C1	22-319	.005 MFD.	600V
C2	22-954	.00035 MFD.	600V
C3	22-887	.001 MFD.	600V
R1	63-719	470 M OHM	1/4 W.
R2	63-649	56 M OHM	1/4 W.
R3	63-271	1 MEG OHM	1/4 W.
1	57224	PHONO SW. & WIRE ASSEMBLY	
2	58070	PLUG & WIRE ASSEMBLY	
3	85-191	A.C. SWITCH	
4	169-36	WEBSTER AUTOMATIC RECORD PLAYER	
5	58069	CINCH "M"-93 PLUG RECEPTACLE & WIRE ASSEM.	
6	58069	CINCH "M"-21 PLUG WITH P-7002 CAP & LINER	
7	58068	PLUG & WIRE ASSEMBLY	

PHONO CIRCUIT DATA
MODEL SPEAKER
10S491 49-356 15"
10S492 49-352 12"
CHASSIS N°1007



QW#	PART	DESCRIPTION	
C1	22-319	.005 MFD.	600V
C2	22-954	.00035 MFD.	600V
C3	22-887	.001 MFD.	600V
R1	63-719	470 M OHM	1/4 W.
R2	63-649	56 M OHM	1/4 W.
R3	63-271	1 MEG OHM	1/4 W.
1	57224	PHONO SW. & WIRE ASSEMBLY	
2	58074	PLUG & WIRE ASSEMBLY	
3	85-191	A.C. SWITCH	
4	169-36	WEBSTER AUTOMATIC RECORD PLAYER	
5	58093	CINCH "M"-93 PLUG RECEPTACLE & WIRE ASSEM.	
6	58093	CINCH "M"-21 PLUG WITH P-7002 CAP & LINER	
7	58092	PLUG & WIRE ASSEMBLY	

PHONO CIRCUIT DATA
MODEL SPEAKER
12S494 49-355 15"
CHASSIS N°1208



QW#	PART	DESCRIPTION	
C1	22-182	.00025 MFD.	600V
C2	22-887	.001 MFD.	600V
R1	63-597	470 M OHM	1/4 W.
R2	63-649	56 M OHM	1/4 W.
1	57224	PHONO SW. & WIRE ASSEMBLY	
2	58108	PLUG & WIRE ASSEMBLY	
3	85-191	A.C. SWITCH	
4	169-36	WEBSTER AUTOMATIC RECORD PLAYER	
5	58107	CINCH "M"-93 PLUG RECEPTACLE & WIRE ASSEM.	
6	58107	CINCH "M"-21 PLUG WITH P-7002 CAP & LINER	
7	58106	PLUG & WIRE ASSEMBLY	

PHONO CIRCUIT DATA
MODEL SPEAKER
15S495 49-375 15"
CHASSIS N°1504

PARTS PRICE LIST

MODELS

FOR CHASSIS MODEL CHART SEE FRONT COVER

Chassis No. Code
5417 A
5420 B
5536 C
5672P D
5675 E

Chassis No. Code
5678 F
5679 G
5724 H
5725 I
5808 J

Chassis No. Code
1005 K
1103 L
1207 M
1503 N

DIAL PARTS

26-223	Dial scale	D-E	.45
26-232	Dial scale	C	.30
26-235	Dial scale	J-K-L	.25
26-238	Dial scale	A-B	.15
26-239	Stationary dial scale	M-N	.15
26-245	Dial scale	G	.25
27-16	Flywheel disc	G-J-K-L-M	1.00
32-15	Drive belt	M-N	.15
32-18	Drive belt	G-J-K-L-N	.15
34-68	Condenser shaft gear & bushing	M-N	.20
34-80	Lower drive gear & pinion	M-N	.20
57-709	Dial scale mounting plate	D-E	.05
57-776	Resonance indicator plate	M-N	.30
59-66	Dial pointer	A-B-C	.10
59-77	Dial pointer	F-H-I	.10
59-78	Dial pointer	D-E	.05
59-84	Frequency indicator pointer	M-N	.10
59-85	Split second pointer	M-N	.20
59-86	"On" indicator	A-B	.05
61-42	Pointer shaft pulley	M-N	.12
61-44	Motor shaft pulley	N	.12
61-53	Drive pulley (brass)	G-J-K-L	.15
61-55	Idler pulley (part of S-6959)	F-H-I	.10
73-8	Dial pulley set screw	A-B-C-G-J-K-L	.02
73-16	#8-32x1/8" headless set screw	M-N	.60 C
73-24	#8-32x1/4" H.H. set screw	G-J-K-L	1.50 C
73-28	Set screw-pointer pulley	M-N	.02
73-33	Set screw for 117-48	M-N	.02
76-229	Split second pointer shaft & pinion		.30
76-258	Tuning control shaft	A-B	.10
76-278	Tuning control shaft	C	.10
76-282	Dial drive shaft	F-H-I	.06
76-289	Volume control shaft	M-N	.08
76-292	Volume control shaft	G-J-K-L	.10
78-226	Dial light socket	G	.08
78-260	Dial light socket & wire	D-E	.18
78-297	Dial light socket & wire	M-N	.20
78-304	Dial light socket & wire	F	.45
80-69	Dial cord tension spring	A-B-C-F-G-H-I	
		J-K-L	.01
80-130	Clutch spring	M-N	.02
80-138	Retainer spring—movable scales	M-N	.01
80-139	Dial spring	M-N	.07
80-151	Return spring—movable scales	M-N	.02
80-181	Spring-pointer clamp	G-J-K-L	.65 C
80-207	Indicator spring	A-B	.02
83-516	Brass spacer strip	M-N	.02
83-666	Dial light diffusion strip	D-E	.02
83-707	Movable scale spacer strip	M-N	.65 C
83-708	Movable scale spacer strip	M-N	.03
93-371	Bakelite washer for dial pointer	A-B-C	.45 C
94-271	Coupling-volume control shaft	G-J-K-L-M-N	.06
97-117	Mtg. stud—MS452 pulley	G-J-K-L	.10
97-120	Mtg stud for 61-55 (Part of S-6959)	F-H-I	1.40 C
100-36	Dial lamp 6.3 volts	F-H-I-J-K-L-M-N	.09
100-39	Dial lamp 2.9 volt	D-E-G	.12
114-46	#6x1 1/8" hex. acorn head self tapping screw	M-N	.45 C
114-47	#6x1 1/8" H.H. slotted P. K. screw		.50 C
114-52	#8-32x1 1/8" H.H. slotted mach. screw	M-N	.35 C
114-62	#8x1 1/4" H.H. slotted self tapping screw	M-N	.60 C
114-115	#6x1 1/4" hex. acorn head		

117-48	self tapping screw	M-N	.45 C
118-16	Lever-band switch shaft	G-J-K-L-M-N	.02
126-329	Lever connecting link	G-J-K-L-M-N	.01
142-49	Center shield for dial glass	M-N	.05
159-12	Dial crystal	B	.20
183-9	Snap button	G-J-K-L-M-N	.01
188-2	Rubber band	M-N	.50 C
188-13	Retaining ring	G-J-K-L-M-N	.01
192-39	Retainer ring for 76-282	F-H-I	.15 C
192-47	Dial crystal	D-E	.15
192-48	Dial glass	M-N	.60
192-49	Dial crystal	C	.15
196-26	Dial crystal	A	.20
199-10	Gasket—dial glass	M-N	.15
199-11	Motor pulley rubber sleeve	N	.02
199-14	Rubber pulley sleeve	G-J-K-L-M-N	.75 C
199-21	Sleeve—MS452 mtg.	G-J-K-L	.03
S-4915	Rubber bumper sleeve	M-N	.03
S-5999	Dial light socket & clip	H-I	.10
S-6220	Dial light socket & clip	J-K-L	.08
S-6221	Drive pulley & clutch assembly	M-N	.25
S-6223	Frequency pointer gear & shaft	M-N	.35
S-6440	Tuning shaft & bushing	G-J-K-L	.25
S-6870	Control arm & bushing for band switch (die cast)	G-J-K-L	.15
S-6959	Indicator disc & bushing	C	.15
S-7046	Dial scale & idler assy. (26-224)	F-H-I	.30
S-7071	Dial cord & eyelet assembly	F-H-I	.15
S-7262	Dial cord & eyelet assembly	C	.05
S-7575	Indicator cam & bushing	A-B	.05
S-7594	Dial cord & eyelet assembly	A-B	.05
S-7595	Broadcast band scale assembly (26-242 & 26-243)	M-N	.55
S-7645	Short wave band scale assembly (26-240 & 26-241)	M-N	.60
S-7648	Dial cord & eyelet	G-J-K-L	.10
S-7766	Dial pointer & clip	G-J-K-L	.12
S-7768	Dial scale mtg. plate assy.	M-N	.55
S-7777	Condenser drive shaft & bushing	M	.20
S-7948	Control arm & pin assembly (die cast)	M-N	.45
MS-418	Condenser drive shaft & bushing	N	.30
MS-452	Dial pulley & bracket assy.	A-B-C	.10
MS-506	Pulley & bracket assy.—Mtd. on chassis	G-J-K-L	.15
MS-577	Dial pulley & bracket assy.	F-H-I	.15
	Pulley & bracket assy.—Mtd. on gang shaft	G-J-K-L	.15

AUTOMATIC AND RADIOORGAN EUSATCHEON ASSEMBLIES

12-729	Catch bracket	G-J-K-L-M-N	.01
46-293	A.C. switch knob (ON)	M-N	.10
46-294	A.C. switch knob (OFF)	M-N	.10
46-295	Automatic tuning knob	G-J-K-L-M-N	.04
46-296	Automatic tuning knob	G-J-K-L-M-N	.04
57-751	Escutcheon plate—dial	M-N	2.00
57-767	Zenith nameplate	M-N	.25
57-769	Escutcheon plate—auto. tuning	G-J-K-L	.30
57-770	Escutcheon plate—auto. tuning	M-N	.30
57-771	Escutcheon plate—tone control	G-J-K-L	.50
57-772	Escutcheon plate—tone control	M-N	.30

PARTS LIST—(Continued)

76-293	Shaft for knobs	G-J-K-L	.01	22-836	.03 mfd. 400 volts	D-E	.15
76-294	Knob shaft	M-N	.03	22-837	.01 mfd. 400 volts	D-E	.15
80-211	Spring for catch	G-J-K-L-M-N	.25 C	22-841	.02 mfd. 200 volts	D-E	.15
80-212	Spring retainer	G-J-K-L-M-N	.02	22-844	.05 mfd. 400 volts	D-E	.15
114-110	#4-40x7/32" H. H. slotted self tapping screw	G-J-K-L-M-N	.40 C	22-846	Trimmer—auto. tuning	F-G-H-I-J-K-L- M-N	.15
156-3	Escutcheon catch	G-J-K-L-M-N	.03	22-847	Trimmer—auto. tuning	F-G-H-I-J-K-L- M-N	.20
S-7882	"Alto" knob & eyelet	G-J-K-L	.10	22-848	Trimmer—auto. tuning	F-G-H-I-J-K-L- M-N	.25
S-7883	"Normal" knob & eyelet	G-J-K-L	.10	22-849	Two gang variable	F-H-I	2.50
S-7884	"Treble" knob & eyelet	G-J-K-L	.10	22-850	Ceramic trimmer—3 section	F-H-I-J-K-L	.50
S-7885	"Lo-Bass" knob & eyelet	G-J-K-L	.10	22-853	Dual fixed padder	F-H-I	.60
S-7886	"Bass" knob & eyelet	G-J-K-L	.10	22-854	.0005 mfd. 600 volts	G-J-K-L-M	.15
S-7887	"Voice" knob & eyelet	M-N	.10	22-859	Trimmer—auto. tuning	F-G-H-I-J-K-L- M-N	.20
S-8026	"Alto" knob & eyelet	M-N	.10	22-866	Broadcast oscillator padder	F-H-I	.30
S-8027	"Normal" knob & eyelet	M-N	.10	22-868	480 mmfd. silver cap	F-G-I-J-K-L	.30
S-8028	"Treble" knob & eyelet	M-N	.10	22-869	.05 mfd. 400 volts	C-H	.15
S-8029	"Lo-Bass" knob & eyelet	M-N	.10	22-873	Trimmer—auto. tuning	F-G-H-I-J-K-L- M-N	.25
S-8030	"Bass" knob & eyelet	M-N	.10	22-875	.15 mfd. 400 volts	D-E	.20
S-8031	"Voice" knob & eyelet	M-N	.10	22-879	60-60 mfd. 150 volt dry electrolytic	C	1.25
CONDENSERS				22-881	Ceramic trimmer—4 section	G-M-N	.75
22-127	25 mmfd. 600 volts	J-K-L-M-N	.15	22-885	Two gang variable	D-E	2.00
22-138	.2 mfd. 200 volts	C	.25	22-887	.001 mfd. 600 volts	C-M-N	.15
22-147	.0005 mfd. 600 volts	K-L-N	.20	22-893	20 mfd. 200 volt electrolytic	D-E	.85
22-162	.0001 mfd. 600 volts	A-B-C-D-F-G-H-I- J-K-L-M-N	.15	22-894	20 mfd. 250 V.—20 mfd. 150 V. 20 mfd. 25 V.	C	2.00
22-171	.05 mfd. 600 volts	M-N	.20	22-910	Two gang variable	D-E	1.25
22-182	.00025 mfd. 600 volts	C-F-G-H-I-J-K- L-N	.20	22-927	Two gang variable	J-K-L	3.50
22-185	.01 mfd. 200 volts	D-E	.15	22-928	40 mfd. 150 volt 20 mfd. 25 volt dry electrolytic	C	.85
22-188	.02 mfd. 400 volts	G	.15	22-929	Padder—broadcast oscillator	J-K-L-M	.30
22-190	.1 mfd. 200 volts	D-I	.12	22-930	Padder—dual fixed	J-K-L-M-N	.65
22-196	.01 mfd. 600 volts	C-F-H-I-M-N	.15	22-931	Ceramic trimmer—2 section		.35
22-199	.5 mfd. 200 volts	A-G	.40	22-933	6-16 mfd. 450 volt dry electrolytic	J	.85
22-212	.05 mfd. 400 volts	E	.15	22-934	20 mfd. 450 volt—20 mfd. 350 volt dry electrolytic	K-L	1.10
22-219	.03 mfd. 200 volts	F-H-I-J	.15	22-939	.1 mfd. 200 volts	E	.15
22-229	.005 mfd. 600 volts	F-H-I-J-K-L-M	.15	22-940	R. F. coil trimmer	F-H-I	.15
22-243	.01 mfd. 400 volts	A-B-C	.15	22-941	5 mfd. x 15 mfd. 450 volts	H-I	1.00
22-250	.05 mfd. 200 volts	D-E	.15	22-944	Compensator	M-N	.40
22-289	50 mmfd. 600 volts	F-G-H-I-M-N	.15	22-951	Three gang variable	M-N	5.50
22-319	.005 mfd. 200 volts	G-M	.15	22-953	200 mmfd. 600 volts	I	.12
22-326	.003 mfd. 400 volts	G-I-N	.15	22-954	350 mmfd. 600 volts	I-J-K-L-M	.12
22-327	.02 mfd. 200 volts	G-J-K-L-M-N	.15	22-958	Trimmer—wave trap	J-K-L	.20
22-350	.25 mfd. 200 volts	C-G	.20	22-959	Ceramic trimmer—single section	M-N	.15
22-358	.002 mfd. 600 volts	F-G-H-I-J-K-L- M-N	.30	22-960	40-40-20 mfd. 25 volt dry electrolytic	N	.75
22-448	.004 mfd. 600 volts	A-B-C-F-G-H-I- J-K-L-M-N	.15	22-961	500 mfd. 15 volt electrolytic	A	1.50
22-455	.01 mfd. 1200 volts	N	.20	22-964	Two gang variable	G	3.25
22-458	.006 mfd. 600 volts	G	.15	22-966	.04 mfd. 600 volts	A	.20
22-463	Oscillator padder	N	.35	22-970	20 mfd. 450 volts—20 mfd. 350 V. dry electrolytic	M	1.15
22-470	.00015 mfd. 600 volts	G-J-K-L-M-N	.15	22-972	.015 mfd. 600 volts	G	.15
22-492	.002 mfd. 600 volts	J-K-L-M	.15	22-973	Dual fixed padder	G	.65
22-525	.005 mfd. 1000 volts	I-J-K-L-M	.45	22-974	20 mfd. 25 V.—20 mfd. 250 V. dry electrolytic	G	.85
22-569	12 mfd. 450 volts Dry Electrolytic	N	1.00	22-975	20 mfd. 450 V. dry electrolytic	F	.75
22-627	.002 mfd. 1000 volts	J	.20	22-976	10 mfd. 450 volt—15 mfd. 350 volt dry electrolytic	F	1.00
22-684	8 mfd. 150 V. dry electrolytic	B	.35	22-982	Trimmer—ceramic—2 section	J-K-L-N	.30
22-695	Two gang variable	A-B	2.25	22-992	.02 mfd. 600 volts	N	.25
22-716	.0005 mfd. 600 volts	F-G-H-I-J	.20	R. F. AND L. F. COILS			
22-719	16 mfd. 350 volts	H-I-J-M	.55	20-208	Antenna coil	A-B-C	.45
22-727	10-10 mfd. 450 volts dry electrolytic	N	1.25	20-216	R. F. plate choke coil	M-N	.45
22-733	.0001 mfd. 500 volts		.20	95-589	1st I. F. transf.	A-B	1.25
22-736	.00043 mfd. 500 volts		.45	95-590	2nd I. F. transf.	A-B	1.25
22-737	.00075 mfd. 500 volts		.35	95-593	1st I. F. transf.	C	1.00
22-742	10-15-15 mfd. 250 V. dry electrolytic	A	1.25	95-594	2nd I. F. transf.	C	1.00
22-747	16 mfd. 450 V.—40 mfd. 200 V. dry electrolytic		1.25	95-596	2nd I. F. transf.	F-H-I	1.00
22-771	30-15-10 mfd. 250 V. dry electrolytic	G	1.25	95-600	1st I. F. transf.	F-H-I	1.00
22-788	2-35 mmfd. ceramic trimmer	F-G-H-I	.15	95-625	1st I. F. transf.	J-K-L	1.25
22-823	.25 mfd. 200 volts	J-K-L-N	.20	95-637	1st I. F. transf.	M	1.25
22-825	.1 mfd. 400 volts	A-B-C-G	.15	95-638	2nd I. F. transf.	M	1.25
22-826	.01 mfd. 200 volts	F-G-H-I-J-K-L- M-N	.18	95-649	1st I. F. transf.	G	1.25
22-827	.1 mfd. 200 volts	A-F-G-H-I-J-K- L-M-N	.15	95-650	2nd I. F. transf.	G	1.25
22-828	.05 mfd. 400 volts	A-B-C-F-G-H-I- J-K-L-M-N	.15				
22-829	.05 mfd. 200 volts	F-G-H-I-J-K-L	.15				
22-830	.02 mfd. 600 volts	D-E	.20				
22-833	.0005 mfd. 600 volts						

PARTS LIST—(Continued)

95-663	2nd I. F. transf.	J	1.25
95-664	2nd I. F. transf.	K-L	1.25
S-5043	Choke assembly—power pack	A	.25
S-6375	2nd I. F. transf.	N	2.25
S-6376	3rd I. F. transf.	N	2.25
S-6381	Oscillator coil	A-C	.65
S-6901	Oscillator coil	E	.55
S-6902	1st I. F. transf.	D-E	.60
S-6903	2nd I. F. transf.	D-E	.60
S-6936	Antenna coil assembly	F-H-I	1.00
S-6937	Oscillator coil assembly	F-H-I	1.25
S-6942	Oscillator coupling coil	D	.55
S-6992	Oscillator coupler coil assy.	F-H-I	.45
S-7500	Wave trap coil assembly	F-H-I	.85
S-7504	Antenna coil assembly	J-K-L	1.00
S-7507	Oscillator coupler coil & bracket	G-J-K-L	.75
S-7559	Wave trap coil	J-K-L	.50

COILS

S-7635	Choke coil & res. assembly.	J-K-L	.40
S-7641	Oscillator coil & shield	J-K-L	1.50
S-7656	Trimmer coil	M-N	.50
S-7665	Oscillator coupl. coil & brkt.	M	.65
S-7666	Oscillator coil	M-N	1.00
S-7667	Detector coil	M	1.10
S-7759	Oscillator coupl. coil & brkt.	N	.85
S-7798	Antenna coil & shield assy.	M	1.50
S-7811	Antenna coil	G	1.50
S-7815	Osc. coil assembly	B	.65
S-7959	Antenna coil & shield assy.	N	1.25
S-7960	Det. coil & shield assy.	N	1.25
S-8007	Oscillator coil & shield assy.	G	1.50
S-8103	1st I. F. transf.	N	2.25
S-8111	Loading coil	J-K-L-M-N	.45

RESISTORS

63-151	15M ohms 1 watt	F-J-K-L	.07
63-160	100M ohms 1/2 watt	G	.08
63-238	1000 ohms 1/4 watt	B	.07
63-271	1 megohm 1/4 watt	A-B-C-F-G-H-I-J- K-L-M-N	.07
63-282	2200 ohms 1/4 watt	M-N	.07
63-296	220M ohms 1/4 watt	A-C-D-E-F-G- H-I	.07
63-381	100M ohms 1/2 watt	F	.08
63-464	1 megohm 1/4 watt	I	.15
63-572	15 ohms 1/4 watt	D-E	.07
63-574	33 ohms 1/4 watt	J-K-L	.07
63-576	68 ohms 1/4 watt	G-J-K-L	.07
63-577	100 ohms 1/4 watt	A-G-N	.07
63-581	470 ohms 1/4 watt	M-N	.07
63-583	1000 ohms 1/4 watt	A-C-E-F-H-I	.07
63-585	2200 ohms 1/4 watt	F-K-L	.07
63-586	3300 ohms 1/4 watt	M-N	.07
63-587	4700 ohms 1/4 watt	B-J-K-L	.07
63-588	6800 ohms 1/4 watt	F-H-I	.07
63-589	10M ohms 1/4 watt	J-K-L	.07
63-591	22M ohms 1/4 watt	D-G-M-N	.07
63-592	33M ohms 1/4 watt	F-H-I	.07
63-593	47M ohms 1/4 watt	A-B-C-D-E-F-G-H- I-J-K-L-M-N	.07
63-594	68M ohms 1/4 watt	A-B-J-K-L-M	.07
63-595	100M ohms 1/4 watt	A-F-H-I-J-K-L- M-N	.07
63-597	470M ohms 1/4 watt	A-C-D-E-F-G-H-I- J-M-N	.07
63-599	1.5 megohms 1/4 watt	F-G-H-I	.07
63-600	2.2 megohms 1/4 watt	A-B-C-D-E	.07
63-602	4.7 megohms 1/4 watt	D	.07
63-604	10 megohms 1/4 watt	A-B-C	.07
63-605	1000 ohms 1/2 watt	A-C-G-J-K-L- M-N	.08
63-607	15M ohms 1/2 watt	F-H-I	.08
63-608	15M ohms 1 watt	N	.10
63-618	22 ohms 1/4 watt	N	.07
63-628	270 ohms 1/4 watt	G	.07
63-634	820 ohms 1/4 watt	G	.07
63-643	18M ohms 1/4 watt	J-K-L	.07
63-647	39M ohms 1/4 watt	M-N	.07
63-648	47M ohms 1/4 watt	K-L-M-N	.07
63-649	56M ohms 1/4 watt	G-M-N	.07
63-652	120M ohms 1/4 watt	C	.07
63-653	150M ohms 1/4 watt	N	.07

63-654	180M ohms 1/4 watt	B	.07
63-655	220M ohms 1/4 watt	J-K-L-M-N	.07
63-657	330M ohms 1/4 watt	K-L-M-N	.07
63-659	470M ohms 1/4 watt	F-G-H-I	.07
63-660	560M ohms 1/4 watt	N	.07
63-669	3.9 megohms 1/4 watt	A-B-C	.07
63-675	5600 ohms 1/2 watt	G	.08
63-676	27M ohms 1 watt	H-I-K-L-M	.10
63-677	33M ohms 1 watt	J	.10
63-680	10M ohms 1 watt	M-N	.10
63-686	150 ohms 1/2 watt wirewound	D-E	.17
63-697	100 ohms 1/4 watt	A	.15
63-711	22M ohms 1/4 watt	G-J-K-L	.15
63-713	47M ohms 1/4 watt	C-E	.15
63-717	220M ohms 1/4 watt	E-I	.15
63-719	470M ohms 1/4 watt	E-I-M	.15
63-724	4.7 megohms 1/4 watt	E	.15
63-739	100 ohms 1/4 watt	F	.15
63-774	220M ohms 1/4 watt	J-K-L	.15
63-796	10M ohms 1/2 watt	G-J	.08
63-961	47M ohms 1 watt	F	.10
63-963	120 ohms 1/2 watt	G	.08
63-966	4700 ohms 2 watt	G	.15
63-976	15 megohms 1/4 watt	F-H	.07
63-977	270 ohms 1/2 watt wirewound	G	.17
63-980	Volume control	N	1.00
63-986	Candohm	N	.75
63-990	Volume control & switch	G	1.50
63-992	Candohm resistor		.30
63-1012	90 ohms 1/2 watt wirewound	C	.17
63-1023	22 ohms 1/2 watt wirewound	D-E	.17
63-1028	Vol. cont. resistance element	D-E	.35
63-1030	Volume cont. & switch	F-H	1.00
63-1035	Volume control & switch	I	1.50
63-1041	Candohm	C	.45
63-1042	1 megohm 1/4 watt	D	.15
63-1048	Candohm	K-L	.30
63-1054	10M ohm 1/2 watt	F-H-I	.17
63-1052	Candohm	M	.30
63-1055	22M ohm 1 watt	H-I	.20
63-1056	280 ohm 1 1/2 watt wirewd.	F-H-I	.20
63-1057	47 ohms 1/2 watt wirewd.	F-H-I	.17
63-1058	22M ohms 2 watt	K-M	.20
63-1060	90 ohms 1 watt (wirewd.)	A	.20
63-1061	7 ohms 1/2 watt (wirewd.)	A	.17
63-1062	10 ohms 1/4 watt (wirewd.)	K-L	.15
63-1065	15M ohms 1 watt	M	.20
63-1066	18 ohms 1/2 watt	I	.17
63-1072	Volume control & switch	B	1.50
63-1074	Volume control & switch	K-L	1.50
63-1075	Vol. control & switch	J	1.50
63-1077	18M ohms 1 watt	J-K-L	.10
63-1078	Volume control	M	1.00
63-1079	Volume control & switch	A	1.50
63-1081	Volume control & switch	C	1.50

MISCELLANEOUS

2-25	Back for 422 cabinet	A-B	.10
14-550	Bakelite cabinet (Mod. 422)		3.75
15-22	Plug cap	D-I-M-N	.05
15-23	Plug cap	D-E-I-M-N	.10
15-28	Volume control cover	D-E	.02
15-29	Tube shield cap	G-H-I	.02
19-51	Goat tube shield cap	G	.03
19-59	Battery clip—positive	A-G	.15
19-60	Battery clip—negative	A-G	.15
24-209	Automatic adj. cover plate	D-F-H-I	.10
44-16	Phono. jack	H-I-J-K-L-M-N	.20
46-221	Power switch knob	G	.20
46-239	Knob—motor cont. switch	N	.05
46-280	Volume control knob	F-H-I	.10
46-286	Tuning control knob	D-E	.10
46-287	Volume control knob	D-E	.10
46-292	Tuning control knob	C	.10
46-304	Power switch knob	C	.04
46-310	Control knob	A-B	.10
49-179	8" Dyn. Speaker (8S443-451)		5.75
	206-179 Output transformer		1.25
	207-179 Field coil		1.75
	208-179 Cone & voice coil		2.00
49-208	10" dyn. speaker (8S463)		7.50
	206-208 Output transformer		1.65
	207-208 Field coil		2.75
	208-208 Cone & voice coil		2.50
(a) 49-249	12" dyn. speaker (7S461-488)		8.00

PARTS LIST—(Continued)

"Note: Power transformers for chassis 5724 and 5725 are marked (a) or (b) above. Speakers for these chassis are also marked (a) or (b) and should be used only with the corresponding transformer."

b)49-301	6½" dyn. spkr. (7S-432-433-434-449)	4.00	49-354	15" dynamic speaker (12S475)	15.50
	206-301 Output transformer	1.25		206-354 output transformer	2.50
	207-301 Field coil (not replaceable)			207-354 field coil	2.75
	208-301 Cone & voice coil	1.50		208-354 cone & voice coil	4.50
b)49-308	10" dyn. speaker (7S458)	7.50	49-355	15" dynamic spkr. (12S494)	15.50
	206-308 output transformer	1.50		206-355 output transformer	2.50
	207-308 field coil	2.25		207-355 field coil	2.75
	208-308 cone & voice coil	2.50		208-355 cone & voice coil	4.50
b)49-309	12" dyn. spkr. (7S458-461)	8.00	49-356	15" dynamic spkr. (10S491)	15.50
	206-309 output transformer	1.50		206-356 output transformer	2.50
	207-309 field coil	2.25		207-356 field coil	2.75
	208-309 cone & voice coil	3.50		208-356 cone & voice coil	4.50
b)49-311	10" dyn. spkr. (7S460-462)	7.50	49-359	8" P. M. Speaker (Models 468-465)	7.00
	206-311 output transformer	1.50		206-359 output transformer	1.25
	207-311 field coil	2.25		208-359 cone & voice coil	2.00
	208-311 cone & voice coil	2.50		206-364 output transformer	4.25
b)49-312	10" dyn. spkr. (7S458)	7.50	49-364	6" dynam. speaker (6S439)	1.25
	206-312 output transformer	1.50		207-364 field coil (not replaceable)	
	207-312 field coil	2.25		208-364 cone & voice coil	1.50
	208-312 cone & voice coil	2.50	(a)49-367	10" dyn. spkr. (7S460-462)	7.50
b)49-314	8" dyn. spkr. (7S450-459)	5.50		206-367 output transformer	1.50
	206-314 output transformer	1.50		207-367 field coil	2.25
	207-314 field coil	1.75		208-367 cone & voice coil	2.50
	208-314 cone & voice coil	2.00	(a)49-368	10" dyn. spkr. (7S458)	1.50
49-320	8" dynamic speaker D	5.50		207-368 field coil	2.25
	206-320 output transformer	1.50		208-368 cone & voice coil	2.50
	207-320 field coil	1.75	49-369	10" dynamic spkr. (7S487)	7.50
	208-320 cone & voice coil	2.00		206-369 output transformer	1.50
49-326	5" dynamic speaker E	3.50		207-369 field coil	2.25
	206-326 output transformer	1.25		208-369 cone & voice coil	2.50
	207-326 field coil (not repl.)		49-374	15" dynamic spkr. (15S479)	17.00
	208-326 cone & voice coil	1.25		206-374 output transformer	2.50
49-328	6½" P. M. speaker (Models 437-435)	5.50		207-374 field coil	3.75
	206-328 output transformer	1.25		208-374 cone & voice coil	5.50
	208-328 cone & voice coil	1.50	49-375	15" dynamic spkr. (15S495)	18.50
49-332	8" P. M. speaker (Mod. 438)	6.75		206-375 output transformer	2.50
	206-332 output transformer	1.25		207-375 field coil	3.75
	208-332 cone & voice coil	2.00		208-375 cone & voice coil	5.50
49-333	10" P. M. spkr. (Mod. 467)	10.00	(a)49-376	6½" dynamic speaker (7S432-433-434-449)	4.00
	206-333 output transformer	1.65		206-376 output transformer	1.25
	208-333 cone & voice coil	2.50		207-376 field coil	1.25
49-342	10" P. M. spkr. (Mod. 466)	10.00	(a)49-377	8" dynamic speaker (7S450-459-490)	5.50
	206-342 output transformer	1.65		206-377 output transformer	1.50
	208-342 cone & voice coil	2.50		207-377 field coil	1.75
49-344	10" dynamic spkr. (6S469)	7.00		208-377 cone & voice coil	2.00
	206-344 output transformer	1.25	49-379	10" dyn. spkr. (10S464)	8.00
	207-344 field coil	2.75		206-379 output transformer	1.50
	208-344 cone & voice coil	2.50		207-379 field coil	2.75
49-345	5" P. M. speaker (Mod. 422)	4.25		208-379 cone & voice coil	2.50
	206-345 output transformer	1.25	52-160	Speaker cable & plug A-B	.30
	208-345 cone & voice coil	1.25	52-164	Speaker cable D	.40
49-346	8" dynamic speaker (10S443) (12S445)	7.25	52-165	Speaker cable E	.35
	206-346 output transformer	1.25	52-181	Shielded lead for phono M	1.00
	207-346 field coil	2.75	52-182	Shielded lead for phono N	.15
	208-346 cone & voice coil	2.00	57-11A	Antenna lead marker A-B-C	.02
49-348	10" P. M. speaker (Model 6J463)	8.75	57-11G	Ground lead marker A-B-C	.02
	206-348 output transformer	1.65	57-661	Motor switch plate N	.35
	208-348 cone & voice coil	2.50	57-708	Television-radio sw. plate H-I-J-K-L-M-N	.03
49-350	8" P. M. speaker (Model 6J436)	7.00	57-712	Escutcheon plate less glass (See S-6945)	
	206-350 output transformer	1.25	57-715	Escutcheon plate E	1.00
	208-350 cone & voice coil	2.00	57-716	Escutcheon plate D	1.50
49-351	10" dynamic speaker (10S452-12S453)	8.00	57-718	Plate I	1.95
	206-351 output transformer	1.50	57-752	Escutcheon only less glass J-K-L	2.00
	207-351 field coil	2.75	57-768	Escutcheon plate C	.25
	208-351 cone & voice coil	2.50	57-781	Escutcheon plate A-B	.60
49-352	12" dynamic speaker (10S492-11S474-12S471)	8.50	57-793	Battery conserver sw. plate G	.04
	206-352 output transformer	1.50	58-73	Battery cable plug C	.10
	207-352 field coil	2.75	62-9	Lamp plug receptacle G	.12
	208-352 cone & voice coil	3.50	62-10	Receptacle—female phono D-E-I-M-N	.20
49-353	12" dynamic speaker (10S470)	8.50	68-1	Autom. adjustment wrench F-G-H-I-J-K-L-M-N	.02
	206-353 output transformer	1.50	76-285	Vol. control shaft & wiper D-E	.18
	207-353 field coil	2.75	78-115	Socket—vibrator in P.P. G	.10
	208-353 cone & voice coil	3.50	78-128	Socket—speaker plug F-H-I-J-K-L-M-N	.10
				78-141 Socket—vibrator A	.10
				78-145 Socket—6F5G tube H-I-J-L	.10
				78-148 Socket—6Q7G tube F-K	.10
				78-149 Socket—6X5G tube F-H-I-J-K-L-M	.10

PARTS LIST—(Continued)

78-150	Socket—6K7G tube	F-H-I-J-K-L-M-N	.10	117-38	Band selector lever	G-J-K-L-M-N	.30
78-151	Socket—6A8G tube	M-N	.10	125-19	Rubber feet	A-B	.01
78-152	Socket—6F6G tube	J-K-L-M-N	.10	126-191	Tube shield	G	.15
78-156	Socket—6C5 tube	F-H-I-J	.10	126-239	Tube shield	F-H-I-J-K-L-M-N	.08
78-175	Socket—6J5G tube	N	.10	126-245	Electrolytic cond. shield	N	.12
78-176	Socket—6V6G tube	H-I-J-K-L-M-N	.10	126-248	Electrolytic cond. shield	N	.15
78-182	Socket—5Y4G tube	K-L-M-N	.10	126-297	Tube shield	A-B-C	.12
78-184	Socket—6T7G tube	N	.10	126-326	Goat tube shield	E-F-H-I	.10
78-185	Socket—6S7G tube	G	.10	126-337	Antenna coil shield	G	.15
78-186	Socket—6D8G tube	G	.10	126-341	Goat tube shield	F-G-H-I	.10
78-190	Socket—speaker plug	G	.10	127-15	Contact—tube socket	D-E	.30 C
78-191	Socket—6ZY5G tube	G	.10	127-16	Contact—power switch (straight)	D-E	.01
78-193	Socket—five contact	D-I-M-N	.10	127-17	Contact—power switch (bent)	D-E	.01
78-194	Socket—two contact	D-E-I-M-N	.10	127-28	Contact—power switch	E	.01
78-208	Socket—speaker	C	.10	139-48	Cardboard speaker baffle (422)		.05
78-219	Socket—5 contact for wavemagnet	F-H-J-K-L-M-N	.10	159-27	Plug buttons—stat. bronze	M	.10
78-228	Socket—6F8 tube	M-N	.10	159-35	Snap button	A-B	.65 C
78-229	Socket—for electrolytic	F-H-I-M	.02	188-27	Retaining ring	A-B-C	.03
78-230	Socket & cable—resonance indicator	J-K-L	.55	188-32	Retaining clip for vol. cont.	D-E	.85 C
78-235	Socket—6G6G tube	G	.10	190-11	Vibrator	G	2.95
78-246	Socket—1A7G tube	A-B-C	.10	190-17	Synchronous vibrator	A	3.50
78-247	Socket—1N5G tube	A-B-C	.10	192-41	Dial glass	F-H-I	.50
78-248	Socket—1H5G tube	A-B-C	.10	192-46	Dial glass	J-K-L	.60
78-249	Socket—1C5G tube	B	.10	196-23	Dial glass gasket	F-H-I	.15
78-250	Socket—electrolytic condenser	G	.05	196-25	Dial glass gasket	J-K-L	.15
78-269	Socket—117Z6G tube	C	.10	202-133	Phono instruction book	D	.03
78-273	Socket—1Q5G tube	A-C	.10	202-144	Phono instruction sheet	E	.50 C
78-290	Socket—7G7 tube	J-K-L	.15	202-147	Instruction book	C	.04
78-296	Socket & cable—resonance indicator	M	.55	202-150	Instruction book & call let.	J	.20
78-301	Socket—6A8G tube	F-H-I	.10	202-153	Instruction book	B	.04
78-307	Socket & cable—resonance indicator	N	.50	202-154	Instruction book & call let.	K	.20
80-198	Chassis mtg. springs	J-K-L-M-N	.01	202-155	Instruction book & call let.	M	.20
80-199	Chassis mtg. springs	J-K-L-M	.01	202-157	Instruction book & call let.	H-I	.15
80-215	Chassis mtg. springs	N	.02	202-162	Instruction book	A	.04
83-334	Antenna-ground term. strip	G	.12	202-165	Instruction book & call let.	N	.20
85-148	A. C. switch only	M-N	.35	202-166	Instruction book	F	.15
85-156	Motor control switch	N	.90	202-169	Instruction book & call let.	G	.20
85-171	Switch—battery conserver & television	G-H-I-J-K-L-M-N	.25	202-171	Instruction book & call let.	L	.20
85-177	Switch—power supply	G	.70	202-172	Short wave instruction sheet		.01
85-187	Tone control switch	C	.20	9267-352	#14 battery cable—red	A	.10ft.
85-198	Power switch	C	.85	9268-324	#14 battery cable—black	A	.10ft.
85-202	Switch—band selector	J-K-L	1.50	S-2778	Choke assy.—power pack	G	.25
85-205	Switch—band selector	F-H-I	1.10	S-5043	Choke assy.—power pack	G	.25
85-209	Switch—band selector	M-N	1.85	S-6398	Lever arm & br. for mot. sw.	N	.35
85-210	Switch—band selector	G	1.00	S-6910	Shield—tube	D-E	.10
90-169	Paper tube—res. indicator.	J-K-L-M-N	.02	S-6911	Shield—electrolytic	D	.12
93-168	Rubber shoulder washer	K-L-M	.05	S-6912	Shield—I. F. coil	E	.12
93-215	Rubber chassis mtg. washer	F-G-H-I	.06	S-6945	Escutcheon plate comp.	F-H-I	1.25
93-344	Rubber washer	K-L	.05	S-6994	Tone cont. sw. & knob assy.	F-H-I	.25
93-392	Brown felt washer	K-L	.01	S-7314	Band sel. knob (46-279 with 73-36)	F-H-I	.10
93-421	Felt washer	H-I	.01	S-7315	Tuning Knob (46-281 with 73-36)	F-H-I	.10
93-457	Insulating disc for 15-29 tube shield cap	H-I	.35 C	S-7350	Escutcheon assy.—dial	G-J-K-L	2.75
95-442	Power choke	N	2.50	S-7411	Shield—electrolytic		.12
95-533	Power transf. 117 V. 50-60 cy.	N	8.25	S-7642	Tone cont. cont. & str. assy.	G-J-K-L	.30
95-627	Power transf. 115 V. 60 cy.	J	3.75	S-7773	A.C. sw. & bracket assembly	M	.75
95-630	Power transf. 115 V. 60 cy.	K-L	5.00	S-7774	Tone cont. cont. & str. assy.	M-N	.25
(b)95-631	Power transf. 115 V. 60 cy.	H	3.25	S-7880	Vol. cont. knob & set screw (46-303 & 73-37)	G-J-K-L-M-N	.15
(a)95-634	Power transf. 115 V. 60 cy.	F-H-I	3.25	S-7881	Tuning control knob & set screw (46-252 & 73-37)	G-J-K-L-M-N	.15
95-635	Power transformer	A	1.75	S-7985	A.C. switch & bracket	N	.90
95-639	Power transf. 117 V. 60 cy.	M	5.00	S-7991	Tuning motor & cover	N	5.00
95-645	Power transformer	G	3.25	MS-517	Tone control switch	D-E	.25
(b)95-646	Power transf. 115 V. 25 cy.	H	6.75				
95-651	Power transf. 115 V. 25 cy.	J	7.85				
95-653	Power transf. 117 V. 25 cy.	K-L	11.25				
95-660	Power transf. 117 V. 25 cy.	M	11.25				
(a)95-661	Power transf. 115 V. 25 cy.	F-H-I	6.75				
100-79	Ballast tube—117 volt	D-E	.50				
112-25	1/4"-20x1 7/8" hex. head chassis mtg. bolt	J-K-L-M-N	.04	22-182	Cond. .00025 mfd.	F-H-I-K-L-M-N	.20
112-232	#10x1" chassis mtg screws.	C	.01	22-865	Trimmer condenser	D-E-F-H-I	.25
114-37	#6x1/4" hex. acorn head self tapping screw	G-J-K-L-M-N	.45 C	22-962	Trimmer condenser	J-K-L-M-N	.15
114-40	#10-32x7/8" chassis mtg. bolt	A-B-F-H-I	.50 C	52-166	Antenna cable (450)		.60
114-48	#6-32x1/4" hex. acorn head machine screw	J-K-L-M-N	.35 C	54-79	#6-32x1/4" brass nut	D-E-F	.30 C
114-80	1/4"-20x1 3/8" hex. washer head chassis mtg. bolts		.04	57-719	Switch plate for 85-171 sw.	F-H-I-J-K-L-M-N	.03
114-85	#10-32x1 1/8" chassis mtg. bolt	A-B	.65 C	57-760	Cover plate	D	.15
				57-786	Sw. plate for 85-189 sw.	F-H-I-J-K-L	.03
				58-54	Five prong plug	F-H-I-J-K-L-M-N	.10
				70-7	#6x1/2" R.H. wood screw	H-I	.20 C
					206-249 Output transformer		1.50
					207-249 Field coil		2.25
					208-249 Cone & voice coil		3.50
				49-286	5" P. M. speaker (Mod. 422)		4.50
					206-286 Output transformer		1.25
					208-286 Cone & voice coil		1.25

WAVEMAGNET PARTS

22-182	Cond. .00025 mfd.	F-H-I-K-L-M-N	.20
22-865	Trimmer condenser	D-E-F-H-I	.25
22-962	Trimmer condenser	J-K-L-M-N	.15
52-166	Antenna cable (450)		.60
54-79	#6-32x1/4" brass nut	D-E-F	.30 C
57-719	Switch plate for 85-171 sw.	F-H-I-J-K-L-M-N	.03
57-760	Cover plate	D	.15
57-786	Sw. plate for 85-189 sw.	F-H-I-J-K-L	.03
58-54	Five prong plug	F-H-I-J-K-L-M-N	.10
70-7	#6x1/2" R.H. wood screw	H-I	.20 C
	206-249 Output transformer		1.50
	207-249 Field coil		2.25
	208-249 Cone & voice coil		3.50
49-286	5" P. M. speaker (Mod. 422)		4.50
	206-286 Output transformer		1.25
	208-286 Cone & voice coil		1.25

PARTS LIST—(Continued)

70-34	#6x3/8" oval head wood scr.	F-H-I	.55 C
70-69	#2x3/8" oval head wood scr.	F-H-I	.35 C
83-334	Ant.-Gnd. terminal strip	D-E-F-H-I	.12
85-171	Switch—wavemagnet	F-H-I-J-K-L-M-N	.25
85-189	Switch—local-distance	F-H-I-J-K-L	.20
86-66	Cinch terminals	E	1.50 C
86-79	Antenna terminal	J-K-L-M-N	.75 C
86-80	Ground terminal	J-K-L-M-N	.75 C
93-125	#6 shakeproof lock washers	E-F-H-I-J	.25 C
93-350	#6 read finishing washer	H-I	.01
93-414	Fibre washer	E	.50 C
110-85	Cloth cover (463)	K-L-M-N	.30
112-227	#6-32x2 3/4" ornamental head screws	F	.02
112-261	#6-32x3" ornamental head screw	J	.02
147-73	Wood spacer	D-E-F-H-I	.01
147-82	Wood spacer	F-J	.01
147-84	Wood spacer	J	.01
S-6984	Loop shield & frame assembly (433-487-488)	D	1.00
S-7080	Front shield & frame assembly (439-432-459)	E	.85
S-7082	Wavemagnet winding assembly (439-432-459)		1.95
S-7098	Loop winding assembly	E	1.85
S-7099	Rear shield & frame assy.	E	1.65
S-7317	Loop winding assembly (487-488)		1.85
S-7335	Loop winding assembly	D	1.40
S-7345	Loop coil assembly	D	.15
S-7431	Antenna loading coil (433-49-58-60-61-62)		.45
S-7458	Wavemagnet winding assy. (469-33-49-50-58-60-61-62-90)		1.35
S-7565	Rear frame & switch assy. (433-460-488)		1.35
S-7566	Plate & switch assy. (458-61)		1.50
S-7611	Plate & switch assy. (462)		2.25
S-7614	Rear frame & sw. assy. (449)		1.35
S-7624	Plate & switch assy. (487)		1.50
S-7652	Frame & sw. assy. (439-32)		1.25
S-7658	Plate & switch assy. (459)		1.35
S-7677	Rear fr. & sw. assy. (450-490)		1.50
S-7877	Plate & switch assy. (443)		1.25
S-7878	Loop wdng. assy. (443-445)		2.25
S-7913	Loading coil assy. (463)		.55
S-7916	Loop winding assembly (463-64-91-92-74)		2.25
S-7917	Plate & switch assy. (463)		
	Replace with S-8074		1.25
S-7920	Front shield & frame assy. (469-490)		.85
S-7922	Plate & switch assy. (469)		1.50
S-7964	Loop winding assy. (451)		1.75
S-7965	Plate & switch assy. (451)		1.00
S-7967	Wavemagnet wdg. (10S452)		1.75
S-7968	Plate & switch assy. (10S452)		1.25
S-8019	Plate & brack. assy. (10S470)		1.25
S-8022	Wavemagnet winding (10S470)		1.75
S-8024	Plate & switch assy. (10S470)		1.25
S-8035	Wavemagnet winding (471-475-494-479)		2.00
S-8036	Plate & sw. assy. (475)		1.75
S-8074	Plate & switch assembly (464-91-92-74)		1.25
S-8081	Wavemagnet winding (453)		2.00
S-8082	Plate & sw. assy. (453)		.75
S-8084	Plate & switch assembly (471-494-495)		1.00
S-8089	Plate & switch assy. (445)		1.25
S-8100	Wavemagnet wdg. assy. (495)		2.00

AUTOMATIC TUNING PARTS

10-77	Cardboard box	G-J-K-M-N	.05
12-718	Unit retaining bracket	M-N	.06
12-719	Unit retaining bracket	G-J-K	.10
12-720	Switch mounting bracket	G-J-K	.15
19-94	Cover retaining clip	F-H-I	.01
22-846	Trimmer condenser	D-H-I	.15
22-847	Trimmer condenser	D-H-I	.20
22-848	Trimmer condenser	D-H-I	.25
22-859	Trimmer condenser	D-H-I	.20
22-868	490 mmfd. compens. cond.	D-H-I	.30
22-873	Trimmer condenser	H-I	.25

24-225	Switch cover	F-H-I	.02
46-278	Automatic knob	D-F-H-I	.05
57-707	Automatic adj. cover	D-F-H-I	.06
68-1	Automatic adj. wrench	D-F-G-H-I-J-K-	
		L-M-N	.02
80-161	Latch bar spring	D-F-H-I	.25 C
80-202	Push lever spring (for S6932)	D-F-H-I	.25 C
80-203	Push lever spring (for S6933)	D	.25 C
83-321	Two contact airpl. term.	F-H-I	.02
83-669	Coil retaining strip	D-F-H-I	.03
83-671	Fibre strip	D-F-H-I	.02
83-672	Latch bar	D-F-H-I	.35 C
83-709	Pin jack terminal	G-J-K	.10
83-710	Coil retaining strip	M-N	.20 C
83-711	Coil retaining strip	G-J-K	.02
83-712	Fibre strip	M-N	.01
83-713	Fibre strip	G-J-K	.01
83-732	Armite strip	M-N	.35 C
83-740	Pin jack terminal strip	M-N	.12
85-201	Automatic switch	G-J-K	2.00
85-206	Automatic switch	M-N	2.50
86-69	Terminals	M-N	.30 C
93-216	Steel washer (latch bar)	D-F-H-I	.30 C
112-223	Adjustment screw & core	D-F-G-H-I-J-K	.08
112-250	#4-40x7/32" R. H. self tapping screw	G-J-K-M-N	.40 C
114-37	6-32x3/8" self tapping screw	D-F-H-I	.40 C
114-39	#8x1/4" hexagon head self tapping screw	G-J-K-M-N	.50 C
114-46	6-32x1/8" self tapping screw	D-F-H-I	.40 C
114-84	#6-32x1/4" hex. head machine screw	G-J-K	.01
149-13	Adjustment screw & core	M-N	.15
S-6926	Contact spr. & base assy.	D	.75
S-6927	Manual osc. coil assembly	D	.40
S-6928	Autom. tuning coil (red)	D-F-H-I	.15
S-6929	Autom. tuning coil (green)	D-F-H-I	.15
S-6930	Autom. tuning coil (blue)	D-F-H-I	.15
S-6931	Autom. tuning coil (white)	D	.15
S-6932	Push lever assy.—autom.	D-F-H-I	.15
S-6933	Push lever assy.—manual	D	.04
S-6934	Cont. spr. & base assembly	F-H-I	.65
S-7021	Autom. tuning coil (yellow)	F-G-H-I-J-K	.15
S-7536	Autom. tuning coil (silver)	H-I	.15
S-7589	Autom. tuning coil (red)	M-N	.30
S-7590	Autom. tuning coil (green)	M-N	.30
S-7591	Autom. tuning coil (orange)	M-N	.30
S-7592	Autom. tuning coil (blue)	M-N	.30
S-7593	Autom. tuning coil (white)	M-N	.30
S-7857	Autom. tuning coil (red)	G-J-K	.20
S-7858	Autom. tuning coil (green)	G-J-K	.20
S-7859	Autom. tuning coil (blue)	G-J-K	.20
S-7860	Autom. tuning coil (silver)	G-J-K	.20

PHONO. PARTS

12-613	Pickup support bracket	D-E-I	.20
12-730	Switch mtg. brkt. for lamp (487)		.05
12-731	Switch mtg. brkt. for lamp (488)		.05
15-22	Plug cap for 58-59 & 78-193	I-K	.05
15-23	Plug cap for 58-50 & 78-194	E-I-K	.05
19-32	Lamp socket retaining clip (487-488-491-492-494)	N	.01
22-319	Cond. .005 mfd. 200 volt	K	.15
22-887	Cond. .001 mfd. 600 volt	K	.15
22-954	Cond. 350 mmfd. 600 volt	K	.12
24-142	Needle cup cover	D-E-I-K-M-N	.05
24-213	Stop switch cover (490)	D-E	.06
29-9	9" turntable (490)	D-E	1.25
29-10	9" turntable (487)		1.75
29-11	11 1/2" turntable (488-491-492-494)	N	2.25
41-1	Needle cup	D-E-I-K-M-N	.05
52-179	Shielded lead (491-492)		.15
57-721	Radio-phono escutcheon	D-E-I	.05
57-744	Switch plate—rad.-phono. (487-88-91-92-94)	N	.10
57-777	Switch plate—motor (487-88-91-92-94)	N	.03
58-39	Plug—five prong (491-492)	I	.07
58-50	Plug—two prong (490)	E	.05

PARTS LIST—(Continued)


62-10	Female receptacle (491-492)		.20	141-78	Motor assy. 115 V 50 cy.	D-E	6.75
63-271	Res. 1 megohm 1/4 watt	K	.07	142-21	Pickup & arm assembly	D	6.25
63-649	Res. 56M ohm 1/4 watt	K	.07	142-22	Pickup & arm assembly 490	E	6.25
63-719	Res. 470M ohm 1/4 watt	K	.15	142-23	Cartridge only for 142-21-22 (490)	D-E	5.00
70-71	#6x1/2" R.H. wood screw—bronze	I	.50 C	142-24	Cartridge only for 169-36 (487-488-491-492-494)	N	6.00
70-72	#6x3/8" R.H. wood screw—bronze	I	.50 C	169-36	Automatic record player 115 V. 60 cy. (487-488-491-492-494)	N	50.00
78-193	Five contact socket	K	.10	169-37	Automatic record player 115 V. 60 cy. (487-488-491-492-494)	N	50.00
78-194	Two contact socket	K	.10	199-20	Rubber sleeve for compartment lamp	I	.03
78-291	Light socket & wire	I-K-M-N	.12	202-133	Phono instruction book (490)	D-E	.03
83-534	Five lug terminal strip	K	.06	202-134	Phono instruction book (487-488-491-492-494)	N	.03
85-181	Autom. stop switch (490)	D-E	1.00				
85-191	A.C. switch	D-E-I-K-M-N	.25				
85-192	Phono. switch	I-K	.35				
85-203	Light switch (488-491-492-494)	N	.55				
85-204	Light switch (487)		.55				
100-80	Lamp bulb (491-492-494)	I-N	.25				
141-77	Motor assy.—115 V. 60 cy. (490)	D-E	6.75				

All Price List subject to Regular Discount and Change w/o notice (10-25-39)




(Chassis No. 5810)

Line voltage 120 A.C.



- F—Filament
H—Heater
D—Diode
G1—Control Grid
G2—Screen Grid
G3—Suppressor Grid
P—Plate
K—Cathode




Operation	Connect Test Oscillator to	Dummy Antenna	Set Test Oscillator to	Band	Set Dial At	Adjust Trimmers	Purpose
1	1st Det. Grid	5 mfd.	455	B'dcast	600	A B C D	I. F.
2	Single *x Turn Coil	—	1500	"	1500	F	Set Osc. to Scale
3	" "	—	1500	"	1500	On Wave Magnet	Alignment of Wave Magnet
4	Rec. Ant. Post **	400 ohms	18000	S.W.#2	18000	K	Set Osc. to Scale
5	"	"	16000	"	16000	L	Rock gang & adj. for max. output
6	"	"	4.500	S.W. #1	4.500	N	"

x Switch in Wave Magnet Position * Loosely coupled to Wave Magnet ** Switch in Antenna Position

See Chassis 5719 in Service Manual H5R for all parts with the addition of the following.

22-940	-	Trimmer condenser	.	.	.	.	.15
63-709	-	10M ohm 1/4 watt.	.	.	.	.	.15
63-715	-	100M " "	.	.	.	.	.15
78-314	-	1232 tube socket	.	.	.	.	.10
95-678	-	Power transformer	.	.	.	.	1.00
S-7496	-	R.F. Coil Assembly	.	.	.	.	.65

DWG NO.	PART NO.	DESCRIPTION
C-1	22-670	1 MFD
C-2	22-669	0.1 MFD
C-3	22-434	0.2 MFD
C-4	22-138	2 MFD
C-5		5 MFD ELECTROLYTIC
C-6	22-667	"
C-7		"
C-8		"
C-9	22-171	0.5 MFD
C-10	22-180	1 MFD
P-1	63-722	22 MEGOHM
P-2	63-726	10 MEGOHM
P-3	63-464	1 MEGOHM
P-4	63-718	330 M OHM
P-5	63-719	470 M OHM
P-6	63-715	100 M OHM
P-7	63-749	680 OHM
P-8	63-900	VOLUME CONTROL
P-9	63-537	1 MEGOHM
P-10	63-271	2200 OHM
P-11	63-949	"
1	5-6819	MICROPHONE ASSEM.
2	5-15	BIAS CELL
3	95-582	OUTPUT TRANS
4	95-510	POWER TRANS 10-40V
5	95-511	POWER TRANS 25V
C-11	22-675	5 MFD ELECTROLYTIC
C-12	8	"
C-13	12	"
C-14	12	"



ZENITH
"RAVOX"
HEARING AID



PARTS PRICES LISTED HEREIN ARE AS PER DATE OF MODEL. FOR LATEST PRICES CONSULT ZENITH PARTS PRICE LIST FORM PI OR YOUR ZENITH DISTRIBUTOR.
ZENITH RADIO CORP.

CHICAGO, ILL.

INDEX

Model	Year	Chassis	Page	Model	Year	Chassis	Page
A	1931		21-22	289	1933	2051	113-116
B	1931		21-22	291	1932	2022	63-66
C	1931		21-22	292	1932	2022	63-66
D	1931		21-22	293	1933	2056	109-112
L	1931	2009C	23-24	299	1933	2031	75-78
LP	1931	2009CP	25-26	410	1933	2030	85-88
AH	1931	2012J	27-30	411	1933	2030	85-88
CH	1931	2012J	27-30	412	1933	2030	85-88
BH	1931	2012J	27-30	414	1933	2030	85-88
RH	1931	2021	59-60	420	1933	2030	85-88
LH	1932	2022	61-62	430	1933	2033	89-92
WH	1932	2022	61-62	440	1933	2033	89-92
MH	1932	2022	61-62	441	1933	2033	89-92
*7 Jr.	1934		207-210	442	1933	2033	89-92
10	1930		13-16	443	1933	2030	85-88
11	1930		13-16	444	1933	2033	89-92
12	1930		13-16	*460	1933	2047	133-142
50	1928		1-8	*462	1934	2057	211-218
52	1928		1-8	470	1932	2044	67-70
54	1928		1-8	472	1933	2031	75-78
60	1929		1-8	473	1933	2030	85-88
61	1929		1-8	474	1933	2053	121-124
62	1929		1-8	475	1933	2054	125-128
64	1929		1-8	476	1933	2032	101-104
67	1929		1-8	476B	1933	2059	105-108
70	1930		9-12	478	1933	2056	109-112
71	1930		9-12	478	1933	2051	113-116
72	1930		9-12	479	1933	2059	105-108
73	1930		9-12	500	1932	2037	97-100
77	1930		9-12	501	1932	2037	97-100
80	1931		17-20	502	1932	2037	97-100
91	1931	2014	31-42	503	1932	2037	97-100
92	1931	2014	31-42	514	1932	2037	97-100
102	1930		13-16	515	1932	2037	97-100
103	1931	2017	47-54	516	1932	2037	97-100
112	1930		13-16	516	1932	2031	75-78
122	1930		13-16	517	1932	2031	75-78
210	1932	2022	63-66	518	1932	2031	75-78
211	1932	2022	63-66	520	1932	2035	93-96
215	1932	2044	67-70	521	1932	2035	93-96
216	1932	2044	67-70	530	1932	2038	79-82
217	1932	2044	67-70	531	1932	2038	79-82
220	1932	2022	63-66	532	1932	2038	79-82
221	1932	2022	63-66	533	1932	2038	79-82
225	1932	2044	67-70	558	1932	2051	113-116
230	1933	2036	71-74	563	1932		83-84
240	1933	2036	71-74	568	1932	2051	113-116
241	1933	2036	71-74	577	1932	2056	109-112
244	1933	2036	71-74	578	1932	2051	113-116
245	1933	2036	71-74	585	1933	2053	121-124
250	1933	2031	75-78	588	1932	2056	109-112
251	1933	2031	75-78	589	1932	2051	113-116
252	1933	2031	75-78	590	1932	2051	113-116
258	1933	2051	113-116	593	1932	2056	109-112
259	1933	2031	75-78	600	1932	2037	97-100
260	1933	2031	75-78	602	1932	2035	93-96
261	1933	2031	75-78	602	1929		1-8
262	1933	2031	75-78	603	1932	2038	79-82
263	1932	2044	67-70	604	1932	2037	97-100
268	1933	2051	113-116	605	1933	2035	93-96
269	1933	2031	75-78	606	1932	2037	97-100
270	1932	2022	63-66	608	1932	2035	93-96
271	1933	2036	71-74	610	1932	2037	97-100
272	1933	2031	75-78	611	1932	2035	93-96
273	1933	2030	85-88	612	1932	2038	79-82
277	1933	2056	109-112	612	1929		1-8
278	1933	2051	113-116	615	1932	2035	93-96
280	1933	2051	113-116	616	1932	2037	97-100
281	1933	2051	113-116	617	1932	2038	79-82
281	1933	2056	109-112	618	1932	2037	97-100
288	1933	2051	113-116	619	1932	2033	89-92
288	1933	2056	109-112	620	1932	2038	79-82

INDEX

Model	Year	Chassis	Page	Model	Year	Chassis	Page
622	1929		1-8	970	1935	5902	193-198
623	1932	2038	79-82	975	1935	5902	193-198
642	1929		1-8	978	1935	1001	143-150
*650	1934	2057	211-218	980	1935	1201	199-206
*660	1935	5616	225-232	983	1935	1001	143-150
*663	1935	5510	219-223	985	1935	1201	199-206
*664	1935	5510	219-223	990	1935	1201	199-206
*666	1935	5616	225-232	1101	1935	1001	143-150
*668	1935	5626	233-238	1105	1935	1001	143-150
672	1929		129-130	1107	1935	1201-L	199-206
701	1933		129-130	1112	1935	5608	163-166
702	1933		131-132	1114	1935	5505-07	159-162
703	1933	2052	117-120	1115	1935	5609	167-170
706	1933	2052	117-120	1116	1935	5608	163-166
707	1933	2052	117-120	1117	1935	5614	181-184
711	1933	2052	117-120	1118	1935	5618	185-188
712	1933	2052	117-120	1160	1935	5605-07	159-162
712	1930		9-12	1162	1935	5609	167-170
715	1933	2053	121-124	1167	1935	5618	185-188
722	1930		9-12	1170	1935	5701R	155-158
732	1930		9-12	**4B106	1937	5405	328-329
750	1933	2052	117-120	**4B131	1937	5406	328-329
755	1933	2053	121-124	**4B132	1937	5406	328-329
756	1933	2053	121-124	**4-B-231	1938	5409	328-329
757	1933	2054	125-128	4-B-313	1939	5410	402-403
760	1933	2054	125-128	4-B-314	1939	5411	462-463
765	1933	2054	125-128	4-B-317	1939	5411	464-465
767	1933	2054	125-128	4-B-422	1940	5417	464-465
770	1933	2032	101-104	4-B-437	1940	5417	580-581
770B	1933	2059	105-108	4-B-466	1940	5417	580-581
772	1930		9-12	4-B-468	1940	5417	580-581
775	1933	2032	101-104	**4F133	1937	5407	359-362
775B	1933	2059	105-108	**4F227	1938	5408	400-401
777	1933	2059	105-108	4K310	1939	5412	515-516
780	1933	2032	101-104	4K329	1939	5413	517-518
785	1933	2053	121-124	4K331	1939	5412	515-516
788	1933	2059	105-108	4K332	1939	5414	515-516
801	1934		179-180	4K354	1939	5414	515-516
805	1934	5502	171-174	4K355	1939	5412	515-516
805	1934	5504-05	175-178	4K400	1940	5416	526-527
807	1934	5504-05	175-178	4K402	1940	5419	530-531
808	1934	5605-07	159-162	4K422	1940	5420	582-583
809	1934	5605-07	159-162	4K435	1940	5420	582-583
810	1934	5509	167-170	4K465	1940	5420	582-583
811	1934	5609	167-170	4K465	1940	5420	582-583
812	1934	5608	163-166	4P26	1936	5401	235-238
816	1934	5608	163-166	4P51	1936	5401	235-238
817	1934	5608	163-166	4T26	1936	5403	239-242
819	1934	5608	163-166	4TJ1	1936	5403	239-242
825	1934	5701	151-154	**4V31	1936	5405	271-274
827	1934	5701	151-154	**4V59	1936	5405	271-274
S827	1934	5701R	155-158	**5F134	1937	5518	363-366
829	1934	5701	151-154	**5F166	1937	5518	363-366
S829	1934	5701R	155-158	**5-F-233	1938	5522	410-411
835	1934	1001	143-150	**5-F-251	1938	5522	410-411
845	1934	5502	171-174	5-G-401	1940	5537	532-533
S847	1934	5504-05	175-178	5-G-438	1940	5536	584-585
850	1934	5504-05	175-178	5-G-441	1940	5537	532-533
850	1934	5605-07	159-162	5-G-442	1940	5537	532-533
861	1934	5605-07	159-162	5-G-461	1940	5537	532-533
862	1934	5609	167-170	5-G-467	1940	5536	584-585
855	1934	5609	167-170	5-G-484	1940	5538	536-537
866	1934	5609	167-170	**5-J-217	1938	5524	408-409
870	1934	5701	151-154	**5-J-247	1938	5524	408-409
S870	1934	5701R	155-158	**5-J-255	1938	5524	408-409
S871	1934	5701R	155-158	5-J-353	1939	5524	408-409
880	1934	1001	143-150	*5M90	1935	5510	312-313
881	1935	1001	143-150	*5M191	1937	5520	378-380
885	1935	1001	143-150	†5M191	1937	5520	393-394
887	1935	2059	105-108	5M291	1938	5527	446-447
908	1935	5614	181-184	5M294	1938	5530	448-449
S908	1935	5618	185-188	5R123	1937	5519	375-376
909	1935	5614	181-184	5R135	1937	5519	375-376
S909	1935	5518	185-188	5R165	1937	5519	375-376
935	1935	1001	143-150	5-R-216	1938	5526	406-407
945	1935	5508-09	189-192	5-R-226	1938	5526	406-407
950	1935	5508-09	189-192	5-R-236	1938	5526	406-407
960	1935	5614	181-184	5-R-303	1939	5528	466-467
S961	1935	5618	185-188	5-R-312	1939	5528	466-467
962	1935	5608	163-166	5-R-316	1939	5528	466-467
963	1935	5609	167-170	5-R-317	1939	5528	466-467
966	1935	5605-07	159-162				

* Indicates Auto Receiver. ** Indicates Battery Receiver. † Indicates Supplement.

INDEX

Model	Year	Chassis	Page	Model	Year	Chassis	Page
5-R-337	1939	5528	466-467	6P419	1940	5661	542-543
5S29	1936	5513	247-250	6P428	1940	5662	544-545
5S56	1936	5513	247-250	6P429	1940	5662	544-545
5S119	1937	5516	332-333	6P430	1940	5662	544-545
5S125	1937	5516	332-333	6P447	1940	5662	544-545
5S127	1937	5516	332-333	6P448	1940	5662	544-545
5S150	1937	5516	332-333	6P457	1940	5662	544-545
5S151	1937	5516	332-333	6R481	1940	5675	588-589
5S161	1937	5516	332-333	6R485	1940	5672P	586-587
5-S-201	1938	5521	404-405	6S27	1936	5619	251-254
5-S-218	1938	5521	404-405	6S52	1936	5619	251-254
5-S-220	1938	5521	404-405	6S128	1937	5634	338-339
5-S-228	1938	5521	404-405	6S137	1937	5634	338-339
5-S-237	1938	5521	404-405	6S147	1937	5634	338-339
5-S-250	1938	5521	404-405	6S152	1937	5634	338-339
5-S-252	1938	5521	404-405	6S157	1937	5634	338-339
5-S-319	1939	5529	468-469	6-S-203	1938	5638	414-415
5-S-327	1939	5529	468-469	6-S-222	1938	5638	414-415
5-S-330	1939	5529	468-469	6-S-223	1938	5638	414-415
5-S-338	1939	5529	468-469	6-S-229	1938	5638	414-415
5-S-339	1939	5529	468-469	6-S-239	1938	5638	414-415
5X230	1938	5523	437-440	6-S-241	1938	5638	414-415
5X248	1938	5523	437-440	6-S-254	1938	5644	418-419
5X274	1938	5523	437-440	6-S-256	1938	5644	418-419
**6B107	1937	5635	330-331	6-S-301	1939	5651	474-475
**6B129	1937	5635	330-331	6-S-304	1939	5651	474-475
**6B164	1937	5635	330-331	6-S-305	1939	5651	474-475
6-B-321	1939	5653	480-481	6-S-306	1939	5651	474-475
6D116	1937	5633	334-335	6-S-321	1939	5651	474-475
6D117	1937	5633	334-335	6-S-322	1939	5651	474-475
6D118	1937	5633	334-335	6-S-330	1939	5648	476-477
6-D-202	1938	5639	412-413	6-S-340	1939	5651	474-475
6-D-219	1938	5639	412-413	6-S-341	1939	5649	478-479
6-D-221	1938	5639	412-413	6-S-351	1939	5649	478-479
6-D-238	1938	5639	412-413	6-S-352	1939	5649	478-479
6-D-302	1939	5646	470-471	6-S-361	1939	5648	476-477
6-D-311	1939	5646	470-471	6-S-362	1939	5649	478-479
6D315	1939	5657	519-520	6-S-439	1940	5678	590-591
6-D-325	1939	5646	470-471	6-S-469	1940	5678	590-591
6-D-312	1939	5647	472-473	**6V27	1936	5621	275-278
6-D-316	1939	5647	472-473	**6V62	1936	5621	275-278
6-D-317	1939	5647	472-473	7D119	1937	5707	336-337
6-D-336	1939	5646	470-471	7D126	1937	5707	336-337
6-D-337	1939	5647	472-473	7D127	1937	5707	336-337
6-D-360	1939	5646	470-471	7D138	1937	5707	336-337
6-D-410	1940	5659	538-539	7D148	1937	5707	335-357
6-D-411	1940	5659	538-539	7D151	1937	5707	336-337
6-D-413	1940	5630	540-541	7D162	1937	5707	336-337
6-D-414	1940	5660	540-541	7D168	1937	5707	336-337
6-D-425	1940	5659	538-539	7-D-203	1938	5710	420-421
6-D-426	1940	5660	540-541	7-D-222	1938	5710	420-421
6-D-427	1940	5660	540-541	7-D-223	1938	5710	420-421
6-D-446	1940	5660	540-541	7-D-229	1938	5710	420-421
6-D-455	1940	5650	540-541	7-D-239	1938	5710	420-421
**6-J-230	1938	5642	416-417	7-D-241	1938	5710	420-421
**6-J-257	1938	5642	416-417	7-D-243	1938	5710	420-421
6-J-322	1939	5654	482-483	7-D-253	1938	5710	420-421
6-J-357	1939	5679	592-593	**7-J-232	1938	5711	424-425
6-J-436	1940	5679	592-593	**7-J-259	1938	5711	424-425
6-J-463	1940	5679	592-593	7-J-323	1939	5715	484-485
*6M92	1936	5632	314-315	7-J-368	1939	5715	484-485
*6M90S	1936	5630	316-317	*7M91S	1936	5706	320-326
*6M90D	1936	5630	316-317	*7M91D	1936	5706	320-326
*6M91S	1936	5631	318-319	7S28	1936	5704	255-258
*6M91D	1936	5631	318-319	7S53	1936	5704	255-258
*6M192	1937	5637	381-383	7-S-204	1938	5709	422-423
*6M192	1937	5637	394	7-S-232	1938	5709	422-423
*6M193	1937	5637	384-385	7-S-240	1938	5709	422-423
*6M193	1937	5637	395-396	7-S-242	1938	5709	422-423
*6M194	1937	5637	384-385	7-S-258	1938	5709	422-423
*6M194	1937	5637	395-396	7-S-260	1938	5709	422-423
6M292	1938	5645	450-455	7-S-251	1938	5709	422-423
6M293	1938	5645	450-455	7-S-323	1939	5714	486-487
6M295	1938	5650	452-455	7-S-342	1939	5714	486-487
6M390	1939	Ford	511-514	7-S-343	1939	5714	486-487
*6MF490	1940	Ford	570-576	7-S-363	1939	5714	486-487
*6MN495	1940	Nash	562-565	7-S-364	1939	5714	486-487
*6MN496	1940	Nash	562-565	7-S-366	1939	5714	486-487
6P416	1940	5661	542-543	7-S-432	1940	5719	546-547
6P417	1940	5661	542-543	7-S-432	1940	5724	594-595
6P418	1940	5661	542-543	7-S-433	1940	5719	546-547
				7-S-433	1940	5724	594-595

INDEX

Model	Year	Chassis	Page	Model	Year	Chassis	Page
7-S-434	1940	5719	546-547	10S452	1940	1005	600-601
7-S-434	1940	5724	594-595	10S454	1940	1005	600-601
7-S-449	1940	5719	546-547	10S470	1940	1005	600-601
7-S-449	1940	5724	594-595	10S491	1940	1005	600-601
7-S-450	1940	5719	546-547	10S492	1940	1005	600-601
7-S-450	1940	5724	594-595	11S474	1940	1103	602-603
7-S-458	1940	5719	546-547	12A57	1936	1202	263-270
7-S-458	1940	5724	594-595	12A58	1936	1202	263-270
7-S-459	1940	5719	546-547	12-S-205	1938	1204	428-429
7-S-459	1940	5724	594-595	12-S-232	1938	1204	428-429
7-S-460	1940	5719	546-547	12-S-245	1938	1204	428-429
7-S-460	1940	5724	594-595	12-S-265	1938	1204	428-429
7-S-461	1940	5719	546-547	12-S-265	1938	1204	428-429
7-S-461	1940	5724	594-595	12-S-267	1938	1204	428-429
7-S-462	1940	5719	546-547	12-S-268	1938	1204	428-429
7-S-462	1940	5724	594-595	12-S-345	1939	1206	492-493
7-S-487	1940	4719	546-547	12-S-370	1939	1206	492-493
7-S-487	1940	5724	594-595	12-S-371	1939	1206	492-493
7-S-488	1940	5719	546-547	12-S-374	1939	1204	428-429
7-S-488	1940	5724	594-595	12-S-445	1940	1207	604-605
7-S-490	1940	5719	546-547	12-S-453	1940	1207	604-605
7-S-490	1940	5724	594-595	12-S-471	1940	1207	604-605
*8M195	1937	5803	386-392	12-S-475	1940	1207	604-605
†8M195	1937	5803	396	12-S-494	1940	1207	604-605
8S129	1937	5801	340-341	12U158	1937	1203	346-358
8S154	1937	5801	340-341	12U159	1937	1203	346-358
8S359	1939	5807	521-525	15-S-308	1939	1502	494-495
8S432	1940	5810	617-618	15-S-346	1939	1502	494-495
8S433	1940	5810	617-618	15-S-372	1939	1502	494-495
8S434	1940	5810	617-618	15-S-373	1939	1502	494-495
8S443	1940	5808	598-599	15-S-479	1940	1503	606-607
8S449	1940	5810	617-618	15-S-495	1940	1503	606-607
8S450	1940	5810	617-618	15-U-246	1938	1501	430-435
8S451	1940	5808	598-599	15-U-269	1938	1501	430-435
8S458	1940	5810	617-618	15-U-270	1938	1501	430-435
8S459	1940	5810	617-618	15-U-271	1938	1501	430-435
8S460	1940	5810	617-618	15-U-272	1938	1501	430-435
8S461	1940	5810	617-618	15-U-273	1938	1501	430-435
8S462	1940	5810	617-618	16A61 Str.	1936	1601-C	279-286
8S463	1940	5808	598-599	16A61 Str.	1936	1601-P	279-286
9S30	1936	5903	259-262	16A63 Str.	1936	1601-P	279-286
9S54	1936	5903	259-262	Radio Nurse	1939	RA-TA	441-444
9S55	1936	5903	259-262	Strato. 1st Ser.	1935	2501-C	287-298
9-S-204	1938	5905	426-427			2501-P	287-298
9-S-232	1938	5905	426-427	Strato. 2nd Ser.	1935	2501-C	299-310
9-S-242	1938	5905	426-427			2501-P	299-310
9-S-244	1938	5905	426-427	Tube Data Sheet			367-374
9-S-262	1938	5905	426-427	Phono. Circ.	1938		432-435
9-S-263	1938	5905	426-427	Phono. Connections	1939		496-506
9-S-264	1938	5905	426-427	Phono. Connections	1940		608-614
9-S-307	1939	5907	490-491	Ravox	1940		618
9-S-324	1939	5907	490-491	Record Changer	1938		507-510
9-S-344	1939	5907	490-491	Record Changer	1939		503-504
9-S-365	1939	5906	488-489	Record Changer	1940		556-561
9-S-367	1939	5907	490-491	Record Player, 1939	56622		523-525
9-S-369	1939	5907	490-491	Record Player	1940	S7000	550-554
10S130	1937	1004	342-344	Record Player	1940	S7001	550-554
10S147	1937	1004	342-344	Record Player	1940	S7002	550-554
10S153	1937	1004	342-344	Record Player	1940	S7003	550-554
10S155	1937	1004	342-344				
10S156	1937	1004	342-344				
10S157	1937	1004	342-344				
10S160	1937	1004	342-344				
10S443	1940	1005	600-601				

* Indicates Auto Receiver. ** Indicates Battery
ceiver. † Indicates Supplement.